



(19) **United States**

(12) **Patent Application Publication**

Matsuo et al.

(10) **Pub. No.: US 2004/0204848 A1**

(43) **Pub. Date: Oct. 14, 2004**

(54) **NAVIGATION APPARATUS FOR RECEIVING DELIVERED INFORMATION**

Publication Classification

(76) Inventors: **Shigeru Matsuo**, Hitachinaka (JP); **Kimiyoshi Machii**, Hitachi (JP); **Katsuaki Tanaka**, Hitachi (JP); **Kozo Nakamura**, Hitachiota (JP); **Yoshinori Endo**, Mito (JP); **Michio Morioka**, Hitachi (JP); **Yoshitaka Sumitomo**, Hitachinaka (JP)

(51) **Int. Cl.⁷ G01C 21/34**

(52) **U.S. Cl. 701/211; 340/990; 340/995.17**

(57) **ABSTRACT**

In a communication-type navigation system for downloading map data according to the present invention, a reduction in the amount of map information to be transferred, correction of a position measured by a GPS, and delivery of advertisements are effected. In this system, a terminal 5 stores rough map data in advance. Then, when detailed map data is required, it is downloaded from a map data delivery center to the terminal 5. Further, together with the map data, GPS correction information is delivered to the terminal 5 from the map data delivery center 80. Still further, coupon information associated with an advertisement is displayed and an electronic mail on the coupon information is issued, by the map data delivery center.

Correspondence Address:
ANTONELLI, TERRY, STOUT & KRAUS, LLP
1300 NORTH SEVENTEENTH STREET
SUITE 1800
ARLINGTON, VA 22209-9889 (US)

(21) Appl. No.: **10/175,318**

(22) Filed: **Jun. 20, 2002**




FIG. 1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG. 7




FIG.8




FIG.9




FIG.10




FIG. 11




FIG.12




FIG.13




FIG.14




FIG.15





FIG. 16



NAVIGATION APPARATUS FOR RECEIVING DELIVERED INFORMATION

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to a navigation apparatus for giving route guidance using map data delivered through communication or broadcasting. The invention also relates to an information delivery apparatus for delivering map data using communication and broadcasting.

[0003] 2. Description of the Related Art

[0004] Recently, there are proposed various navigation apparatuses for giving a vehicle guidance on a route to a destination.

[0005] In JP-A-9-325040 and JP-A-10-246641, for example, there are disclosed navigation apparatuses for downloading map data from a data center. Since the navigation apparatuses of this type eliminates the need for installing therein a storage device such as a CD-ROM unit, miniaturization of the apparatuses can be effected. In addition, the most up-to-date map data and real-time information can be obtained from the apparatuses.

[0006] In JP-A-9-325040, there is disclosed a navigation system in which a route search is not performed by a navigation apparatus, but is performed by a server. The server is provided so that it can be communicated with the navigation apparatus.

[0007] It is well known that position measurement using a GPS (Global Positioning System) produces an error of approximately 100 m. In order to reduce the error, conventional navigation apparatuses employ a D-GPS. In this system, GPS error information broadcasted by an FM-multiplexed data broadcast is used to correct the position measurement error caused by the GPS. There is also provided a navigation apparatus equipped with a gyro sensor, for using an output from the gyro sensor to correct the position measurement error caused by the GPS.

[0008] In JP-A-11-296540, there is disclosed a technique for delivering advertisement information associated with a map by using an Internet. Further, in JP-A-11-248484, there is disclosed a technique for providing advertisements for a vehicle-mounted terminal.

[0009] The conventional techniques described above have the following disadvantages:

[0010] (1) Disadvantage of the Techniques Described in JP-A-9-325040 and JP-A-10-246641

[0011] In the navigation apparatuses described in these literatures, map data is downloaded from the data center. Thus, if a distance from the current position of a vehicle to a destination is increased, it becomes necessary to download from the data center all the map data representing maps associated with a recommended route. For this reason, the amount of communication data increases, so that it sometimes happens that display of maps for route guidance is retarded, depending on communication conditions.

[0012] (2) Disadvantage of the Technique Described in JP-A-9-325040

[0013] In the navigation system described in this literature, the navigation apparatus does not perform a route search. The server provided so as to allow communication with the navigation apparatus performs the route search. This system, however, does not takes into account action which should be taken in a situation where the position of a vehicle being under route guidance has been deviated from a route obtained by the route search.

[0014] (3) Disadvantage of Correction of an Error Produced in Position Measurement Using the D-GPS and the Gyro Sensor

[0015] Since these techniques require special hardware such as an FM receiver and the gyro sensor, the cost of the navigation apparatus rises.

[0016] (4) Disadvantage of the Techniques Described in JP-A-11-296540 and JP-A-11-248484

[0017] Recently, there is proposed service in which discounts on merchandise advertised through the Internet are given. In this service, advertisement information on a piece of the merchandise, laid open to the public through the Internet, is displayed by using a personal computer. In order to get a discount on this merchandise, the advertisement information should be printed onto paper by a printer, and presented to an advertiser as a coupon. If this type of service is applied to the techniques described in the above-mentioned literatures, the printer becomes essential. For this reason, this service is not suited to be in use for a vehicle-mounted navigation apparatus and a navigation apparatus of a hand-held terminal type, because in the cases of these navigation apparatuses, an installing space for the printer is limited.

SUMMARY OF THE INVENTION

[0018] The present invention has been made in view of the problems described above. It is therefore an object of the invention to solve various kinds of the problems with these conventional navigation apparatuses and to thereby improve the operability of a navigation system of a type which downloads map data delivered through communication and broadcasting to give route guidance.

[0019] More specifically, it is a first object of the present invention to ensure quick display of a map for route guidance even when map data delivered from a data center to a navigation apparatus is decreased so as to effect a reduction in the amount of communication data.

[0020] Further, when the position of a vehicle being under route guidance has been deviated from a route obtained by a route search, it is a second object of the present invention to notify deviation of the position of the vehicle so that a user can take appropriate action.

[0021] Still further, it is a third object of the present invention to improve accuracy with which position measurement of a vehicle is performed, while effecting a reduction in the cost of a navigation apparatus.

[0022] Yet, it is a fourth object of the present invention to provide an environment where an advertisement coupon is available even if a printer cannot be installed.

[0023] In order to achieve the first object, a navigation apparatus according to a first aspect of the present invention

obtains map data delivered through communication or broadcasting, and then stores the map data in a first storage area. The navigation apparatus also stores map data in a second storage area in advance. It is preferable that a map represented by the map data stored in the second storage area is rougher and more extensive than a map represented by the map data stored in the first storage area, which was delivered through communication and broadcasting.

[0024] According to the first aspect of the present invention, if the map data delivered through communication and broadcasting does not contain all of map data on a route from the current position of a vehicle to a destination, it becomes possible to read out map data on the route from the second storage area and then to give route guidance using a map represented by the map data. Accordingly, even if the amount of the map data delivered through communication and broadcasting is decreased to effect a reduction in the amount of communication data, quick display of maps for route guidance can be performed.

[0025] Further, in order to achieve the second object, a navigation apparatus according to a second aspect of the present invention asks a user to check whether, if the current position of a vehicle being under route guidance has been deviated from a recommended route to a destination, a new route to the destination should be searched again. If an approval from the user can be obtained, the new recommended route to the destination is obtained from an information delivery device.

[0026] According to the second aspect of the present invention, if the position of the vehicle being under route guidance has been deviated from the recommended route, the user is asked to check whether the new route to the destination should be searched again. Accordingly, it becomes possible for the user to take appropriate action, according to whether the position of the vehicle has been deviated from the recommended route intentionally or unintentionally.

[0027] Still further, in order to achieve the third object, a navigation apparatus according to a third aspect of the present invention obtains GSP correction data from an information delivery device for delivering map data to correct a position measurement error caused by GPS position measurement means, when a vehicle being under guidance on a route to a destination has come close to a route change point such as an intersection on the route where the course of the vehicle should be changed.

[0028] According to the third aspect of the present invention, the GPS correction data is obtained from the information delivery device for delivering the map data. Thus, it can be so arranged that a receiver for receiving the map data also serves as a receiver for obtaining the GPS correction data. With this arrangement, special hardware such as an FM receiver or a gyro sensor is not required for obtaining the correction data. Thus, it becomes possible to improve measuring accuracy while achieving a reduction in the cost of the navigation apparatus.

[0029] Still further, in order to achieve the fourth object, an information delivery device according to a fourth aspect of the present invention delivers advertisement data. Then, in response to an instruction from a terminal that has received the advertisement data, the information delivery

device notifies both the terminal that has received the advertisement data and the terminal of an advertiser of coupon information on an advertisement represented by the advertisement data.

[0030] According to the fourth aspect of the present invention, in response to the instruction from the terminal that has received the advertisement data, the coupon information is notified to the terminal that has received the advertisement data. The coupon information is also notified to the terminal of the advertiser. Accordingly, the advertiser can be informed that the coupon information has been notified to the terminal that has received the advertisement data. Thus, if the user of the terminal notifies the advertiser of the coupon information, the present invention according to the fourth aspect can provide an environment where an advertisement coupon can be utilized, even if a printer cannot be installed.

[0031] Other objects, features and advantages of the invention will become apparent from the following description of the embodiments of the invention taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0032] FIG. 1 is an illustrative diagram schematically illustrating a navigation system according to a first embodiment of the present invention;

[0033] FIG. 2 is a block diagram showing a hardware configuration of a terminal main unit 5 of a navigation terminal 5 illustrated in FIG. 1;

[0034] FIG. 3 is an illustrative diagram showing a configuration of software implemented on the terminal main unit 20 illustrated in FIG. 2;

[0035] FIG. 4 is a functional block diagram of a server 81 of a map data delivery center 80 illustrated in FIG. 1;

[0036] FIG. 5 is an illustrative diagram showing a configuration of map data stored in a map DB 82 in the map data delivery center 80 illustrated in FIG. 1;

[0037] FIG. 6 is a flowchart for explaining a flow of the operation of the navigation system according to the first embodiment of the present invention;

[0038] FIG. 7 is a flowchart for explaining the flow of the operation of the navigation system according to the first embodiment of the present invention;

[0039] FIG. 8 is an illustrative diagram showing maps displayed on a display 10 of the navigation terminal 5 of a vehicle being under route guidance according to the first embodiment of the present invention;

[0040] FIG. 9 is an illustrative diagram showing an example of guidance displayed on the display 10 of the navigation terminal 5 of the vehicle being under route guidance according to the first embodiment of the present invention when the current position of the vehicle has been deviated from a recommended route;

[0041] FIG. 10 is an illustrative diagram schematically showing a navigation system according to a second embodiment of the present invention;

[0042] FIG. 11 is a functional block diagram of a server 81' of the map data delivery center 80 illustrated in FIG. 1;

[0043] FIG. 12 is an illustrative diagram showing a display example of map data transmitted to the navigation terminal 5 from the map data delivery center 80, according to the second embodiment of the present invention;

[0044] FIG. 13 is an illustrative diagram showing a display example on a display screen illustrated in FIG. 12 when a user of the navigation terminal 5 has selected a banner advertisement 12 using a remote controller 40;

[0045] FIG. 14 is an illustrative diagram showing a display example on the display screen in FIG. 13 when the user of the navigation terminal 5 has selected a coupon issuing button 13 using the remote controller 40;

[0046] FIG. 15 is an illustrative diagram showing a display example where a coupon mail transmitting button 14 is displayed in place of the coupon issuing button 13 on the display screen illustrated in FIG. 13; and

[0047] FIG. 16 is a diagram showing a display example of a mail received at a cellular phone 35 of a user when the user of the navigation terminal 5 has selected a coupon mail transmitting button 14 using the remote controller 40.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0048] Now, embodiments of the present invention will be described.

[0049] First, a first embodiment of the present invention will be described.

[0050] FIG. 1 is an illustrative diagram schematically showing a configuration of a navigation system according to the first embodiment of the present invention.

[0051] In FIG. 1, reference numeral 5 denotes a communication-type navigation terminal for being mounted on a vehicle, reference numeral 70 denotes a cellular phone base station for performing radio communication with a cellular phone, reference numeral 80 denotes a map data delivery center for delivering map data, and reference numerals 90₁ to 90_n denote GPS correction base stations for calculating GPS correction data.

[0052] First, the navigation terminal 5 will be described.

[0053] The navigation terminal 5 obtains map data delivered from the map data delivery center 80 and then gives guidance of a route to a destination, using the map data obtained. Further, the navigation terminal 5 stores rough map data covering large geographic areas in advance. The rough map data is the map data indicating only main map elements such as natural terrains of Japan, expressways, and national roads, for example. If map data to be displayed is not included in the map data obtained from the map data delivery center 80, the navigation terminal 5 uses the rough map data covering large geographic areas to give guidance of the route to the destination. With this arrangement, even in an area where communication with the map data delivery center 80 cannot be performed, it becomes possible to use the navigation terminal 5. Further, if a distance from a departure point to a destination is long, detailed map data covering only areas around the departure point and the destination can be obtained from the map data delivery center 80, and map data on areas located enroute to the destination can be obtained from the extensive, rough map

data stored in advance, for example. With this arrangement, it becomes unnecessary to obtain all the map data representing the areas from the departure point to the destination, from the map data delivery center 80. Thus, even when the amount of data to be obtained from the map data delivery center 80 is reduced, quick display of maps for route guidance becomes possible. However, upon reception of a request from a user, all the map data on the route may also be obtained from the map data delivery center 80.

[0054] As illustrated in FIG. 1, the navigation terminal 5 comprises a terminal main unit 20, a display 10, a memory card 30, a remote controller 40, a GPS antenna 50, a cellular phone 35 equipped with an electronic mail receiving function, a microphone 60, and a parking brake sensor 25.

[0055] The memory card 30 is structured to be insertable into the terminal main unit 20, and stores information such as map data the terminal main unit 20 has obtained from the map data delivery center 80. The display 10 displays a map image outputted from the terminal main unit 20. The display 10 contains a loudspeaker, which supplies an audio output from the terminal main unit 20. The remote controller 40 receives an instruction from an operator and sends the instruction to the terminal main unit 20. The cellular phone 35 receives information such as map data from the map data delivery center 80, for supply to the terminal main unit 20. The GPS antenna 50 receives GPS data for supply to the terminal main unit 20. The microphone 60 delivers an audio output received to the terminal main unit 20. The parking brake sensor 25 senses a parking brake, and then supplies a sensing signal to the terminal main unit 20.

[0056] FIG. 2 shows a hardware configuration of the terminal main unit 20.

[0057] In FIG. 2, a CPU 204 is a processor for performing supervision and control over the components of the terminal main unit 20. As illustrated, the CPU 204 is connected to the respective components through a system bus 218. The CPU herein assumes what is called a single-chip microcomputer in which a communication function and a control function over peripheral devices such as an A/D converter and a D/A converter, and parallel I/Os are integrated into a single chip with a 32-bit RISC processor as a core. As the microcomputer suitable for this purpose, there is provided a Hitachi HD6417707, for example. Details of the Hitachi HD6417707 are described in a Hitachi's "SH7707 Hardware Manual".

[0058] The CPU 204 contains a plurality of communication ports, one of which is connected to a photoreceptor 205. The CPU 204 receives an instruction from the user input to the remote controller 40 via the photoreceptor 205. Other one of the communication ports is connected to an RS-232C driver 206. Since the RS-232C driver is a standard interface that has been traditionally employed, connection to various devices becomes possible. Other one of the communication ports is connected to the parking braking sensor 25. In response to a signal from the parking brake sensor 25, the CPU 204 senses a stop of a vehicle on which the navigation terminal 5 is mounted, and operates for giving route guidance responsive to the stop of the vehicle. Still further, other one of the communication ports is connected to the microphone 60. The CPU 204 recognizes the voice of the user input into the microphone 60 to analyze an instruction from the user.

[0059] An SRAM 207 and a DRAM 208 are employed as main memories for the CPU 204. A flash memory 209 is a nonvolatile memory that is rewritable. Programs, data that should not be erased when the navigation terminal is turned off, and extensive, rough map data are stored in the flash memory 209 in advance.

[0060] A graphics processor 211 is a processor for displaying a picture on a display 10. The graphics processor 211 has a function of writing a picture in a graphics memory 213 according to an instruction from the CPU 204 and a function of reading out the picture written periodically to display the picture on the display 10.

[0061] An NTSC encoder 212 converts RGB picture data outputted by the display function of the graphics processor 211 into an NTSC signal. The NTSC signal is supplied to the display 10, for display as a picture.

[0062] A USB (Universal Serial Bus) controller is provided to connect the terminal main unit 20 to a device having an USB interface. The USB interface is the one mainly employed for personal computers. For this reason, connection of peripheral devices for personal computers, such as a mouse and a CCD camera to the terminal main unit 20 becomes possible.

[0063] A modem controller 215 connects the terminal main unit 20 to a telephone line. The cellular phone 35 is connected to the modem controller 215 through the telephone line.

[0064] A D/A converter 216 converts digital audio data supplied from the CPU 204 to analog audio data. An analog amplifier 217 amplifies the analog audio data supplied from the D/A converter 216. The amplified analog audio data is outputted from the loudspeaker contained in the display 10 as an audio output.

[0065] A mode setting SW 203 specifies an operation mode for the terminal main unit 20. The mode setting SW 203 performs switching between a normal operation mode for the navigation apparatus and a program version-up mode. In the program version-up mode, collective erasing of data in the flash memory 209 is performed. Then, a new program is downloaded from the memory card 30, for writing in the flash memory 209. With this arrangement, program updating for the terminal main unit 20 can be readily performed.

[0066] A PCMCIA card slot 210 is an interface for the memory card 30. The CPU 204 makes access to the memory card 30 through the PCMCIA card slot 210, reads out data from the memory card 30, or writes data on the memory card 30.

[0067] A GPS unit 219 receives a GPS signal from a GPS satellite via the GPS antenna 50, and then uses the GPS signal to measure the position of a vehicle.

[0068] Next, a configuration of software implemented on the terminal main unit 20 is shown in FIG. 3.

[0069] Incidentally, the respective software shown in FIG. 3 is stored in the flash memory 209 in advance, and then loaded into the SRAM 207 and the DRAM 208 by the CPU 204, for implementation.

[0070] In FIG. 3, an OS 500 is provided to control the overall operations of the terminal main unit 20 and performs

task management. A device driver 501 contains driver software by which the CPU 204 performs data communications with the cellular phone 30 via the modem controller 215, driver software by which the CPU 204 receives an instruction from the remote controller via the photoreceptor 205, and driver software by which the CPU 204, in cooperation with the graphics processor 211, exercises control over the screen of the display 10. Communications software 502 is provided so that the navigation terminal 5 performs communication with the map data delivery center 80 over a network such as the Internet. The communications software contains WWW browser software and electronic mail software. Car navigation software 504 uses map data obtained from the map data delivery center 80 and map data stored in the flash memory 209 to display maps such as a map including a route to a destination and a map near the position of a vehicle, for giving route guidance. The car navigation software 504 uses correction data obtained from one of the GPS correcting base stations 90₁ to 90_n to perform error correction for the position of a vehicle measured by the GPS unit 219.

[0071] Next, the map data delivery center 80 will be described.

[0072] The map data delivery center 80 delivers map data to the navigation terminal 5 via the cellular phone base station 70. As shown in FIG. 1, the map data delivery center 80 includes a server 81, a map database (DB) 82 for storing map data, and a point information database (DB) 83 for storing information indicating the types, names, addresses, and telephone numbers of primary facilities such as restaurants, gas stations, leisure facilities, and public facilities in respective areas of a map.

[0073] The server 81 can be constructed in a computer (such as a personal computer) having a typical configuration that comprises a CPU, a memory, an external storage such as a hard disk, and a communication device for performing communications with other device over the network such as the Internet.

[0074] A configuration of functional blocks of the server 81 is illustrated in FIG. 4.

[0075] The functional blocks shown in FIG. 4 are, for example, stored in the external storage such as the hard disk in advance, and then loaded into the memory by the CPU for being constructed in the computer.

[0076] In FIG. 4, a communication unit 800 performs a process by which the server 81 exchanges information with the navigation terminal 5 over the Internet, and supports an Internet protocol.

[0077] A user authentication unit 801 performs a user authentication process when accessed by the navigation terminal 5, and permits only a navigation terminal 5 registered in advance to make access to the server 81.

[0078] Upon receipt of a request from the navigation terminal 5 that has been permitted to make access to the server, a route search unit 802 is notified of the current position and the destination of the navigation terminal 5, searches for a route from the current position to the destination, using the map DB 82, and notifies the navigation terminal 5 of the result of the search.

[0079] Upon receipt of a request from the navigation terminal **5** that has been permitted to make access to the server **81**, a map data cutting unit **803** reads out from the map DB **82** map data around a place, requested by the navigation terminal **5**, for transfer to the navigation terminal **5**.

[0080] A point information search unit **804** supports a destination search for the navigation terminal **5** that has been permitted to make access. When the navigation terminal **5** requests a list of restaurants around the current position of the navigation terminal **5**, for example, the point information search unit **804** searches the point information DB **83** based on the coordinates of the current position notified from the terminal **5**, and then notifies the navigation terminal **5** of the list. Upon receipt of the list, the navigation terminal **5** selects one of the restaurants included in the notified list. Then, with the selected restaurant as a destination, the navigation terminal **5** requests the server **81** to perform a route search. The route search unit **801** performs the route search described above. The point information search unit **804** also performs various searches such as an address search and a telephone number search, according to a request from the navigation terminal **5**.

[0081] FIG. 5 shows a configuration of map data stored in the map DB **82**.

[0082] As illustrated, respective meshes of map data obtained by dividing an entire map into the meshes is stored in the map DB **82**. Then, more detailed map data contained in the respective meshes of map data is hierarchically stored in different layers, being associated with the respective meshes of map data. In an example illustrated in FIG. 5, the entire land of Japan is divided into 42 meshes of regions. Map data for the respective meshes of regions is stored, and more detailed map data in the respective meshes of map data is hierarchically stored in different layers.

[0083] Next, the GPS correction base stations 90_1 to 90_n will be described.

[0084] The GPS correction base stations 90_1 to 90_n are disposed in diverse locations, being scattered all over the country. Each of the GPS correction base stations 90_1 to 90_n receives the GPS signal from a GPS satellite, and uses the GPS signal to measure the its own installation position. Then, the result of measurement is compared with the exact coordinates of its installation position, thereby detecting an error in position measurement data obtained through the use of the GPS. Then, each of the GPS correction base stations generates correction data according to the error. The correction data is notified to the navigation terminal **5** via the map data delivery center **80**. The navigation terminal **5** uses the correction data to correct the result of measurement performed in the GPS unit **219**, thereby enabling an improvement in the accuracy of measurement of the position of a vehicle on which the navigation terminal **5** is mounted.

[0085] The GPS correction base station 90_1 to 90_n can be configured by connecting the GPS antenna and the GPS unit to a computer having a communication function for performing communication with other device over a network such as the Internet. The GPS unit receives the GPS signal from the GPS satellite via the GPS antenna **50**, and performs position measurement. In this case, computation of correction data is implemented by software.

[0086] Next, an operation of the navigation system will be described.

[0087] FIGS. 6 and 7 are flowcharts for explaining flows of the operations of the navigation system according to the first embodiment of the present invention.

[0088] The operation of the navigation terminal **5** in these drawings is started when the communications software **502** and the car navigation software **504** have been loaded into the SRAM **207** or the DRAM **208** by the CPU **204** for implementation with the OS **500** and the device driver **501** already loaded into the SRAM **207** or the DRAM **208** by the CPU **204** for implementation.

[0089] First, the CPU **204** in the navigation terminal **5** obtains position measurement data from the GPS unit **219**, and checks whether map data containing the coordinates of the current position of a vehicle, indicated by the position measurement data is stored on the memory card **30** (step S1000).

[0090] If the map data is not stored, the CPU makes access to the map data delivery center **80** via the modem controller **215** and the cellular phone **35**, and transmits a request to transfer detailed map data around the current position of the vehicle, together with the coordinates of the current position (step S1002). At this point, the CPU also transmits to the map data delivery center information that is necessary for authentication of a user (the information is stored on the memory card **30** in advance, for example).

[0091] Upon receipt of the request and the information, the user authentication unit **801** in the map data delivery center **80** performs user authentication and permits access only when the user has been authenticated. Then when access is permitted, the map data cutting unit **803** reads out from the map DB **82** the detailed map data around the coordinates of the current position of the vehicle, notified by the navigation terminal **5**, and transmits the map data to the navigation terminal **5** through the communication unit **800** (step S2000).

[0092] Upon receipt of the map data from the map data delivery center **80**, the CPU **204** in the navigation terminal **5** stores the map data on the memory card **30**. Further, in cooperation with the graphics processor **211**, the CPU causes the display **10** to display a detailed map around the current position of the vehicle, represented by the map data (step S1004).

[0093] On the other hand, when it is found that the map data containing the coordinates of the current position of the vehicle is stored on the memory card **30** in step S1000, the CPU reads out the map data from the memory card **30**. Then, in cooperation with the graphics processor **211**, the CPU causes the display **10** to display the detailed map around the current position of the vehicle, represented by the map data (step S1004).

[0094] Next, the CPU **204** in the navigation terminal **5** checks whether the user has provided an instruction to set a destination through the use of the remote controller **40** or the microphone **60** (step S1006). Then, if it is found that the user has provided the instruction to set the destination, the CPU **204** receives criteria for a search for the destination entered by the user through the use of the remote controller **40** or the microphone **60**, and sends the criteria to the map data delivery center (step S1008).

[0095] At this point, if access to the map data delivery center **80** has been made for the first time, or if it is found that the map data containing the coordinates of the current position of the vehicle is stored on the memory card **30** in step **S1000**, and the map data is then read from the memory card **30** for display on the display **10**, the CPU transmits information necessary for user authentication as well. When a predetermined facility nearest to the current position of the vehicle is searched, for example, the CPU **204** receives from the user the coordinates of the current position of the vehicle and the type of the facility (such as a restaurant, a gas station, a leisure facility, or a public facility), as the destination search criteria. When the destination is searched for by its telephone number, the CPU **204** receives the telephone number from the user.

[0096] Upon receipt of the destination search criteria, the point information search unit **804** in the map data delivery center **80** reads out from the point information **DB83** destination candidates that meet the search criteria notified by the navigation terminal **5**. If the notified search criteria comprise the coordinates of the current position of the vehicle and the type of the facility, the point information search unit **804** searches the point information **DB83** for a facility that is classified into the type notified and is located at around a location indicated by the coordinates of the current position of the vehicle. If the notified search criterion is a telephone number, the point information search unit **804** searches the point information **DB83** for a facility where the notified telephone number is registered. Then, the point information search unit **804** reads out information on the facility searched (such as the type, name, address, and telephone number), from the point information **DB83**, and transmits the readout information to the navigation terminal **5** through the communication unit **800** (step **S2002**).

[0097] If the map data delivery center **80** receives information necessary for user authentication together with destination search criteria from the navigation terminal **5**, the user authentication unit **801** performs authentication of the user before the search for the destination by the point information search unit **804**. Then, the user authentication unit **801** permits access only when the user has been authenticated. Then, the destination search is performed.

[0098] Upon receipt of the result of the search or data on destination candidates from the map data delivery center **80**, the CPU **204** in the navigation terminal **5** causes the data to be displayed on the display **10**, in cooperation with the graphics processor **211**. Then, the CPU **204** causes the user to select one of the destination candidates through the use of the remote controller **40**, and sets the selected one of the destination candidates as the destination (step **S1010**).

[0099] Next, when the destination has been set, the CPU **204** in the navigation terminal **5** checks whether map data containing the coordinates of the destination is stored on the memory card **30** (step **S1012**). If the map data is not stored, the CPU **204** transmits a request to transfer detailed map data around the destination together with the coordinates of the destination to the map data delivery center **80** (step **S1014**).

[0100] Upon receipt of the request and the coordinates of the destination, the map cutting unit **803** reads out from the map **DB82** the detailed map data around the coordinates of the destination notified by the navigation terminal **5**, and

transmits the map data to the navigation terminal **5** through the communication unit **800** (step **S2004**).

[0101] Upon receipt of the map data from the map data delivery center **80**, the CPU **204** in the navigation terminal **5** stores the map data on the memory card **30**. Next, the CPU **204** transmits to the map data delivery center **80** a request to search for a route from the current position of the vehicle to the destination together with the coordinates of the current position and the destination (step **S1016**). When the user requests detailed map data on an area from the current position of the vehicle to the destination at this point, the CPU **204** transmits a request to transfer the detailed map data as well.

[0102] Upon receipt of the request and the coordinates, the route search unit **802** in the map data delivery center **80** searches for a recommended route from the current position of the vehicle to the destination based on the coordinates of the current position and destination notified by the navigation terminal **5**, and transmits the result of the search to the navigation terminal **5** via the communication unit **800** (step **S2006**). If the request to transfer the detailed map data is also notified by the navigation terminal **5**, the map cutting unit **803** reads out from the map **DB82** map data containing the recommended route searched by the route search unit **802**, for transmission to the navigation terminal **5** together with the recommended route. Upon receipt of the data on the recommended route (or the data on the recommended route together with the detailed map data), the CPU **204** in the navigation terminal **5** stores the received data on the memory card **30**.

[0103] Next, upon receipt of the recommended route data from the map data delivery center **80**, the CPU **204** in the navigation terminal **5** starts to give guidance on the route to the destination according to the recommended route indicated by the recommended route data (step **S1018**).

[0104] Specifically, the CPU **204** gives route guidance by displaying marks indicating the current position of the vehicle and the destination on maps containing the detailed map data around the current position and the destination and the recommended route data, all stored on the memory card **30**. At this point, if map data associated with a map of an area along the recommended route except the current position and the destination is stored on the memory card **30**, the CPU **204** reads out the map data from the memory card **30**, and causes the map data to be displayed on the display **10**. If the map data is not stored on the memory card **30**, the CPU separates the map data from the extensive, rough map data stored in the flash memory **209**, and causes the map data to be displayed on the display **10**.

[0105] FIG. 8 illustrates an example of the maps displayed on the display **10** of the navigation terminal **5** of a vehicle being under route guidance.

[0106] In FIG. 8, reference numeral **3000** denotes a map represented by detailed map data around the current position of the vehicle, which has been read out from the memory card **30**. Reference numeral **3010** denotes a map represented by detailed map data around the destination of the vehicle, which has been read out from the memory card **30**. Reference numeral **3020** denotes a recommended route represented by recommended route data obtained from the map data delivery center **80** and then stored on the memory card

30. In this example, the map of an area along the recommended route **3020** except the current position and the destination is read out from the flash memory **209** and then displayed. Specifically, this example illustrates the case where route guidance is being given by simultaneously displaying the detailed maps around the current position and the destination, stored on the memory card **30** and the rough map of the area along the recommended route except the current position and the destination, stored in the flash memory **209**.

[**0107**] When the GPS **219** unit updates the current position while the vehicle is under route guidance, the CPU **204** in the navigation terminal **5** executes processes from step **S1000** to step **S1004**, thereby updating the detailed map around the current position to be displayed on the display **10** (step **1020**). Then, the CPU **204** checks whether the current position measured by the GPS unit **219** is on the recommended route (step **S1022**).

[**0108**] If the current position is on the recommended route, the CPU **204** further checks whether the vehicle has come to a point located a predetermined distance before a route change point such as an intersection on the recommended route, from which the course of the vehicle should be changed (step **S1024**). Then, if the vehicle has reached the route change point, the CPU **204** transmits to the map delivery center **80** a request to transmit GPS correction data together with the coordinates of the current position of the vehicle (step **S1026**).

[**0109**] The predetermined distance before the route change point is at most 200 m, for example. The distance of 200 m is determined because the error caused by the GPS is approximately 100 m, as described above. In order to display the mark of the current position of the vehicle on the display **10** so that the user can change the course at the route change point without error, it is necessary to correct the error in position measurement data caused by the GPS at a point further before the point that is located 100 m before the route change point.

[**0110**] Upon receipt of the request to transmit the GPS correction data from the navigation terminal **5**, the GPS correction unit **805** in the map data delivery center **80** selects one of the GSP correction base stations **90₁** to **90_n**, which is the nearest to the coordinates of the current position of the vehicle that have been transmitted together with the request. Then, the GPS correction unit **805** obtains the GPS correction data from the selected base station and transfers the GPS correction data to the navigation terminal **50** (step **S2008**).

[**0111**] Upon receipt of the GPS correction data, the CPU **204** in the navigation terminal **5** uses this data to correct the result of measurement by the GPS unit **219** (step **S1028**). For displaying the current position of the vehicle on a map, the accuracy is in particular required when the vehicle has come close to the route change point such as an intersection where the course of the vehicle should be changed. In this embodiment, therefore, when the vehicle has come close to the route change point, an error in position measurement by the GPS unit **219** is corrected.

[**0112**] If the CPU **204** in the navigation terminal **5** has judged that the current position of the vehicle measured by the GPS unit **219** is not on the recommended route (or a negative reply has been obtained in step **S1022**), that is, if

the current position has been deviated from the recommended route, the CPU **204** executes processes in steps **S1016** and **S1018**. The CPU **204** causes the map data delivery center **80** to search for a recommended route from the current position to the destination again and starts to give route guidance again (step **S1030**).

[**0113**] Incidentally, if the current position has been deviated from the recommended route, the CPU **204**, in cooperation with the graphics processor **211**, may cause a picture as illustrated in **FIG. 9** to be displayed on the display **10**. Then, the CPU **204** may give guidance so that the user stops the vehicle. The CPU **204** may continue display of the picture until the user has entered confirmation through the use of the remote controller **40** or the microphone, or the parking brake sensor **25** has sensed the state where the parking brake is applied. Then, after the confirmation from the user has been entered, or after the state where the parking brake is applied has been detected, the CPU **204** may ask whether a search for a recommended route is to be performed again or not, through the display **10** or the loudspeaker contained in the display **10**. Only when a reply to the effect that the search for the recommended route is performed again has been obtained from the user through the remote-controller **40** or the microphone **60**, the CPU **204** may execute processes in step **S1030**. If the reply to that effect has not been obtained, the procedure may be returned to step **S1000**.

[**0114**] If the vehicle, the current position of which has been updated through the use of the GPS unit **219**, has reached the destination (or an affirmative reply has been obtained in step **S1032**), the CPU **204** in the navigation terminal **5** terminates route guidance (step **S1032**). Then, the procedure is returned to step **S1000**, for continuation of the above-mentioned processes.

[**0115**] The above is a description about the first embodiment of the present invention.

[**0116**] According to this embodiment, if detailed map data stored on the memory card **30** does not contain all the map data on a route from the current position of a vehicle to a destination, rough map data on the route is read out from the flash memory **209**, and a map represented by the rough map data is displayed on the display **10**. Accordingly, even when the amount of map data obtained from the map data delivery center **80** is reduced to effect a reduction in the amount of communication data, maps for route guidance can be quickly displayed. Even in this case, detailed map data around the current position of the vehicle and destination is delivered from the map data delivery center **80** as necessary, for storage on the memory card **30**. Thus, detailed maps around the current position and the destination can be displayed on the display **10**. With this arrangement, information required by the user especially for route guidance, can be provided efficiently.

[**0117**] Further, according to the present invention, when the current position of the vehicle being under route guidance has been deviated from a recommended route, the user is checked to see whether a search for a new route to the destination should be made again. Thus, the user can take appropriate action according to whether the current position has been deviated from the recommended route intentionally or unintentionally.

[**0118**] Further, according to this embodiment, a receiver for receiving map data, which is the cellular phone **35** in this

embodiment, also serves as a receiver for obtaining GPS correction data from the map data delivery center **80**. For this reason, special hardware such as an FM receiver or a gyro sensor for obtaining the GPS correction data is not required, so that this embodiment can improve measuring accuracy while effecting a reduction in the cost of the navigation terminal **5**.

[0119] In addition, in this embodiment, the memory card **30** that is removable from the terminal main unit **20** of the navigation terminal **5** is employed as a storage for storing detailed map data. For this reason, a plurality of the memory cards **30** respectively storing detailed map data for different areas can be employed. Further, a personal computer installed at home, not shown, for example, can also be employed for downloading from the map data delivery center **80** detailed map data to be stored on the memory card **30**.

[0120] In this embodiment, the GPS correction data is requested when the vehicle being under route guidance to the destination, becomes close to the route change point on the recommended route such as an intersection where the course of the vehicle should be changed. The present invention is not limited to this case. A request for the GPS correction data may also be made in step **S1016** in **FIG. 6** or step **S1030** in **FIG. 7** where the request to search for the recommended route from the current position to the destination is made to the map data delivery center **80**. Alternatively, even when the vehicle is not being under route guidance, the request for the GPS correction data may also be made to the map data delivery center **80** when the vehicle has become close to an intersection located in the advance direction of the vehicle.

[0121] In this embodiment, communication between the navigation terminal **5** and the map data delivery center **80** is made by the cellular phone. The present invention is not limited to this. To take an example, transmission of information from the navigation terminal **5** to the map data delivery center **80** may be performed by the cellular phone, and transmission of information from the map data delivery center **80** to the navigation terminal **5** may be performed by using digital broadcasting.

[0122] Next, a second embodiment of the present invention will be described.

[0123] **FIG. 10** is an illustrative diagram schematically showing a configuration of a navigation system according to the second embodiment of the present invention. Elements that have the same functions as those in **FIG. 1** according to the first embodiment are indicated by like reference numerals and characters.

[0124] The navigation system according to this embodiment is different from the navigation system according to the first embodiment in that the map data delivery center **80** has a function of transmitting to the navigation terminal **5** data on an advertisement requested by an advertiser to be advertised. Then, when coupon information for a commodity discount is issued to a user who has seen the data on the advertisement, issue of the coupon information is notified to a terminal **93** of the advertiser.

[0125] As illustrated, the map data delivery center **80** according to this embodiment comprises a server **81'**, the map DB **82**, the point information DB **83**, and an advertisement database (DB) **84**.

[0126] Data on advertisements requested by advertisers to be advertised or coupon information is stored in the advertisement DB **84**, together with the names and coordinates of shops of the advertisers, for example.

[0127] **FIG. 11** shows a configuration of functional blocks of the server **81'**.

[0128] As illustrated, the server **81'** according to this embodiment is obtained by adding an advertisement data search unit **806**, a coupon issuing unit **807**, an electronic mail issuing unit **808**, and a coupon history management unit **809** to the server **81** according to the first embodiment, illustrated in **FIG. 4**.

[0129] The advertisement data search unit **806** searches the advertisement DB **84** for advertisement data on a facility contained in map data cut by the map data cutting unit **803**, based on the coordinates and the name of the facility, for example. Then, the advertisement data search unit **806** reads out the searched advertisement data and associates it with the corresponding facility for transmission to the navigation terminal **5**, together with the map data that has been cut, through the communication unit **800**.

[0130] When requested to issue a coupon for advertisement data transmitted to the navigation terminal **5**, the coupon issuing unit **807** generates a coupon number for identifying the coupon that will be issued to the navigation terminal **5**. Then, the coupon issuing unit **807** transmits the generated coupon number to the navigation terminal **5** through the communication unit **800**.

[0131] The electronic mail issuing unit **808** notifies the terminal of the advertiser of the advertisement data, of the coupon number issued by the coupon issuing unit **807**, using an electronic mail. Further, the electronic mail issuing unit **808** notifies the navigation terminal **5** as well, which has requested to issue the coupon, of the coupon number, as necessary.

[0132] The coupon history management unit **809** manages a coupon issue history (such as a combination of a coupon number, advertisement data, an address of the terminal **93** of the advertiser, and an address of the navigation terminal **5** accessed).

[0133] **FIG. 12** shows an example of display of map data transmitted to the navigation terminal **5** by the map data delivery center **80** configured as described above. This example shows the case where a map around the current position of a vehicle being stopped is displayed on the display of the navigation terminal **5** (or shows the state where steps **S1000** to **S1004** in **FIG. 6** have been executed). On the map displayed on the screen of the display **10**, the name of a facility "○×restaurant" contained in map data is displayed, being superimposed on the display position of the facility. At this point, when advertisement data on this facility has been sent together with the map data, the advertisement data on the facility is displayed in outline, being reduced in size, as a banner advertisement **12** in the bottom right-hand corner of the display screen.

[0134] **FIG. 13** shows an example of display where the user of the navigation terminal **5** has selected the banner advertisement **12** on the display screen in **FIG. 12**, using the remote controller **40**. As shown in this drawing, the details of the advertisement data displayed in outline as the banner

advertisement **12**, or coupon information is displayed together with a coupon issuing button **13**.

[0135] FIG. 14 shows an example of display where the user of the navigation terminal **5** has selected the coupon issuing button **13** on a display screen shown in FIG. 13, using the remote controller **40**. When the coupon issuing button **13** has been selected, the navigation terminal **5** transmits to the map data delivery center **80** a request to issue a coupon for the advertisement data being displayed. Upon receipt of the request, the coupon issuing unit **807** of the map data delivery center **80** generates a coupon number for identifying the coupon that will be issued to the navigation terminal **5**, for transmission to the navigation terminal **5**. The coupon number is also notified to the terminal **93** of the advertiser of the advertisement data by the electronic mail issuing unit **808**, by using an electronic mail. Thus, the user of the navigation terminal **5** memorize the coupon number displayed on the screen as "Today's Number 1234". Then, when using the facility of the advertiser of the advertisement data, by telling the coupon number, the user can obtain discount service.

[0136] FIG. 15 is a variation of display shown in FIG. 13, and shows an example where the coupon mail transmitting button **14** is displayed in place of the coupon issuing button **13**. When the user of the navigation terminal **5** has selected the coupon mail transmitting button **14** using the remote controller **40**, the request to issue the coupon for the advertisement data being displayed is transmitted to the map data delivery center **80** together with the mail address of the cellular phone **35**, stored in advance. Upon receipt of the request and the mail address, the coupon issuing unit **807** of the map data delivery center **80** generates the coupon number for identifying the coupon that will be issued to the navigation terminal **5**. Then, the electronic mail issuing unit **808** notifies the cellular phone **35** having the mail address added to the coupon issuing request, of the coupon number, using an electronic mail.

[0137] FIG. 16 shows an example of display of the mail which indicates that the coupon number has been received by the cellular phone **35**. Suppose the user of the navigation terminal **5** carries the cellular phone **35** when getting off the vehicle. Then, when using the facility of the advertiser of the advertisement data, if the user presents the cellular phone **35** that displays this mail, he can obtain discount service.

[0138] The above is a description about the second embodiment of the present invention.

[0139] According to this embodiment, in response to a request from the navigation terminal **5** that has received advertisement data, the map data delivery center **80** notifies the navigation terminal **5** of coupon information. Further, the map data delivery center **80** notifies the advertiser terminal **93** that the coupon information has been notified to the navigation terminal **5**. Accordingly, this embodiment can provide an environment where an advertisement coupon can be utilized even if a printer cannot be installed. Further, since the advertiser can keep track of the frequency of notification of the coupon information by the map data delivery center **80**, he can learn about the effect of the advertisement using the map data delivery center **80** on sales. Still further, the coupon history management unit **809** of the map data delivery center **80** manages issue of coupons. The map data delivery center **80** can thereby charge the advertiser an appropriate advertisement fee.

[0140] As described above, according to the present invention, the operability of a navigation system that downloads map data delivered through communication or broadcasting to give route guidance can be improved.

[0141] Specifically, even if map data to be transferred from the map data delivery center to the navigation apparatus is reduced so as to effect a reduction in the amount of communication data, maps for route guidance can be displayed quickly.

[0142] When the position of a vehicle being under route guidance has been deviated from a route searched by a route search, the present invention can inform the user of deviation and can help the user to take appropriate action.

[0143] Further, the present invention can improve position measuring accuracy while effecting a reduction in the cost of the navigation apparatus.

[0144] Still further, the present invention can provide an environment where an advertisement coupon can be utilized even if a printer cannot be installed.

[0145] It should be further understood by those skilled in the art that the foregoing description has been made on embodiments of the invention and that various changes and modifications may be made in the invention without departing from the spirit of the invention and the scope of the appended claims.

1-6 (canceled).

7. The navigation apparatus for providing route guidance, comprising:

- a data acquisition unit which obtains map data delivered through communication or broadcasting;

- a storage media which stores the map data obtained by the data acquisition unit in a first storage area; and

- a route guidance controller which reads out map data on a route from a current position of a vehicle to a destination from the first storage area when the map data on the route is stored in the first storage area to give route guidance using a map represented by the map data, and reads out the map data on the route from a second storage area where map data has been stored in advance, when the map data on the route is not stored in the first storage area, to give route guidance using a map represented by the map data,

- wherein the map data stored in the second storage area represents a map more simplified map than the map represented by the map data delivered and then stored in the first storage area, and

- wherein the first storage area and the second storage area are provided on different storages.

8-15 (canceled).

16. A navigation apparatus for providing route guidance to a destination by downloading map data from a server, comprising:

- a communication unit for communicating with the server;

- a storage unit which has a first storage area storing map data obtained by said communication unit and a second storage area storing rough map data covering large geographic areas in advance;

a route guidance unit, for moving from a current position to the destination, which reads out map data around a running position from said storage unit, said map data represents a map on a presentation apparatus to give route guidance, requests detailed map data around the destination and the current positions from the server through said communication unit by transmitting information of the destination and the current position to the server, and stores detailed map data around the destination and the current position, said detailed map data is downloaded from the server based upon said request to the first storage area of the storage unit,

wherein said route guidance unit provides route guidance, when the map data around the running position is stored in the first storage area, by reading out the detailed map data around the running position in said first storage area and using a map represented by said detailed map data, and

wherein said route guidance unit provides route guidance, when the map data around the running position is not stored in the first storage area, by reading out the rough map data from said second storage area and using a map represented by said rough map data.

17. The navigation apparatus according to claim 16, wherein the map data stored in the second storage area represents map data that includes main map elements and is more simplified than the map represented by the map data stored in the first storage area.

18. The navigation apparatus according to claim 16, wherein the map data stored in the second storage area represents a map covering a wide area covering all of a country's geography.

19. The navigation apparatus according to claim 17, wherein the map data stored in the second storage area represents a map covering a wide area covering all of a country's geography.

20. The navigation apparatus according to claim 16, wherein said first storage area and said second storage areas are provided in different storages.

21. The navigation apparatus according to claim 17, wherein said first storage area and said second storage areas are provided in different storages.

22. The navigation apparatus according to claim 18, wherein said first storage area and said second storage areas are provided in different storages.

* * * * *