



US007675614B2

(12) **United States Patent**  
**Sekiya**

(10) **Patent No.:** **US 7,675,614 B2**  
(45) **Date of Patent:** **Mar. 9, 2010**

(54) **WAFER INSPECTING METHOD AND DEVICE**

(75) Inventor: **Kazuma Sekiya**, Ota-Ku (JP)

(73) Assignee: **Disco Corporation**, Tokyo (JP)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/104,088**

(22) Filed: **Apr. 16, 2008**

(65) **Prior Publication Data**

US 2008/0285021 A1 Nov. 20, 2008

(30) **Foreign Application Priority Data**

May 18, 2007 (JP) ..... 2007-132781

(51) **Int. Cl.**  
**G01N 21/00** (2006.01)

(52) **U.S. Cl.** ..... 356/237.4; 356/237.1; 356/237.6

(58) **Field of Classification Search** ... 356/237.1-237.6, 356/239.3, 239.7, 239.8

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,917,588 A *	6/1999	Addiego .....	356/237.2
6,585,471 B2 *	7/2003	Odajima et al. ....	414/403
7,239,127 B2 *	7/2007	Odan et al. ....	324/158.1
2002/0028399 A1 *	3/2002	Nakasuji et al. ....	356/237.5

FOREIGN PATENT DOCUMENTS

JP A 11-173993 7/1999

\* cited by examiner

*Primary Examiner*—Gregory J Toatley, Jr.


*Assistant Examiner*—Iyabo S Alli

(74) *Attorney, Agent, or Firm*—Greer, Burns & Crain, Ltd.

(57) **ABSTRACT**

A wafer inspecting method including the steps of scanning the surface of a wafer along a street by using a line sensor having a plurality of elements arranged in a line, and determining a deposited condition of foreign matter on the surface of the wafer near electrodes formed on both sides of the street according to image information obtained by the above scanning step. By the use of the linear sensor, it is possible to efficiently determine whether or not the electrodes are good.

**5 Claims, 4 Drawing Sheets**





# FIG. 2




FIG. 3





FIG. 4



## WAFER INSPECTING METHOD AND DEVICE

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to a method and device for inspecting a wafer for the deposition of foreign matter.

#### 2. Description of the Related Art

A wafer is formed with a plurality of devices such as ICs and LSIs, and these devices are partitioned by a plurality of streets. The wafer is cut by dicing along these streets to obtain the individual devices. Each device is mounted on a lead frame or the like and next packaged to be used in various electronic equipment. The surface of each device is formed with a plurality of electrodes arranged along each street, so as to allow the electrical connection with the lead frame.

However, there is a possibility that foreign matter such as cutting dust and grinding dust may be deposited to the devices during the fabrication steps, causing a reduction in quality of the devices due to the deposited foreign matter. To cope with this possibility, there has been proposed a method of detecting the deposited foreign matter such as cutting dust (see Japanese Patent Laid-open No. 11-173993, for example).

However, the scale of integration in each device is increased to result in size reduction. With such size reduction, the space between the electrodes becomes as small as 50 to 10  $\mu\text{m}$ , for example. Accordingly, there arises a problem such that foreign matter such as cutting dust may be deposited over the adjacent electrodes to cause a short circuit between these electrodes. Further, checking the wafer for deposited foreign matter by using a microscope or the like is inefficient to cause a reduction in productivity.

### SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a method and device for inspecting a wafer which can efficiently inspect the surface of the wafer for the deposition of foreign matter such as cutting dust near the electrodes.

In accordance with an aspect of the present invention, there is provided a wafer inspecting method for inspecting a wafer along streets, the wafer being formed with a plurality of devices partitioned by the streets, the wafer inspecting method including the steps of scanning the surface of the wafer along the streets by using a line sensor having a plurality of elements arranged in a line; and determining a deposited condition of foreign matter on the surface of the wafer near electrodes formed on both sides of the streets according to image information obtained by the scanning step.

In accordance with another aspect of the present invention, there is provided a wafer inspecting device including a chuck table for holding a wafer formed with a plurality of devices partitioned by streets; inspecting means for inspecting the surface of the wafer held on the chuck table; and alignment means for aligning an inspection area of the wafer to the inspecting means; the inspecting means including a line sensor having a plurality of elements arranged in a line, displaying means for displaying image information obtained by scanning the surface of the wafer along the streets by the use of the line sensor, and recording means for recording the image information. Preferably, the inspecting means further includes determining means for determining whether or not electrodes formed on both sides of the street are good according to the image information.

Preferably, the wafer inspecting device further includes chuck table driving means for moving the chuck table in an X

direction as a scanning direction of the line sensor; indexing means for moving the inspecting means in a Y direction orthogonal to the X direction, the Y direction being the same as the transverse direction of the street; a cassette mounting table for mounting a cassette in which a plurality of wafers are stored; extracting means for extracting one of the wafers stored in the cassette; a temporary placement table on which the wafer extracted by the extracting means is temporarily placed; and carrying means for carrying the wafer temporarily placed on the temporary placement table to the chuck table.

According to the present invention, the electrodes formed on both sides of the street are scanned by using the line sensor to thereby efficiently determine whether or not the electrodes are good according to the deposited condition of foreign matter. Further, in the case that the inspection of the wafer is performed by using the inspecting means after dicing the wafer, the scanning speed of the wafer in the inspecting device may be set so as to match with the cutting speed in a dicing device. In this case, the inspection of the wafer can be performed in timing with the dicing of the wafer, thereby improving the productivity.

The above and other objects, features and advantages of the present invention and the manner of realizing them will become more apparent, and the invention itself will best be understood from a study of the following description and appended claims with reference to the attached drawings showing some preferred embodiments of the invention.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a wafer inspecting device according to a preferred embodiment of the present invention;

FIG. 2 is an enlarged perspective view of an essential part of the wafer inspecting device shown in FIG. 1;

FIG. 3 is a schematic plan view showing the configuration of inspecting means; and

FIG. 4 is an enlarged view illustrating image information obtained by the inspecting means shown in FIG. 3.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIG. 1, there is shown a wafer inspecting device 1 according to a preferred embodiment of the present invention. The wafer inspecting device 1 functions to detect foreign matter deposited to a wafer. The wafer inspecting device 1 includes a chuck table 2 for holding a wafer, inspecting means 3 for inspecting the surface of the wafer held on the chuck table 2 by using image information on the wafer, alignment means 4 for detecting an inspection area of the wafer and aligning this inspection area to the inspecting means 3, a cassette mounting table 5 for mounting a cassette 5a in which a plurality of wafers are stored, extracting means 6 for extracting one of the wafers stored in the cassette 5a, a temporary placement table 7 on which the wafer extracted by the extracting means 6 is temporarily placed, and carrying means 8 for carrying the wafer temporarily placed on the temporary placement table 7 to the chuck table 2. As shown in FIG. 2, the chuck table 2 is driven by chuck table driving means 9 to move in an X direction shown by an arrow X. The inspecting means 3 is driven by indexing means 10 to move in a Y direction shown by an arrow Y, the Y direction being orthogonal to the X direction.

As shown in FIG. 2, the chuck table driving means 9 includes a ball screw 90 extending in the X direction, a pair of guide rails 91 extending parallel to the ball screw 90, a motor

**92** connected to one end of the ball screw **90** for rotating the ball screw **90**, a slide plate **93** having an internal nut (not shown) threadedly engaged with the ball screw **90** and a lower portion slidably fitted with the guide rails **91**, and a rotationally driving member **94** fixed to the upper surface of the slide plate **93** and having a pulse motor (not shown) for rotating the chuck table **2**. Accordingly, when the motor **92** is driven to rotate the ball screw **90**, the slide plate **93** is moved in the X direction as being guided by the guide rails **91**, and the chuck table **2** is also moved in the X direction together with the slide plate **93**.

As shown in FIG. 2, the indexing means **10** includes a ball screw **100** extending in the Y direction, a pair of guide rails **101** extending parallel to the ball screw **100**, a pulse motor **102** connected to one end of the ball screw **100** for rotating the ball screw **100**, a slide plate **103** having an internal nut (not shown) threadedly engaged with the ball screw **100** and a side portion slidably fitted with the guide rails **101**, and vertically moving means **104** provided on the other side portion of the slide plate **103**. Accordingly, when the pulse motor **102** is driven to rotate the ball screw **100**, the slide plate **103** is moved in the Y direction as being guided by the guide rails **101**, and the vertically moving means **104** is also moved in the Y direction together with the slide plate **103**.

The vertically moving means **104** includes a ball screw **104a** extending in a Z direction shown by an arrow Z as a vertical direction, a pair of guide rails **104b** extending parallel to the ball screw **104a**, a pulse motor **104c** connected to one end of the ball screw **104a** for rotating the ball screw **104a**, and a vertically moving member **104d** having an internal nut (not shown) threadedly engaged with the ball screw **104a** and a side portion slidably fitted with the guide rails **104b**. The alignment means **4** and the inspecting means **3** are fixed to the vertically moving member **104d**.

The alignment means **4** has an imaging member **40** for imaging a wafer. The inspecting means **3** includes a line sensor **30** having an element array **30a** (see FIG. 3) composed of a plurality of elements linearly arranged in the Y direction. As shown in FIG. 3, the element array **30a** is positioned on an extension line extending from the imaging member **40** in the X direction. Each element is provided by a CCD having 5000 pixels arranged in series on a straight line having a length of 5 mm, for example.

As shown in FIG. 3, the inspecting means **3** further includes displaying means **31** for displaying image information obtained by the line sensor **30**, recording means **32** for recording the image information obtained above, and determining means **33** for determining whether or not electrodes formed on the wafer are good (nondefective) according to the image information obtained above.

As shown in FIG. 1, the carrying means **8** includes a rail **80** extending in the Y direction, a moving member **81** adapted to move along the rail **80**, and a suction member **82** for holding a ringlike frame F by suction. The suction member **82** is movable at least between the temporary placement table **7** and the chuck table **2**. A wafer W as a subject to be inspected is integrated with the frame F through a tape T, and a plurality of such wafers W with the frames F are stored in the cassette **5a**. The cassette mounting table **5** is vertically movable, so that the height of the wafer W to be extracted from the cassette **5a** is adjusted by the vertical movement of the cassette mounting table **5**. The frame F to be extracted is held by the extracting means **6** and then moved in the Y direction by the extracting means **6**. When the wafer W is moved to the temporary placement table **7**, the wafer W is removed from the extracting means **6** and then placed on the temporary placement table **7**.

Thereafter, the suction member **82** is lowered to hold the frame F with the wafer W, and is next raised. In this raised condition of the wafer W, the moving member **81** is moved to carry the wafer W to a position directly above the chuck table **2**. Thereafter, the suction member **82** is lowered to remove the wafer W and to set it on the chuck table **2**. Thus, the wafer W integrated with the frame F is held on the chuck table **2**. Thereafter, the chuck table **2** holding the wafer W is moved in the X direction to a position directly below the alignment means **4**. In this position, the surface of the wafer W is imaged by the imaging member **40**, and pattern matching is performed between the image obtained by the imaging member **40** and the image information preliminarily stored in a memory or the like, thereby detecting a street S extending in the X direction shown in FIG. 4, for example. Then, alignment is performed in the Y direction between the center of the street S along its width and the element array (photosensitive member) **30a** of the line sensor **30**.

As shown in FIG. 4, a plurality of crossing streets S extending in the X and Y directions are formed on the wafer W to partition a plurality of device areas D. In each device area D, a plurality of bonding pads B as a kind of electrodes are arranged in a line along each street S extending in the X direction. Further, each street S is previously cut to form a groove G. In inspecting the surface of the wafer W for deposited foreign matter, the chuck table **2** is moved in the X direction orthogonal to the direction of extension of the element array **30a**, thereby scanning the surface of the wafer W along the subject street S extending in the X direction by using the line sensor **30** to obtain image information in the inspection area including the subject street S and the bonding pads B as the electrodes formed on both sides of this subject street S. In this scanning operation, the moving speed of the chuck table **2** is set to 50 mm/sec, for example.

The image information obtained by the line sensor **30** can be displayed by the displaying means **31**. By viewing the displaying means **31**, an operator can check whether or not foreign matter such as cutting dust is deposited on the surface of the wafer W, thereby preventing a short circuit between any adjacent ones of the plural bonding pads B as the electrodes. For example, in the case that the diameter of each bonding pad B is 5  $\mu\text{m}$ , that the distance between the centers of any adjacent ones of the bonding pads B is 10  $\mu\text{m}$ , and that foreign matter having a diameter of 5 to 10  $\mu\text{m}$  is deposited over the adjacent bonding pads B, a short circuit occurs between these adjacent bonding pads B.

Further, the image information obtained by the line sensor **30** can be recorded by the recording means **32**. The determining means **33** can binarize the image information obtained above, for example, thereby recognizing the shape and size of each bonding pad B. The deposition of foreign matter on any one of the bonding pads B may be determined by calculating the area of each bonding pad B from the number of pixels constituting the image information of each bonding pad B and by finding any bonding pad B having a larger area. This defective bonding pad B may be identified from the X and Y coordinates of the image information. In this manner, the deposition of foreign matter can be automatically determined by the determining means **33** without the need for visual checking on the displaying means **31** by the operator. In particular, since the line sensor **30** has a high resolution, accurate determination can be performed.

After finishing the inspection on both sides of the subject street S, the inspecting means **3** is indexed in the Y direction by the indexing means **10** to obtain image information on both sides of the next street S extending in the X direction and to perform similar inspection. This indexing operation is

5

repeated to sequentially perform the inspection for all the streets S extending in the X direction. Thereafter, the chuck table 2 is rotated 90° to perform similar processing for all the other streets S. Thus, the inspection is performed over the entire surface of the wafer W.

In this preferred embodiment, the single line sensor 30 having the element array 30a composed of the plural elements linearly arranged is used to obtain image information on the electrodes arranged along a single street. As a modification, a plurality of such line sensors may be provided to simultaneously obtain image information on the electrodes arranged along a plurality of streets. In this case, image information can be efficiently obtained.

In the case that the inspection of the wafer is performed by using the inspecting device 1 after dicing the wafer, the scanning speed of the wafer in the inspecting device 1 may be set so as to match with the cutting speed in a dicing device. In this case, the inspection of the wafer can be performed in timing with the dicing of the wafer, thereby improving the productivity. For example, in the case of using a dicing device having such a configuration that a chuck table for holding the wafer is movable in the X direction and cutting means having a cutting blade is movable in the Y and Z directions, the chuck table in the dicing device and the chuck table in the inspecting device 1 may be adjusted in feed speed in such a manner that the time required for cutting of one street by the cutting blade (the time required for a travel of the chuck table) becomes equal to the time required for scanning of one street in the inspecting device 1.

The present invention is not limited to the details of the above described preferred embodiments. The scope of the invention is defined by the appended claims and all changes and modifications as fall within the equivalence of the scope of the claims are therefore to be embraced by the invention.

What is claimed is:

1. A wafer inspecting method for inspecting a wafer along streets, said wafer being formed with a plurality of devices partitioned by said streets, said wafer inspecting method comprising the steps of:

scanning the surface of said wafer along said streets by using a line sensor having a plurality of elements arranged in a line;

determining a deposited condition of foreign matter on the surface of said wafer near or on electrodes formed on both sides of said streets according to image information obtained by said scanning step; and

binarizing the image information to recognize a size and shape of each electrode to determine whether foreign matter is deposited on each electrode, and

6

wherein a scanning speed of said wafer along said streets matches a cutting speed of said wafer.

2. A wafer inspecting device comprising:

a chuck table for holding a wafer formed with a plurality of devices partitioned by streets; inspecting means for inspecting the surface of said wafer held on said chuck table; and alignment means for aligning an inspection area of said wafer to said inspecting means; said inspecting means including a line sensor having a plurality of elements arranged in a line, displaying means for displaying image information obtained by scanning the surface of said wafer along said streets by the use of said line sensor, said image information being binarized to recognize a size and shape of each electrode to determine whether foreign matter is deposited on each electrode and recording means for recording said image information, wherein said inspecting means further comprises means for calculating an area of each element from a number of pixels constituting said displayed image information of each element, and a scanning speed of scanning said surface of said wafer matches a cutting speed of said wafer.

3. The wafer inspecting device according to claim 2, wherein said inspecting means further includes determining means for determining whether or not electrodes formed on both sides of said streets are good according to said image information.

4. The wafer inspecting device according to claim 2, further comprising:

chuck table driving means for moving said chuck table in an X direction as a scanning direction of said line sensor;

indexing means for moving said inspecting means in a Y direction orthogonal to said X direction, said Y direction being the same as the transverse direction of said streets;

a cassette mounting table for mounting a cassette in which a plurality of wafers are stored;

extracting means for extracting one of said wafers stored in said cassette;

a temporary placement table on which said wafer extracted by said extracting means is temporarily placed; and

carrying means for carrying said wafer temporarily placed on said temporary placement table to said chuck table.

5. The wafer inspecting method of claim 1, further comprising the step of calculating an area of each element based on a number of pixels constituting said image information for each element.

\* \* \* \* \*