



US007724282B2

(12) **United States Patent**
Silverbrook

(10) **Patent No.:** **US 7,724,282 B2**

(45) **Date of Patent:** **May 25, 2010**

(54) **METHOD OF PROCESSING DIGITAL IMAGE TO CORRECT FOR FLASH EFFECTS**

(52) **U.S. Cl.** 348/207.2; 348/241; 348/371

(58) **Field of Classification Search** 348/371, 348/370, 207.2, 241, 222.1; 347/20, 40
See application file for complete search history.

(75) Inventor: **Kia Silverbrook**, Balmain (AU)

(73) Assignee: **Silverbrook Research Pty Ltd.**, Balmain, New South Wales (AU)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 863 days.

4,868,676 A 9/1989 Matsuura et al.
5,420,635 A * 5/1995 Konishi et al. 348/362
5,748,764 A * 5/1998 Benati et al. 382/117
5,757,388 A * 5/1998 Stephenson 347/2
5,845,166 A * 12/1998 Fellegara et al. 396/429
2002/0054212 A1* 5/2002 Fukuoka 348/207

(21) Appl. No.: **10/636,285**

(22) Filed: **Aug. 8, 2003**

* cited by examiner

(65) **Prior Publication Data**

US 2004/0032526 A1 Feb. 19, 2004

Primary Examiner—Jason Chan
Assistant Examiner—Nicholas G Giles

Related U.S. Application Data

(63) Continuation of application No. 09/112,742, filed on Jul. 10, 1998, now abandoned.

(57) **ABSTRACT**


(30) **Foreign Application Priority Data**

Jul. 15, 1997 (AU) PO7991
Jul. 15, 1997 (AU) PO7998

An image captured by a digital camera with a flash is processed by locating distortions of said captured image due to said flash such as “red-eye” effects and removing them. The process includes the steps of determining if the flash is on (step 11), if so, determining any faces within the captured image (step 12), locating eyes within said faces (step 13), determining if “red-eye” removal is required (step 14), and if so, correcting for such effects (step 15) and storing corrected image (step 16) in a memory device of the digital camera.

(51) **Int. Cl.**
H04N 5/225 (2006.01)
H04N 5/217 (2006.01)
H04N 5/222 (2006.01)

3 Claims, 2 Drawing Sheets






FIG. 1




FIG. 2

**METHOD OF PROCESSING DIGITAL IMAGE
TO CORRECT FOR FLASH EFFECTS**

**CROSS REFERENCES TO RELATED
APPLICATIONS**

This is a Continuation of U.S. application Ser. No. 09/112,742, tiled on Jul. 10, 1998 now abandoned. The following Australian provisional patent applications are hereby incorporated by cross-reference. For the purposes of location and identification, US patent applications identified by their US patent application serial numbers (USSN) are listed alongside the Australian applications from which the US patent applications claim the right of priority.

Cross-Referenced Australian Provisional Patent Application No.	U.S. patent/Patent Application (Claiming Right of Priority from Australian Provisional Application)	Docket No.
PO7991	6,750,901	ART01US
PO8505	6,476,863	ART02US
PO7988	6,788,336	ART03US
PO9395	6,322,181	ART04US
PO8017	6,597,817	ART06US
PO8014	6,227,648	ART07US
PO8025	6,727,948	ART08US
PO8032	6,690,419	ART09US
PO7999	6,727,951	ART10US
PO8030	6,196,541	ART13US
PO7997	6,195,150	ART15US
PO7979	6,362,868	ART16US
PO7978	6,831,681	ART18US
PO7982	6,431,669	ART19US
PO7989	6,362,869	ART20US
PO8019	6,472,052	ART21US
PO7980	6,356,715	ART22US
PO8018	6,894,694	ART24US
PO7938	6,636,216	ART25US
PO8016	6,366,693	ART26US
PO8024	6,329,990	ART27US
PO7939	6,459,495	ART29US
PO8501	6,137,500	ART30US
PO8500	6,690,416	ART31US
PO7987	7,050,143	ART32US
PO8022	6,398,328	ART33US
PO8497	7,110,024	ART34US
PO8020	6,431,704	ART38US
PO8504	6,879,341	ART42US
PO8000	6,415,054	ART43US
PO7934	6,665,454	ART45US
PO7990	6,542,645	ART46US
PO8499	6,486,886	ART47US
PO8502	6,381,361	ART48US
PO7981	6,317,192	ART50US
PO7986	6,850,274	ART51US
PO7983	09/113,054	ART52US
PO8026	6,646,757	ART53US
PO8028	6,624,848	ART56US
PO9394	6,357,135	ART57US
PO9397	6,271,931	ART59US
PO9398	6,353,772	ART60US
PO9399	6,106,147	ART61US
PO9400	6,665,008	ART62US
PO9401	6,304,291	ART63US
PO9403	6,305,770	ART65US
PO9405	6,289,262	ART66US
PP0959	6,315,200	ART68US
PP1397	6,217,165	ART69US
PP2370	6,786,420	DOT01US
PO8003	6,350,023	Fluid01US
PO8005	6,318,849	Fluid02US
PO8066	6,227,652	IJ01US
PO8072	6,213,588	IJ02US
PO8040	6,213,589	IJ03US
PO8071	6,231,163	IJ04US

-continued

5	Cross-Referenced Australian Provisional Patent Application No.	U.S. patent/Patent Application (Claiming Right of Priority from Australian Provisional Application)	Docket No.
	PO8047	6,247,795	IJ05US
	PO8035	6,394,581	IJ06US
	PO8044	6,244,691	IJ07US
10	PO8063	6,257,704	IJ08US
	PO8057	6,416,168	IJ09US
	PO8056	6,220,694	IJ10US
	PO8069	6,257,705	IJ11US
	PO8049	6,247,794	IJ12US
	PO8036	6,234,610	IJ13US
15	PO8048	6,247,793	IJ14US
	PO8070	6,264,306	IJ15US
	PO8067	6,241,342	IJ16US
	PO8001	6,247,792	IJ17US
	PO8038	6,264,307	IJ18US
	PO8033	6,254,220	IJ19US
20	PO8002	6,234,611	IJ20US
	PO8068	6,302,528	IJ21US
	PO8062	6,283,582	IJ22US
	PO8034	6,239,821	IJ23US
	PO8039	6,338,547	IJ24US
	PO8041	6,247,796	IJ25US
	PO8004	6,557,977	IJ26US
25	PO8037	6,390,603	IJ27US
	PO8043	6,362,843	IJ28US
	PO8042	6,293,653	IJ29US
	PO8064	6,312,107	IJ30US
	PO9389	6,227,653	IJ31US
	PO9391	6,234,609	IJ32US
30	PP0888	6,238,040	IJ33US
	PP0891	6,188,415	IJ34US
	PP0890	6,227,654	IJ35US
	PP0873	6,209,989	IJ36US
	PP0993	6,247,791	IJ37US
	PP0890	6,336,710	IJ38US
35	PP1398	6,217,153	IJ39US
	PP2592	6,416,167	IJ40US
	PP2593	6,243,113	IJ41US
	PP3991	6,283,581	IJ42US
	PP3987	6,247,790	IJ43US
	PP3985	6,260,953	IJ44US
	PP3983	6,267,469	IJ45US
40	PO7935	6,224,780	IJM01US
	PO7936	6,235,212	IJM02US
	PO7937	6,280,643	IJM03US
	PO8061	6,284,147	IJM04US
	PO8054	6,214,244	IJM05US
	PO8065	6,071,750	IJM06US
45	PO8055	6,267,905	IJM07US
	PO8053	6,251,298	IJM08US
	PO8078	6,258,285	IJM09US
	PO7933	6,225,138	IJM10US
	PO7950	6,241,904	IJM11US
	PO7949	6,299,786	IJM12US
50	PO8060	6,866,789	IJM13US
	PO8059	6,231,773	IJM14US
	PO8073	6,190,931	IJM15US
	PO8076	6,248,249	IJM16US
	PO8075	6,290,862	IJM17US
	PO8079	6,241,906	IJM18US
55	PO8050	6,565,762	IJM19US
	PO8052	6,241,905	IJM20US
	PO7948	6,451,216	IJM21US
	PO7951	6,231,772	IJM22US
	PO8074	6,274,056	IJM23US
	PO7941	6,290,861	IJM24US
	PO8077	6,248,248	IJM25US
60	PO8058	6,306,671	IJM26US
	PO8051	6,331,258	IJM27US
	PO8045	6,110,754	IJM28US
	PO7952	6,294,101	IJM29US
	PO8046	6,416,679	IJM30US
65	PO9390	6,264,849	IJM31US
	PO9392	6,254,793	IJM32US
	PP0889	6,235,211	IJM35US

-continued

Cross-Referenced Australian Provisional Patent Application No.	U.S. patent/Patent Application (Claiming Right of Priority from Australian Provisional Application)	Docket No.
PP0887	6,491,833	IJM36US
PP0882	6,264,850	IJM37US
PP0874	6,258,284	IJM38US
PP1396	6,312,615	IJM39US
PP3989	6,228,668	IJM40US
PP2591	6,180,427	IJM41US
PP3990	6,171,875	IJM42US
PP3986	6,267,904	IJM43US
PP3984	6,245,247	IJM44US
PP3982	6,315,914	IJM45US
PP0895	6,231,148	IR01US
PP0869	6,293,658	IR04US
PP0887	6,614,560	IR05US
PP0885	6,238,033	IR06US
PP0884	6,312,070	IR10US
PP0886	6,238,111	IR12US
PP0877	6,378,970	IR16US
PP0878	6,196,739	IR17US
PP0883	6,270,182	IR19US
PP0880	6,152,619	IR20US
PO8006	6,087,638	MEMS02US
PO8007	6,340,222	MEMS03US
PO8010	6,041,600	MEMS05US
PO8011	6,299,300	MEMS06US
PO7947	6,067,797	MEMS07US
PO7944	6,286,935	MEMS09US
PO7946	6,044,646	MEMS10US
PP0894	6,382,769	MEMS13US

FIELD OF INVENTION

The present invention relates to an image processing method and apparatus and, in particular, discloses a process for correcting for flash induced distortions in a Digital Image Camera.

The present invention further relates to the field of digital image processing and in particular, the field of processing of images taken via a digital camera.

BACKGROUND OF THE INVENTION

Recently, digital cameras have become increasingly popular. These cameras normally operate by means of imaging a desired image utilising a charge coupled device (CCD) array and storing the imaged scene on an electronic storage medium for later down loading onto a computer system for subsequent manipulation and printing out. Normally, when utilising a computer system to print out an image, sophisticated software may be available to manipulate the image in accordance with requirements.

Unfortunately such systems require significant post processing of a captured image and normally present the image in an orientation in which it was taken, relying on the post processing process to perform any necessary or required modifications of the captured image. Further, much of the environmental information available when the picture was taken is lost.

SUMMARY OF THE INVENTION

It is an object of the present invention to utilise flash information in a digital image camera for processing digital images.

In accordance with a first aspect of the present invention there is provided a method of processing an image captured utilising a digital camera and a flash said method comprising the steps of:

- 5 (a) locating distortions of said captured image due to the utilisation of said flash;
 - (b) retouching said image so as to locally reduce the effect of said distortions.
- In accordance with the second aspect of the present invention there is provided a digital camera having reduced flash distortion effects on captured images comprising;
- 10 (a) a digital image capture means for the capture of images;
 - (b) a distortion location means for locating flash induced colour distortions in the captured image; and
 - 15 (c) image correction means connected to said distortion location means and said digital image capture means and adapted to process said captured image to reduce the effects of said distortions;
 - (d) display means connected to said image correction means for displaying said captured image having reduced flash distortion effects.
 - 20

BRIEF DESCRIPTION OF DRAWING

Notwithstanding any other forms which may fall within the scope of the present invention, preferred forms of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

- FIG. 1 illustrates the process of capturing and outputting an image; and
- FIG. 2 illustrates the process of red-eye removal.
- 30

DESCRIPTION OF PREFERRED AND OTHER EMBODIMENTS

The preferred embodiment is preferably implemented through suitable programming of a hand held camera device such as that described in patent application having applicant's reference (ART01) U.S. Ser. No. 09/113,060 filed concurrently herewith by the present applicant the content of which is hereby specifically incorporated by cross reference.

The aforementioned patent specification discloses a camera system, hereinafter known as an "Artcam" type camera, wherein sensed images can be directly printed out by an Artcam portable camera unit. Further, the aforementioned specification discloses means and methods for performing various manipulations on images captured by the camera sensing device leading to the production of various effects in any output image. The manipulations are disclosed to be highly flexible in nature and can be implemented through the insertion into the Artcam of cards having encoded thereon various instructions for the manipulation of images, the cards hereinafter being known as Artcards. The Artcam further has significant onboard processing power in an Artcam Central Processor unit (ACP) which is interconnected to a memory device for the storage of important data and images.

As disclosed in U.S. Ser. No. 09/113,060 (issued as U.S. Pat. No. 6,750,901), the Artcards contain, on one surface encoded information and on the other surface, contain an image distorted by the particular effect produced by the Artcard. The Artcard is inserted in an Artcard reader in the side of camera and, upon insertion, results in an output image being distorted in the same manner as the distortion appearing on the surface of Artcard.

One important form of processing is the removal of "red-eye" effects that can result in captured images as result of utilisation of a flash.

Turning now to FIG. 1, in the preferred embodiment, the image 2 as originally captured by the CCD device is subject to a processing step 3 when a flash has been utilised so as to produce a processed output image for printing.

Turning now to FIG. 2, there is illustrated in more detail, one particular image processing algorithm 10 which can be utilised when a flash has been utilised in capturing an image by a CCD device. The algorithm is preferably only utilised when a flash was used 11 to take the picture captured by the CCD. The purpose of the algorithm is to reduce the image effects due to the utilisation of the flash. Such image effects can include the well known "red-eye" effect of individual eyes appearing red in a photographic image. Other effects such as flash reflections off reflective surfaces can also be separately processed utilising other algorithms. The first step 12 in eliminating red-eye effects in the images is to determine the faces within the image. The face detection process 12 can proceed by detecting regions of contiguous colour which map the hue, saturation and value (HSV) of the range of human face colours under the range of normal lighting encountered after any other applied image enhancements or hue corrections. The detected regions can then be passed through various heuristic tests including determining the presence of eyes, mouth, overall shape and overlap. The heuristic tests produce a resulting probability of a face being present in the image and where this is above a threshold, a face is determined to be located in the image.

Once a face has been determined within an image, the eyes are located within the face in step 13. Each eye in step 12 is then independently processed to determine its special range of colours so as to determine whether a red-eye removal process is required in step 14.

If the red-eye removal process 14 is required, a retouching algorithm 15 is applied to the eye area so as to reduce the red saturation whilst simultaneously not introducing any discontinuities or likely artefacts in the output image. Of course, many different techniques could be utilised including a form of gaussian alteration around a central point of the eye. Finally, the image is written in step 16 in its updated form, back to the memory device of the ACP.

Preferably, any other retouching algorithms including remapping colours affected by the spectral nature of the flash-light are also utilised at this time.

Alternatively, the Artcard inserted could have a number of manipulations applied to the image which are specific to the flash setting. For example, clip arts containing candles, light globes etc could be inserted in an image utilising a flash and large suns inserted in non-flash images.

It would be appreciated by a person skilled in the art that numerous variations and/or modifications may be made to the present invention as shown in the specific embodiment without departing from the spirit or scope of the invention as broadly described. The present embodiment is, therefore, to be considered in all respects to be illustrative and not restrictive.

Ink Jet Technologies

The embodiments of the invention use an ink jet printer type device. Of course many different devices could be used. However presently popular ink jet printing technologies are unlikely to be suitable.

The most significant problem with thermal ink jet is power consumption. This is approximately 100 times that required for high speed, and stems from the energy-inefficient means of drop ejection. This involves the rapid boiling of water to produce a vapor bubble which expels the ink. Water has a very high heat capacity, and must be superheated in thermal ink jet

applications. This leads to an efficiency of around 0.02%, from electricity input to drop momentum (and increased surface area) out.

The most significant problem with piezoelectric ink jet is size and cost. Piezoelectric crystals have a very small deflection at reasonable drive voltages, and therefore require a large area for each nozzle. Also, each piezoelectric actuator must be connected to its drive circuit on a separate substrate. This is not a significant problem at the current limit of around 300 nozzles per print head, but is a major impediment to the fabrication of pagewidth print heads with 19,200 nozzles.

Ideally, the ink jet technologies used meet the stringent requirements of in-camera digital color printing and other high quality, high speed, low cost printing applications. To meet the requirements of digital photography, new ink jet technologies have been created. The target features include:

- low power (less than 10 Watts)
- high resolution capability (1,600 dpi or more)
- photographic quality output
- low manufacturing cost
- small size (pagewidth times minimum cross section)
- high speed (<2 seconds per page).

All of these features can be met or exceeded by the ink jet systems described below with differing levels of difficulty. Forty-five different ink jet technologies have been developed by the Assignee to give a wide range of choices for high volume manufacture. These technologies form part of separate applications assigned to the present Assignee as set out in the table under the heading Cross References to Related Applications.

The inkjet designs shown here are suitable for a wide range of digital printing systems, from battery powered one-time use digital cameras, through to desktop and network printers, and through to commercial printing systems

For ease of manufacture using standard process equipment, the print head is designed to be a monolithic 0.5 micron CMOS chip with MEMS post processing. For color photographic applications, the print head is 100 mm long, with a width which depends upon the ink jet type. The smallest print head designed is IJ38, which is 0.35 mm wide, giving a chip area of 35 square mm. The print heads each contain 19,200 nozzles plus data and control circuitry.

Ink is supplied to the back of the print head by injection molded plastic ink channels. The molding requires 50 micron features, which can be created using a lithographically micro-machined insert in a standard injection molding tool. Ink flows through holes etched through the wafer to the nozzle chambers fabricated on the front surface of the wafer. The print head is connected to the camera circuitry by tape automated bonding.

Tables of Drop-on-Demand Ink Jets

Eleven important characteristics of the fundamental operation of individual ink jet nozzles have been identified. These characteristics are largely orthogonal, and so can be elucidated as an eleven dimensional matrix. Most of the eleven axes of this matrix include entries developed by the present assignee.

The following tables form the axes of an eleven dimensional table of ink jet types.

- Actuator mechanism (18 types)
- Basic operation mode (7 types)
- Auxiliary mechanism (8 types)
- Actuator amplification or modification method (17 types)
- Actuator motion (19 types)
- Nozzle refill method (4 types)
- Method of restricting back-flow through inlet (10 types)

- Nozzle clearing method (9 types)
- Nozzle plate construction (9 types)
- Drop ejection direction (5 types)
- Ink type (7 types)

The complete eleven dimensional table represented by these axes contains 36.9 billion possible configurations of ink jet nozzle. While not all of the possible combinations result in a viable ink jet technology, many million configurations are viable. It is clearly impractical to elucidate all of the possible configurations. Instead, certain ink jet types have been investigated in detail. These are designated IJ01 to IJ45 which match the docket numbers in the table under the heading Cross References to Relation Applications.

Other ink jet configurations can readily be derived from these forty-five examples by substituting alternative configurations along one or more of the 11 axes. Most of the IJ01 to

IJ45 examples can be made into ink jet print heads with characteristics superior to any currently available ink jet technology.

Where there are prior art examples known to the inventor, one or more of these examples are listed in the examples column of the tables below. The IJ01 to IJ45 series are also listed in the examples column. In some cases, a print technology may be listed more than once in a table, where it shares characteristics with more than one entry.

Suitable applications for the ink jet technologies include: Home printers, Office network printers, Short run digital printers, Commercial print systems, Fabric printers, Pocket printers, Internet WWW printers, Video printers, Medical imaging, Wide format printers, Notebook PC printers, Fax machines, Industrial printing systems, Photocopiers, Photographic minilabs etc.

The information associated with the aforementioned 11 dimensional matrix are set out in the following tables.

ACTUATOR MECHANISM (APPLIED ONLY TO SELECTED INK DROPS)				
	Description	Advantages	Disadvantages	Examples
Thermal bubble	An electrothermal heater heats the ink to above boiling point, transferring significant heat to the aqueous ink. A bubble nucleates and quickly forms, expelling the ink. The efficiency of the process is low, with typically less than 0.05% of the electrical energy being transformed into kinetic energy of the drop.	Large force generated Simple construction No moving parts Fast operation Small chip area required for actuator	High power Ink carrier limited to water Low efficiency High temperatures required High mechanical stress Unusual materials required Large drive transistors Cavitation causes actuator failure Kogation reduces bubble formation Large print heads are difficult to fabricate	Canon Bubblejet 1979 Endo et al GB patent 2,007,162 Xerox heater-in-pit 1990 Hawkins et al U.S. Pat. No. 4,899,181 Hewlett-Packard TIJ 1982 Vaught et al U.S. Pat. No. 4,490,728
Piezo-electric	A piezoelectric crystal such as lead lanthanum zirconate (PZT) is electrically activated, and either expands, shears, or bends to apply pressure to the ink, ejecting drops.	Low power consumption Many ink types can be used Fast operation High efficiency	Very large area required for actuator Difficult to integrate with electronics High voltage drive transistors required Full pagewidth print heads impractical due to actuator size Requires electrical poling in high field strengths during manufacture	Kyser et al U.S. Pat. No. 3,946,398 Zoltan U.S. Pat. No. 3,683,212 1973 Stemme U.S. Pat. No. 3,747,120 Epson Stylus Tektronix IJ04
Electro-strictive	An electric field is used to activate electrostriction in relaxor materials such as lead lanthanum zirconate titanate (PLZT) or lead magnesium niobate (PMN).	Low power consumption Many ink types can be used Low thermal expansion Electric field strength required (approx. 3.5 V/μm) can be generated without difficulty Does not require electrical poling	Low maximum strain (approx. 0.01%) Large area required for actuator due to low strain Response speed is marginal (~10 μs) High voltage drive transistors required Full pagewidth print heads impractical due to actuator size	Seiko Epson, Usui et al JP 253401/96 IJ04
Ferro-electric	An electric field is used to induce a phase transition between the antiferroelectric (AFE) and ferroelectric (FE) phase. Perovskite	Low power consumption Many ink types can be used Fast operation (<1 μs)	Difficult to integrate with electronics Unusual materials such as PLZSnT are required Actuators require a	IJ04

-continued

ACTUATOR MECHANISM (APPLIED ONLY TO SELECTED INK DROPS)					
Description	Advantages	Disadvantages	Examples		
	materials such as tin modified lead lanthanum zirconate titanate (PLZSnT) exhibit large strains of up to 1% associated with the AFE to FE phase transition.	Relatively high longitudinal strain High efficiency Electric field strength of around 3 V/ μ m can be readily provided	large area		
Electrostatic plates	Conductive plates are separated by a compressible or fluid dielectric (usually air). Upon application of a voltage, the plates attract each other and displace ink, causing drop ejection. The conductive plates may be in a comb or honeycomb structure, or stacked to increase the surface area and therefore the force.	Low power consumption Many ink types can be used Fast operation	Difficult to operate electrostatic devices in an aqueous environment The electrostatic actuator will normally need to be separated from the ink Very large area required to achieve high forces High voltage drive transistors may be required Full pagewidth print heads are not competitive due to actuator size	IJ02, IJ04	
Electrostatic pull on ink	A strong electric field is applied to the ink, whereupon electrostatic attraction accelerates the ink towards the print medium.	Low current consumption Low temperature	High voltage required May be damaged by sparks due to air breakdown Required field strength increases as the drop size decreases High voltage drive transistors required Electrostatic field attracts dust	1989 Saito et al, U.S. Pat. No. 4,799,068 1989 Miura et al, U.S. Pat. No. 4,810,954 Tone-jet	
Permanent magnet electro-magnetic	An electromagnet directly attracts a permanent magnet, displacing ink and causing drop ejection. Rare earth magnets with a field strength around 1 Tesla can be used. Examples are: Samarium Cobalt (SaCo) and magnetic materials in the neodymium iron boron family (NdFeB, NdDyFeBNb, NdDyFeB, etc)	Low power consumption Many ink types can be used Fast operation High efficiency Easy extension from single nozzles to pagewidth print heads	Complex fabrication Permanent magnetic material such as Neodymium Iron Boron (NdFeB) required. High local currents required Copper metalization should be used for long electromigration lifetime and low resistivity Pigmented inks are usually infeasible Operating temperature limited to the Curie temperature (around 540 K)	IJ07, IJ10	
Soft magnetic core electro-magnetic	A solenoid induced a magnetic field in a soft magnetic core or yoke fabricated from a ferrous material such as electroplated iron alloys such as CoNiFe [1], CoFe, or NiFe alloys. Typically, the soft magnetic material is in two parts, which are normally held apart by a spring, When the solenoid is	Low power consumption Many ink types can be used Fast operation High efficiency Easy extension from single nozzles to pagewidth print heads	Complex fabrication Materials not usually present in a CMOS fab such as NiFe, CoNiFe, or CoFe are required High local currents required Copper metalization should be used for long electromigration lifetime and low resistivity	IJ01, IJ05, IJ08, IJ10, IJ12, IJ14, IJ15, IJ17	

-continued

ACTUATOR MECHANISM (APPLIED ONLY TO SELECTED INK DROPS)				
	Description	Advantages	Disadvantages	Examples
	actuated, the two parts attract, displacing the ink.		Electroplating is required High saturation flux density is required (2.0-2.1 T is achievable with CoNiFe [1])	
Lorenz force	The Lorenz force acting on a current carrying wire in a magnetic field is utilized. This allows the magnetic field to be supplied externally to the print head, for example with rare earth permanent magnets. Only the current carrying wire need be fabricated on the print head, simplifying materials requirements.	Low power consumption Many ink types can be used Fast operation High efficiency Easy extension from single nozzles to pagewidth print heads	Force acts as a twisting motion Typically, only a quarter of the solenoid length provides force in a useful direction High local currents required Copper metalization should be used for long electromigration lifetime and low resistivity Pigmented inks are usually infeasible	IJ06, IJ11, IJ13, IJ16
Magnetostriction	The actuator uses the giant magnetostrictive effect of materials such as Terfenol-D (an alloy of terbium, dysprosium and iron developed at the Naval Ordnance Laboratory, hence Ter-Fe-NOL). For best efficiency, the actuator should be pre-stressed to approx. 8 MPa.	Many ink types can be used Fast operation Easy extension from single nozzles to pagewidth print heads High force is available	Force acts as a twisting motion Unusual materials such as Terfenol-D are required High local currents required Copper metalization should be used for long electromigration lifetime and low resistivity Pre-stressing may be required	Fischenbeck, U.S. Pat. No. 4,032,929 IJ25
Surface tension reduction	Ink under positive pressure is held in a nozzle by surface tension. The surface tension of the ink is reduced below the bubble threshold, causing the ink to egress from the nozzle.	Low power consumption Simple construction No unusual materials required in fabrication High efficiency Easy extension from single nozzles to pagewidth print heads	Requires supplementary force to effect drop separation Requires special ink surfactants Speed may be limited by surfactant properties	Silverbrook, EP 0771 658 A2 and related patent applications
Viscosity reduction	The ink viscosity is locally reduced to select which drops are to be ejected. A viscosity reduction can be achieved electrothermally with most inks, but special inks can be engineered for a 100:1 viscosity reduction.	Simple construction No unusual materials required in fabrication Easy extension from single nozzles to pagewidth print heads	Requires supplementary force to effect drop separation Requires special ink viscosity properties High speed is difficult to achieve Requires oscillating ink pressure A high temperature difference (typically 80 degrees) is required	Silverbrook, EP 0771 658 A2 and related patent applications
Acoustic	An acoustic wave is generated and focussed upon the drop ejection region.	Can operate without a nozzle plate	Complex drive circuitry Complex fabrication Low efficiency Poor control of drop position Poor control of drop volume	1993 Hadimioglu et al, EUP 550,192 1993 Elrod et al, EUP 572,220

-continued

ACTUATOR MECHANISM (APPLIED ONLY TO SELECTED INK DROPS)				
	Description	Advantages	Disadvantages	Examples
Thermo-elastic bend actuator	An actuator which relies upon differential thermal expansion upon Joule heating is used.	Low power consumption Many ink types can be used Simple planar fabrication Small chip area required for each actuator Fast operation High efficiency CMOS compatible voltages and currents Standard MEMS processes can be used Easy extension from single nozzles to pagewidth print heads	Efficient aqueous operation requires a thermal insulator on the hot side Corrosion prevention can be difficult Pigmented inks may be infeasible, as pigment particles may jam the bend actuator	IJ03, IJ09, IJ17, IJ18, IJ19, IJ20, IJ21, IJ22, IJ23, IJ24, IJ27, IJ28, IJ29, IJ30, IJ31, IJ32, IJ33, IJ34, IJ35, IJ36, IJ37, IJ38, IJ39, IJ40, IJ41
High CTE thermo-elastic actuator	A material with a very high coefficient of thermal expansion (CTE) such as polytetrafluoroethylene (PTFE) is used. As high CTE materials are usually non-conductive, a heater fabricated from a conductive material is incorporated. A 50 μm long PTFE bend actuator with polysilicon heater and 15 mW power input can provide 180 μN force and 10 μm deflection. Actuator motions include: Bend Push Buckle Rotate	High force can be generated Three methods of PTFE deposition are under development: chemical vapor deposition (CVD), spin coating, and evaporation PTFE is a candidate for low dielectric constant insulation in ULSI Very low power consumption Many ink types can be used Simple planar fabrication Small chip area required for each actuator Fast operation High efficiency CMOS compatible voltages and currents Easy extension from single nozzles to pagewidth print heads	Requires special material (e.g. PTFE) Requires a PTFE deposition process, which is not yet standard in ULSI fabs PTFE deposition cannot be followed with high temperature (above 350° C.) processing Pigmented inks may be infeasible, as pigment particles may jam the bend actuator	IJ09, IJ17, IJ18, IJ20, IJ21, IJ22, IJ23, IJ24, IJ27, IJ28, IJ29, IJ30, IJ31, IJ42, IJ43, IJ44
Conductive polymer thermo-elastic actuator	A polymer with a high coefficient of thermal expansion (such as PTFE) is doped with conducting substances to increase its conductivity to about 3 orders of magnitude below that of copper. The conducting polymer expands when resistively heated. Examples of conducting dopants include: Carbon nanotubes Metal fibers Conductive polymers such as doped	High force can be generated Very low power consumption Many ink types can be used Simple planar fabrication Small chip area required for each actuator Fast operation High efficiency CMOS compatible voltages and currents Easy extension from single nozzles to pagewidth print heads	Requires special materials development (High CTE conductive polymer) Requires a PTFE deposition process, which is not yet standard in ULSI fabs PTFE deposition cannot be followed with high temperature (above 350° C.) processing Evaporation and CVD deposition techniques cannot be used Pigmented inks may	IJ24

-continued

<u>ACTUATOR MECHANISM (APPLIED ONLY TO SELECTED INK DROPS)</u>				
	Description	Advantages	Disadvantages	Examples
	polythiophene Carbon granules		be infeasible, as pigment particles may jam the bend actuator	
Shape memory alloy	A shape memory alloy such as TiNi (also known as Nitinol-Nickel Titanium alloy developed at the Naval Ordnance Laboratory) is thermally switched between its weak martensitic state and its high stiffness austenic state. The shape of the actuator in its martensitic state is deformed relative to the austenic shape. The shape change causes ejection of a drop.	High force is available (stresses of hundreds of MPa) Large strain is available (more than 3%) High corrosion resistance Simple construction Easy extension from single nozzles to pagewidth print heads Low voltage operation	Fatigue limits maximum number of cycles Low strain (1%) is required to extend fatigue resistance Cycle rate limited by heat removal Requires unusual materials (TiNi) The latent heat of transformation must be provided High current operation Requires pre-stressing to distort the martensitic state	IJ26
Linear Magnetic Actuator	Linear magnetic actuators include the Linear Induction Actuator (LIA), Linear Permanent Magnet Synchronous Actuator (LPMSA), Linear Reluctance Synchronous Actuator (LRSA), Linear Switched Reluctance Actuator (LSRA), and the Linear Stepper Actuator (LSA).	Linear Magnetic actuators can be constructed with high thrust, long travel, and high efficiency using planar semiconductor fabrication techniques Long actuator travel is available Medium force is available Low voltage operation	Requires unusual semiconductor materials such as soft magnetic alloys (e.g. CoNiFe) Some varieties also require permanent magnetic materials such as Neodymium iron boron (NdFeB) Requires complex multi-phase drive circuitry High current operation	IJ12

BASIC OPERATION MODE

	Description	Advantages	Disadvantages	Examples
Actuator directly pushes ink	This is the simplest mode of operation: the actuator directly supplies sufficient kinetic energy to expel the drop. The drop must have a sufficient velocity to overcome the surface tension.	Simple operation No external fields required Satellite drops can be avoided if drop velocity is less than 4 m/s Can be efficient, depending upon the actuator used	Drop repetition rate is usually limited to around 10 kHz. However, this is not fundamental to the method, but is related to the refill method normally used All of the drop kinetic energy must be provided by the actuator Satellite drops usually form if drop velocity is greater than 4.5 m/s	Thermal ink jet Piezoelectric ink jet IJ01, IJ02, IJ03, IJ04, IJ05, IJ06, IJ07, IJ09, IJ11, IJ12, IJ14, IJ16, IJ20, IJ22, IJ23, IJ24, IJ25, IJ26, IJ27, IJ28, IJ29, IJ30, IJ31, IJ32, IJ33, IJ34, IJ35, IJ36, IJ37, IJ38, IJ39, IJ40, IJ41, IJ42, IJ43, IJ44
Proximity	The drops to be printed are selected by some manner (e.g. thermally induced surface tension reduction of pressurized ink). Selected drops are separated from the ink in the nozzle by	Very simple print head fabrication can be used The drop selection means does not need to provide the energy required to separate the drop from the nozzle	Requires close proximity between the print head and the print media or transfer roller May require two print heads printing alternate rows of the image Monolithic color	Silverbrook, EP 0771 658 A2 and related patent applications

-continued

<u>BASIC OPERATION MODE</u>				
	Description	Advantages	Disadvantages	Examples
	contact with the print medium or a transfer roller.		print heads are difficult	
Electrostatic pull on ink	The drops to be printed are selected by some manner (e.g. thermally induced surface tension reduction of pressurized ink). Selected drops are separated from the ink in the nozzle by a strong electric field.	Very simple print head fabrication can be used The drop selection means does not need to provide the energy required to separate the drop from the nozzle	Requires very high electrostatic field Electrostatic field for small nozzle sizes is above air breakdown Electrostatic field may attract dust	Silverbrook, EP 0771 658 A2 and related patent applications Tone-Jet
Magnetic pull on ink	The drops to be printed are selected by some manner (e.g. thermally induced surface tension reduction of pressurized ink). Selected drops are separated from the ink in the nozzle by a strong magnetic field acting on the magnetic ink.	Very simple print head fabrication can be used The drop selection means does not need to provide the energy required to separate the drop from the nozzle	Requires magnetic ink Ink colors other than black are difficult Requires very high magnetic fields	Silverbrook, EP 0771 658 A2 and related patent applications
Shutter	The actuator moves a shutter to block ink flow to the nozzle. The ink pressure is pulsed at a multiple of the drop ejection frequency.	High speed (>50 kHz) operation can be achieved due to reduced refill time Drop timing can be very accurate The actuator energy can be very low	Moving parts are required Requires ink pressure modulator Friction and wear must be considered Stiction is possible	IJ13, IJ17, IJ21
Shuttered grill	The actuator moves a shutter to block ink flow through a grill to the nozzle. The shutter movement need only be equal to the width of the grill holes.	Actuators with small travel can be used Actuators with small force can be used High speed (>50 kHz) operation can be achieved	Moving parts are required Requires ink pressure modulator Friction and wear must be considered Stiction is possible	IJ08, IJ15, IJ18, IJ19
Pulsed magnetic pull on ink pusher	A pulsed magnetic field attracts an 'ink pusher' at the drop ejection frequency. An actuator controls a catch, which prevents the ink pusher from moving when a drop is not to be ejected.	Extremely low energy operation is possible No heat dissipation problems	Requires an external pulsed magnetic field Requires special materials for both the actuator and the ink pusher Complex construction	IJ10

AUXILIARY MECHANISM (APPLIED TO ALL NOZZLES)

	Description	Advantages	Disadvantages	Examples
None	The actuator directly fires the ink drop, and there is no external field or other mechanism required.	Simplicity of construction Simplicity of operation Small physical size	Drop ejection energy must be supplied by individual nozzle actuator	Most ink jets, including piezoelectric and thermal bubble. IJ01, IJ02, IJ03, IJ04, IJ05, IJ07, IJ09, IJ11, IJ12, IJ14, IJ20, IJ22, IJ23, IJ24, IJ25, IJ26, IJ27, IJ28, IJ29, IJ30, IJ31, IJ32, IJ33, IJ34,

-continued

AUXILIARY MECHANISM (APPLIED TO ALL NOZZLES)

	Description	Advantages	Disadvantages	Examples
				IJ35, IJ36, IJ37, IJ38, IJ39, IJ40, IJ41, IJ42, IJ43, IJ44
Oscillating ink pressure (including acoustic stimulation)	The ink pressure oscillates, providing much of the drop ejection energy. The actuator selects which drops are to be fired by selectively blocking or enabling nozzles. The ink pressure oscillation may be achieved by vibrating the print head, or preferably by an actuator in the ink supply.	Oscillating ink pressure can provide a refill pulse, allowing higher operating speed. The actuators may operate with much lower energy. Acoustic lenses can be used to focus the sound on the nozzles	Requires external ink pressure oscillator. Ink pressure phase and amplitude must be carefully controlled. Acoustic reflections in the ink chamber must be designed for	Silverbrook, EP 0771 658 A2 and related patent applications. IJ08, IJ13, IJ15, IJ17, IJ18, IJ19, IJ21
Media proximity	The print head is placed in close proximity to the print medium. Selected drops protrude from the print head further than unselected drops, and contact the print medium. The drop soaks into the medium fast enough to cause drop separation.	Low power. High accuracy. Simple print head construction	Precision assembly required. Paper fibers may cause problems. Cannot print on rough substrates	Silverbrook, EP 0771 658 A2 and related patent applications

BASIC OPERATION MODE

	Description	Advantages	Disadvantages	Examples
Transfer roller	Drops are printed to a transfer roller instead of straight to the print medium. A transfer roller can also be used for proximity drop separation.	High accuracy. Wide range of print substrates can be used. Ink can be dried on the transfer roller	Bulky. Expensive. Complex construction	Silverbrook, EP 0771 658 A2 and related patent applications. Tektronix hot melt piezoelectric ink jet. Any of the IJ series
Electro-static	An electric field is used to accelerate selected drops towards the print medium.	Low power. Simple print head construction	Field strength required for separation of small drops is near or above air breakdown	Silverbrook, EP 0771 658 A2 and related patent applications. Tone-Jet
Direct magnetic field	A magnetic field is used to accelerate selected drops of magnetic ink towards the print medium.	Low power. Simple print head construction	Requires magnetic ink. Requires strong magnetic field	Silverbrook, EP 0771 658 A2 and related patent applications
Cross magnetic field	The print head is placed in a constant magnetic field. The Lorentz force in a current carrying wire is used to move the actuator.	Does not require magnetic materials to be integrated in the print head manufacturing process	Requires external magnet. Current densities may be high, resulting in electromigration problems	IJ06, IJ16
Pulsed magnetic field	A pulsed magnetic field is used to cyclically attract a paddle, which pushes on the ink. A small	Very low power operation is possible. Small print head size	Complex print head construction. Magnetic materials required in print head	IJ10

-continued

<u>BASIC OPERATION MODE</u>				
Description	Advantages	Disadvantages	Examples	
actuator moves a catch, which selectively prevents the paddle from moving.				
<u>ACTUATOR AMPLIFICATION OR MODIFICATION METHOD</u>				
Description	Advantages	Disadvantages	Examples	
None	No actuator mechanical amplification is used. The actuator directly drives the drop ejection process.	Operational simplicity	Many actuator mechanisms have insufficient travel, or insufficient force, to efficiently drive the drop ejection process	Thermal Bubble Ink jet IJ01, IJ02, IJ06, IJ07, IJ16, IJ25, IJ26
Differential expansion bend actuator	An actuator material expands more on one side than on the other. The expansion may be thermal, piezoelectric, magnetostrictive, or other mechanism. The bend actuator converts a high force low travel actuator mechanism to high travel, lower force mechanism.	Provides greater travel in a reduced print head area	High stresses are involved Care must be taken that the materials do not delaminate Residual bend resulting from high temperature or high stress during formation	Piezoelectric IJ03, IJ09, IJ17, IJ18, IJ19, IJ20, IJ21, IJ22, IJ23, IJ24, IJ27, IJ29, IJ30, IJ31, IJ32, IJ33, IJ34, IJ35, IJ36, IJ37, IJ38, IJ39, IJ42, IJ43, IJ44
Transient bend actuator	A trilayer bend actuator where the two outside layers are identical. This cancels bend due to ambient temperature and residual stress. The actuator only responds to transient heating of one side or the other.	Very good temperature stability High speed, as a new drop can be fired before heat dissipates Cancels residual stress of formation	High stresses are involved Care must be taken that the materials do not delaminate	IJ40, IJ41
Reverse spring	The actuator loads a spring. When the actuator is turned off, the spring releases. This can reverse the force/distance curve of the actuator to make it compatible with the force/time requirements of the drop ejection.	Better coupling to the ink	Fabrication complexity High stress in the spring	IJ05, IJ11
Actuator stack	A series of thin actuators are stacked. This can be appropriate where actuators require high electric field strength, such as electrostatic and piezoelectric actuators.	Increased travel Reduced drive voltage	Increased fabrication complexity Increased possibility of short circuits due to pinholes	Some piezoelectric ink jets IJ04
Multiple actuators	Multiple smaller actuators are used simultaneously to move the ink. Each actuator need provide only a portion of the force required.	Increases the force available from an actuator Multiple actuators can be positioned to control ink flow accurately	Actuator forces may not add linearly, reducing efficiency	IJ12, IJ13, IJ18, IJ20, IJ22, IJ28, IJ42, IJ43
Linear Spring	A linear spring is used to transform a motion with small travel and high force into a	Matches low travel actuator with higher travel requirements Non-contact method	Requires print head area for the spring	IJ15

-continued

ACTUATOR AMPLIFICATION OR MODIFICATION METHOD				
	Description	Advantages	Disadvantages	Examples
Coiled actuator	longer travel, lower force motion. A bend actuator is coiled to provide greater travel in a reduced chip area.	of motion transformation Increases travel Reduces chip area Planar implementations are relatively easy to fabricate.	Generally restricted to planar implementations due to extreme fabrication difficulty in other orientations.	IJ17, IJ21, IJ34, IJ35
Flexure bend actuator	A bend actuator has a small region near the fixture point, which flexes much more readily than the remainder of the actuator. The actuator flexing is effectively converted from an even coiling to an angular bend, resulting in greater travel of the actuator tip.	Simple means of increasing travel of a bend actuator	Care must be taken not to exceed the elastic limit in the flexure area Stress distribution is very uneven Difficult to accurately model with finite element analysis	IJ10, IJ19, IJ33
Catch	The actuator controls a small catch. The catch either enables or disables movement of an ink pusher that is controlled in a bulk manner.	Very low actuator energy Very small actuator size	Complex construction Requires external force Unsuitable for pigmented inks	IJ10
Gears	Gears can be used to increase travel at the expense of duration. Circular gears, rack and pinion, ratchets, and other gearing methods can be used.	Low force, low travel actuators can be used Can be fabricated using standard surface MEMS processes	Moving parts are required Several actuator cycles are required More complex drive electronics Complex construction Friction, friction, and wear are possible	IJ13
Buckle plate	A buckle plate can be used to change a slow actuator into a fast motion. It can also convert a high force, low travel actuator into a high travel, medium force motion.	Very fast movement achievable	Must stay within elastic limits of the materials for long device life High stresses involved Generally high power requirement	S. Hirata et al, "An Ink-jet Head Using Diaphragm Microactuator", Proc. IEEE MEMS, February 1996, pp 418-423. IJ18, IJ27
Tapered magnetic pole	A tapered magnetic pole can increase travel at the expense of force.	Linearizes the magnetic force/distance curve	Complex construction	IJ14
Lever	A lever and fulcrum is used to transform a motion with small travel and high force into a motion with longer travel and lower force. The lever can also reverse the direction of travel.	Matches low travel actuator with higher travel requirements Fulcrum area has no linear movement, and can be used for a fluid seal	High stress around the fulcrum	IJ32, IJ36, IJ37
Rotary impeller	The actuator is connected to a rotary impeller. A small angular deflection of the actuator results in a rotation of the impeller vanes, which push the ink against stationary vanes and out of the nozzle.	High mechanical advantage The ratio of force to travel of the actuator can be matched to the nozzle requirements by varying the number of impeller vanes	Complex construction Unsuitable for pigmented inks	IJ28
Acoustic lens	A refractive or diffractive (e.g. zone plate) acoustic lens is used to concentrate sound waves.	No moving parts	Large area required Only relevant for acoustic ink jets	1993 Hadimioglu et al, EUP 550,192 1993 Elrod et al, EUP 572,220

-continued

ACTUATOR AMPLIFICATION OR MODIFICATION METHOD

	Description	Advantages	Disadvantages	Examples
Sharp conductive point	A sharp point is used to concentrate an electrostatic field.	Simple construction	Difficult to fabricate using standard VLSI processes for a surface ejecting ink-jet Only relevant for electrostatic ink jets	Tone-jet

ACTUATOR MOTION

	Description	Advantages	Disadvantages	Examples
Volume expansion	The volume of the actuator changes, pushing the ink in all directions.	Simple construction in the case of thermal ink jet	High energy is typically required to achieve volume expansion. This leads to thermal stress, cavitation, and kogation in thermal ink jet implementations	Hewlett-Packard Thermal Ink jet Canon Bubblejet
Linear, normal to chip surface	The actuator moves in a direction normal to the print head surface. The nozzle is typically in the line of movement.	Efficient coupling to ink drops ejected normal to the surface	High fabrication complexity may be required to achieve perpendicular motion	IJ01, IJ02, IJ04, IJ07, IJ11, IJ14
Parallel to chip surface	The actuator moves parallel to the print head surface. Drop ejection may still be normal to the surface.	Suitable for planar fabrication	Fabrication complexity Friction Stiction	IJ12, IJ13, IJ15, IJ33, IJ34, IJ35, IJ36
Membrane push	An actuator with a high force but small area is used to push a stiff membrane that is in contact with the ink.	The effective area of the actuator becomes the membrane area	Fabrication complexity Actuator size Difficulty of integration in a VLSI process	1982 Howkins U.S. Pat. No. 4,459,601
Rotary	The actuator causes the rotation of some element, such a grill or impeller	Rotary levers may be used to increase travel Small chip area requirements	Device complexity May have friction at a pivot point	IJ05, IJ08, IJ13, IJ28
Bend	The actuator bends when energized. This may be due to differential thermal expansion, piezoelectric expansion, magnetostriction, or other form of relative dimensional change.	A very small change in dimensions can be converted to a large motion.	Requires the actuator to be made from at least two distinct layers, or to have a thermal difference across the actuator	1970 Kyser et al U.S. Pat. No. 3,946,398 1973 Stemme U.S. Pat. No. 3,747,120 IJ03, IJ09, IJ10, IJ19, IJ23, IJ24, IJ25, IJ29, IJ30, IJ31, IJ33, IJ34, IJ35
Swivel	The actuator swivels around a central pivot. This motion is suitable where there are opposite forces applied to opposite sides of the paddle, e.g. Lorenz force.	Allows operation where the net linear force on the paddle is zero Small chip area requirements	Inefficient coupling to the ink motion	IJ06
Straighten	The actuator is normally bent, and straightens when energized.	Can be used with shape memory alloys where the austenitic phase is planar	Requires careful balance of stresses to ensure that the quiescent bend is accurate	IJ26, IJ32
Double bend	The actuator bends in one direction when one element is energized, and bends	One actuator can be used to power two nozzles. Reduced chip size.	Difficult to make the drops ejected by both bend directions identical.	IJ36, IJ37, IJ38

-continued

<u>ACTUATOR MOTION</u>				
	Description	Advantages	Disadvantages	Examples
	the other way when another element is energized.	Not sensitive to ambient temperature	A small efficiency loss compared to equivalent single bend actuators.	
Shear	Energizing the actuator causes a shear motion in the actuator material.	Can increase the effective travel of piezoelectric actuators	Not readily applicable to other actuator mechanisms	1985 Fishbeck U.S. Pat. No. 4,584,590
Radial constriction	The actuator squeezes an ink reservoir, forcing ink from a constricted nozzle.	Relatively easy to fabricate single nozzles from glass tubing as macroscopic structures	High force required Inefficient Difficult to integrate with VLSI processes	1970 Zoltan U.S. Pat. No. 3,683,212
Coil/uncoil	A coiled actuator uncoils or coils more tightly. The motion of the free end of the actuator ejects the ink.	Easy to fabricate as a planar VLSI process Small area required, therefore low cost	Difficult to fabricate for non-planar devices Poor out-of-plane stiffness	IJ17, IJ21, IJ34, IJ35
Bow	The actuator bows (or buckles) in the middle when energized.	Can increase the speed of travel Mechanically rigid	Maximum travel is constrained High force required	IJ16, IJ18, IJ27
Push-Pull	Two actuators control a shutter. One actuator pulls the shutter, and the other pushes it.	The structure is pinned at both ends, so has a high out-of-plane rigidity	Not readily suitable for ink jets which directly push the ink	IJ18
Curl inwards	A set of actuators curl inwards to reduce the volume of ink that they enclose.	Good fluid flow to the region behind the actuator increases efficiency	Design complexity	IJ20, IJ42
Curl outwards	A set of actuators curl outwards, pressurizing ink in a chamber surrounding the actuators, and expelling ink from a nozzle in the chamber.	Relatively simple construction	Relatively large chip area	IJ43
Iris	Multiple vanes enclose a volume of ink. These simultaneously rotate, reducing the volume between the vanes.	High efficiency Small chip area	High fabrication complexity Not suitable for pigmented inks	IJ22
Acoustic vibration	The actuator vibrates at a high frequency.	The actuator can be physically distant from the ink	Large area required for efficient operation at useful frequencies Acoustic coupling and crosstalk Complex drive circuitry Poor control of drop volume and position	1993 Hadimioglu et al, EUP 550,192 1993 Elrod et al, EUP 572,220
None	In various ink jet designs the actuator does not move.	No moving parts	Various other tradeoffs are required to eliminate moving parts	Silverbrook, EP 0771 658 A2 and related patent applications Tone-jet

NOZZLE REFILL METHOD

	Description	Advantages	Disadvantages	Examples
Surface tension	This is the normal way that ink jets are refilled. After the actuator is energized, it typically returns rapidly to its normal position. This rapid return sucks in air	Fabrication simplicity Operational simplicity	Low speed Surface tension force relatively small compared to actuator force Long refill time usually dominates the total repetition	Thermal ink jet Piezoelectric ink jet IJ01-IJ07, IJ10-IJ14, IJ16, IJ20, IJ22-IJ45

-continued

<u>NOZZLE REFILL METHOD</u>				
	Description	Advantages	Disadvantages	Examples
	through the nozzle opening. The ink surface tension at the nozzle then exerts a small force restoring the meniscus to a minimum area. This force refills the nozzle.		rate	
Shuttered oscillating ink pressure	Ink to the nozzle chamber is provided at a pressure that oscillates at twice the drop ejection frequency. When a drop is to be ejected, the shutter is opened for 3 half cycles: drop ejection, actuator return, and refill. The shutter is then closed to prevent the nozzle chamber emptying during the next negative pressure cycle.	High speed Low actuator energy, as the actuator need only open or close the shutter, instead of ejecting the ink drop	Requires common ink pressure oscillator May not be suitable for pigmented inks	IJ05, IJ13, IJ15, IJ17, IJ18, IJ19, IJ21
Refill actuator	After the main actuator has ejected a drop a second (refill) actuator is energized. The refill actuator pushes ink into the nozzle chamber. The refill actuator returns slowly, to prevent its return from emptying the chamber again.	High speed, as the nozzle is actively refilled	Requires two independent actuators per nozzle	IJ09
Positive ink pressure	The ink is held a slight positive pressure. After the ink drop is ejected, the nozzle chamber fills quickly as surface tension and ink pressure both operate to refill the nozzle.	High refill rate, therefore a high drop repetition rate is possible	Surface spill must be prevented Highly hydrophobic print head surfaces are required	Silverbrook, EP 0771 658 A2 and related patent applications Alternative for, IJ01-IJ07, IJ10-IJ14, IJ16, IJ20, IJ22-IJ45

METHOD OF RESTRICTING BACK-FLOW THROUGH INLET

	Description	Advantages	Disadvantages	Examples
Long inlet channel	The ink inlet channel to the nozzle chamber is made long and relatively narrow, relying on viscous drag to reduce inlet back-flow.	Design simplicity Operational simplicity Reduces crosstalk	Restricts refill rate May result in a relatively large chip area Only partially effective	Thermal ink jet Piezoelectric ink jet IJ42, IJ43
Positive ink pressure	The ink is under a positive pressure, so that in the quiescent state some of the ink drop already protrudes from the nozzle. This reduces the pressure in the nozzle chamber which is required to eject a certain volume of ink. The reduction in chamber pressure	Drop selection and separation forces can be reduced Fast refill time	Requires a method (such as a nozzle rim or effective hydrophobizing, or both) to prevent flooding of the ejection surface of the print head.	Silverbrook, EP 0771 658 A2 and related patent applications Possible operation of the following: IJ01-IJ07, IJ09-IJ12, IJ14, IJ16, IJ20, IJ22, , IJ23-IJ34, IJ36-IJ41, IJ44

-continued

<u>METHOD OF RESTRICTING BACK-FLOW THROUGH INLET</u>				
	Description	Advantages	Disadvantages	Examples
Baffle	<p>results in a reduction in ink pushed out through the inlet.</p> <p>One or more baffles are placed in the inlet ink flow. When the actuator is energized, the rapid ink movement creates eddies which restrict the flow through the inlet. The slower refill process is unrestricted, and does not result in eddies.</p>	<p>The refill rate is not as restricted as the long inlet method.</p> <p>Reduces crosstalk</p>	<p>Design complexity</p> <p>May increase fabrication complexity (e.g. Tektronix hot melt Piezoelectric print heads).</p>	<p>HP Thermal Ink Jet</p> <p>Tektronix piezoelectric ink jet</p>
Flexible flap restricts inlet	<p>In this method recently disclosed by Canon, the expanding actuator (bubble) pushes on a flexible flap that restricts the inlet.</p>	<p>Significantly reduces back-flow for edge-shooter thermal ink jet devices</p>	<p>Not applicable to most ink jet configurations</p> <p>Increased fabrication complexity</p> <p>Inelastic deformation of polymer flap results in creep over extended use</p>	<p>Canon</p>
Inlet filter	<p>A filter is located between the ink inlet and the nozzle chamber. The filter has a multitude of small holes or slots, restricting ink flow. The filter also removes particles which may block the nozzle.</p>	<p>Additional advantage of ink filtration</p> <p>Ink filter may be fabricated with no additional process steps</p>	<p>Restricts refill rate</p> <p>May result in complex construction</p>	<p>IJ04, IJ12, IJ24, IJ27, IJ29, IJ30</p>
Small inlet compared to nozzle	<p>The ink inlet channel to the nozzle chamber has a substantially smaller cross section than that of the nozzle, resulting in easier ink egress out of the nozzle than out of the inlet.</p>	<p>Design simplicity</p>	<p>Restricts refill rate</p> <p>May result in a relatively large chip area</p> <p>Only partially effective</p>	<p>IJ02, IJ37, IJ44</p>
Inlet shutter	<p>A secondary actuator controls the position of a shutter, closing off the ink inlet when the main actuator is energized.</p>	<p>Increases speed of the ink-jet print head operation</p>	<p>Requires separate refill actuator and drive circuit</p>	<p>IJ09</p>
The inlet is located behind the ink-pushing surface	<p>The method avoids the problem of inlet back-flow by arranging the ink-pushing surface of the actuator between the inlet and the nozzle.</p>	<p>Back-flow problem is eliminated</p>	<p>Requires careful design to minimize the negative pressure behind the paddle</p>	<p>IJ01, IJ03, IJ05, IJ06, IJ07, IJ10, IJ11, IJ14, IJ16, IJ22, IJ23, IJ25, IJ28, IJ31, IJ32, IJ33, IJ34, IJ35, IJ36, IJ39, IJ40, IJ41</p>
Part of the actuator moves to shut off the inlet	<p>The actuator and a wall of the ink chamber are arranged so that the motion of the actuator closes off the inlet.</p>	<p>Significant reductions in back-flow can be achieved</p> <p>Compact designs possible</p>	<p>Small increase in fabrication complexity</p>	<p>IJ07, IJ20, IJ26, IJ38</p>
Nozzle actuator does not result in ink back-flow	<p>In some configurations of ink jet, there is no expansion or movement of an actuator which may cause ink back-flow through the inlet.</p>	<p>Ink back-flow problem is eliminated</p>	<p>None related to ink back-flow on actuation</p>	<p>Silverbrook, EP 0771 658 A2 and related patent applications</p> <p>Valve-jet</p> <p>Tone-jet</p>

NOZZLE CLEARING METHOD

	Description	Advantages	Disadvantages	Examples
Normal nozzle firing	All of the nozzles are fired periodically, before the ink has a chance to dry. When not in use the nozzles are sealed (capped) against air. The nozzle firing is usually performed during a special clearing cycle, after first moving the print head to a cleaning station.	No added complexity on the print head	May not be sufficient to displace dried ink	Most ink jet systems I101, I102, I103, I104, I105, I106, I107, I109, I110, I111, I112, I114, I116, I120, I122, I123, I124, I125, I126, I127, I128, I129, I130, I131, I132, I133, I134, I136, I137, I138, I139, I140,, I141, I142, I143, I144,, I145
Extra power to ink heater	In systems which heat the ink, but do not boil it under normal situations, nozzle clearing can be achieved by over-powering the heater and boiling ink at the nozzle.	Can be highly effective if the heater is adjacent to the nozzle	Requires higher drive voltage for clearing May require larger drive transistors	Silverbrook, EP 0771 658 A2 and related patent applications
Rapid succession of actuator pulses	The actuator is fired in rapid succession. In some configurations, this may cause heat build-up at the nozzle which boils the ink, clearing the nozzle. In other situations, it may cause sufficient vibrations to dislodge clogged nozzles.	Does not require extra drive circuits on the print head Can be readily controlled and initiated by digital logic	Effectiveness depends substantially upon the configuration of the ink jet nozzle	May be used with: I101, I102, I103, I104, I105, I106, I107, I109, I110, I111, I114, I116, I120, I122, I123, I124, I125, I127, I128, I129, I130, I131, I132, I133, I134, I136, I137, I138, I139, I140, I141, I142, I143, I144, I145
Extra power to ink pushing actuator	Where an actuator is not normally driven to the limit of its motion, nozzle clearing may be assisted by providing an enhanced drive signal to the actuator.	A simple solution where applicable	Not suitable where there is a hard limit to actuator movement	May be used with: I103, I109, I116, I120, I123, I124, I125, I127, I129, I130, I131, I132, I139, I140, I141, I142, I143, I144, I145
Acoustic resonance	An ultrasonic wave is applied to the ink chamber. This wave is of an appropriate amplitude and frequency to cause sufficient force at the nozzle to clear blockages. This is easiest to achieve if the ultrasonic wave is at a resonant frequency of the ink cavity.	A high nozzle clearing capability can be achieved May be implemented at very low cost in systems which already include acoustic actuators	High implementation cost if system does not already include an acoustic actuator	I108, I113, I115, I117, I118, I119, I121
Nozzle clearing plate	A microfabricated plate is pushed against the nozzles. The plate has a post for every nozzle. A post moves through each nozzle, displacing dried ink.	Can clear severely clogged nozzles	Accurate mechanical alignment is required Moving parts are required There is risk of damage to the nozzles Accurate fabrication is required	Silverbrook, EP 0771 658 A2 and related patent applications
Ink pressure pulse	The pressure of the ink is temporarily increased so that ink streams from all of the nozzles. This may be used in conjunction	May be effective where other methods cannot be used	Requires pressure pump or other pressure actuator Expensive Wasteful of ink	May be used with all IJ series ink jets

-continued

NOZZLE CLEARING METHOD

	Description	Advantages	Disadvantages	Examples
Print head wiper	with actuator energizing. A flexible 'blade' is wiped across the print head surface. The blade is usually fabricated from a flexible polymer, e.g. rubber or synthetic elastomer.	Effective for planar print head surfaces Low cost	Difficult to use if print head surface is non-planar or very fragile Requires mechanical parts Blade can wear out in high volume print systems	Many ink jet systems
Separate ink boiling heater	A separate heater is provided at the nozzle although the normal drop e-jection mechanism does not require it. The heaters do not require individual drive circuits, as many nozzles can be cleared simultaneously, and no imaging is required.	Can be effective where other nozzle clearing methods cannot be used Can be implemented at no additional cost in some ink jet configurations	Fabrication complexity	Can be used with many IJ series ink jets

NOZZLE PLATE CONSTRUCTION

	Description	Advantages	Disadvantages	Examples
Electro-formed nickel	A nozzle plate is separately fabricated from electroformed nickel, and bonded to the print head chip.	Fabrication simplicity	High temperatures and pressures are required to bond nozzle plate Minimum thickness constraints Differential thermal expansion	Hewlett Packard Thermal Ink jet
Laser ablated or drilled polymer	Individual nozzle holes are ablated by an intense UV laser in a nozzle plate, which is typically a polymer such as polyimide or polysulphone	No masks required Can be quite fast Some control over nozzle profile is possible Equipment required is relatively low cost	Each hole must be individually formed Special equipment required Slow where there are many thousands of nozzles per print head May produce thin burrs at exit holes	Canon Bubblejet 1988 Sercel et al., SPIE, Vol. 998 Excimer Beam Applications, pp. 76-83 1993 Watanabe et al., U.S. Pat. No. 5,208,604
Silicon micro-machined	A separate nozzle plate is micromachined from single crystal silicon, and bonded to the print head wafer.	High accuracy is attainable	Two part construction High cost Requires precision alignment Nozzles may be clogged by adhesive	K. Bean, IEEE Transactions on Electron Devices, Vol. ED-25, No. 10, 1978, pp 1185-1195 Xerox 1990 Hawkins et al., U.S. Pat. No. 4,899,181
Glass capillaries	Fine glass capillaries are drawn from glass tubing. This method has been used for making individual nozzles, but is difficult to use for bulk manufacturing of print heads with thousands of nozzles.	No expensive equipment required Simple to make single nozzles	Very small nozzle sizes are difficult to form Not suited for mass production	1970 Zoltan U.S. Pat. No. 3,683,212
Monolithic, surface micro-machined using VLSI litho-	The nozzle plate is deposited as a layer using standard VLSI deposition techniques. Nozzles are etched in the nozzle plate using	High accuracy (<1 µm) Monolithic Low cost Existing processes can be used	Requires sacrificial layer under the nozzle plate to form the nozzle chamber Surface may be fragile to the touch	Silverbrook, EP 0771 658 A2 and related patent applications IJ01, IJ02, IJ04, IJ11, IJ12, IJ17,

-continued

NOZZLE PLATE CONSTRUCTION				
	Description	Advantages	Disadvantages	Examples
graphic processes	VLSI lithography and etching.			IJ18, IJ20, IJ22, IJ24, IJ27, IJ28, IJ29, IJ30, IJ31, IJ32, IJ33, IJ34, IJ36, IJ37, IJ38, IJ39, IJ40, IJ41, IJ42, IJ43, IJ44
Monolithic, etched through substrate	The nozzle plate is a buried etch stop in the wafer. Nozzle chambers are etched in the front of the wafer, and the wafer is thinned from the back side. Nozzles are then etched in the etch stop layer.	High accuracy (<1 μm) Monolithic Low cost No differential expansion	Requires long etch times Requires a support wafer	IJ03, IJ05, IJ06, IJ07, IJ08, IJ09, IJ10, IJ13, IJ14, IJ15, IJ16, IJ19, IJ21, IJ23, IJ25, IJ26
No nozzle plate	Various methods have been tried to eliminate the nozzles entirely, to prevent nozzle clogging. These include thermal bubble mechanisms and acoustic lens mechanisms	No nozzles to become clogged	Difficult to control drop position accurately Crosstalk problems	Ricoh 1995 Sekiya et al U.S. Pat. No. 5,412,413 1993 Hadimioglu et al EUP 550,192 1993 Elrod et al EUP 572,220
Trough	Each drop ejector has a trough through which a paddle moves, There is no nozzle plate.	Reduced manufacturing complexity Monolithic	Drop firing direction is sensitive to wicking.	IJ35
Nozzle slit instead of individual nozzles	The elimination of nozzle holes and replacement by a slit encompassing many actuator positions reduces nozzle clogging, but increases crosstalk due to ink surface waves	No nozzles to become clogged	Difficult to control drop position accurately Crosstalk problems	1989 Saito et al U.S. Pat. No. 4,799,068

DROP EJECTION DIRECTION

	Description	Advantages	Disadvantages	Examples
Edge ('edge shooter')	Ink flow is along the surface of the chip, and ink drops are ejected from the chip edge.	Simple construction No silicon etching required Good heat sinking via substrate Mechanically strong Ease of chip handling	Nozzles limited to edge High resolution is difficult Fast color printing requires one print head per color	Canon Bubblejet 1979 Endo et al GB patent 2,007,162 Xerox heater-in-pit 1990 Hawkins et al U.S. Pat. No. 4,899,181 Tone-jet
Surface ('roof shooter')	Ink flow is along the surface of the chip, and ink drops are ejected from the chip surface, normal to the plane of the chip.	No bulk silicon etching required Silicon can make an effective heat sink Mechanical strength	Maximum ink flow is severely restricted	Hewlett-Packard TIJ 1982 Vaught et al U.S. Pat. No. 4,490,728 IJ02, IJ11, IJ12, IJ20, IJ22
Through chip, forward ('up shooter')	Ink flow is through the chip, and ink drops are ejected from the front surface of the chip.	High ink flow Suitable for pagewidth print heads High nozzle packing density therefore low manufacturing cost	Requires bulk silicon etching	Silverbrook, EP 0771 658 A2 and related patent applications IJ04, IJ17, IJ18, IJ24, IJ27-IJ45

-continued

<u>DROP EJECTION DIRECTION</u>				
	Description	Advantages	Disadvantages	Examples
	Through chip, reverse ('down shooter')	Ink flow is through the chip, and ink drops are ejected from the rear surface of the chip.	High ink flow Suitable for pagewidth print heads High nozzle packing density therefore low manufacturing cost	Requires wafer thinning Requires special handling during manufacture IJ01, IJ03, IJ05, IJ06, IJ07, IJ08, IJ09, IJ10, IJ13, IJ14, IJ15, IJ16, IJ19, IJ21, IJ23, IJ25, IJ26
	Through actuator	Ink flow is through the actuator, which is not fabricated as part of the same substrate as the drive transistors.	Suitable for piezoelectric print heads Pagewidth print heads require several thousand connections to drive circuits Cannot be manufactured in standard CMOS fabs Complex assembly required	Epson Stylus Tektronix hot melt piezoelectric ink jets

<u>INK TYPE</u>				
	Description	Advantages	Disadvantages	Examples
	Aqueous, dye	Water based ink which typically contains: water, dye, surfactant, humectant, and biocide. Modern ink dyes have high water-fastness, light fastness	Environmentally friendly No odor	Slow drying Corrosive Bleeds on paper May strikethrough Cockles paper Most existing ink jets All IJ series ink jets Silverbrook, EP 0771 658 A2 and related patent applications
	Aqueous, pigment	Water based ink which typically contains: water, pigment, surfactant, humectant, and biocide. Pigments have an advantage in reduced bleed, wicking and strikethrough.	Environmentally friendly No odor Reduced bleed Reduced wicking Reduced strikethrough	Slow drying Corrosive Pigment may clog nozzles Pigment may clog actuator mechanisms Cockles paper IJ02, IJ04, IJ21, IJ26, IJ27, IJ30 Silverbrook, EP 0771 658 A2 and related patent applications Piezoelectric ink-jets Thermal ink jets (with significant restrictions) All IJ series ink jets
	Methyl Ethyl Ketone (MEK)	MEK is a highly volatile solvent used for industrial printing on difficult surfaces such as aluminum cans.	Very fast drying Prints on various substrates such as metals and plastics	Odorous Flammable
	Alcohol (ethanol, 2-butanol, and others)	Alcohol based inks can be used where the printer must operate at temperatures below the freezing point of water. An example of this is in-camera consumer photographic printing.	Fast drying Operates at sub-freezing temperatures Reduced paper cockle Low cost	Slight odor Flammable All IJ series ink jets
	Phase change (hot melt)	The ink is solid at room temperature, and is melted in the print head before jetting. Hot melt inks are usually wax based, with a melting point around 80° C. After jetting the ink freezes	No drying time-ink instantly freezes on the print medium Almost any print medium can be used No paper cockle occurs No wicking occurs No bleed occurs	High viscosity Printed ink typically has a 'waxy' feel Printed pages may 'block' Ink temperature may be above the curie point of permanent magnets Tektronix hot melt piezoelectric ink jets 1989 Nowak U.S. Pat. No. 4,820,346 All IJ series ink jets

-continued

<u>INK TYPE</u>				
	Description	Advantages	Disadvantages	Examples
	almost instantly upon contacting the print medium or a transfer roller.	No strikethrough occurs	Ink heaters consume power Long warm-up time	
Oil	Oil based inks are extensively used in offset printing. They have advantages in improved characteristics on paper (especially no wicking or cockle). Oil soluble dyes and pigments are required.	High solubility medium for some dyes Does not cockle paper Does not wick through paper	High viscosity: this is a significant limitation for use in ink jets, which usually require a low viscosity. Some short chain and multi-branched oils have a sufficiently low viscosity. Slow drying	All IJ series ink jets
Micro-emulsion	A microemulsion is a stable, self forming emulsion of oil, water, and surfactant. The characteristic drop size is less than 100 nm, and is determined by the preferred curvature of the surfactant.	Stops ink bleed High dye solubility Water, oil, and amphiphilic soluble dyes can be used Can stabilize pigment suspensions	Viscosity higher than water Cost is slightly higher than water based ink High surfactant concentration required (around 5%)	All IJ series ink jets

I claim:

1. A method of processing and printing an image captured 30
by a digital camera, said digital camera comprising a digital
image sensor means, self-contained processor means,
memory means, a flash and a 100 millimeter pagewidth inkjet
printhead connected to the processor means, said method of 35
processing and printing being performed within and by said
processor means of said digital camera and comprising the
steps of:
reading an algorithm encoded on a card inserted into said
camera;
using said algorithm, locating distortions of said captured 40
image due to the utilisation of said flash;

using said algorithm, retouching said image so as to locally
reduce the effect of said distortions to produce a
retouched image;
generating print data representing the retouched image;
and
selectively controlling 19,200 inkjet nozzles across the
pagewidth inkjet printhead to print the retouched image
using said print data.
2. A method as claimed in claim 1 wherein said locating
step comprises automatically locating faces within an image.
3. A method as claimed 1 wherein said distortions include
"red-eye" effects.

* * * * *