



US005947525A

United States Patent [19]
Pollman

[11] **Patent Number:** **5,947,525**
[45] **Date of Patent:** **Sep. 7, 1999**

[54] **INDEX DIVIDER LABEL APPLICATION AND ALIGNMENT KIT AND METHOD OF USING SAME**

[75] Inventor: **Russ Pollman**, Long Beach, Calif.

[73] Assignee: **Avery Dennison Corporation**,
Pasadena, Calif.

[21] Appl. No.: **08/844,093**

[22] Filed: **Apr. 18, 1997**

[51] **Int. Cl.⁶** **G09F 3/00; G09F 3/10**

[52] **U.S. Cl.** **283/36; 283/37; 283/38;**
283/39; 283/40; 283/41; 283/42; 402/79;
281/38; 40/359; 40/360

[58] **Field of Search** **283/36, 37, 38,**
283/39, 40, 41, 42; 402/79; 281/38; 40/359,
360

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,282,268	11/1966	Jacobs .	
3,807,069	4/1974	Daley	283/39
3,938,268	2/1976	Gilhula .	
4,329,191	5/1982	Barber .	
4,335,172	6/1982	Sato .	
4,445,711	5/1984	Cunningham .	
4,523,776	6/1985	Barber .	
4,832,374	5/1989	Prest, Jr. .	
4,927,179	5/1990	Ehret et al. .	
5,007,191	4/1991	Klein	402/79
5,039,131	8/1991	Scholtysik .	

5,129,682	7/1992	Ashby .	
5,143,466	9/1992	Baldwin et al. .	
5,182,152	1/1993	Ericson .	
5,243,173	9/1993	Dunn .	
5,271,642	12/1993	Jahier et al. .	
5,288,107	2/1994	Johnson et al. .	
5,330,230	7/1994	Craig .	
5,468,085	11/1995	Kline	283/37
5,503,435	4/1996	Kline .	
5,503,436	4/1996	Alpaugh et al. .	
5,543,191	8/1996	Dronzek, Jr. et al. .	
5,547,227	8/1996	Laurash et al. .	

Primary Examiner—Willmon Fridie, Jr.


Assistant Examiner—Mark T. Henderson




Attorney, Agent, or Firm—Oppenheimer Wolff & Donnelly
LLP

[57] **ABSTRACT**

An improved index divider label application kit that includes at least one set of divider sheets and at least one set of precut labels removably attached to carrier strips which are removably secured to a backing sheet. The divider sheets have outwardly extending tabs vertically offset from one another for receiving the precut labels. The precut labels are spaced apart on the carrier strips to align substantially with the tabs on the divider sheets. A user may (1) separate a carrier strip and precut labels affixed to that carrier strip from the backing sheet, (2) place and align the carrier strip across the divider sheets such that the precut labels are placed on the tabs of the divider sheets, and (3) pull the carrier strip upwardly and away from the divider sheets such that the precut labels separate from the carrier strip and remain on the divider tabs.

19 Claims, 3 Drawing Sheets








FIG. 4.




FIG. 5.




FIG. 6.

FIG. 7.




FIG. 8.





FIG. 10.





FIG. 11.



INDEX DIVIDER LABEL APPLICATION AND ALIGNMENT KIT AND METHOD OF USING SAME

TECHNICAL FIELD

The present invention relates in general to an improved index divider label application kit and a method of using same. The invention more particularly relates to a kit and method of using the kit for organizing and indexing documents where the kit includes index divider sheets and a pressure sensitive label sheet for facilitating the labeling of the divider sheets in a fast and efficient manner.

BACKGROUND ART

There have been many types and kinds of indexing and labeling systems to facilitate the organization of documents in a convenient manner. For example, reference may be made to the following U.S. Pat. Nos.: 3,282,268; 3,938,268; 4,329,191; 4,335,172; 4,445,711; 4,523,776; 4,832,374; 4,927,179; 5,039,131; 5,129,682; 5,143,466; 5,182,152; 5,243,173; 5,271,642; 5,288,107; 5,330,230; 5,468,085; 5,503,435; 5,503,436; 5,543,191; and 5,547,227.

As disclosed in the foregoing mentioned patents, various systems for indexing documents utilizing dividers and labels are available. More particularly, groups of documents are separated by divider sheets to help identify the types and kinds of documents. To help a user locate the type or kind of document distinguished by a given divider, dividers include outwardly extending tabs where the tabs of the individual dividers are vertically offset from one another and include indicia for helping a user to locate and organize documents.

While such systems may have been satisfactory for helping to index groups of documents, the task of applying identifying indicia or identifying labels to the divider tabs is time consuming, clumsy and subject to error. In this regard, applying indicia to individual tabs has been difficult, and thus, tab attachable labels have been employed to help overcome such difficulties. Even though the use of attachable labels may have permitted the divider tabs to have identifying indicia, such labels have not been convenient to use, as such labels must be separated from one another and then attached individually to corresponding ones of the divider tabs. Further, in the course of individually applying the labels, they are often not applied evenly, or properly aligned with the divider sheet tabs.

Therefore it would be highly desirable to have a new and improved index divider label application kit and method of using the kit to facilitate the application of tab labels in a fast, efficient, and accurately aligned manner. Such a new and improved kit and method should enable a user to apply all of the divider tab labels substantially simultaneously.

DISCLOSURE OF INVENTION

Therefore, the principal object of the present invention is to provide a new and improved index divider label application kit and method of using same, wherein all of the divider tab labels for a given set of dividers can be applied substantially simultaneously, and with the labels accurately aligned with the dividers.

Briefly, the above and further objects of the present invention are realized by providing a new and improved index divider label application kit which can be utilized to separate and help identify groups of different types and kinds of documents according to a novel label application method of the present invention.

The index divider label application kit includes at least one set of precut, pressure sensitive divider tab labels disposed on a backing sheet and at least one set of divider sheets, each having outwardly extending tabs vertically offset from one another for receiving the divider tab labels. The labels are spaced from one another in the same offset manner as the divider tabs and the labels are attached removably to a precut strip that is secured removably to the backing sheet. A set of ties hold the pre-cut labels to the strip.

According to the novel method of label application, the precut strip is pulled from the backing sheet, along with the offset labels. The strip with labels is then aligned over a set of stacked dividers so that the labels and divider tabs are in corresponding alignment with one another. The strip is then laid in engagement with the top divider and then, using finger pressure, each label is pressed into engagement with its corresponding tab. The strip is then pulled away from the divider sheets, hesitating slightly at each tie allowing the ties to tear, leaving each label perfectly positioned on and aligned with its corresponding tab.

BRIEF DESCRIPTION OF DRAWINGS

The above-mentioned and other objects and features of this invention and manner of attaining them will become apparent, and the invention itself will be best understood by reference to the following description of the embodiments of the invention taken in conjunction with the accompanying drawings, wherein:

FIG. 1 is a pictorial view of an index divider label application and alignment kit, which is constructed in accordance with the present invention;

FIG. 2 is a front elevational view of a pressure sensitive label sheet forming part of the kit of FIG. 1;

FIG. 3 is a fragmentary cross-sectional view of the label sheet of FIG. 2 taken along line 3—3 of FIG. 2;

FIG. 4 is an enlarged fragmentary pictorial view of a partially removed frame strip forming part of label sheet of FIGS. 2 and 3;

FIG. 5 is a fragmentary pictorial view of an applied set of labels being separated from the frame strip shown in FIG. 4;

FIG. 6 is a fragmentary front plan view of another pressure sensitive label sheet forming part of the kit of FIG. 1;

FIG. 7 is a fragmentary pictorial view of a another embodiment of transparent label with adhesive material on labels only;

FIG. 8 is a fragmentary cross-sectional view of the label sheet of FIG. 7 taken along line 8—8 thereof;

FIG. 9 is a greatly enlarged view of a precut label forming part of the frame strip of FIG. 4;

FIG. 10 is a greatly enlarged view of a precut label forming part of the base strip of FIG. 6; and

FIG. 11 is a greatly enlarged view of a precut label forming part of the frame strip of FIG. 7.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Referring now to the drawings, and more particularly to FIG. 1 thereof, there is shown an index divider label application kit 10 which is constructed in accordance with the present invention. The kit 10 can be utilized to facilitate the application of a set of divider tab labels to a set of divider tabs in a fast and efficient manner in accordance with the label application method of the present invention.

The kit **10** generally comprises a set of dividers **12** for helping to separate groups of different types and kinds of documents (not shown), and a pressure sensitive label sheet **14** having a set of transparent labels **16** mounted removably thereon.

The kit **10** also includes a pressure sensitive label sheet **18** having a set of opaque labels **20** mounted removably thereon. For purposes of displaying and marketing the kit **10**, the set of dividers **12** and the pressure sensitive label sheets **14** and **18** are enclosed in a product package **22** that includes an eye-catching design (not shown) on its front face.

The set of dividers **12** includes five individual divider sheets, such as divider sheets **30-34** (see FIG. **5**), for use in separating the groups of different types and kinds of documents. In the preferred embodiment of the present invention, the divider sheets **30-34** are each about 8.5 inches in width and about 11.0 inches in length and each includes outwardly extending tabs, such as the tabs **35-39** that are vertically offset from one another along the vertical axis of the dividers **30-34**. The divider tabs **35-39** each extend outwardly from the perimeter of their respective dividers **30-34** by about 0.5 inches and each tab is about 2.0 inches in length.

Although in the preferred embodiment of the present invention a set of five divider sheets and two different types of label sheets is disclosed, divider sheets and label sheets of greater and lesser amount are contemplated within the true scope and spirit of the present invention. Accordingly, the number of divider sheets and label sheets within the kit may be in any combination between two and twenty sheets.

The pressure sensitive label sheet **14** may be dimensioned to about the same dimensions of an individual one of the divider sheets, such as the divider sheet **30**. In this regard, the label sheet **14** is about 8.5 inches in width and about 11.0 inches in length.

As best seen in FIG. **3**, the label sheet **14** is multi-layered having a backing sheet **40** and a face sheet **42**. A pressure sensitive layer of adhesive material **44** is disposed on a bottom face **46** of the face sheet **42** for removably securing together the backing sheet **40** and the face sheet **42**. As is customary, a very thin release coating of material **41**, such as a silicone coated material, may be applied to the backing sheet **40**, to facilitate removal of the labels and associated label strips.

In order to facilitate the application of the labels to the divider sheets **30-34**, the face sheet **42** is divided into a plurality of frame or label carrier strips, such as the frame strips **50-53** (FIG. **2**). The face sheet **42** is die cut into strip segments by face sheet cut lines **60-67** that extend or traverse the entire longitudinal length of the face sheet **42**. Although the face sheet **42** is cut into strips **50-53**, those skilled in the art will understand that the face sheet **42** remains secured to the backing sheet **40** due to the pressure sensitive adhesive material **44**.

In this manner, the strips **50-53** remain in contact with the backing sheet **40** until individual ones of the strips, such as the strip **50**, is grasped at one of its terminal ends, such as the terminal end **54**, and pulled upwardly and laterally away from the backing sheet **40** until it is completely separated from the backing sheet **40** and the remaining portion or portions of the face sheet **42**.

As each of the frame strips **50-53** are substantially identical, only frame strip **50** will be described in greater detail.

Considering now the frame strip **50** in greater detail with reference to FIGS. **2-4**, the set of labels **16** includes five

equally spaced apart like dimensioned transparent labels **55-59**. As will be explained hereinafter in greater detail, each of the labels **55-59** are precut to a rectangular dimension that corresponds to about the same rectangular dimension as an individual one of the divider tabs, such as the divider tab **35**. The precut labels **55-59** are held or secured removably to the face sheet **42** by a plurality of ties areas **80-83** that will be described hereinafter in greater detail.

Considering now the method of using the index divider label application kit **10** in greater detail with reference to FIGS. **1-5**, the product package **22** is opened and the set of dividers **12** and the set of pressure sensitive label sheets **14** and **18** are removed therefrom.

Next the divider sheets **30-34** are stacked one on top of the other to form a stack, such as a stack **19** (FIG. **5**). While forming the stack **19**, the user simultaneously aligns the divider sheets **30-34**, so their respective tabs **35-39** are aligned spaced apart from one another along a common longitudinal axis (L) of the dividers **30-34** and in a series of closely spaced apart parallel planes. Each parallel plane being defined by the thickness of a corresponding one of the dividers.

The parallel planes are closely spaced relative to one another, so that the vertical distance between the top plane and the bottom plane is considered insignificant for the purposes of alignment as will be described hereinafter in greater detail.

The user then selects a desired one of the pressure sensitive label sheets **14** and **18** based upon whether the user desires to utilize transparent labels, such as the transparent labels **16**, or opaque labels, such as the opaque labels **20**. Appropriate indexing information is then typed or computer printed onto the individual labels.

Once the user selects for example, the pressure sensitive label sheet **14**, the user grasps one of the frame strips of the label sheet **14**, such as the frame strip **50**, and pulls its terminal end **54** upwardly and laterally away from the backing sheet **40**, as best seen in FIG. **4**, until the frame strip **50** is completely separated from the backing sheet **40**.

The frame strip **50**, with its associated set of attached labels **55-59**, is then moved into alignment over the stack **19** relative to its associated divider tabs **35-39** and then down onto the stack **19** of aligned divider sheets **30-34** while aligning the labels **55-59** with respective ones of the divider tabs **35-39**. The frame strip **50** functions as a long lever arm that helps the user gauge parallelism to tab edges visually so that alignment of the labels **55-59** on the divider tabs **35-39** is greatly improved relative to applying labels one by one as accomplished under prior art methods of attachment and alignment.

When the labels **55-59** are resting in engagement with respective ones of the divider tabs **35-39**, the user engages the top surface of each label with his or her finger, and using finger pressure, presses each label into engagement with it associated divider tab. The finger pressure is sufficient to cause that portion of the pressure sensitive layer of adhesive material **44** disposed on the bottom face **46** of the label to securely fasten the label to its associated divider tab.

As best seen in FIG. **5**, once each label has been secured to a corresponding one of the divider tabs, the user again grasps the terminal end **54** of the frame strip **50** and pulls it upwardly and away from the stack **19** hesitating at each label for a slight moment to allow the pulling force to tear the label ties associated with each label. In this manner, each of the labels **55-59** are successively affixed to their respective divider tabs **35-39** in a substantially continuous manner.

After the labels **55–59** have been secured to the divider **30–34**, the dividers **30–34**, may be secured in a notebook (not shown) or other means for holding dividers and documents and utilized to separate the different types and kinds of documents to be carried in the notebook.

Although in the preferred embodiment of the present invention the label indicia may be typed or printed, it is contemplated that labels may also be preprinted with desired indexing information. As is customary, a very thin transparent coating of an indicia holding material may be applied to the face surface of the labels to facilitate preprinting with desired indexing information.

Considering now the frame strip **50** in still greater detail with reference to FIGS. **2** and **3**, each of the labels **55–59** affixed to the strip **50** are substantially identical. Accordingly, only the label **55** will be described hereinafter in greater detail. In this regard, the reference characters mentioned with respect to label **55** apply to each individual one of the label **56–59**.

As best seen in FIG. **2**, the transparent label **55** is defined by a plurality of label die cut lines **70–77** that are arranged in the strip **50** to form a generally rectangularly shaped label configuration.

In order to hold or secure the label configuration to carrier strip **50**, the label **55** is further defined by a set of vertically and horizontally spaced apart tie area **80–83**. The tie areas **80–83** affix the label **55** to the strip **50**.

The ties **80–83** are small uncut sheet material areas that help couple the cut lines **70–77** into the rectangularly shaped label configuration. In this regard, the tie **80** interconnects the cut lines **71** and **72**; the tie **81** interconnects the cut lines **72** and **73**; the tie **82** interconnects the cut lines **75** and **76**; and the tie **83** interconnects the cut lines **76** and **77**.

In order to assure that the label **55** will be separated from the strip **50**, the ties **80** and **83** are inset from the cut line **70** by about 0.125 inches each while the ties **81** and **82** are inset from the cut line **74** by the same distance of about 0.125 inches.

From the foregoing, those skilled in the art will understand that the small uncut tie areas **80–83** secure the label **55** to the strip **50** with a sufficient amount of force to prevent the label **55** from separating from the strip **50** when it is pulled away and separated from the backing sheet **40**, but such uncut tie areas do not secure the label **55** to the strip **50** with a sufficient amount of force to prevent the label from separating from the strip **50** when its is pulled away from the stack **19**. More particularly, those skilled in the art will understand that the finger pressure of the user utilized to secure the label **55** to the tab divider **35** causes the adhesive material **44** to grip the tab divider **35** with a greater amount of force than the face sheet **42** and its associated strips **50–54**. This difference in hold strength is attributed to the fact that the backing sheet **40** has a very thin release coating **41** disposed thereon.

In order to help facilitate proper placement of the label **55** on its associated tab divider **35**, the label **55** is about 0.375 inches tall and about 1.50 inches wide. Thus, the label **55** will fit within the tab divider area which is 0.5 inches by 2.0 inches.

Considering now the pressure sensitive label sheet **14** in still greater detail with reference to FIGS. **2–4**, the backing sheet **40** and the face sheet **42** each have a horizontal dimension (H) and a vertical dimension (V) that corresponds substantially to the horizontal dimension (h) and the vertical dimension (v) of an individual one of the dividers, such as the divider **35**. In this regard, the horizontal dimension (H) is about 8.5 inches, while the vertical dimension (V) is about 11.0 inches.

Considering now the pressure sensitive label sheet **18** in greater detail with reference to FIG. **6**, the label sheet **18** is substantially identical to the label sheet **14** except for the location of the adhesive material and the arrangement of its cut lines.

As been seen in FIG. **6**, the set of opaque labels **20** includes five spaced apart labels **85–89** that are substantially identical in shape to labels **55–59**. The label sheet **18** is divided into a plurality of base or carrier strips, such as a base strip **90** where each of the labels **85–89** carried thereon are connected in series. In this regard, the base strip **90** includes a plurality of base cut lines **91–94** that interconnect the labels **85–89** in series.

For example, the base cut line **91** extends between the labels **85** and **86**; the base cut line **92** extends between the labels **86** and **87**; the base cut line **93** extends between the labels **87** and **88**; and the base cut line **94** extends between the labels **88** and **89**.

A pair of outer base cut lines **95** and **96** respectively, help extend the series connection to the outer periphery of the strip. In this regard, the base cut line **95** extends between the label **85** with an outer perimeter side **78** of the label sheet **18** to facilitate the complete separation of the label **85** from the sheet **18**. In a like manner, the series extends to an opposite outer perimeter side **79** of the label sheet **18** by the base cut line **96** to facilitate the complete separation of the label **89** from the sheet **18**. The base strip **90** holds the labels **85–89** in alignment as they are applied to the index tabs in a manner similar to the showing of FIG. **5**.

A lesser number of ties hold each of the labels **85–89** to the base strip **90**. In this regard for example, a pair of ties **97** and **98** hold the label **85** to the base strip **90**.

Although in the preferred embodiment of the present invention the ties are shown in offset pairs, such as the tie pair **97** and **98**, it is contemplated that ties may be arranged in other configurations for holding labels to carrier sheets. For example as best seen in FIGS. **7**, **8**, and **11**, a label **101** is held to a precut die strip **100** by a set of ties **126–127** that are centrally disposed on each end of the label **101**.

As best seen in FIG. **8**, a pressure sensitive layer of adhesive material **102** is disposed on only the bottom face of each of the strip labels, such as the label **101**.

From the foregoing, it should be understood by those skilled in the art that while specific tie configurations have been illustrated, different configurations of ties are contemplated within the true spirit and scope of the present invention.

While particular embodiments of the present invention have been disclosed, it is to be understood that various different modifications are possible and are contemplated within the true spirit and scope of the appended claims. For example, the divider sheets **30–35** are described as having divider tabs that extend along the longitudinal axis of the divider. It is contemplated within the true spirit and scope of the embodiments that the divider tabs could extend outwardly along the transverse axis of the divider. Accordingly, the configuration of the sheets **14** and **18** would need to be modified to accommodate the different divider configuration. Thus, there is no intention, therefore, of limitations to the exact abstract or disclosure herein presented.

I claim:

1. An index divider label application kit, comprising:
at least one set of divider sheets, each having outwardly divider tabs vertically offset from one another in a predetermined arrangement when said divider sheets overlay one another;

at least one carrier type pressure sensitive label sheet having a backing sheet and a face sheet secure removably together by a layer of pressure sensitive adhesive material;

said face sheet including a plurality of spaced apart carrier strips each secured removably to said backing sheet and to said face sheet;

each of said carrier strips includes a plurality of spaced apart precut labels aligned in an alignment configuration that corresponds substantially to said predetermined arrangement of the divider tabs extending outward from said divider sheets such that when each of said carrier strips overlies said divider tabs on said set of divider sheets, each of said precut labels is located on top of a respective divider tab; and

said precut labels being affixed to said carrier strips such that said labels do not tear from said carrier strips when said carrier strips are separated from said backing sheet and said face sheet;

whereby a user may (1) separate a carrier strip and precut labels affixed to that carrier strip from the backing sheet and the face sheet, (2) place and align the carrier strip across the divider sheets such that the precut labels affixed to the carrier strip are placed on the divider tabs of the divider sheets, and (3) pull the carrier strip upwardly and away from the divider sheets such that the precut labels tear from the carrier strip and remain on the divider tabs.

2. An index divider label application kit according to claim 1, further comprising:

at least one base type pressure sensitive label sheet having a plurality of spaced apart base strips, wherein each base strip includes a plurality of spaced apart precut labels affixed to the base strip and interconnected in series along an imaginary base line extending the entire vertical dimension of the base strip, said imaginary base line being defined in part by a plurality of spaced apart base cut lines for helping to facilitate separation of the spaced apart precut labels from the base strip.

3. A label sheet, comprising:

a backing sheet having a thin coating of a releasing agent disposed on the front face thereof;

a face sheet removably affixed to said front face of the backing sheet in an overlying aligned manner, said face sheet having at least one set of precut pressure sensitive divider tab labels affixed removably thereto;

said divider tab labels being spaced part from one another in an offset manner that substantially corresponds to a set of vertically offset divider sheet tabs extending outwardly from a stacked group of divider sheets having a predefined arrangement of divider tabs;

a plurality of small area ties affixed to each individual divider tab label, each individual tie and divider tab label having a sufficient amount of pressure sensitive adhesive material coated on a bottom surface thereof to substantially prevent label divider tab separation as said divider tab labels are separated from said face sheet and applied to said set of vertically offset divider sheet tabs in a substantially continuous manner; and

said face sheet includes a plurality of spaced apart face sheet die cut lines for separating said face sheet into a plurality of precut carrier strips.

4. A label sheet according to claim 3, wherein each individual precut carrier strip carries one set of precut pressure sensitive divider tab labels.

5. A label sheet according to claim 4, wherein each individual precut carrier strip is a frame strip.

6. A label sheet according to claim 4, wherein each individual precut carrier strip is a base strip.

7. A label sheet according to claim 3, wherein each individual divider tab label is transparent.

8. A label sheet according to claim 3, wherein each individual divider tab label is opaque.

9. A label sheet according to claim 3, wherein said face sheet has a thin coating of a pressure sensitive adhesive material on a bottom face thereof for removably securing together the backing sheet and the face sheet.

10. A label sheet according to claim 9, wherein said face sheet includes a plurality of spaced apart face sheet die cut lines for separating said face sheet into a plurality of precut carrier strips;

each individual one of said plurality of spaced apart carrier strips including a plurality of spaced apart precut labels aligned in an alignment configuration that corresponds substantially to the offset spacings of the vertically offset divider sheet tabs extending outwardly from said group of divider sheets; and

each of said precut labels being affixed to its associated carrier strip by a set of said plurality of small area ties, said small area ties being sufficiently strong not to tear from the carrier strip when it is pulled upwardly and away from said backing sheet for separating the strip from both the backing sheet and the face sheet, but not sufficiently strong to prevent tearing from the carrier strip when the labels are pressed into engagement with individual ones of the divider tabs and the carrier strip is then pulled upwardly and away from the divider tabs.

11. A label sheet according to claim 9, wherein each precut label is defined partially by a set of label cut lines that are extended along a long axis of an associated label by horizontally and vertically spaced apart pair sets of the area ties.

12. A label sheet according to claim 9, wherein each precut label is defined by a set of spaced apart horizontal cut lines and a set of spaced apart vertical cut lines, each horizontal set of cut lines being interconnected by a pair of area ties.

13. A label sheet according to claim 12, wherein each precut label is generally rectangular in shape.

14. A label sheet according to claim 13, wherein said backing sheet has a horizontal dimension (H) and a vertical dimension (V), said vertical dimension (V) corresponding substantially to a vertical dimension (v) along which said successive tabs extend, on an individual one of the divider sheets in the set of divider sheets; and

wherein said backing sheet and said face sheet have substantially the same horizontal and vertical dimensions.

15. A label sheet according to claim 14, wherein the horizontal dimension (H) of said backing sheet is about 8.5 inches and the vertical dimension (V) of said backing sheet is about 11.0 inches.

16. A label sheet according to claim 3, wherein said area ties are arranged in pairs of area ties, each pair of area ties affixing one of the divider tab labels to said face sheet.

17. A label sheet according to claim 16, wherein each of said divider tab labels has a generally rectangular shape defined by sets of parallel die cut lines.

18. A label sheet according to claim 17, wherein each pair of ties are inset from at least one set of the parallel die cut lines helping to define the rectangular shape.

19. A method of applying a set of precut labels to a corresponding set of offset divider tabs extending outwardly from divider sheets, comprising:

9

stacking the divider sheets in alignment with their divider tabs extending spaced apart along a single common axis of the divider sheets;

using a pressure sensitive label sheet having a backing sheet and a face sheet secured removably together by a layer of pressure sensitive adhesive material;

said face sheet including a plurality of spaced apart carrier strips each secured removably to said backing sheet and to face sheet;

each of said spaced apart carrier strips including a plurality of spaced apart divider tab labels aligned in an alignment spacing configuration that corresponds substantially to the offset spacings of the divider tabs extending outwardly from said set divider sheets;

each of said divider tab labels being affixed to its associated carrier strip by a plurality of small area ties;

grasping a terminal end of a user selected individual one of said plurality of carrier strips;

pulling the grasped carrier strip upwardly and away from said backing strip a sufficient distance to separate the

10

carrier strip from the remaining portion of the face sheet attached to said backing sheet;

aligning the separated carrier strip over the stacked divider sheets;

bringing the carrier strip into engagement with the divider tabs of the stacked divider sheets so that each of said divider tab labels is in substantial alignment with a corresponding individual one of the divider tabs;

pressing said divider tab labels into engagement with their corresponding divider tabs with a sufficient finger pressure to assure said divider tab labels are affixed to the divider tab; and

pulling the carrier strip upwardly and away from the stacked dividers a sufficient distance to separate said divider tab labels substantially simultaneously from the carrier strip and leaving the labels secured to the divider tabs.

* * * * *