

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date
30 May 2014 (30.05.2014)

(10) International Publication Number
WO 2014/079052 A1

(51) International Patent Classification:
H04W 24/08 (2009.01)

(74) Agent: CHINA PATENT AGENT (HK) LTD, 22/F., Great Eagle Center, 23 Harbour Road, Wanchai, Hong Kong (CN).

(21) International Application Number:

PCT/CN2012/085238

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:

26 November 2012 (26.11.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET L M ERICSSON (PUBL) [SE/SE]; S-164 83 Stockholm (SE).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(71) Applicants (for US only): LI, Shaohua [CN/CN]; B83-1-502, Lingxiuxingguigu, Xierqi, Haidian district, Beijing 100085 (CN). GUO, Zhiheng [CN/CN]; No. 5 Lize East Street, Chaoyang district, Beijing 100102 (CN). LIU, Jin-hua [CN/CN]; Room 5-201, Building 113, Nanhuzhongyuan Yiqu, Chaoyang District, Beijing 100102 (CN). SONG, Xinghua [CN/CN]; Ericsson Tower, No. 5 Lize East Street, Chaoyang District, Beijing 100102 (CN). ZHANG, Zhan [CN/CN]; Ericsson Tower, No. 5, Lize East Street, Chaoyang District, Beijing 100102 (CN).

Published:

— with international search report (Art. 21(3))

(54) Title: METHODS AND RADIO NETWORK NODES FOR MEASURING INTERFERENCE




Fig. 2

(57) Abstract: A first radio network node (110) and a method therein for measuring interference as well as a second radio network node (120) and a method therein for enabling the first radio network node to measure interference are disclosed. The first radio network node (110) obtains (201) configuration information for indicating a designated subframe in which a reference signal for measurement of the interference is to be transmitted by the second radio network node (120). The second radio network node (120) obtains (202) configuration information for configuring a designed subframe for transmission of a reference signal. The first radio network node (110) receives (205), in the designated subframe indicated by the configuration information, the reference signal transmitted by the second radio network node (120). The first radio network node (110) determines (206) a value of the interference based on the reference signal.

METHODS AND RADIO NETWORK NODES FOR MEASURING INTERFERENCE

TECHNICAL FIELD

The present invention relates generally to radio communication systems, such 5 as telecommunication systems, and particularly to a first radio network node and a method therein for measuring interference as well as a second radio network node, and a method therein for enabling the first radio network node to measure interference.

10 BACKGROUND

Time Division Duplex (TDD) is flexible in terms of possibility to adapt time resources between uplink and downlink transmissions, i.e. between number of uplink and downlink subframes. By dynamically changing a ratio between the number of subframes for uplink and downlink, respectively, such as to match the instantaneous 15 traffic situation, performance experienced by an end-user may be improved. The ratio between uplink/downlink subframes is determined by an uplink/downlink (UL/DL) configuration, referred to as TDD configuration hereinafter, of a radio base station.

Another benefit of dynamic TDD is network energy savings, i.e. an improvement of downlink resource utilization allows a radio base station, such as an 20 evolved Node B (eNB), to configure DL subframes more efficiently so that energy savings may be achieved.

A heterogeneous network may typically comprise macro nodes and micro nodes. The macro nodes have a higher transmit power than the micro nodes. In general, it is not preferable to change the TDD configuration for the macro nodes, at 25 least not on a small time scale. However, for heterogeneous networks, it may be that only a few user equipments (UEs) are active simultaneously per micro node, which implies a high possibility that many neighbouring nodes, or cells, are momentarily empty. The traffic dynamics are expected to be large with relatively low average load, but high instantaneous data rates. In this case, the traffic asymmetry between uplink 30 and downlink directions may become a significant. Therefore, dynamic TDD configuration becomes attractive.

When the neighbouring nodes are configured with different TDD configurations, interference between UL and DL including both eNB-to-eNB (DL-to-UL) and UE-to-UE (UL-to-DL) interference needs to be considered. The cross-link

interference should be either mitigated or avoided so that the benefit of dynamic TDD could be achieved.

In scenarios of dynamic uplink and downlink (UL/DL) allocation in a TDD cellular system, different neighbouring eNBs will use different TDD configurations from time to time. As an example, a certain cell could become an 'aggressor cell', which uses a configuration different from a neighbouring 'victim cell'. For instance, in a specific subframe, there is a DL subframe of the aggressor cell, while in the same specific subframe, there is a UL subframe for the victim cell. Hence, in the specific subframe, the uplink of victim cell will be interfered by eNB-to-eNB interference from the aggressor cell. A problem is, hence, how to measure and estimate the eNB-to-eNB interference.

SUMMARY

One object of the solution described herein is to measure interference between radio network nodes in a radio communication system.

According to one aspect, the object is achieved by a method in a first radio network node for measuring interference between the first radio network node and a second radio network node. The first radio network node obtains configuration information for indicating a designated subframe in which a reference signal for measurement of the interference is to be transmitted by the second radio network node. The designated subframe is designated for enabling measurement of the interference. The first radio network node receives, from the second radio network node in the designated subframe indicated by the configuration information, the reference signal. The first radio network node determines a value of the interference based on the reference signal.

According to another aspect, the object is achieved by a first radio network node configured to measure interference between the first radio network node and a second radio network node. The first radio network node comprises a processing circuit configured to obtain configuration information for indicating a designated subframe in which a reference signal for measurement of the interference is to be transmitted by the second radio network node. The designated subframe is designated for enabling measurement of the interference. Furthermore, the processing circuit is configured to receive, from the second radio network node in the designated subframe indicated by the configuration information, the reference signal.

Moreover, the processing circuit is configured to determine a value of the interference based on the reference signal.

According to a further aspect, the object is achieved by a method in a second radio network node for enabling a first radio network node to measure interference between the first radio network node and the second radio network node. The second radio network node obtains configuration information for configuring a designed subframe for transmission of a reference signal, the designated subframe being designated for enabling the first radio network node to measure the interference. The second radio network node sends, in the designated subframe, the reference signal to the first radio network node.

According to a still further aspect, the object is achieved by a second radio network node configured to enable a first radio network node to measure interference between the first radio network node and the second radio network node. The second radio network node comprises a processing circuit configured to obtain configuration information for configuring a designed subframe for transmission of a reference signal. The designated subframe is designated for enabling the first radio network node to measure the interference. Furthermore, the processing circuit is configured to send, in the designated subframe, the reference signal to the first radio network node.

Since both the first and second radio network nodes obtain the configuration information, the first and second radio network nodes are aligned, e.g. in time and/or frequency, with regard to when interference measurement by the first radio network node may be performed.

Then, the first radio network node receives, in the designated subframe, the reference signal from the second radio network node. The designated subframe may be a flexible uplink/downlink subframe, a special subframe or the like. The special subframe is known from 3GPP terminology.

Based on the reference signal, the first radio network node determines a value of the interference between the first and second radio network nodes. Hence, in this example, a measurement of the interference is performed by obtaining the configuration information, receiving the reference signal and determining the value of the interference. As a result, the above mentioned object is achieved.

Advantageously, no or little coordination between the first and second radio network nodes is required.

Moreover, embodiments herein beneficially provide means for measuring interference caused by different TDD configurations.

5 As a further advantage, the embodiments herein may be implemented while having a negligible impact on Hybrid Automatic Repeat reQuest (HARQ) timing.

Furthermore, embodiments herein enable accurate eNB-to-eNB interference measurements to support any eNB-to-eNB interference management scheme, such as Inter-Cell Interference Cancellation (ICIC) or the like.

10 Additionally, embodiments herein may for example be implemented within current and/or future 3GPP specifications.

BRIEF DESCRIPTION OF THE DRAWINGS

The various aspects of the embodiments disclosed herein, including particular features and advantages thereof, will be readily understood from the following 15 detailed description and the accompanying drawings, in which:

Figure 1 is a schematic block diagram illustrating embodiments in an exemplifying radio communication system,

20 Figure 2 is a combined signaling scheme and flowchart illustrating embodiments of the methods,

Figure 3 is a table illustrating an aggressor cell and a victim cell,

Figure 4 is a table illustrating exemplifying TDD configurations,

Figure 5 is a table illustrating exemplifying TDD configurations,

25 Figure 6 is a table illustrating exemplifying TDD configurations,

Figure 7 is a block diagram illustrating an exemplifying designated subframe,

Figure 8 is a block diagram illustrating an exemplifying designated subframe,

Figure 9 is a flowchart illustrating embodiments of the method in the first radio network node,

30 Figure 10 is a block diagram illustrating embodiments of the first radio network node,

Figure 11 is a flowchart illustrating embodiments of the method in the second radio network node, and

35 Figure 12 is a block diagram illustrating embodiments of the second radio network node.

DETAILED DESCRIPTION

Throughout the following description similar reference numerals have been used to denote similar elements, network nodes, parts, items or features, when applicable. In the Figures, features that appear in some embodiments are indicated 5 by dashed lines.

Figure 1 depicts an exemplifying **radio communications system 100** in which embodiments herein may be implemented. In this example, the radio communications system 100 is a Long Term Evolution (LTE) system. In other 10 examples, the radio communication system may be any wireless system including those based on 3GPP cellular communication systems, such as a Wideband Code Division Multiple Access (WCDMA) network, a Global System for Mobile communication (GSM network), IEEE 802.16 family of wireless-networks standards, Worldwide Interoperability for Microwave Access (WiMAX), Wireless Local Network 15 (WLAN) or the like.

The radio communication system 100 comprises a **first radio network node 110** and a **second radio network node 120**. As used herein, the term “radio network node” may refer to an evolved Node B (eNB), a control node controlling one or more 20 Remote Radio Units (RRUs), a radio base station, an access point, a relay or the like. The second radio network node 120 is configured to **send 130** a reference signal to the first radio network node 110.

In this example, the first radio network node 110 is configured to operate in time division duplex mode. In other examples, the first radio network node 110 may 25 be configured to operate in frequency division duplex mode or in a combined time/frequency duplex mode.

In this example, the second radio network node 120 is configured to operate in time division duplex mode. In other examples, the second radio network node 120 may be configured to operate in frequency division duplex mode or in a combined 30 time/frequency duplex mode.

The first radio network node 110 may operate a first cell, such as a macro cell, and the second radio network node 120 may operate a second cell, such as a pico or micro cell. More generally, the first and second cells may be comprised in the radio communication system 100. In some examples, the first and second cells are 35 comprised in a heterogeneous network comprised in the radio communication system 100.

Furthermore, a **user equipment 140** is served by the first radio network node 110. Expressed differently, the user equipment 140 may be associated with the first cell. The user equipment 131 may **transmit 150** a transmission to the first radio network node 110. As used herein, the term “user equipment” may refer to a mobile phone, a cellular phone, a Personal Digital Assistant (PDA) equipped with radio communication capabilities, a smartphone, a laptop or personal computer (PC) equipped with an internal or external mobile broadband modem, a tablet PC with radio communication capabilities, a portable electronic radio communication device, a sensor device equipped with radio communication capabilities or the like. The sensor may be any kind of weather sensor, such as wind, temperature, air pressure, humidity etc. As further examples, the sensor may be a light sensor, an electronic switch, a microphone, a loudspeaker, a camera sensor etc.

Furthermore, the radio communication system 100 comprises a **network management unit 160** for controlling for example the first and second radio network nodes 110, 120. The network management unit 160 may be configured to **send 161** a communication signal. In some embodiments, the network management unit 160 is an entity for handling information about subscription of the user of the user equipment 120, about user equipment context and/or about mobility of the user equipment 120, e.g. a Mobility Management Entity (MME). In some embodiments, the network management unit 160 is an entity responsible for operation and maintenance (O&M) tasks, e.g. an O&M node such as an Operation Support System (OSS). In some embodiments, the network management unit 160 is an entity for handling user plane traffic, such as a Serving Gateway (SGW). Thus, the network management unit 160 may be e.g. an O&M node/system, MME or SGW.

According to embodiments herein, methods and measurement patterns for eNB-to-eNB interference measurement are described. Based on a given measurement pattern, such as a transmission and reception (Tx/Rx) configuration pattern for a subframe or parts of a subframe, radio network nodes may measure interference without any coordination or only little coordination.

Figure 2 illustrates an exemplifying method for measuring interference between the first radio network node 110 and the second radio network node 120 when implemented in the radio communication system 100 of Figure 1.

The interference is to be measured at a carrier frequency of the first and second radio network nodes 110, 120. In more detail, the carrier frequency may relate to the first and second cells.

It shall be understood that the following example is given with reference to 5 only two radio network nodes 110, 120 for the sake of simplicity. The embodiments herein may be readily applied to three, four or more radio network nodes, or cells.

The following actions may be performed in any suitable order.

Action 201

10 In order to align, e.g. in terms of time and/or frequency, the first and second radio network nodes 110, 120 such that the first and second radio network node 110, 120 are aware of when a measurement of the interference may be performed, action 201 and action 202 below provides the same, or similar, configuration information to the first radio network node 110 and the second radio network node 120.

15 Thus, the first radio network node 110 obtains configuration information for indicating a designated subframe in which a reference signal for measurement of the interference is to be transmitted by the second radio network node 120. The designated subframe is designated for enabling measurement of the interference. Thanks to the configuration information the first radio network node 110 is known 20 when and/or where the reference signal is sent. The configuration information is used in action 205.

25 The configuration information provided to the first radio network node 110 may be similar to, or corresponding to, the configuration information provided to the second radio network node 120 in that when the first radio network node 110 is in a receiving mode, in part of or in the entire designated subframe, the second radio network node 120 may be in a transmitting mode, in part of or in the entire designated subframe, for transmission of reference signals. The transmission of reference signals is described in action 205.

30 In some examples, the configuration information may be predetermined. In these examples, the first radio network node 110 may obtain the configuration information by determining the configuration information based on an identifier for identifying the first radio network node 110.

35 The identifier for identifying the first radio network node 110 may comprise one or more of: a cell identity; Internet Protocol IP address; Public Land Mobile Network identity (PLMN ID); measurement periodicity; geographical information of the first radio network node 110 and the second radio network node 120;

downlink/uplink Time Division Duplex configuration (DL/UL TDD configuration) or the like.

5 The cell identity may be a Physical Cell Identity (PCI), which provides a unique identity each cell handled by the first radio network node 110. In other examples, the cell identity is a global cell identity which is unique within the radio communication system 100.

10 In some other examples, the configuration information may be determined by a central node, such as the network management unit 160. Therefore, the first radio network node 110 may obtain the configuration information by receiving the configuration information from the network management unit 160.

Action 202

15 The second radio network node 120 obtains configuration information for configuring a designed subframe for transmission of a reference signal. The designated subframe is designated for enabling the first radio network node 110 to measure the interference.

20 Similarly to action 201, the configuration information may be pre-determined or received from the network management unit 150.

Hence, the second radio network node 120 may obtain the configuration information by determining the configuration information based on an identifier for identifying the second radio network node 120.

25 The identifier for identifying the second radio network node 120 may comprise one or more of: a cell identity; Internet Protocol IP address; Public Land Mobile Network identity (PLMN ID); measurement periodicity; geographical information of the first radio network node 110 and the second radio network node 120; and downlink/uplink Time Division Duplex configuration.

30 Alternatively or additionally, the second radio network node 120 may obtain the configuration information by receiving the configuration information from the network management unit 160.

Action 203

35 According to some first embodiments, the designated subframe may be a flexible uplink and/or downlink subframe. The designated subframe is defined by that the entire subframe, or parts thereof, e.g. symbols, may selectively, by the first radio network node 110, be put in reception or transmission mode. As an example, the

designated subframe may be a Flexible uplink/DownLink subframe (FDL subframe). The FDL subframe may be either an uplink subframe or a downlink subframe as selected by the first radio network node 110. Expressed somewhat differently, the FDL subframe may be flexibly configured into a downlink subframe or an uplink 5 subframe by a radio network node, such as the first radio network node 110 or the second radio network node 120.

Therefore, the configuration information may indicate to the first radio network node 110 that the flexible uplink and/or downlink subframe is to be configured as an uplink subframe when the interference is to be measured.

10 The first radio network node 110 may obtain the configuration information by configuring the flexible uplink and/or downlink subframe as the uplink subframe indicated by the configuration information.

15 According to some second embodiments, the designated subframe may be a special subframe known from 3GPP terminology. The special subframe may comprise an uplink timeslot, a downlink timeslot and a guard period between the uplink and downlink timeslots. The term "timeslot" may comprise one or more symbols in the time domain. Similarly, the term "guard period" may comprise one or more symbols in the time domain. The term "symbol" may refer to an Orthogonal 20 Frequency-Division Multiplexing (OFDM) symbol or the like.

The configuration information may indicate to the first radio network node 110 that the special subframe is to be configured according to a subframe configuration.

25 The first radio network node 110 may obtain the configuration information by configuring the special subframe according to the subframe configuration indicated by the configuration information. A first downlink timeslot of the first radio network node (110) may be shorter than a second downlink timeslot of the second radio network node (120).

30 In some examples, the subframe configuration may for example be "Mode 4" in accordance with 3GPP TS 36.211. In other examples, the subframe configuration is any other mode according to for example 3GPP TS 36.211 or similar future 3GPP specifications. Any mode is feasible, if a so called Downlink Pilot TimeSlot (DwPTS) of the designated subframe in the second radio network node 120 is longer than the DwPTS of the designated subframe in the first radio network node 110. For example, a measured cell, such as the second cell of the second radio network node 120, uses 35 "Mode 1", as specified in 3GPP TS 36.211, and a measuring cell, such as the first cell of the first radio network node 110, uses Mode 5, is also feasible. Therefore, it may be said that the subframe configuration information for the designated subframe

of the first radio network node 110 may indicate a first subframe configuration according to which the first downlink timeslot, such as DwPTS, has a first length, or duration in e.g. ms. In connection therewith, the subframe configuration information for the designated subframe of the second radio network node 120 may indicate a 5 second subframe configuration according to which the second downlink timeslot, such as DwPTS, has a second length, or duration in e.g. ms. The first length may be shorter than the second length such as to allow measurement of the interference.

10 In these examples, in "Mode 1", 9 OFDM symbols are used in the measured cell, while 3 OFDM symbols are configured in the measuring cell according to the specification TS 36.211. Hence, OFDM symbols 4-9 may be used for measurement.

15 The configuring, according to the first embodiments and/or the second embodiments, may be performed based on a need for measurement of the interference. As an example, if an indication of the need is above a threshold value relating to the need, then the first radio network node 110 configures the designated subframe as the uplink subframe, whereby reception, in action 205, of the reference signal is enabled. In turn, this implies that action 206 may be performed.

20 The need may occur due to that the value of the interference value is old, i.e. the time past since last determination of the value, see action 206, is above a threshold value.

In other examples, the need may occur when a Block Error Rate (BLER) is above a threshold value for BLER. That is to say the BLER is bad. The BLER may be said to be good when the BLER is below the threshold value for BLER.

25 For example, if BLER is good and there is a lot of data to transmit, the measuring node may decide to use the designated subframe in which measurement is possible for downlink transmission, for example towards the user equipment 140, instead.

30 Similarly, for example, if BLER is good and there is a lot of data to receive, the first radio network node 100 may decide to use the designated subframe for uplink transmission from the user equipment 140 instead of transmission of reference signals from the second radio network node 120.

35 In other examples, the value of the interference is used for interference management. During for example a low load scenario or for user equipments in the so called cell range extension, the designated subframe may be configured into an uplink subframe, which may be a completely empty subframe if desired. In contrast, CRS is always transmitted in a downlink subframe. Thus, if the designated subframe is configured as an uplink subframe the interference may be reduced thanks to that

no CRS is transmitted. With this configuration, no interference comes from this subframe.

Action 204

5 According to some first embodiments, the designated subframe may comprise a flexible uplink and/or downlink subframe.

The configuration information may indicate to the second radio network node 120 that the flexible uplink and/or downlink subframe is to be configured as a downlink subframe.

10 In these embodiments, the second radio network node 120 may obtain the configuration information by configuring the flexible uplink and/or downlink subframe as the downlink subframe indicated by the configuration information.

15 According to some second embodiments, the designated subframe may be a special subframe. The special subframe may comprise an uplink timeslot, a downlink timeslot and a guard period between the uplink and downlink timeslots.

The configuration information may indicate to the second radio network node 120 that the special subframe is to be configured according to a subframe configuration. The first downlink timeslot of the first radio network node (110) may be 20 shorter than the second downlink timeslot of the second radio network node (120).

In these embodiments, the second radio network node 120 may obtain the configuration information by configuring the special subframe according to the subframe configuration indicated by the configuration information.

25 It may be noted that according to preferred embodiments, the second radio network node 120 does always transmit the reference signal. Thus, the decision on whether or not to perform a measurement is left solely to the first radio network node 110. In contrast, the first radio network node 110 performs action 203 based on the need for measurement of the interference as explained above.

30

Action 205

In order to measure the interference, e.g. from the second radio network node 120 towards the first radio network node 110, the second radio network node 120 sends, in the designated subframe, the reference signal to the first radio network 35 node 110.

As explained above in conjunction with action 203, it is up to the first radio network node 110 to decide whether or not to configure, at least partially, the

designated subframe for reception of the reference signal. Again, when the designated subframe is partially configured for reception, some symbols of the designated subframe are uplink symbols, i.e. reception is possible, and some symbols of the designated subframe are downlink symbols. Also as mentioned, the 5 designated subframe may be an uplink subframe, in which reception is possible.

Action 206

The first radio network node 110 determines a value of the interference based on the reference signal. In this manner, the first radio network node 110 completes, 10 or finalizes, the measurement of the interference.

The value of the interference may be represented by one or more of: a Channel Quality Indicator (CQI), a Signal-to-Interference-and-Noise-Ratio (SINR), a Signal-to-Interference-Ratio (SIR), a Signal-to- Noise-Ratio (SNR), a Reference Signal Received Power (RSRP), a Reference Signal Received Quality (RSRQ), a 15 Received Signal Strength Indicator (RSSI) and the like.

The first radio network node 110 may need to obtain information about transmission power of the reference signals from the second radio network node according to known methods.

Action 207

The first radio network node 110 may adapt transmit power, Tx power, of the first radio network node 110 based on the value. Typically, when the value of interference is above a threshold for the value of interference, the transmit power of the first radio network node 110 is increased. Likewise, when the value of 25 interference is below the threshold for the value of interference, the transmit power of the first radio network node 110 may be decreased.

If action 207 is performed, thus adjusting Tx power of the first radio network node 110, it may be that it is not necessary to also adjust the Tx power of the second radio network node 120 as in action 209. Hence, action 208 and 209 need not be 30 performed after action 207 has been performed. Advantageously, less information is transmitted.

Action 208

The first radio network node 110 may send the value of the interference to the second radio network node 120. Thereby, the second radio network node 120 may 35 use the value in action 209.

The value of the interference may be represented by one or more of:
Channel Quality Indicator, Signal-to-Interference-and-Noise-Ratio, Signal-to-
Interference -Ratio, Signal-to- Noise-Ratio, Reference Signal Received Power,
Reference Signal Received Quality, and Received Signal Strength Indicator and the
5 like.

Action 209

The second radio network node 120 may adapt transmit power of the second
radio network node 120 based on the value. Typically, when the value of interference
10 is above a second threshold for the value of interference, the transmit power of the
second radio network node 120 is decreased. Likewise, when the value of
interference is below the second threshold for the value of interference, the transmit
power of the second radio network node 120 may be increased.

15 Some further details with reference to action 203 and 204 will now be
described.

In order to measure eNB-to-eNB interference at the designated subframe, the
second radio network node 120 shall be in Tx mode, i.e. at least the symbol(s)
carrying the reference signal shall be in Tx mode. The first radio network node 110
20 shall be to be in Rx mode, i.e. at least those symbols during which the reference
signal is sent by the second radio network node 120 shall be in Rx mode. Therefore,
Tx and Rx modes in subframes of different cells are relevant each other for the
measurement of the interference. The alignment of the Tx/Rx modes of the first and
second radio network nodes 110, 120, e.g. a measured cell and a measuring cell, is
25 necessary.

In order to align the Tx/Rx modes without a real-time online coordination
during operation, it is herein described how the Tx/Rx modes of different cells at the
designated subframe, and possibly also at a specific radio frame number, may be
pre-defined according to the cell identifier, TDD configuration and other parameters,
30 e.g. PLMN ID, IP address or the like.

The specific radio frame number i of DL Tx for the measured cell is defined
as follows:

$$i = f_1(id, M, DL/UL \text{ conf}, \text{Timing})$$

where id may be a physical cell identifier (PCI), IP address, PLMN ID or any identifier which can identify the measured cell, M is the measurement period, and $DL/UL\ conf$ is the DL/UL TDD configuration and special subframe configuration, Timing refers to global timing, i.e., obtained from GPS, or from core network. One 5 simple example of the function $f_1()$ is:

$$i = (cellid + k * N) \bmod(1024) \quad k = 0,1,\dots$$

N is a pre-set periodicity, and the periodicity can be from seconds to minutes, or even hours. The period can be set according to the eNB-to-eNB interference time-domain variation characteristics.

10 In the corresponding subframe, and optionally also radio frame number, given above, the measuring cell can be configured into Rx mode to estimate eNB-to-eNB interference.

15 In general, the above method may be extended to a method based on geographical information of each eNBs instead of PCI or any other identification number other than PCI.

20 **Figure 3** shows exemplifying TDD configurations for the first cell “Cell 1” and the second cell “Cell 2”. The terms “victim cell” and “aggressor cell” are explained and illustrated. In the Figure, a radio frame 0 “Radio Frame 0” comprises 10 subframes, denoted by reference numerals 0 - 9. In a fourth subframe 4 the first cell “Cell 1” is configured with an uplink subframe U and the second cell “Cell 2” is configured with a downlink subframe D. Thereby, the first cell may receive transmission from the second cell. This means that the first cell becomes a victim cell and the second cell becomes an aggressor cell. Additionally, special subframes S 25 are shown in subframe 1 and 6.

30 **Figure 4** illustrates an exemplifying TDD configuration according to the first embodiments, in which the designated subframe may be a FDL subframe. The same or similar reference numerals denote the same or similar cells, radio frames or the like as in Figure 3.

35 In this example, subframe 4 is a pre-determined, or pre-set, subframe for flexible DL/UL. In order to measure eNB-to-eNB interference, in radio frame m, cell 2 operates in DL according to aforementioned TDD configuration, while cell 1 is configured to either DL or UL as determined by the first radio network node 110, e.g. depending on traffic status, or load on the first cell. If cell 1, e.g. the first radio

network node 110, needs to estimate interference between Cell 2 to its own cell “Cell 1”, at the corresponding subframe, it is configured into an UL subframe for receiving the reference signal from the second cell, e.g. the second radio network node 120.

5 Similarly, in another radio frame occasions, i.e., radio frame k, Cell 1 is predetermined to Tx for DL and the second cell is configured to be UL if interference estimation is needed. Otherwise, the configurations can be flexible.

Figure 5 illustrates an exemplifying TDD configuration according to the second embodiments, in which the designated subframe may be a special subframe.

10 The same or similar reference numerals denote the same or similar cells, radio frames or the like as in Figure 3.

As an example, at a special subframe S of radio frame m in subframe 1, a first number of DL OFDM symbols of cell 2 are configured. Furthermore, a second number of DL OFDM symbols of cell 1 are configured. Here, the first number of DL 15 OFDM symbols is greater than the second number of DL OFDM symbols. In one or more of the subframes corresponding to those DL OFDM symbols which are in excess compared to the second number of DL OFDM symbols, the first cell may measure eNB-to-eNB interference measurement. In another radio frame, i.e., radio frame k, more DL OFDM symbols are configured in the special subframe of cell 1, 20 and thus the second cell may conduct eNB-to-eNB interference measurement when needed.

Figure 6 illustrates an exemplifying TDD configuration according to the first embodiments, in which the designated subframe may be a FDL subframe. The same 25 or similar reference numerals denote the same or similar cells, radio frames or the like as in Figure 3.

As shown in Figure 6, the first radio network node 110, “Measuring node”, may wish to measure the eNB-to-eNB interference from the second radio network node 120 “Measured node”. Assume subframe 4 is the FDL subframe, the following 30 configuration and procedure may be used for eNB-to-eNB interference measurement.

A Tx/Rx configuration pattern relates to a pattern according to which the designated subframe is configured as a DL subframe, whereby measurement by the first radio network node 110 is possible. In this example, the Tx/Rx configuration pattern is applied, by the second radio network node 120, to the FDL subframe.

35 The Tx/Rx configuration pattern for the FDL subframe may be predetermined by utilizing the identifier based alignment as described in action 201 and 202 in

Figure 2. Hence, no further coordination between the first and second radio network nodes is required.

Alternatively or additionally, the Tx/Rx configuration pattern for the FDL subframe may be determined by coordination/mutual negotiations between the first 5 and second radio network nodes 110, 120.

According to the Tx/Rx configuration pattern determined, the second radio network node 120 has configured the FDL subframe as a DL subframe. See subframe 4 of cell 2. In this DL subframe, the reference signal, such as a Cell-10 specific Reference Signal (CRS), a Channel State Information Reference Signal (CSI-RS) or the like, is transmitted.

For the first radio network node 110, the FDL subframe is configured into UL subframe for reception of the reference signal when needed. In this UL subframe, the first radio network node 110 is in Rx mode. The first radio network node 110 15 estimates the eNB-to-eNB interference from the reference signal (RS) transmitted by the second radio network node.

Figure 7 and 8 show exemplifying designated subframes according to the second embodiment.

20 In **Figure 7**, an example of the special subframe is shown. The first radio network node 110 “Measuring node” may wish to measure the eNB-to-eNB interference from the second radio network node 120 “Measured node”. Then, the following configuration and procedure may be used for eNB-to-eNB interference 25 measurement.

The Tx/Rx configuration pattern for the special subframe may be predetermined by utilizing the identifier based alignment as described in action 201 and 202 in Figure 2. Hence, no further coordination between the first and second radio network nodes is required.

30 Alternatively or additionally, the Tx/Rx configuration pattern for the special subframe may be determined by coordination/mutual negotiations between the first and second radio network nodes 110, 120.

According to the Tx/Rx configuration pattern determined, the second radio network node 120 transmits the reference signal in a certain special subframe, for 35 example in a DwPTS time slot at a TD-LTE frame. This special subframe configuration is set as mode 4 and is standardized in LTE specification TS36.211.

Other special sub-frame configurations, according to for example TS36.211, can also be used if there are enough available reference signals in the corresponding configuration. The structure of the special sub-frame is illustrated in Figure 7 with a normal cyclic prefix.

5

Now referring to **Figure 8**, for the first radio network node 110, OFDM symbol 0 to 2 are the so called Downlink Pilot TimeSlot (DwPTS) in the special subframe. This means that OFDM symbol 0 to 2 are DL symbols. In contrast, OFDM symbol 13th is an UL symbol, and OFDM symbol 12th GP is a guard period, i.e. here just one symbol, for switching from downlink to uplink. The GP duration is much longer than that of the second radio network node 120, during most of which the second radio network node 120 conducts a DL Tx.

Thus, the first radio network node 110 may receive the OFDM symbol 3 to 11 sent from the second radio network node 120, where OFDM symbol 4, 7 and 11 have the DL cell specific reference signal (CRS) or other reference signals. Then first radio network node 110 can estimate signal strength of second radio network node 120 by processing received signals at OFDM symbol 4, 7 and 11. The configuration in Figure 8 is just one example. The guard period (GP) can be reduced according to the network. If the guard period is reduced, less OFDM symbols may be used for interference measurement, or interference estimation.

After the eNB-to-eNB interference is estimated according any one of the examples described herein, e.g. with reference to Figure 6 or Figure 7 and 8, the first radio network node 110 may signal, or send, the measurement results, i.e. the value of the interference, to the second radio network node 120 e.g. via a backhaul connection such as X2 link. See action 208. The second radio network node 120 takes action to handle transmit power control based on the feedback in terms of the value of the interference. See action 209.

By exploiting channel reciprocity, the first radio network node 110 may also adapt its own power control strategy based on the value of the interference. In this manner, the first radio network node 110 controls its own Tx power to reduce the interference towards the second radio network node 120 based on e.g. a pre-defined rule. See action 207. In principle, any pair of radio network nodes only need only one measurement if the radio communication system 100 is homogeneous, whereby channel reciprocity is maintained and reliable.

With reference to **Figure 9**, embodiments of the method in the first radio network node 110 for measuring interference between the first radio network node 110 and the second radio network node 120 are described.

The following actions may be performed in any suitable order.

5

Action 901

The first radio network node 110 obtains configuration information for indicating a designated subframe in which a reference signal for measurement of the interference is to be transmitted by the second radio network node 120. The 10 designated subframe is designated for enabling measurement of the interference. This action is similar to action 201.

The first radio network node 110 may obtain the configuration information by determining the configuration information based on an identifier for identifying the first 15 radio network node 110.

The identifier for identifying the first radio network node 110 may comprise one or more of: a cell identity; Internet Protocol IP address; Public Land Mobile Network identity; measurement periodicity; geographical information of the first radio network node 110 and the second radio network node 120; and downlink/uplink Time 20 Division Duplex configuration.

The first radio network node 110 may obtain the configuration information by receiving the configuration information from the network management unit 160.

25 Action 902

According to the first embodiments, the designated subframe may be a flexible uplink and/or downlink subframe.

The configuration information may indicate to the first radio network node 110 that the flexible uplink and/or downlink subframe is to be configured as an uplink 30 subframe when the interference is to be measured.

The first radio network node 110 may obtain the configuration information by configuring the flexible uplink and/or downlink subframe as the uplink subframe indicated by the configuration information.

The configuring may be performed based on a need for measurement of the 35 interference.

According to the second embodiments, the designated subframe may be a special subframe. The special subframe may comprise an uplink timeslot, a downlink timeslot and a guard period between the uplink and downlink timeslots.

5 The configuration information may indicate to the first radio network node 110 that the special subframe is to be configured according to a subframe configuration.

The first radio network node 110 may obtain the configuration information by configuring the special subframe according to the subframe configuration indicated by the configuration information. A first downlink timeslot of the first radio network node (110) may be shorter than a second downlink timeslot of the second radio 10 network node (120).

The configuring may be performed based on a need for measurement of the interference.

This action is similar to action 203.

15

Action 903

The first radio network node 110 receives, from the second radio network node 120 in the designated subframe indicated by the configuration information, the reference signal. This action is similar to action 205.

20

Action 904

The first radio network node 110 determines a value of the interference based on the reference signal. This action is similar to action 206.

The value of the interference may be represented by one or more of:

25 Channel Quality Indicator, Signal-to-Interference-and-Noise-Ratio, Signal-to-Interference -Ratio, Signal-to- Noise-Ratio, Reference Signal Received Power, Reference Signal Received Quality, and Received Signal Strength Indicator and the like.

30 **Action 905**

The first radio network node 110 may adapt transmit power, Tx power, of the first radio network node 110 based on the value. This action is similar to action 207.

Action 906

35 The first radio network node 110 may send the value of the interference to the second radio network node 120. This action is similar to action 208.

With reference to **Figure 10**, embodiments of the first radio network node 110 when configured to perform the embodiments described herein. Thus, the network node 110, 111, 112 is configured to measure interference between the first radio network node 110 and the second radio network node 120.

5

The first radio network node 110 comprises a **processing circuit 1010** configured to obtain configuration information for indicating a designated subframe in which a reference signal for measurement of the interference is to be transmitted by the second radio network node 120. The designated subframe is designated for enabling measurement of the interference.

Furthermore, the processing circuit 1010 is configured to receive, from the second radio network node 120 in the designated subframe indicated by the configuration information, the reference signal. Moreover, the processing circuit 1010 is configured to determine a value of the interference based on the reference signal.

10

The processing circuit 1010 may further be configured to determine the configuration information based on an identifier for identifying the first radio network node 110.

The processing circuit 1010 may further be configured to receive the configuration information from a network management unit 160.

15

The processing circuit 1010 may further be configured to send the value of the interference to the second radio network node 120.

The processing circuit 1010 may be a processing unit, a processor, an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA) or the like. As an example, a processor, an ASIC, an FPGA or the like may comprise one or more processor kernels.

20

The identifier for identifying the first radio network node 110 may comprise one or more of: a cell identity; Internet Protocol IP address; Public Land Mobile Network identity; measurement periodicity; geographical information of the first radio network node 110 and the second radio network node 120; and downlink/uplink Time Division Duplex configuration.

30

The value of the interference may be represented by one or more of: a Channel Quality Indicator, a Signal-to-Interference-and-Noise-Ratio, a Signal-to-Interference -Ratio, a Signal-to- Noise-Ratio, a Reference Signal Received Power, a Reference Signal Received Quality, and a Received Signal Strength Indicator and the like.

The designated subframe may be a flexible uplink and/or downlink subframe.

The configuration information may indicate to the first radio network node 110 that the flexible uplink and/or downlink subframe is to be configured as an uplink subframe when the interference is to be measured.

5 The processing circuit 1010 may further be configured to configure the flexible uplink and/or downlink subframe as the uplink subframe indicated by the configuration information.

The processing circuit 1010 may further be configured to configure the flexible uplink and/or downlink subframe as the uplink subframe indicated by the

10 configuration information based on a need for measurement of the interference.

The designated subframe may be a special subframe. The special subframe may comprise an uplink timeslot, a downlink timeslot and a guard period between the uplink and downlink timeslots.

15 The configuration information may indicate to the first radio network node 110 that the special subframe is to be configured according to a subframe configuration,

The processing circuit 1010 may further be configured to configure the special subframe according to the subframe configuration indicated by the configuration information. A first downlink timeslot of the first radio network node (110) may be 20 shorter than a second downlink timeslot of the second radio network node (120).

The first radio network node 110 according to claim 33, wherein the processing circuit 1010 further is configured to configure the special subframe according to the subframe configuration indicated by the configuration information based on a need for measurement of the interference.

25 The processing circuit 1010 may further be configured to adapt transmit power of the first radio network node 110 based on the value.

The first radio network node 110 further comprises a **transmitter 1020**, which may be configured to send one or more of the value of interference and other 30 numbers, values or parameters described herein.

The first radio network node 110 further comprises a **receiver 1030**, which may be configured to receive one or more of the reference signal and other numbers, values or parameters described herein.

35

The first radio network node 110 further comprises a **memory 1040** for storing software to be executed by, for example, the processing circuit. The software

may comprise instructions to enable the processing circuit to perform the method in the first radio network node 110 as described above in conjunction with Figure 2 and/or 9. The memory may be a hard disk, a magnetic storage medium, a portable computer diskette or disc, flash memory, random access memory (RAM) or the like.

5 Furthermore, the memory may be an internal register memory of a processor.

Figure 11 illustrates embodiments of the method in the second radio network node 120 for enabling a first radio network node 110 to measure interference between the first radio network node 110 and the second radio network node 120.

10 The following actions may be performed in any suitable order.

Action 1101

The second radio network node 120 obtains configuration information for configuring a designed subframe for transmission of a reference signal, the 15 designated subframe being designated for enabling the first radio network node 110 to measure the interference. This action is similar to action 202.

The second radio network node 120 may obtain the configuration information by determining the configuration information based on an identifier for identifying the 20 second radio network node 120.

The identifier for identifying the first radio network node 110 may comprise one or more of: a cell identity; Internet Protocol IP address; Public Land Mobile Network identity, “PLMN ID”; measurement periodicity; geographical information of the first radio network node 110 and the second radio network node 120; and 25 downlink/uplink Time Division Duplex configuration, “DL/UL TDD configuration” and the like.

The second radio network node 120 may obtain the configuration information by receiving the configuration information from a network management unit 160.

30

Action 1102

According to some first embodiments, the designated subframe may comprise a flexible uplink and/or downlink subframe.

The configuration information may indicate to the second radio network node 35 120 that the flexible uplink and/or downlink subframe is to be configured as a downlink subframe.

In these embodiments, the second radio network node 120 may obtain the configuration information by configuring the flexible uplink and/or downlink subframe as the downlink subframe indicated by the configuration information.

5 According to some second embodiments, the designated subframe may be a special subframe. The special subframe may comprise an uplink timeslot, a downlink timeslot and a guard period between the uplink and downlink timeslots.

The configuration information may indicate to the second radio network node 120 that the special subframe is to be configured according to a subframe 10 configuration. A first downlink timeslot of the first radio network node (110) may be shorter than a second downlink timeslot of the second radio network node (120).

In these embodiments, the second radio network node 120 may obtain the configuration information by configuring the special subframe according to the subframe configuration indicated by the configuration information.

15

This action is similar to action 204.

Action 1103

The second radio network node 120 sends, in the designated subframe, the 20 reference signal to the first radio network node 110. This action is similar to action 205.

Action 1104

The second radio network node 120 may receive a value of the interference. 25 This action is similar to action 208.

The value of the interference may be represented by one or more of: Channel Quality Indicator, Signal-to-Interference-and-Noise-Ratio, Signal-to-Interference - Ratio, Signal-to- Noise-Ratio, Reference Signal Received Power, Reference Signal Received Quality, Received Signal Strength Indicator and the like.

30

Action 1105

The second radio network node 120 may adapt transmit power of the second radio network node 120 based on the value. This action is similar to action 209.

35

Figure 12 illustrates embodiments of the second radio network node 120 when configured to perform the embodiments described herein. Thus, the second radio network node 120 is configured to enable a first radio network node 110 to

measure interference between the first radio network node 110 and the second radio network node 120.

The second radio network node 120 comprises a **processing circuit 1210** 5 configured to obtain configuration information for configuring a designed subframe for transmission of a reference signal. The designated subframe is designated for enabling the first radio network node 110 to measure the interference. Furthermore, the processing circuit 1210 is configured to send, in the designated subframe, the reference signal to the first radio network node 110.

10

The processing circuit 1210 may further be configured to determine the configuration information based on an identifier for identifying the second radio network node 120.

The processing circuit 1210 may further be configured to receive the 15 configuration information from a network management unit 160.

The processing circuit 1210 may further be configured to receive a value of the interference; and adapt transmit power of the second radio network node 120 based on the value.

The processing circuit 1210 may be a processing unit, a processor, an 20 application specific integrated circuit (ASIC), a field-programmable gate array (FPGA) or the like. As an example, a processor, an ASIC, an FPGA or the like may comprise one or more processor kernels.

The identifier for identifying the first radio network node 110 may comprise 25 one or more of: a cell identity; Internet Protocol IP address; Public Land Mobile Network identity; measurement periodicity; geographical information of the first radio network node 110 and the second radio network node 120; and downlink/uplink Time Division Duplex configuration.

The value of the interference may be represented by one or more of: a 30 Channel Quality Indicator, a Signal-to-Interference-and-Noise-Ratio, a Signal-to-Interference -Ratio, a Signal-to- Noise-Ratio, a Reference Signal Received Power, a Reference Signal Received Quality, and a Received Signal Strength Indicator and the like.

35 In some embodiments, the designated subframe may be a flexible uplink and/or downlink subframe.

The configuration information may indicate to the second radio network node 120 that the flexible uplink and/or downlink subframe is to be configured as a downlink subframe

5 In these embodiments, the processing circuit 1210 may further be configured to configure the flexible uplink and/or downlink subframe as the downlink subframe indicated by the configuration information.

In some embodiments, the designated subframe may be a special subframe. The special subframe may comprise an uplink timeslot, a downlink timeslot and a 10 guard period between the uplink and downlink timeslots.

The configuration information may indicate to the second radio network node 120 that the special subframe is to be configured according to a subframe configuration.

15 In these embodiments, the processing circuit 1210 may further be configured to configure the special subframe according to the subframe configuration indicated by the configuration information. A first downlink timeslot of the first radio network node (110) may be shorter than a second downlink timeslot of the second radio network node (120).

20 The second radio network node 120 further comprises **a transmitter 1220**, which may be configured to send one or more of the reference signal and other numbers, values or parameters described herein.

25 The second radio network node 120 further comprises **a receiver 1230**, which may be configured to receive one or more of the value of interference and other numbers, values or parameters described herein.

30 The second radio network node 120 further comprises **a memory 1240** for storing software to be executed by, for example, the processing circuit. The software may comprise instructions to enable the processing circuit to perform the method in the second radio network node 120 as described above in conjunction with Figure 2 and/or 11. The memory may be a hard disk, a magnetic storage medium, a portable computer diskette or disc, flash memory, random access memory (RAM) or the like. Furthermore, the memory may be an internal register memory of a processor.

35

As used herein, the terms “number”, “value” may be any kind of digit, such as binary, real, imaginary or rational number or the like. Moreover, “number”, “value”

may be one or more characters, such as a letter or a string of letters. “number”, “value” may also be represented by a bit string.

Even though embodiments of the various aspects have been described, many
5 different alterations, modifications and the like thereof will become apparent for those
skilled in the art. The described embodiments are therefore not intended to limit the
scope of the present disclosure.

CLAIMS

1. A method in a first radio network node (110) for measuring interference between the first radio network node (110) and a second radio network node (120), the method comprising:

5 obtaining (201, 901) configuration information for indicating a designated subframe in which a reference signal for measurement of the interference is to be transmitted by the second radio network node (120), the designated subframe being designated for enabling measurement of the interference;

10 receiving (205, 903), from the second radio network node (120) in the designated subframe indicated by the configuration information, the reference signal; and

determining (206, 904) a value of the interference based on the reference signal.

15 2. The method according to claim 1, wherein the obtaining (201) of the configuration information comprises determining the configuration information based on an identifier for identifying the first radio network node (110).

3. The method according to claim 2, wherein the identifier for identifying the first
20 radio network node (110) comprises one or more of:

a cell identity;

Internet Protocol address;

Public Land Mobile Network identity;

measurement periodicity;

25 geographical information of the first radio network node (110) and
the second radio network node (120); and

downlink/uplink Time Division Duplex configuration.

4. The method according to any one of claims 1-3, wherein the obtaining (201) of
30 configuration information comprises receiving the configuration information from a
network management unit (160).

5. The method according to any one of claims 1-4, wherein the value of the interference is represented by one or more of:

35 Channel Quality Indicator,
Signal-to-Interference-and-Noise-Ratio,

Signal-to-Interference -Ratio,
Signal-to- Noise-Ratio,
Reference Signal Received Power,
Reference Signal Received Quality, and
Received Signal Strength Indicator.

5

6. The method according to any one of claims 1-5, wherein the designated subframe is a flexible uplink and/or downlink subframe.

10 7. The method according to claim 6, wherein the configuration information indicates to the first radio network node (110) that the flexible uplink and/or downlink subframe is to be configured as an uplink subframe when the interference is to be measured, wherein the obtaining of configuration information comprises:
configuring (203, 902) the flexible uplink and/or downlink subframe as the uplink subframe indicated by the configuration information.

15

8. The method according to claim 7, wherein the configuring (203, 902) is performed based on a need for measurement of the interference.

20 9. The method according to any one of claims 1-5, wherein the designated subframe is a special subframe, wherein the special subframe comprises an uplink timeslot, a downlink timeslot and a guard period between the uplink and downlink timeslots.

25 10. The method according to claim 9, wherein the configuration information indicates to the first radio network node (110) that the special subframe is to be configured according to a subframe configuration, wherein the obtaining of configuration information comprises:
configuring (203, 902) the special subframe according to the subframe configuration indicated by the configuration information, wherein a first downlink timeslot of the first radio network node (110) is shorter than a second downlink timeslot of the second radio network node (120).

30

11. The method according to claim 10, wherein the configuring (203, 902) is performed based on a need for measurement of the interference.

35

12. The method according to any one of claim 1-11, further comprising:

adapting (207, 905) transmit power of the first radio network node (110) based on the value.

13. The method according to any one of claim 1-12, further comprising:

5 sending (208, 906) the value of the interference to the second radio network node (120).

14. A method in a second radio network node (120) for enabling a first radio network node (110) to measure interference between the first radio network node (110)

10 and the second radio network node (120), the method comprising:

obtaining (202, 1101) configuration information for configuring a designed subframe for transmission of a reference signal, the designated subframe being designated for enabling the first radio network node (110) to measure the interference; and

15 sending (205, 1103), in the designated subframe, the reference signal to the first radio network node (110).

16. The method according to claim 14, wherein the obtaining (202) of the configuration information comprises determining the configuration information based on an identifier for identifying the second radio network node (120).

20 16. The method according to claim 15, wherein the identifier for identifying the first radio network node (110) comprises one or more of:

a cell identity;

25 Internet Protocol address;

Public Land Mobile Network identity;

measurement periodicity;

geographical information of the first radio network node (110)

and the second radio network node (120); and

30 downlink/uplink Time Division Duplex configuration.

17. The method according to any one of claims 14-16, wherein the obtaining of configuration information comprises receiving the configuration information from a network management unit (160).

35

18. The method according to any one of claims 14-17, wherein the designated subframe is a flexible uplink and/or downlink subframe.

19. The method according to claim 18, wherein the configuration information indicates to the second radio network node (120) that the flexible uplink and/or downlink subframe is to be configured as a downlink subframe, wherein the

5 obtaining of configuration information comprises:

configuring (204, 1102) the flexible uplink and/or downlink subframe as the downlink subframe indicated by the configuration information.

20. The method according to any one of claims 14-17, wherein the designated

10 subframe is a special subframe, wherein the special subframe comprises an uplink timeslot, a downlink timeslot and a guard period between the uplink and downlink timeslots.

21. The method according to claim 20, wherein the configuration information

15 indicates to the second radio network node (120) that the special subframe is to be configured according to a subframe configuration, wherein the obtaining of configuration information comprises:

20 configuring (204, 1102) the special subframe according to the subframe configuration indicated by the configuration information, wherein a first downlink timeslot of the first radio network node (110) is shorter than a second downlink timeslot of the second radio network node (120).

22. The method according to any one of claim 14-21, further comprising:

25 receiving (208, 1104) a value of the interference; and

adapting (209, 1105) transmit power of the second radio network node (120) based on the value.

23. The method according to any one of claims 22, wherein the value of the

interference is represented by one or more of:

30 a Channel Quality Indicator,
a Signal-to-Interference-and-Noise-Ratio,
a Signal-to-Interference -Ratio,
a Signal-to- Noise-Ratio,
a Reference Signal Received Power,
35 a Reference Signal Received Quality, and
a Received Signal Strength Indicator.

24. A first radio network node (110) configured to measure interference between the first radio network node (110) and a second radio network node (120), wherein the first radio network node (110) comprises a processing circuit (1010) configured to:

5 obtain configuration information for indicating a designated subframe in which a reference signal for measurement of the interference is to be transmitted by the second radio network node (120), the designated subframe being designated for enabling measurement of the interference;

10 receive, from the second radio network node (120) in the designated subframe indicated by the configuration information, the reference signal; and determine a value of the interference based on the reference signal.

15 25. The first radio network node (110) according to claim 24, wherein the processing circuit (1010) further is configured to determine the configuration information based on an identifier for identifying the first radio network node (110).

26. The first radio network node (110) according to claim 25, wherein the identifier for identifying the first radio network node (110) comprises one or more of:

20 a cell identity;
Internet Protocol address;
Public Land Mobile Network identity;
measurement periodicity;
geographical information of the first radio network node (110) and the second radio network node (120); and
25 downlink/uplink Time Division Duplex configuration.

30 27. The first radio network node (110) according to any one of claims 24-26, wherein the processing circuit (1010) further is configured to receive the configuration information from a network management unit (160).

28. The first radio network node (110) according to any one of claims 24-27, wherein the value of the interference is represented by one or more of:

35 a Channel Quality Indicator,
a Signal-to-Interference-and-Noise-Ratio,
a Signal-to-Interference -Ratio,
a Signal-to- Noise-Ratio,
a Reference Signal Received Power,

a Reference Signal Received Quality, and
a Received Signal Strength Indicator.

29. The first radio network node (110) according to any one of claims 24-28, wherein

5 the designated subframe is a flexible uplink and/or downlink subframe.

30. The first radio network node (110) according to claim 29, wherein the

configuration information indicates to the first radio network node (110) that the
flexible uplink and/or downlink subframe is to be configured as an uplink

10 subframe when the interference is to be measured, wherein the processing circuit
(1010) further is configured to configure the flexible uplink and/or downlink
subframe as the uplink subframe indicated by the configuration information.

31. The first radio network node (110) according to claim 30, wherein the processing

15 circuit (1010) further is configured to configure the flexible uplink and/or downlink
subframe as the uplink subframe indicated by the configuration information based
on a need for measurement of the interference.

32. The first radio network node (110) according to any one of claims 24-28, wherein

20 the designated subframe is a special subframe, wherein the special subframe
comprises an uplink timeslot, a downlink timeslot and a guard period between the
uplink and downlink timeslots.

33. The first radio network node (110) according to claim 32, wherein the

25 configuration information indicates to the first radio network node (110) that the
special subframe is to be configured according to a subframe configuration,
wherein the processing circuit (1010) further is configured to configure the special
subframe according to the subframe configuration indicated by the configuration
information, wherein a first downlink timeslot of the first radio network node (110)
30 is shorter than a second downlink timeslot of the second radio network node
(120).

34. The first radio network node (110) according to claim 33, wherein the processing

35 circuit (1010) further is configured to configure the special subframe according to
the subframe configuration indicated by the configuration information based on a
need for measurement of the interference.

35. The first radio network node (110) according to any one of claim 24-34, wherein the processing circuit (1010) further is configured to adapt transmit power of the first radio network node (110) based on the value.

5 36. The first radio network node (110) according to any one of claim 24-35, wherein the processing circuit (1010) further is configured to send the value of the interference to the second radio network node (120).

10 37. A second radio network node (120) configured to enable a first radio network node (110) to measure interference between the first radio network node (110) and the second radio network node (120), the second radio network node (120) comprising a processing circuit (1210) configured to:

15 obtain configuration information for configuring a designed subframe for transmission of a reference signal, the designated subframe being designated for enabling the first radio network node (110) to measure the interference; and send, in the designated subframe, the reference signal to the first radio network node (110).

38. The second radio network node (120) according to claim 37, wherein the

20 processing circuit (1210) further is configured to determine the configuration information based on an identifier for identifying the second radio network node (120).

39. The second radio network node (120) according to claim 38, wherein the identifier

25 for identifying the first radio network node (110) comprises one or more of:

a cell identity;
Internet Protocol address;
Public Land Mobile Network identity;
measurement periodicity;

30 geographical information of the first radio network node (110) and the second radio network node (120); and downlink/uplink Time Division Duplex configuration.

40. The second radio network node (120) according to any one of claims 37-39,

35 wherein the processing circuit (1210) further is configured to receive the configuration information from a network management unit (160).

41. The second radio network node (120) according to any one of claims 37-40, wherein the designated subframe is a flexible uplink and/or downlink subframe.
42. The second radio network node (120) according to claim 41, wherein the configuration information indicates to the second radio network node (120) that the flexible uplink and/or downlink subframe is to be configured as a downlink subframe, wherein the processing circuit (1210) further is configured to configure the flexible uplink and/or downlink subframe as the downlink subframe indicated by the configuration information.
43. The second radio network node (120) according to any one of claims 37-40, wherein the designated subframe is a special subframe, wherein the special subframe comprises an uplink timeslot, a downlink timeslot and a guard period between the uplink and downlink timeslots.
44. The second radio network node (120) according to claim 43, wherein the configuration information indicates to the second radio network node (120) that the special subframe is to be configured according to a subframe configuration, wherein the processing circuit (1210) further is configured to configure the special subframe according to the subframe configuration indicated by the configuration information, wherein a first downlink timeslot of the first radio network node (110) is shorter than a second downlink timeslot of the second radio network node (120).
45. The second radio network node (120) according to any one of claim 37-44, wherein the processing circuit (1210) further is configured to receive a value of the interference; and adapt transmit power of the second radio network node (120) based on the value.
46. The second radio network node (120) according to any one of claims 45, wherein the value of the interference is represented by one or more of:
 - a Channel Quality Indicator,
 - a Signal-to-Interference-and-Noise-Ratio,
 - a Signal-to-Interference -Ratio, a Signal-to- Noise-Ratio,
 - a Reference Signal Received Power,
 - a Reference Signal Received Quality, and
 - a Received Signal Strength Indicator.





Fig. 1



1st radio network node



120




Fig. 2

		Radio Frame 0										
		0	1	2	3	4	5	6	7	8	9	
Cell 1		D	S	U	U	U	U	D	S	U	U	D
Cell 2		D	S	U	U	D	D	S	U	U	D	

Fig. 3

	Radio Frame m										Radio Frame k											
	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9		
Cell 1	D	S	U	U	D	U	D	S	U	U	D	...	D	S	U	U	D	D	S	U	U	D
Cell 2	D	S	U	U	D	D	S	U	U	D	...	D	S	U	U	D	U	D	S	U	U	D

Fig. 4

	Radio Frame m										Radio Frame k										
	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	
Cell 1	D	S	U	U	D	D	S	U	U	D	...	D	S	U	U	D	D	S	U	U	D
Cell 2	D	S	U	U	D	D	S	U	U	D	...	D	S	U	U	D	D	S	U	U	D

Fig. 5

		Radio Frame 0									
		0	1	2	3	4	5	6	7	8	9
Cell 1		D	S	U	U	U	D	S	U	U	D
Cell 2		D	S	U	U	D	D	S	U	U	D

Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10





Fig. 12

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2012/085238

A. CLASSIFICATION OF SUBJECT MATTER

H04W 24/08 (2009.01) i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: H04W, H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

VEN, USTXT, CNABS, CNKI, CNTXT: radio network node, enb, e-nb, base station, interference, disturbance, jam, measure, subframe, configuration information

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	CN 102387528 A (ZTE CORP) 21 March 2012 (21.03.2012) the whole document	1-46
A	CN 102652442 A (MEDIATEK INC) 29 August 2012 (29.08.2012) the whole document	1-46
A	WO 2012064070 A2 (SAMSUNG ELECTRONICS CO LTD) 18 May 2012 (18.05.2012) the whole document	1-46

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents:

“A” document defining the general state of the art which is not considered to be of particular relevance

“E” earlier application or patent but published on or after the international filing date

“L” document which may throw doubts on priority claim (S) or which is cited to establish the publication date of another citation or other special reason (as specified)

“O” document referring to an oral disclosure, use, exhibition or other means

“P” document published prior to the international filing date but later than the priority date claimed

“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

“&” document member of the same patent family

Date of the actual completion of the international search
23 August 2013(23.08.2013)

Date of mailing of the international search report
05 Sep. 2013 (05.09.2013)

Name and mailing address of the ISA/CN
The State Intellectual Property Office, the P.R.China
6 Xitucheng Rd., Jimen Bridge, Haidian District, Beijing, China
100088
Facsimile No. 86-10-62019451

Authorized officer
ZHANG Bingqing
Telephone No. (86-10)62411502

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/CN2012/085238

Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
CN 102387528 A	21.03.2012	None	
CN 102652442 A	29.08.2012	US 2012115469 A1	10.05.2012
		EP 2599343 A1	05.06.2013
		WO 2012062196 A1	18.05.2012
		TW 201225552 A	16.06.2012
WO 2012064070 A2	18.05.2012	KR 2012049449 A	17.05.2012
		WO 2012064070 A3	19.07.2012
		EP 2451234 A2	09.05.2012
		US 2012113812 A1	10.05.2012