










US 20120010633A1




(19) **United States**(12) **Patent Application Publication****Noda et al.**(10) **Pub. No.: US 2012/0010633 A1**(43) **Pub. Date: Jan. 12, 2012**(54) **DEVICES AND METHODS FOR SECURING
TISSUE****Publication Classification**(76) Inventors: **Wayne A. Noda**, Mission Viejo, CA
(US); **Stephen Graham Bell**, Rome
(IT)(51) **Int. Cl.**
A61B 17/10 (2006.01)(52) **U.S. Cl.** **606/140**(21) Appl. No.: **13/240,018**(57) **ABSTRACT**(22) Filed: **Sep. 22, 2011****Related U.S. Application Data**(63) Continuation of application No. 12/141,391, filed on
Jun. 18, 2008, now Pat. No. 8,062,308.(60) Provisional application No. 60/982,083, filed on Oct.
23, 2007, provisional application No. 61/012,124,
filed on Dec. 7, 2007.

A compression ring to grip and compress body structure such as diverticulum, hemorrhoids, and tissue adjacent a hole. A resilient ring-shaped body defines a compression channel, and one or more axially rigid elongated spikes extend from the body into the channel. The body defines a first axial segment surrounding the compression channel and a second axial segment surrounding the compression channel, with the spike being engaged only with the second axial segment. The first axial segment more tightly compresses the body structure than the second axial segment.












Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19




Figure 20




Figure 21




Figure 22




Figure 23




Figure 24




Figure 25




Figure 26

Figure 27




Figure 28



Figure 29




Figure 30




Figure 31




Figure 32




Figure 33




Figure 34




Figure 35




Figure 36

Figure 37




Figure 38




Figure 39




Figure 40




Figure 41




Figure 42




Figure 43




Figure 44




Figure 45




Figure 46




Figure 47




Figure 48




Figure 49




Figure 50




Figure 51




Figure 52




Figure 53




Figure 54





Figure 55




Figure 56




Figure 57




Figure 58




Figure 59




Figure 60

DEVICES AND METHODS FOR SECURING TISSUE

[0001] This application claims priority from U.S. provisional patent applications Ser. Nos. 60/982,083, filed Oct. 23, 2007 and 61/012,124, filed Dec. 7, 2007, both of which are incorporated herein by reference.

FIELD OF THE INVENTION

[0002] The present application relates generally to devices and methods for securing inverted tissue, and more particularly, though not exclusively, to securing inverted diverticulum serosa to serosa.

BACKGROUND OF THE INVENTION

[0003] Diverticulosis is an unfortunately common condition in which an area of the intestine bulges out into the peritoneal cavity to form a sac referred to as a "diverticulum". Diverticula are also formed when a point of weakness in the intestinal wall, e.g., where blood vessels take their entry, causes the muscular structure to divide and allows part of the inner mucosal membrane to be pushed out of the hole into the peritoneal cavity and become filled with fecal matter. Diverticula may also be present in other parts of the gastrointestinal tract such as the esophagus or the duodenum. A burst or leaky diverticulum results in the release of contaminants into the peritoneal cavity, potentially causing peritonitis.

[0004] A natural orifice-based method for resolving diverticulum is disclosed in the present assignee's co-pending U.S. patent application Ser. No. 11/788,597, filed Apr. 20, 2007, incorporated herein by reference. As understood herein, a diverticulum may be inverted into the bowel and tied off and either resected into a tube or allowed to slough off using natural orifice principles to avoid the complications inherent in other surgical methods. As further understood herein, for optimal closing the inverted diverticulum ideally is closed off serosa to serosa. As still further recognized by present principles, a diverticulum preferably is tightly and securely held closed off to alleviate the risk of peritonitis.

SUMMARY OF THE INVENTION

[0005] A method for treating a diverticulum formed in an intestinal wall of a patient includes advancing an applicator such as a tube into the intestine through a natural orifice to the site of the diverticulum. The method also includes inverting the diverticulum using the tube, and clamping the diverticulum with a resilient ring having one or more spikes that engage the diverticulum.

[0006] In some embodiments, intestinal wall tissue adjacent the diverticulum is held by the ring serosa to serosa. The ring may include a round resilient body defining an axial through-opening configured to receive the diverticulum, with the spikes extending from the body into the through-opening. The body can be defined by first and second portions that are coaxial to each other and offset from each other in the axial dimension defined by the body. The first portion is configured to compress the diverticulum a first magnitude and the second portion is configured to compress the diverticulum a second magnitude, with the first magnitude being greater than the second magnitude. The spikes preferably are engaged with

the second portion and no spike is engaged with the first portion. The ring is advanced onto the inverted diverticulum first portion first.

[0007] In some implementations, the first portion is defined by a first wall and the second portion is defined by a second wall, and the first wall is thicker than the second wall. In other implementations, the first portion is made of a first material and the second portion is made of a second material different than the first material.

[0008] The ring may be preloaded onto the tube and urged off the tube onto the diverticulum. Or, the rings can stay static and the tube retracted to release the rings. If desired, plural rings can be preloaded onto the tube. The ring can be preloaded onto the tube with the spike extending distal of the body, or the ring can be preloaded onto the tube with the spike extending proximal to the body. In some embodiments the ring is urged from a side opening in the tube onto the diverticulum.

[0009] The spikes may extend substantially across a diameter of the through-hole. Or, each spike may define an end disposed substantially in the center of the ring when the ring is relaxed. The ring may include tabs arranged on an outer periphery of the ring.

[0010] In still other embodiments, the spikes may be movable on the ring in the radial plane defined by the ring between a retracted position and an extended position. An actuating ring can be supplied to engage with the resilient ring to move the spike toward the extended position.

[0011] In another aspect, a tissue compressing device includes a round resilient body defining an axial central passage configured to receive tissue therein. At least one spike extends from the body into the central passage. The body is defined by at least first and second portions that are coaxial to each other and offset from each other in the axial dimension defined by the body. The first portion is configured to compress the diverticulum a first magnitude and the second portion is configured to compress the diverticulum a second magnitude, with the first magnitude being greater than the second magnitude.

[0012] In another aspect, a method for holding tissue together includes advancing into a patient through a natural orifice a closure ring including a resilient ring-shaped body defining a compression channel and at least one axially rigid elongated gripping element extending from the body into the channel. The method includes engaging the closure ring with body structure such that the gripping element penetrates the body structure and the body surrounds and compresses in the compression channel at least a part of the body structure. The body structure may be, without limitation, a diverticulum, a hemorrhoid, or tissue defining a tissue hole.

[0013] In another aspect, an apparatus includes a resilient ring-shaped body defining a compression channel. At least one axially rigid elongated gripping element extends from the body into the channel. The body defines a first axial segment surrounding the compression channel and a second axial segment surrounding the compression channel. The first axial segment is not engaged with the gripping element while the second axial segment is indeed engaged with the gripping element. The first axial segment more tightly compresses the body structure than the second axial segment.

[0014] A compression ridge can be molded into the ring, with the radius of curvature of the ridge being established as desired for achieving a desired rate of sloughing. A sharper

ridge causes the tissue to slough off faster, while a less sharp ridge allows greater time for serosa to serosa healing prior to sloughing.

[0015] The details of the present invention, both as to its structure and operation, can best be understood in reference to the accompanying drawings, in which like reference numerals refer to like parts, and in which:

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1 is a schematic view showing a tissue compression ring deployment mechanism including an overtube and colonoscope being advanced through the anus into the colon;

[0017] FIG. 2 is a schematic view showing the colonoscope advanced to a diverticulum;

[0018] FIG. 3 is a schematic view in partial cross-section showing a grasper being advanced out of the colonoscope into the diverticulum;

[0019] FIG. 4 is a schematic view in partial cross-section showing the grasper being retracted to invert the diverticulum, possibly aided by vacuum;

[0020] FIG. 5 is a schematic view in partial cross-section showing the grasper being retracted to more fully invert the diverticulum;

[0021] FIG. 6 is a schematic view in partial cross-section showing a compression ring just after it has been pushed off the end of the colonoscope onto the inverted diverticulum;

[0022] FIG. 7 is a schematic view in partial cross-section showing the compression ring on the inverted diverticulum in full side view;

[0023] FIG. 8 is a schematic view in partial cross-section showing a grasper being advanced out of the colonoscope into a relatively large diverticulum in which the overtube is advanced against the surrounding colonic wall and evacuated;

[0024] FIG. 9 is a perspective view of a non-limiting colonoscope with pre-loaded compression ring, illustrating one mechanism to push the ring off the scope, with the proximal portions of the scope cut away for clarity;

[0025] FIGS. 10-15 are side views of an alternate side-access compression ring deployment mechanism showing successive steps of using the alternate mechanism;

[0026] FIG. 16 is a partial cross-sectional view of an example compression ring;

[0027] FIG. 17 is a side view of the ring shown in FIG. 16 loaded onto a delivery tube, which could be established by a colonoscope, with the ring shown in cross-section;

[0028] FIG. 18 is a side view of the ring after being pushed off of the tube, with the ring shown in cross-section;

[0029] FIG. 19 is a cross-sectional view of an alternate compression ring;

[0030] FIG. 20 is a cross-sectional view of another alternate compression ring;

[0031] FIG. 21 is a cross-sectional view of yet another alternate compression ring;

[0032] FIG. 22 is a perspective view of a compression ring with four spikes;

[0033] FIG. 23 is a cross-sectional view of the ring shown in FIG. 22;

[0034] FIG. 24 is a perspective view of a compression ring with four spikes and optional manipulation tails on the outer periphery of the ring;

[0035] FIG. 25 is a perspective view of an alternate compression ring with overlapping spikes;

[0036] FIG. 26 is a partial cross-section of a compression ring loaded onto a delivery tube, with the spikes oriented distally on the tube;

[0037] FIGS. 27 and 28 are schematic views showing successive configurations of the ring shown in FIG. 26 as it is pushed onto a diverticulum;

[0038] FIG. 29 is a side view of a compression ring loaded onto a delivery tube, with the spikes oriented proximally on the tube;

[0039] FIGS. 30 and 31 are schematic views showing successive configurations of the ring shown in FIG. 29 as it is pushed onto a diverticulum;

[0040] FIG. 32 is a partial cross-sectional view of an alternate compression ring with axially movable spikes;

[0041] FIG. 33 is a cross-sectional view of an actuating ring to be used to move the spikes shown in FIG. 32;

[0042] FIG. 34 is a partial cross-sectional view showing the actuating ring surrounding the compression ring to drive the spikes inward;

[0043] FIG. 35 is a side view showing the compression ring of FIG. 32 pushed onto a diverticulum, with the diverticulum shown in partial phantom;

[0044] FIG. 36 is a side view showing the actuating ring pushed onto the compression ring, with the diverticulum shown in partial phantom;

[0045] FIGS. 37-43 are schematic side views of an alternate device for closing gastric openings, illustrating sequential steps in the process;

[0046] FIGS. 44-46 are side views in partial cross-section showing a hemorrhoid closure device;

[0047] FIG. 47 is a perspective view of a compression ring on an applicator with longitudinal slits to guide the spikes of the ring;

[0048] FIGS. 48 and 49 show compression rings that are not circular;

[0049] FIG. 50 is a perspective view of a distal portion of a side fire applicator;

[0050] FIGS. 51 and 52 show barbed spikes;

[0051] FIGS. 53-55 show curved spikes;

[0052] FIGS. 56-58 show various applicators that are not complete cylinders;

[0053] FIG. 59 shows an expandable applicator in a relaxed configuration; and

[0054] FIG. 60 shows the expandable applicator in an expanded configuration.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0055] Referring initially to FIG. 1, a catheter assembly is shown, generally designated 10, that includes a flexible hollow overtube 12 fixedly or slidably holding one or more components such as but not limited to an endoscope such as a colonoscope 14 that may have plural working channels. The overtube 12 may be transparent plastic. The overtube 12 with colonoscope 14 is configured for being advanced into the patient through a natural orifice, such as the anus 15. The colonoscope 14 may extend from the open distal end 16 of the overtube 12 as shown to a colonoscope control handle (not shown) that is external to the patient. In this way, for example, images of the colon 18 from the colonoscope 14 can be presented on a monitor 20 to a surgeon. Accordingly, it will be appreciated that the colonoscope 14 bears one or more light guides 22 such as optical fibers for imaging the interior of the patient. The colonoscope 14 may extend through a working

lumen of the overtube 12. Additional components may extend through additional working lumens and/or may be swapped according to the stage of the procedure for the colonoscope 14.

[0056] As intended herein, the overtube 12 can be flexible and can be sized as appropriate for the patient, e.g., shorter and radially smaller overtubes can be provided for pediatric patients. Although not shown in FIG. 1, the open distal end 16 of the overtube 12 may be tapered into a frusto-conical shape to reduce the risk that parts of the colon wall may become trapped between the overtube 12 and the colonoscope 14 during advancement of the overtube 12. Also, the inner surface of the overtube 12 can be coated with a lubricious material to ensure smooth advancement of the overtube 12 over the colonoscope 14.

[0057] In one non-limiting procedure, the catheter assembly 10 is advanced through the anus 15 into the colon 18 to an area of diverticulum disease, i.e., to a diverticulum 24. Due to the nature and location of the diverticulum 24, the assembly 10 may be guided by an imaging system—optical or radiography (colonoscope, gastroscope, radiologically or a combination thereof). Alternatively, the catheter can be advanced into the small intestine through the esophagus, in which case upper GI imaging and enteroscopy may be used to guide the catheter. Present principles may also be employed to use the below-described compression rings to close off hemorrhoids, close openings in tissue, etc.

[0058] The overtube 12 is typically advanced together with the colonoscope 14. When the distal end 16 of the overtube 12 is kept behind the tip of the colonoscope 14, the colonoscope 14 has full maneuverability. During colonoscopy, air or some other gas may be used if desired to insufflate the otherwise collapsed colon.

[0059] To enhance locating diverticulum, a barium study can first be employed to ascertain the number and location of diverticulum prior to diverticulectomy. Alternatively, contrast media can be flushed into the colonic lumen during colonoscopy.

[0060] Turning to FIG. 2, the overtube 12 is positioned adjacent to a diverticulum 24 and then the colonoscope 14 advanced to the diverticulum 24 as shown. Referring to FIG. 3, the distal end of the colonoscope 14 may be formed with or engaged with a load collar 26 that bears one or more compression rings 28, as well as, in some embodiments, a pushing element 30 for pushing the rings 28 one at a time off the collar 26 as either the pushing element is slid distally on the scope or the scope is pulled proximally relative to the pushing element. With the distal end of the collar 26 forming a seal against tissue surrounding the diverticulum, if desired a vacuum may be established in the colonoscope 14 to urge the diverticulum into the colonoscope. When a separate applicator other than the scope is used, this comment applies to the separate applicator. Additionally or in lieu of a vacuum, an applicator such as but not limited to an inversion tube 32 may be advanced out of a working channel of the colonoscope 14 and into the diverticulum 24, and gripping structure such as a corkscrew element 34 used to grip the diverticulum 24.

[0061] FIGS. 4 and 5 show successive locations of the diverticulum 24 as the inversion tube 32 is retracted (and/or as vacuum is drawn in the colonoscope 14), inverting the diverticulum 24 into the colonoscope 14. Then, the pushing element 30 is actuated to push the distal-most compression ring 28 onto the diverticulum 24 as shown, with substantially all of the diverticulum 24 pulled proximal to the ring 28.

[0062] It is now to be appreciated that in the relaxed state, the ring 28 assumes a radially smaller configuration (as shown for the distal-most ring 28 in FIG. 6 as engaged with the diverticulum), and is resilient so that it can be stretched to a radially enlarged state to fit onto the collar 26 (as shown for the proximal ring 28 in FIG. 6). FIG. 7 shows that in side view, the ring 28 that engages the diverticulum 24 surrounds and compresses the diverticulum 24. Because the diverticulum 24 is compressed in its inverted state, it is closed off serosa to serosa. Further details of example embodiments of the compression ring 28 are set forth further below.

[0063] FIG. 8 shows that for a relatively large diverticulum 24a, instead of inversion by evacuating the colonoscope 14, the overtube 12 may be positioned against tissue surrounding the diverticulum 24a and evacuated to aid in inverting the diverticulum 24a.

[0064] FIG. 9 shows an example non-limiting embodiment of the pushing element 30. While the pushing element 30 of FIG. 9 envisions the pushing element 30 moving distally to push the rings 28 off the distal end of the colonoscope 14 as the colonoscope 14 remains stationary, in other implementations the pushing element 30 may simply prevent the rings 28 from moving with the colonoscope 14 as the colonoscope 14 is retracted proximally. Additional details of non-limiting example pushing elements that may be used are disclosed in the following U.S. patents, incorporated herein by reference: U.S. Pat. Nos. 5,320,630; 5,423,834; 5,423,834; 5,735,861; 5,462,559; 5,624,453; 6,007,551; 6,149,659; 6,565,578.

[0065] As shown in FIG. 9, in one specific example of the pushing element 30 designated 30a in FIG. 9, a movable proximal ring 36 can slide on the colonoscope 14 and an anchor ring 38 can be affixed to the colonoscope 14. The pushing element 30a can also include a movable distal ring 40 that can slide on a reduced diameter extension of the anchor ring 38.

[0066] One or more axially rigid push rods 42 extend from the proximal ring 36, through respective channels of the anchor ring 38, and to the distal ring 40. A flexible actuating wire or cord 44 has its proximal end (not shown) disposed outside the patient and its distal end affixed to the proximal ring 36 as shown. The wire or cord 44 extends around a pulley element 46 (shown in phantom in FIG. 9) that is engaged with the anchor ring 38.

[0067] With this structure, it may readily be appreciated that the wire or cord 44 can be pulled proximally to move the proximal ring 36 distally on the colonoscope 14. In turn, owing to the axially rigid push rods 42, the distal ring 40 is moved distally against the compression rings 28, pushing the distal-most compression ring 28 off the end of the colonoscope 14. Once released, the compression ring assumes the relaxed, radially smaller configuration discussed above in which the compression ring 28 surrounds and compresses tissue such as the diverticulum 24.

[0068] Before discussing details of preferred non-limiting compression rings, attention is first drawn to FIGS. 10-15 to illustrate that a compression ring 28 may be advanced out of a side opening 46 of an elongated flexible tube 48 toward a diverticulum 24. As shown in FIG. 10, the compression ring 28 is preloaded in an expanded configuration onto a cylinder 50 in the tube 48. An axially rigid reciprocating actuator rod 52 with ramped surface 54 is disposed in the tube 48 adjacent the cylinder 50.

[0069] As shown in FIG. 11, the interior of the tube 48 may be evacuated to invert the diverticulum 24 through the cylin-

der 50 into the colonoscope. Then, as illustrated in FIG. 12 the actuator rod 52 can be moved distally in the tube 48, causing the ramped surface 54 to ride against the compression ring 28, thereby urging the compression ring 28 off the cylinder 50. As the compression ring 28 clears the cylinder 50 it assumes its relaxed, radially smaller configuration around the diverticulum 24 adjacent the colonic wall as shown, compressing the diverticulum 24.

[0070] FIG. 13 shows that in addition to or in lieu of vacuum, a grasping device 56 may be advanced in the tube 48 to mechanically grasp and invert the diverticulum 24. The grasping device 56 shown in FIG. 13 has opposed distal pivoting clasp arms 58 that clasp the diverticulum 24 between them. Alternatively, in lieu of clasp arms, the grasping device 56 may have a barbed or pronged distal element to pierce the tissue.

[0071] To further effect inversion and serosa to serosa approximation, the grasping device 56 shown in FIG. 14 can have a barbed or pronged distal element 62 that may be twisted to pull the diverticulum 24 into the tube 48. As shown in FIG. 15, once the diverticulum 24 is inverted the actuator rod 52 is operated as described above to push the compression ring 28 onto the diverticulum 24.

[0072] Attention is now drawn to various details of embodiments of the compression ring 28. Beginning with FIGS. 16-18, the compression ring 28 includes a resilient expandable plastic or rubber ring-shaped body 64 defining a compression channel 66 that extends axially entirely through the body 64. The body 64 defines a first axial segment 64a that completely surrounds the compression channel 66 as shown. Also, the body 64 defines a second axial segment 64b that is contiguous to the first axial segment 64a and that also completely surrounds the compression channel 66. The body 64 may be made of a drug eluting material. The second axial segment 64b can be regarded as a compression ridge that can be formed or molded into the ring, with the radius of curvature of the ridge being established as desired for achieving a desired rate of sloughing. A sharper ridge causes the tissue to slough off faster, while a less sharp ridge allows greater time for serosa to serosa healing prior to sloughing.

[0073] When the body is drug eluting material, it can be coated with and then elute drugs such as antiinflammatories, antibiotics, antibacterial drugs, and tissue healing factors. The drug coating can include a bioabsorbable polymer that is loaded with the drug that releases over time.

[0074] In one implementation, for example, the body 64 and/or below-described gripping elements such as spikes may be coated with a polymer such as Polyglycolic-Lactic Acid (PGLA) layers. The layers may be, e.g., bonded to the spikes. The PGLA can be loaded with a carrier drug that elutes as the PGLA absorbs. PGLA can be solubilized in a vapor form by dissolving it in a solvent such as, e.g., dimethyl formamide (DMF). This composition can then have the required drug added, and then sprayed in layer coatings onto the spike or the body. The dosage can be by weight. Furthermore, antimicrobials, anti-inflammatories, heavy weight proteins such as tissue growth factors, etc. may also be mixed into the composition to help with wound healing. The drug eluting coating can be applied with no primer and then heat set onto the spikes or ring.

[0075] As shown in FIG. 16, one or more axially rigid elongated gripping elements 70 such as spikes extend from the body 64 into the channel 66. The gripping elements 70 may have flat heads 71 as shown to establish a generally "T"

shape or, as disclosed below, the heads may be rounded, e.g., hemispherical so that the ring material can impart optimal tissue penetrating force to the gripping elements 71, and to allow the ring material to better control the rotation and orientation of the gripping element 70. The gripping elements 70 may be molded into the body 64.

[0076] In the embodiment shown in FIG. 16 the first axial segment 64a is not engaged with any gripping element 70, while the second axial segment 64b is engaged with the gripping elements 70 by, e.g., embedding or overmolding or otherwise coupling the gripping elements 70 with the second axial segment 64b. The first axial segment 64a may more tightly compress body structure such as diverticulum than the second axial segment 64b. In the non-limiting embodiment shown in FIGS. 16-18, this is effected by making the wall of the first axial segment 64a thicker than the wall of the second axial segment 64b as shown, and more particularly by configuring the first axial segment 64a with a smaller inside diameter than the second axial segment 64b. While FIGS. 16-18 show that the first axial segment 64a and second axial segment 64b are made integrally, they may be separately and juxtaposed with each other.

[0077] FIG. 16 shows the compression ring 16 in the relaxed configuration, in which the diameter of the compression channel 66 is relatively small and in which the axial gripping elements 70 are oriented substantially perpendicularly to the axis defined by the body 64. In contrast, FIG. 17 shows the compression ring 28 loaded onto a tube 72 such as the colonoscope 14 discussed above, wherein the configuration of the compression ring 28 is radially enlarged such that the ring 28 closely surrounds the tube 70. In other words, the inside diameter of the compression channel 66 is smaller than the outside diameter of the tube 72 when the ring 28 is in the relaxed configuration, and the ring 28 is deformably stretched such that the inside diameter of the ring 28 is equal to the outside diameter of the tube 72 when the ring is engaged with the tube 72.

[0078] Also, in the embodiment shown in FIG. 17, the gripping elements 70 extend in a proximal orientation relative to the body 64 of the ring 28, although as discussed below the elements 70 may be oriented distally. Thus, not only is the ring 28 radially stretched to fit onto the tube 72, but it is twisted about its circumference as well.

[0079] With this in mind, it may be appreciated in reference to FIG. 18 that when the compression ring is pushed off the tube onto, e.g., the diverticulum 24, the ring 28 collapses around the diverticulum 24 as the ring assumes the relaxed configuration, with the diverticulum 24 captured and compressed in the compression channel 66. Furthermore, owing to its material bias the ring 28 twists about its circumference into the relaxed configuration, wherein the gripping elements 70 extend perpendicularly to the compression channel 66, penetrating the tissue as shown in FIG. 18 owing to the hoop strength of the compression ring.

[0080] Still further, as mentioned above the first axial segment 64a of the ring 28 grips the tissue more tightly than the second axial segment 64b. Thus, particularly in the case of diverticulum, contaminant substances that might otherwise pass through tissue perforations that may be caused by the gripping elements 70 are sealed from the peritoneum by the tight closure afforded by the first axial segment 64a.

[0081] FIG. 19 shows a compression ring 74 with a resilient body defining a substantially continuously tapered inner annular surface 76, with gripping elements 78 being engaged

with a wider axial segment of the ring **74** as shown and with no gripping elements **78** being engaged with a narrower axial segment of the ring **74** as shown. The taper of the surface **76** also facilitates loading the ring **74** onto a delivery tube and releasing the ring from the tube. Also, the taper provides a rolling action upon release for driving the gripping elements **78** into tissue.

[0082] On the other hand, FIG. **20**, which shows only half of a compression ring **80** in cross-section, shows that a first axial segment **82** may be established by a first material and a second axial segment **84** may be established by a second, different material. The second segment **84** is engaged with gripping elements **86**. The second material may be softer and/or thinner than the first material, which in any case affords greater compression than the second material. By making the first material (in which the gripping elements **86** are embedded) softer than the second material, the risk of ripping or other damage to the second axial segment **84** from relative motion with the gripping elements **86** when the ring **80** changes configurations is reduced. The two materials may be molded into one compression ring **80** using multiple molding steps.

[0083] FIG. **21** shows a compression ring **88** (omitting the gripping elements for clarity) that in all substantial respects may be identical to any of the compression rings discussed above, except that the compression ring **88** may have a flat, rectangular shaped exterior surface **90**.

[0084] FIGS. **22** and **23** show a compression ring **92** in which four tissue spikes **94** are equidistantly radially spaced and extend into the compression channel, with the ends of the spikes **94** meeting substantially in the center (axis) of the channel. FIG. **24** shows that a compression ring **96** with interior spikes **98** may also be formed around its outer periphery with tabs or tails **100** for facilitating gripping and/or manipulating the compression ring **96** onto a delivery tube.

[0085] In another alternate embodiment, FIG. **25** shows a compression ring **102** in which each spikes **104** extends substantially across the diameter of the compression channel formed by the ring **102**.

[0086] As discussed above, while the gripping elements of the compression ring may be oriented proximally on the delivery tube, they alternately may be oriented distally as shown in FIG. **26**, in which gripping elements **106** of a compression ring **108** are oriented distally on a delivery tube **110**. FIGS. **27** and **28** illustrate that when the compression ring **108** is engaged with body structure, the elements **106** rotate to a position in which they are perpendicular to the axis of the ring to penetrate and grip the tissue.

[0087] FIGS. **29-31** illustrate the proximal orientation of gripping elements **112** of a compression ring **114** on a delivery tube **116**. In this orientation, not only the material bias of the ring **114** but the relaxing action of the diverticulum **24** toward the right in FIGS. **29-31** tend to move the gripping elements **112** back to the perpendicular (relaxed) orientation shown in FIG. **31**.

[0088] While the compression rings disclosed above have gripping elements that are affixed within the ring bodies, FIGS. **32-36** illustrate a compression ring **120** with resilient body **122** defining a ramped inside surface **124** in which axially rigid gripping elements **126** can move along their respective axes in respective channels **128** formed in the body **122**. As shown in FIG. **32**, the gripping elements **126** are initially positioned in a retracted position, in which the gripping elements **126** substantially do not extend into the com-

pression channel **130** of the ring **120**. Each gripping element **126** may have a rounded head **126a** if desired, and this configuration may be used on any of the gripping elements herein.

[0089] FIG. **33** shows a resilient actuating ring **132** with central opening **134** for receiving the compression ring **120** therein. The actuating ring **132** can be deformed to an expanded configuration to receive the compression ring **120** coaxially in the opening **134**. When the actuating ring **132** is released (FIG. **34**) it relaxes to a radially smaller configuration to urge the gripping elements **126** toward an extended position, in which the gripping elements **126** extend into the compression channel **130** to penetrate tissue disposed in the compression channel **130**.

[0090] FIGS. **35** and **36** further illustrate the above-described operation. With the compression ring **120** delivered over a delivery tube **136** onto tissue such as the diverticulum **24**, the actuating ring **132** is held in the expanded configuration on the tube **136** (FIG. **35**). The actuating ring is then pushed off of the tube **136** (FIG. **36**) to relax onto the compression ring, driving the gripping elements **126** into the diverticulum **24**.

[0091] As contemplated herein, diverticulum are not the only example of tissue that can be closed off using one of the present compression rings. As shown in FIGS. **37-43**, for example, tissue **140** defining a hole **142** can be held together to close the hole. The hole may be a defect in the tissue or a puncture in the tissue or otherwise require closure.

[0092] FIG. **37** shows that any one of the above-described compression rings, designated **144** in FIG. **37**, may be loaded onto an applicator tube **146** in which a hook control tube **148** is disposed. Plural elongated hooks **150** reciprocate in the hook tube **148**. When the applicator tube **146** is advanced to the hole **142**, the hook control tube **148** is retracted, the hooks **150** are advanced through the hole (FIG. **38**), and once the hook ends clear the hole the hooks **150** under material bias or mechanical actuation expand away from each other (FIG. **39**). The hook control tube **148** is advanced (FIG. **40**) and the applicator tube **146** advanced to the tissue **140** such that the tissue is pulled (FIG. **41**) into the applicator tube **146**. The compression ring **144** is then pushed off the applicator tube **146** (FIG. **42**) to gather and hold the tissue together, in the case of bowel tissue, serosa to serosa. If desired, electrocautery current can be applied to the hooks **150** (FIG. **43**) to release the hooks from the tissue. Or, the hooks may simply be retracted through the tissue. Yet again, the hooks may be made of elastic metal that permits them to straighten when pulled proximally, facilitating removal from the tissue.

[0093] FIGS. **44-46** show that any one of the above-described compression rings, designated **152** in FIG. **44**, may be loaded onto a delivery tube **154** to resolve a hemorrhoid **156**. The delivery tube **154** can be advanced to the hemorrhoid **156** and the tube evacuated to draw the hemorrhoid into the tube (FIG. **45**). The compression ring **152** is then pushed off the tube **154** to surround, compress, and close off the hemorrhoid **156** (FIG. **46**).

[0094] FIG. **47** shows a compression ring **200** expanded onto an applicator **202** that has longitudinal slits **204** formed in its outer surface, such that each spike **206** of the ring **200** can slide in a respective slit **204**. The slits maintain the spikes and guide the spikes as the ring is slid off the applicator.

[0095] FIG. **48** shows a compression ring **210** that is elliptical as shown, while FIG. **49** shows a compression ring **212** that is octagonal as shown.

[0096] FIG. 50 shows that an overtube 220 can be used to deliver an endoscope 222 that can be retroflexed as shown for viewing an applicator 224 with a side opening 226 through which a compression ring 228 can be delivered onto tissue.

[0097] If desired, the present compression ring body and/or spikes may be made of absorbable material such as PDS or magnesium so that the spikes could be slowly absorbed by the body over time.

[0098] As shown in FIGS. 51 and 52, any of the spikes shown herein can be textured as with one or more quills 230 to better grip tissue. The texturing can be done by mechanical cutting or laser etching to form a fenestrated surface angled in one direction to prevent tissue slippage.

[0099] Also, as shown in FIGS. 53-55, any of the spikes herein as shown at 232 can overlap each other and can curve upward with their free ends distanced from the radial plane of the ring when the ring is in the relaxed configuration (FIG. 53) so that the spikes do not unintentionally puncture tissue, moving toward the plane of the ring as shown in FIG. 55 when the ring is stretched. This also provides the ability to use longer spikes that do not pierce the opposite side of the ring from where they are molded, since the spike curve up and away from the radial plane in the relaxed configuration. FIG. 54 shows at 234 that the spikes may be curved but not overlap each other.

[0100] FIGS. 56-60 show that different size applicator tubes or an expandable applicator tube or an incomplete cylinder can be used to allow for expansion of the ring over various sizes of diverticulum. Specifically, FIG. 56 shows a tube 240 that defines about 0.9 of a full cylinder, with a slit 242 being formed in the tube, while FIG. 57 shows an applicator tube 244 that has an end ring 246 connected to plural long thin parallel applicator elements 248 such as rods to define an applicator tube structure. FIG. 58 shows that an applicator tube 250 may be established by two semi-cylindrical halves. Thus, an applicator tube can be a complete cylinder or a partially open cylinder with, e.g., an elongated open slit or even semicircular cross-sectional structure.

[0101] FIGS. 59 and 60 show an expandable delivery tube 260 onto which a spiked ring 262 can be mounted, with the tube 260 being expandable as shown in FIG. 6 by means of pushing a cross-bar 264 into the tube's diameter, to accommodate different sizes of diverticulum.

[0102] The rings can be loaded onto cartridges that in turn can be removably engaged with an applicator tube one at a time to permit removing a cartridge exhausted of rings and replacing it with a reloaded cartridge.

[0103] While the particular DEVICES AND METHODS FOR SECURING TISSUE are herein shown and described in detail, it is to be understood that the subject matter which is encompassed by the present invention is limited only by the claims.

1. A method for treating a diverticulum formed in an intestinal wall of a patient, comprising:

advancing an applicator into the intestine through a natural orifice to the site of the diverticulum;

inverting the diverticulum at least in part using the applicator; and

clamping the diverticulum with a resilient ring having at least one spike that engages the diverticulum, a distal end of the applicator being formed with or engaged with a collar that bears the ring, the ring being materially biased to a relaxed state, in which the ring assumes a radially smaller configuration, the ring being stretchable

to an enlarged state to fit onto the collar, the ring assuming the enlarged state when on the collar and assuming the relaxed state when urged off the collar and onto the diverticulum.

2. The method of claim 1, wherein intestinal wall tissue adjacent the diverticulum is held by the ring serosa to serosa.

3. The method of claim 1, wherein the ring comprises:

a round resilient body defining an axial through-opening configured to receive the diverticulum;

the at least one spike extending from the body into the through-opening, wherein

the body is defined by at least first and second portions that are coaxial to each other and offset from each other in the axial dimension defined by the body, the first portion configured to compress the diverticulum a first magnitude and the second portion configured to compress the diverticulum a second magnitude, the first magnitude being greater than the second magnitude.

4. The method of claim 1, wherein the spike is engaged with the second portion and no spike is engaged with the first portion, and the method further comprises:

advancing the ring onto the diverticulum first portion first.

5. The method of claim 1, wherein the first portion is defined by a first wall and the second portion is defined by a second wall, and the first wall is thicker than the second wall.

6. The method of claim 1, wherein the first portion is made of a first material and the second portion is made of a second material different than the first material.

7. The method of claim 1, comprising:

preloading the ring onto the applicator; and

urging the ring off the applicator onto the diverticulum.

8. The method of claim 7, comprising preloading plural rings onto the applicator.

9. The method of claim 1, wherein the ring is preloaded onto the applicator with the spike extending distal of the body.

10. The method of claim 1, wherein the ring is preloaded onto the applicator with the spike extending proximal to the body.

11. The method of claim 1, wherein the ring is urged from a side opening in the applicator onto the diverticulum.

12. The method of claim 1, wherein the ring comprises plural spikes.

13. The method of claim 1, wherein the at least one spike extends substantially across a diameter of the through-hole.

14. The method of claim 12, wherein each spike defines an end disposed substantially in the center of the ring when the ring is relaxed.

15. The method of claim 1, wherein the ring includes plural tabs arranged on an outer periphery of the ring.

16. The method of claim 1, wherein the spike is movable on the ring in the radial plane defined by the ring between a retracted position and an extended position, an actuating ring being engaged with the resilient ring to move the spike toward the extended position.

17. A tissue compressing device, comprising:

a round resilient body defining an axial central passage configured to receive tissue therein;

at least one spike extending from the body into the central passage, wherein

the body is defined by at least first and second portions that are coaxial to each other and offset from each other in the axial dimension defined by the body, the first portion configured to compress the diverticulum a first magnitude and the second portion configured to compress the

diverticulum a second magnitude, the first magnitude being greater than the second magnitude.

18. The tissue compressing device of claim **17**, wherein the spike is engaged with the second portion and no spike is engaged with the first portion.

19. The tissue compressing device of claim **18**, wherein the first portion is defined by a first wall and the second portion is defined by a second wall, and the first wall is thicker than the second wall.

20. The tissue compressing device of claim **18**, wherein the first portion is made of a first material and the second portion is made of a second material different than the first material.

21. The tissue compressing device of claim **17**, comprising: an applicator onto which the ring is preloaded in a radially expanded configuration.

22. The tissue compressing device of claim **21**, wherein the ring is preloaded onto the applicator with the spike extending distal of the body.

23. The tissue compressing device of claim **21**, wherein the ring is preloaded onto the applicator with the spike extending proximal to the body.

24. The tissue compressing device of claim **17**, wherein the ring comprises plural spikes.

25. The tissue compressing device of claim **17**, wherein the at least one spike extends substantially across a diameter of the central passage.

26. The tissue compressing device of claim **24**, wherein each spike defines an end disposed substantially in the center of the ring when the ring is relaxed.

27. The tissue compressing device of claim **17**, wherein the ring includes plural tabs arranged on an outer periphery of the ring.

28. The tissue compressing device of claim **17**, wherein the spike is movable on the ring in the radial plane defined by the ring between a retracted position and an extended position.

29. The tissue compressing device of claim **17**, wherein the spike includes at least one barb.

30. The tissue compressing device of claim **17**, wherein at least one of the spike or the body is coated for eluting a drug.

31. A method for holding tissue together, comprising: advancing into a patient through a natural orifice a closure ring including a resilient ring-shaped body defining a compression channel and at least one axially rigid elongated gripping element extending from the body into the channel;

engaging the closure ring with body structure such that the gripping element penetrates the body structure and the body surrounds and compresses in the compression channel at least a part of the body structure.

32. The method of claim **31**, wherein the body structure is a diverticulum.

33. The method of claim **31**, wherein the body structure is a hemorrhoid.

34. The method of claim **31**, wherein the body structure includes tissue defining a tissue hole.

35. The method of claim **31**, wherein the body defines a first axial segment surrounding the compression channel and a second axial segment surrounding the compression channel, the first axial segment not being engaged with the gripping element, the second axial segment being engaged with the gripping element, the first axial segment more tightly compressing the body structure than the second axial segment.

36. The method of claim **35**, wherein the first axial segment is defined by a first wall and the second axial segment is defined by a second wall, and the first wall is thicker than the second wall.

37. The method of claim **35**, wherein the first axial segment is made of a first material and the second axial segment is made of a second material different than the first material.

38. The method of claim **31**, comprising: preloading the ring onto an applicator; and urging the ring off the applicator onto the body structure.

39. The method of claim **38**, comprising preloading plural rings onto the applicator.

40. The method of claim **31**, wherein the ring is preloaded onto an applicator with the gripping element extending distal of the body.

41. The method of claim **31**, wherein the ring is preloaded onto an applicator with the gripping element extending proximal to the body.

42. The method of claim **31**, wherein the ring is urged from a side opening in an applicator onto the body structure.

43. The method of claim **31**, wherein the ring comprises plural gripping elements.

44. The method of claim **31**, wherein the at least one gripping element extends substantially across a diameter of the compression channel.

45. The method of claim **31**, wherein each gripping element defines an end disposed substantially in the center of the ring when the ring is relaxed.

46. The method of claim **31**, wherein the ring includes plural tabs arranged on an outer periphery of the body.

47. The method of claim **31**, wherein the gripping element is movable on the body in the radial plane defined by the ring between a retracted position and an extended position, an actuating ring being engaged with the closure ring to move the gripping element toward the extended position.

48. The method of claim **31**, wherein the gripping element includes at least one barb.

49. The method of claim **31**, wherein at least one of the gripping element or the ring is coated for eluting a drug.

50. Apparatus comprising: a resilient ring-shaped body defining a compression channel; and

at least one axially rigid elongated gripping element extending from the body into the channel, wherein the body defines a first axial segment surrounding the compression channel and a second axial segment surrounding the compression channel, the first axial segment not being engaged with the gripping element, the second axial segment being engaged with the gripping element, the first axial segment more tightly compressing the body structure than the second axial segment.

51. The apparatus of claim **50**, wherein the first axial segment is defined by a first wall and the second axial segment is defined by a second wall, and the first wall is thicker than the second wall.

52. The apparatus of claim **50**, wherein the first axial segment is made of a first material and the second axial segment is made of a second material different than the first material.

53. The apparatus of claim **50**, comprising an applicator onto which the ring is preloaded.

54. The apparatus of claim **53**, wherein the ring is preloaded onto the applicator with the gripping element extending distal of the body.

55. The apparatus of claim **53**, wherein the ring is pre-loaded onto the applicator with the gripping element extending proximal to the body.

56. The apparatus of claim **50**, wherein the ring comprises plural gripping elements.

57. The apparatus of claim **50**, wherein the at least one gripping element extends substantially across a diameter of the compression channel.

58. The apparatus of claim **56**, wherein each gripping element defines an end disposed substantially in the center of the ring when the ring is relaxed.

59. The apparatus of claim **50**, wherein the ring includes plural tabs arranged on an outer periphery of the body.

60. The apparatus of claim **50**, wherein the gripping element is movable on the body in the radial plane defined by the ring between a retracted position and an extended position, an

actuating ring being engaged with the closure ring to move the gripping element toward the extended position.

61. The apparatus of claim **50**, wherein the gripping element includes at least one barb.

62. The apparatus of claim **50**, wherein at least one of the gripping element or the body is coated for eluting a drug.

63. A method for treating a diverticulum formed in an intestinal wall of a patient, comprising:

advancing an applicator into the intestine through a natural orifice to the site of the diverticulum;

inverting the diverticulum at least in part using the applicator; and

clamping the diverticulum with a resilient ring having at least one spike that engages the diverticulum.

* * * * *