(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
6 February 2014 (06.02.2014)

WIPO | PCT

(10) International Publication Number
WO 2014/021979 A1

(51) International Patent Classification:
H04B 7/26 (2006.01) *H04W 80/02* (2009.01)

(21) International Application Number:
PCT/US2013/043261

(22) International Filing Date:
30 May 2013 (30.05.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/679,627 3 August 2012 (03.08.2012) US
13/728,658 27 December 2012 (27.12.2012) US

(71) Applicant: **INTEL CORPORATION** [US/US]; 2200 Mission College Blvd, M/S: RNB4-150, Santa Clara, California 95052 (US).

(72) Inventors; and
(71) Applicants : **KOC, Ali Taha** [TR/US]; 2356 NW Edinburg Dr., Hillsboro, Oregon 97124 (US). **JHA, Satish** [NP/US]; 2111 NE 25th Ave, Hillsboro, Oregon 97124 (US). **GUPTA, Maruti** [IN/US]; 1435 SW Montgomery Street, Portland, Oregon 97201 (US). **BANGOLAE, Sangeetha** [IN/US]; 15990 SW Catbird LN, Beaverton, Oregon 97007 (US). **TARRADELL, Marta Martinez** [ES/US]; 2111 NE 25th Avenue, Hillsboro, Oregon 97124 (US). **VANNITHAMBY, Rath** [CA/US]; 13470 Alvada St, Portland, Oregon 97229 (US).

(74) Agents: **PFLEGER, Edmund P.** et al.; Grossman, Tucker, Perreault & Pfleger, PLLC, 55 South Commercial Street, Manchester, New Hampshire 03101 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report (Art. 21(3))*

(54) **Title**: USER EQUIPMENT ASSISTANCE INFORMATION SIGNALING IN A WIRELESS NETWORK




FIG. 1

(57) **Abstract**: Generally, this disclosure provides apparatus and methods for improved signaling of User Equipment (UE) assistance information in a wireless network. The UE device may include a processing circuit configured to generate an assistance information message including a power preference indicator (PPI) and mobility state information (MSI), the PPI and the MSI associated with the UE; a signal generation module configured to generate a Medium Access Control (MAC) layer Control Element (CE) signal, the MAC CE signal including the assistance information message; and a transmitter circuit configured to transmit the MAC CE signal to an evolved Node B (eNB) of a wireless network associated with the UE, the MAC CE signal transmitted on an uplink shared channel (UL-SCH). The assistance information message may also be generated as a Radio Resource Control (RRC) message and transmitted on an uplink dedicated control channel (UL-DCCH).

WO 2014/021979 A1

USER EQUIPMENT ASSISTANCE INFORMATION SIGNALING IN A WIRELESS NETWORK

CROSS-REFENCE TO RELATED APPLICATIONS

The present patent application claims priority to U.S. Patent Application 13/728,658 filed December 27, 2012 and U.S. Provisional Patent Application Serial No. 61/679,627, filed August 3, 2012, the contents of which are incorporated herein by reference in their entirety.

FIELD

The present disclosure relates to wireless networks, and more particularly, to apparatus and methods for improved signaling of User Equipment (UE) assistance information in a wireless network.

BACKGROUND

In wireless networks, for example Long Term Evolution (LTE) and LTE-Advanced (LTE-A) networks, mobile communication devices, also referred to as User Equipment or UEs, operate within cellular coverage regions or cells. One or more base stations, also known as evolved Node B (eNB) transceivers, are typically associated with each cell. The eNBs communicate with and manage the UEs by monitoring UE status and adjusting configuration options and parameters associated with the UEs and/or the network to increase operational efficiency.

As network traffic increases, new system enhancements are being implemented in the LTE/LTE-A networks. Along with these enhancements, new forms of UE status information and operational preference indicators may need to be transmitted between the UE and the eNB. This additional information transfer, however, may have an adverse impact on signaling overhead and/or consume additional bandwidth, which is a limited resource.

BRIEF DESCRIPTION OF THE DRAWINGS

Features and advantages of embodiments of the claimed subject matter will become apparent as the following Detailed Description proceeds, and upon reference to the Drawings, wherein like numerals depict like parts, and in which:

Figure 1 illustrates a top level system diagram of one exemplary embodiment consistent with the present disclosure;

Figure 2 illustrates a block diagram of one exemplary embodiment consistent with the present disclosure;

Figure 3 illustrates a message structure associated with one exemplary embodiment consistent with the present disclosure;

Figure 4 illustrates a message flow diagram of an exemplary embodiment consistent with the present disclosure;

Figure 5 illustrates a data structure associated with one exemplary embodiment consistent with the present disclosure;

Figure 6 illustrates a data structure associated with another exemplary embodiment consistent with the present disclosure;

Figure 7 illustrates a data structure associated with another exemplary embodiment consistent with the present disclosure;

Figure 8 illustrates a data structure associated with another exemplary embodiment consistent with the present disclosure;

Figure 9 illustrates a data structure associated with another exemplary embodiment consistent with the present disclosure;

Figure 10 illustrates a flowchart of operations of an exemplary embodiment consistent with the present disclosure; and

Figure 11 illustrates a platform of one exemplary embodiment consistent with the present disclosure.

Although the following Detailed Description will proceed with reference being made to illustrative embodiments, many alternatives, modifications, and variations thereof will be apparent to those skilled in the art.

DETAILED DESCRIPTION

Generally, this disclosure provides apparatus and methods for improved signaling of User Equipment (UE) assistance information in a wireless network, for

example an LTE or LTE-A network. The UE (e.g., the mobile device) may be configured to generate a power preference indicator (PPI). The PPI may be associated with a tradeoff between UE power consumption and latency. The UE may also be configured to generate mobility state information (MSI). The MSI may be associated with a handover rate when the UE is in a connected state and a cell re-selection rate when the UE is in an idle state. The PPI and/or the MSI may be transmitted to an evolved Node B (eNB) in the form of a UE assistance information message that enables the network to configure Radio Resource Control (RRC) parameters to improve system/network performance.

In some embodiments, UE assistance information message may be transmitted as a Medium Access Control (MAC) layer Control Element (CE) signal on an uplink shared channel (UL-SCH). In some embodiments, UE assistance information message may be transmitted as a Radio Resource Control (RRC) message on an uplink dedicated control channel (UL-DCCH).

Figure 1 illustrates a top level system diagram 100 of one exemplary embodiment consistent with the present disclosure. A wireless network 108 is shown to include an eNB 104 and a UE 102. The eNB 104 may be serving the cell coverage area in which the UE 102 is operating. The UE 102 may be configured to transmit an assistance information message 106 to the eNB 104, as will be explained in greater detail below. The assistance information may include a PPI and an MSI associated with the UE 102 that enables the eNB 104 to configure RRC parameters to improve system/network performance. In some embodiments, the assistance information may further include a measurement or estimation of average packet inter-arrival time, background traffic versus active traffic, battery power level and/or any other suitable information..

The wireless network 108 may comply with, or otherwise be compatible with, the Third Generation Partnership Project (3GPP) Long Term Evolution (LTE) and/or LTE–Advanced (LTE-A) based wireless network standard, including current, previous and future versions of that standard. While this is a simplified example, for illustration purposes, it will be appreciated that in practice the network may comprise any number of eNBs and UEs deployed in any configuration.

Figure 2 illustrates a block diagram 200 of one exemplary embodiment consistent with the present disclosure. UE 102 is shown to comprise receiver circuit

202, processing circuit 204, transmitter circuit 206, signal generation module 208 and timer/counter circuit 210.

Processing circuit 204 may be configured to determine a power preference state for the UE 102. The power preference state may correspond to any of a range of values from a relatively low power consumption state to a relatively high power consumption state. The lower power preference state may offer the advantage of increased battery life, but this may come at the expense of certain degradations in device performance, such as, for example, increased communication latency. Conversely, a higher power preference state may provide increased device performance in exchange for a reduced battery life. Processing circuit 204 may generate a PPI to indicate the desired power preference state for the UE 102. In some embodiments, the PPI may represent or correspond to the actual desired power preference state or it may indicate the desire for a default state. In other embodiments, the PPI may represent a change in state (e.g., up or down) from the current state towards either end of the range of states.

Processing circuit 204 may also be configured to determine a mobility state of the UE 102. In some embodiments, the mobility state may represent the number of handovers of the UE per unit of time (e.g., a handover rate) during a time period in which the UE is in a connected state. In some embodiments, the mobility state may represent the number of cell re-selections of the UE per unit of time (e.g., a cell re-selection rate) during a time period in which the UE is in an idle state. An MSI may be generated to represent or quantify the mobility state within a range of values from a relatively low mobility (or no mobility) to a relatively high mobility. Processing circuit 204 may further be configured to generate an assistance information message (or information element) comprising the PPI and the MSI.

In some embodiments, signal generation module 208 may be configured to generate a MAC layer CE signal based on the assistance information message, as will be described in greater detail below. In these embodiments, transmitter circuit 206 may be configured to transmit the signal to an eNB 104 on a UL-SCH.

In some embodiments, signal generation module 208 may be configured to generate an RRC message based on the assistance information element, as will be described in greater detail below. In these embodiments, transmitter circuit 206 may be configured to transmit the RRC message to an eNB 104 on a UL-DCCH.

Receiver circuit 202 may be configured to receive a message from the eNB 104 in response to the transmission of the assistance information. The response may be an RRCConnectionReconfiguration message that includes updated discontinuous reception (DRX) configuration parameters that may be based on the PPI and MSI of the UE 102. The updated DRX parameters may enable more efficient UE operation such as increased conservation of battery power with affecting latency.

In some embodiments, the transmission of the assistance information to the eNB 104 may be repeated or re-transmitted until a response is received from the eNB. Timer/counter circuit 210 may be configured to impose a minimum time period or delay between consecutive re-transmissions of the assistance message. This minimum time period between re-transmissions may be set to a threshold value to reduce signaling overhead and increase bandwidth efficiency between the UE 102 and the eNB 104. In some embodiments, separate timers may be used for re-transmission of the PPI and re-transmission of the MSI. The timer/counter circuit 210 may further be configured to limit the total number of such re-transmissions since the eNB may choose not to respond to the assistance information. The timer delay threshold and maximum re-transmission threshold values may be set by the eNB and provided to the UE. In some embodiments, these values may be defined as an integer value common to each cell, an integer value defined for each RRC connection or an integer value defined for each assistance information trigger event (e.g., a UE transition out of an idle state or a change in UE power preference settings).

Figure 3 illustrates a message structure 300 associated with one exemplary embodiment consistent with the present disclosure. A MAC layer CE signal may comprise a MAC CE header and an optional payload. An existing MAC CE header format 302 is shown which includes a logic channel identifier (LCID) in bits 3-7. Bits 0 and 1 are reserved and bit 2 is an extension bit used to indicate the presence of an extended length header (using additional octets). LCIDs in the range from 01011 to 11000, inclusive, are reserved, so one or more of these values may be employed in a new MAC CE header format to indicate that the MAC CE signal is used to convey assistance information (AI). For example, an LCID value of 10111 may indicate that the new MAC CE header 304 includes an MSI in bit 0. As another example, an LCID value of 11000 may indicate that the new MAC CE header 306 includes a PPI in bit 0. As a further example, another selected LCID value from the reserved range may indicate that the new MAC CE header 308 includes both an MSI in bit 0 and a PPI in

bit 1. As yet a further example, another selected LCID value from the reserved range may indicate that the new MAC CE header 310 is accompanied by a single octet payload 312, 314 or 316. The payloads may include an MSI bit, a PPI bit or both. In some embodiments, the payload may allow the PPI and/or MSI to be represented by 2 or more bits (not shown) to provide additional levels within their respective range of values.

Figure 4 illustrates a message flow diagram 400 of an exemplary embodiment consistent with the present disclosure. The message flow diagram 400 provides an example of UE assistance information handling between UE 102 and eNB 104 through RRC message exchanges. The RRC message formats will be described in greater detail below. An initial connection 402 is established between the UE and eNB by sending an RRCConnectionRequest (or RCConnectionReestablishmentRequest) from the UE 102. The eNB then responds with an RRCConnectionSetup (or RRCConnectionReestablishment) message and the UE acknowledges setup completion with an RRCConnectionSetupComplete (or RRCConnectionReestablishmentComplete) message. At some later point in time, a UE assistance transmission is triggered 404. This may result, for example, from a UE transition out of an idle state to a connected state or by a change in UE power preference settings. The UE assistance information, in the form of an RRC message 406, is sent to the eNB. The eNB may respond with an RRCConnectionReconfiguration message that provides updated DRX configuration setting to the UE and the UE may acknowledge with an RRCConnectionReconfigurationComplete message.

Figures 5 through 9 illustrate data structures and/or message fields that may comply with, or otherwise be compatible with, the 3GPP LTE and/or LTE-A based wireless network standard, including current, previous and future versions of that standard.

Figure 5 illustrates a data structure 500 associated with one exemplary embodiment consistent with the present disclosure. The UE 102 may send the assistance information to the eNB 104 as an inclusion in any one of a number of different types of RRC messages which are transmitted on a UL-DCCH channel which conforms to the UL-DCCH message type 510. In some embodiments, the available existing RRC message types comprise RRCConnectionReestablishmentComplete 520, RRCConnectionSetupComplete 530

and UEInformationResponse-r9 540. In some embodiments, a new RRC message type, UEAssistanceInfoTransfer-r11 550, may be provided. The UEAssistanceInfoTransfer-r11 550 message may be provided as an additional choice information element, for example c2 560, in the UL-DCCH message structure.

Figure 6 illustrates a data structure 600 associated with another exemplary embodiment consistent with the present disclosure. The new UEAssistanceInfoTransfer-r11 550 message type is shown to include a UE-AssistanceInfo-r11 information element 610 which in turn comprises a power-Preference-Indication information element 620 and a mobility-State-Indication information element 630. The UEAssistanceInfoTransfer-r11 550 message may use signaling radio bearer 1 and Radio Link Control (RLC) Acknowledge Mode (AM) mode over logical channel DCCH.

Figure 7 illustrates a data structure 700 associated with another exemplary embodiment consistent with the present disclosure. The UEInformationResponse-r9 540 message type is shown to be modified to include the new UEInformationResponse-v11xx-IEs information element 710 which in turn includes the previously described UE-AssistanceInfo-r11 information element 610.

Figure 8 illustrates a data structure 800 associated with another exemplary embodiment consistent with the present disclosure. The RRCConnectionReestablishmentComplete 520 message type is shown to be modified to include the new RRCConnectionReestablishmentComplete-v11xx-IEs information element 810 which in turn includes the previously described UE-AssistanceInfo-r11 information element 610. This may provide a more efficient signaling mechanism for transmitting assistance information from the UE 102 to the eNB 104.

Figure 9 illustrates a data structure 900 associated with another exemplary embodiment consistent with the present disclosure. The RRCConnectionSetupComplete 530 message type is shown to be modified to include the new RRCConnectionSetupComplete-v11xx-IEs information element 910 which in turn includes the previously described UE-AssistanceInfo-r11 information element 610. This may provide a more efficient signaling mechanism for transmitting assistance information from the UE 102 to the eNB 104.

Figure 10 illustrates a flowchart of operations 1000 of an exemplary embodiment consistent with the present disclosure. At operation 1010, a power preference is determined for a UE. At operation 1020, a mobility state is determined

for the UE. The mobility state represents a handover rate associated with a UE connected state and a cell-reselection rate associate with a UE idle state. At operation 1030, a UE assistance information message is generated. The message includes the power preference and the mobility state. At operation 1040, the UE assistance information message is transmitted to an eNB of a wireless network associated with the UE. The message may be transmitted as a MAC CE signal on a UL-SCH channel or as an RRC message on a UL-DCCH channel.

Figure 11 illustrates a platform configuration 1100 of one exemplary embodiment consistent with the present disclosure. The platform 1110 may be a mobile communication device, such as, for example, a UE device (smartphone), a tablet, a laptop computing device or any other device configured to transmit or receive wireless signals. In some embodiments, platform 1110 may comprise a processor 1120, memory 1130, an input/output (I/O) system 1140, a display/keyboard or other type of user interface (UI) 1170 such as, for example, a touchscreen. Platform 1110 may further comprise a baseband processing module 1150 and an RF processing module 1160 as well as one or more antennas 1180 which may form part of a Multiple Input Multiple Output (MIMO) antenna system. Any number of platforms 1100 may transmit or receive signals through RF module 1160 and antennas 1180 over a wireless network which may be an LTE or LTE-A wireless network.

Embodiments of the methods described herein may be implemented in a system that includes one or more storage mediums having stored thereon, individually or in combination, instructions that when executed by one or more processors perform the methods. Here, the processor may include, for example, a system CPU (e.g., core processor) and/or programmable circuitry. Thus, it is intended that operations according to the methods described herein may be distributed across a plurality of physical devices, such as processing structures at several different physical locations. Also, it is intended that the method operations may be performed individually or in a subcombination, as would be understood by one skilled in the art. Thus, not all of the operations of each of the flow charts need to be performed, and the present disclosure expressly intends that all subcombinations of such operations are enabled as would be understood by one of ordinary skill in the art.

The storage medium may include any type of tangible medium, for example, any type of disk including floppy disks, optical disks, compact disk read-only memories (CD-ROMs), compact disk rewritables (CD-RWs), digital versatile disks

(DVDs) and magneto-optical disks, semiconductor devices such as read-only memories (ROMs), random access memories (RAMs) such as dynamic and static RAMs, erasable programmable read-only memories (EPROMs), electrically erasable programmable read-only memories (EEPROMs), flash memories, magnetic or optical cards, or any type of media suitable for storing electronic instructions.

"Circuitry", as used in any embodiment herein, may comprise, for example, singly or in any combination, hardwired circuitry, programmable circuitry, state machine circuitry, and/or firmware that stores instructions executed by programmable circuitry. An app may be embodied as code or instructions which may be executed on programmable circuitry such as a host processor or other programmable circuitry. A module, as used in any embodiment herein, may be embodied as circuitry. The circuitry may be embodied as an integrated circuit, such as an integrated circuit chip.

Thus, the present disclosure provides apparatus and methods for improved signaling of User Equipment (UE) assistance information in a wireless network.

According to one aspect there is provided a UE. The UE may include a processing circuit configured to generate an assistance information message including a PPI and an MSI, the PPI and the MSI associated with the UE. The UE of this example may also include a signal generation module configured to generate a MAC layer CE signal, the MAC CE signal including the assistance information message. The UE of this example may further include a transmitter circuit configured to transmit the MAC CE signal to an eNB of a wireless network associated with the UE, the MAC CE signal transmitted on a UL-SCH.

Another example UE includes the forgoing components and further includes a receiver circuit configured to receive an RRCConnectionReconfiguration message from the eNB in response to the MAC CE signal transmission, the RRCConnectionReconfiguration message including DRX configuration parameters.

Another example UE includes the forgoing components and further includes a timer circuit configured to delay transmission of the MAC CE signal such that the time period between consecutive transmissions of the MAC CE signal exceeds a minimum elapsed time threshold.

Another example UE includes the forgoing components and further includes a counter circuit configured to limit the number of consecutive transmissions of the MAC CE signal to a maximum threshold value, the counter circuit reset in response to

receiving a reply from the eNB, the reply in response to the transmitted MAC CE signal.

Another example UE includes the forgoing components and the PPI represents a UE power preference state, the state being a lower power configuration state or a lower latency configuration state.

Another example UE includes the forgoing components and the PPI represents a UE power preference state change, the state change between a lower power configuration state and a lower latency configuration state.

Another example UE includes the forgoing components and the MSI represents a handover rate associated with a UE connected state and a cell-reselection rate associated with a UE idle state.

Another example UE includes the forgoing components and further includes memory coupled to the processing circuit, an I/O system coupled to the processing circuit, and a touchscreen display coupled to the I/O system.

According to another aspect there is provided a UE. The UE may include a processing circuit configured to generate a UE assistance information element including a PPI and an MSI, the PPI and the MSI associated with the UE. The UE of this example may also include a signal generation module configured to generate an RRC message, the RRC message including the UE assistance information element. The UE of this example may further include a transmitter circuit configured to transmit the RRC message to an eNB of a wireless network associated with the UE, the RRC message transmitted on a UL-DCCH.

Another example UE includes the forgoing components and further includes a receiver circuit configured to receive an RRCConnectionReconfiguration message from the eNB in response to the RRC message transmission, the RRCConnectionReconfiguration message including DRX configuration parameters.

Another example UE includes the forgoing components and the RRC message is an rrcConnectionReestablishmentComplete message, an rrcConnectionSetupComplete message and/or a ueInformationResponse-r9 message.

Another example UE includes the forgoing components and the RRC message is a UEAssistanceInfoTransfer-r11 message.

Another example UE includes the forgoing components and further includes a timer circuit configured to delay transmission of the RRC message such that the time

period between consecutive transmissions of the RRC message exceeds a minimum elapsed time threshold.

Another example UE includes the forgoing components and further includes a counter circuit configured to limit the number of consecutive transmissions of the RRC message to a maximum threshold value, the counter circuit reset in response to receiving a reply from the eNB, the reply in response to the transmitted RRC message.

Another example UE includes the forgoing components and the PPI represents a UE power preference state, the state being a lower power configuration state or a lower latency configuration state.

Another example UE includes the forgoing components and the PPI represents a UE power preference state change, the state change between a lower power configuration state and a lower latency configuration state.

Another example UE includes the forgoing components and the MSI represents a handover rate associated with a UE connected state and a cell-reselection rate associated with a UE idle state.

Another example UE includes the forgoing components and further includes memory coupled to the processing circuit, an I/O system coupled to the processing circuit, and a touchscreen display coupled to the I/O system.

According to another aspect there is provided a method. The method may include determining a power preference for a UE. The method of this example may also include determining a mobility state for the UE, the mobility state representing a handover rate associated with a UE connected state and a cell-reselection rate associated with a UE idle state. The method of this example may further include generating a UE assistance information message, the message including the power preference and the mobility state. The method of this example may further include transmitting the UE assistance information message to an eNB of a wireless network associated with the UE.

Another example method includes the forgoing operations and further includes transmitting the UE assistance information message as a MAC layer CE signal on a UL-SCH.

Another example method includes the forgoing operations and further includes transmitting the UE assistance information message as an RRC message on a UL-DCCH.

Another example method includes the forgoing operations and the RRC message is an rrcConnectionReestablishmentComplete message, an rrcConnectionSetupComplete message, a ueInformationResponse-r9 message, and/or a UEAssistanceInfoTransfer-r11 message.

Another example method includes the forgoing operations and further includes receiving an RRCConnectionReconfiguration message from the eNB in response to the UE assistance information message transmission, the RRCConnectionReconfiguration message including DRX configuration parameters.

Another example method includes the forgoing operations and the power preference is a lower power configuration state or a lower latency configuration state.

The terms and expressions which have been employed herein are used as terms of description and not of limitation, and there is no intention, in the use of such terms and expressions, of excluding any equivalents of the features shown and described (or portions thereof), and it is recognized that various modifications are possible within the scope of the claims. Accordingly, the claims are intended to cover all such equivalents. Various features, aspects, and embodiments have been described herein. The features, aspects, and embodiments are susceptible to combination with one another as well as to variation and modification, as will be understood by those having skill in the art. The present disclosure should, therefore, be considered to encompass such combinations, variations, and modifications.

CLAIMS

What is claimed is:

1. User Equipment (UE) comprising:

a processing circuit configured to generate an assistance information message comprising a power preference indicator (PPI) and mobility state information (MSI), said PPI and said MSI associated with said UE;

a signal generation module configured to generate a Medium Access Control (MAC) layer Control Element (CE) signal, said MAC CE signal comprising said assistance information message; and

a transmitter circuit configured to transmit said MAC CE signal to an evolved Node B (eNB) of a wireless network associated with said UE, said MAC CE signal transmitted on an uplink shared channel (UL-SCH).

2. The UE of claim 1, further comprising a receiver circuit configured to receive an RRCConnectionReconfiguration message from said eNB in response to said MAC CE signal transmission, said RRCConnectionReconfiguration message comprising discontinuous reception (DRX) configuration parameters.

3. The UE of claim 1 or 2, further comprising a timer circuit configured to delay transmission of said MAC CE signal such that the time period between consecutive transmissions of said MAC CE signal exceeds a minimum elapsed time threshold.

4. The UE of claim 1 or 2, further comprising a counter circuit configured to limit the number of consecutive transmissions of said MAC CE signal to a maximum threshold value, said counter circuit reset in response to receiving a reply from said eNB, said reply in response to said transmitted MAC CE signal.

5. The UE of any of claims 1 through 4, wherein said PPI represents a UE power preference state and said state is a lower power configuration state or a lower latency configuration state.

6. The UE of any of claims 1 through 4, wherein said PPI represents a UE power preference state change, said state change between a lower power configuration state and a lower latency configuration state.

7. The UE of any of claims 1 through 4, wherein said MSI represents a handover rate associated with a UE connected state and a cell-reselection rate associated with a UE idle state.

8. The UE of any of claims 1 through 7, further comprising memory coupled to said processing circuit, an input/output (I/O) system coupled to said processing circuit, and a touchscreen display coupled to said I/O system.

9. User Equipment (UE) comprising:

a processing circuit configured to generate a UE assistance information element comprising a power preference indicator (PPI) and mobility state information (MSI), said PPI and said MSI associated with said UE;

a signal generation module configured to generate a Radio Resource Control (RRC) message, said RRC message comprising said UE assistance information element; and

a transmitter circuit configured to transmit said RRC message to an evolved Node B (eNB) of a wireless network associated with said UE, said RRC message transmitted on an uplink dedicated control channel (UL-DCCH).

10. The UE of claim 9, further comprising a receiver circuit configured to receive an RRCConnectionReconfiguration message from said eNB in response to said RRC message transmission, said RRCConnectionReconfiguration message comprising discontinuous reception (DRX) configuration parameters.

11. The UE of claim 9 or 10, wherein said RRC message is an rrcConnectionReestablishmentComplete message, an rrcConnectionSetupComplete message and/or a ueInformationResponse-r9 message.

12. The UE of claim 9 or 10, wherein said RRC message is a UEAssistanceInfoTransfer-r11 message.

13. The UE of claim 9 or 10, further comprising a timer circuit configured to delay transmission of said RRC message such that the time period between consecutive transmissions of said RRC message exceeds a minimum elapsed time threshold.

14. The UE of claim 9 or 10, further comprising a counter circuit configured to limit the number of consecutive transmissions of said RRC message to a maximum threshold value, said counter circuit reset in response to receiving a reply from said eNB, said reply in response to said transmitted RRC message.

15. The UE of claim 9 or 10, wherein said PPI represents a UE power preference state and said state is a lower power configuration state or a lower latency configuration state.

16. The UE of claim 9 or 10, wherein said PPI represents a UE power preference state change, said state change between a lower power configuration state and a lower latency configuration state.

17. The UE of claim 9 or 10, wherein said MSI represents a handover rate associated with a UE connected state and a cell-reselection rate associated with a UE idle state.

18. The UE any of claims 9 through 17, further comprising memory coupled to said processing circuit, an input/output (I/O) system coupled to said processing circuit, and a touchscreen display coupled to said I/O system.

19. A method comprising:

determining a power preference for a User Equipment (UE);

determining a mobility state for said UE, said mobility state representing a handover rate associated with a UE connected state and a cell-reselection rate associated with a UE idle state;

generating a UE assistance information message, said message comprising said power preference and said mobility state; and

transmitting said UE assistance information message to an evolved Node B (eNB) of a wireless network associated with said UE.

20. The method of claim 19, further comprising transmitting said UE assistance information message as a Medium Access Control (MAC) layer Control Element (CE) signal on an uplink shared channel (UL-SCH).

21. The method of claim 19, further comprising transmitting said UE assistance information message as a Radio Resource Control (RRC) message on an uplink dedicated control channel (UL-DCCH).

22. The method of claim 19 or 21, wherein said RRC message is an rrcConnectionReestablishmentComplete message, an rrcConnectionSetupComplete message, a ueInformationResponse-r9 message, and/or a UEAssistanceInfoTransfer-r11 message.

23. The method of any of claims 19 through 22, further comprising receiving an RRCConnectionReconfiguration message from said eNB in response to said UE assistance information message transmission, said RRCConnectionReconfiguration message comprising discontinuous reception (DRX) configuration parameters.

24. The method of any of claims 19 through 23, wherein said power preference is a lower power configuration state or a lower latency configuration state.



100
Wireless Network
108
eNB
104
Assistance Information
106
UE
102

FIG. 1



200
UE
102
Receiver Circuit
202
Processing
Circuit
204
Transmitter
Circuit
206
Signal
Generation
Module
208
Timer/Counter
Circuit
210

FIG. 2



300
0 1 2 3 4 5 6 7
R R E LCID
MAC CE Header 302
0 1 2 3 4 5 6 7
M R E LCID = an AI value
New MAC CE Header 304
P R E LCID = an AI value
New MAC CE Header 306
M P E LCID = an AI value
New MAC CE Header 308
0 1 2 3 4 5 6 7
R R E LCID = an AI value
New MAC CE Header 310
R M
New MAC CE Payload 312
R P
New MAC CE Payload 314
R M P
New MAC CE Payload 316

FIG. 3

400



UE
102
eNB
104
RRCConnectionRequest
(RRCConnectionReestablishmentRequest)
402
RRCConnectionSetup
(RRCConnectionReestablishment)
RRCConnectionSetupComplete
(RRCConnectionReestablishmentComplete)
404
UE Assistance
Triggered
406
UE Assistance Information
(RRC Message)
408
RRCConnectionReconfiguration
(updated DRX configuration settings)
410
RRCConnectionReconfigurationComplete

FIG. 4



500
510
UL-DCCH-Message ::= SEQUENCE {
message UL-DCCH-MessageType
}
UL-DCCH-MessageType ::= CHOICE {
c1 CHOICE {
csfbParametersRequestCDMA2000 CSFBParametersRequestCDMA2000,
measurementReport MeasurementReport,
rrcConnectionReconfigurationComplete RRCConnectionReconfigurationComplete,
520
rrcConnectionReestablishmentComplete RRCConnectionReestablishmentComplete,
rrcConnectionSetupComplete RRCConnectionSetupComplete,
530
securityModeComplete SecurityModeComplete,
securityModeFailure SecurityModeFailure,
ueCapabilityInformation UECapabilityInformation,
ulHandoverPreparationTransfer ULHandoverPreparationTransfer,
ulInformationTransfer ULInformationTransfer,
counterCheckResponse CounterCheckResponse,
540
ueInformationResponse-r9 UEInformationResponse-r9,
proximityIndication-r9 ProximityIndication-r9,
rnReconfigurationComplete-r10 RNReconfigurationComplete-r10,
mbmsCountingResponse-r10 MBMSCountingResponse-r10,
interFreqRSTDMeasurementIndication-r10 InterFreqRSTDMeasurementIndication-r10
},
560
c2 CHOICE {
ueAssistanceInfoTransfer-r11 UEAssistanceInfoTransfer-r11,
spare15 NULL, ... spare1 NULL
},
550
messageClassExtension SEQUENCE {}
}

FIG. 5



600
550
UEAssistanceInfoTransfer-r11 ::= SEQUENCE {
rrc-TransactionIdentifier RRC-TransactionIdentifier,
criticalExtensions CHOICE {
c1 CHOICE{
ueAssistanceInfoTransfer –r11 UEAssistanceInfoTransfer –r11-IEs,
spare3 NULL, spare2 NULL, spare1 NULL
},
criticalExtensionsFuture SEQUENCE {}
}
}
}
UEAssistanceInfoTransfer –r11-IEs::= SEQUENCE {
ue-assistanceInfo-r11 UE-AssistanceInfo-r11,
nonCriticalExtension SEQUENCE {} OPTIONAL
}
610
UE-AssistanceInfo-r11 ::= SEQUENCE {
power-Preference-Indication BOOLEAN OPTIONAL,
mobility-State-Indication BOOLEAN OPTIONAL,
...
}
620
630

FIG. 6

700

540

```
UEInformationResponse-r9 ::= SEQUENCE {
        rrc-TransactionIdentifier       RRC-TransactionIdentifier,
        criticalExtensions              CHOICE {
                c1                      CHOICE {
                        ueInformationResponse-r9    UEInformationResponse-r9-IEs,
                        spare3 NULL, spare2 NULL, spare1 NULL
                },
                criticalExtensionsFuture        SEQUENCE {}
        }
}

UEInformationResponse-r9-IEs ::= SEQUENCE {
        rach-Report-r9          SEQUENCE {
                numberOfPreamblesSent-r9    INTEGER (1..200),
                contentionDetected-r9       BOOLEAN
        }       OPTIONAL,
        rlf-Report-r9           RLF-Report-r9           OPTIONAL,
        nonCriticalExtension    UEInformationResponse-v930-IEs      OPTIONAL
}

UEInformationResponse-v930-IEs ::= SEQUENCE {
        lateNonCriticalExtension    OCTET    STRING                 OPTIONAL,
        nonCriticalExtension        UEInformationResponse-v1020-IEs OPTIONAL
}

UEInformationResponse-v1020-IEs ::= SEQUENCE {
        logMeasReport-r10       LogMeasReport-r10       OPTIONAL,
        nonCriticalExtension    UEInformationResponse-v11xx-IEs     OPTIONAL
}
```

710

```
UEInformationResponse-v11xx-IEs ::= SEQUENCE {
        ue-assistanceInfo-r11   UE-AssistanceInfo-r11,
        nonCriticalExtension    SEQUENCE {}  OPTIONAL
}
```

610

```
UE-AssistanceInfo-r11 ::= SEQUENCE {
        power-Preference-Indication     BOOLEAN     OPTIONAL,
        mobility-State-Indication       BOOLEAN     OPTIONAL,
...
}
```

FIG. 7

800

520

```
RRCConnectionReestablishmentComplete ::= SEQUENCE {
        rrc-TransactionIdentifier          RRC-TransactionIdentifier,
        criticalExtensions                 CHOICE {
                rrcConnectionReestablishmentComplete-r8      RRCConnectionReestablishmentComplete-r8-IEs,
                criticalExtensionsFuture SEQUENCE {}
        }
}

RRCConnectionReestablishmentComplete-r8-IEs ::= SEQUENCE {
        nonCriticalExtension     RRCConnectionReestablishmentComplete-v920-IEs      OPTIONAL
}

RRCConnectionReestablishmentComplete-v920-IEs ::= SEQUENCE {
        rlf-InfoAvailable-r9       ENUMERATED {true}   OPTIONAL,
        nonCriticalExtension       RRCConnectionReestablishmentComplete-v8a0-IEs      OPTIONAL
}

RRCConnectionReestablishmentComplete-v8a0-IEs ::= SEQUENCE {
        lateNonCriticalExtension           OCTET STRING OPTIONAL,
        nonCriticalExtension               RRCConnectionReestablishmentComplete-v1020-IEs OPTIONAL
}

RRCConnectionReestablishmentComplete-v1020-IEs ::= SEQUENCE {
        logMeasAvailable-r10    ENUMERATED {true} OPTIONAL,
        nonCriticalExtension    RRCConnectionReestablishmentComplete-v11xx-IEs          OPTIONAL
}
```

810

```
RRCConnectionReestablishmentComplete-v11xx-IEs ::= SEQUENCE {
        ue-assistanceInfo-r11   UE-AssistanceInfo-r11
        nonCriticalExtension    SEQUENCE {} OPTIONAL
}
```

610

```
UE-AssistanceInfo-r11 ::= SEQUENCE {
        power-Saving-Preference          BOOLEAN      OPTIONAL,
        mobility-State-Indication        BOOLEAN      OPTIONAL,
        ...
}
```

FIG. 8

900

530

```
RRCConnectionSetupComplete ::= SEQUENCE {
        rrc-TransactionIdentifier          RRC-TransactionIdentifier,
        criticalExtensions                 CHOICE {
                c1                                 CHOICE{
                        rrcConnectionSetupComplete-r8
                                RRCConnectionSetupComplete-r8-IEs,
                        spare3 NULL, spare2 NULL, spare1 NULL
                },
                criticalExtensionsFuture           SEQUENCE {}
        }
}

RRCConnectionSetupComplete-r8-IEs ::= SEQUENCE {
        selectedPLMN-Identity              INTEGER (1..6),
        registeredMME                      RegisteredMME OPTIONAL,
        dedicatedInfoNAS                   DedicatedInfoNAS,
        nonCriticalExtension               RRCConnectionSetupComplete-v8a0-IEs OPTIONAL
}

RRCConnectionSetupComplete-v8a0-IEs ::= SEQUENCE {
        lateNonCriticalExtension           OCTET        STRING        OPTIONAL,
        nonCriticalExtension               RRCConnectionSetupComplete-v1020-IEs OPTIONAL
}

RRCConnectionSetupComplete-v1020-IEs ::= SEQUENCE {
        gummei-Type-r10                    ENUMERATED {native, mapped} OPTIONAL,
        rlf-InfoAvailable-r10              ENUMERATED {true} OPTIONAL,
        logMeasAvailable-r10               ENUMERATED {true} OPTIONAL,
        rn-SubframeConfigReq-r10           ENUMERATED {required, notRequired} OPTIONAL,
        nonCriticalExtension               RRCConnectionSetupComplete-v11xx-IEs OPTIONAL
}
```

910

```
RRCConnectionSetupComplete-v11xx-IEs ::= SEQUENCE {
        ue-assistanceInfo-r11              UE-AssistanceInfo-r11
        nonCriticalExtension               SEQUENCE {} OPTIONAL
}
```

610

```
UE-AssistanceInfo-r11 ::= SEQUENCE {
        power-Saving-Preference            BOOLEAN OPTIONAL,
        mobility-State-Indication          BOOLEAN OPTIONAL,
        ...
}
```

FIG. 9

1000



1010
Determine a power preference for a UE
1020
Determine a mobility state for the UE, the mobility state representing a handover rate associated with a UE connected state and a cell-reselection rate associate with a UE idle state
1030
Generate a UE assistance information message, the message including the power preference and the mobility state
1040
Transmit the UE assistance information message to an eNB of a wireless network associated with the UE

FIG. 10



1100
1180
1160
RF Module
1150
Baseband Processing Module
1170
Display
UE Platform
1110
Processor
Memory
I/O System
1120
1130
1140

FIG. 11

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2013/043261

A. CLASSIFICATION OF SUBJECT MATTER

H04B 7/26(2006.01)i, H04W 80/02(2009.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H04B 7/26; H04W 72/12; H04W 52/16; H04L 1/18; H04W 80/02

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
Korean utility models and applications for utility models
Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
eKOMPASS(KIPO internal) & Keywords:assistance information message, Power Preference Indicator (PPI), Mobility State Infor-mation (MSI), Medium Access Control (MAC) layer Control Element (CE), UpLink Shared channel (UL-SCH)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	CHINA UNICOM, `Discussion on UE assistant information`, R2-122437, 3GPP TSG-RAN WG2 Meeting #78, Prague, Czech, 21-25 May 2012 <http://www.3gpp.org/ftp/tsg_ran/WG2_RL2/TSGR2_78/Docs></http:> See page 1, lines 25-26; page 2, lines 25-26; page 3, lines 8-9; and table 1.	19
Y		1-2,9-12,15-17 ,20-22
A		3-4,13-14
Y	WO 2012-021879 A2 (INTERDIGITAL PATENT HOLDINGS, INC.) 16 February 2012 See paragraphs 66, 80, 102, 133, 262; and figure 3.	1-2,9-12,15-17 ,20-22
A	CHINA UNICOM, `Consideration on DRX Configuration for Background Traffic`, R2-121429, 3GPP TSG-RAN WG2 Meeting #77bis, Jeju, South Korea, 26-30 March 2012 <http://www.3gpp.org/ftp/tsg_ran/WG2_RL2/TSGR2_77bis/Docs></http:> See page 1, lines 4-5; page 1, lines 10-12; and page 1, lines 20-34.	1-4,9-17,19-22
A	KR 10-2012-0018041 A (PANTECH CO., LTD.) 29 February 2012 See paragraphs 36, 72, 119, 121, 144, 149, 176; and figure 14.	1-4,9-17,19-22
A	KR 10-2010-0044715 A (INNOVATIVE SONIC LIMITED) 30 April 2010 See paragraphs 27-28, 35; and figure 1.	1-4,9-17,19-22

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:
"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier application or patent but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed
"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents,such combination being obvious to a person skilled in the art
"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
12 September 2013 (12.09.2013)	**13 September 2013 (13.09.2013)**

Name and mailing address of the ISA/KR
Korean Intellectual Property Office
189 Cheongsa-ro, Seo-gu, Daejeon Metropolitan City, 302-701, Republic of Korea
Facsimile No. +82-42-472-7140

Authorized officer
KANG Hee Gok
Telephone No. +82-42-481-8264

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2013/043261

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. ☒ Claims Nos.: 5-8,18,23-24
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required addtional search fees were timely paid by the applicant, this international search report covers all searchable claims.

2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.

3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:

4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.

☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.

☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.
PCT/US2013/043261

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2012-021879 A2	16/02/2012	CA 2808274 A1	16/02/2012
		CN 103069911 A	24/04/2013
		EP 2604085 A2	19/06/2013
		SG 187831 A1	28/03/2013
		US 2012-207040 A1	16/08/2012
		WO 2012-021879 A3	02/08/2012
KR 10-2012-0018041 A	29/02/2012	US 2013-0148619 A1	13/06/2013
		WO 2012-023812 A2	23/02/2012
		WO 2012-023812 A3	31/05/2012
KR 10-2010-0044715 A	30/04/2010	CN 101730252 A	09/06/2010
		CN 101730252 B	10/04/2013
		JP 2010-103991 A	06/05/2010
		US 2010-0098010 A1	22/04/2010
		US 8411626 B2	02/04/2013