




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁶ : G21B 1/00, H05H 1/22, 6/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 98/43249</p> <p>(43) International Publication Date: 1 October 1998 (01.10.98)</p>
<p>(21) International Application Number: PCT/IB98/00388</p> <p>(22) International Filing Date: 19 March 1998 (19.03.98)</p> <p>(30) Priority Data: BO97A000169 20 March 1997 (20.03.97) IT</p> <p>(71) Applicant (for all designated States except US): CAPPELLETTI, David, Anthony [US/US]; 55852 Riverdale Drive, Elkhart, IN 46514 (US).</p> <p>(71)(72) Applicant and Inventor: BOSCOLI, Renzo [IT/IT]; Via dei Cacciatori, 4460, I-40010 Palata Pepoli (IT).</p> <p>(74) Agents: JORIO, Paolo et al.; Studio Torta, S.r.l., Via Viotti, 9, I-10121 Torino (IT).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>	

(54) Title: METHOD AND MACHINE FOR PRODUCING ENERGY BY NUCLEAR FUSION REACTIONS



(57) Abstract

An experimental machine (1) for producing low-temperature nuclear fusion reactions, wherein an ion source (3) feeds a flux of positive deuterium ions to a reaction chamber (2) housing a target (5) defined by active elements (30, 31) and by an aggregate of metal sulfates hydrated with heavy water; a pumping assembly (4) being provided to maintain a vacuum in the reaction chamber (2); and the reaction chamber (2) having an accelerating device (10) for accelerating the positive deuterium ions, and which generates an electric field inside the reaction chamber (2) to convey and accelerate the deuterium ions against the active element of the target (5) in such a manner as to initiate nuclear fusion reactions between the incident deuterium ions and some of the atoms of the active element.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

5

METHOD AND MACHINE FOR PRODUCING ENERGY BY NUCLEAR
FUSION REACTIONS

10 TECHNICAL FIELD

The present invention relates to a method of
producing energy by nuclear fusion reactions.

BACKGROUND ART

The general consensus in most scientific circles
15 is that neutron emission in itself is incontrovertible
proof of the nuclear fusion of two deuterium atoms, or
of one deuterium and one tritium atom.

DISCLOSURE OF INVENTION

It is an object of the present invention to
20 confute this assumption by showing that preliminary
and/or simultaneous emission of neutrons and gamma rays
is an essential condition for nuclear fusion reactions
between deuterium and tritium atoms to take place. In
other words, it is an object of the present invention
25 to show that the deuterium/tritium nuclear fusion
phenomenon is invariably preceded and/or accompanied by
the deuterium/deuterium nuclear fusion phenomenon.

CONFIRMATION COPY

- 2 -

According to the present invention, there is provided a method of producing energy by nuclear fusion reactions, and comprising the steps of:

- feeding a flux of positive deuterium ions to a
5 reaction chamber containing a target having deuterium atoms in its crystal lattice and active metal elements;
and

- conveying, inside the reaction chamber, said flux of positive deuterium ions towards the target, so
10 that the flux of positive deuterium ions strikes the target to produce nuclear fusion reactions between the incident positive deuterium ions and some of the atoms constituting the target itself.

The present invention also relates to a machine
15 for producing energy by nuclear fusion reactions.

According to the present invention, there is provided a machine for producing energy by nuclear fusion reactions, characterized by comprising a reaction chamber; a target housed inside said reaction
20 chamber; a positive deuterium ion source communicating with said reaction chamber; and a pumping assembly communicating with said reaction chamber to maintain a vacuum inside the reaction chamber; said target having deuterium atoms in its crystal lattice; and said
25 positive deuterium ion source feeding a flux of positive deuterium ions into the reaction chamber, so that said flux of positive deuterium ions strikes all the elements of the target to produce low-temperature

- 3 -

nuclear fusion reactions between the incident positive deuterium ions and the atoms constituting the target itself.

BRIEF DESCRIPTION OF DRAWINGS

5 A non-limiting embodiment of the present invention will be described by way of example with reference to the accompanying drawings, in which:

Figure 1 shows a schematic view of a machine for producing energy by nuclear fusion reactions in
10 accordance with the teachings of the present invention;

Figure 2 shows a section of a detail of the Figure 1 machine;

Figure 3 shows a graph illustrating the production of neutrons.

15 BEST MODE FOR CARRYING OUT THE INVENTION

Number 1 in Figure 1 indicates as a whole a machine for producing energy by low-temperature nuclear fusion reactions, as distinct from hypothetical "thermonuclear" reactions.

20 Machine 1 comprises a reaction chamber 2; a positive deuterium ion source 3 for feeding a flux of positive deuterium ions (deuterons) into reaction chamber 2; a known pumping assembly 4 for maintaining a relatively low pressure inside reaction chamber 2; and
25 a target 5 housed inside reaction chamber 2, and which is struck by the flux of positive deuterium ions fed into reaction chamber 2 by source 3.

- 4 -

Reaction chamber 2 is preferably, but not necessarily, cylindrical, extends coaxially with a reference axis 6, and communicates with positive ion source 3 and pumping assembly 4 via respective
5 connecting conduits 7 and 8, each of which is connected to reaction chamber 2 at a respective end 2a, 2b of reaction chamber 2. In particular, conduit 7 connecting reaction chamber 2 to source 3 is so connected to end 2a of reaction chamber 2 that said positive deuterium
10 ions are fed into reaction chamber 2.

With reference to Figure 1, reaction chamber 2 is connected to an ion accelerating device 10 for generating an electric field inside reaction chamber 2 to accelerate the flux of positive ions towards target
15 5. Accelerating device 10 comprises a pair of electrodes located at the two ends 2a, 2b of reaction chamber 2; and an electric energy source 11 for maintaining a given difference in electric potential between the two electrodes. One of the electrodes,
20 indicated 12, is located at one end of and penetrates chamber 2, and the other electrode is defined by target 5, which is housed inside reaction chamber 2, close to end 2b of reaction chamber 2.

In the example shown, reaction chamber 2 is made
25 of Pirex® glass, and houses a focusing device 13 close to target 5. Focusing device 13 is made of metal material, is insulated electrically from electrode 12 and target 5, and provides for concentrating the flux

- 5 -

of positive deuterium ions on target 5. More specifically, focusing device 13 is divided into two portions 13a and 13b, the first of which faces electrode 12 and is defined by a cylindrical tubular body extending coaxially with reference axis 6, and the second of which faces target 5 and is defined by an ogival body coaxial with reference axis 6 and having a through hole with an inside diameter much smaller than the inside diameter of the cylindrical tubular body defining portion 13a.

In the example shown, source 3 of positive deuterium ions - hereinafter also referred to as "deuterons" - comprises a known tank 15 for storing gaseous deuterium, and which communicates with reaction chamber 2 via conduit 7; and a known ionizing unit 16 for ionizing the deuterium from tank 15 to form the flux of positive deuterium ions to be fed into reaction chamber 2.

Positive deuterium ion source 3 also comprises, in sequence, a known on-off valve 17 located along conduit 7 to permit and cut off supply of gaseous deuterium from tank 15; a known pressure reducing device 18; and a known mini on-off and regulating valve 19. Reducing device 18 provides for maintaining a given pressure of the gaseous deuterium from tank 15.

More specifically, ionizing unit 16 comprises a substantially cylindrical ionizing chamber 20 located along conduit 7; and a device 21 for generating high-

- 6 -

frequency electric oscillations, and in turn comprising a coil 22 of electrically conducting material wound about ionizing chamber 20, and a power supply 23 for inducing a high-frequency electric current in coil 22 to generate inside ionizing chamber 20 an electromagnetic field capable of ionizing the gaseous deuterium from tank 15.

Ionizing unit 16 also comprises an ion accelerating device for generating an electric field inside ionizing chamber 20 to convey the flux of positive ions generated inside ionizing chamber 20 to the portion of conduit 7 communicating with reaction chamber 2. The accelerating device comprises a pair of electrodes 25 located at the two opposite ends of ionizing chamber connected to conduit 7; and a source 26 of medium-voltage electric energy, for maintaining a given adjustable difference in electric potential between the two electrodes 25.

In the example shown, electrode 12 is connected electrically to the electrode 25 located at the inlet of the portion of conduit 7 connecting ionizing chamber 20 to reaction chamber 2.

Pumping assembly 4 is defined by a pair of known vacuum pumps 28 (one rotary and one diffusion pump) connected to reaction chamber 2 by conduit 8 via the interposition of a known on-off valve 29 for selectively isolating reaction chamber 2 from pumping assembly 4.

- 7 -

With reference to Figures 1 and 2, target 5 comprises a preferably, but not necessarily, cylindrical outer casing 30, which is substantially cup-shaped and coaxial with axis 6 with its cavity 30a facing focusing device 13; and a substantially cup-shaped active element 31 housed inside casing 30 with its cavity 31a coaxial with axis 6 and facing focusing device 13.

In the example shown, casing 30 is itself also an active element, and is defined by a stack of alternating washers 32 of different metals (e.g. copper, titanium, iron, nickel and/or other metals of similar chemical-physical characteristics) held together by gripping elements (not shown) such as longitudinal screw ties.

Active element 31 is defined by a compact aggregate of metal salts, in turn defined by a number of powdered metal sulfates (e.g. copper sulfate, lithium sulfate, titanium sulfate, potassium sulfate, etc.) mixed together with the addition of catalyzing and/or binding elements to improve the compactness of the aggregate. The copper and lithium sulfates are hydrated with heavy water (D_2O).

Each metal salt hydrated with heavy water (D_2O) is obtained from a corresponding metal salt hydrated with water (H_2O), e.g. $CuSO_4 \cdot 5H_2O$, which is first placed in an oven at a temperature of about $250^\circ C$ until all the water (H_2O) molecules are eliminated, and is

- 8 -

then placed in a silica gel dryer (known type) in which the salt is recrystallized in the presence of heavy water (D_2O) to obtain a corresponding metal salt hydrated with heavy water (D_2O), e.g. $CuSO_4 \cdot 4D_2O$.

5 Titanium sulfate is preferably, but not necessarily, used as a catalyzing element, and a silicone resin or alkaline alkylsiliconate dissolved in heavy water (D_2O) is preferably, but not necessarily, used as a binding element.

10 A first possible composition of active element 31 includes:

0.278 moles of $CuSO_4 \cdot 4D_2O$;
1.853 moles of $LiSO_4 \cdot 0.8D_2O$;
0.0625 moles of $TiOSO_4$; and

15 q.s. of a 5% ethereal solution of an alkylpolysiloxane resin with a R/Si ratio of about 1.5 to obtain a thick homogeneous mixture, which is then dried in a mold at a given temperature (about $40^\circ C$).

 A second possible composition of active element
20 31 includes:

0.125 moles of $NiSO_4 \cdot 5.6D_2O$;
0.278 moles of $CuSO_4 \cdot 4D_2O$;
1.853 moles of $Li_2SO_4 \cdot 0.8D_2O$;
0.172 moles of K_2SO_4 ; and

25 q.s. of a 5% ethereal solution of an alkylpolysiloxane resin with a R/Si ratio of about 1.5 to obtain a thick homogeneous mixture, which is then dried in a mold at a given temperature (about $40^\circ C$).

- 9 -

A third possible composition of active element 31 includes:

0.278 moles of $\text{CuSO}_4 \cdot 4\text{D}_2\text{O}$;

1.853 moles of $\text{Li}_2\text{SO}_4 \cdot 0.8\text{D}_2\text{O}$;

5 0.172 moles of K_2SO_4 ;

0.125 moles of TiOSO_4 ; and

q.s. of a 5% ethereal solution of an alkylpolysiloxane resin with a R/Si ratio of about 1.5 to obtain a thick homogeneous mixture, which is then
10 dried in a mold at a given temperature (about 40°C).

The quantity of heavy water (D_2O) to recrystallize metal salts CuSO_4 , Li_2SO_4 and NiSO_4 is 20% less than the stoichiometrically calculated quantity, to reduce the activation time of target 5.

15 With reference to Figure 1, machine 1 also comprises a device 33 (e.g. a thermocouple) for measuring the temperature of target 5, a device 34 for detecting and counting the neutrons emitted, and a device 35 for measuring gamma ray emissions, all of
20 which are located close to reaction chamber 2; a device 36 for measuring the pressure inside reaction chamber 2, and which is branch connected to conduit 8 between reaction chamber 2 and valve 29; and a device 37 for detecting the presence of tritium in reaction chamber
25 2, and which is located along conduit 8 downstream from pumping assembly 4.

Devices 33, 34, 35, 36, 37 are all known types and therefore require no description.

- 10 -

Operation of machine 1 will now be described assuming pumps 28 of pumping assembly 4 have already brought the pressure inside reaction chamber 2 to extremely low values (a few thousandths of a mm of Hg).


5 In actual use, when valve 17 is opened, the gaseous deuterium flows into conduit 7 and through pressure reducing device 18 into ionizing unit 16, where it is ionized to supply reaction chamber 2 with a flux of deuterons. More specifically, the gaseous
10 deuterium is ionized by electromagnetic excitation by the high-frequency magnetic field produced by device 21, and is conveyed towards reaction chamber 2 by the electric field generated by the two electrodes 25, between which a difference in electric potential of a
15 few kilovolts is maintained.

At the same time, source 11 maintains a difference in electric potential of preferably, but not necessarily, 2 to 10 kilovolts between electrode 12 and target 5, so that the deuterons, once inside reaction
20 chamber 2, are conveyed towards target 5 by the electric field in reaction chamber 2, to bombard target 5 as shown in the Figure 3 graph, which shows the production of neutrons per second as a function of the acceleration voltage applied.

25 Prior to bombarding target 5, the flux of deuterons is fed through focusing device 13, by which it is concentrated into a narrow deuteron beam suitable for striking active element 31.



- 11 -

Upon the deuteron beam striking active element 31, device 33 detects a fall in the temperature of target 5, and device 36 a fall in the pressure inside reaction chamber 2; which phenomena may be explained by
5 absorption of the incident deuterons into active element 31, and by subsequent catalytic disintegration of the deuterons inside the crystal lattice of active element 31 according to endothermic nuclear reaction:



10 where "D" indicates a deuterium atom, "n" a neutron, and "p" a proton.

Subsequently, device 33 detects a sharp increase in the temperature of target 5 (to about 1000°C), while devices 34, 35, 37 respectively detect a neutron flux
15 (up to 10^5 neutrons per second) several magnitude order (from 3 to 5) greater than the natural flux, a high emission of electromagnetic waves of various wavelengths including gamma and x-rays, and the production of tritium; which phenomena may be explained
20 by the initiation of low-temperature nuclear fusion reactions according to the following exothermic reactions:



- 12 -

where "D" indicates a deuterium atom, "T" a tritium atom, "³He" a helium-3 atom, "n" a neutron, "p" a proton, and "γ" the emission of gamma rays.


More specifically, exothermic reaction (I) may be
 5 the result of the following sum of reactions:

$$\begin{array}{l} D \xrightarrow{\text{Metal}} n + p(-2.224 \text{ MeV}) + \\ D + n \longrightarrow T + \gamma(+6.239 \text{ MeV}) = \\ \hline D + D \longrightarrow T + p + \gamma(+4.015 \text{ MeV}); \end{array}$$

and exothermic reaction (II) the result of the
 10 following sum of reactions:

$$\begin{array}{l} D \xrightarrow{\text{Metal}} n + p(-2.224 \text{ MeV}) + \\ D + p \longrightarrow {}^3\text{He} + \gamma(+5.474 \text{ MeV}) = \\ \hline D + D \longrightarrow {}^3\text{He} + n + \gamma(+3.250 \text{ MeV}). \end{array}$$

As exothermic reaction (I) involves the
 15 production of tritium, a further low-temperature nuclear fusion reaction may be initiated according to the following exothermic reaction:



20 where "D" indicates a deuterium atom, "T" a tritium atom, "⁴He" a helium-4 atom, and "n" a neutron.

In view of the large amount of energy produced, exothermic reaction (III) may account for the sharp increase in the temperature of target 5 (during
 25 experiments, target 5 reached temperatures of around 1000°C).

- 13 -

Given the heterogeneous composition of active element 31, other low-temperature nuclear fusion reactions may also take place, such as:

- Deuterium+Deuterium \longrightarrow Helium-4
- 5 Deuterium+proton \longrightarrow Helium-3+gamma photon
- Deuterium+neutron \longrightarrow Tritium+gamma photon
- Lithium-6+neutron \longrightarrow Tritium+Helium-4
- Lithium-7+neutron \longrightarrow Tritium+Helium-4+neutron
- Lithium-7+proton \longrightarrow Beryllium+gamma photon
- 10 Copper+gamma photon \longrightarrow Radioactive copper+neutron
- Titanium+neutron \longrightarrow Radioactive titanium+gamma photon
- Potassium+neutron \longrightarrow Radioactive potassium+2 neutrons
- Beryllium-9+proton \longrightarrow Beryllium-8+deuteron

During operation, experiments showed that a
15 reduction in the electric potential difference between electrode 12 and target 5 immediately following the rapid increase in temperature, assimilable with commencement of the nuclear fusion reactions, does not result in a proportional reduction in neutron flux (a
20 reduction in potential from 5 to 3 kilovolts resulted in a roughly 25% reduction in the number of neutrons emitted per unit time).

The method according to the present invention therefore comprises feeding a flux of positive
25 deuterium ions to a reaction chamber 2 housing a target 5 having deuterium atoms in its crystal lattice. Subsequently, the method provides for conveying the flux of positive deuterium ions entering reaction

- 14 -

chamber 2 towards target 5, so that the flux of positive deuterium ions strikes target 5 to produce nuclear fusion reactions between the incident positive deuterium ions and some of the atoms constituting
5 target 5.

More specifically, the step of conveying the positive deuterium ions towards target 5 comprises accelerating the flux of positive deuterium ions by means of an electric field, and focusing the flux of
10 positive deuterium ions into a concentrated beam prior to impact with target 5.

In the example shown, the step of feeding the flux of positive deuterium ions to reaction chamber 2 comprises drawing deuterium atoms in gaseous form from
15 tank 15, and subsequently ionizing the deuterium atoms to produce the flux of positive deuterium ions for supply to reaction chamber 2.

Clearly, changes may be made to the method and machine 1 as described and illustrated herein without,
20 however, departing from the scope of the present invention.

- 15 -

CLAIMS

1) A method of producing energy by nuclear fusion reactions, and comprising the steps of:

5 - feeding a flux of positive deuterium ions to a reaction chamber (2) containing a target (5) having deuterium atoms in its crystal lattice and active metal elements; and

 - conveying, inside the reaction chamber (2),
10 said flux of positive deuterium ions towards the target (5), so that the flux of positive deuterium ions strikes the target (5) to produce nuclear fusion reactions between the incident positive deuterium ions and some of the atoms constituting the target (5)
15 itself.

2) A method as claimed in Claim 1, wherein said step of conveying the positive deuterium ions towards the target (5) comprises accelerating said flux of positive deuterium ions by means of an electric field.

20 3) A method as claimed in Claim 1 and/or 2, wherein said step of conveying the positive deuterium ions towards the target (5) comprises focusing the flux of positive deuterium ions into a concentrated beam prior to impact with the target (5).

25 4) A method as claimed in any one of the foregoing Claims, wherein said step of feeding the flux of positive deuterium ions to the reaction chamber (2) comprises drawing deuterium atoms from a tank (15), and

- 16 -

subsequently ionizing said deuterium atoms to produce said flux of positive deuterium ions.

5) A machine (1) for producing energy by nuclear fusion reactions, characterized by comprising a reaction chamber (2); a target (5) housed inside said reaction chamber (2); a positive deuterium ion source (3) communicating with said reaction chamber (2); and a pumping assembly (4) communicating with said reaction chamber (2) to maintain a vacuum inside the reaction chamber (2); said target (5) having deuterium atoms in its crystal lattice; and said positive deuterium ion source (3) feeding a flux of positive deuterium ions into the reaction chamber (2), so that said flux of positive deuterium ions strikes all the elements of the target (5) to produce low-temperature nuclear fusion reactions between the incident positive deuterium ions and the atoms constituting the target (5) itself.

6) A machine as claimed in Claim 5, characterized in that said reaction chamber (2) comprises accelerating means (10) for conveying said flux of positive deuterium ions against said target (5) and accelerating the positive deuterium ions.

7) A machine as claimed in Claim 6, characterized in that said accelerating means (10) comprise at least two electrodes (5, 12) housed inside the reaction chamber (2); and an electric energy source (11) for maintaining an in any way variable difference in electric potential between the two electrodes (5, 12);

- 17 -

one of said two electrodes (5, 12) being defined by said target (5).

8) A machine as claimed in any one of the foregoing Claims from 5 to 7, characterized in that
5 said reaction chamber (2) comprises a focusing device (13) through which said flux of positive deuterium ions travels prior to striking said target (5); said focusing device (13) focusing said flux of positive deuterium ions to form a concentrated beam of positive
10 deuterium ions.

9) A machine as claimed in any one of the foregoing Claims from 5 to 8, characterized in that said target (5) comprises an outer casing (30), which is substantially cup-shaped with a cavity (30a) facing
15 said focusing device (13); and an active element (31) housed inside said outer casing (30), and which is substantially cup-shaped with a cavity (31a) facing said focusing device (13); said active element (31) being struck by said concentrated beam of positive
20 deuterium ions.

10) A machine as claimed in Claim 9, characterized in that said outer casing (30) is made of metal material.

11) A machine as claimed in Claim 10,
25 characterized in that said outer casing (30) is defined by a stack of alternating washers (32) made of different metal materials and held together by gripping means.

- 18 -

12) A machine as claimed in Claim 9, characterized in that said active element (31) is defined by an aggregate comprising metal salts.

13) A machine as claimed in Claim 12,
5 characterized in that some of the metal salts belong to the class of sulfates comprising ferrous sulfate, nickel sulfate, titanium sulfate and potassium sulfate.

14) A machine as claimed in Claim 12, characterized in that the metal salts are selected from
10 copper sulfate and lithium sulfate; said sulfate being hydrated with heavy water.

15) A machine as claimed in Claim 9, characterized in that said active element (31) absorbs the incident positive deuterium ions according to an
15 endothermic catalytic disintegration reaction.

16) A machine as claimed in Claim 5, characterized in that said positive deuterium ion source (3) comprises a tank (15) containing deuterium atoms in gaseous form for supply to said reaction
20 chamber (2); and an ionizing unit (16) interposed between said tank (15) and said reaction chamber (2) to so ionize the deuterium atoms as to supply said reaction chamber (2) with a flux of positive deuterium ions.




Fig. 1

2 / 3




Fig. 2

3 / 3




Fig. 3

INTERNATIONAL SEARCH REPORT

Inter national Application No
PCT/IB 98/00388

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G21B1/00 H05H1/22 H05H6/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G21B H05H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	BACON F M ET AL: "Intense neutron source development for use in cancer therapy" 1980 CONFERENCE ON THE APPLICATION OF ACCELERATORS IN RESEARCH AND INDUSTRY, DENTON, TX, USA, 3-5 NOV. 1980, vol. ns-28, no. 2, ISSN 0018-9499, IEEE TRANSACTIONS ON NUCLEAR SCIENCE, APRIL 1981, USA, pages 1902-1905, XP002052288	1-3,5,6, 8
Y	see page 1902, paragraph 1 - page 1903, right-hand column, paragraph 2; figure 1	4,16
Y	PATENT ABSTRACTS OF JAPAN vol. 015, no. 083 (P-1171), 26 February 1991 & JP 02 298891 A (SEIKO EPSON CORP), 11 December 1990, see abstract	4,16
A	---	1,2,5,6
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

9 July 1998

Date of mailing of the international search report

15/07/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Capostagno, E

INTERNATIONAL SEARCH REPORT

Inter national Application No
PCT/IB 98/00388

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	KITAMURA A ET AL: "In situ elastic recoil detection analysis of hydrogen isotopes during deuterium implantation into metals" FUSION TECHNOLOGY, MAY 1996, ANS, USA, vol. 29, no. 3, ISSN 0748-1896, pages 372-378, XP002052289 see page 372, right-hand column, paragraph 3 - page 373, right-hand column, last paragraph; figure 1 ---	1-3,5,6, 8
A	MOO S P ET AL: "An investigation of the ion beam of a plasma focus using a metal obstacle and deuterated target" IEEE TRANSACTIONS ON PLASMA SCIENCE, JUNE 1991, USA, vol. 19, no. 3, ISSN 0093-3813, pages 515-519, XP002052290 see page 515, left-hand column, paragraph 3 see page 515, right-hand column, paragraph 2; figure 1 ---	9,10
A	FALLAVIER M: "SEARCH FOR NUCLEAR FUSION IN DEUTERATED TARGETS UNDER CLUSTER-BEAM IMPACT" PHYSICAL REVIEW LETTERS, vol. 65, no. 5, 30 July 1990, pages 621-624, XP000206161 see page 621, paragraph 1 - page 622, paragraph 3 ---	1-3,5,6, 8
A	EP 0 338 619 A (SODERN ;PHILIPS NV (NL)) 25 October 1989 see column 4, line 30 - line 51 -----	11,15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 98/00388

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0338619 A	25-10-1989	FR 2630251 A	20-10-1989
		DE 68923476 D	24-08-1995
		DE 68923476 T	14-03-1996
		JP 1312500 A	18-12-1989
		US 4935194 A	19-06-1990
