US 20040148370A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2004/0148370 A1

Sadiq (43) Pub. Date: Jul. 29, 2004

(54) SYSTEM AND METHOD FOR COMPOSING, CONFIGURING, DEPLOYING, AND MANAGING SERVICES USING A GRAPHICAL USER INTERFACE

(75) Inventor: **Waqar Sadiq**, Plano, TX (US)

Correspondence Address:
DOCKET CLERK, DM/EDS
P.O. DRAWER 800889
DALLAS, TX 75380 (US)

(73) Assignee: **Electronic Data Systems Corporation**, Plano, TX

(21) Appl. No.: **10/350,164**

(22) Filed: **Jan. 23, 2003**


Publication Classification

(51) **Int. Cl.**[7] **G06F 15/173**

(52) **U.S. Cl.** **709/223**

(57) **ABSTRACT**

A system and method for composing, configuring, deploying, and managing services in a data processing system and data processing system network. This system provides deployment domains to define a logical set of business services that have similar requirements for an application infrastructure. A deployment domain is created, and a graphical user interface allows a user to compose, configure, deploy, and manage services within the deployment domain and associated hosts using a drag-and-drop interface.





Business Service Implementation
110
Implementation Framework
130
Management Framework
120
Application Server
Environment
140
Implementation Services
150

Figure 1



Model / Introspect 205
Build / Generate 210
Configure 215
Deploy 220
Manage 225
Federated Meta-Model 230
Standards & Technologies 240
Industry Specific Templates (Reusable Assets) 250
Service Orchestrations 260

Figure 2



Deployment Domain 300
Virtual Service Container 320
Metadata 330
Management Services / Tools 310

Figure 3




Management Tools
415
Runtime Environment
410
Development Tools
405
Metadata Access System
420
Federated Meta Repository
430

Figure 4


500
Hosts
Host 1
Host 2
Infrastructure services
Accounting
Security
Metrics
Service Implementations
Online Catalog
Package Tracking
Deployment Domains
Domain 1
Host 1
Host 2
Security
Package Tracking
Domain 2
Domain 3
510
Domain 1
Hosts
Host 1
Host 2
520
Infrastructure Services
Security
520
Virtual Containers
Package Tracking
520
Properties
530
540



Business Service
620
PLUGIN
610
PLUGIN
610
PLUGIN
610
Virtual Service
Container
600

Figure 6



User Selects Deployment Domain 705
User Drops Host into DD 710
Host Associated with DD 715
User Drops IS into DD 720
IS Associated with DD 725
User Drops SI into DD 730
User Edits SI Properties 735
SI Associated with DD 740
User Drops IS on VC 745
User Edits IS Properties 750
IS Associated with VC 755
System Evaluates Associations 760
Code Generated 765
Code Installed 770

Figure 7

SYSTEM AND METHOD FOR COMPOSING, CONFIGURING, DEPLOYING, AND MANAGING SERVICES USING A GRAPHICAL USER INTERFACE

TECHNICAL FIELD OF THE INVENTION

[0001] The present invention is directed, in general, to data processing system services management.

BACKGROUND OF THE INVENTION

[0002] In the area of conventional business service development, there are, in general, three major roles, each role having specific tools to address its needs.

[0003] Application architects are primarily concerned with defining the contracts of the business services to meet the business requirements. An application contract consists of one or more interface definitions, reflecting the right level of interface granularity and service behavior such as operations exposed and their inputs and outputs.

[0004] An important aspect of the architect's task here is to ensure that existing interface types are reused so that multiple interface types and messages are not reinvented to fulfill similar requirements.

[0005] Once the correct interfaces have been defined, the application developers are ready to implement those interfaces. This often involves writing code that implements business logic. The developers also have to be able to unit test the code that they have just written.

[0006] Finally, once the code has been developed, it can be given to the system administrators for configuration, deployment and management. They can then configure the runtime execution environment for the newly developed service and deploy the application. Once deployed, the application can then be managed through the means available in the environment.

[0007] In the conventional development model, the applications are developed from scratch. This allows the users to perform top-down design and leverage the full capabilities of the available technologies since no baggage needs to be carried from the past.

[0008] Currently, there are 5 major phases of the lifecycle of the business services. In the model phase, the application architects design the interfaces for the business services to be developed. Once the interfaces have been designed, the business logic is developed by the developers of the system. The system architects then configure the runtime for the business service and the administrators then deploy and manage the business services.

[0009] In many cases, the business services already exist but are not manageable. These services may be either 3rd party off-the-shelf (COTS) applications or custom applications developed in-house or by system integrators.

[0010] This style of development is bottom-up development where the interfaces are actually constructed based on existing applications. The architects first use introspection to reverse engineer metadata from the existing applications. These applications may exist in one of many supported technologies such as Java classes, CORBA, EJB's, existing web services or COTS packages such as SAP or Siebel. Introspection would result in one-to-one interface generation. However, in real world, these interfaces may need to be refactored. Refactoring involves either suppressing some of the operation in an interface, creating brand new ones, combining two or more interfaces (contract aggregation) or splitting a contract into two or more contracts (contract dissemination).

[0011] It should be noted that the existing applications could also be web services. The process should however be no different than that for 3rd party COTS or custom applications supporting a particular technology.

[0012] Business logic generally does not change in nature. However, the underlying technologies are changing very rapidly. For example, there are a number of new standards that are being developed to address various aspects of distributed business services. Many standards do not have any sort of industry consensus and many areas have competing standards. However, the applications have to be developed today. Typically, the business services are written to provide all the other necessary functionality, such as security and others (application infrastructure services) that do not actually contribute to the business behavior itself. As the standards and technologies for these other services (application infrastructure services) evolve, the business services have to be modified and enhanced in order to take advantage of them. Furthermore, in the current state of the art, the configuration and deployment of these services is specific to a particular underlying environment and the underlying products.

[0013] There is, therefore, a need in the art for an improved system and method for composing, configuring, deploying, and managing business services in a data processing system and data processing system network.

SUMMARY OF THE INVENTION

[0014] To address the above-discussed deficiencies of the prior art, it is a primary object of the present invention to provide an improved system and method for business services development and management in a data processing system and data processing system network.

[0015] The preferred embodiment provides a system and method for composing, configuring, deploying, and managing services in a data processing system and data processing system network. This system provides deployment domains to define a logical set of business services that have similar requirements for an application infrastructure. A deployment domain is created, and a graphical user interface allows a user to compose, configure, deploy, and manage services within the deployment domain and associated hosts using a drag-and-drop interface.

[0016] The foregoing has outlined rather broadly the features and technical advantages of the present invention so that those skilled in the art may better understand the detailed description of the invention that follows. Additional features and advantages of the invention will be described hereinafter that form the subject of the claims of the invention. Those skilled in the art will appreciate that they may readily use the conception and the specific embodiment disclosed as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. Those skilled in the art will also realize that such

equivalent constructions do not depart from the spirit and scope of the invention in its broadest form.

[0017] Before undertaking the DETAILED DESCRIPTION OF THE INVENTION below, it may be advantageous to set forth definitions of certain words or phrases used throughout this patent document: the terms "include" and "comprise," as well as derivatives thereof, mean inclusion without limitation; the term "or" is inclusive, meaning and/or; the phrases "associated with" and "associated therewith," as well as derivatives thereof, may mean to include, be included within, interconnect with, contain, be contained within, connect to or with, couple to or with, be communicable with, cooperate with, interleave, juxtapose, be proximate to, be bound to or with, have, have a property of, or the like; and the term "controller" means any device, system or part thereof that controls at least one operation, whether such a device is implemented in hardware, firmware, software or some combination of at least two of the same. It should be noted that the functionality associated with any particular controller may be centralized or distributed, whether locally or remotely. Definitions for certain words and phrases are provided throughout this patent document, and those of ordinary skill in the art will understand that such definitions apply in many, if not most, instances to prior as well as future uses of such defined words and phrases.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] For a more complete understanding of the present invention, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, wherein like numbers designate like objects, and in which:

[0019] **FIG. 1** depicts a block diagram of the relationships between service layers in accordance with a preferred embodiment of the present invention;

[0020] **FIG. 2** depicts a block diagram relating a development and deployment lifecycle with data objects and service objects in accordance with a preferred embodiment of the present invention;

[0021] **FIG. 3** depicts a block diagram of a runtime environment in accordance with a preferred embodiment of the present invention;

[0022] **FIG. 4** illustrates a federated metadata storage and access system in accordance with a preferred embodiment of the present invention;

[0023] **FIG. 5** depicts a virtual composition environment in accordance with a preferred embodiment of the present invention;

[0024] **FIG. 6** depicts a block diagram of a virtual container accordance with a preferred embodiment of the present invention; and

[0025] **FIG. 7** depicts a flowchart of a process in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0026] **FIGS. 1 through 7**, discussed below, and the various embodiments used to describe the principles of the present invention in this patent document are by way of illustration only and should not be construed in any way to limit the scope of the invention. Those skilled in the art will understand that the principles of the present invention may be implemented in any suitably arranged device. The numerous innovative teachings of the present application will be described with particular reference to the presently preferred embodiment.

[0027] Definitions: Following are short definitions of the usual meanings of some of the technical terms which are used in the present application. (However, those of ordinary skill will recognize whether the context requires a different meaning.) Additional definitions can be found in the standard technical dictionaries and journals.

[0028] Business Service Contract—A business service contract describes the business service exposed. This normally contains information such as operations provided by the service, their inputs and outputs.

[0029] Business Service Implementation—A business service implementation is the software code required strictly to implement the above mentioned business behavior. This does not include other capabilities such as providing security or managing transactions.

[0030] Application Infrastructure Services—Application Infrastructure Services are all those services that themselves do not contribute to the business behavior, however they are necessary for the correct operation of the business service. These services can be added, removed or replaced without changing the business behavior of the business service.

[0031] Virtual Container—A virtual container couples a business service implementation with one or more application infrastructure services and provides the definition for a complete business service. This definition exists in metadata and contains all the metadata that customizes the specific usage of application infrastructure services inside the said virtual container.

[0032] Physical Business Service—A physical business service is the platform specific programming code that can be generated according to the previously discussed definition of the virtual container. This code can then be compiled and deployed in the underlying platform specific manner.

[0033] Web Services will soon be providing complex and mission critical services to business partners and internal customers by providing a viable alternative to most application integration scenarios.

[0034] The disclosed embodiments provide a system and method for composing, configuring, deploying, and managing services in a data processing system and data processing system network. This system provides deployment domains to define a logical set of business services that have similar requirements for an application infrastructure. A deployment domain is created, and within it is contained a set of metadata that defines available hosts, application infrastructure services, and deployed business services. The metadata is managed by a federated metamodel system. A visual composition environment allows composition of a virtual

container that couples the business service in question with the application level infrastructure services that it needs. The code generators can then generate platform specific code for the virtual container. All this can be packaged for easy shipment. The packaged business services can then be easily deployed on any of the machines available to the system.

[0035] The disclosed embodiments include a method and system for describing the underlying application services infrastructure, a virtual execution environment for business services implementations and a system to integrate the two in a loosely coupled way through metadata so that the two can evolve independently and still stay compatible.

[0036] In the preferred embodiment, a deployment domain is created, and a graphical user interface allows a user to compose, configure, deploy, and manage services within the deployment domain and associated hosts using a drag-and-drop interface.

[0037] Furthermore, once the metadata has been defined, it becomes very easy to provide user interface based tools that allow construction of a business service by visually composing an execution environment for the already-built business service implementation. The implementation itself does not know about the kind of the environment in which it will be deployed. Because of this, the implementation can be deployed in execution environments that provide vastly different quality of service.

[0038] The preferred embodiment includes the following features:

[0039] The ability to build business service implementations without any knowledge of the underlying infrastructure environment.

[0040] The ability to describe a deployment environment without any knowledge of what kind of business services will be deployed in it.

[0041] The ability to enhance an infrastructure environment by providing custom application infrastructure services. These services, by implementing abstract interfaces, can be plugged into any supported infrastructure environment. These application infrastructure services provide discrete non-business related services and do not make any assumptions about who is going to use them and how will they be used.

[0042] The ability to construct a virtual container, once the business service implementations have been developed, that integrates them with preexisting infrastructure services and allows for better management.

[0043] The ability to describe various components and provide plug-and-play development and deployment using a metadata foundation.

[0044] **FIG. 1** illustrates these objectives further. A management framework **120** hides the underlying application server environment **140** from the business service implementation **110** and augments the underlying environment by providing the ability to add and integrate application infrastructure services. Further, an implementation framework **130** can be provided that even provides implementation services **150** such as a database management system.

[0045] The preferred embodiment provides a platform that provides a level of abstraction, much higher than the one that is provided by application servers and other web services platforms currently available. This platform brings the development, configuration, deployment and management capabilities to the business services.

[0046] The lifecycle shown in **FIG. 2** relates to either doing new development or introspecting existing application for the purpose of converting them into managed business services. As described above, the lifecycle includes the model or introspection phase **205**, in which the application architects design the interfaces for the business services to be developed or introspect an existing service. In the case of new development, once the interfaces have been designed, the skeleton of business service implementation can be generated and then developed by the developers. In case of existing service, once the existing service has been introspected, a gateway implementation can be automatically generated **210**. The system architects then con **FIG. 215** the runtime for the business service. Finally, the administrators then deploy **220** and manage **225** the business services.

[0047] One disclosed feature of the preferred embodiment is a federated meta-model **230** that stores and provides access to the metadata describing the business services themselves and their infrastructure. This metadata describes the interface of the business service itself, the metadata about those infrastructure services, and the metadata about the virtual container that couples a business service implementation with one or more infrastructure services along with their uniquely customized properties.

[0048] The preferred embodiment is designed to expose a level of abstraction higher than those provided by industry standards **240**. The standards and technologies in the web services area are changing very rapidly. As a result, the business services that leverage those standards run the risk of becoming outdated very quickly. The preferred embodiment exposes a higher level interface that can be generated by the metadata itself. This results in more stable and longer-lasting applications.

[0049] The preferred embodiment provides the horizontal platform that can be used to build the vertical solutions that are more specific to industries in the form of industry specific templates **250**. These solutions do not have to be complete themselves. In fact, most likely these solutions will be partial solutions designed to be extended for particular business problems.

[0050] Once the business services have been created, they can be orchestrated **260** using business service orchestration tools. These orchestrations themselves can be manifested as web services, thus forming a recursive relationship.

[0051] **FIG. 3** describes the runtime environment for which the business services are configured and in which they are deployed. This architecture is described here at the logical level and can have one or more physical manifestations, in accordance with the disclosed or claimed embodiments.

[0052] A deployment domain **300** is a mechanism for partitioning a large IT environment into smaller logical clusters of machines and applications so that these different clusters can be configured differently from each other. In this case, these deployment domains serve to logically separate environments with different requirements domain. For example, there may be a deployment domain called internal

applications. This domain may be configured with a specific security service. Another domain may be for business partners and may be configured with a different kind of security service. Additionally, this domain may also be configured with a management service, e.g., to bill the users for usage of the business service. The deployment domain serves to define the scope of the infrastructure services that it is composed of and the business services that are deployed in it.

[0053] The deployment domain defines the logical boundaries and scope of the infrastructure and business services within it. It is a logical partition of a large computing environment which consists of many physical machines. The metadata data related to the deployment domain defines that logical partition.

[0054] One or more physical machines can be configured for a deployment domain and one or more application infrastructure services can be made part of the fabric that is a deployment domain. Each server machine, called a host, that is configured to participate in one or more deployment domains will contain a core software service.

[0055] The metadata that describes a host can include such items as host name, host's IP address, the core directory path on the host for the application, etc.

[0056] Since there is a many-to-many relationship between the hosts and deployment domains, a list of hosts can exist independently of the deployment domains. When a host is configured for a deployment domain, it has to be able to run all of the business services deployed in that domain. The application infrastructure services do not have to run on the host because they can themselves be remote.

[0057] An application infrastructure service is defined as a service that provides a discrete non-business level service. Some examples of infrastructure services are security services, transaction services, service monitoring, load balancing, fault tolerance, and messaging service. An infrastructure may also provide some other services such as reliable delivery or asynchronous messaging. These services can also be much higher level; services such as accounting & billing services, service level agreement management services and user profile management services.

[0058] The best way to characterize an application infrastructure service or differentiate it from a business service is that business service in itself performs a business function, such as procurement or a human resource system. In contrast, an infrastructure service provides secondary functionality that is not part of the business functions itself.

[0059] The metadata of an infrastructure service consists of property sheets with each property sheet containing one or more related properties. For example, a security service may contain five sheets for general properties, authentication, authorization, message integrity, and message confidentiality. Each sheet contains properties that allow customization of the underlying infrastructure service for this specific use. Since these properties are specific to the underlying service, their interpretation is left completely up to the service itself and its plugin. Furthermore, since the property values are specific to the specific usage of this service, these properties need only be defined once a virtual service container is configured with this service.

[0060] Once an infrastructure service has been written or purchased, it has to be made part of one or more deployment domains so that it can be used. This is accomplished by defining an abstract plugin interface. This interface allows the deployment management tools and runtime software to plugin an infrastructure service into the deployment domain and allows the service to be used at runtime. The tools that allow the user to visually configure the virtual service container may allow mechanisms to "drag" the infrastructure service and "drop" it on the virtual service container on a canvass. The tools can at this time present the required set of properties to be defined for the service for this particular container. This is accomplished by requesting the plugin to provide its customizable property sheets so that they can be filled.

[0061] At runtime, the virtual container receives the requests sent to the business service and invokes plugs for all the application infrastructure services configured for this container. The plugin can then retrieve the metadata and use it to perform the work. If the actual infrastructure service is implemented as a set of libraries, then the plugin can invoke those libraries or if it represents a remote service then it can communicate with that remote service in a manner that is specific to that infrastructure service. In any case, the runtime is not aware of the details of the operation—it simply invokes the plugin and passes it the runtime invocation-related data.

[0062] Each infrastructure service is therefore required to implement the plugin interface as a precondition to it becoming part of an infrastructure. An infrastructure service may provide different plugins for different deployment domains. The location and other necessary information required to load the plugin is part of the metadata of the infrastructure service.

[0063] A business service implementation is an implementation of the business behavior that a service is expected to provide. This behavior should be implementable in a manner independent of how it is accessed. For example, it should be possible to implement the business logic for a procurement service without being specific to Jave Platform 2 Enterprise Edition (J2EE)-based access or Microsoft NET based access. However, once the service has been constructed, it may be deployed in a virtual container **320** that is specific to the underlying platform. This virtual container then decouples the service implementation from the infrastructure in which it is deployed.

[0064] This virtual service container **320** is conceptually similar to a J2EE container to the extent in that it provides the several needed services such as transaction and database management. However, unlike J2EE like containers, these services are not fixed but can be added, removed and updated. The virtual container **320** of the preferred embodiment, is a higher level concept. It views an environment as a collection of discrete higher level services and recognizes the need for business services to be integrated with those higher level services. It limits its scope to the infrastructure level services and does not provide those services that are needed for implementing the business logic, such as database management.

[0065] The container is called "virtual" because it itself is a platform independent definition rather than a physical implementation. It is described in terms of metadata. The

metadata for the container describes the business service implementation that is it hosting. This service was built using the development tools and its definition is part of the development metadata. In an integrated system of tools, the deployment tool may retrieve this definition from the development metadata repository.

[0066] The metadata for the container also describes one or more application infrastructure services required by the virtual container. When a virtual container is created, it is created for a particular deployment domain. This deployment domain is already preconfigured with one or more infrastructure-level services. The deployment engineer can select from those infrastructure services and integrate them into the container using visual mechanisms such as dragging and dropping them on the container. At this time, the tools may invoke the plugin and bring up the set of properties necessary to correctly use the infrastructure-level service.

[0067] Once the virtual container has been defined, there is enough metadata to generate a physical implementation of the virtual container, build it, package it and transfer the required binaries to the host. Once this is done, the business service is ready to be deployed and used. When the code is generated, it is generated according to some pre-defined mappings of the metadata to the underlying platform. So for example, the physical implementation for NET platform may be quite different from the physical implementation for J2EE. These mappings define what elements of the metadata generate what kind of code for the underlying platform.

[0068] Many underlying platforms either need to add software code that is specific to them or require certain information in various configuration files for the applications to function properly. For example, an application infrastructure service using microsoft's implementation of WS-Security specification requires certain information to be placed into the NET specific configuration files. Also, some application infrastructure services may need to insert specific programming code in the generated code. For example, a load balancing service may need to insert specific programming code in the generated container code as well as the generated client proxy to properly exploit its capabilities. For this reason, the code generators involve the application infrastructure service plugs in the code generation process. When code generator starts, it also loads the plugs for the infrastructure services being used by the container. All code to be generated, whether it is language code or configuration code is represented in XML. The code generator first creates XML documents for all the code that it wants to generate. It then invokes the infrastructure service plugs and provides them an opportunity to add code specific to them by passing the XML documents representing the code to be generated. Once all the plugs have added their code, the code generator converts the XML documents back into either language specific code or configuration code, as necessary. This way, the code generation process can be kept completely independent of a particular infrastructure service while still allowing them to customize the generated code.

[0069] The separation between the business service implementation and the underlying environment provides two benefits. First, it allows the underlying application infrastructure and the business service implementation itself to evolve independent of each other. Secondly, this allows the physical manifestation of the hosted service to leverage fully the capabilities offered by various infrastructures. This is explained in more detailed below, but simply put it means that the virtual container **320**, through metadata **330** and visual tools, can be visually composed to integrate one or more services offered by the underlying infrastructure. Since this integration is performed through the virtual container and at configuration time, it does not become part of the service implementation itself. The same procurement service can then be configured and deployed in two different deployment domains providing different levels of service.

[0070] Once the container has been configured and its software code has been generated and built, a package can be created that includes all the necessary platform specific binary assemblies required for this service. This package is then placed in a master vault. At this point, a visual deployment tool can provide some mechanism such as drag-and-drop to deploy this business service on any machine that is part of the deployment domain. If a host is then dragged and dropped on the virtual container, its package is collected from the master vault and brought over to the machine being dragged and dropped. This package is then opened up and its contents are extracted. These contents are then configured in a manner that is specific to the underlying platform.

[0071] The actual addressable and accessible service is then provided by the physical form of the virtual container **320** which can be specific to the underlying environment.

[0072] The traditional definition of management services tools **310** are network managers. The management services and tools described here have more application level context than the system level context. Some examples of management tools are business service monitoring tools, service level agreement (SLA) management tools, fault tolerance tools, application event handling, billing and accounting services or user profile management.

[0073] Various application infrastructure services may provide their own management tools that will use the data collected by their plugins.

[0074] The most fundamental and core capability of this architecture is the metadata **330**. The metadata described here is logical metadata. Logically, each deployment domain **300** has its own instance of metadata **330**. This metadata describes the deployment domain itself in terms of the infrastructure services that it is able to offer and the virtual service containers **320** that are deployed in it.

[0075] As a general rule, the exact form that the metadata is stored in is not important. The platform can choose an XML format, a relational database or some binary form.

[0076] **FIG. 4** illustrates a federated metadata storage and access system with various possible clients of the metadata. The development tools will require metadata that describes the team development environment and will allow sharing of development artifacts. One exemplary implementation of the metadata architecture is illustrated below.

[0077] The metadata has been described above as a part of other elements. It is useful to note that the two kinds of metadata that are relevant here are configuration/deployment metadata and operational metadata.

[0078] The configuration/deployment metadata is used by the configuration and deployment tools as well as by the runtime system. This data will not change often but will

rather be accessed concurrently by large number of users. A configuration metadata server should preferably offer extensive caching features where the data is handed out with a time-to-live parameter indicating how long the client can use the data before being required to refresh it.

[0079] Operational metadata is used by one or more infrastructure services such as a monitoring service, load balancing service, and fault-tolerance service. This data tends to change very frequently and the tools that present this data, for viewing and analysis, may be required to refresh based on user preferences.

[0080] The following is an exemplary case use in accordance with the preferred embodiment. Here, we look at a typical use case scenario of a large bank that serves consumer loan market. The bank has a large internal IT organization, responsible for delivering the business services to its users. The IT organization has to overcome the challenges of building applications that will survive the changing technology. Furthermore, the enterprise considers the conformance of industry standards as its strategic goal.

[0081] The two initial applications that have been identified have different needs. The first application is an Online Loan Approval System. Although the logic for credit-approval already exists in the form of many small systems, the bank wants to build a new system that uses that logic but re-implements it in a more consolidated and scalable manner. Previously, the bank employed a large loan approval department that received the loan requests either through fax or telephone and used these multiple systems to score the applicant's credit history and make the loan decisions. However, the bank wants to make this system available online so that the applicant's could themselves apply for the loan. In addition to its potential clients, the bank may also decide later on to make this system available to its smaller business partners to get credit history of clients and to provide services such as credit risk scoring. For those services, the bank may charge those business partners on a per-transaction basis.

[0082] The second system is an application, called Customer Service Online system, that will allow bank's consumer loan clients to get the status of their accounts, directly without going through customer service. This information already exists in a legacy J2EE system that is deployed in the internal secure network. The bank wants to build a front-end web service to this system.

[0083] In order to meet its strategic technical objectives, the bank has standardized on toolkit in accordance with the preferred embodiment. The bank also has a well-structured group that runs its data centers. The data center has system architects and system administrators who collectively run the managed environment for all the bank's applications.

[0084] As is with any system, the normal steps of requirements gathering and requirements analysis are performed. These steps are no different than any other application development project. However, once the requirements have been analyzed, the application architect will transform the requirement for the Online Loan Approval System into a business interface. This business interface becomes the contract that has to be implemented. The logic that implements this business interface is termed as the business logic that has to be developed.

[0085] The application architects use a off-the-shelf modeling tool to model the service contract. This contract identifies the operations (business functions) that the service exposes, defines a type system that defines the data required as inputs or is returned as outputs by those operations. This business interface is critical data because it defines the Contract between this business service and its users. Once the application architects have stabilized the business contract, they extract contract information from the modeling tools and generate metadata in a metadata repository, in accordance with the preferred embodiment.

[0086] The development team then takes this business contract and conducts a detailed design and develops the business logic. The development team decides to use C# as the development language and the implementation is developed as C# assembly.

[0087] The development team only focuses on implementing the business logic as required by the business contract. They do not address other key issues such as security, billing or scalability. Their efforts are strictly focused on building one or more assemblies that implement the business logic.

[0088] Once the implementation has been built and tested in stand-alone mode, an implementation package is created that contains the necessary metadata and DLLs and is handed over to the data center that is responsible for deploying and managing bank's applications.

[0089] The customer service system presents a different scenario than the first one. The bank really does not want to change the exiting system. The system works well and already has all the necessary functions required to fulfill the task. However, this system was purchased by the bank from a 3rd party and provides no way for bank to expose it to external users and is not manageable.

[0090] The application architects have decided to use a system in accordance with the preferred embodiment to build a front-end gateway service that will expose the functionality of this system to the external users and will conform to the strategic goals of the bank in being standards compliant and be manageable.

[0091] This process is very simple. The introspection capabilities of the preferred embodiment are used to analyze the J2EE interfaces exposed by the existing applications. From these, then one or more functions are selected and system then automatically generates the required metadata, populates the metadata repository and then generates a gateway implementation that can delegate requests to the existing system. As in the previous case, this gateway implementation is then packaged in JAR files, and an implementation package is created. This implementation package is then handed over to the data center that is responsible for configuring, deploying and managing bank's applications.

[0092] Once the data center receives an implementation package, it is ready to configure the service. It is assumed that by this time the minimal metadata that describes the service interface has been defined in the metadata repository.

[0093] The data center already has several different deployment domains configured. The data center also uses several infrastructure services such as Security. For some of its infrastructure services, the vendors provided toolkit-

compatible plug-ins and for others the data center wrote its own. In either case, those infrastructure services are properly configured for the preferred embodiment and fit in its plug-and-play architecture.

[0094] Configuring a business service involves several different steps that allow a business service implementation to be transformed into a managed and hosted web service.

[0095] The business service implementation provided to the data center is an implementation package that contains one or more DLLs or JAR files that implement the business behavior. These implementations lack the appropriate environment required to make the business service addressable and hostable and they also lack the necessary infrastructure capabilities such as security.

[0096] The first step that the system architects do is to define a virtual container. This virtual container extends the metadata describing the service contract with metadata relating to the desired infrastructure services. This metadata will be used later on to create a physical web service that will provide a proper execution environment for the business logic implemented by the developers and will provide the flexible management environment required by the data center to perform its functions.

[0097] During this process, the system architects also decide what infrastructure level capabilities (security, transactions, etc.) are required for this business service. They then use the drag-and-drop facilities available in the visual composition environment of the preferred embodiment to create this container. As new infrastructure services are dragged onto the virtual container, these infrastructure services plugs are invoked by the graphical environment and at this time, these plugs populate the metadata with a set of properties that they would like to be customized. The graphical environment then presents those properties in a property editor and lets the system architect provide unique values of those properties. They can also customize the container itself by setting its logging levels as well as choose the correct QoS parameters such as various delivery modes.

[0098] Once the virtual container has been configured, the system architects can select the target platform for this web service. For example, if the business implementation is written in Java, then the potential target platforms can be any of the J2EE environments supported by the installation. Alternatively, if the implementation was provided in DLLs, then the target platform can be Microsoft's NET environment.

[0099] Once the target platform has been selected, the composer tool can generate the code necessary for a web service that can be physically deployed and managed and then build that code along with the provided implementation into an executable. The composer then creates a deployment package that contains all the necessary DLLs or the JAR files required for deployment.

[0100] This package is then automatically placed in a master vault that is managed by the system of the preferred embodiment. All machines that are configured in the data center have an agent service running on them. These agents cooperate with each other to transfer packages in and out of the master vault and configure particular underlying target platforms for business services.

[0101] Once a deployable package has been created for a web service, the composer tool can be used to drag different hosts on a business service. This drag-and-drop operation triggers the actual deployment process.

[0102] When a host is dragged on a business service, the SOA Agent running on that host retrieves the deployment package from the master vault, unpackages it on that machine, performs the steps necessary to configure the underlying environment and makes the web service addressable.

[0103] A web service can be undeployed from a host by selecting that host in composer tool and simply deleting it from there. This results in all traces of that package being removed from the machine.

[0104] One a service has been deployed, it can be easily managed. Whenever, a request is sent to that service, the physical container provided by the runtime environment receives it. The runtime environment then executes all the necessary infrastructure services configured for this container and then invokes the business implementation provided by the user. When it gets the response from the business service implementation, it re-invokes any necessary infrastructure services and sends the response back to the caller.

[0105] As the technology changes, the infrastructure services can change. The system architects can use the composer tool to slowly transition the deployed business services from an old or obsolete module to a new module by simply removing the old plug from the business service and using drag-and-drop to configure the business service with new plug. The preferred embodiment automatically removes older DLLs or JARs from the physically deployed services and copies the new ones for the new plug. The business services adjust to the new infra-structure service without the typical need for interruption and modification.

[0106] To continue the bank example, after the Online Loan Approval service has been deployed, the bank decides to make that service available to its business partners for a price. An internal infrastructure level billing service is developed (along with its toolkit compatible plug) and configured. The system architects simple drag this infrastructure service on the Online Loan Approval service, without modifying the business implementation or bringing the service down. The preferred embodiment automatically modifies the metadata, reconfigures the deployed services and the runtime environment starts using this new infrastructure service when requests are sent to the business service.

[0107] One specific feature of the preferred embodiment is a visual composition environment. The preferred embodiment uses visual tools to generate metadata. These tools can present the core metadata in a tree structure as shown in **FIG. 5**.

[0108] **FIG. 5** shows an exemplary user interface **500** for a visual composition environment in accordance with the preferred embodiment. GUI interface **500** is divided into multiple areas, including available objects area **510**, active object identifier **540**, related objects area **520**, and properties area **530**.

[0109] Available objects area **510** shows all objects that are available to be configured or deployed, including hosts,

infrastructure services, service implementations, and deployment domains. The folder named "hosts" contains the list of all available hosts in the entire managed space. The information that is visible for each host in this list can be such as the name of the server and its machine address.

[0110] The folder named "infrastructure services" contains a list of all available infrastructure services. This information preferably does not contain anything more than the name of the service and its description and purpose. These are all the infrastructure services available to be deployed.

[0111] The folder named "implementation services" contains all the implementation packages that have been made available. Each of these contain the related metadata describing the service contract as well as the binaries that contain the actual implementation of that service contract behavior. It is also possible to further group the service implementations.

[0112] The folder named "deployment domains" contains the deployment domains underneath it. Each deployment domain can have a folder of its own. Each deployment domain furthermore has one folder for each virtual container in it. The folder for the virtual container all the infrastructure services that it is configured with and all the hosts that it is deployed on.

[0113] Active object identifier **540** shows which object is currently active. Here, "Domain 1" is the active object; this label will change to correspond to whichever object the user is acting upon. This area is actually sensitive to whether a deployment domain is selected or a virtual container is selected.

[0114] Related objects area **520** shows all objects, grouped according to type, which are currently associated with the active object. In this example, because deployment domain "Domain 1" is the active objects, the related objects area **520** shows all hosts, infrastructure services, and virtual containers for business services that are currently deployed in Domain 1. In this example, both Host 1 and Host 2 are associated with Domain 1, and the Security and Package Tracking services are deployed in Domain 1.

[0115] Note that if, for example, "Host 1" were the active object **540**, then the related objects area **520** would display all deployment domains, infrastructure services, and virtual containers related to Host 1. Whatever type of object is showing as the active object **540**, the other types of objects will be show in the related objects area **540**.

[0116] Finally, properties area **530** is used to define and modify the properties for any object. When an object is selected anywhere in the user interface **500**, any customizable properties related to that object will be shown in properties area **530**. The user may then edit these properties as appropriate.

[0117] Using interface **500**, the user can select an active object **540**, then drag and drop objects between the available objects **510** and the related objects area **520**. When an object is dragged from the available objects area **510** into the related objects area **520**, the system will then perform all necessary file generation and configuration, as defined by the appropriate properties, to actually form the logical relationship between the dropped object and the active object. This process is described in more detail elsewhere in this disclosure, and the implementation is within the abilities of one of skill in the art.

[0118] For example, if the "Online Catalog" service implementation were dragged into the related objects area **520** when the active object **540** is "Domain 1," then the system will automatically generate all necessary binaries, and transfer and install them as appropriate, to deploy the Online Catalog service in the Domain 1 deployment domain.

[0119] In the same manner, if an object is dragged out of the related objects area **520**, then the system will remove its logical relationship with the active object.

[0120] Up to this level, the elements are those that 4xist in global space. These are elements or pieces of metadata that are not specific to a deployment domain. Further into the deployment domain, the metadata becomes more specific.

[0121] One or more hosts can be prepared to host a deployment domain. Similarly, a single deployment domain can span multiple hosts. All the hosts configured for a specific deployment domain appear in the folder belonging to that deployment domain. These nodes may contain data such as the working area to store different deployment packages containing different binaries and configuration files belonging to the infrastructure as well as business services in that deployment domain.

[0122] An infrastructure service can be configured in multiple deployment domains and a single deployment domain will have multiple infrastructure services. This relationship is similar to the many-to-many relationship that the hosts have to a deployment domain. When an infrastructure service is configured for a deployment domain, its related software, such as its plugins, is physically transferred to all the hosts that are configured for the domain.

[0123] When a new virtual service container is created, it is ready to be deployed to any of the physical machines. Each container has a folder of its own underneath the deployment domain folder. The list of hosts that appear here are the hosts where this container is physically deployed and the list of infrastructure services are the ones that his container is configured to use.

[0124] By organizing the information like this, a visual tool of the preferred embodiment can use drag-and-drop capabilities to compose the virtual service container.

[0125] **FIG. 6** shows an exemplary virtual container represented on a canvas. In this figure, the larger outside cylinder is the virtual service container **600**. The smaller cylinders inside the larger one represent the plugins **610** for the infrastructure services. At the end of the chain is the business service implementation **620** that the virtual service container is hosting. Using this representation, the user can drag and drop infrastructure services, configured for that domain, from either the tree structure or a graphical palette. Similarly, the container can be dragged onto a host in that domain, thus triggering the physical deployment.

[0126] Another feature is the unique customization of the use of the configured infrastructure properties through a system of property sheets. When a virtual container is configured with an infrastructure service, at that time the preferred embodiment loads the plug of the infrastructure service and invokes the plug, providing it the empty collec-

tion of property sheets. The plug responds by populating this collection with property sheets that contain properties that it is interested in. The runtime system and the composition tools do not know anything about these properties. One the plug has populated the property collections with properties specific to it, the composition tools presents those properties in a property editor that allows the user to provide unique values for those properties. These properties are then saved with the other metadata and can be changed later on. Each collection contains one or more property sheets and each property sheet contains one or more properties. This organization of properties allows for a more readable and understandable organization of the properties.

[0127] Another feature of the preferred embodiment is the code-generation capability. Once a container has been configured, its definition is complete. However, it is not yet ready to be physically deployed because it is only a definition at this point. However, since now the definition is complete, the user can select a target environment such as NET or an EJB server. Once the target environment has been selected a code generation scheme can be selected to generate software code that maps the definition of the virtual container to the computer facilities offered by the underlying target platform. This code can then be compiled and linked with the runtime environment required by the platform and a package is created.

[0128] Various color coding schemes can be used to describe the state that the container is in. The possible stages identified include configured, packaged, and deployed.

[0129] The code generation software can additionally generate smart proxies that perform the equivalent of the virtual service container for the client. These smart proxies integrate the infrastructure services as defined by the business service for the client. For example, a business service may require the client application to authenticate itself against the security infrastructure service and send only the authentication token to the business service. A smart proxy will retrieve the metadata for the client and invoke the infrastructures configured for the virtual container that are relevant for the client environment. These plugs can then prompt the client for any data that they might require and use the runtime environment to send that data to the virtual container along with the rest of the request data.

[0130] Just as the virtual service container can be packaged into a distributable unit, the smart proxies can also be packaged into a distributable unit. These units can then be separately provided to those who are interested in building client applications to those business services.

[0131] Another feature of the preferred embodiment is software configuration capability. Once the code for the virtual service container has been generated, compiled, and packaged, the container can be placed into a packaged state. At this point, a host can be dragged on the container. This will cause the software configuration facility to perform separate steps:

[0132] It can transfer the deployment package that contains all the related files to the target host machine;

[0133] These files can then be unpackaged on that machine by this facility automatically and placed into the specific directories structure required by the underlying platform;

[0134] In the case of web services, the web server can be configured to know about the web service. Similarly in case of an J2EE, the EJB server can be configured to know about the service; and

[0135] The configuration files can be placed into the proper areas.

[0136] Once these steps have been performed, the virtual service container has been transformed into a physical service that can be invoked.

[0137] At a later time, when updates are made available for either the business service implementation or the infrastructure services plugs, the corresponding packages can be updated and these updates can be propagated to all the machines where the physical business services are deployed.

[0138] **FIG. 7** shows a flowchart of an exemplary process in accordance with the preferred embodiment. In this process, the user accesses a user interface and selects a deployment domain (step **705**). The user then drags an icon representing a host system into the deployment domain area depicted on the user interface (step **710**). In response, the host is associated with that deployment domain and any other objects in the deployment domain (labeled DD in figure, step **715**).

[0139] The user drags an icon representing an infrastructure service (labeled IS in figure) into the deployment domain area depicted on the user interface (step **720**. In response, the infrastructure service is associated with the deployment domain and any other objects within the deployment domain (step **725**).

[0140] The user drags an icon representing a service implementation (labeled SI in figure) into the deployment domain area depicted on the user interface (step **730**), thus starting the definition of a virtual container, and optionally specifies properties for the virtual container (step **735**). In response, the service implementation is associated with the deployment domain and any other objects within the deployment domain (step **740**).

[0141] The user then drags one or more infrastructure services from within this domain onto the virtual container (labeled VC in figure, step **745**), and optionally specifies the properties for the infrastructure services (step **750**). In response, the system associates this infrastructure service with the virtual container (step **755**).

[0142] The system then evaluates any new or changed associations (step **760**). The system generates any code necessary to implement the associations (step **765**), and transmits and installs the generated code as necessary (step **770**). In this way, the user is able to fully manage the deployment domain, and to deploy and manage the hosts and services within it, all using a simple and intuitive user interface.

[0143] It should be noted that in the exemplary process described above, and other processes described herein, not all steps must be performed at any given time. Furthermore, many of the process steps described above may be performed in any order, or repeated, without changing the nature of the process or the advantages it provides.

[0144] It should also be noted, as discussed above, that a similar method can be used when a host or service is first

selected, then other services, hosts, or a deployment domain is then associated with that host or service using the drag-and-drop technique above. Similarly, the implementing code will then be generated and installed by the system.

[0145] Those skilled in the art will recognize that, for simplicity and clarity, the full structure and operation of all data processing systems suitable for use with the present invention is not being depicted or described herein. Instead, only so much of a data processing system as is unique to the present invention or necessary for an understanding of the present invention is depicted and described. The remainder of the construction and operation of data processing system may conform to any of the various current implementations and practices known in the art.

[0146] It is important to note that while the present invention has been described in the context of a fully functional system, those skilled in the art will appreciate that at least portions of the mechanism of the present invention are capable of being distributed in the form of instructions contained within a machine usable medium in any of a variety of forms, and that the present invention applies equally regardless of the particular type of instruction or signal bearing medium utilized to actually carry out the distribution. Examples of machine usable mediums include: nonvolatile, hard-coded type mediums such as read only memories (ROMs) or erasable, electrically programmable read only memories (EEPROMs), user-recordable type mediums such as floppy disks, hard disk drives and compact disk read only memories (CD-ROMs) or digital versatile disks (DVDs), and transmission type mediums such as digital and analog communication links.

[0147] Although an exemplary embodiment of the present invention has been described in detail, those skilled in the art will understand that various changes, substitutions, variations, and improvements of the invention disclosed herein may be made without departing from the spirit and scope of the invention in its broadest form.

[0148] None of the description in the present application should be read as implying that any particular element, step, or function is an essential element which must be included in the claim scope: THE SCOPE OF PATENTED SUBJECT MATTER IS DEFINED ONLY BY THE ALLOWED CLAIMS. Moreover, none of these claims are intended to invoke paragraph six of 35 USC §112 unless the exact words "means for" are followed by a participle.

What is claimed is:

1. A method for managing services, comprising:

receiving a selection of a deployment domain;

receiving an instruction to associate an object with the deployment domain;

generating software code necessary to associate the object with the deployment domain; and

installing the software code.

2. The method of claim 1, wherein the object is a host data processing system.

3. The method of claim 1, wherein the object is a service implementation software module.

4. The method of claim 1, wherein the object is an infrastructure service software module.

5. The method of claim 1, wherein the selection is received in a graphical user interface.

6. The method of claim 1, wherein the instruction is made by dropping an icon representing the object onto a graphical user interface screen portion associated with the deployment domain.

7. The method of claim 1, further comprising receiving property information associated with the object.

8. A data processing system having at least a processor and accessible memory, comprising:

means for receiving a selection of a deployment domain;

means for receiving an instruction to associate an object with the deployment domain;

means for generating software code necessary to associate the object with the deployment domain; and

means for installing the software code.

9. The data processing system of claim 8, wherein the object is a host data processing system.

10. The data processing system of claim 8, wherein the object is a service implementation software module.

11. The data processing system of claim 8, wherein the object is an infrastructure service software module.

12. The data processing system of claim 8, wherein the selection is received in a graphical user interface.

13. The data processing system of claim 8, wherein the instruction is made by dropping an icon representing the object onto a graphical user interface screen portion associated with the deployment domain.

14. The data processing system of claim 8, further comprising means for receiving property information associated with the object.

15. A computer program product tangibly embodied in a computer-readable medium, comprising:

instructions for receiving a selection of a deployment domain;

instructions for receiving an instruction to associate an object with the deployment domain;

instructions for generating software code necessary to associate the object with the deployment domain; and

instructions for installing the software code.

16. The computer program product of claim 15, wherein the object is a host data processing system.

17. The computer program product of claim 15, wherein the object is a service implementation software module.

18. The computer program product of claim 15, wherein the object is an infrastructure service software module.

19. The computer program product of claim 15, wherein the selection is received in a graphical user interface.

20. The computer program product of claim 15, wherein the instruction is made by dropping an icon representing the object onto a graphical user interface screen portion associated with the deployment domain.

21. The computer program product of claim 15, further comprising instructions for receiving property information associated with the object.

* * * * *