



EP 6945

(51) International Patent Classification:  G01B 9/02, 11/16	A1	(11) International Publication Number: WO 79/00320 (43) International Publication Date: 14 June 1979 (14.06.79)
---	----	--

(21) International Application Number: PCT/GB78/00043

(22) International Filing Date:  
24 November 1978 (24.11.78)

(31) Priority Application Number: 49170/77

(32) Priority Date: 25 November 1977 (25.11.77)

(33) Priority Country: GB

(71) Applicants: NATIONAL RESEARCH DEVELOPMENT CORPORATION; P. O. Box 236, Kingsgate House, 66-74 Victoria Street, London, United Kingdom SW1 E6SL (*for all designated States except US*). McKELVIE, James; 2 Waterside Gardens, Carmunnock, Clarkston, Glasgow, United Kingdom (*for US only*). WALKER, Colin, Alexander; 44 North Grange Road, Bearsden, Glasgow, United Kingdom (*for US only*).


(72) Inventors: McKELVIE, James; 2 Waterside Gardens, Carmunnock, Clarkston, Glasgow, United Kingdom. WALKER, Colin, Alexander; 44 North Grange Road, Bearsden, Glasgow, United Kingdom.

(74) Agent: IRISH, Vivien, Elizabeth; Patent Department, P. O. Box 236, Kingsgate House, 66-74 Victoria Street, London, United Kingdom SW1 E6SL.

(81) Designated States: CH, DE, FR (European patent), JP, US.

Published with:  
*International search report*  
*Amended claims*

(54) Title: METHOD AND APPARATUS FOR SENSING IN-PLANE DEFORMATION OF A SURFACE



## (57) Abstract

A surface on which there is a regular periodic pattern, often a relief pattern (12), is deformed, and in-plane deformation is sensed by illuminating the deformed pattern with a beam (12) of coherent light so that light is reflected as one zero order beam and a plurality of diffracted beams, and combining two of the beams (16, 18) so that they interfere in a manner related to the deformation along the direction of intersection of the surface plane with the plane in which the two interfering beams lie. The magnitude and direction of in-plane deformation in one or more directions and the magnitude and direction of the maximum in-plane stress or strain, can be determined automatically.

*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT

AT	Austria	LU	Luxembourg
BR	Brazil	MC	Monaco
CF	Central African Empire	MG	Madagascar
CG	Congo	MW	Malawi
CH	Switzerland	NL	Netherlands
CM	Cameroon	SE	Sweden
DE	Germany, Federal Republic of	SN	Senegal
DK	Denmark	SU	Soviet Union
FR	France	TD	Chad
GA	Gabon	TG	Togo
GB	United Kingdom	US	United States of America
JP	Japan		

- 1 -

METHOD AND APPARATUS FOR SENSING IN-PLANE DEFORMATION  
OF A SURFACE

This invention relates to a method and apparatus for sensing in-plane deformation of a surface.

It is known to sense the in-plane deformation of a surface by applying a regular relief pattern to the surface, deforming  
05 the surface, recording the deformed relief pattern by forming a cast, and examining the cast by two incident beams of light. This is described in the specification of UK Patent No. 1,454,340, University of Strathclyde. However, the casting step may in some circumstances be inconvenient.

10 In the specification of UK Patent No. 1,364,607, Canon Kabushiki Kaisha, a photographic record of a deformed periodic pattern on a surface is illuminated by two beams of light, and two beams diffracted by the record are combined. Such an arrangement allows photographic recording of contours of in-plane  
15 deformation in one dimension, but does not allow instantaneous analysis.

According to the invention, a method of sensing in-plane deformation of a surface on which there is a regular periodic pattern comprises deforming the surface so as to deform the  
20 pattern; illuminating the deformed pattern with a beam of coherent electromagnetic radiation so that the radiation is reflected as one zero order beam and a plurality of diffracted



- 2 -

beams; and combining two of said beams, whereby the beams interfere in a manner related to the deformation along the direction of the intersection of said plane of the surface with the plane in which the two interfering beams lie.

05        Conveniently and for geometrical simplicity, the illuminating beam is collimated and is incident normally on the grating and two beams of the same diffracted order number and of opposite sign are combined. Alternatively, the zero order beam can be combined with a diffracted beam, or two beams each in a different  
10        diffracted order may be combined.

         The regular periodic patterns may be intrinsic to the surface, or may be a grating, preferably a phase grating such as a relief grating, attached to the surface, for example by a suitable adhesive, or formed in a material which itself adheres  
15        to the surface.

         Preferably the relief pattern is such that all of the incident energy is diffracted into only a small number of diffracted orders. Such a relief pattern may have a substantially sinusoidal transverse section and may be of pitch of between  
20        about  $10^{-1}$  and about  $10^{-3}$  millimetres. The illuminating wavelength is not limited by the grating pitch, and for convenience visible light may be used.

         If the deformation in a single in-plane direction is to be sensed, then the relief pattern may be periodic in that  
25        direction only. However, measurement of strain in a single



- 3 -

direction is not always adequate, and the direction of strain is not always predictable.

Further according to the invention, a method in which the pattern is periodic in two in-plane dimensions and at least three beams are combined as at least two pairs, one beam intersecting the plane defined by two other beams. Usually the pattern will be periodic in two orthogonal directions. For convenience and simplicity two pairs of beams may be combined, each pair lying in one of two planes relatively at right angles, or at another known angle, and both planes intersecting the deformed surface, preferably at right angles. Alternatively, there may be three pairs of beams each pair lying in a plane with two planes lying relatively at right angles and the third plane lying at a substantial angle, often  $45^{\circ}$ , to each of the other planes, all three planes intersecting the deformed surface, preferably but not necessarily at right angles.

It is an advantage of any arrangement which provides at least two combined beams that a full analysis of the in-plane strain including shear can be made with relative ease, although use of six beams combined as three beam pairs is the conceptually most simple arrangement.

Also according to the invention, apparatus for sensing in-plane deformation of a surface on which there is a regular periodic pattern comprises means for illuminating the periodic pattern with a beam of coherent electromagnetic radiation; and



- 4 -

receiving and combining means for receiving from the pattern at least two of a zero order beam and a plurality of diffracted beams, and for combining as at least one pair said at least two beams whereby the combined beams interfere. Usually the  
05 illuminating means will comprise a laser.

The or each combined pair of diffracted beams may be viewed by an observer for a qualitative assessment, or may be recorded, e.g. photographically, for subsequent quantitative assessment. However, it is an advantage of the present invention that a  
10 measurement of strain can be made automatically and almost instantaneously.

Also according to the invention, strain-sensing apparatus comprising receiving and combining means for receiving from a deformed periodic pattern illuminated by a beam of coherent  
15 electromagnetic radiation at least two of a zero order beam and a plurality of diffracted beams and for combining as at least one pair said at least two beams whereby the combined beams interfere; and sensing means to sense the average wavelength of the spatial variation transverse to the combined beam in intensity of radiation  
20 in each beam due to the interference.

The means to sense the average wavelength may comprise a linear array of photosensitive devices arranged transverse to each combined-pair beam, in the plane defined by the pair of beams before combination, the devices being small in comparison  
25 with the beam diameter. The array may be an array of photodiodes



- 5 -

or charge-coupled devices plus scanning means to repeatedly scan the array and provide an output signal depending on the intensity of the radiation on each diode or device. Alternatively, the sensing means may be a vidicon device.

05           In another arrangement there is provided phase-modulation means arranged to cause a continuously varying phase relationship between the two beams in each combined pair, whereby a moving interference pattern is produced; and two photosensitive devices arranged to receive the pattern, the devices being spaced apart  
10 by a distance which is small compared with the spatial wavelength of the interference pattern and in a direction such that the devices are separated to some extent in the plane in which the two combined beams lie; and phase comparator means to sense the difference in phase of the output signals from the two photo-  
15 sensitive devices.

The invention will now be described by way of example with reference to the accompanying drawings in which:-

Figure 1 shows schematically apparatus for sensing strain in one dimension;

20           Figure 2(a) is a section through part of a relief pattern grating suitable for use in the apparatus of Figure 1;

Figure 2(b) shows the diffracted beams when such a grating is illuminated normally;

Figure 2(c) shows the position of the diffracted orders;

25           Figure 3 illustrates a set of Moiré fringes;

Figure 4(a) shows schematically apparatus for sensing strain in three different coplanar directions;



- 6 -

Figure 4(b) shows a relief grating for such an apparatus and the relative position of the diffracted orders;

Figure 5 shows a typical interference fringe waveform viewed by an array of photodiodes;

05      Figure 6 illustrates schematically a circuit for calculating strain in three in-plane directions;

Figure 7 illustrates the use of a phase modulator in one diffracted beam;

Figure 8 illustrates the effect of phase modulation;

10      Figure 9 illustrates use of one phase modulator in the input beam of a polarised optical system;

Figures 10(a) and 10(b) show two possible arrangements of linear detector arrays; and

15      Figure 10(c) shows a two dimensional matrix of photo-detectors.

In Figure 1, an object which is to be strained is represented by reference 10 and a relief grating 12 is attached to the surface of the object by a suitable adhesive. The grating 12 is illuminated by a normally-incident collimated beam of  
20      light 14 a few millimetres in diameter produced by a laser 15 having a power supply 17 and power source 19. For example a 2 milliwatt Hughes laser can be used. The grating 12 has a regular periodic structure in one dimension as shown in Figure 2(a), with a sinusoidally varying surface of pitch AB of about 1 or  
25       $2 \times 10^{-3}$  millimetres. The grating lines formed by the surface variations are therefore perpendicular to the plane of Figure 1;





- 7 -

as shown in Figure 2(b) the incident light will be diffracted into only a few orders each of high intensity. As shown in Figure 2(c), the diffracted orders can be viewed as a line of dots of light parallel to the grating plane and perpendicular to the grating lines. Referring again to Figure 1, suppose the second order diffracted beams of opposite sign 16, 18 are reflected by means of plane mirrors 20, 22 and 24 and a beam combiner 26 to form a combined beam 30. If the grating 12 is unstrained, the light in the combined beam 30 will be spatially constant, provided the mirrors are correctly aligned. If, however, the grating is strained in the plane of the Figure and perpendicular to the incident beam from laser 14 by deforming the object 10, the combined beam will contain an interference pattern related to strain in that direction.

Consider the conventional Moiré pattern illustrated in Figure 3. The smaller the separation in the pattern, the greater the strain, synonymously with contours on a map; each contour represents unit displacement, thus strain in region C is greater than in region D. In the present invention, the arrangement in Figure 1 senses strain only in one dimension, such as the direction shown by arrow G, and represents the component in that direction of a complex strain. The pattern in the combined beam 30, although not a Moiré pattern, has some of the properties of a set of Moiré fringes. It can be displayed on a screen and viewed by eye, or recorded directly by photography, and the magnitude of the strain can be calculated.



- 8 -

Usually, a measure of the component of strain in one in-plane direction will be insufficient, and it will be necessary to duplicate or triplicate the mirrors and beam combiner in Figure 1 in order to sense strain in two or three directions in the plane of the surface. If measurements are made in two in-plane directions, they will usually be orthogonal but may be at another known relative angle. However, the most convenient arrangement is to have three systems each measuring strain in a different direction, and one possible arrangement is shown schematically in Figure 4(a).

Figure 4(a) illustrates a view equivalent to that along the laser beam 14 towards the grating (not shown) and shows the mirrors 22, 24 and beam combiner 26 arranged as in Figure 1. Two other similarly arranged sets of mirrors 32, 34 and 42, 44 each have an associated beam combined 36; 46 as shown; each optical system can sense strain in a different direction in the plane of the relief grating. For convenience two directions are orthogonal and the third makes an angle of  $45^\circ$  with the other two, although other relative angles can be used, provided they are substantial, e.g. more than  $20^\circ$ .

It is now necessary to provide a relief grating having a periodic structure in two dimensions, again preferably of sinusoidal shape. In Figure 4(b), which is the two-dimensional equivalent of Figure 2(c), the lines on grating 13 are seen to form a grid structure with the diffracted beams visible as a two-dimensional array of dots.



- 9 -

Referring again to Figure 4(a), the combined beams from each optical system are in different directions, and can be received on a screen or recorded photographically e.g. at position 31 in Figure 1 and at the other two corresponding

05 positions. Each combined beam is in a different direction and contains information related to a strain along one in-plane direction so that calculation of the value of strain in each in-plane direction can be made simply and easily from each interference pattern with no problem of superimposition of information

10 from different strain directions. Measurements can be made simultaneously in two or more directions. However, there is still the problem that, for an overall picture, the information on the measured strains must be combined if maximum strain and its direction are required. This may involve considerable

15 mathematical computation.

It is a great advantage of a method and apparatus according to the invention that an entirely automatic analysis system can be provided to carry out these calculations in real time. In Figure 1 instead of an observer's eye or a photographic camera

20 being placed at position 31, an electronic scanning system 38 may be used; the system may be an array of photodiodes or charge-coupled devices plus a scanning arrangement, or may be a vidicon or similar device. One scanned system is provided for each of the three optical systems in Figure 4, although for

25 clarity they are not illustrated in that Figure.



- 10 -

Suppose the spatial variation about a base line 50 of the light intensity of the interference pattern in one combined beam is as shown in Figure 5, and that this light pattern is incident on a linear array 52 of photodiodes 54. There may be 256 diodes in the array, and the voltage on each photodiode will depend on the incident light intensity. By sequential comparison of the voltage on each photodiode with a reference voltage by means of a voltage comparator, an output signal can be provided each time the base line 50 is crossed. By counting the number of photodiodes between each output signal, an average wavelength of the intensity variation in the light pattern can be calculated. A suitable apparatus is shown in Figure 6 in which three photodiode arrays 52A, 52B, 52C one for each measurement direction, are each connected to a respective scanning device 51A, B, C and the output signals supplied to one of three voltage comparators 53A, B, C, each of which supplies an output signal to an 8-bit microprocessor 55. Each comparator is supplied with a reference voltage from a unit 57A, B, C.

The microprocessor can be programmed to calculate from the three input signals the maximum principal in-plane strain averaged over the field of view on the relief grating, the maximum shear strain, and the angle of the principal strain. The result is obtained almost instantaneously and can be in numerical form. Use by operators unskilled in the interpretation of interference fringes is therefore possible. Alternatively, if the strains are in the elastic domain, stresses rather than



- 11 -

strains can be calculated by providing values of the Young's modulus and Poisson's ratio for the material which is being deformed.

In practice, it has been found that the waveform is not  
05 the smooth sinusoid shown in Figure 5 (whether of varying or invariant wavelength) but shows small-scale irregularities in its curvature; these may be caused, for example, by dirt in the optical system. A working device may operate in many adverse industrial environments so that cleanliness is impossible, and  
10 a correction must be applied. The microprocessor is operated so that from the output signals corresponding to each measuring direction an average wavelength is calculated, and the standard deviation of the distribution. Readings greater than one standard deviation from the average are discarded and the  
15 average wavelength is recalculated. It has been found that this conventional statistical technique gives an accurate measurement of fringe spacing.

However, noise from whatever source may still be a problem and an alternative technique may be used. Referring now to  
20 Figure 7, which is equivalent to Figure 1 and in which identical items of apparatus are given the same reference numerals but using a two-dimensional relief grating 13, a phase modulator 60 is placed in the optical path of beam 18. The phase modulator is arranged to apply a continuous phase,  
25 modulation to the beam 18 in a manner such as to change its



- 12 -

wavelength. The effect may be achieved using an electro-optic device, or a piezoelectric crystal, driven by a sawtooth waveform; or an acousto-optic device; or a moving diffraction grating; the change in wavelength will then be continual rather  
05 than strictly continuous.

The effect of the change of wavelength in one component of the combined beam 33 is that the previously stationary interference pattern now moves transversely to the beam, as indicated by the arrow in Figure 8. However, the background  
10 noise remains stationary. The moving pattern can be viewed by two photodiodes 56, 58 separated by a distance  $\delta x$  which is small with respect to the wavelength  $\lambda$  of the fringe pattern. Knowing  $\delta x$ , a measurement by phase comparator 59 of the phase difference between the outputs of the two photodiodes 56, 58  
15 allows a calculation, of the average wavelength  $\lambda$  of the pattern, which is unaffected by background noise. The two photodiodes replace the diode array 52 in Figures 5 and 6 and this arrangement is alternative to use of a diode array plus calculation of standard deviation.

20 In this arrangement, one phase modulator and one phase comparator must be supplied in each of the three optical systems shown in Figure 4, and the outputs from the two photodiodes associated with each system are connected to the respective comparator.

- 13 -

An alternative arrangement avoids the need for two or three phase modulators which may be bulky and/or expensive, and is shown in Figure 9. Only one phase modulator is used in conjunction with a polarised optical system. The general  
05 arrangement is similar to that in Figures 1 and 7, although one mirror is omitted for simplicity.

The laser beam 14, having a first plane of polarisation indicated by the bars on the axial path, is incident on a beam splitter 64, which reflects part of the beam, via a plane  
10 mirror 66, to a phase modulator 68.

The modulated beam passes through a polarisation rotator 70 which rotates the plane of polarisation of the beam through  $90^\circ$  to a second plane of polarisation indicated by the dots on the axial path. The modulated and rotated beam is reflected by a  
15 plane mirror 72 to a beam combiner 74 which combines it with the part of the incident beam which passes through beam splitter 64. The beam from the combiner 74 is reflected from the relief grating 12 into two second order diffracted beams 16 and 18, which both contain components at two orthogonal planes of polarisation,  
20 one component being modulated. The beam 18 is reflected from plane mirror 24 through a polariser 76 which allows passage of radiation only in the second plane of polarisation, i.e. the phase-modulated beam; the polarised radiation then passes through a polarisation rotator 78 which causes rotation through  $90^\circ$  into  
25 the first plane of polarisation. The beam 16 is reflected by



- 14 -

mirror 22 through a polariser 80 which allows passage of radiation only in the first plane of polarisation, i.e. which prevents passage of the modulated beam component. The two transmitted beams are combined by beam combiner 26 and are sensed  
05 by two closely-spaced photodiodes 56, 58 as before. The combined beam is linearly polarised in the first plane of polarisation but contains both phase-modulated and unmodulated components from beams 18 and 16 respectively, so that a moving fringe system is provided as in the Figure 7 one-dimensional arrangement. By  
10 supplying second and third sets of optical components equivalent to mirrors 22, 24, polarisers 76, 80, rotator 78 and beam combiner 26, patterns relating to second and third sensing directions can be provided, but use of the polarisers and polarisation rotators allows the provision of only one phase modulator.

15 Several alternatives are available in the apparatus according to the invention. For example, instead of using a coarse relief grating and higher diffracted orders as shown in Figure 1, a high frequency grating and beam pairs from lower diffracted orders can be used. It has already been stated that analysis using  
20 one or two directions is possible, although a three-direction in-plane analysis system is most widely applicable.

Throughout the description of the invention it has been assumed that the undeformed regular periodic grating is perfect. This will not usually be the case in practice, but in most  
25 cases grating imperfections will significantly affect the





- 15 -

measurement of strain in the deformed grating only when the measured value is less than about 10 microstrains i.e. grating imperfections are normally less than 10 microstrain. It is the usual practice to check for grating imperfections by viewing  
05 at least one combined beam pair before deforming the grating; when an automatic fringe-counting system is used, this initial measurement may be used to correct the measurement made on the deformed grating if great accuracy is required.

When an automatic fringe-counting system is used, a typical  
10 beam diameter is a few millimetres, and the strain measured is averaged over the field of view (the photodiodes usually view an area smaller than the beam diameter). For use without an automatic readout, the beam diameter may be about 50 millimetres, and strain variations within the field of view can be observed.

15 It is an advantage of the arrangements using the larger beam area that buckling of the grating out of the plane of measurement is only a second order effect. When an automatic system is used, the effect is still small, but can be compensated by measuring the position of the zero diffraction order, and applying the  
20 appropriate correction to the measured values.

A further modification involves the use of two beam pairs whose generating beams lie in planes which intersect at a substantial angle. Usually they will intersect at right angles. A two-dimensional array of photosensitive devices may be used  
25 to sense the spatial variations of the interference fringes

- 16 -

both parallel to the plane of two uncombined beams, and perpendicular to it. Figures 10(a) and 10(b) show suitable detector arrays 82, 84 arranged to form a T shape or an L shape. A cross shape may also be used. One such array is used in each  
05 combined beam, and the in-plane strain may be calculated from the four measurements. It is an advantage of this that the optical system is less complex.

Yet another modification involving use of a large field of view may be made even with an automatic measuring system. A  
10 two-dimensional photosensitive device or a matrix 86 of discrete photosensitive devices 88 as shown in Figure 10(c) may be used to sense the spatial variation transverse to the combined beam, and at a number of points in the field of view. For example, the interference fringe spacings may be measured by selecting  
15 pairs of photosensitive devices and measuring the phase difference between the signal outputs, due to the interference fringes sweeping across. By selecting pairs of photosensitive devices, which are arrayed along lines parallel to and perpendicular to the plane of the uncombined beams, the fringe  
20 spacings in these two directions can be gauged at a plurality of points in the field of view. From two such combined beam fringe pattern analyses, a complete strain contour pattern for the field of view can be constructed with suitable computation.



- 17 -

The illuminating beam in this modification may be 10 - 100 mm diameter.

It is a great advantage of the method and apparatus according to the invention that the relief grating and viewing system  
05 need not be mounted rigidly with respect to each other. Vibrations out of the plane of the relief grating, and linear in-plane vibration, have only second-order effects on the interference fringes. In-plane rotation affects both components of each combined beam. Even if the fringes are not continuously visible,  
10 the trends of a changing situation can be followed.

However, in any arrangement according to the invention, it is essential to keep the items of optical apparatus accurately in alignment, otherwise there is a risk that mechanical vibration of the system will prevent the formation or reception  
15 of one or more combined beams. It will often be necessary to use a conventional servo mechanism to stabilise the system and maintain the required alignment.

While the invention has been described with reference to relief gratings, which have been found to be efficient in this  
20 use, other regular periodic gratings may be used, for example an intensity-modulated grating or a bleached thick hologram having a reflecting back surface.

The invention has been described with reference to a system which does not incorporate any lenses. If a very small  
25 field of view is required, for example when spatial resolution



- 18 -

is important, a magnifying system can be provided to magnify the beam incident on the detector system.

In the described arrangement, two diffracted beams in the same order but of opposite sign are caused to interfere; this is  
05 advantageous because the interfering beams will be of the same intensity; further, sensitivity is related to the angle between the diffracted beams, so a symmetrical system gives highest sensitivity. However, if maximum sensitivity is not important, the zero order beam can be combined with one or two or three  
10 diffracted beams. This minimises the physical size of the apparatus by halving the angle between the received diffracted beams, so that use in a restricted position, such as in a corner, may be facilitated, but there is the disadvantage that at least one additional beam splitter is required.

15 In the illustrations, the required beams are combined after reflection from small mirrors. This assumes that the general proportions of the apparatus are such that each mirror receives only one beam, either because the incident beam is narrow, or because the distance of the mirrors from the surface is sufficient  
20 for the diffracted beams in a wide-beam system to be separated. A possible method of separating overlapping diffracted orders is to position a lens and an aperture stop between the beam combiner (reference 26 in Figure 1) and the detecting system.

- 19 -

CLAIMS

1. A method of sensing in-plane deformation of a surface on which there is a regular periodic pattern and which is deformed when the surface is deformed characterised by comprising  
05 illuminating the deformed relief pattern with a beam of coherent electromagnetic radiation so that the radiation is reflected as one zero order beam and a plurality of diffracted beams; and combining two of said beams, whereby the beams interfere in a manner related to the deformation along the direction of the  
10 intersection of said plane of the surface with the plane in which the two interfering beams lie.
2. A method according to Claim 1 in which the regular periodic pattern is a relief pattern.
3. A method according to Claim 1 or Claim 2 in which two  
15 beams of the same diffracted order number and of opposite sign are combined.
4. A method according to Claim 1 or Claim 2 in which the zero order beam is combined with a diffracted beam.
5. A method according to any preceding claim in which the  
20 pattern is periodic in two in-plane dimensions, and at least three beams are combined as at least two pairs, one beam intersecting the plane in which two other beams lie.
6. A method according to Claim 5 in which the pattern is periodic in two orthogonal directions, and two pairs of beams  
25 are combined, each pair of beams lying in one of two orthogonal planes.



- 20 -

7. A method according to Claim 5 in which the pattern is periodic in two orthogonal directions, and three pairs of beams are combined, each pair lying in a plane with two of the planes being orthogonal and the third plane lying at  $45^{\circ}$  to each of the orthogonal planes, all three planes intersecting the deformed surface at right angles.
8. Apparatus for sensing in-plane deformation of a surface on which there is a regular periodic pattern and having means for illuminating the pattern with a beam of coherent electromagnetic radiation: characterised by comprising receiving and combining means (20, 22, 24, 26) for receiving from the pattern at least two of a zero order beam and a plurality of diffracted beams, and for combining as at least one pair said at least two beams whereby the combined beams interfere.
9. Apparatus according to Claim 8 having means (20, 22, 24, 26) for receiving and combining two beams of the same diffracted order number and of opposite sign.
10. Apparatus according to Claim 8 having means for receiving and combining the zero order beam and a diffracted beam.
11. Apparatus according to Claim 8 having means (22, 24, 26, 32, 34, 36) for receiving and combining at least three beams to form two pairs, one beam intersecting the plane in which the other two beams lie..



- 21 -

12. Apparatus according to Claim 8 having means (22, 24, 26, 32, 34, 36) for receiving and combining four beams as two pairs; each pair of beams lying in one of two orthogonal planes.
13. Apparatus according to Claim 8 having means (22, 24, 26, 32, 34, 36, 42, 44, 46) for receiving and combining three pairs of beams, each pair lying in a plane with two of the planes being orthogonal and the third plane lying at  $45^\circ$  to each of the orthogonal planes, all three planes intersecting the deformed surface at right angles.
14. A strain measuring apparatus characterised by comprising receiving and combining means (20, 22, 24, 26) for receiving from a deformed periodic pattern illuminated by a beam of coherent electromagnetic radiation at least two of a zero order beam and a plurality of diffracted beams and for combining as at least one pair said at least two beams whereby the combined beams interfere, and sensing means (38) to sense the average wavelength of the spatial variation transverse to the combined beam of the interference pattern in the combined beam.
15. Strain measuring apparatus according to Claim 14 in which the sensing means includes a linear array (52) of photosensitive devices (54) arranged transverse to the combined-pair beam and in the plane defined by the pair of beams before combination.
16. Strain measuring apparatus according to Claim 14 in which the average wavelengths of the spatial variation of the interference patterns in two combined beams are each sensed by two linear



- 22 -

arrays (82, 84) of photosensitive devices arranged transverse to each combined beam and at right angles to each other.

17. Strain measuring apparatus according to Claim 14 in which the sensing means includes a two-dimensional photosensitive device (86) arranged transverse to the combined-pair beam.
18. Strain measuring apparatus according to Claim 14 comprising phase-modulation means (60) arranged to cause a continuously varying phase relationship between the two beams in a combined pair whereby a moving interference pattern is produced; two photosensitive devices (56, 58) arranged to receive the pattern, the devices being spaced apart by a distance which is small compared with the spatial wavelength of the interference pattern and in a direction such that the devices are separated in the plane in which the two combined beams lie; and phase comparator means (59) to sense the difference in phase of the output signals from the two photosensitive devices.
19. Strain measuring apparatus according to Claim 18 in which the illuminating means further comprises polarising and modulating means (68, 70) arranged to provide an illuminating beam consisting of radiation at two orthogonal directions of polarisation, radiation polarised in one direction being modulated and radiation polarised in the other direction being unmodulated; and the receiving and combining means further comprises polarising means (76, 78, 80) arranged so that the modulated component of one received beam and the unmodulated component of the other received beam are combined as a beam pair.





- 23 -

20. Strain measuring apparatus according to Claim 19 comprising three receiving and combining systems, each including a polarising means arranged so that in each of three beam pairs a modulated component of one received beam is combined with an  
05 unmodulated component of the other received beam.

21. A strain measuring system for measuring in-plane deformation of a surface on which there is a regular pattern which is periodic in two in-plane directions and which is illuminated by a beam of coherent electromagnetic radiation characterised  
10 by comprising receiving and combining means (20, 22, 24, 26) for receiving from the pattern at least three of a zero order beam and a plurality of diffracted beams, one beam intersecting the plane in which the other two beams lie, and for combining as at least two pairs said at least three beams whereby the combined  
15 beams interfere; sensing means (52A, B, C) to sense the average wavelength of the spatial variation of the interference pattern in each combined beam; and calculating means (55) to calculate from the sensed average wavelengths at least one of the maximum principal in-plane stress or strain, the angle of  
20 the principal stress or strain, and the maximum shear stress or strain.



-24-

## AMENDED CLAIMS

(received by the International Bureau on 9 March 1979 (09.03.79))

1. A method of sensing in-plane deformation of a surface on which there is a regular periodic pattern and which is deformed when the surface is deformed characterised by comprising  
05 illuminating the deformed relief pattern with a beam of coherent electromagnetic radiation so that the radiation is reflected as one zero order beam and a plurality of diffracted beams; and combining two of said beams, whereby the beams interfere in a manner related to the deformation along the direction of the  
10 intersection of said plane of the surface with the plane in which the two interfering beams lie.
2. A method according to Claim 1 in which the regular periodic pattern is a relief pattern.
3. A method according to Claim 1 or Claim 2 in which two  
15 beams of the same diffracted order number and of opposite sign are combined.
4. A method according to Claim 1 or Claim 2 in which the zero order beam is combined with a diffracted beam.
5. A method according to any preceding claim in which the  
20 pattern is periodic in two in-plane dimensions, and at least three beams are combined as at least two pairs, one beam intersecting the plane in which two other beams lie.
6. A method according to Claim 5 in which the pattern is periodic in two orthogonal directions, and two pairs of beams  
25 are combined, each pair of beams lying in one of two orthogonal planes.



7. A method according to Claim 5 in which the pattern is periodic in two orthogonal directions, and three pairs of beams are combined, each pair lying in a plane with two of the planes being orthogonal and the third plane lying at  $45^{\circ}$  to each of the orthogonal planes,  
05 all three planes intersecting the deformed surface at right angles.

8. Apparatus for sensing in-plane deformation of a surface on which there is a regular periodic pattern and having means for illuminating the pattern with a beam of coherent electromagnetic radiation characterised by comprising receiving and combining  
10 means (20, 22, 24, 26) for receiving from the pattern at least two of a zero order beam and a plurality of diffracted beams, and for combining as at least one pair said at least two beams so that the combined beams interfere in a manner related to the deformation along the direction of the intersection of said plane  
15 of the surface with the plane in which the two interfering beams lie.

9. Apparatus according to Claim 8 having means (20, 22, 24, 26) for receiving and combining two beams of the same diffracted order number and of opposite sign.

20 10. Apparatus according to Claim 8 having means for receiving and combining the zero order beam and a diffracted beam.

11. Apparatus according to Claim 8 having means (22, 24, 26, 32, 34, 36) for receiving and combining at least three beams to form two pairs, one beam intersecting the plane in which the other two  
25 beams lie.

12. Apparatus according to Claim 8 having means (22, 24, 26, 32, 34, 36) for receiving and combining four beams as two pairs; each pair of beams lying in one of two orthogonal planes.
13. Apparatus according to Claim 8 having means (22, 24, 26, 32, 34, 36, 42, 44, 46) for receiving and combining three pairs of beams, each pair lying in a plane with two of the planes being orthogonal and the third plane lying at  $45^\circ$  to each of the orthogonal planes, all three planes intersecting the deformed surface at right angles.
14. A strain measuring apparatus characterised by comprising receiving and combining means (20, 22, 24, 26) for receiving from a deformed periodic pattern illuminated by a beam of coherent electromagnetic radiation at least two of a zero order beam and a plurality of diffracted beams and for combining as at least one pair said at least two beams whereby the combined beams interfere, and sensing means (38) to sense the average wavelength of the spatial variation transverse to the combined beam of the interference pattern in the combined beam.
15. Strain measuring apparatus according to Claim 14 in which the sensing means includes a linear array (52) of photosensitive devices (54) arranged transverse to the combined-pair beam and in the plane defined by the pair of beams before combination.
16. Strain measuring apparatus according to Claim 14 in which the average wavelengths of the spatial variation of the interference patterns in two combined beams are each sensed by two linear

-27-

arrays (82, 84) of photosensitive devices arranged transverse to each combined beam and at right angles to each other.

17. Strain measuring apparatus according to Claim 14 in which the sensing means includes a two-dimensional photosensitive device (86) arranged transverse to the combined-pair beam.
18. Strain measuring apparatus according to Claim 14 comprising phase-modulation means (60) arranged to cause a continuously varying phase relationship between the two beams in a combined pair whereby a moving interference pattern is produced; two photosensitive devices (56, 58) arranged to receive the pattern, the devices being spaced apart by a distance which is small compared with the spatial wavelength of the interference pattern and in a direction such that the devices are separated in the plane in which the two combined beams lie; and phase comparator means (59) to sense the difference in phase of the output signals from the two photosensitive devices.
19. Strain measuring apparatus according to Claim 18 in which the illuminating means further comprises polarising and modulating means (68, 70) arranged to provide an illuminating beam consisting of radiation at two orthogonal directions of polarisation, radiation polarised in one direction being modulated and radiation polarised in the other direction being unmodulated; and the receiving and combining means further comprises polarising means (76, 78, 80) arranged so that the modulated component of one received beam and the unmodulated component of the other received beam are combined as a beam pair.



20. Strain measuring apparatus according to Claim 19 comprising three receiving and combining systems, each including a polarising means arranged so that in each of three beam pairs a modulated component of one received beam is combined with an
- 05 unmodulated component of the other received beam.
21. A strain measuring system for measuring in-plane deformation of a surface on which there is a regular pattern which is periodic in two in-plane directions and which is illuminated by a beam of coherent electromagnetic radiation characterised
- 10 by comprising receiving and combining means (20, 22, 24, 26) for receiving from the pattern at least three of a zero order beam and a plurality of diffracted beams, one beam intersecting the plane in which the other two beams lie, and for combining as at least two pairs said at least three beams whereby the combined
- 15 beams interfere; sensing means (52A, B, C) to sense the average wavelength of the spatial variation of the interference pattern in each combined beam; and calculating means (55) to calculate from the sensed average wavelengths at least one of the maximum principal in-plane stress or strain, the angle of
- 20 the principal stress or strain, and the maximum shear stress or strain.

1/4




Fig. 1

Fig. 2a




Fig. 2b




Fig. 2c





Fig. 3



2/4




Fig. 4a




Fig. 4b




Fig. 5






Fig. 7





4/4



# INTERNATIONAL SEARCH REPORT

International Application No PCT/GB 78/00043

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (If several classification symbols apply, indicate all) <sup>3</sup> According to International Patent Classification (IPC) or to both National Classification and IPC <p style="text-align: center;">G 01 B 9/02; G 01 B 11/16</p>				
<b>II. FIELDS SEARCHED</b>				
Minimum Documentation Searched <sup>4</sup>				
Classification System	Classification Symbols			
Int.Cl. <sup>2</sup>	G 01 B 9/02; G 01 J 9/02; G 01 B 11/16; G 02 B 5/18			
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched <sup>5</sup>				
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT</b> <sup>14</sup>				
Category <sup>*</sup>	Citation of Document, <sup>16</sup> with indication, where appropriate, of the relevant passages <sup>17</sup>	Relevant to Claim No. <sup>18</sup>		
A	US, A, 3822942, date of publication July 9, 1974, see heading; column 8, lines 37 to 67; column 10, lines 16 to 48; figures 6, 10 F. HOCK	1-3, 5, 6, 8, 9, 11, 12, 14, 21		
A	Journal of Physics, E: Scientific Instruments, volume 5, no. 9, issued September 1972, London. C.S. Sciamarella "Use of gratings in strain analysis", pages 833-845, see pages 833-835	1, 2		
A	Instruments and Control Systems, volume 44, no. 12, issued December 1971, Radnor R.S. Steele et al., "Parallel Incidence for diffraction grating strain gages", see pages 64-66	1, 2, 4		
A	Proceedings of the Soc. of Photo-Optical Instrumentation Engineers. Laser Range Instrumentation. Seminar, 16-17 October 1967, El Paso B.D. Kroeger "Electro optical shaft angle encoder utilizing laser interferometry" see pages 93-97	1, 3, 8-10		
<p><b>* Special categories of cited documents: <sup>16</sup></b></p> <table style="width: 100%;"> <tr> <td style="width: 50%; vertical-align: top;"> <p><b>"A"</b> document defining the general state of the art</p> <p><b>"E"</b> earlier document but published on or after the international filing date</p> <p><b>"L"</b> document cited for special reason other than those referred to in the other categories</p> <p><b>"O"</b> document referring to an oral disclosure, use, exhibition or other means</p> </td> <td style="width: 50%; vertical-align: top;"> <p><b>"P"</b> document published prior to the international filing date but on or after the priority date claimed</p> <p><b>"T"</b> later document published on or after the international filing date or priority date and not in conflict with the application, but cited to understand the principle or theory underlying the invention</p> <p><b>"X"</b> document of particular relevance</p> </td> </tr> </table>			<p><b>"A"</b> document defining the general state of the art</p> <p><b>"E"</b> earlier document but published on or after the international filing date</p> <p><b>"L"</b> document cited for special reason other than those referred to in the other categories</p> <p><b>"O"</b> document referring to an oral disclosure, use, exhibition or other means</p>	<p><b>"P"</b> document published prior to the international filing date but on or after the priority date claimed</p> <p><b>"T"</b> later document published on or after the international filing date or priority date and not in conflict with the application, but cited to understand the principle or theory underlying the invention</p> <p><b>"X"</b> document of particular relevance</p>
<p><b>"A"</b> document defining the general state of the art</p> <p><b>"E"</b> earlier document but published on or after the international filing date</p> <p><b>"L"</b> document cited for special reason other than those referred to in the other categories</p> <p><b>"O"</b> document referring to an oral disclosure, use, exhibition or other means</p>	<p><b>"P"</b> document published prior to the international filing date but on or after the priority date claimed</p> <p><b>"T"</b> later document published on or after the international filing date or priority date and not in conflict with the application, but cited to understand the principle or theory underlying the invention</p> <p><b>"X"</b> document of particular relevance</p>			
<b>IV. CERTIFICATION</b>				
Date of the Actual Completion of the International Search <sup>2</sup> 16th February 1979		Date of Mailing of this International Search Report <sup>2</sup> 23rd February 1979		
International Searching Authority <sup>1</sup> European Patent Office		Signature of Authorized Officer <sup>20</sup> G.L.M. Kruydenberg		