



US008678456B2

(12) **United States Patent**
Bouligny et al.

(10) **Patent No.:** **US 8,678,456 B2**
(45) **Date of Patent:** ***Mar. 25, 2014**

(54) **SINGLE JOINT ELEVATOR HAVING
DEPLOYABLE JAWS**

(56) **References Cited**

U.S. PATENT DOCUMENTS

- (71) Applicants: **Vernon Joseph Bouligny**, New Iberia,
LA (US); **Scott Joseph Arceneaux**,
Lafayette, LA (US)
- (72) Inventors: **Vernon Joseph Bouligny**, New Iberia,
LA (US); **Scott Joseph Arceneaux**,
Lafayette, LA (US)
- (73) Assignee: **Frank's Casing Crew and Rental
Tools, Inc.**, Lafayette, LA (US)
- (*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.
- This patent is subject to a terminal dis-
claimer.

1,211,999	A *	1/1917	Arej et al.	294/91
1,535,625	A *	4/1925	O'Bannon	294/91
1,548,337	A *	8/1925	Smith	294/91
1,558,261	A *	10/1925	Grady	294/91
1,656,582	A *	1/1928	Harder	294/91
1,690,709	A *	11/1928	Wilson	294/91
1,736,187	A *	11/1929	Coleman	294/91
1,754,288	A *	4/1930	Smith	294/91
1,766,920	A *	6/1930	Moody	294/91
1,814,990	A *	7/1931	Weston	294/91
2,009,942	A *	7/1935	Moody	294/91
2,105,077	A *	1/1938	Hertel	294/90
2,218,000	A *	10/1940	Grau et al.	294/91
2,617,678	A *	11/1952	Kelso	294/115
3,915,244	A *	10/1975	Brown	175/85
4,035,012	A *	7/1977	Guier	294/90

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **13/761,974**

WO WO 2005/106185 * 11/2005

(22) Filed: **Feb. 7, 2013**

Primary Examiner — Dean Kramer

(65) **Prior Publication Data**

(74) Attorney, Agent, or Firm — Osha Liang LLP

US 2013/0129466 A1 May 23, 2013

Related U.S. Application Data

- (63) Continuation of application No. 13/341,308, filed on
Dec. 30, 2011, now Pat. No. 8,393,661, and a
continuation of application No. 11/624,771, filed on
Jan. 19, 2007, now Pat. No. 8,141,923.

(51) **Int. Cl.**
E21B 19/10 (2006.01)

(52) **U.S. Cl.**
USPC **294/102.2**; 294/197


(58) **Field of Classification Search**
USPC 294/102.1, 102.2, 103.1, 104, 113, 902,
294/91, 197, 201

See application file for complete search history.

(57) **ABSTRACT**

The present invention provides an apparatus and a method for lifting a single joint of pipe. The single joint elevator of the present invention comprises, in one embodiment, a pair of deployable jaws cooperating with a pair of static jaws to secure a pipe within the slot of a generally horseshoe-shaped body. The deployable jaws of the single joint elevator of the present invention may be rotatably deployable or translatable deployable, or both. In one embodiment, each jaw, including the static jaws and the deployable jaws, comprises a pipe slip movably disposed within the jaw to secure a pipe segment within the slot and to self-tighten as the weight of the pipe segment secured within the single joint elevator is transferred to the slips and the jaws.

30 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,269,554	A *	5/1981	Jackson	414/22.63	5,340,182	A *	8/1994	Busink et al.	294/199
4,275,487	A *	6/1981	Gray et al.	188/67	5,791,410	A *	8/1998	Castille et al.	166/77.1
4,361,940	A *	12/1982	McFadden	188/67	5,909,768	A *	6/1999	Castille et al.	166/77.1
4,441,749	A *	4/1984	Blaschke et al.	294/194	6,138,529	A *	10/2000	Pietras	81/57.33
4,576,254	A *	3/1986	Cox	188/67	6,227,587	B1 *	5/2001	Terral	294/102.2
4,579,379	A *	4/1986	Berg	294/102.2	6,270,136	B1 *	8/2001	Dagenais	294/207
4,604,724	A *	8/1986	Shaginian et al.	700/213	6,568,479	B2 *	5/2003	Mosing et al.	166/380
4,647,099	A *	3/1987	Berry et al.	294/103.1	6,742,596	B2 *	6/2004	Haugen	166/380
4,649,777	A *	3/1987	Buck	81/57.19	6,938,697	B2 *	9/2005	Haugen	166/380
4,676,312	A *	6/1987	Mosing et al.	166/77.53	6,976,540	B2 *	12/2005	Berry	166/380
4,743,055	A *	5/1988	Dantan	294/199	6,997,265	B2 *	2/2006	Berry	166/380
5,027,926	A *	7/1991	Cox	188/67	7,032,678	B2 *	4/2006	Mosing et al.	166/380
5,127,790	A *	7/1992	Teague	414/800	8,141,923	B2 *	3/2012	Bouligny et al.	294/102.2
5,299,848	A *	4/1994	Boyer	294/106	2006/0185854	A1 *	8/2006	Mosing et al.	166/379
					2008/0136203	A1 *	6/2008	Krijnen et al.	294/91
					2009/0110535	A1 *	4/2009	Pietras et al.	414/814

* cited by examiner





FIG. 1
(Prior Art)






FIG. 3




FIG. 4




FIG. 5




FIG. 5A





FIG. 5B

**FIG. 6**

1

SINGLE JOINT ELEVATOR HAVING DEPLOYABLE JAWS

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of, and therefore claims benefit under 35 U.S.C. §120 to, U.S. patent application Ser. No. 13/341,308, filed on Dec. 30, 2011, which is a continuation of, and therefore claims benefit under 35 U.S.C. §120 to, U.S. patent application Ser. No. 11/624,771, filed on Jan. 19, 2007, having issued as U.S. Pat. No. 8,141,923 on Mar. 27, 2012. These priority applications are hereby incorporated by reference in their entirety herein.

FIELD OF THE INVENTION

The present invention, is directed to an apparatus and a method for securing a pipe segment or a stand of pipe to a cable, rope, line or other hoisting member to facilitate lifting of the pipe to an elevated position. The present invention is directed to an apparatus and a method for securely gripping and releasing a pipe segment, or stand of pipe for use in drilling operations.

BACKGROUND OF THE RELATED ART

Wells are drilled into the earth's crust using a drilling rig. Pipe strings are lengthened by threadably coupling add-on pipe segments to the proximal end of the pipe string. The pipe string is generally suspended within the borehole using a rig floor-mounted spider as each new pipe segment or stand is coupled to the proximal end of the pipe string just above the spider. A single joint elevator is used to grip and secure the segment or stand to a hoist to lift the segment or stand into position for threadably coupling to the pipe string.

For installing a string of casing, existing single joint elevators generally comprise a pair of hinged body halves that open to receive a joint of pipe and close to secure the pipe within the elevator. Elevators are specifically adapted for securing and lifting pipe having conventional connections. A conventional connection comprises an internally threaded sleeve that receives and secures one externally threaded end from each of two pipe segments to secure the segments in a generally abutting relationship. The internally threaded sleeve is first threaded onto the end of a first segment of pipe to form a "box end." The externally threaded "pin end" of the second segment of pipe is threaded into the box end to complete the connection between the segments. Typical single joint elevators have a circumferential shoulder that forms a circle upon closure of the hinged body halves. The shoulder of the elevator engages the shoulder formed between the end of the sleeve and the pipe segment. Conventional single joint elevators cannot grip a pipe segment having integral connections (having no circumferential shoulder), and conventional single joint elevator can only grip a pipe segment at the threaded sleeve that secures the connection.

Conventional elevators are difficult to use on pipe segments that are not conveniently accessible. For example, casing segments are often moved to the rig floor from a horizontal pipe rack and presented to the rig floor at a "V"-door. A conventional elevator requires enough clearance to close the hinged body halves around the casing segment. Depending on the length of the pipe and the proximity of the floor or other rig structures, there may be insufficient clearance around the casing segment for installing a conventional single joint elevator, often requiring repositioning of the casing segment

2

so that the single joint elevator can be installed around the casing segment. Even if repositioning of each casing segment takes only a few seconds, delays for repeatedly repositioning casing segments in the V-door consumes a substantial amount of rig time.

What is needed is a single joint elevator that is securable to a pipe at multiple positions along the length of the pipe segment, and not only at the end connection. What is needed is a single joint elevator that is adapted for securing to the pipe segment notwithstanding close proximity of the rig floor or other rig structure. What is needed is a single joint elevator that can be used to lift single pipe segments without repositioning the pipe segment to secure the single joint elevator. What is needed is a versatile single joint elevator that facilitates lifting both a pipe segment having integral connections and a pipe segment having a conventional connection with a threaded sleeve received onto the end of the pipe segment.

SUMMARY OF THE PRESENT INVENTION

The present invention is directed to an apparatus for releasably securing a pipe segment or stand to a cable, rope, line or other hoisting member for lifting the pipe segment or stand into position for being threadably coupled to a pipe string suspended in a borehole. One embodiment of the invention comprises a generally horseshoe-shaped body having a slot for receiving a pipe, at least one static jaw, and at least one deployable jaw that deploys to trap the pipe within the slot of the body. The static jaw may be secured to the body in a position to contact and bear against a pipe that has been sufficiently received into the slot. The at least one deployable jaw has a removed position permitting entry of the pipe into the slot, and a deployed position to secure the pipe within the slot. The body is adapted for supporting the at least one static jaw and the at least one deployable jaw, and also for being lifted and for transferring the weight of the pipe to a cable, rope, line or other hoisting member.

The deployable jaw of the present invention comprises a jaw movable between a removed position and a deployed position. The deployable jaw is either rotatably deployed or translatably deployed, or a combination of both, from its removed position to its deployed position. The deployable jaw may be pneumatically, hydraulically, manually and/or electrically actuated from its removed position to its deployed position. The deployable jaw of the present invention may be deployed using a pneumatic, hydraulic or electric motor for deploying the jaw to trap the pipe within the slot of the body.

Each static jaw and each deployable jaw may comprise a pipe slip that is movable between an engaged position and a disengaged position. Movement of the slip toward the engaged position moves the slip radially inwardly toward the pipe within the slot to decrease the clearance between the pipe slip in the at least one static jaw and the generally opposed pipe slip in the at least one deployable jaw, and movement of the slip toward its disengaged position moves the slip radially outwardly away from the pipe within the slot to increase the clearance between the pipe slip in the at least one static jaw and the generally opposed pipe slip in the at least one deployable jaw. Each static jaw and each deployable jaw may comprise one or more grooves for slidably receiving tabs, keys, or guides for imposing a predetermined path for movement of the pipe slip within the jaw. For example, a pipe slip may have a pair of tabs, one protruding from each side of the slip, and each tab may be slidably received into a groove in the jaw for imposing upon the pipe slip a predetermined path of movement extending in the engaged direction for closing the pipe slips on the pipe received within the slot, and in the disen-

3

gaged direction for retracting the pipe slips away from the pipe received within the slot. Each slip may comprise a pipe contact surface, such as a removable insert, that may comprise a textured surface adapted for gripping contact with the external wall of the pipe received into the slot.

The deployable jaw may be mechanically locked into its deployed position within the slot for gripping and supporting a pipe. An over-center mechanical linkage and a worm gear are two examples of mechanisms that may be used for mechanically locking the deployed jaw into its deployed position. The deployable jaw may also be equipped with one or more deployment sensors for sensing proper deployment and position, and for automatically enabling use of the apparatus only when the deployable jaws are deployed and/or locked in their pipe gripping positions within the slot. For example, a deployment sensor(s) may operate to prevent deployment of a second deployable jaw until the first deployable jaw is fully deployed and/or locked into position.

The foregoing and other objects, features and advantages of the invention will be apparent from the following more particular description of a preferred embodiment of the invention, as illustrated in the accompanying drawings wherein like reference numbers represent like parts of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a prior art single joint elevator having a pair of opposing hinged body halves for opening, receiving a pipe, and then closing around a pipe received within the opened body halves.

FIG. 2 is a perspective view of one embodiment of the single joint elevator of the present invention showing a pair of rotatably deployable jaws in their deployed positions to secure a pipe segment (not shown) within the slot in the body of the elevator.

FIG. 3 is a bottom view of the embodiment of FIG. 2 showing one of the pair of deployable jaws deployed by operation of a cylinder to its deployed position within the slot.

FIG. 4 is a front elevation view of the embodiment of FIG. 2 showing the pipe slips of the static jaws elevated and retracted to their disengaged positions and the deployable jaws retracted to their disengaged positions.

FIG. 5 is a perspective view of an alternate embodiment of the present invention having a pair of translatable deployable jaws with one jaw translated to its deployed position within the slot of the body and the opposing deployable jaw remaining in its retracted position.

FIG. 5A is a side elevation view of the retracted translatable deployable jaw shown in the embodiment of FIG. 5.

FIG. 5B is a side elevation view of the deployed translatable deployable jaw shown in the embodiment of FIG. 5.

FIG. 6 is a logic flow diagram showing the steps of one embodiment of the method of securing and lifting a pipe of the present invention.

DETAILED DESCRIPTION OF THE PRESENT INVENTION

FIG. 1 is a perspective view of a prior art single joint elevator having a pair of opposing and hinged body halves for opening, receiving a pipe segment and closing around a pipe segment (not shown) that is received within the opened body halves. These elevators are unsuitable for gripping pipe having integral connections, and they are unsuitable for gripping pipe with conventional connections at locations along the length of the pipe segment removed from the end of the segment. These elevators are often difficult to position on the

4

pipe segment due to interference with the rig floor or other rig structures, as well as difficult to open and close, especially if the locking pin is in a bind.

FIG. 2 is a perspective view of one embodiment of the single joint elevator 10 of the present invention showing a pair of generally opposed rotatably deployable jaws 30, both shown in their deployed positions to secure a pipe segment (not shown) within the slot 13 in the generally horseshoe-shaped body 12. Each deployable jaw 30 is supported by the body 12 and rotatably deployable about a pivot 33, and the range of rotation of the deployable jaw 30 is determined by the position of a stop 35 and also by the dimensions of the linkages that operate to deploy and retract the jaw 30. Each deployable jaw 30 comprises a pipe slip 39 movably received within a slip well 31 in the deployable jaw 30, each pipe slip 39 being movable between an engaged position and a retracted position, as will be discussed in more detail below.

The body 12 in FIG. 2 also supports a pair of static jaws 36, each having a pipe slip 38 movably received within the static jaw 36. In the embodiment shown in FIG. 2, each pipe slip 38 has a pair of opposed keys (not shown) extending generally parallel with the contact surface 32A of the pipe slip 38 and outwardly from each opposed side of the pipe slip 38. The keys (not shown) are received into generally opposed grooves 36A in the jaw for imparting a predetermined pathway to the pipe slip 38 as it moves between its lowered and engaged position and its raised and disengaged position. The pipe slips 38 are coupled to and positionable by powered movement of the leveling member 42. The leveling member 42 slides vertically on collar post 34 and supports and moves the pipe slips 38 upwardly to disengage the pipe segment (not shown) and downwardly to engage the pipe segment. The leveling member 42 is positionable by operation of a static jaw cylinder 60 to position the leveling member 42 and the pipe slips 38 within the static jaws 36 to cooperate with the pipe slips 39 of the deployable jaws 30 when in their deployed position, as shown in FIG. 2.

The body 12 of the single joint elevator 10 may be securable to one or more cables, ropes, lines or other hoisting members (not shown) at a pair of generally opposed lugs 14 to facilitate lifting and positioning of the single joint elevator 10 and the pipe segment (not shown) secured therein. The lugs 14 may be removable and replaceable to facilitate securing the single joint elevator 10 to a loop formed in the end of a cable (not shown).

The deployable jaws 30 are rotatably deployable from their removed positions (see left-side deployable jaw 30 in FIG. 3) to their deployed positions (see FIG. 2) using a deployment cylinder 50. As shown in FIG. 3, each deployment cylinder 50 is pivotally secured to body 12 at pivot 52. The pivot 52 allows the cylinder 50 to rotate about pivot 52 during deployment of the deployable jaw 30 from its removed position to its deployed position. The cylinder rod 51 extends from the cylinder 50 during actuation by the introduction of a pressurized fluid acting against a piston (not shown) within the cylinder to operate the mechanical deployment linkage comprising the rod end clevis 84, stabilizer 82 and deployment arm 86. Rod end clevis 84 pivotally couples the moving end 82B of rotating stabilizer 82 to the cylinder rod 51 and also to the deployment arm 86. The cylinder rod 51 extends upon actuation of the cylinder to rotate stabilizer 82 and simultaneously rotate and deploy deployable jaw 30 about pivot 33 and into the slot 13 to its deployed position (shown in FIG. 2 and on the right side of FIG. 3.) The deployable jaw 30 may rotate until it contacts and bears against stop 35. The cylinder rod 51 may be spring biased to its extended position corresponding to the deployed position of the deployable jaw 30.

5

In one embodiment of the present invention, the deployment linkage comprising rod end clevis **84**, stabiliser **82** and deployment arm **86** is configured to be an over-center linkage; that is, the dimensions and shapes of these components cooperate with the deployment stroke of the cylinder rod **51** to secure the deployable jaw **30** in its deployed position by briefly reversing the angular direction of rotation of the deployment jaw **30** about its pivot **33** just before the rod **51** achieves its maximum deployment extension from cylinder **50**. This configuration of the deployment linkage causes the deployment jaw **30** to briefly reverse and rotate through a relatively insubstantial angle back toward its removed position (shown on the left side of FIG. 3) before the actuation of the cylinder **50** terminates. Maintaining fluid pressure on the cylinder **50** to bear against cylinder rod **51** and the rod end clevis **84** rotatably locks the deployment jaw **30** into position for engaging and supporting the pipe (not shown) received within the slot **13**. Upon initial retraction of the cylinder rod **51** from its fully deployed position back towards its retracted position within the cylinder **50**, the deployment jaw **30** briefly rotates about pivot **33** and further into the slot **13** before it reverses and rotates back to its removed position within or adjacent to the body **12**.

The body **12** may be adapted with apertures, recesses, channels, lugs, and related features for accommodating the various components that cooperate to facilitate the single joint elevator function. Lugs **14** accommodate coupling to rigid lift links or to a cable, chain, rope or lift line for lifting of the single joint elevator using a hoist. Cylinder recesses **54** (see FIG. 2) within each prong **12A**, **12B** of body **12** receive the pivotably secured cylinders **50** that operate to deploy the deployable jaws **30**. Static jaw cylinder **60** engages and reciprocates leveling member **42** (see FIG. 2) to position the slips **38** of static jaws **36**. Deployable jaw pivot **33** may be a bolt received through two or more aligned apertures in the deployment jaws **30** and in prongs **12A**, **12B** of the body **12**. These and other components may be removable or adjustable to provide for removal, repair or replacement of components of the single joint elevator, or modular replacement of components to adapt the single joint elevator to accommodate a range of sizes of pipe within the slot **13**.

FIG. 3 is a bottom view of the embodiment of the single joint elevator of FIG. 2 showing one (the right) of the pair of deployable jaws **30** rotated, by operation of the right cylinder **50**, to its deployed position within the slot **13**. The left cylinder **50** remains inactive and the left deployment jaw **30** remains in its removed position within the cylinder recess **54** of the body **12**. Both deployment jaws **30** may be adapted for simultaneous deployment into the slot **13**. For illustration purposes, FIG. 3 shows both the deployed and retracted positions of the deployable jaws **30** of the single joint elevator **10** of the present.

FIG. 4 is a front elevation view of the embodiment of FIG. 2 showing the pipe slips **38** elevated within static jaws **36** by leveling member **42** raised vertically on collar post **34** to retract the pipe slips **38** to their disengaged positions, and also showing the deployable jaws **30** retracted to their disengaged positions. The leveling member **42** engages and slidably elevates the pipe slips **38** along the predetermined path imposed by keys **36B** slidably received within opposed grooves **36A** within the static jaw **36**. The pipe slips **38** slide between the engaged and retracted positions and, in the engaged position, bear against load bearing surface **44**. The leveling member **42** may be spring or gravity-biased to its engaged position, spring-biased to retract upwardly to its disengaged position, or it may be powered in one or both of the upwardly (retracted) and downwardly (engaged) direc-

6

tions using the same source of fluid pressure used to operate deployment cylinders (see element **50** in FIG. 3).

FIG. 5 is a perspective view of an alternate embodiment of the present invention having a pair of translatably deployable jaws **69** with the left deployable jaw translated and deployed into the slot **13** to its deployed position to engage a pipe segment (not shown), and the right deployable jaw remaining in its retracted position. The translatably deployable jaws **69** shown in FIG. 5 are secured to the top surface of prongs **12A**, **12B** of the body **12**, but may alternately be disposed within and deployable from recesses within the body **12** or below the body **12** as are the deployment cylinders **50** shown in FIGS. 2 and 3.

FIG. 5A is a side elevation view of the retracted translatably deployable jaw **69** shown in the embodiment of FIG. 5 secured to the right prong **12B** of the body **12**. The translatably deployable jaw **69** comprises a T-rail **74** secured to a base **40** that is, in turn, secured to the right prong (see element **12B** of FIG. 5) of the body **12**. The T-rail **74** is slidably received into a mating T-shaped groove (not shown) within sliding block **70** to facilitate sliding translation of the sliding block **70** relative to the body **12**. Translation is controllably imparted to the sliding block **70** using one or more translation cylinders **90** (see FIGS. 5A and 5B) that extend and retract a translation rod **91** having a piston end (not shown) within translating cylinder **90** and a static rod end (not shown) coupled to the base **40** at or near the end of the T-rail **74**. The translation cylinder **90** may be a double-acting cylinder, or it may be spring-biased to either its extended position (shown in FIG. 5B) or to its retracted position (shown in FIG. 5A).

The translatably deployable jaw **69** further comprises a descending block **41** for cooperating with the sliding block **70**. The descending block **41** may comprise a pipe contact surface **37** for contacting a pipe (not shown) to be secured within the slot of the single joint elevator. The descending block **41** comprises a first sliding surface **41A** for sliding along the sliding surface **70A** of the sliding block **70**, and a second sliding surface **41B** for sliding along the supporting surface **40B** of the base **40**. The second sliding surface **41B** on the descending block **41** is adapted for sliding along the supporting surface **40B** of base **40** when the sliding surface **41B** of the descending block **41** is aligned with the sliding surface **70B** of the sliding block **70** as shown in FIG. 5A. Descending block **41** is selectively moveable relative to the sliding block **70** only when the sliding surface **70A** of the sliding block **70** is aligned with the sliding surface **40A** of the base **40**. Descending block cylinder **78** is pivotally coupled at pivot **80A** to a boomerang link **95**. The sliding block cylinder **78** is pivotally secured at pivot end **78A** to the sliding block **70**, and extends and retracts cylinder rod **79** coupled to an elbow coupling **80** for pivotally coupling the rod **79** to the first leg **83** of boomerang link **95**. The boomerang link **95** is pivotally coupled to the sliding block **70** at pivot **81A**. The second leg **81** of the boomerang link **95** extends at an angle to the first leg **83** and is pivotally coupled to retainer pin **81B** that extends generally perpendicular from the second leg **81** into rod slot **94** in the descending block **41**. The retainer rod **81B** extends into and is movable within rod slot **94** of the descending block **41** to facilitate downwardly and inwardly movement of the descending block along the inclined sliding surface **70A** of the sliding block **70** and aligned sliding surface **40A** of the base **40**.

The operation of the components of the translating jaw **69** shown in FIGS. 5, 5A and 5B is easily determined from examination of FIGS. 5A and 5B. Prior to deployment, the translating jaw **69** appears as it does in FIG. 5A. As deployment begins, the translation cylinder **90** is actuated to extend

7

rod 91 and to translate both sliding block 70 and descending block 41 horizontally along the base 40. During this translation, aligned sliding surfaces 70B and 41B slide along support surface 40B of the base 40. The inwardly (into the slot—see element 13 on FIG. 5) and downwardly movement of descending block 41 toward engagement with the pipe (not shown) begins when the translation of sliding block 70 and descending block 41 aligns sliding surface 41A of the descending block 41 with sliding surface 40A of the base 40. After alignment, the descending block 41 descends along the sliding surface 40A as permitted by the length (in a direction parallel to the sliding interface between sliding surfaces 41A and 40A) of rod slot 94 until it achieves a position shown in FIG. 5B and the radial inwardly movement of the descending block 41 causes the pipe contact surface 37 to engage and grip the pipe segment (not shown) received into the slot (see element 13 of FIG. 5).

FIGS. 5, 5A and 5B show one embodiment of the present invention having translatable deployable jaws, each translatable deployable jaw having two or more cylinders for deploying the jaw to engage the pipe. The translatable deployable jaw may be adapted for operation using only one cylinder by, for example, eliminating translation cylinder 90 and by pivotally coupling descending block cylinder 78 to the T-rail at pivot 93 instead of pivotally coupling descending block cylinder 78 to the sliding block 70 at pivot 78A. Other cylinder arrangements may provide satisfactory deployment of the translatable deployable jaw in accordance with the scope of this invention.

FIG. 6 is a logic flow diagram showing the steps of one embodiment of a method for securing a pipe segment to a lift line. The method comprises supplying air pressure to the first pneumatic positioning cylinder 100, deploying first pneumatic positioning cylinder and first deployable jaw 200, sensing deployment of the first pneumatic positioning cylinder 300, supplying air pressure to the second pneumatic positioning cylinder 400, deploying second pneumatic positioning cylinder and second deployable jaw 500, sensing deployment of the second pneumatic cylinder 600, and lifting the pipe segment by activation of a winch and cable coupled to the single joint elevator 700. If the first or second deployment cylinders fail to function, an alert is activated 800.

The terms “comprising,” “including,” and “having,” as used in the claims and specification herein, indicate an open group that includes other elements or features not specified. The term “consisting essentially of” as used in the claims and specification herein, indicates a partially open group that includes other elements not specified, so long as those other elements or features do not materially alter the basic and novel characteristics of the claimed invention. The terms “a,” “an” and the singular forms of words include the plural form of the same words, and the terms mean that one or more of something is provided. The terms “at least one” and “one or more” are used interchangeably.

The term “one” or “single” shall be used to indicate that one and only one of something is intended. Similarly, other specific integer values, such as “two,” are used when a specific number of things is intended. The terms “preferably,” “preferred,” “prefer,” “optionally,” “may,” and similar terms are used to indicate that an item, condition or step being referred to is an optional (not required) feature of the invention.

It should be understood from the foregoing description that various modifications and changes may be made in the preferred embodiments of the present invention without departing from its true spirit. The foregoing description is provided for the purpose of illustration only and should not be con-

8

strued in a limiting sense. Only the language of the following claims should limit the scope of this invention.

We claim:

1. An elevator configured to grip and lift a rigid shoulderless pipe segment having a substantially circular cross-section, the elevator comprising:

a U-shaped body having a proximal end configured to receive an outer surface of the rigid shoulderless pipe segment and a distal end with a first prong and a second prong;

a first deployable jaw coupled to the first prong of the U-shaped elevator; and

a second deployable jaw coupled to the second prong of the U-shaped elevator;

the first deployable jaw and the second deployable jaw configured to move between a removed position and a deployed position such that, in the deployed position, the first deployable jaw and the second deployable jaw have a gap formed therebetween and are configured to engage the rigid shoulderless pipe segment,

wherein the first deployable jaw comprises a first pipe contact member and the second deployable jaw comprises a second pipe contact member, and

wherein at least one of the first pipe contact member and the second pipe contact member comprises a slip.

2. The elevator of claim 1, further comprising:

a first static jaw positioned in the proximal end of the U-shaped body; and

a second static jaw positioned in the proximal end of the U-shaped body.

3. The elevator of claim 2, wherein the first static jaw and the second static jaw are configured to engage the rigid shoulderless pipe segment when the first deployable jaw and the second deployable jaw are in the deployed position.

4. The elevator of claim 2, wherein the first static jaw comprises a third pipe contact member and the second static jaw comprises a fourth pipe contact member, and wherein the third pipe contact member and the fourth pipe contact member are movable between an engaged position and a disengaged position.

5. The elevator of claim 4, further comprising:

a leveling member coupled between the first static jaw and the second static jaw such that the leveling member is configured to move the third contact member and the fourth contact member together between the engaged position and the disengaged position.

6. The elevator of claim 5, wherein the leveling member is configured to vertically slide along a collar post to move the third pipe contact member and the fourth pipe contact member between the engaged position and the disengaged position.

7. The elevator of claim 2, wherein the first deployable jaw, the second deployable jaw, the first static jaw, and the second static jaw are configured to transfer substantially all of the lifting loads from the U-shaped body to the outer surface of the rigid shoulderless pipe segment when engaged with the rigid shoulderless pipe segment.

8. The elevator of claim 2, wherein substantially all of the lifting loads are transferred from lifting lugs coupled to the U-shaped body, through the U-shaped body and each of the first deployable jaw, the second deployable jaw, the first static jaw, and the second static jaw, to the rigid shoulderless pipe segment.

9. The elevator of claim 1, wherein, in the removed position, the first deployable jaw and the second deployable jaw are configured to disengage the rigid shoulderless pipe segment.

9

10. The elevator of claim 1, wherein the first deployable jaw and the second deployable jaw are configured to move within the U-shaped body when moving between the removed position and the deployed position.

11. The elevator of claim 1, further comprising:

at least one actuator operatively coupled between the U-shaped body and at least one of the first deployable jaw and the second deployable jaw such that the at least one actuator moves the least one of the first deployable jaw and the second deployable jaw between the removed position and the deployed position.

12. The elevator of claim 1, further comprising:

a first lug and a second lug coupled to the U-shaped body to facilitate lifting of the U-shaped body.

13. A method to engage and lift a rigid shoulderless pipe segment having a substantially circular cross-section, the method comprising:

receiving an outer surface of the rigid shoulderless pipe segment within a proximal end of a U-shaped body of an elevator;

moving a first deployable jaw coupled to a first prong at a distal end of the U-shaped body and a second deployable jaw coupled to a second prong at the distal end of the U-shaped body between a removed position and a deployed position, wherein a gap is formed between the first deployable jaw and the second deployable jaw,

wherein the first deployable jaw comprises a first pipe contact member and the second deployable jaw comprises a second pipe contact member,

wherein at least one of the first pipe contact member and the second pipe contact member comprises a slip;

engaging the rigid shoulderless pipe segment with the first deployable jaw and the second deployable jaw in the deployed position; and

lifting the rigid shoulderless pipe segment with the elevator.

14. The method of claim 13, wherein the elevator comprises a first static jaw and a second static jaw positioned in the proximal end of the U-shaped body, the method further comprising:

engaging the rigid shoulderless pipe segment with the first static jaw and the second static jaw when the first deployable jaw and the second deployable jaw are in the deployed position.

15. The method of claim 14, wherein the first static jaw comprises a third pipe contact member and the second static jaw comprises a fourth pipe contact member, the method further comprising:

moving the third pipe contact member and the fourth pipe contact member between an engaged position and a disengaged position.

16. The method of claim 15, wherein the elevator comprises a leveling member coupled between the first static jaw and the second static jaw to move the third contact member and the fourth contact member together between the engaged position and the disengaged position.

17. The method of claim 16, further comprising:

sliding the leveling member along a collar post to move the third pipe contact member and the fourth pipe contact member between the engaged position and the disengaged position.

18. The method of claim 14, wherein the first deployable jaw, the second deployable jaw, the first static jaw, and the second static jaw are configured to transfer substantially all of the lifting loads from the U-shaped body to the outer surface of the rigid shoulderless pipe segment when engaged with the rigid shoulderless pipe segment.

10

19. The method of claim 13, further comprising:

moving the first deployable jaw and the second deployable jaw to the removed position; and

disengaging the rigid shoulderless pipe segment with the first deployable jaw and the second deployable jaw in the removed position.

20. The method of claim 13, wherein the first deployable jaw and the second deployable jaw move within the U-shaped body when moving between the removed position and the deployed position.

21. The method of claim 13, wherein the elevator comprises at least one actuator operatively coupled between the U-shaped body and at least one of the first deployable jaw and the second deployable jaw such that the at least one actuator moves the least one of the first deployable jaw and the second deployable jaw between the removed position and the deployed position.

22. The method of claim 13, wherein the elevator comprises a first lug and a second lug, the method further comprising:

lifting the U-shaped body of the elevator through the first lug and the second lug.

23. The method of claim 22, wherein substantially all of the lifting loads are transferred from the lifting lugs, through the U-shaped body and each of the first deployable jaw and the second deployable jaw to the rigid shoulderless pipe segment.

24. An elevator configured to grip and lift a rigid shoulderless pipe segment having a substantially circular cross-section, the elevator comprising:

a U-shaped body having a proximal end configured to receive an outer surface of the rigid shoulderless pipe segment and a distal end with a first prong and a second prong;

a plurality of pipe contact members coupled to the U-shaped body;

a first pipe contact member of the plurality of pipe contact members coupled to the first prong of the U-shaped elevator;

a second deployable jaw of the plurality of pipe contact members coupled to the second prong of the U-shaped elevator, wherein a gap is formed between the first pipe contact member and the second deployable jaw; and

a first lug and a second lug coupled to the U-shaped body to facilitate lifting of the U-shaped body;

the first pipe contact member and a second pipe contact member configured to move between a removed position and a deployed position such that, in the deployed position, the first pipe contact member and the second pipe contact member are configured to engage the rigid shoulderless pipe segment;

the plurality of pipe contact members configured to transfer substantially all of the lifting loads from the U-shaped body to the outer surface of the rigid shoulderless pipe segment when engaged with the rigid shoulderless pipe segment.

25. The elevator of claim 24, further comprising:

a third pipe contact member positioned in the proximal end of the U-shaped body; and

a fourth pipe contact member positioned in the proximal end of the U-shaped body.

26. The elevator of claim 25, wherein at least one of the first pipe contact member, the second pipe contact member, the third pipe contact member, and the fourth pipe contact member comprises a slip.

27. The elevator of claim 25, wherein at least one of the first pipe contact member, the second pipe contact member, the

third pipe contact member, and the fourth pipe contact member is movable between an engaged position and a disengaged position.

28. The elevator of claim 24, wherein the first pipe contact member and the second pipe contact member are configured to move within the U-shaped body when moving between the removed position and the deployed position. 5

29. The elevator of claim 24, further comprising:

at least one actuator operatively coupled between the U-shaped body and at least one of the first pipe contact member and the second pipe contact member such that the at least one actuator moves the least one of the first pipe contact member and the second pipe contact member between the removed position and the deployed position. 10 15

30. The elevator of claim 24, wherein substantially all of the lifting loads are transferred from the lifting lugs, through the U-shaped body and the second deployable jaw to the rigid shoulderless pipe segment.

* * * * *

20