




(86) **Date de dépôt PCT/PCT Filing Date:** 2012/07/11
 (87) **Date publication PCT/PCT Publication Date:** 2013/03/07
 (45) **Date de délivrance/Issue Date:** 2020/06/02
 (85) **Entrée phase nationale/National Entry:** 2014/01/14
 (86) **N° demande PCT/PCT Application No.:** US 2012/046157
 (87) **N° publication PCT/PCT Publication No.:** 2013/032583
 (30) **Priorité/Priority:** 2011/08/26 (US13/219,206)

(51) **Cl.Int./Int.Cl. F16L 59/135** (2006.01),
F16L 3/00 (2006.01), **F16L 59/14** (2006.01)
 (72) **Inventeurs/Inventors:**
 ZAGORSKI, KENNETH, US;
 DONOGHUE, JOSEPH A., US;
 BOCK, MICHAEL E., US
 (73) **Propriétaire/Owner:**
 RILCO MANUFACTURING COMPANY, INC., US
 (74) **Agent:** BERESKIN & PARR LLP/S.E.N.C.R.L.,S.R.L.

(54) **Titre : ANCRAGE DE TUYAU**
 (54) **Title: PIPE ANCHOR**



(57) **Abrégé/Abstract:**

A pipe anchor is disclosed having a pipe trunnion stop for attaching to an outer surface of a pipe by welding. A mating top cradle and bottom cradle generally encircle and hold a length of the pipe. The bottom cradle has a pass-through to accommodate the pipe trunnion stop. There is a base onto which the bottom cradle sets, the base includes a void into which the pipe trunnion is secured. An insulation layer is positioned between the pipe and the top cradle and bottom cradle, and around the pipe trunnion stop. A bolting assembly on the top cradle portion and a mating bolting assembly on the bottom cradle portion secures the top cradle portion and the bottom cradle portion to each other. Another embodiment includes multiple pipe trunnion stops along with respective pass-through and base void sections.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
7 March 2013 (07.03.2013)



(10) International Publication Number
WO 2013/032583 A9

- (51) International Patent Classification:** F16L 3/08 (2006.01)
- (21) International Application Number:** PCT/US2012/046157
- (22) International Filing Date:** 11 July 2012 (11.07.2012)
- (25) Filing Language:** English
- (26) Publication Language:** English
- (30) Priority Data:** 13/219,206 26 August 2011 (26.08.2011) US
- (71) Applicant (for all designated States except US):** RILCO MANUFACTURING COMPANY, INC. [US/US]; 11435 Brittmoore Park Drive, Houston, TX 77041 (US).
- (72) Inventors; and**
- (75) Inventors/Applicants (for US only):** ZAGORSKI, Kenneth [US/US]; 11435 Brittmoore Park Drive, Houston, TX 77041 (US). DONOGHUE, Joseph, A. [US/US]; 11435 Brittmoore Park Drive, Houston, TX 77041 (US). **BOCK, Michael, E.** [US/US]; 11435 Brittmoore Park Drive, Houston, TX 77041 (US).
- (74) Agent:** PETRUZZI, James, D.; Mason & Petruzzi, 4900 Woodway, Suite 745, Houston, Texas 77056 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,

[Continued on next page]

(54) Title: PIPE ANCHOR




FIGURE 1

(57) Abstract: A pipe anchor is disclosed having a pipe trunnion stop for attaching to an outer surface of a pipe by welding. A mating top cradle and bottom cradle generally encircle and hold a length of the pipe. The bottom cradle has a pass-through to accommodate the pipe trunnion stop. There is a base onto which the bottom cradle sets, the base includes a void into which the pipe trunnion is secured. An insulation layer is positioned between the pipe and the top cradle and bottom cradle, and around the pipe trunnion stop. A bolting assembly on the top cradle portion and a mating bolting assembly on the bottom cradle portion secures the top cradle portion and the bottom cradle portion to each other. Another embodiment includes multiple pipe trunnion stops along with respective pass-through and base void sections.

WO 2013/032583 A9

WO 2013/032583 A9 

UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

(48) Date of publication of this corrected version:

11 July 2013

(15) Information about Correction:

see Notice of 11 July 2013

Declarations under Rule 4.17:

— *of inventorship (Rule 4.17(iv))*

PIPE ANCHOR

Cross Reference to Related Applications:

[0001] This application is based on U.S. utility patent application number 13/219,206 entitled "Pipe Anchor" filed on August 26, 2011.

5 **Background of the invention:**

[0002] Typical pipe anchor supports use lugs or plates attached to the pipe. These lugs encircle the pipe and transmit the forces generated by the pipe movement from the pipe lugs, through the insulation, and to an opposing lug welded to a housing, There are serious design shortcomings when using this arrangement. In such environments, the insulation cross
10 section width has to be great enough to allow sufficient compressive area to resist the compressive axial forces generate by the pipe and the stresses under which the pipe is held. Newer insulation materials allow for a thinner Insulation cross section due to improved insulating qualities, thus greatly decreasing the area of compression to the point that typically pipe lugs will not function properly.

15 **Brief Summary of the invention:**

[0003] An advantage of the present invention is to provide a clamp-on anchor that can be assembled to a pipeline in the field that positively limits the movement of the pipe section relative to the housing assembly axially, laterally, and rotationally.

[0004] In accordance with the present invention, an improved pipe trunnion stop anchor
20 provides a unique axial restraining system, A pipe trunnion stop is welded to a process pipe to transmit the axial force generated by the pipe to a base cradle. The

base cradle includes structural, thermal inserts, which isolate the pipe trunnion stop from the base assembly. The assembly also restrains the pipe trunnion stop from moving axially relative to the base assembly and restrains the pipe trunnion stop from moving laterally relative to the base assembly. There is also a vertical support for the pipe
5 trunnion stop.

[0005] In accordance with a preferred embodiment of the invention, there is shown a pipe anchor assembly having a pipe trunnion stop having sides and bottom for attaching to an outer surface of a pipe, mating top cradle and bottom cradle portions to generally encircle and hold a length of the pipe, a pass-through in the bottom cradle to
10 allow the pipe trunnion stop to pass through, a base onto which the bottom cradle sets, and the base includes a void into which the pipe trunnion stop is secured.

[0006] In accordance with a preferred embodiment of the invention, there is shown a pipe anchor assembly having a pipe trunnion stop having sides and bottom, and a generally polygonal cross-sectional shape, for attaching to an outer surface of a
15 pipe, a mating top cradle and bottom cradle portions to generally encircle and hold a length of the pipe, a pass-through in the bottom cradle to allow the pipe trunnion stop to pass through, a base onto which bottom cradle sets, the base includes a void into which the pipe trunnion is secured, an insulation layer positioned between the pipe and bottom cradle portion, an insulation layer positioned all sides and bottom of the pipe trunnion
20 stop; and a base support having at least two stops.

[0007] In accordance with a preferred embodiment of the invention, there is shown a pipe anchor assembly having a pipe trunnion stop having sides and bottom for attaching to an outer surface of the pipe, at least one strap to generally encircle and

hold a length of the pipe, a base onto which strap sets, the base includes a void into which the pipe trunnion is secured, and an insulation void positioned around the trunnion stop in the base void.

Brief Description of the Drawings:

5 **[0010]** The drawings constitute a part of this specification and include exemplary embodiments to the invention, which may be embodied in various forms. It is to be understood that in some instances various aspects of the invention may be shown exaggerated or enlarged to facilitate an understanding of the invention.

[0011] Figure 1 shows an exploded view of the pipe anchor assembly in accordance with
10 a preferred embodiment of the present invention.

[0012] Figure 2 is a head on view of the pipe anchor assembly in accordance with another preferred embodiment of the present invention.

[0012.1] Figure 3A shows an exploded view of an alternative pipe anchor assembly in accordance with a preferred embodiment of the present invention.

15 **[0012.2]** Figure 3B shows an exploded view of an alternative pipe anchor assembly in accordance with a preferred embodiment of the present invention.

[0012.2] Figure 3C shows an exploded view of an alternative pipe anchor assembly in accordance with a preferred embodiment of the present invention.

Detailed Description of the Preferred Embodiments:

[0013] Detailed descriptions of the preferred embodiments are provided herein. It is to be understood, however, that the present invention may be embodied in various forms. Various aspects of the invention may be inverted, or changed in reference to specific part shape and detail, part location, or part composition. Therefore, specific details disclosed herein are not to be interpreted as limiting, but rather as a basis for the claims and as a representative basis for teaching one skilled in the art to employ the present invention in virtually any appropriately detailed system, structure or manner.

[0014] Turning first to Figure 1, there is shown a pipe anchor in accordance with the preferred embodiment of the present invention. Pipe anchor 10 is shown in the exploded view encircling a cross-sectional length of pipe 15. Pipe anchor 10 captures pipe 15 in two ways. First, pipe anchor 10 clamps to pipe 15, encircling it completely and is secured bolting by assemblies 62, described in more detail below.

Simultaneously, pipe trunnion stop 21 engages with cavity 44 in the base assembly 42, also described in more detail below.

[0015] Pipe trunnion stop 21 is welded to pipe 15 in the preferred, illustrated embodiment, though other ways of securing pipe trunnion stop 21 to pipe 15 may be used, including intermediate tabs and bolts, brazing, and integrally fabricating the stop on the pipe section. The cross-sectional shape of pipe trunnion stop 21 is shown as rectangular, but it will be appreciated that the shape may be of a variety of shapes, depending upon the particular environment in which the pipe anchor assembly is intended to be used. The pipe trunnion stop 21 in conjunction with the opposing cavity 44 in base assembly 62 offers improved anchoring. Preferably, it will be shaped in a

polygonal configuration to prevent slippage or movement within the cavity. In some embodiments, it may be also be circular, oval or elliptical. The base assembly 42 length and width along with pipe trunnion stop 21 length and width can be modified as required to develop sufficient area to oppose the forces generated by movement from forces to the pipe 15.

[0016] Pipe anchor 10 includes top cradle 24 and base cradle 27. Top cradle 24 includes bolting tubes 25 that mate with bolting tubes 26 on base cradle 27. By these mating bolting tubes 25, 26, pipe anchor 10 encircles pipe 15. Bottom cradle 24 also includes pass-through void 29 so that pipe trunnion stop 21 may pass through and be secured in base assembly 42 as illustrated. In the illustrated embodiment, there are shown eight bolting tubes 25 on top cradle 24, and eight mating bolting tubes 26 on base cradle 27, though it will be appreciated that any appropriate number of bolting tubes may be employed, depending upon the environment. Alternatively, mating top cradle 24 and base cradle 27 may be hingedly attached on one side and appropriately affixed to each other on the other side with bolts or other mechanisms known in the art.

[0017] To provide required insulation to the pipe 15 in the area of pipe anchor 10, top thermal insulation 31 is provided and located between pipe 15 and top cradle 24. Similarly, lower thermal insulation 33 is located between pipe 15 and base cradle 27. Also provided in lower thermal insulation 33 is pass-through void 36 to allow pipe trunnion stop 21 to pass through lower thermal insulation 33 and mate securely with base assembly 42 as illustrated. As can be readily appreciated, the preferred design includes a void or space for insertion of insulation about the trunnion and other areas where thermal loss may be present. Alternatively, pipe 15 may be secured to top

thermal insulation 31 and lower thermal insulation 33 by encircling straps, ties, or other circumferential brackets which allow for passage of the pipe trunnion stop 21. Also, cradles may be configured to encircle pipe 15 and then bracketed or strapped to encircle pipe 15 and permit use of insulation.

5 **[0018]** Due to pipe trunnion stop 21 being attached to pipe 15, further insulation is desired. Accordingly, axial stop structural insulation 51 is shown forward and aft of the forward and rearward side walls of pipe trunnion stop 21, to insulate around pipe trunnion stop 21 and aide in axial stability of pipe 15. Similarly, lateral stop structural insulation 53 is shown adjacent lateral side walls of pipe trunnion stop 21, to provide
10 insulation and aide in lateral stability of pipe 15. To complete insulation around pipe trunnion stop 21, there is provided vertical stop structural insulation 55, and aides in vertical stability of pipe trunnion stop 21. Axial stop insulation 51, lateral stop structural insulation 53, and vertical stop structural insulation 55 are shown in Figure 1 as separated by some distance from pipe trunnion stop 21, but it is only for illustrative
15 purposes, and in use, are immediately adjacent the respective walls of pipe trunnion stop 21.

[0019] Continuing in Figure 1, there is shown base assembly 42 on which pipe 15, along with pipe anchor 10, are supported. Base assembly 42 is curved to support and provide stability for pipe 15 and base cradle 27. Base assembly 42 further includes
20 cavity 44 into which pipe trunnion stop 21 along with axial stop insulation 51, lateral stop structural insulation 53, and vertical stop structural insulation 55 fit. Support fins 45 are also illustrated on base assembly 42 to provide additional structural support, and it will be understood that any number and design of support fins may be employed for a

particular purpose. Base assembly 42 fits onto base assembly support 61 as shown in Figure 1 and includes external axial stops 65 and external lateral stops 67 to provide additional axial and lateral support to deter movement of pipe 15. In the field, base assembly support 61 is often pre-existing and base assembly 42 is attached to base assembly support 61 by, in the illustrated embodiment, welding.

[0020] As illustrated in the preferred embodiment, pipe trunnion stop 21 provides improved lateral, axial and vertical support while maintaining insulation for pipe 15. It will be appreciated that in the particular insulation used is not part of the inventions, and any appropriate insulation material may be used. In the preferred embodiment shown, a thin insulation based on aerogel may be employed including insulation sold under the trademark Cryogel®.

[0021] Turning next to Figure 2, there is shown a front view of a pipe anchor in accordance with another preferred embodiment of the present invention. Similar elements of Figure 1, described above, are labeled with similar number labels for consistency, though with a prime after the number label. The embodiment of Figure 2 shows four pipe trunnion stops 21' positioned around the circumference of the pipe at approximately 0°, 90°, 180°, and 270°. It will be appreciated by those in the art that any one, two, three or all four pipe trunnion stops 21' may be used and can be positioned at any location about the pipe circumference, as is appropriate for the particular environment and use desired. To accommodate four pipe trunnion stops 21', bolt assembly 62' is offset at approximately 45° for the horizontal, though any appropriate positioning may be employed. Depending upon the number and location of pipe trunnion stops 21', the number and location of cradle pass-through voids, as well as

insulation pass-through voids and base assemblies and respective voids 44' will also be adjusted. As noted above, encircling metal brackets, straps or straps to affix circumferential metal casing may be employed without departing from the scope of the invention.

5 **[0022]** While the invention has been described in connection with a preferred embodiment, it is not intended to limit the scope of the invention to the particular form set forth, but on the contrary, it is intended to cover such alternatives, modifications, and equivalents as may be included within the scope of the invention as defined by the appended claims.

10 **[0023]** Turning next to Figures 3A, 3B, and 3C, there are shown alternative preferred embodiments of the present invention, in which the trunnion stops 21'', 21''' and 21'''' are shown in Figures 3A, 3B, and 3C respectively as having a polygonal cross sectional configuration of an ellipse, oval or circle. Trunnion stops 21'', 21''' and 21'''' are surrounded by insulation in similar fashion to items 51, 53 and 55 as shown in Figure 1
15 by respective elements 51'', 53'', and 55'', 51''', 53''', and 55''', and 51'''', 53'''', and 55''''. The remaining elements of Figures 3A, 3B, and 3C have similar function to those described in Figure 1, but with a double, triple, or quadruple primes after the item number to reflect similar items whose only difference is to conform with the different trunnion stops 21'', 21''', and 21''''.

20

Claims

1. A pipe anchor assembly comprising:
 - a) a pipe welded to a trunnion stop, said trunnion stop comprising side(s), a cross section and bottom surface, the cross section having an oval shape, an elliptical shape, a rectangular shape or a circular shape and said trunnion stop further having an upper arcuate edge, where said pipe is positioned on the upper arcuate edge of the trunnion stop;
 - b) a pipe anchor encircling a partial length of said pipe including a top cradle and bottom cradle, and a bolted securing assembly to secure said top cradle to said bottom cradle when said pipe anchor encircles said partial length of said pipe;
 - c) an insulation layer positioned between said pipe and said pipe anchor;
 - d) a pass-through in said insulation layer, said pass-through having a shape matching the rectangular shape, the oval shape, the elliptical shape or the circular shape of the cross section of said trunnion stop to accommodate said trunnion stop;
 - e) a pass-through in said bottom cradle to accommodate said trunnion stop;
 - f) a plurality of structural insulation pieces, each of said plurality of structural insulation pieces being positioned immediately adjacent an outer periphery of said trunnion stop or said bottom surface of said trunnion stop; and
 - g) a base, wherein said bottom cradle is positioned on said base, said base includes a mating void having a cross-sectional shape matching the rectangular shape, the oval shape, the elliptical shape or the circular shape of the cross section of said trunnion stop, and said trunnion stop and said plurality of

structural insulation pieces securely fit into said mating void for stable engagement of said pipe to said base.

2. A pipe anchor assembly as claimed in claim 1 wherein said trunnion stop is generally box shaped.
3. A pipe anchor assembly as claimed in claim 1 wherein said base includes at least one axial stop.
4. A pipe anchor assembly as claimed in claim 1 wherein said base includes at least one lateral stop.
5. A pipe anchor assembly as claimed in claim 1 further comprising:
 - a) insulation void positioned on all sides and bottom of the pipe trunnion stop.
6. A pipe anchor assembly as claimed in claim 1 further comprising:
 - a) a base support onto which the base is set, the base support having axial stops and lateral stops.
7. A pipe anchor assembly as claimed in claim 1 further comprising:
 - a) a bolting assembly on the top cradle portion; and
 - b) a mating bolting assembly on the bottom cradle portion for securing the top cradle portion and the bottom cradle portion to each other.

8. A pipe anchor assembly as claimed in claim 1 wherein the pipe trunnion stop has a generally square cross-sectional shape.
9. A pipe anchor assembly comprising:
 - a) a pipe welded to a trunnion stop, said trunnion stop having a polygonal shaped cross-section, said trunnion stop includes a bottom wall, a pair of lateral side walls extending perpendicularly from said bottom wall and positioned parallel to each other, and a pair of axial side walls extending perpendicularly from said bottom wall and positioned parallel to each other, each side wall of said pair of axial side walls is perpendicular to said pair of lateral side walls and connects together said pair of lateral side walls, wherein said pipe is positioned on an upper arcuate edge of each of said pair of axial side walls;
 - b) a pipe anchor encircling a partial length of said pipe, said pipe anchor including a top cradle, a bottom cradle, and a securing assembly to secure said top cradle to said bottom cradle when encircling said partial length of said pipe;
 - c) an insulation layer positioned between said pipe and said pipe anchor;
 - d) a pass-through in said insulation layer to accommodate said trunnion stop;
 - e) a pass-through in said bottom cradle to accommodate said trunnion stop;
 - f) a plurality of insulation pieces, each of said plurality of insulation pieces positioned immediately adjacent a corresponding one of said bottom wall, said plurality of lateral side walls, and said plurality of axial side walls; and
 - g) a base onto which said bottom cradle is positioned, said base includes a mating void having a shape substantially similar to a shape of said trunnion stop,

which said trunnion stop and said plurality of insulation pieces securely fit into said mating void for stable engagement of said pipe to said base.

10. A pipe anchor assembly comprising:
 - a) a pipe affixed to a trunnion stop, said trunnion stop includes a pair of lateral side walls extending generally perpendicularly from said pipe and positioned opposite to each other, and a pair of axial side walls extending generally perpendicularly from said pipe and positioned opposite to each other, each side wall of said pair of axial side walls is perpendicular to said pair of lateral side walls and connects together said pair of lateral side walls, wherein said pipe is positioned on an upper arcuate edge of each side wall of said pair of axial side walls;
 - b) a pipe anchor encircling a partial length of said pipe, said pipe anchor including a top cradle, a bottom cradle, and a bolted securing assembly to secure said top cradle to said bottom cradle when encircling said partial length of said pipe;
 - c) an insulation layer positioned between said pipe and said pipe anchor;
 - d) a pass-through in said insulation layer to accommodate said trunnion stop;
 - e) a pass-through in said bottom cradle to accommodate said trunnion stop;
 - f) a plurality of structural insulation pieces, each of said plurality of insulation pieces positioned immediately adjacent a corresponding one of said plurality of lateral side walls and said plurality of axial side walls; and
 - g) a base, wherein said bottom cradle is positioned on said base, said base

includes a void into which said trunnion stop and said plurality of insulation pieces securely fit.

11. A pipe anchor assembly as claimed in claim 10 further comprising:
 - a) a bolting assembly on the top cradle portion; and
 - b) a mating bolting assembly on the bottom cradle portion for securing the top cradle portion and the bottom cradle portion to each other.

12. A pipe anchor assembly as claimed in claim 10 further comprising:
 - a) an axial stop.

13. A pipe anchor assembly as claimed in claim 10 further comprising a lateral stop.

14. A pipe anchor assembly as claimed in claim 10 wherein said trunnion stop is generally box shaped.

15. A pipe anchor assembly as claimed in claim 10 further comprising:
 - a) an insulation layer positioned between the pipe and top cradle portion.




FIGURE 1

Replacement Sheet




FIGURE 2




Figure 3A

Replacement Sheet




Figure 3B

Replacement Sheet




Figure 3C

Replacement Sheet

