

(12) **United States Patent**
Vanderwalker et al.

(10) **Patent No.:** **US 10,422,322 B2**
(45) **Date of Patent:** **Sep. 24, 2019**

(54) **SYSTEM AND METHOD FOR REMOVING OR INSTALLING A MAIN SHAFT OF A WIND TURBINE WITH MAIN SHAFT SUPPORT ELEMENTS**

(71) Applicant: **General Electric Company**,
Schenectady, NY (US)

(72) Inventors: **Darrick Adam Vanderwalker**,
Pattersonville, NY (US); **Gregory Clarence Thomas**,
Saratoga Springs, NY (US); **Hunter Ryan Anderson**,
Muskegon, MI (US); **Waylon James Esser**,
Canova, SD (US)

(73) Assignee: **General Electric Company**,
Schenectady, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 315 days.

(21) Appl. No.: **15/498,778**

(22) Filed: **Apr. 27, 2017**

(65) **Prior Publication Data**
US 2018/0313330 A1 Nov. 1, 2018

(51) **Int. Cl.**
F03D 13/10 (2016.01)
F03D 80/50 (2016.01)

(52) **U.S. Cl.**
CPC **F03D 80/50** (2016.05); **F03D 13/10** (2016.05); **F05B 2230/61** (2013.01); **F05B 2230/70** (2013.01); **F05B 2240/60** (2013.01); **Y02E 10/722** (2013.01)

(58) **Field of Classification Search**
CPC F03D 13/00; F03D 13/10; F03D 80/50
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,944,079	B1 *	5/2011	Signore	F03D 15/00	290/55
9,624,902	B2 *	4/2017	Westergaard	F03D 1/0666	
9,757,821	B2 *	9/2017	Thomas	B23B 5/08	
2007/0193014	A1 *	8/2007	Henley	B23P 19/022	29/428
2007/0200103	A1 *	8/2007	Viladomiu i Guarro	B66C 23/207	254/334
2009/0159549	A1 *	6/2009	Trede	B66C 1/108	212/270
2009/0261594	A1 *	10/2009	Christensen	F03D 13/20	290/55
2010/0021278	A1 *	1/2010	Stegemann	B66C 23/06	414/629
2010/0218508	A1 *	9/2010	Brown	F01D 25/285	60/796
2011/0162194	A1 *	7/2011	Sugimoto	B66C 9/02	29/592.1

(Continued)

FOREIGN PATENT DOCUMENTS

EP	1101934	A2 *	5/2001	B66C 23/207
EP	1291521	A1 *	3/2003	F03D 7/0268
EP	1677006	A2 *	7/2006	B66C 23/207



Primary Examiner — Jason L Vaughan

(74) *Attorney, Agent, or Firm* — Dority & Manning, P.A.

(57) **ABSTRACT**

A method and system for removing or installing a main shaft and attached main bearing assembly of a wind turbine from a bedplate form an extension onto a downwind end of the main shaft with one or more support elements to support the mains shaft on a bearing unit as it is pulled or pushed into the bedplate.

18 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0200435	A1*	8/2011	Pedersen	F03D 80/50 416/146 R
2012/0073134	A1*	3/2012	Bywaters	H02K 7/1838 29/889.1
2012/0131786	A1*	5/2012	Neumann	F03D 15/00 29/464
2012/0141292	A1*	6/2012	Signore	B66C 1/108 416/244 R
2012/0217089	A1*	8/2012	Fenger	F03D 80/50 182/2.1
2014/0373353	A1*	12/2014	Westergaard	F03D 80/70 29/889
2015/0026979	A1*	1/2015	Muller	B25B 27/06 29/889.1
2015/0096174	A1*	4/2015	Lohan	F16C 33/60 29/889.1
2015/0132119	A1*	5/2015	Fenger	F03D 80/50 415/201
2015/0135534	A1*	5/2015	Viscome	F03D 13/10 29/889
2016/0131105	A1*	5/2016	Westergaard	F03D 15/00 29/468
2017/0211547	A1*	7/2017	Thomas	F03D 13/10
2017/0306930	A1*	10/2017	Fenger	F03D 80/70

* cited by examiner




FIG. 1




FIG. 2




FIG. 3








FIG. 4








FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20

1

**SYSTEM AND METHOD FOR REMOVING
OR INSTALLING A MAIN SHAFT OF A
WIND TURBINE WITH MAIN SHAFT
SUPPORT ELEMENTS**

FIELD OF THE INVENTION

The present disclosure relates generally to wind turbines, and more particularly to systems and methods for removing and/or installing a main shaft to and from a nacelle located atop a wind turbine tower.

BACKGROUND OF THE INVENTION

Wind power is considered one of the cleanest, most environmentally friendly energy sources presently available, and wind turbines have gained increased attention in this regard. A modern wind turbine typically includes a tower, a generator, a gearbox, a nacelle, and one or more rotor blades. The nacelle includes a rotor assembly coupled to the gearbox and to the generator. The rotor assembly and the gearbox are mounted on a bedplate support frame located within the nacelle. In many wind turbines, the gearbox is mounted to the bedplate via one or more torque supports or arms. The rotor blades capture kinetic energy of wind using known airfoil principles and transmit the kinetic energy in the form of rotational energy so as to turn a main shaft coupling the rotor blades to the gearbox, or if a gearbox is not used, directly to the generator. The generator then converts the mechanical energy to electrical energy that may be deployed to a utility grid.

More specifically, the majority of commercially available wind turbines utilize multi-stage geared drivetrains to connect the turbine blades to an electrical generator. The wind turns the turbine blades, which spin a low speed shaft, i.e. the main shaft. The main shaft is coupled to an input shaft of a gearbox, which has a higher speed output shaft connected to a generator. Thus, the geared drivetrain aims to increase the velocity of the mechanical motion. Further, the gearbox and the generator are typically supported by one or more bearings and mounted to the bedplate via one or more torque arms or supports.

Over time, the main shaft and associated bearings may become worn and/or damaged due to loads and forces from the wind acting on the wind turbine components. Unfortunately, repair of the main shaft and/or the main bearing assembly often requires the turbine head (machine head) to be removed from atop the nacelle and transported to a factory wherein the bedplate is stood up vertically to remove the main shaft and bearing assembly, which is a very time-consuming and expensive procedure.

U.S. Pat. No. 8,696,302 discloses a method for repairing or replacing a main bearing on a wind turbine without removing the rotor and main shaft. This method is not suited for wind turbine designs wherein bearing replacement or repair requires removal of the rotor and main shaft.

U.S. Pat. No. 8,108,997 discloses a method for stabilizing the main shaft within the bedplate on a single bearing unit to repair or replace the gear box. This method is not suited for a procedure that requires removal of the rotor and main shaft to replace or repair the main bearing assembly.

To date, there has been no viable method for repairing, replacing, or upgrading a dual main bearing unit seated in a bedplate atop in the field wherein the procedure requires removal of the rotor and main shaft from the bedplate.

Thus, the industry is in need of new and improved systems and methods for repairing, replacing, or upgrading

2

the main shaft bearing seated in the bedplate of the wind turbine in the field, wherein the bedplate remains installed in a horizontal position atop the tower, or is removed from the tower in the field.

BRIEF DESCRIPTION OF THE INVENTION

Aspects and advantages of the invention will be set forth in part in the following description, or may be obvious from the description, or may be learned through practice of the invention.

In one aspect, the present invention is directed to a system and method wherein a support structure is formed on the downwind end of the main shaft to facilitate pulling or pushing of the main shaft into or out of the bedplate.

In this regard, a method is provided for removing an installed main shaft and attached main bearing assembly of a wind turbine from a bedplate in the field, wherein a rotor has been removed from the main shaft, a downwind end of the main shaft has been disconnected from a gearbox, and the gearbox has been removed from the bedplate. The method includes forming an extension onto a downwind end of the main shaft. The upwind end of the main shaft is supported with a rigging system and crane while the downwind end is pushed at least partway through the bedplate. During these steps, the main shaft at the downwind end is supported by the extension on a bearing unit fixed in the bedplate and the main shaft at the upwind end is supported by the rigging system. With the crane, the main shaft is supported to unload the bearing unit and slide the main shaft until the downwind end is free of the bearing unit. Then, with the crane fully supporting the main shaft, the main shaft is horizontally slid out from the bedplate.

In a particular embodiment, the extension is formed by fitting one or more support elements onto the main shaft at the downwind end of the main shaft.

The one or more support elements may be fitted onto a reduced diameter section of the main shaft adjacent the downwind end of the main shaft.

The support elements may include at least one full or partial cylindrical ring member slid or fitted onto the reduced diameter section of the main shaft. For example, a plurality of the ring members may be slid or fitted onto the reduced diameter section of the main shaft.

The ring member may have a tapered inner diameter at an end thereof that matches a taper on the main shaft that defines the reduced diameter section of the main shaft.

In an embodiment, the method may include attaching an end support element onto the downwind end of the main shaft to extend the extension axially beyond the downwind end of the main shaft.

In certain embodiments, the support element may be an end-cap element having an end ring section that extends the cylindrical extension axially beyond the downwind end of the main shaft and a cylindrical wall section that slides onto the main shaft, for example onto a reduced diameter section of the main shaft adjacent to the downwind end of the main shaft.

The invention also encompasses a method for installing a main shaft and attached main bearing assembly for a wind turbine in a bedplate in the field, wherein a gearbox has been removed from the bedplate. This installation method includes forming an extension onto a downwind end of the main shaft intended to be installed. A rigging system is connected to an upwind end of the main shaft, the rigging system suspended from a crane. With the crane, the main shaft is fully supported and moved through the bedplate until

3

the extension is positioned at a bearing unit fixed in the bedplate. The load at the downwind end of the main shaft is then transferred to the extension and bearing unit. The downwind end of the main shaft is then pulled until the main bearing assembly is seated in the bedplate. The rigging system is then removed from the upwind end of the main shaft.

The methods for forming the extension onto the main shaft discussed above are applicable to the installation method as well.

These and other features, aspects and advantages of the present invention will become better understood with reference to the following description and appended claims. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

A full and enabling disclosure of the present invention, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:

FIG. 1 is a perspective view of a conventional wind turbine;

FIG. 2 is a perspective view of a simplified, internal view of one embodiment of a nacelle of a conventional wind turbine;

FIG. 3 is a perspective view of one embodiment of a drivetrain assembly particularly illustrating the main shaft and main bearing assembly;

FIG. 4 is a perspective view of initial steps for pulling the main shaft from the wind turbine bedplate in accordance with aspects of the invention;

FIG. 5 is a perspective view of additional steps for pulling the main shaft from the wind turbine bedplate;

FIG. 6 is a perspective view of still further steps for pulling the main shaft from the wind turbine bedplate;

FIG. 7 is a perspective view of additional steps for pulling the main shaft from the wind turbine bedplate;

FIG. 8 is a perspective view of the main shaft removed from the bedplate and supported by a crane;

FIG. 9 is a perspective view of a main shaft prior to installation of support elements thereon;

FIG. 10 is a perspective view of the main shaft of FIG. 9 with the support elements installed on the downwind end thereof;

FIG. 11 is a diagram view of a main shaft with support elements to define a cylindrical extension region on the downwind end of the main shaft;

FIG. 12 is a perspective view of the outer ring member of the support elements;

FIG. 13 is a perspective view of the inner ring member of the support elements;

FIG. 14 is a perspective view of the support ring member of the outer support elements;

FIG. 15 is a perspective view of a hydraulic ram assembly in a push configuration for pushing the downwind end of the main shaft through the bedplate;

FIG. 16 is a perspective view of the hydraulic ram assembly of FIG. 15 at the end of its push stroke;

FIG. 17 is a perspective view of the hydraulic ram assembly in a pull configuration for pulling the downwind end of the main shaft into the bedplate;

FIG. 18 is a perspective view of the hydraulic ram assembly of FIG. 17 at the end of its pull stroke;

4

FIG. 19 is a flow chart of a method embodiment for removal of the main shaft from the wind turbine bedplate; and

FIG. 20 is a flow chart of a method embodiment for installation of the main shaft in the wind turbine bedplate.

DETAILED DESCRIPTION OF THE INVENTION

Reference now will be made in detail to embodiments of the invention, one or more examples of which are illustrated in the drawings. Each example is provided by way of explanation of the invention, not limitation of the invention. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the scope or spirit of the invention. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to yield a still further embodiment. Thus, it is intended that the present invention covers such modifications and variations as come within the scope of the appended claims and their equivalents.

Generally, the present invention is directed to methods for installation and/or removal of the main shaft (with attached main bearing assembly) from a bedplate (e.g., a single piece forged bedplate) in the field, wherein the nacelle (machine head) remains atop the tower or is removed from the tower for servicing at ground level in the field. The methods provide significant commercial advantages in terms of time and expense for maintenance procedures that require removal of the main shaft from the machine head, such as repair/replacement of the main bearing assembly fitted on the shaft. Aspects of the present inventive methods are described below with reference to the drawings.

Referring now to the drawings, FIG. 1 illustrates a perspective view of one embodiment of a wind turbine 10 relevant to the present discussion. As shown, the wind turbine 10 generally includes a tower 12 extending from a support surface 14, a nacelle 16 (also referred to as a machine head) mounted on the tower 12, and a rotor 18 coupled to the nacelle 16. The rotor 18 includes a rotatable hub 20 and at least one rotor blade 22 coupled to and extending outwardly from the hub 20. For example, in the illustrated embodiment, the rotor 18 includes three rotor blades 22. However, in an alternative embodiment, the rotor 18 may include more or less than three rotor blades 22. Each rotor blade 22 may be spaced about the hub 20 to facilitate rotating the rotor 18 to enable kinetic energy to be transferred from the wind into usable mechanical energy, and subsequently, electrical energy. For instance, the hub 20 may be rotatably coupled to an electric generator 24 (FIG. 2) positioned within the nacelle 16 to permit electrical energy to be produced.

The wind turbine 10 may also include a wind turbine controller 26 centralized within the nacelle 16. However, in other embodiments, the controller 26 may be located within any other component of the wind turbine 10 or at a location outside the wind turbine. Further, the controller 26 may be communicatively coupled to any number of the components of the wind turbine 10 in order to control the components thereof. As such, the controller 26 may include a computer or other suitable processing unit. Thus, in several embodiments, the controller 26 may include suitable computer-readable instructions that, when implemented, configure the controller 26 to perform various different functions, such as

receiving, transmitting and/or executing wind turbine control signals and/or performing the various method steps as described herein.

Referring now to FIG. 2, a simplified, internal view of one embodiment of the nacelle 16 shown in FIG. 1 is illustrated, particularly illustrating the drivetrain assembly 30. As shown, the drivetrain assembly 30 includes the generator 24, which may be coupled to the rotor 18 for producing electrical power from the rotational energy generated by the rotor 18. The rotor 18 includes a main shaft 34 coupled to the hub 20 via a rotor flange 36 for rotation therewith. The main shaft 34, in turn, is rotatably coupled to a generator shaft 54 of the generator 24 through a gearbox 38 connected to a bedplate support frame 40 by torque support arms 52. The bedplate 40 is depicted in the figures, for illustrative purposes, as a single-piece bedplate made from one complete casting with bores machined therein where the bearings are seated. The present invention may also have utility with a two-piece bedplate that is split horizontally, particularly if the invention offers a time and expense advantage as compared to unbolting the split bedplate and lifting the main shaft and bearings from the bottom half of the bedplate.

Referring to FIG. 3, the main shaft 34 is supported by one or more bearing assemblies 46, 48. For example, as shown, a forward “upwind” end 42 of the shaft 36 is supported by the main bearing assembly 46, which in this particular embodiment is depicted as a double taper-roller bearing (TRB) assembly (the main bearing assembly 46 in the embodiment of FIGS. 9 and 10 is a single taper-roller bearing). This main bearing assembly 46 is fitted onto the main shaft 36 and can only be replaced or repaired by pulling the main shaft 34 from the bedplate 40. The aft “downwind” end 44 of the main shaft 36 is supported by the bearing unit 48, which in this particular embodiment is depicted as a cylindrical roller bearing (CRB) assembly. The CRB assembly 48 is mounted to the bedplate 40, and the shaft is able to be slid axially through this bearing 48 upon being pulled from the bedplate 40.

As is generally understood, the main shaft 34 may provide a low speed, high torque input to the gearbox 38 in response to rotation of the rotor blades 22 and the hub 20. The gearbox 38 may then be configured to convert the low speed, high torque input to a high speed, low torque output to drive the generator shaft 36 and, thus, the generator 24.

Each rotor blade 22 may also include a pitch adjustment mechanism 60 configured to rotate each rotor blade 22 about its pitch axis 28. Further, each pitch adjustment mechanism 60 may include a pitch drive motor 68 (e.g., any suitable electric, hydraulic, or pneumatic motor), a pitch drive gearbox 62, and a pitch drive pinion 64. The pitch drive motor 68 is coupled to the pitch drive gearbox 62 to impart a mechanical force to the pitch drive gearbox 62. Similarly, the pitch drive gearbox 62 is coupled to the pitch drive pinion 64 for rotation therewith. The pitch drive pinion 64 is in rotational engagement with a pitch bearing 66 coupled between the hub 20 and a corresponding rotor blade 22 such that rotation of the pitch drive pinion 64 causes rotation of the pitch bearing 66, thereby rotating the rotor blade 22 about the pitch axis 28. Similarly, the wind turbine 10 may include one or more yaw drive mechanisms 56 communicatively coupled to the controller 26, with each yaw drive mechanism(s) 56 being configured to change the angle of the nacelle 16 relative to the wind (e.g., by engaging a yaw bearing 58 of the wind turbine 10).

FIG. 19 provides a flowchart representation of a method embodiment 100 in accordance with the present invention for removing an installed main shaft 34 and attached main

bearing assembly 46 from the bedplate 40 in the field with the nacelle 16 remaining attached to the tower 12, or removed from the tower and placed at ground level for servicing. Step 102 involves preparing the wind turbine 10 for removal of the main shaft 34. This may include any one or combination of removing the blades 22 and rotor hub 20, removing various panels/wall of the nacelle 16 to expose the bedplate 40, removing the generator 24, removing the gearbox 38, arranging a crane 78 (FIG. 8) at the site, staging a rigging system 70, and any other preparatory step or procedure that is necessitated by the wind turbine design or site location for a subsequent removal of the main shaft 34. Although it may be desired for space and safety concerns, the method 100 may be practiced without removing the generator 24 in certain wind turbine designs.

At step 104, part of the rigging system 70 is connected to the upwind end 44 of the main shaft 34. For example, referring to FIG. 4, the rigging system 70 may include multiple “legs” 72, 74 in the form of chains, cables, webbing, slings, and the like, attachable to a cable on the crane 78 by any suitable conventional means (e.g., a turnbuckle). One or more of these legs 72, 74 are connected to the upwind end 42 in a manner sufficient for the crane to support the full load of the upwind end 42 without the upwind end 42 rolling. In the depicted embodiment, the first leg 72 and second leg 74 are connected (e.g., using turnbuckles or other suitable devices) to preexisting holes in the rotor flange 36 at upper, opposite sides of the flange 36.

Once the rigging is connected to the crane cable and the upwind end 42 of the main shaft 34 is supported, step 106 involves pushing the downwind end 44 of the main shaft 34 at least partway through the bedplate 40. This “pushing” may be accomplished by electrical, hydraulic, pneumatic, or electro/hydraulic motive means. In the embodiment of FIGS. 15-18, a hydraulic ram assembly 82 is configured at the downwind end 44 for this purpose, as explained in greater detail below.

FIG. 5 depicts the upwind end 42 of the main shaft 34 being pushed out of the bedplate 40 to the extent that the main bearing assembly 46 (e.g., the TRB assembly) has been unseated and is partially out of the bedplate 40.

At step 108, the main shaft 34 is slid through the bedplate 40 at least until a center of gravity of the main shaft 34 and main bearing assembly 46 are free of the bedplate 40, as depicted in FIG. 6. The axial location of the center of gravity is predefined and will vary depending on the size of the main shaft, the main bearing assembly, materials, and so forth.

At step 110, a “leveling” leg 76 of the rigging system 70 is attached to the main shaft 34 at a location such that the center of gravity is located between the leveling leg 76 and the first and second legs 72, 74 of the rigging system 70. The leveling leg 76 is preferably adjustable (manually or remotely) for balancing the main shaft 34. In this manner, the main shaft 34 can be balanced and eventually fully supported by the crane 70 in an essentially horizontal orientation (FIG. 8). In the depicted embodiment, the leveling leg 76 is depicted as an adjustable sling or cradle that wraps around the main shaft 34. Any suitable rigging device that supports the main shaft at the desired axial location may be used for this purpose.

At step 112, with the crane 70, the main shaft 34 is fully supported to unload the bearing unit 48 at the upwind side 42 of the bedplate. The main shaft 34 can then be slid completely out of the bedplate 40 with the crane 78 (step 114), until the downwind end is free of the bearing unit 48, as depicted for example in FIG. 8. The main shaft 34 and

main bearing assembly **46** are supported by the rigging system in a horizontal and balanced orientation during this process.

At this point, at step **116**, the main shaft **34** and attached main bearing assembly **46** can be lowered to the ground, at which time repair/replacement of the main bearing assembly **46** can be done.

With certain main shaft designs, it may be desired to increase the effective length of the downwind end **44** of the main shaft **34** to ensure that the downwind end is supported by the bearing unit **48** at least until the center of gravity of the main shaft **34** and bearing assembly **46** are free of the upwind end **42** of the bedplate **40**. Referring to the view in FIG. **8**, this may be accomplished by essentially adding extension or support elements **90** to the end of the main shaft **34** in order to extend the cylindrical length of the shaft, as explained in more detail below with reference to FIGS. **9** through **14**.

Referring to FIG. **20**, the present invention also encompasses a method **200** for installing a main shaft **34** and attached main bearing assembly **46** for a wind turbine **10** in a bedplate **40** installed atop a wind turbine tower **12** in the field, wherein a gearbox **38** has been removed from the bedplate **40**. The installation method **200** is essentially the reverse of the removal method **100**.

At step **202**, necessary preparations are made to the wind turbine for the installation.

At step **204**, at least a first leg **72** of the rigging system **70** is connected to the upwind end **42** of the main shaft **34**, which may be at ground level. The leveling leg **76** of the rigging system **70** is connected to the main shaft **34** at a location such that a center of gravity of the main shaft **34** and bearing assembly **46** is located between the leveling leg **76** and the first/second legs **72**, **74** of the rigging system **70**. If not yet done, the rigging system **70** is connected to the crane cable, and the main shaft **34** is raised in a balanced, horizontal orientation.

At step **206**, with the crane **78** fully supporting the main shaft **34**, the main shaft **34** is slid through the bedplate until the downwind end **44** of the main shaft is positioned at the bearing unit **48** fixed in the bedplate **40**.

At step **208**, the load of the downwind end **44** is transferred to the bearing unit, and at step **210**, the leveling leg **76** is removed from the main shaft **34** so that the main shaft can be pulled into the bedplate **40**.

At step **212**, the downwind end **44** is "pulled" to further slide the main shaft into the bedplate **40** until the main bearing assembly **46** is seated. The pull system hydraulic ram assembly **82** discussed above, or other pull system means, can be operated in reverse for this purpose, or any other suitable electrical, hydraulic, or electric/hydraulic system may be used for this purpose.

At step **214**, the remaining legs **72**, **74** of the rigging system **70** can be removed from the main shaft **70**. The shaft can be slide further into the bedplate **40** with the hydraulic ram assembly **82** if needed.

As discussed, the effective length of the downwind end **44** of the main shaft **34** may be increased, for example by the addition of the support elements **90**, to ensure that the downwind end **44** is supported by the bearing unit **48** prior to pulling the downwind end **44** of the main shaft **34**.

Operation of one embodiment for pushing the main shaft **34** from the downwind end **44** thereof in the removal method **100**, and pulling the main shaft **34** at the downwind end **44** in the installation method **220**, is depicted in FIGS. **15** through **18**, in which FIG. **15** depicts the hydraulic ram assembly **82** in a "push" configuration. Initially, a specifi-

cally designed ring or partial arc component **85** is mounted to the bedplate **40** around the main shaft **34** at the downwind end **44**. A plurality of rods **86** (depending on the number of hydraulic cylinders used) are threaded into this ring at equally circumferentially spaced locations. These rods **86** may be threaded along the length thereof. In the depicted embodiment, three rods **86** are spaced around the ring **85**. A plate **88** is designed with holes corresponding to the locations of the rods **86** on the ring **85**, wherein the plate is slidable onto the rods **86**. The plate **88** can have any shape, such as circular. In the depicted embodiment, the plate **88** is star-shaped with an arm at each of the rod **86** locations.

Referring to FIGS. **15** through **18**, a hydraulic cylinder **84** is mounted on the plate **88** at each hole location. In the depicted embodiment, the hydraulic cylinders **84** are single acting "hollow" cylinders and mounted on the plate **88** such that a ram **87** of each cylinder **84** moves in a direction away from the plate **88** when actuated. At each location, the rod **86** runs through the cylinder **84** and ram **87**. Suitable hydraulic cylinders **84** are commercially available from different manufacturers, including ENERPAC.

In the push configuration of FIGS. **15** and **16**, the plate **88** and hydraulic cylinders **84** are slid onto the rods **86** such that the plate **88** bears against the downwind end **44** of the main shaft **34** or an end support ring **94** (discussed below) attached to the end of the main shaft **34**. The position of the rams **87** on the rods **86** is locked in place by a nut threaded onto the rods **86** against which the rams **87** bear upon actuation of the cylinders **84**. Other locking devices on the rods **86** can be used for this purpose. FIG. **15** depicts an initial position of the hydraulic ram assembly **82** in the push configuration, and FIG. **16** depicts a final position wherein the plate **88** has "bottomed out" against the ring **85** and the main shaft **34** has been pushed into the bedplate **40**. The push stroke of the hydraulic cylinders **84** is thus equal to effective displacement distance of the rams **87**. Prior to downwind end **44** of the main shaft **34** reaching the position depicted in FIG. **16**, the main bearing assembly **46** has unseated from the bedplate **40** and the leveling leg **76** of the rigging system has been attached to the main shaft, as depicted in FIG. **6**.

FIG. **17** depicts the hydraulic ram assembly **82** configured in a "pull" configuration for pulling the downwind end **44** of the main shaft through the bedplate **40** for the installation method **220** described above. In the depicted embodiment, the hydraulic rams **84** are single action rams as discussed above. Thus, in the pull configuration, the orientation of the plate **88** and hydraulic cylinders **84** on the rods **86** is reversed as compared to FIG. **15** such that the rams **87** act against the ring **85** and the hydraulic cylinders **84** (and attached plate **88**) are locked in position by stops (e.g., nuts) on the rods **86**. An inner plate **89** (a "pull" plate) may be fixed to the downwind end **44** of the main shaft **34** (or end support ring **94**) to provide a better surface for fixing the plate **88** relative to the main shaft **34**.

FIG. **17** depicts the hydraulic ram assembly **82** as it is being configured in the pull position, and FIG. **18** depicts the hydraulic ram assembly **82** and main shaft **34** at the end of the pull stroke of the hydraulic cylinders **84**, wherein the main shaft **34** assumes a final position in the bedplate **40** corresponding to FIG. **4** where the main bearing assembly **46** is seated at its operation position within the bedplate **40**. At this point, the hydraulic ram assembly **82** can be dismantled from the main shaft **34** and the support elements **90** removed.

The assist motive system is illustrated in the figures as the hydraulic ram assembly **82** for illustrative purposes only. As

mentioned, the assist system may be any one or combination of an electrical, hydraulic, pneumatic, or electro/hydraulic system configured in a push mode at the downwind end of the main shaft.

An embodiment of the means used to extend the cylindrical profile of the main shaft **34** to ensure that the end of the main shaft **34** remains fully supported by the bearing unit **48** at the downwind end **44** of the bedplate **40** until load is transferred fully to the crane **78** is the support elements **90** discussed above and depicted in greater detail in FIGS. **9** through **12**.

FIG. **9** depicts an embodiment of a main shaft **34** with a main bearing assembly **46** fitted thereon adjacent the upwind end thereof. At the downwind end **44** it can be seen that the main shaft **34** tapers radially inward just aft of the bearing surface **91** that engages the bearing unit **48** when the main shaft **34** is configured in the bedplate **40**. Without the support elements **90** fitted onto this section of the main shaft **34**, when the bearing surface **91** is pushed past the bearing unit **48**, the shaft would “drop” to a certain degree onto the radially reduced aft section and cant to a non-horizontal orientation within the bedplate **40**, making further removal of the main shaft difficult. The opposite action would occur upon installation of the shaft without the support elements **90**.

The support elements **90** essentially define an extension **92** (FIG. **10**) along the radially reduced aft section of the main shaft **34** that ensures the end of the main shaft **34** remains fully supported on the bearing unit **48** in a horizontal orientation of the main shaft **34** until the full load of the main shaft **34** and main bearing assembly **46** is borne by the rigging system **70** and crane **78**. This extension **92** may be, for example, a full cylindrical extension that completely encircles the main shaft **34**, or a partial semi-circular extension around a bottom portion of the main shaft **34**. The extension **92** may have a continuous surface, or a discontinuous surface (e.g., a cage-like structure). The extension could be defined by one or more axially extending planks or strip members. It should be appreciated that various support element **90** designs can be configured to meet the need for supporting the end of the main shaft **34** on the bearing unit **48**. The cylindrical support elements **90** and full cylindrical extension **92** illustrated in the present figures is for illustrative purposes only.

In the depicted embodiment, the support elements **90** include one or more cylindrical rings **96**, **98** that slide onto or are fitted onto the main shaft **34** around the reduced diameter section thereof. For example, an inner support ring **96** (FIGS. **11** and **13**) may have a tapered inner diameter (or other non-cylindrical profile) at one end thereof that essentially matches the taper (or other profile) on the main shaft **34**, as depicted in FIG. **11**, thereby extending the cylindrical extension **92** to include the tapered region of the main shaft **34**. An adjacent outer support ring **98** may be fitted onto the shaft **34** and extend essentially to the downwind end **44** thereof.

It should be appreciated that the inner and outer support rings **96**, **98** could be replaced by a single ring, a partial arc, or any combination thereof.

The support elements **90** may also include an end support ring **94** (FIGS. **11** and **14**) that bolts to the downwind end **44** of the main shaft and extends the cylindrical extension **92** past the downwind end **44**, as can be appreciated from FIG. **11**. The end support ring **94** may have a diameter that matches the diameter of the main shaft **34** with inner and outer rings **96**, **98** fitted thereon.

It should be appreciated that a single support element **90** configured as an end-cap **93** could also serve all of the functions of the rings **94**, **96**, and **98**, as depicted in the alternative in FIG. **11**. The end-cap **93** can be formed as an integral or multi-component element with an end ring section **95** and a cylindrical wall section **97**.

The various support elements **90** may be formed of a material having a low coefficient of friction, yet sturdy enough to support the main shaft **34** on the bearing unit **48** without significant deformation.

This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

What is claimed is:

1. A method for removing an installed main shaft and attached main bearing assembly of a wind turbine from a bedplate in the field, wherein a rotor has been removed from an upwind end of the main shaft, a downwind end of the main shaft has been disconnected from a gearbox, and the gearbox has been removed from the bedplate, the method comprising:

forming an extension onto a downwind end of the main shaft;
supporting the upwind end of the main shaft with a rigging system;
pushing the downwind end of the main shaft partway through the bedplate, wherein the main shaft at the downwind end is supported by the extension on a bearing unit fixed in the bedplate and the main shaft at the upwind end is supported by the rigging system;
with the crane, supporting the main shaft to unload the bearing unit and slide the main shaft until the downwind end is free of the bearing unit;
with the crane fully supporting the main shaft, horizontally sliding the main shaft out from the bedplate.

2. The method of claim 1, wherein the extension is formed by fitting one or more support elements onto the main shaft at the downwind end of the main shaft.

3. The method of claim 2, wherein the one or more support elements are fitted onto a reduced diameter section of the main shaft adjacent the downwind end of the main shaft.

4. The method of claim 3, wherein the one or more support elements comprise at least one full or partial cylindrical ring member slid or fitted onto the reduced diameter section of the main shaft.

5. The method of claim 4, wherein a plurality of the ring members are slid or fitted onto the reduced diameter section of the main shaft.

6. The method of claim 4 wherein the ring member has a tapered inner diameter at an end thereof that matches a taper on the main shaft defining the reduced diameter section of the main shaft.

7. The method of claim 2, further comprising attaching an end support element onto the downwind end of the main shaft to extend the extension axially beyond the downwind end of the main shaft.

11

8. The method of claim 2, wherein the support element is an end-cap element having an end ring section that extends the extension axially beyond the downwind end of the main shaft and a cylindrical wall section that slides onto the main shaft.

9. The method of claim 8, wherein the cylindrical wall section slides onto a reduced diameter section of the main shaft adjacent to the downwind end of the main shaft.

10. A method for installing a main shaft and attached main bearing assembly for a wind turbine in a in the field, wherein a gearbox has been removed from the bedplate, the method comprising:

- forming an extension onto a downwind end of the main shaft intended to be installed;
- connecting a rigging system to an upwind end of the main shaft, the rigging system suspended from a crane;
- with the crane, fully supporting and moving the main shaft through the bedplate until the extension is positioned at a bearing unit fixed in the bedplate;
- transferring load at the downwind end of the main shaft to the extension and bearing unit;
- pulling the downwind end of the main shaft until the main bearing assembly is seated in the bedplate; and
- removing the rigging system from the upwind end of the main shaft.

11. The method of claim 10, wherein the extension is formed by fitting one or more support elements onto the main shaft at the downwind end of the main shaft.

12

12. The method of claim 11, wherein the one or more support elements are fitted onto a reduced diameter section of the main shaft adjacent the downwind end of the main shaft.

5 13. The method of claim 12, wherein the one or more support elements comprise at least one full or partial cylindrical ring member slid or fitted onto the reduced diameter section of the main shaft.

10 14. The method of claim 13, wherein a plurality of the ring members are slid or fitted onto the reduced diameter section of the main shaft.

15 15. The method of claim 13, wherein the ring member has a tapered inner diameter at an end thereof that matches a taper on the main shaft defining the reduced diameter section of the main shaft.

16. The method of claim 11, further comprising attaching an end support member onto the downwind end of the main shaft to extend the extension axially beyond the downwind end of the main shaft.

20 17. The method of claim 11, wherein the support element is an end-cap element having an end ring section that extends the cylindrical extension axially beyond the downwind end of the main shaft and a cylindrical wall section that slides onto the main shaft.

25 18. The method of claim 17, wherein the cylindrical wall section slides onto a reduced diameter section of the main shaft adjacent to the downwind end of the main shaft.

* * * * *