



(11)

EP 4 378 627 A2

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
05.06.2024 Bulletin 2024/23

(51) International Patent Classification (IPC):
B25B 15/02^(2006.01)

(21) Application number: **24163032.6**

(52) Cooperative Patent Classification (CPC):
B25B 15/005; B25B 15/008

(22) Date of filing: **30.07.2020**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **30.07.2019 PCT/IB2019/056500**
22.08.2019 US 201916548470
29.07.2020 US 202016942658

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
20846157.4 / 3 990 221

(71) Applicant: **Grip Holdings LLC**
Brandon, FL 33510 (US)

(72) Inventors:
• **KUKUCKA, Paul
Brandon, 33509 (US)**
• **KUKUCKA, Thomas Stefan
Brandon, 33509 (US)**

(74) Representative: **Loo, Chi Ching et al**
Albright IP Limited
County House
Bayshill Road
Cheltenham, Gloucestershire GL50 3BA (GB)

Remarks:

This application was filed on 12-03-2024 as a
divisional application to the application mentioned
under INID code 62.

(54) **ADVANCED HOLDING APPARATUS**

(57) A screw bit body which allows for efficient torque force application onto a socket fastener. The screw bit body includes a plurality of laterally-bracing sidewalls, a first base, and a second base. The laterally-bracing sidewalls are radially distributed about a rotation axis of the screw bit body with each further including a first lateral edge, a second lateral edge, a bracing surface, and an engagement cavity. The engagement cavity creates an additional gripping point to prevent slippage in between the screw bit body and the socket fastener. The engagement cavity traverses normal and into the bracing surface. Additionally, the engagement cavity traverses into the screw bit body from the first base to the second base. The engagement cavity is specifically positioned offset from the first lateral edge by a first distance.




FIG. 1

EP 4 378 627 A2

Description

FIELD OF THE INVENTION

[0001] The present invention generally relates to various tools designed for tightening or loosening fasteners, in particular bolts and nuts. More specifically, the present invention is an anti-slip multidirectional driver bit, designed to prevent damaging or stripping fasteners during the extraction or tightening process.

BACKGROUND OF THE INVENTION

[0002] Hex bolts, nuts, screws, and other similar threaded devices are used to secure and hold multiple components together by being engaged to a complimentary thread, known as a female thread. The general structure of these types of fasteners is a cylindrical shaft with an external thread and a head at one end of the shaft. The external thread engages a complimentary female thread tapped into a hole or a nut and secures the fastener in place, fastening the associated components together. The head receives an external torque force and is the means by which the fastener is turned, or driven, into the female threading. The head is shaped specifically to allow an external tool like a wrench to apply a torque to the fastener in order to rotate the fastener and engage the complimentary female threading to a certain degree. This type of fastener is simple, extremely effective, cheap, and highly popular in modern construction.

[0003] One of the most common problems in using these types of fasteners, whether male or female, is the tool slipping in the head portion, or slipping on the head portion. This is generally caused by either a worn fastener or tool, corrosion, overtightening, or damage to the head portion of the fastener. The present invention is a driving bit design that virtually eliminates slippage. The design uses a series of segmented portions that bite into the head of the fastener and allow for efficient torque transfer between the driving bit and the head portion of the fastener. The present invention eliminates the need for the common bolt extractors as they require unnecessary drilling and tools. With the development of electric screwdrivers, and drills, people have been using, power tools to apply the required torsional forces and remove various fasteners. The present invention provides a double-sided driver end bit, thus allowing for torque to be applied to the fastener in both clockwise and counterclockwise directions, thus tightening or loosening the fastener. Most driver end bits have a standardized one fourth inch hex holder and come in various configurations including but not limited to, square end, hex end, or star end.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004]

FIG. 1 is a perspective view of the present invention.

FIG. 2 is a perspective view of an alternative embodiment of the present invention.

FIG. 3 is a front view of the alternative embodiment of the present invention in FIG. 2.

FIG. 4 is a rear view of the alternative embodiment of the present invention in FIG. 2.

FIG. 5 is a perspective view of an alternative embodiment of the present invention.

FIG. 6 is a bottom perspective of the present invention.

FIG. 7 is a perspective view of an alternative embodiment of the present invention.

FIG. 8 is a perspective view of an alternative embodiment of the present invention.

FIG. 9 is a front view of the alternative embodiment of the present invention in FIG. 8.

FIG. 10 is a perspective view of an alternative embodiment of the present invention.

FIG. 11 is a perspective view of an alternative embodiment of the present invention.

FIG. 12 is a perspective view of an alternative embodiment of the present invention.

FIG. 13 is a front view of a separate alternative embodiment of the present invention in relation to FIG. 2, wherein an entire cross-section of the engagement cavity as a triangular profile.

FIG. 14 is a rear view of the separate alternative embodiment of the present invention in relation to FIG. 2, wherein an entire cross-section of the engagement cavity as a triangular profile.

FIG. 15 is a front view of another separate alternative embodiment of the present invention in relation to FIG. 2, wherein an entire cross-section of the engagement cavity as a triangular profile.

FIG. 16 is a front view of another separate alternative embodiment of the present invention in relation to FIG. 15, wherein different portions of a laterally-bracing sidewall are either concave or convex.

FIG. 17 is a front view of another separate alternative embodiment of the present invention in relation to FIG. 15, wherein different portions of a laterally-bracing sidewall are either convex or concave.

DETAIL DESCRIPTIONS OF THE INVENTION

[0005] All illustrations of the drawings are for the purpose of describing selected versions of the present invention and are not intended to limit the scope of the present invention.

[0006] The present invention generally related to torque tool accessories. More specifically, the present invention is a multi-grip screw bit, also known as a screw bit or driver. The present invention allows for a higher torque to be applied to a fastener than a similarly sized conventional driver bit without damaging the head of the fastener or the bit tool. This is achieved through the use of a multitude of engagement features which effectively grip the head of the fastener. The present invention is a

screw bit that is compatible with a variety of torque tools including, but not limited to, traditional drills, bit-receiving screwdrivers, socket wrenches, and socket drivers.

[0007] In its simplest embodiment, referring to FIG. 1, the present invention comprises an at least one screw bit body **1** and an attachment body **19**. The screw bit body **1** is a shank which engages the socket fastener, such as a socket screw or a socket bolt, in order to apply a torque force onto the socket faster. The screw bit body **1** comprises a plurality of laterally-bracing sidewalls **2**, a first base **14**, and a second base **15**. In general, the screw bit body **1** is a prism composed of a strong metal. Each of the plurality of laterally-bracing sidewalls **2** engage within and grip the socket fastener in order to efficiently transfer torque from a torque tool to the socket fastener. The first base **14** and the second base **15** are positioned opposite to each other along the plurality of laterally-bracing sidewalls **2**. Additionally, the first base **14**, and thus second base **15**, is preferably oriented perpendicular to each of the plurality of laterally-bracing sidewalls and thus enclose/complete the prism shape of the screw bit body **1**. More specifically, it is preferred that the first base **14** comprises a first base surface **26**, wherein the first base surface **26** is flat and is oriented perpendicular to the bracing surface **5** of each of the plurality of laterally-bracing sidewalls **2**.

[0008] The attachment body **19** allows the present invention to be attached to an external torque tool and, thus, allow torque force to be applied to the socket fastener through the screw bit body **1**. The attachment body **19** is centrally positioned around and along a rotation axis **16** of the screw bit body **1** such that the rotation axis of the attachment body **19** and the rotation axis **16** of the screw bit body **1** are coincidentally aligned. Additionally, the attachment body **19** is connected adjacent to the second base **15**. The attachment body **19** preferably has a hexagonal cross-section in order to fit within a female attachment member of the external torque tool. External torque tools include, but are not limited to, electric drills, torque wrenches, pneumatic drills, socket screw drivers, and other similar torque tools. In an exemplary embodiment, the entire cross-section **9** of the at least one engagement cavity **8** is a triangular profile. This arrangement provides ample space while applying torque for relief of residual stresses and material that would otherwise strain the at least one engagement cavity **8**. Furthermore, the triangular profile may be concave along a direction from the first lateral edge **3** to the second lateral edge **4**. In this way, torquing stresses are captured within the at least one engagement cavity **8** during the application of torsion.

[0009] The triangular profile may further comprise a plurality of vertexes **27**, as represented in FIG. 15. The plurality of vertexes **27** relates to the locus of points representing corners of the triangular profile. Each of the plurality of vertexes **27** may be a rounded corner. This arrangement prevents point stresses from building at the plurality of vertexes **27** without significantly reducing the

space required for effective mitigation of fatigue effects.

[0010] In many cases, it may be advantageous to allow for slight modifications to a strictly triangular profile, depending upon the intensity of torquing stresses and the shape of the bolt or fixture. To enhance efficiency in such situations, the triangular profile may comprise a plurality of vertexes **31** and a pair of elongated portions **32**, as shown in FIG. 16 and 17. The plurality of vertexes **31** relates to a set of points representing the corners of the triangular profile. The plurality of vertexes **31** may be viewed as two leading edge elements along the first lateral edge **3** and the second lateral edge **4** and one cavity base element. The one cavity base element may also be a straight line connected to the pair of elongated portions **32**. The pair of elongated portions **32** denotes the edges which join the plurality of vertexes **31** together. The pair of elongated portions **32** is interspersed amongst the plurality of vertexes **31**. Thus, the pair of elongated portions **32** connects each of the plurality of vertexes **31** together. Each of the pair of elongated portions **32** is a shape selected from the group consisting of: straight line, concave, and convex. The group of shapes that may be selected for the plurality of vertexes **31**, the pair of elongated portions **32**, or the one cavity base element may be a radius or angular shape. This arrangement enables the pair of elongated portions **32** to better adapt to different torquing stresses, thus preventing detrimental wear upon the used bit due to fatigue.

[0011] Other uses may call for modifications to the shape of the edges surrounding the triangular profile together. To provide for this, a bracing surface **5** comprises a first portion **33** and a second portion **34**, as shown in FIG. 16 and 17. The first portion **33** and the second portion **34** relate to the edges surrounding the triangular profile. The first portion **33** is positioned along a first distance **21**, which arranges the first portion **33** adjacent to the first lateral edge **3**. In addition, the second portion **34** is positioned along a second distance **22**, which arranges the second portion **34** adjacent to the second lateral edge **4**. The first portion **33** is a shape selected from the group consisting of: straight line, concave, and convex. In this way, the first portion **33** may be adapted to best address potential mechanical fatigue to the present invention. Similarly, the second portion **34** is a shape selected from the group consisting of: straight line, concave and convex. In this way, the second portion **34** may be adapted to best address potential mechanical fatigue to the present invention. The group of shapes that may be selected for the first portion **33** and a second portion **34**, as shown in FIG. 16 and 17, may be a radius or angular shape. It is often most advantageous for the first portion **33** and the second portion **34** to display opposite curvatures, with one being concave and the other being convex, for optimal reduction of cyclical stress-based effects on the present invention. Additional modifications may be implemented to the first lateral edge **3** and the second lateral edge **4** to form lateral edges which are angular or radial in shape.

[0012] Referring to FIG. 3 and FIG. 4, each of the plurality of laterally-bracing sidewalls 2 comprises a first lateral edge 3, a second lateral edge 4, a bracing surface 5, and an at least one engagement cavity 8. The plurality of laterally-bracing sidewalls 2 is radially positioned about the rotation axis 16 of the screw bit body 1 in order to yield a geometric profile complimentary to that of the socket fastener. The number within the plurality of laterally-bracing sidewalls 2 is subject to change to complement the shape and profile of a variety of socket fasteners. In one embodiment of the present invention, the number within the plurality of laterally-bracing sidewalls 2 is six and the resulting geometric profile of the screw bit body 1 is a hexagon. In an alternative embodiment of the present invention, the number within the plurality of laterally-bracing sidewalls 2 is four.

[0013] The bracing surface 5 physically presses against the socket fastener, specifically against the lateral sidewall of a head portion from the socket fastener. The first lateral edge 3 and the second lateral edge 4 are positioned opposite to each other across the bracing surface 5. When viewed from either the top perspective or the bottom perspective, the first lateral edge 3 and the second lateral edge 4 from each of the plurality of laterally-bracing sidewalls 2 make up the corners of the screw bit body 1. The engagement cavity 8 extends normal and into the bracing surface 5 and creates an additional gripping point/tooth on the bracing surface 5. Additionally, the engagement cavity 8 is positioned offset from the first lateral edge 3 by a first distance 21. Resultantly, the gripping point is created by the engagement cavity 8 and the bracing surface 5. In another embodiment, the gripping point is created by the engagement cavity 8 and an adjacent edge, wherein the adjacent edge is either the first lateral edge 3 or the second lateral edge 4; in particular, the adjacent edge is the edge closest to the engagement cavity 8. Additionally, the engagement cavity 8 extends into the screw bit body 1 from the first base 14 towards the second base 15. This ensures that the additional gripping point extends along the length of the screw bit body 1 for maximum grip engagement between the screw bit body 1 and the socket fastener. To further accomplish this, it is preferred that an entire cross-section 9 of the engagement cavity 8 is parallel to the first base 14 and the second base 15. In one embodiment of the present invention, the engagement cavity 8 also tapers from the first base 14 to the second base 15 as seen in FIG. 11. As a consequence of this embodiment, the at least one engagement cavity 8 may taper from the first base 14 to the second base 15 in such a way that the triangular profile adjacent to the first base 14 is larger than the triangular profile adjacent to the second base 15. In this way, the at least one engagement cavity 8 may be appropriately shaped to meet the needs and requirements of the user. Referring to FIG. 3, in one embodiment of the present invention, the entire cross-section 9 of the engagement cavity 8 is a partially-circular profile. Additionally, the partially-circular profile is concave along a

direction from the first lateral edge 3 to the second lateral edge 4. The partially-circular profile ensures that there are little to no high stress points in the screw bit body 1, thus increasing the overall longevity of the tool. Referring to FIG. 13 and FIG. 14, in a separate embodiment of the present invention, the entire cross-section 9 of the engagement cavity 8 is a triangular profile. Additionally, the triangular profile is concave along a direction from the first lateral edge 3 to the second lateral edge 4. Alternative profiles may be used for the engagement cavity 8 including, but not limited to, a semi-square profile, a semi-rectangular profile, and a semi-oval profile.

[0014] In one embodiment of the present invention, referring to FIG. 8 and FIG. 9, the entire cross-section 9 of the engagement cavity 8 comprises a curved portion 10 and a straight portion 11. In this embodiment, the present invention is implemented as an extraction bit, wherein the present invention is designed to extract damaged or broken fasteners, damaged rods, broken studs, and other similar items. The engagement cavity 8 is uniquely shaped in order to form a sharp engagement tooth that grips in the corners of the socket fastener, allowing material from the internal sides of the fastener socket into the engagement cavity 8 and thus yielding a superior grip over traditional tools which are simply designed to push material away. This is especially true for worn or damaged fastener socket. More specifically, the curved portion 10 is a semi-circular curve that is positioned adjacent to the first lateral edge 3. The straight portion 11 is positioned adjacent to the curved portion 10, opposite the first lateral edge 3. The straight portion 11 guides a portion of the socket fastener to press against the engagement tooth. As such, the straight portion 11 extends from the curved portion 10 to the second lateral edge 4. Specifically, the straight portion 11 starts at the curved portion 10 and ends at the second lateral edge 4.

[0015] In another embodiment of the present invention, referring to FIG. 11, the engagement cavity 8 is centrally positioned on the bracing surface 5. In particular, the engagement cavity 8 is positioned offset from the second lateral edge 4 by a second distance 22. For central positioning, the first distance 21 is equal to the second distance 22, which is shown in FIG. 15. This positions the engagement cavity 8 to engage the internal lateral sidewall of the socket fastener and moves the torquing stresses to or away from the fastener lateral corners to enhance the gripping function and prevent fastener rounding for the most efficient transfer of torque with the least possibility of slippage. Additionally, this embodiment may be used to rotate the socket fastener in either the clockwise or the counter-clockwise direction.

[0016] In another embodiment of the present invention, the proportion between the first distance 21, the second distance 22, and the width of the engagement cavity 8 may be altered in order to achieve a dedicated clockwise or counterclockwise design. In one embodiment, the present invention is configured to be a clockwise drive bit. For this embodiment, the second distance 22 is great-

er than the first distance **21**. In particular, the proportion between the first distance **21**, the second distance **22**, and the width of the engagement cavity **8** is 1:5:4, thus yielding a design of the present invention which grips and applies torque to the socket fastener in the clockwise direction. This design is used to screw in and secure the socket fastener. In another embodiment, the present invention is configured to be a counter-clockwise screw bit. For this embodiment, the first distance **21** is greater than the second distance **22**. In particular, the proportion between the first distance **21**, the second distance **22**, and the width of the engagement cavity **8** is 5:1:4, thus yielding a design which grips and applies torque to the socket fastener in the counter-clockwise direction. This design is used to release and extract the socket fastener.

[0017] Referring to FIG. 5 and FIG. 10, the present invention may also be implemented in a spline/square/other-polygonal bit design. More specifically, if the screw bit body **1** was a spline-type bit body, then the spline-type bit body would be able to transfer torque to the socket fastener through a multitude of protrusions. Thus, the screw bit body **1** may further comprise a plurality of intermittent sidewalls **24**. Each of the plurality of intermittent sidewalls **24** is a flat surface which engages the socket fastener like a traditional screw bit design. The plurality of intermittent sidewalls **24** is radially positioned about the rotation axis **16**. Additionally, the plurality of intermittent sidewalls **24** is interspersed amongst the plurality of laterally-bracing sidewalls **2**. The ratio between the plurality of laterally-bracing sidewalls **2** and the plurality of intermittent sidewalls **24** is subject to change to yield a variety of different screw bit designs. In one embodiment, the plurality of intermittent sidewalls **24** and the plurality of laterally-bracing sidewalls **2** radially alternate between each other. In another embodiment, there are three sidewalls from the plurality of intermittent sidewalls **24** in between each of the plurality of laterally-bracing sidewalls **2**. Resultantly, this configuration places an engagement feature/tooth at every other protrusion of the screw bit body **1**.

[0018] In an exemplary embodiment, a first intermittent sidewall **28**, a second intermittent sidewall **29**, and a third intermittent sidewall **30** among the plurality of intermittent sidewalls **24** are interspersed on a corresponding laterally-bracing sidewall among the plurality of laterally-bracing sidewalls **2**, as represented in FIG. 10. The first intermittent sidewall **28**, second intermittent sidewall **29**, and third intermittent sidewall **30** enable effective connection with a fastener while providing the desired space that prevents mechanical wear and fatigue on parts. The first intermittent sidewall **28** and the second intermittent sidewall **29** are perpendicularly positioned to each other. This arrangement results in a 90-degree angle, which may be optimal for certain applications. The third intermittent sidewall **30** is located in between the at least one engagement cavity **8** of the corresponding laterally-bracing sidewall and the second intermittent sidewall **29**. Thus, the third intermittent sidewall **30** provides structural

support for the at least one engagement cavity **8** during preferred usage of the present invention.

[0019] In another embodiment, referring to FIG. 6, the present invention further comprises an engagement bore **20**. The engagement bore **20** allows the present invention to be attached to a male attachment member of an external torque tool, such as a socket wrench or a screw driver. The engagement bore **20** extends into the attachment body **19** along the rotation axis, opposite the screw bit body **1**. The engagement bore **20** is shaped to receive a male attachment member of a socket wrench; the preferred shape is square as the majority of socket wrenches utilize a square attachment member. In this embodiment, the preferred attachment body **19** is cylindrical shaped. In alternative embodiments, the shape and design of the engagement bore **20** and the attachment body **19** may vary to be adaptable to different torque tool designs and different attachment means.

[0020] In one embodiment, referring to FIG. 2, the present invention is implemented as a dual sided screw bit, thus providing both a clockwise and a counter-clockwise configuration simultaneously in a single tool. In this embodiment, the at least one screw bit body **1** comprises a first screw bit body **17** and a second screw bit body **18**. The attachment body **19** preferably has a hexagonal cross-section. The attachment body **19** is centrally positioned around and along the rotation axis **16** of the first screw bit body **17** such that the rotation axis of the attachment body **19** and the rotation axis **16** of the first screw bit body **17** are coincidentally aligned. Additionally, the attachment body **19** is connected adjacent to the second base **15** of the first screw bit body **17**. The second screw bit body **18** shares the attachment body **19** with the first screw bit body **17**. Thus, the second screw bit body **18** is concentrically positioned with the first screw bit body **17**. Additionally, the second screw bit body **18** is positioned adjacent to the attachment body **19**, opposite the first screw bit body **17**, similar to traditional double-sided screw bit designs. Similar to the first screw bit body **17**, the attachment body **19** is connected to the second base **15** of the second screw bit body **18**. The first screw bit body **17** is designed to screw in a socket fastener, the clockwise configuration. For this, referring to FIG. 3, the second distance **22** of the first screw bit body **17** is greater than the first distance **21** of the first screw bit body **17**. This positions the additional gripping point of the first screw bit body **17** adjacent to the first lateral edge **3** of the first screw bit body **17**. The second screw bit body **18** is designed to unscrew/extract the socket fastener, i.e. the counter-clockwise configuration. Referring to FIG. 4, the first distance **21** of the second screw bit body **18** is greater than the second distance **22** of the second screw bit body **18**. This positions the additional gripping point of the second screw bit body **18** adjacent to the second lateral edge **4** of the second screw bit body **18**.

[0021] In another embodiment of the present invention, referring to FIG. 5, the at least one engagement cavity **8**

comprises a first cavity **12** and a second cavity **13**. This embodiment is an alternative configuration which yields a clockwise and counter-clockwise configuration. In particular, the first cavity **12** and the second cavity **13** are oriented parallel and offset to each other. The first cavity **12** is positioned adjacent and offset to the first lateral edge **3** and the second cavity **13** is positioned adjacent and offset to the second lateral edge **4**. This allows the user to rotate the present invention either in the clockwise or counter-clockwise rotation without removing the present invention from the torque tool while still taking advantage of the additional gripping point(s). In this embodiment, it is preferred that the present invention further comprises the plurality of intermittent sidewalls **24**, wherein the plurality of intermittent sidewalls **24** is interspersed amongst the plurality of laterally-bracing sidewalls **2**. As a consequence of this embodiment, the triangular profile may be a plurality of triangular profiles arranged along the plurality of laterally-bracing sidewalls **2**. Such an embodiment enables enhanced adaptation to various high-stress uses of the present invention.

[0022] Referring to FIG. **7**, in an alternative embodiment, the present invention is implemented as a ball-end screw bit. In this embodiment, the bracing surface **5** for each of the plurality of laterally-bracing sidewalls **2** comprises a convex portion **6** and a concave portion **7**. The convex portion **6** and the concave portion **7** delineate a curved surface such that, overall, the plurality of laterally-bracing sidewalls **2** forms a ball-like shape. The convex portion **6** is positioned adjacent to the first base **14** such that the convex portion **6** from each of the plurality of laterally-bracing sidewalls **2** forms the body of the ball-like shape. The concave portion **7** is positioned adjacent to the convex portion **6**, opposite to the first base **14** such that the concave portion **7** from each of the plurality of laterally-bracing sidewalls **2** further forms the ball-like shape and provides clearance for when the screw bit body **1** is engaged to the socket fastener at an angle. The convex portion **6** and the concave portion **7** are oriented along the rotation axis **16** of the screw bit body **1**, and thus the length of the screw bit body **1**, to position the ball-like shaped terminally on the screw bit body **1**. It is preferred that the curvature, length, and height of the concave portion **7** and the convex portion **6** is identical. Additionally, it is preferred that the engagement cavity **8** extends along the whole length of the convex portion **6** and the concave portion **7**. Thus, additional gripping is provided along the screw bit body **1**, regardless of the angle between the socket fastener and the screw bit body **1**.

[0023] Referring to FIG. **10**, in one embodiment, the present invention is implemented as a tamper-resistant screw bit. In particular, the present invention further comprises a pin-in security hole **23** which interlocks with a complimentary post within a unique socket fastener. Thus, a set of unique socket fasteners and a unique-key screw bit may be sold, utilized, or manufactured to ensure tamper proof design. This type of interlocking design is

used for security reasons, preventing unauthorized personnel from accessing certain socket fasteners. The pin-in security hole **23** is concentrically positioned with the rotation axis **16** of the screw bit body **1**. Additionally, the pin-in security hole **23** extends into the screw bit body **1** from the first base **14**. The size, depth, and profile of the pin-in security is subject to change to meet the needs and specifications of the user.

[0024] In one embodiment, referring to FIG. **11**, the present invention includes additional features in order to guide the screw bit body **1** into the socket fastener. In particular, a lateral edge **25** between the first base **14** and each of the plurality of laterally-bracing sidewalls **2** is chamfered which aids the user in interlocking the screw bit body **1** within the socket fastener. Referring to FIG. **12**, in another embodiment, the present invention is implemented in a screwdriver design. In this embodiment, the screw bit body **1** is tapered from the second base **15** towards the first base **14**, similar to traditional screwdrivers. The degree of tapering is subject to change to meet the needs and requirements of the user.

[0025] In other embodiments, the present invention may be implemented in the form of a socket for tightening or loosening of bolts and other similar fasteners. For this, the screw bit body **1** is implemented as a cavity traversing into a cylinder, similar to traditional socket designs.

[0026] Although the invention has been explained in relation to its preferred embodiment, it is to be understood that many other possible modifications and variations can be made without departing from the spirit and scope of the invention as hereinafter claimed.

ORIGINAL PARENT CLAIMS FORMING PART OF THE DESCRIPTION AS PREFERRED EMBODIMENTS OF THE DIVISIONAL APPLICATION ONLY

[0027]

1. An advanced holding apparatus comprising:

- at least one screw bit body;
- an attachment body;
- the at least one screw bit body comprising a plurality of laterally-bracing sidewalls, a first base, and a second base;
- each of the plurality of laterally-bracing sidewalls comprising a first lateral edge, a second lateral edge, a bracing surface, and at least one engagement cavity;
- the plurality of laterally-bracing sidewalls being radially positioned about a rotation axis of the at least one screw bit body;
- the first lateral edge and the second lateral edge being positioned opposite to each other across the bracing surface;
- the at least one engagement cavity extending normal and into the bracing surface;
- the at least one engagement cavity extending

into the at least one screw bit body from the first base towards the second base;
the at least one engagement cavity being positioned offset from the first lateral edge by a first distance;
the at least one engagement cavity being positioned offset from the second lateral edge by a second distance;
an entire cross-section of the at least one engagement cavity being parallel to the first base and the second base;
the attachment body being centrally positioned around and along the rotation axis;
the attachment body being connected adjacent to the second base;
the entire cross-section of the at least one engagement cavity being a triangular profile; and
the triangular profile being concave along a direction from the first lateral edge to the second lateral edge.

2. The advanced holding apparatus as claimed in claim 1 comprising:

the triangular profile comprises a plurality of vertexes; and
each of the plurality of vertexes being a rounded corner.

3. The advanced holding apparatus as claimed in claim 1 comprising:

the triangular profile comprises a plurality of vertexes and a pair of elongated portions;
the pair of elongated portions being interspersed amongst the plurality of vertexes; and
each of the pair of elongated portions being a shape selected from the group consisting of: straight line, concave, and convex.

4. The advanced holding apparatus as claimed in claim 1 comprising:

the bracing surface comprises a first portion and a second portion;
the first portion being positioned along the first distance;
the second portion being positioned along the second distance;
the first portion being a shape selected from the group consisting of: concave and convex; and
the second portion being a shape selected from the group consisting of: straight line, concave, and convex.

5. The advanced holding apparatus as claimed in claim 1, wherein the first distance is equal to the second distance.

6. The advanced holding apparatus as claimed in claim 1, wherein the second distance is greater than the first distance.

7. The advanced holding apparatus as claimed in claim 1, wherein the first distance is greater than the second distance.

8. The advanced holding apparatus as claimed in claim 1 comprising:

the at least one screw bit body comprising a first screw bit body and a second screw bit body;
the attachment body being centrally positioned around and along the rotation axis of the first screw bit body;
the attachment body being connected adjacent to the second base of the first screw bit body;
the second screw bit body being concentrically positioned with the first screw bit body;
the second screw bit body being positioned adjacent to the attachment body, opposite the first screw bit body;
the attachment body being connected adjacent to the second base of the second screw bit body;
the first distance of the first screw bit body being greater than the second distance of the first screw bit body; and
the second distance of the second screw bit body being greater than the first distance of the second screw bit body.

9. The advanced holding apparatus as claimed in claim 1 comprising:

the bracing surface comprising a convex portion and a concave portion;
the convex portion being positioned adjacent to the first base;
the concave portion being positioned adjacent to the convex portion, opposite to the first base; and
the convex portion and the concave portion being oriented along the rotation axis of the at least one screw bit body.

10. The advanced holding apparatus as claimed in claim 1 comprising:

the at least one screw bit body further comprising a plurality of intermittent sidewalls;
the plurality of intermittent sidewalls being radially positioned about the rotation axis; and
the plurality of intermittent sidewalls being interspersed amongst the plurality of laterally-bracing sidewalls.

11. The advanced holding apparatus as claimed in claim 8 comprising:

a first intermittent sidewall, a second intermittent sidewall, and a third intermittent sidewall among the plurality of intermittent sidewalls being interspersed on a corresponding laterally-bracing sidewall among the plurality of laterally-bracing sidewalls;

the first intermittent sidewall and the second intermittent sidewall being perpendicularly positioned to each other; and

the third intermittent sidewall being located in between the at least one engagement cavity of the corresponding laterally-bracing sidewall and the second intermittent sidewall.

12. The advanced holding apparatus as claimed in claim 1, wherein a lateral edge between the first base and each of the plurality of laterally-bracing sidewalls is chamfered.

13. The advanced holding apparatus as claimed in claim 1, wherein the at least one screw bit body is tapered from the second base towards the first base.

14. The advanced holding apparatus as claimed in claim 1 comprising:

the first base comprising a first base surface; the first base surface and the bracing surface each being flat; and

the first base surface and the bracing surface being oriented perpendicular to each other.

15. The advanced holding apparatus as claimed in claim 1, wherein the at least one engagement cavity tapers from the first base to the second base such that the triangular profile adjacent to the first base is larger than the triangular profile adjacent to the second base.

16. The advanced holding apparatus as claimed in claim 1 comprising:

a pin-in security hole; the pin-in security hole being concentrically positioned with the rotation axis of the at least one screw bit body; and the pin-in security hole normally extending into the at least one screw bit body from the first base.

17. The advanced holding apparatus as claimed in claim 1 comprising:

an engagement bore; and the engagement bore extending into the attachment body along the rotation axis, opposite the at least one screw bit body.

18. The advanced holding apparatus as claimed in claim 1 comprising:

the at least one engagement cavity comprising a first cavity and a second cavity;

the first cavity and the second cavity being orientated parallel and offset to each other;

the first cavity being positioned adjacent to the first lateral edge; and the second cavity being positioned adjacent to the second lateral edge.

Claims

1. An advanced holding apparatus comprising:

at least one screw bit body (1);
an attachment body (19);
the at least one screw bit body (1) comprising a plurality of laterally-bracing sidewalls (2), a first base (14), and a second base (15);
each of the plurality of laterally-bracing sidewalls (2) comprising a first lateral edge (3), a second lateral edge (4), a bracing surface (5), and at least one engagement cavity (8);
the bracing surface (5) comprising a first portion (33) and a second portion (34);
the plurality of laterally-bracing sidewalls (2) being radially positioned about a rotation axis (16) of the at least one screw bit body (1);
the first lateral edge (3) and the second lateral edge (4) being positioned opposite to each other across the bracing surface (5);
the at least one engagement cavity (8) extending normal and into the bracing surface (5);
the at least one engagement cavity (8) extending into the at least one screw bit body (1) from the first base (14) towards the second base (15);
the at least one engagement cavity (8) being positioned offset from the first lateral edge (3) by a first distance (21);
the first portion (33) of the bracing surface (5) positioned along the first distance (21), adjacent to the first lateral edge (3);
the at least one engagement cavity (8) being positioned offset from the second lateral edge (4) by a second distance (22);
the second portion (34) of the bracing surface (5) positioned along the second distance (22), adjacent to the second lateral edge (4);
an entire cross-section (9) of the at least one engagement cavity (8) being parallel to the first base (14) and the second base (15);
the attachment body (19) being centrally positioned around and along the rotation axis (16); and
the attachment body (19) being connected adjacent to the second base (15);

characterized in that:

- the first portion (33) is flat along a direction from the first lateral edge (3) to the second lateral edge (4);
the second portion (34) is flat along a direction from the first lateral edge (3) to the second lateral edge (4);
the entire cross-section (9) of the at least one engagement cavity (8) is concave along a direction from the first lateral edge (3) to the second lateral edge (4); and
the at least one concave engagement cavity (8) is a triangular profile.
2. The advanced holding apparatus as claimed in claim 1 comprising:
- the at least one screw bit body (1) comprising a first screw bit body (17) and a second screw bit body (18);
the attachment body (19) being centrally positioned around and along the rotation axis (16) of the first screw bit body (1);
the attachment body (19) being connected adjacent to the second base (15) of the first screw bit body (17);
the second screw bit body (18) being concentrically positioned with the first screw bit body (17);
the second screw bit body (18) being positioned adjacent to the attachment body (19), opposite the first screw bit body (17);
the attachment body (19) being connected adjacent to the second base (15) of the second screw bit body (18);
the first distance (21) of the first screw bit body (17) being greater than the second distance (22) of the first screw bit body (17); and
the second distance (22) of the second screw bit body (18) being greater than the first distance (21) of the second screw bit body (18).
3. The advanced holding apparatus as claimed in claim 1 comprising:
- the first base (14) comprising a first base surface (26);
the first base surface (26) and the bracing surface (5) each being flat; and
the first base surface (26) and the bracing surface (5) being oriented perpendicular to each other.
4. The advanced holding apparatus as claimed in claim 2, wherein the at least one engagement cavity (8) tapers from the first base (14) to the second base (15) such that the triangular profile adjacent to the first base (14) is larger than the triangular profile adjacent to the second base (15).
5. The advanced holding apparatus as claimed in claim 1 comprising:
- a pin-in security hole (23);
the pin-in security hole (23) being concentrically positioned with the rotation axis (16) of the at least one screw bit body (1); and
the pin-in security hole (23) normally extending into the at least one screw bit body from the first base.
6. The advanced holding apparatus as claimed in claim 1 comprising:
- an engagement bore (20); and
the engagement bore (20) extending into the attachment body (19) along the rotation axis (16), opposite the at least one screw bit body (1).
7. The advanced holding apparatus as claimed in claim 1 comprising:
- the triangular profile comprises a plurality of vertexes (31) and a pair of elongated portions (32);
the pair of elongated portions (32) being interspersed amongst the plurality of vertexes (31); and
each of the pair of elongated portions (32) being a shape selected from the group consisting of: straight line, concave, and convex.
8. The advanced holding apparatus as claimed in claim 1 comprising:
- the triangular profile comprises a plurality of vertexes (31), at least one of the plurality of vertexes (31) being radial.
9. The advanced holding apparatus as claimed in claim 1, wherein the first distance (21) is equal to the second distance (22).




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17