

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2011238600 B2**

(54) Title
Air filtration device

(51) International Patent Classification(s)
B01D 46/00 (2006.01) **B01D 53/00** (2006.01)
A62B 7/10 (2006.01)

(21) Application No: **2011238600** (22) Date of Filing: **2011.03.30**

(87) WIPO No: **WO11/126887**

(30) Priority Data

(31) Number	(32) Date	(33) Country
61/321,352	2010.04.06	US

(43) Publication Date: **2011.10.13**

(44) Accepted Journal Date: **2013.05.09**

(71) Applicant(s)
3M Innovative Properties Company

(72) Inventor(s)
Ausen, David L.

(74) Agent / Attorney
Freehills Patent Attorneys, MLC Centre Martin Place, SYDNEY, NSW, 2000

(56) Related Art
US 2007/0044800
US 5283914

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 October 2011 (13.10.2011)

(10) International Publication Number
WO 2011/126887 A3

- (51) **International Patent Classification:**
B01D 46/00 (2006.01) *A62B 7/10* (2006.01)
B01D 53/00 (2006.01)
- (21) **International Application Number:**
PCT/US2011/030526
- (22) **International Filing Date:**
30 March 2011 (30.03.2011)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/321,352 6 April 2010 (06.04.2010) US
- (71) **Applicant (for all designated States except US):** **3M INNOVATIVE PROPERTIES COMPANY** [US/US]; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US).
- (72) **Inventor; and**
- (75) **Inventor/Applicant (for US only):** **AUSEN, David, L.** [US/US]; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US).
- (74) **Agents:** **OLOFSON, Jeffrey, M.** et al.; 3M Center, Office of Intellectual Property Counsel, 3M Center, Saint Paul, Minnesota 55133-3427 (US).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

[Continued on next page]

(54) **Title:** AIR FILTRATION DEVICE




FIG. 1B

(57) **Abstract:** Air filtering devices may be helmet-mounted or belt-mounted. The air filtering devices include a filtering device shell and a filtering unit. The filtering unit includes a contaminated-air inlet, a filter assembly in fluid communication with the contaminated-air inlet, a blower assembly in fluid communication with the filter assembly via a duct, and containing a filtered-air outlet, and a filtered-air passageway in fluid communication with the blower assembly outlet and leading to breathing headgear. The blower assembly is vibrationally isolated from the filtering device shell by being only attached to the filtering device shell by the duct. The duct includes an elastomeric material.

WO 2011/126887 A3



SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

— with international search report (Art. 21(3))

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(88) Date of publication of the international search report:

23 February 2012

AIR FILTRATION DEVICE

Field of the Disclosure

5 The present disclosure pertains to air filtration devices, especially powered air filtration devices.

Background

10 Supplied air respirators are regularly worn in environments where the surrounding air contains or may contain contaminants. Clean air is delivered to the wearer from a supply tank or from a powered air source that drives or draws ambient air through an air filter.

15 Systems that use a powered air source to supply clean air to the wearer are referred to as powered air purifying respirators, or "PAPRs". PAPRs may come in a variety of types, but two common types are belt pack PAPRs and helmet PAPRs. Belt pack PAPRs typically have two main parts: a facepiece and a filtering unit. The facepiece is worn at least over the nose and mouth of the user (it also may cover the eyes and ears), and the filtering unit is worn about the user's waist. Typically a hose connects the filtering unit to the facepiece. Helmet PAPRs typically include a pivotal visor as a facepiece and a filtering unit contained within or attached to the helmet.

20 In both types of PAPRs, the filtering unit often includes one or more filter cartridges, a housing, a fan, and an electric motor that drives the fan. The fan and motor are contained within the housing, and the filter cartridges are attached to the housing body. Ambient air is filtered by being drawn through filter elements that are contained within the filter cartridges. The electrically powered fan drives or draws the air through the filter cartridges, through the hose, and into the facepiece interior. Because the fan does the work required for air movement through the PAPR system, the user is able to comfortably receive a clean supply of air with little effort.

25 Each style of PAPR has advantages and disadvantages. The belt pack style can be easier for a user to wear because the weight of the filtering unit is carried on the waist and not the head. However, having a two piece system can be cumbersome and the connecting hose can interfere with the free movement of the user and also is at risk of becoming tangled, ruptured or even detached. The helmet style PAPR avoids these drawbacks by

being a single self-contained unit, but the weight of the filtering unit can be uncomfortable especially when worn for long periods of time.

Summary

5 The present disclosure is directed to a blower assembly that is isolated from a filtering device shell by being only attached to the filtering device shell by a duct. The duct comprises an elastomeric material.

10 Also disclosed herein are air filtering devices comprising a filtering device shell and a filtering unit, the filtering unit comprising a contaminated-air inlet, a filter assembly in fluid communication with the contaminated-air inlet, a blower assembly in fluid communication with the filter assembly via a duct, and the blower assembly also containing a filtered-air outlet, and a filtered-air passageway in fluid communication with the blower assembly outlet. The filter assembly comprises a filter member in fluid communication with the contaminated-air inlet, and the blower assembly is vibrationally isolated from the filtering device shell by being only attached to the filtering device shell by the duct. The duct comprises an elastomeric material.

15 The filtered-air outlet is in fluid communication with a breathing head piece. The air filtering device may be helmet-mounted or belt-mounted. In belt-mounted configurations the filtered-air outlet comprises a hose connecting the belt-mounted filtering portion to the breathing head piece portion.

Brief Description of the Drawings

20 The disclosure may be more completely understood in consideration of the following detailed description of various embodiments of the disclosure in connection with the accompanying drawings.

Figure 1A shows a rear perspective view of a helmet-mounted powered air purifying respirator of this disclosure.

25 Figure 1B shows a side view of a helmet-mounted powered air purifying respirator of this disclosure.

Figure 2 shows a cut away view of a blower assembly and duct of this disclosure.

Figure 3 shows an exploded view of a blower assembly and duct of this disclosure.

2011238600 16 Oct 2012

Figure 4 shows schematically a perspective view of an exemplary embodiment of a powered air purifying respirator of this disclosure.

Figure 5 shows a perspective view of the belt pack filtering unit portion of a powered air purifying respirator of this disclosure.

In the following description of the illustrated embodiments, reference is made to the accompanying drawings, in which is shown by way of illustration, various embodiments in which the disclosure may be practiced. It is to be understood that the embodiments may be utilized and structural changes may be made without departing from the scope of the present invention. The figures are not necessarily to scale. Like numbers used in the figures refer to like components. However, it will be understood that the use of a number to refer to a component in a given figure is not intended to limit the component in another figure labeled with the same number.

Detailed Description

The present disclosure provides a powered, portable air filtering device for a powered air purifying respirator or PAPR. The PAPR may be helmet-mounted or belt-mounted. When helmet-mounted, the PAPR is located within the helmet, when belt-mounted the PAPR is located in a belt pack and connected to breathing headgear by a device such as a hose. Air filtering devices are regularly used in environments where the surrounding air contains contaminants or may potentially contain contaminants. Such contaminants include, for example, fumes, gases, particulates, vapors and the like which may be present alone or in combination.

Each style of PAPR has advantages and disadvantages. A common drawback to each, however, is that the motion of the blower can cause vibrations within the filtering device. The vibrations can manifest as physical vibrations as well as sound vibrations. These vibrations can be transmitted to the wearer causing annoyance and discomfort. The PAPRs of the present disclosure are designed to decrease or even eliminate the vibrations caused by the blower by the design and materials choice for the duct connecting the filter assembly to the blower. The duct is designed in such a way that the blower assembly is attached to the helmet only via a duct, with the duct comprising an elastomeric material.

As used herein, the term "powered air purifying respirator or PAPR" means a supplied air respirator that uses a power source to deliver filtered air to breathing headgear.

As used herein, the terms "filtered air" and "filtered-air" means air (or other oxygen-containing gas) that has been filtered. Typically, "filtered-air" is hyphenated

when used as an adjective to describe an assembly such as, for example, a “filtered-air chamber” but when used as a noun, “filtered air” is not hyphenated.

As used herein the terms “contaminated air” and “contaminated-air” mean air (or other oxygen-containing gas) that has not filtered and may contain one or more contaminants. Typically, “contaminated-air” is hyphenated when used as an adjective to describe an assembly such as, for example, a “contaminated-air inlet” but when used as a noun, “contaminated air” is not hyphenated.

As used herein, the term "breathing head gear" means an apparatus to which purified air is supplied that is worn by a person, such breathing head gear includes for example facepieces which fit snugly over at least the respiratory passages (nose and mouth) of a person, as well as loose fitting facepieces such as, for example, face shield assemblies hingeably attached to and depending from the front of a helmet.

As used herein, the term "filter bed" means a structure that includes a filter element and that is adapted for connection to or use in a filtering unit, a “curved filter bed” is one that is not planar but has a radius of curvature; generally the curved filter bed is continuous over the length of curvature, i.e. it is not subdivided along the length of curvature into different filter modules; typically the filter bed includes adsorbent particles.

As used herein, the term "filter cartridge" means a structure that includes a filter element and that is adapted for connection to or use in a filtering unit, a “curved filter cartridge” is one that is not planar but has a radius of curvature.

As used herein, the term "filtering unit" means the portion of a PAPR that is responsible for filtering ambient air and causing powered air movement.

As used herein the term "hose" means a device that includes a conduit that has fluid impermeable wall(s) through which air can travel for delivering clean air from a clean air supply source to breathing headgear;

As used herein the term "powered air purifying respirator or PAPR" means a supplied air respirator that uses a power source to deliver filtered air to breathing headgear.

Figures 1A and 1B show side views of a helmet mounted PAPR **100**. In Figure 1A, PAPR **100** comprises a motorized system, in which contaminated air enters the PAPR through contaminated air inlet **10**, passes through the filter assembly **20**, enters blower assembly **25** and exits blower assembly **25** by filtered-air outlet **30**. Filtered air outlet **30**

is in fluid communication with face shield assembly **40** via channel **35**. As shown in further detail in Figure 1B, contaminated air inlet **10** is in fluid communication with filter assembly **20** via fluid communication passageway **15** which may be a chamber or a channel. Filter assembly **20** comprises filter member **21** which is in fluid communication with blower assembly **25** via fluid communication passageway **22** and duct **23**. Duct **23** not only connects blower assembly **25** to fluid communication passageway **22**, it also attaches the blower assembly to the filtering device. The contaminated air enters the filter member **21** via filter inlet **21a** and filtered-air leaves the filter member **21** via filter outlet **21b**. Upon leaving the filter member **21**, the filtered air passes through fluid communication passageway **22** and enters blower assembly **25** via duct **23**. Upon leaving the blower assembly **25**, the filtered-air passes through filtered-air outlet **30**.

Contaminated air inlet **10** may be a simple orifice or series of orifices or it may be a more complex apparatus such as, for example, it may contain a pre-filter or screen to reduce the flow of particulates into the PAPR. Examples of pre-filters include, for example, fibrous webs, meshes, foams, nonwoven fabrics and the like. The pre-filters may be removable so that they can be removed and cleaned or replaced. Examples of suitable screens include, for example, metal or plastic grids which may be permanently affixed to the inlet or may be removable.

Filter assembly **20** comprises filter member **21**. Filter member **21** can include a housing for the filter member, or the filter member may be a stand alone member. Filter member **21** can be constructed from a variety of materials and can target a variety of substances. For example, filter member **21** can include a traditional filter bed, a pleated medium, or any other type of filtering medium or combination of media. The filter medium can include a particulate filtering medium, a chemical filtering medium, or any combination of the two. A chemical filtering medium may include one or more of a sorbent, a catalyst or a chemically reactive medium and may target gases such as ammonia, methylamine, formaldehyde, chlorine, hydrogen chloride, sulfur dioxide, acidic gases, organic vapors or any other desired gas or contaminant. The contaminated air enters the filter member **21** via filter inlet **21a** and filtered air leaves the filter member **21** via filter outlet **21b**. Filter inlet **21a** and filter outlet **21b** may simply comprise surfaces of filter member **21**, or they may be orifices in the housing for the filter member, if filter member **21** is contained within a housing.

Blower assembly **25** and duct **23** that connects blower assembly **25** to the filtering device as well as providing fluid communication for the filtered air to enter the blower assembly, are illustrated in further detail in Figures 2 and 3. The inlet of blower assembly **25** (not shown) is attached to duct **23**. The blower assembly typically also comprises a blower fan and a motor. The blower motor drives the blower fan which causes the air to flow through the PAPR. Typically, the blower motor is a DC motor. Typically, the power source for the blower motor comprises batteries, either rechargeable or non-rechargeable.

From blower assembly **25**, the filtered air passes through filtered-air outlet **30**. Filtered-air outlet **30** is in fluid communication with face shield assembly **40**. The face shield assembly **40** is adapted to be positioned in the front of the helmet. In some embodiments, the face shield assembly **40** is pivotally attached to and depending from the front of the helmet. Filtered-air outlet **30** may be in fluid communication with a channel, a plurality of channels or it may simply be an orifice leading to the inside portion of the helmet. In Figures 1A and 1B, filtered-air outlet **30** leads to a channel **35** (not shown) that is in fluid communication with face shield assembly **40**.

As described previously, duct **23** not only connects blower assembly **25** to fluid communication passageway **22**, it also is the sole support mechanism for blower assembly **25**. Because duct **23** contains or is fashioned from an elastomeric material, any vibrations generated by blower assembly **25** are dampened and not passed along to the filtering device.

A wide range of elastomeric materials may be used to prepare duct **23**. For example, thermoplastic elastomers (TPEs), thermoplastic vulcanizates (TPVs), silicones, and natural rubbers, synthetic rubbers or combinations thereof are suitable. The material selection for the duct is generally made to optimize the balance between vibration dampening and structural strength. Materials with a high dampening coefficient are typically very soft and flexible, however, materials suitable for preparing duct **23** also should be rigid enough to support the blower assembly. Specific material properties useful to evaluate potential material candidates may include dampening coefficient, modulus of elasticity, creep rates, and compression set.

Figure 2 shows a cut away view of blower assembly **25** and duct **23**, including filtered-air outlet **30**. Filtered air enters blower assembly **25** from duct **23**, and exits via filtered-air outlet **30**. Duct **23** is in fluid communication with fluid communication

passageway **22** (not shown). Duct **23** may be connected to blower assembly **25** by one or more of a variety of different attachment systems, such as mechanical interlocking, pins, screws, snaps, adhesive bonding and the like. In this instance, duct **23** is attached to blower assembly **25** by barbed pins **24**. Similarly, duct **23** may be connected to the filtering device by one or more of a variety of different attachment systems, such as mechanical interlocking, pins, screws, snaps, adhesive bonding and the like. In this instance, duct **23** is connected to the filtering device by barbed pins **24**.

Figure 3 shows an exploded view of a blower assembly **25** and duct **23**. Duct **23** is attached to blower assembly **25** at duct outlet **23a** and attached to blower assembly **25** by barbed pins **24**. Duct outlet **23a** is configured to attach to and provide a seal with blower assembly **25**.

While a helmet-mounted PAPR **100** is shown in Figure 1, other types of PAPRs, for example, belt mounted designs, can be used in accordance with the present disclosure. A belt mounted PAPR is shown in Figure 4. The belt mounted PAPR comprises a belt portion **200** that contains the filter and blower assemblies, and breathing head gear **300** which is attached to the belt portion **200** via hose **310**. Hose **310** is attached to filtered-air outlet **210**.

Figure 5 shows an expanded view of the belt portion **200** of Figure 4. The same assemblage of components described for helmet respirator **100** of Figures 1A and 1B are present, namely, the contaminated air inlet, filter assembly, blower assembly (not shown) and filtered-air outlet **210**. The blower assembly is held in the belt pack by a duct similar to the blower assembly and duct of Figures 2 and 3.

25

What is claimed is:

1. An air filtering device comprising:

5 a filtering device shell and a blower that is vibrationally isolated from the shell by being attached to the shell by only a duct, wherein the duct comprises an elastomeric material.

2. The air filtering device of claim 1, wherein the blower further comprises a filtering unit encompassing the blower, the filtering unit comprising:

a contaminated-air inlet;

10 a filter assembly in fluid communication with the contaminated-air inlet;

a blower assembly in fluid communication with the filter assembly via a duct, the blower assembly also comprising a filtered-air outlet; and

a filtered-air passageway in fluid communication with the blower assembly filtered-air outlet; wherein the filter assembly comprises a filter member in fluid communication

15 with

the contaminated-air inlet.

3. The air filtering device of claim 1, wherein the filtering device shell comprises a belt pack.

20

4. The air filtering device of claim 2, wherein the filtering device shell comprises a belt pack and wherein the filtered-air outlet of the belt pack is in fluid communication with breathing head gear.

25 5. The air filtering device of claim 1, wherein the filtering device shell comprises a helmet.

6. The air filtering device of claim 2, wherein the filtering device shell comprises a helmet and wherein the filtered-air passageway of the helmet is in fluid communication with a
30 face shield assembly adapted to be positioned in the front of the helmet.

7. The air filtering device of claim 2, wherein the filter member comprises a removable filter cartridge.
8. The air filtering device of claim 7, wherein the removable filter cartridge comprises a filter cartridge case and a filter web or a filter bed.
9. The air filtering device of claim 7, wherein the removable filter cartridge comprises a filter web or a filter bed.
10. The air filtering device of claim 1, wherein the elastomeric material of the duct comprises, a thermoplastic elastomer (TPE), thermoplastic vulcanizate (TPV), silicone, and natural rubber, synthetic rubber or combination thereof.
11. The air filtering device of claim 1, wherein the elastomeric material of the duct comprises a vibration damping material.
12. The air filtering device of claim 11, wherein the vibration damping material has a vibration damping property determined by dampening coefficient, modulus of elasticity, creep rate, or compression set.
13. The air filtering device of claim 2, wherein the blower assembly further comprises a motor and a fan.
14. A method of making a powered air respirator comprising:
providing a helmet;
providing a filtering device; and
attaching the filtering device within the helmet to form a powered air purifying respirator, the filtering device comprising:
a filtering device shell and a filtering unit, the filtering unit comprising:
a contaminated-air inlet;
a filter assembly in fluid communication with the contaminated-air inlet;

a blower assembly in fluid communication with the filter assembly via a duct,

the blower assembly also comprising a filtered-air outlet; and a filtered-air passageway in fluid communication with the blower

5 assembly

filtered-air outlet; wherein the filter assembly comprises:

a filter member in fluid communication with the

contaminated-

air inlet; and wherein the blower assembly is vibrationally isolated from the filtering device shell by being only

10

attached to

the filtering device shell by the duct, wherein the duct comprises

an elastomeric material.

15

15. A method of making a powered air respirator comprising:

providing breathing head gear;

providing a filtering device; and

attaching the filtering device to the breathing head gear by a hose attached to

20

the breathing head gear and to the filtering device to form a powered air purifying respirator, the filtering device comprising:

a filtering device shell and a filtering unit, the filtering unit comprising:

a contaminated-air inlet;

a filter assembly in fluid communication with the contaminated-air inlet;

25

a blower assembly in fluid communication with the filter assembly via a

duct,

the blower assembly also comprising a filtered-air outlet; and

a filtered-air passageway in fluid communication with the blower

assembly

30

filtered-air outlet; wherein the filter assembly comprises:

a filter member in fluid communication with the

contaminated-

air inlet; and

wherein the blower assembly is vibrationally isolated from the filtering device shell by being only attached to the filtering device shell by the duct, wherein the duct comprises an elastomeric material.

- 5 16. The method of claim 15, wherein the filtering device shell comprises a belt pack.
17. An air filtering device substantially as herein described with reference to the accompanying drawings.
18. A method of making a powered air respirator substantially as herein described with reference to the accompanying drawings.




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5