



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2437227 C 2007/12/18

(11)(21) **2 437 227**

(12) **BREVET CANADIEN
CANADIAN PATENT**

(13) **C**

(86) Date de dépôt PCT/PCT Filing Date: 2000/02/04
(87) Date publication PCT/PCT Publication Date: 2001/08/09
(45) Date de délivrance/Issue Date: 2007/12/18
(85) Entrée phase nationale/National Entry: 2003/08/01
(86) N° demande PCT/PCT Application No.: US 2000/002907
(87) N° publication PCT/PCT Publication No.: 2001/056621

(51) Cl.Int./Int.Cl. *A61L 9/12* (2006.01),
B01D 39/14 (2006.01), *B01J 20/02* (2006.01),
C01B 31/08 (2006.01), *F25D 17/06* (2006.01)
(72) Inventeurs/Inventors:
STIROS, PAUL, US;
KVIETOK, FRANK ANDREJ, US
(73) Propriétaire/Owner:
THE PROCTER & GAMBLE COMPANY, US
(74) Agent: DIMOCK STRATTON LLP

(54) Titre : DISPOSITIF DESODORISANT D'AIR A CARTOUCHE AMOVIBLE
(54) Title: AIR DEODORIZATION DEVICE WITH A DETACHABLE CARTRIDGE

(57) **Abrégé/Abstract:**

The present invention relates to air deodorizing devices for removing malodor from the air. Such devices are useful for example for storing and preserving food in closed compartments such as refrigerators. The air deodorizing device of the present invention comprises a cartridge member and an air moving member whereby the cartridge member is detachable from the device.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
9 August 2001 (09.08.2001)

PCT

(10) International Publication Number
WO 01/56621 A1

(51) International Patent Classification⁷: A61L 9/014, 9/12

(21) International Application Number: PCT/US00/02907

(22) International Filing Date: 4 February 2000 (04.02.2000)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): **THE PROCTER & GAMBLE COMPANY** [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **STIROS, Paul** [US/US]; 9230 Deercross Parkway 2D, Cincinnati, OH 45236 (US). **KVIETOK, Frank, Andrej** [US/US]; 1103 Richwood Avenue, Cincinnati, OH 45208 (US).

(74) Agents: **REED, David, T.** et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217-1087 (US).

(81) Designated States (*national*): AE, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AIR DEODORIZATION DEVICE WITH A DETACHABLE CARTRIDGE

(57) Abstract: The present invention relates to air deodorizing devices for removing malodor from the air. Such devices are useful for example for storing and preserving food in closed compartments such as refrigerators. The air deodorizing device of the present invention comprises a cartridge member and an air moving member whereby the cartridge member is detachable from the device.



WO 01/56621 A1

AIR DEODORIZATION DEVICE WITH A DETACHABLE CARTRIDGE

Air deodorization device having a detachable cartridge member**Field of the invention**

The present invention relates to air deodorizing devices for removing malodor from the air. Such devices are useful for example for storing and preserving food in closed compartments such as refrigerators.

Background

Nowadays, refrigerators have become a common appliance in virtually every household and typically are used for storage and preservation of food, in particular of fresh food such as fruits, vegetables, dairy products, and the like. It is desirable to keep the food items fresh as long as possible in the refrigerator.

It is a well known problem that many food items tend to release malodors into the air which are then captured in the limited air space in a refrigerator. Not only are these malodors unpleasant and offensive to the user of the refrigerator, they can also have a negative impact on the quality of other foods in the refrigerator. For example, it is known that some foods emit strong odors (e.g. fish, boiled eggs, onions, etc.) and that these odors can transfer to other nearby foods and hurt the taste and freshness of those foods. A common example is transfer of odors into an open container of orange juice or of milk resulting in a noticeable degradation in their taste. It is also well known that malodors from some vegetables (onions, garlic) can transfer to other foods stored within a vegetable drawer. This problem

is aggravated when the vegetable drawer is sealed such that there is very little air exchange with the larger compartment of the refrigerator (herein referred to as the "fresh food compartment") and when vegetables have been cut or are stored without any outer wrapping. This problem of odor transfer is particularly acute in the case of ice cubes where odors from the fresh food compartment of the refrigerator can be transferred to the ice in the freezer compartment of the refrigerator. This is especially true in the case of refrigerators in which there is air exchange between the fresh food and freezer compartments, and especially in the case of refrigerators with built-in ice-makers.

U.S. patent No. 5,403,548 discloses an activated carbon absorbent to be used for example in refrigerators, shoe boxes, closets, toilets, cars, cupboard, or the like. The activated carbon absorbent is applied in a gas treating apparatus comprising an air inlet, an air outlet, a cylinder housing the activated carbon honeycomb, and a fan aspirating malodor through the air inlet. Change of battery and withdrawal of the cylinder housing the activated carbon are achieved by dismounting the cover of the apparatus. The gas treating apparatus may further comprise an action member for alerting the user to the event that the useful life of the activated carbon adsorbent has run out. This gas treating apparatus has the disadvantages that exchange of batteries and withdrawal of the activated carbon require a multitude of steps including dismounting of the cover and that exchange of battery and activated carbon are carried out separate from each other.

It is therefore an object of the present invention to provide an air deodorizing device which overcomes the disadvantages of the prior art devices.

It is a further object of the present invention to provide an air deodorizing device comprising a replaceable cartridge member housing a filter member whereby the cartridge member is directly accessible from the outside.

It is a further object of the present invention to provide an air deodorizing device comprising a cartridge member housing a replaceable filter member whereby the cartridge member is directly accessible from the outside.

It is a further object of the present invention to provide an air deodorizing device comprising a replacement cartridge member housing a power supply and a filter member.

It is a further object of the present invention to provide an air deodorizing device having a replaceable power supply and a replaceable filter member, the lifetimes of the power supply and the filter member being of the same magnitude.

Summary of the invention

The present invention provides an air deodorizing device comprising a cartridge member, the air deodorizing device having an air flow path from an air inlet to an air outlet. The cartridge member comprises a filter member and is arranged with the filter element in interaction with the air flowing along the air flow path. The air deodorizing device further comprises an air moving member for moving air along the air flow path, and is characterized in that the cartridge member is detachable from the air deodorizing device.

Detailed description of the invention

The device of the present invention is intended to deodorize air, in particular air in confined compartments such as refrigerators, trash bins, cars, closets, and the like.

The cartridge member of the present invention housing the filter member is detachable from the device. The term "detachable" as used herein refers to members which can be easily removed, in particular where no tools such as

screw drivers are needed. Preferably, no excessive forces are need for detaching the cartridge means, the cartridge means is directly accessible from the outside, and the cartridge member can be removed by holding the device of the present invention in one hand and by removing the cartridge member with the other hand.

Deodorization of the air in the device of the present invention is achieved by adsorbing the molecules constituting a malodor onto a surface of a filter member. The term "adsorption" is well defined in the art and refers to the adherence of molecules to surfaces which effectively reduces the mobility of these molecules to the two dimensions of the surface. Those molecules remaining in the air will then diffuse so that further molecules come into contact with the surface and subsequently will be adsorbed. Consequently, most of the malodor molecules will travel into the proximity of one of the surfaces at some point in time so that finally most of the malodor will be removed from the air.

A suitable filter member comprises activated carbon for the adsorption. Activated carbon is known to be a very effective filter medium due to its high specific surface area. Whilst activated carbon is very effective as such, the filter member of the present invention may further comprise agents supported on the activated carbon to specifically attack certain malodors such as those comprising S atoms or N atoms. A wide variety of activated carbon based filter media is known in the art. Preferably, the filter members of the present invention comprise at least 2 grams, more preferably at least 5 grams, and most preferably at least 10 grams of activated carbon. Preferably, the filter members of the present invention comprise less than 100 grams, more preferably less than 50 grams, yet more preferably less than 40 grams, and most preferably less than 30 grams of activated carbon.

The filter member of the present invention comprises an air inlet, an air outlet, and an air flow path through the filter member from the air inlet to the air outlet. The filter medium is disposed in the filter member of the present invention such

that it comes into contact with the air flowing along the air flow path. The filter medium may be arranged as a flow by filter or as a flow through filter. The filter member of the present invention may comprise a support for the filter medium for example in the form of a foam, a nonwoven material or a woven material. Preferably, the activated carbon is supported on a polyurethane foam having an activated carbon density of at least 0.01 grams per cm³, more preferably of at least 0.05 grams per cm³, and most preferably of at least 0.1 grams per cm³ and having an activated carbon density of less than 0.3 grams per cm³.

The deodorization of the air in the device of the present invention is enhanced by increasing the air flow through the filter member by means of an air moving member. Preferably, the air moving means moves at least 100 ml of air per second through the air inlet into the device, more preferably at least 200 ml/s, most preferably at least 300ml/s. There are known in the art a wide variety of suitable air moving members such as for example fans and blowers. A particularly suitable fan is a centrifugal fan. A suitable member for driving the fan is a small motor, for example a DC motor available from MABUCHI MOTOR CO.,LTD., Japan, under the designation of RF-330TK. The air moving members of the present invention may be powered electrically. Many electrical power sources could be imagined including domestic AC electrical power or power from a static power supply. Alternatively and preferably electrical power may be supplied by means of a battery, preferably a dry alkaline cell battery, or a rechargeable battery. The electrical power may also be received from a solar cell. Any replaceable power supply preferably is designed to last at least one month, more preferably at least two months, yet more preferably at least three months, most preferably at least four months.

To improve the malodor removal performance and to simplify the mechanical construction of the air deodorizing device of the present invention, the filter member and the air moving member are preferably arranged such that substantially all air aspired by the air moving member is forced to flow through the filter member before it penetrates the air inlet of the air moving member. In

other words, the air inlet of the cartridge member is unitary with the air inlet of the air deodorizing device. In this setup, only one air path connection is needed between the filter member and the air member and hence complexity is decreased. Furthermore, withdrawal of the cartridge member is greatly simplified if only one connection has to be disengaged. Any disengageable air flow connection may of course comprise sealing members to improve air flow performance. Any such connection may further comprise a mechanical engaging members to stabilize the connection.

The filter member of the present invention may be replaced by detaching the cartridge member from the device of the present invention and inserting in a new one. It is to be understood in this context that the present invention includes embodiments in which the cartridge member as a whole comprising a filter member is replaced and further includes embodiments in which the cartridge is reused and contains a replaceable filter element.

Preferably, the cartridge member of the present invention is directly accessible from the outside of the device without the need to unmount any covers or the like. More preferably, the cartridge member can simply be lifted off from the device. For example, the cartridge member may simply be sitting on top of the air moving member only held in place by gravitational forces whereby the surface topology of the interfacing parts of the cartridge member and the air moving member match each other such as in a hemispherical design.

Optionally, the cartridge member of the present invention may further comprise the power supply for the air moving member. In this case, the interface between the cartridge member and the air moving member needs to comprise electrical contacts connecting the power supply with the drive member of the air moving member. In this context, it is to be understood, that the

Preferably, the lifetime of the filter member and the lifetime of the power supply are substantially equal so that both members may be replaced at the same time

intervals. In this case, an empty power supply would also signal that the filter element has to be replaced.

The air deodorizing device of the present invention may comprise a signal member to indicate if the life span of the filter member has run out. The signal member may be slaved to the time the filter member has been exposed to air or may be slaved to the overall runtime of the air moving member. In case the power supply for the air moving member is included in the filter member and accordingly is replaced with the filter member, the signal member may be slaved to the remaining charge of the power supply thus indicating that filter member and power supply needs to be replaced.

Claims:

1. An air deodorizing device having an air flow path from an air inlet to an air outlet, said deodorizing device comprising:
 - a) a cartridge member detachable from a portion of said deodorizing device, said cartridge member comprising a filter member having an air inlet and an air outlet, wherein said cartridge member is adapted to be arranged with respect to said portion of said deodorizing device such that said filter member comes into contact with the air flowing along said air flow path of said deodorizing device; and
 - b) an air moving member for moving air along said air flow path, said air moving member comprising a fan connected to an electric motor wherein said electric motor is powered by a source of electricity and wherein said air moving member is adapted to displace at least 100 ml of air per second through the air inlet of said deodorizing device, and wherein said cartridge member is adapted to be positioned above said air moving member when said air moving member moves air along said air flow path and wherein a surface topology of parts of said cartridge member and said air moving member match each other.
2. A refrigerator air deodorizing device according to claim 1.
3. The air deodorizing device according to claim 1 wherein said cartridge member is directly accessible from the outside of said deodorizing device.
4. The air deodorizing device according to claim 1 wherein said filter member comprises activated carbon.
5. The air deodorizing device according to claim 4 wherein said activated carbon is supported on a support member, said support member comprising a foam, a woven, or a nonwoven web material.

6. The air deodorizing device according to claim 5 wherein said activated carbon is supported on a polyurethane foam and has a carbon density of from 0.01 to 0.3 grams per cm³.

7. The air deodorizing device according to claim 4 wherein said filter member comprises between 5 and 30 grams of activated carbon.

8. The air deodorizing device of claim 1 wherein said cartridge member is adapted only to be held in place with respect to said air moving member by gravitational forces.

9. The air deodorizing device of claim 1 wherein said surface topology comprises a hemispherical design.

10. The air deodorizing device according to claim 1, said air moving member being powered by a replaceable power supply wherein said cartridge member comprises said replaceable power supply.

11. An air deodorizing device having an air flow path from an air inlet to an air outlet, said deodorizing device comprising:

a) a cartridge member detachable from a portion of said deodorizing device, said cartridge member comprising a filter member having an air inlet and an air outlet, said cartridge member being arranged within an area of said deodorizing device such that said filter member comes into contact with the air flowing along said air flow path of said deodorizing device; and

b) an air moving member for moving air along said air flow path, said air moving member comprising a fan connected to an electric motor wherein said electric motor is powered by a source of electricity and wherein said air moving member is adapted to displace at least 100 ml of air per second through the air inlet of said deodorizing device and wherein a surface topology of parts of said cartridge member and said air moving member match each other.

12. The air deodorizing device of claim 11 wherein said surface topology comprises a hemispherical design.

13. The air deodorizing device according to claim 11 wherein said source of electricity is a battery, wherein said battery is located within said cartridge member and wherein said battery and said filter member have substantially equal lifetimes.

14. The air deodorizing device according to claim 11 wherein said filter member is located between the air inlet of said deodorizing device and said air moving member such that substantially all the air aspired by said air moving member is forced to flow through said filter member along said air flow path.

15. The air deodorizing device of claim 11, wherein only a single air path connection exists between the said filter member and said air moving member wherein substantially all air aspired by said air moving member is forced to flow through said filter member before it penetrates an inlet of said air moving member.

16. The air deodorizing device of claim 11, wherein said air inlet of said cartridge member is unitary with said air inlet of said air deodorizing device wherein substantially all air aspired by said air moving member is forced so flow through said filter member before it penetrates an inlet of said air moving member.

17. An air deodorizing device having an air flow path from an air inlet to an air outlet, said deodorizing device comprising:

a) a cartridge member detachable from a portion of said deodorizing device, said cartridge member comprising a filter member having an air inlet and an air outlet, wherein said cartridge member is adapted to be arranged with respect to said portion of said deodorizing device such that said filter member comes into contact with the air flowing along said air flow path of said deodorizing device; and

b) an air moving member for moving air along said air flow path, said air moving member comprising a fan connected to an electric motor wherein said electric motor is powered by a source of electricity and wherein said air moving member is adapted to displace at least 100 ml of air per second through the air inlet of said deodorizing device, wherein interfacing parts of said cartridge member and said air moving member include a hemispherical surface topology that match each other and wherein the cartridge member is adapted to rest above the air moving member such that the cartridge member is only held in place by gravitational forces.

18. The air deodorizing device according to claim 17 wherein said cartridge member is directly accessible from the outside of said deodorizing device.

19. The air deodorizing device according to claim 17 wherein said filter member comprises activated carbon.

20. The air deodorizing device according to claim 19 wherein said activated carbon is supported on a support member, said support member comprising a foam, a woven, or a nonwoven web material.

21. The air deodorizing device according to claim 20 wherein said activated carbon is supported on a polyurethane foam and has a carbon density of from 0.01 to 0.3 grams per cm³.

22. The air deodorizing device according to claim 17 wherein said filter member comprises between 5 and 30 grams of activated carbon.