



US011678901B2

(12) **United States Patent**  
**Scoggins et al.**

(10) **Patent No.:** **US 11,678,901 B2**

(45) **Date of Patent:** **Jun. 20, 2023**

(54) **VESSEL SENSING FOR ADAPTIVE  
ADVANCED HEMOSTASIS**

(58) **Field of Classification Search**

CPC ..... A61B 17/320068; A61B 17/00234; A61B  
17/22012; A61B 17/320092;

(Continued)

(71) Applicant: **Cilag GmbH International**, Zug (CH)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,853,416 A 4/1932 Hall  
2,222,125 A 11/1940 Stehlik

(Continued)

(72) Inventors: **Patrick J. Scoggins**, Loveland, OH  
(US); **Madeleine C. Jayme**, Cincinnati,  
OH (US); **Kristen G. Denzinger**,  
Cincinnati, OH (US); **Cameron R.  
Nott**, Fairfield, OH (US); **Craig N.  
Faller**, Batavia, OH (US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Cilag GmbH International**, Zug (CH)

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 1042 days.

AU 2015201140 A1 3/2015  
CA 2795323 A1 5/2014

(Continued)

(21) Appl. No.: **16/144,434**

OTHER PUBLICATIONS

(22) Filed: **Sep. 27, 2018**

US 10,504,709, 08/2018, Karancsi et al. (withdrawn).

(Continued)

(65) **Prior Publication Data**

US 2019/0274711 A1 Sep. 12, 2019

*Primary Examiner* — Daniel W Fowler

*Assistant Examiner* — Annie L Shoulders

(57) **ABSTRACT**

**Related U.S. Application Data**

(60) Provisional application No. 62/640,415, filed on Mar.  
8, 2018, provisional application No. 62/640,417, filed  
on Mar. 8, 2018.

An ultrasonic device may include an electromechanical  
ultrasonic system that includes an ultrasonic transducer  
coupled to an ultrasonic blade. A method of delivering  
energy to the ultrasonic device may include sensing a vessel  
type in contact with the blade, determining that the vessel  
type is either a vein or an artery, and delivering power to the  
transducer based on the vessel type. Power may be applied  
to the transducer at a power level P that differs from a  
nominal power level P<sub>n</sub> for a period T that differs from a  
nominal period T<sub>n</sub> based on the vessel. The power level P  
may be lower than P<sub>n</sub> for a period T that is longer than T<sub>n</sub>  
when the vessel is a vein. Alternatively, the power level P may  
be greater than P<sub>n</sub> for a period T that is shorter than T<sub>n</sub> when  
the vessel is an artery.

(51) **Int. Cl.**

**A61B 17/32** (2006.01)

**A61B 18/12** (2006.01)


(Continued)

(52) **U.S. Cl.**

CPC ..... **A61B 17/320068** (2013.01); **A61B  
17/00234** (2013.01); **A61B 17/22012**  
(2013.01);

(Continued)

**12 Claims, 33 Drawing Sheets**



- (51) **Int. Cl.**  
*A61B 18/14* (2006.01)  
*A61B 34/30* (2016.01)  
*A61B 18/00* (2006.01)  
*A61B 17/00* (2006.01)  
*A61B 17/3211* (2006.01)  
*A61B 17/22* (2006.01)  
*A61B 17/28* (2006.01)  
*A61B 34/10* (2016.01)  
*A61B 90/00* (2016.01)

- (52) **U.S. Cl.**  
 CPC .. *A61B 17/3211* (2013.01); *A61B 17/320092* (2013.01); *A61B 18/12* (2013.01); *A61B 18/1206* (2013.01); *A61B 18/1233* (2013.01); *A61B 18/14* (2013.01); *A61B 18/1442* (2013.01); *A61B 18/1445* (2013.01); *A61B 17/282* (2013.01); *A61B 34/30* (2016.02); *A61B 90/361* (2016.02); *A61B 2017/0003* (2013.01); *A61B 2017/00017* (2013.01); *A61B 2017/00022* (2013.01); *A61B 2017/00026* (2013.01); *A61B 2017/00039* (2013.01); *A61B 2017/00061* (2013.01); *A61B 2017/00075* (2013.01); *A61B 2017/00084* (2013.01); *A61B 2017/00084* (2013.01); *A61B 2017/00106* (2013.01); *A61B 2017/00115* (2013.01); *A61B 2017/00137* (2013.01); *A61B 2017/00146* (2013.01); *A61B 2017/00154* (2013.01); *A61B 2017/00199* (2013.01); *A61B 2017/00221* (2013.01); *A61B 2017/00398* (2013.01); *A61B 2017/00464* (2013.01); *A61B 2017/00477* (2013.01); *A61B 2017/00482* (2013.01); *A61B 2017/22014* (2013.01); *A61B 2017/2825* (2013.01); *A61B 2017/32007* (2017.08); *A61B 2017/320073* (2017.08); *A61B 2017/320074* (2017.08); *A61B 2017/320084* (2013.01); *A61B 2017/320094* (2017.08); *A61B 2017/320095* (2017.08); *A61B 2017/320097* (2017.08); *A61B 2018/0063* (2013.01); *A61B 2018/00589* (2013.01); *A61B 2018/00595* (2013.01); *A61B 2018/00601* (2013.01); *A61B 2018/00607* (2013.01); *A61B 2018/00648* (2013.01); *A61B 2018/00684* (2013.01); *A61B 2018/00702* (2013.01); *A61B 2018/00791* (2013.01); *A61B 2018/00827* (2013.01); *A61B 2018/00875* (2013.01); *A61B 2018/00886* (2013.01); *A61B 2018/00892* (2013.01); *A61B 2018/00994* (2013.01); *A61B 2018/126* (2013.01); *A61B 2018/128* (2013.01); *A61B 2018/1253* (2013.01); *A61B 2018/1412* (2013.01); *A61B 2018/1452* (2013.01); *A61B 2034/107* (2016.02); *A61B 2090/065* (2016.02); *A61B 2090/066* (2016.02); *A61B 2090/0808* (2016.02); *A61B 2090/0809* (2016.02); *A61B 2090/0811* (2016.02); *A61B 2217/005* (2013.01); *A61B 2218/002* (2013.01); *A61B 2218/008* (2013.01)

- (58) **Field of Classification Search**  
 CPC ..... *A61B 17/3211*; *A61B 17/282*; *A61B 18/1206*; *A61B 18/1233*; *A61B 18/14*; *A61B 18/1442*; *A61B 18/1445*; *A61B 34/30*; *A61B 2017/320074*; *A61B 2018/00595*

See application file for complete search history.

(56) **References Cited**  
 U.S. PATENT DOCUMENTS

3,082,426	A	3/1963	Miles
3,503,396	A	3/1970	Pierie et al.
3,584,628	A	6/1971	Green
3,626,457	A	12/1971	Duerr et al.
3,633,584	A	1/1972	Farrell
3,759,017	A	9/1973	Young
3,863,118	A	1/1975	Lander et al.
3,898,545	A	8/1975	Coppa et al.
3,912,121	A	10/1975	Steffen
3,915,271	A	10/1975	Harper
3,932,812	A	1/1976	Milligan
4,041,362	A	8/1977	Ichiyanagi
4,052,649	A	10/1977	Greenwell et al.
4,087,730	A	5/1978	Goles
4,157,859	A	6/1979	Terry
4,171,700	A	10/1979	Farin
4,202,722	A	5/1980	Paquin
4,412,539	A	11/1983	Jarvik
4,448,193	A	5/1984	Ivanov
4,523,695	A	6/1985	Braun et al.
4,608,160	A	8/1986	Zoch
4,614,366	A	9/1986	North et al.
4,633,874	A	1/1987	Chow et al.
4,701,193	A	10/1987	Robertson et al.
4,735,603	A	4/1988	Goodson et al.
4,788,977	A	12/1988	Farin et al.
4,849,752	A	7/1989	Bryant
D303,787	S	10/1989	Messenger et al.
4,892,244	A	1/1990	Fox et al.
4,976,173	A	12/1990	Yang
5,010,341	A	4/1991	Huntley et al.
5,026,387	A	6/1991	Thomas
5,035,692	A	7/1991	Lyon et al.
5,042,460	A	8/1991	Sakurai et al.
5,047,043	A	9/1991	Kubota et al.
5,084,057	A	1/1992	Green et al.
5,100,402	A	3/1992	Fan
D327,061	S	6/1992	Soren et al.
5,129,570	A	7/1992	Schulze et al.
5,151,102	A	9/1992	Kamiyama et al.
5,156,315	A	10/1992	Green et al.
5,158,585	A	10/1992	Saho et al.
5,171,247	A	12/1992	Hughett et al.
5,189,277	A	2/1993	Boisvert et al.
5,197,962	A	3/1993	Sansom et al.
5,204,669	A	4/1993	Dorfe et al.
5,217,003	A	6/1993	Wilk
5,242,474	A	9/1993	Herbst et al.
5,253,793	A	10/1993	Green et al.
5,271,543	A	12/1993	Grant et al.
RE34,519	E	1/1994	Fox et al.
5,275,323	A	1/1994	Schulze et al.
5,318,516	A	6/1994	Cosmescu
5,318,563	A	6/1994	Malis et al.
5,322,055	A	6/1994	Davison et al.
5,342,349	A	8/1994	Kaufman
5,364,003	A	11/1994	Williamson, IV
5,383,880	A	1/1995	Hooven
5,385,544	A	1/1995	Edwards et al.
5,396,900	A	3/1995	Slater et al.
5,397,046	A	3/1995	Savage et al.
5,403,312	A	4/1995	Yates et al.
5,403,327	A	4/1995	Thornton et al.
5,413,267	A	5/1995	Solyntjes et al.
5,415,335	A	5/1995	Knodell, Jr.
5,417,699	A	5/1995	Klein et al.
5,439,468	A	8/1995	Schulze et al.
5,445,304	A	8/1995	Plyley et al.
5,462,545	A	10/1995	Wang et al.
5,465,895	A	11/1995	Knodell et al.
5,467,911	A	11/1995	Tsuruta et al.
5,474,566	A	12/1995	Alesi et al.
5,485,947	A	1/1996	Olson et al.
5,496,315	A	3/1996	Weaver et al.
5,496,317	A	3/1996	Goble et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,503,320	A	4/1996	Webster et al.	6,126,592	A	10/2000	Proch et al.	
5,529,235	A	6/1996	Boiarski et al.	6,126,658	A	10/2000	Baker	
5,531,743	A	7/1996	Nettekoven et al.	6,131,789	A	10/2000	Schulze et al.	
5,545,148	A	8/1996	Wurster	6,155,473	A	12/2000	Tompkins et al.	
5,552,685	A	9/1996	Young et al.	6,214,000	B1	4/2001	Fleenor et al.	
5,560,372	A	10/1996	Cory	6,258,105	B1	7/2001	Hart et al.	
5,584,425	A	12/1996	Savage et al.	6,269,411	B1	7/2001	Reasoner	
5,610,379	A	3/1997	Muz et al.	6,273,887	B1	8/2001	Yamauchi et al.	
5,610,811	A	3/1997	Honda	6,283,960	B1	9/2001	Ashley	
5,613,966	A	3/1997	Makower et al.	6,301,495	B1	10/2001	Gueziec et al.	
5,624,452	A	4/1997	Yates	6,302,881	B1	10/2001	Farin	
D379,346	S	5/1997	Mieki	6,308,089	B1	10/2001	von der Ruhr et al.	
5,626,587	A	5/1997	Bishop et al.	6,325,808	B1	12/2001	Bernard et al.	
5,643,291	A	7/1997	Pier et al.	6,325,811	B1	12/2001	Messerly	
5,654,750	A	8/1997	Weil et al.	6,331,181	B1	12/2001	Tierney et al.	
5,673,841	A	10/1997	Schulze et al.	6,341,164	B1	1/2002	Dilkie et al.	
5,673,842	A	10/1997	Bittner et al.	6,391,102	B1	5/2002	Bodden et al.	
5,675,227	A	10/1997	Roos et al.	6,423,057	B1	7/2002	He et al.	
5,693,042	A	12/1997	Boiarski et al.	6,434,416	B1	8/2002	Mizoguchi et al.	
5,693,052	A	12/1997	Weaver	6,443,973	B1	9/2002	Whitman	
5,695,502	A	12/1997	Pier et al.	6,451,015	B1	9/2002	Rittman, III et al.	
5,697,926	A	12/1997	Weaver	6,454,781	B1	9/2002	Witt et al.	
5,706,998	A	1/1998	Plyley et al.	6,457,625	B1	10/2002	Tormala et al.	
5,718,359	A	2/1998	Palmer et al.	6,461,352	B2	10/2002	Morgan et al.	
5,724,468	A	3/1998	Leone et al.	6,466,817	B1	10/2002	Kaula et al.	
5,725,536	A	3/1998	Oberlin et al.	6,480,796	B2	11/2002	Wiener	
5,725,542	A	3/1998	Yoon	6,524,307	B1	2/2003	Palmerton et al.	
5,735,445	A	4/1998	Vidal et al.	6,530,933	B1	3/2003	Yeung et al.	
5,735,848	A	4/1998	Yates et al.	6,551,243	B2	4/2003	Bocionek et al.	
5,746,209	A	5/1998	Yost et al.	6,569,109	B2	5/2003	Sakurai et al.	
5,749,362	A	5/1998	Funda et al.	6,582,424	B2	6/2003	Fleenor et al.	
5,749,893	A	5/1998	Vidal et al.	6,584,358	B2	6/2003	Carter et al.	
5,752,644	A	5/1998	Bolanos et al.	6,585,791	B1	7/2003	Garito et al.	
5,762,255	A	6/1998	Chrisman et al.	6,611,793	B1	8/2003	Burnside et al.	
5,762,458	A	6/1998	Wang et al.	6,618,626	B2	9/2003	West, Jr. et al.	
5,766,186	A	6/1998	Faraz et al.	6,633,234	B2	10/2003	Wiener et al.	
5,769,791	A	* 6/1998	Benaron ..... A61B 5/0084 600/473	6,648,223	B2	11/2003	Boukhny et al.	
5,775,331	A	7/1998	Raymond et al.	6,678,552	B2*	1/2004	Pearlman ..... A61B 5/0536 600/547	
5,797,537	A	8/1998	Oberlin et al.	6,679,899	B2	1/2004	Wiener et al.	
5,800,350	A	9/1998	Coppleson et al.	6,685,704	B2	2/2004	Greep	
D399,561	S	10/1998	Ellingson	6,699,187	B2	3/2004	Webb et al.	
5,817,093	A	10/1998	Williamson, IV et al.	6,731,514	B2	5/2004	Evans	
5,820,009	A	10/1998	Melling et al.	6,742,895	B2	6/2004	Robin	
5,833,690	A	11/1998	Yates et al.	6,752,816	B2	6/2004	Culp et al.	
5,836,849	A	11/1998	Mathiak et al.	6,760,616	B2	7/2004	Hoey et al.	
5,836,869	A	11/1998	Kudo et al.	6,770,072	B1	8/2004	Truckai et al.	
5,836,909	A	11/1998	Cosmescu	6,773,444	B2	8/2004	Messerly	
5,843,080	A	12/1998	Fleenor et al.	6,775,575	B2	8/2004	Bommannan et al.	
5,846,237	A	12/1998	Nettekoven	6,778,846	B1	8/2004	Martinez et al.	
5,849,022	A	12/1998	Sakashita et al.	6,781,683	B2	8/2004	Kacyra et al.	
5,873,873	A	2/1999	Smith et al.	6,783,524	B2	8/2004	Anderson et al.	
5,878,938	A	3/1999	Bittner et al.	6,783,525	B2	8/2004	Greep et al.	
5,893,849	A	4/1999	Weaver	6,793,652	B1	9/2004	Whitman et al.	
5,906,625	A	5/1999	Bitto et al.	6,793,663	B2	9/2004	Kneifel et al.	
5,942,333	A	8/1999	Arnett et al.	6,824,539	B2	11/2004	Novak	
5,947,996	A	9/1999	Logeman	6,846,308	B2	1/2005	Whitman et al.	
5,968,032	A	10/1999	Sleister	6,849,074	B2	2/2005	Chen et al.	
5,980,510	A	11/1999	Tsonton et al.	6,852,219	B2	2/2005	Hammond	
5,987,346	A	11/1999	Benaron et al.	6,863,650	B1	3/2005	Irion	
5,997,528	A	12/1999	Bisch et al.	6,869,430	B2	3/2005	Balbierz et al.	
6,004,269	A	12/1999	Crowley et al.	6,869,435	B2	3/2005	Blake, III	
6,010,054	A	1/2000	Johnson et al.	6,911,033	B2	6/2005	de Guillebon et al.	
6,030,437	A	2/2000	Gourrier et al.	6,913,471	B2	7/2005	Smith	
6,036,637	A	3/2000	Kudo	6,937,892	B2	8/2005	Leyde et al.	
6,039,734	A	3/2000	Goble	6,945,981	B2	9/2005	Donofrio et al.	
6,039,735	A	3/2000	Greep	6,951,559	B1	10/2005	Greep	
6,059,799	A	5/2000	Aranyi et al.	6,962,587	B2	11/2005	Johnson et al.	
6,066,137	A	5/2000	Greep	6,978,921	B2	12/2005	Shelton, IV et al.	
6,079,606	A	6/2000	Milliman et al.	6,988,649	B2	1/2006	Shelton, IV et al.	
6,090,107	A	7/2000	Borgmeier et al.	7,000,818	B2	2/2006	Shelton, IV et al.	
6,099,537	A	8/2000	Sugai et al.	7,009,511	B2	3/2006	Mazar et al.	
6,102,907	A	8/2000	Smethers et al.	7,030,146	B2	4/2006	Baynes et al.	
6,109,500	A	8/2000	Alli et al.	7,032,798	B2	4/2006	Whitman et al.	
6,113,598	A	9/2000	Baker	7,041,941	B2	5/2006	Faries, Jr. et al.	
				7,044,352	B2	5/2006	Shelton, IV et al.	
				7,044,911	B2	5/2006	Drinan et al.	
				7,044,949	B2	5/2006	Orszulak et al.	
				7,048,775	B2	5/2006	Jornitz et al.	

(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,053,752	B2	5/2006	Wang et al.	7,699,860	B2	4/2010	Huitema et al.
7,055,730	B2	6/2006	Ehrenfels et al.	7,720,306	B2	5/2010	Gardiner et al.
7,073,765	B2	7/2006	Newkirk	7,721,934	B2	5/2010	Shelton, IV et al.
7,077,853	B2	7/2006	Kramer et al.	7,721,936	B2	5/2010	Shalton, IV et al.
7,077,856	B2	7/2006	Whitman	7,736,357	B2	6/2010	Lee, Jr. et al.
7,081,096	B2	7/2006	Brister et al.	7,742,176	B2	6/2010	Braunecker et al.
7,097,640	B2	8/2006	Wang et al.	7,743,960	B2	6/2010	Whitman et al.
7,103,688	B2	9/2006	Strong	7,753,245	B2	7/2010	Boudreaux et al.
7,104,949	B2	9/2006	Anderson et al.	7,757,028	B2	7/2010	Druke et al.
7,118,564	B2	10/2006	Ritchie et al.	7,766,207	B2	8/2010	Mather et al.
7,121,460	B1	10/2006	Parsons et al.	7,766,905	B2	8/2010	Paterson et al.
7,137,980	B2	11/2006	Buyse et al.	7,770,773	B2	8/2010	Whitman et al.
7,140,528	B2	11/2006	Shelton, IV	7,771,429	B2	8/2010	Ballard et al.
7,143,923	B2	12/2006	Shelton, IV et al.	7,776,037	B2	8/2010	Odom
7,143,925	B2	12/2006	Shelton, IV et al.	7,782,789	B2	8/2010	Stultz et al.
7,147,139	B2	12/2006	Schwemberger et al.	7,784,663	B2	8/2010	Shelton, IV
7,155,316	B2	12/2006	Sutherland et al.	7,803,151	B2	9/2010	Whitman
7,164,940	B2	1/2007	Hareyama et al.	7,810,692	B2	10/2010	Hall et al.
7,169,145	B2	1/2007	Isaacson et al.	7,818,041	B2	10/2010	Kim et al.
7,177,533	B2	2/2007	McFarlin et al.	7,819,298	B2	10/2010	Hall et al.
7,182,775	B2	2/2007	de Guillebon et al.	7,832,612	B2	11/2010	Baxter, III et al.
7,207,472	B2	4/2007	Wukusick et al.	7,833,219	B2	11/2010	Tashiro et al.
7,208,005	B2	4/2007	Freckler et al.	7,836,085	B2	11/2010	Petakov et al.
7,217,269	B2	5/2007	El-Galley et al.	7,837,079	B2	11/2010	Holsten et al.
7,230,529	B2	6/2007	Ketcherside, Jr. et al.	7,837,680	B2	11/2010	Isaacson et al.
7,232,447	B2	6/2007	Gellman et al.	7,841,980	B2	11/2010	Minosawa et al.
7,236,817	B2	6/2007	Papas et al.	7,845,537	B2	12/2010	Shelton, IV et al.
7,246,734	B2	7/2007	Shelton, IV	7,857,185	B2	12/2010	Swayze et al.
7,252,664	B2	8/2007	Nasab et al.	D631,252	S	1/2011	Leslie
7,278,563	B1	10/2007	Green	7,862,560	B2	1/2011	Marion
7,294,106	B2	11/2007	Birkenbach et al.	7,862,579	B2	1/2011	Ortiz et al.
7,294,116	B1	11/2007	Ellman et al.	7,865,236	B2	1/2011	Cory et al.
7,296,724	B2	11/2007	Green et al.	7,884,735	B2	2/2011	Newkirk
7,317,955	B2	1/2008	McGreevy	7,887,530	B2	2/2011	Zemlok et al.
7,328,828	B2	2/2008	Ortiz et al.	7,892,337	B2	2/2011	Palmerton et al.
7,334,717	B2	2/2008	Rethy et al.	7,907,166	B2	3/2011	Lamprecht et al.
7,343,565	B2	3/2008	Ying et al.	7,913,891	B2	3/2011	Doll et al.
7,344,532	B2	3/2008	Goble et al.	7,918,230	B2	4/2011	Whitman et al.
7,353,068	B2	4/2008	Tanaka et al.	7,918,377	B2	4/2011	Measamer et al.
7,362,228	B2	4/2008	Nycz et al.	7,920,706	B2	4/2011	Asokan et al.
7,371,227	B2	5/2008	Zeiner	7,927,014	B2	4/2011	Dehler
7,380,695	B2	6/2008	Doll et al.	7,932,826	B2	4/2011	Fritchie et al.
7,383,088	B2	6/2008	Spinelli et al.	7,942,300	B2	5/2011	Rethy et al.
7,391,173	B2	6/2008	Schena	7,945,065	B2	5/2011	Menzl et al.
7,407,074	B2	8/2008	Ortiz et al.	7,945,342	B2	5/2011	Tsai et al.
7,408,439	B2	8/2008	Wang et al.	7,951,148	B2	5/2011	McClurken
7,422,136	B1	9/2008	Marczyk	7,954,682	B2	6/2011	Giordano et al.
7,422,139	B2	9/2008	Shelton, IV et al.	7,955,322	B2	6/2011	Devengenzo et al.
7,423,972	B2	9/2008	Shaham et al.	7,956,620	B2	6/2011	Gilbert
D579,876	S	11/2008	Novotney et al.	7,963,433	B2	6/2011	Whitman et al.
7,457,804	B2	11/2008	Uber, III et al.	7,966,269	B2	6/2011	Bauer et al.
D583,328	S	12/2008	Chiang	7,967,180	B2	6/2011	Scirica
7,464,847	B2	12/2008	Viola et al.	7,976,553	B2	7/2011	Shelton, IV et al.
7,464,849	B2	12/2008	Shelton, IV et al.	7,979,157	B2	7/2011	Anvari
7,496,418	B2	2/2009	Kim et al.	7,980,443	B2	7/2011	Scheib et al.
D589,447	S	3/2009	Sasada et al.	7,982,776	B2	7/2011	Dunki-Jacobs et al.
7,515,961	B2	4/2009	Germanson et al.	7,988,028	B2	8/2011	Farascioni et al.
7,518,502	B2	4/2009	Austin et al.	7,993,140	B2	8/2011	Sakezles
7,554,343	B2	6/2009	Bromfield	7,995,045	B2	8/2011	Dunki-Jacobs
7,563,259	B2	7/2009	Takahashi	8,005,947	B2	8/2011	Morris et al.
7,568,604	B2	8/2009	Ehrenfels et al.	8,007,494	B1	8/2011	Taylor et al.
7,575,144	B2	8/2009	Ortiz et al.	8,007,513	B2	8/2011	Nalagatla et al.
7,597,731	B2	10/2009	Palmerton et al.	8,010,180	B2	8/2011	Quaid et al.
7,617,137	B2	11/2009	Kreiner et al.	8,012,170	B2	9/2011	Whitman et al.
7,621,192	B2	11/2009	Conti et al.	8,015,976	B2	9/2011	Shah
7,621,898	B2	11/2009	Lalomia et al.	8,016,855	B2	9/2011	Whitman et al.
7,631,793	B2	12/2009	Rethy et al.	8,019,094	B2	9/2011	Hsieh et al.
7,637,410	B2	12/2009	Marczyk	8,025,199	B2	9/2011	Whitman et al.
7,637,907	B2	12/2009	Blaha	8,027,710	B1	9/2011	Dannan
7,641,092	B2	1/2010	Kruszynski et al.	8,035,685	B2	10/2011	Jensen
7,644,848	B2	1/2010	Swayze et al.	8,038,686	B2	10/2011	Huitema et al.
7,667,592	B2	2/2010	Ohyama et al.	8,038,693	B2	10/2011	Allen
7,667,839	B2	2/2010	Bates	8,043,560	B2	10/2011	Okumoto et al.
7,670,334	B2	3/2010	Hueil et al.	8,054,184	B2	11/2011	Cline et al.
7,694,865	B2	4/2010	Scirica	8,054,752	B2	11/2011	Druke et al.
				8,062,306	B2	11/2011	Nobis et al.
				8,062,330	B2	11/2011	Prommersberger et al.
				8,066,721	B2	11/2011	Kortenbach et al.
				8,074,861	B2	12/2011	Ehrenfels et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,075,571	B2	12/2011	Vitali et al.	8,468,030	B2	6/2013	Stroup et al.
8,096,459	B2	1/2012	Ortiz et al.	8,469,973	B2	6/2013	Meade et al.
8,118,206	B2	2/2012	Zand et al.	8,472,630	B2	6/2013	Konrad et al.
8,120,301	B2	2/2012	Goldberg et al.	8,473,066	B2	6/2013	Aghassian et al.
8,123,764	B2	2/2012	Meade et al.	D687,146	S	7/2013	Juzkiw et al.
D655,678	S	3/2012	Kobayashi et al.	8,476,227	B2	7/2013	Kaplan et al.
8,128,625	B2	3/2012	Odom	8,478,418	B2	7/2013	Fahey
8,131,565	B2	3/2012	Dicks et al.	8,489,235	B2	7/2013	Moll et al.
8,136,712	B2	3/2012	Zingman	8,499,992	B2	8/2013	Whitman et al.
D657,368	S	4/2012	Magee et al.	8,500,728	B2	8/2013	Newton et al.
8,147,486	B2	4/2012	Honour et al.	8,500,756	B2	8/2013	Papa et al.
8,155,479	B2	4/2012	Hoffman et al.	8,503,759	B2	8/2013	Greer et al.
8,157,145	B2	4/2012	Shelton, IV et al.	8,505,801	B2	8/2013	Ehrenfels et al.
8,157,150	B2	4/2012	Viola et al.	8,506,478	B2	8/2013	Mizuyoshi
8,157,151	B2	4/2012	Ingmanson et al.	8,512,325	B2	8/2013	Mathonnet
8,160,098	B1	4/2012	Yan et al.	8,512,365	B2	8/2013	Wiener et al.
8,160,690	B2	4/2012	Wilfley et al.	8,515,520	B2	8/2013	Brunnett et al.
8,161,977	B2	4/2012	Shelton, IV et al.	8,517,239	B2	8/2013	Scheib et al.
8,170,396	B2	5/2012	Kuspa et al.	8,521,331	B2	8/2013	Itkowitz
8,172,836	B2	5/2012	Ward	8,523,043	B2	9/2013	Ullrich et al.
8,181,839	B2	5/2012	Beetel	8,540,709	B2	9/2013	Allen
8,185,409	B2	5/2012	Putnam et al.	8,546,996	B2	10/2013	Messerly et al.
8,206,345	B2	6/2012	Abboud et al.	8,554,697	B2	10/2013	Claus et al.
8,208,707	B2	6/2012	Mendonca et al.	8,560,047	B2	10/2013	Haider et al.
8,210,411	B2	7/2012	Yates et al.	8,561,870	B2	10/2013	Baxter, III et al.
8,214,007	B2	7/2012	Baker et al.	8,562,598	B2	10/2013	Falkenstein et al.
8,216,849	B2	7/2012	Petty	8,566,115	B2	10/2013	Moore
8,220,688	B2	7/2012	Laurent et al.	8,567,393	B2	10/2013	Hickle et al.
8,225,643	B2	7/2012	Abboud et al.	8,571,598	B2	10/2013	Valavi
8,225,979	B2	7/2012	Farascioni et al.	8,573,459	B2	11/2013	Smith et al.
8,229,549	B2	7/2012	Whitman et al.	8,573,465	B2	11/2013	Shelton, IV
8,231,042	B2	7/2012	Hessler et al.	8,574,229	B2	11/2013	Eder et al.
8,239,066	B2	8/2012	Jennings et al.	8,585,631	B2	11/2013	Dacquay
8,241,322	B2	8/2012	Whitman et al.	8,585,694	B2	11/2013	Amoah et al.
8,255,045	B2	8/2012	Gharib et al.	8,590,762	B2	11/2013	Hess et al.
D667,838	S	9/2012	Magee et al.	8,591,536	B2	11/2013	Robertson
8,257,387	B2	9/2012	Cunningham	8,595,607	B2	11/2013	Nekoomaram et al.
8,260,016	B2	9/2012	Maeda et al.	8,596,513	B2	12/2013	Olson et al.
8,262,560	B2	9/2012	Whitman	8,596,515	B2	12/2013	Okoniewski
8,292,639	B2	10/2012	Achammer et al.	8,604,709	B2	12/2013	Jalbout et al.
8,292,888	B2	10/2012	Whitman	8,608,044	B2	12/2013	Hueil et al.
8,295,902	B2	10/2012	Salahieh et al.	8,608,045	B2	12/2013	Smith et al.
8,308,040	B2	11/2012	Huang et al.	8,616,431	B2	12/2013	Timm et al.
8,321,581	B2	11/2012	Katis et al.	8,617,155	B2	12/2013	Johnson et al.
8,322,590	B2	12/2012	Patel et al.	8,620,055	B2	12/2013	Barratt et al.
8,328,065	B2	12/2012	Shah	8,620,473	B2	12/2013	Diolaiti et al.
8,335,590	B2	12/2012	Costa et al.	8,622,275	B2	1/2014	Baxter, III et al.
D675,164	S	1/2013	Kobayashi et al.	8,623,027	B2	1/2014	Price et al.
8,343,065	B2	1/2013	Bartol et al.	8,627,483	B2	1/2014	Rachlin et al.
8,346,392	B2	1/2013	Walsler et al.	8,627,993	B2	1/2014	Smith et al.
8,360,299	B2	1/2013	Zemlok et al.	8,627,995	B2	1/2014	Smith et al.
8,364,222	B2	1/2013	Cook et al.	8,628,518	B2	1/2014	Blumenkranz et al.
D676,392	S	2/2013	Gassauer	8,628,545	B2	1/2014	Cabrera et al.
8,365,975	B1	2/2013	Manoux et al.	8,631,987	B2	1/2014	Shelton, IV et al.
D678,196	S	3/2013	Miyauchi et al.	8,632,525	B2	1/2014	Kerr et al.
D678,304	S	3/2013	Yakoub et al.	8,636,190	B2	1/2014	Zemlok et al.
8,388,652	B2	3/2013	Viola	8,636,736	B2	1/2014	Yates et al.
8,393,514	B2	3/2013	Shelton, IV et al.	8,641,621	B2	2/2014	Razzaque et al.
8,397,972	B2	3/2013	Kostrzewski	8,652,086	B2	2/2014	Gerg et al.
8,398,541	B2	3/2013	DiMaio et al.	8,652,121	B2	2/2014	Quick et al.
8,403,944	B2	3/2013	Pain et al.	8,652,128	B2	2/2014	Ward
8,403,945	B2	3/2013	Whitfield et al.	8,657,176	B2	2/2014	Shelton, IV et al.
8,403,946	B2	3/2013	Whitfield et al.	8,657,177	B2	2/2014	Scirica et al.
8,406,859	B2	3/2013	Zuzak et al.	8,663,220	B2	3/2014	Wiener et al.
8,411,034	B2	4/2013	Boillot et al.	8,666,544	B2	3/2014	Moll et al.
8,413,871	B2	4/2013	Racenet et al.	8,679,114	B2	3/2014	Chapman et al.
8,422,035	B2	4/2013	Hinderling et al.	8,682,049	B2	3/2014	Zhao et al.
8,423,182	B2	4/2013	Robinson et al.	8,682,489	B2	3/2014	Itkowitz et al.
8,428,722	B2	4/2013	Verhoef et al.	8,685,056	B2	4/2014	Evans et al.
8,429,153	B2	4/2013	Birdwell et al.	8,688,188	B2	4/2014	Heller et al.
8,439,910	B2	5/2013	Greep et al.	8,690,864	B2	4/2014	Hoarau
8,444,663	B2	5/2013	Houser et al.	8,701,962	B2	4/2014	Kostrzewski
8,452,615	B2	5/2013	Abri	D704,839	S	5/2014	Juzkiw et al.
8,454,506	B2	6/2013	Rothman et al.	8,719,061	B2	5/2014	Birchall
8,461,744	B2	6/2013	Wiener et al.	8,720,766	B2	5/2014	Hess et al.
				8,733,613	B2	5/2014	Huitema et al.
				8,740,840	B2	6/2014	Foley et al.
				8,740,866	B2	6/2014	Reasoner et al.
				8,747,238	B2	6/2014	Shelton, IV et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,752,749	B2	6/2014	Moore et al.	9,023,032	B2	5/2015	Robinson
8,757,465	B2	6/2014	Woodard, Jr. et al.	9,023,071	B2	5/2015	Miller et al.
8,761,717	B1	6/2014	Buchheit	9,027,431	B2	5/2015	Tang et al.
8,763,879	B2	7/2014	Shelton, IV et al.	9,028,494	B2	5/2015	Shelton, IV et al.
8,768,251	B2	7/2014	Claus et al.	9,035,568	B2	5/2015	Ganton et al.
8,771,270	B2	7/2014	Burbank	9,038,882	B2	5/2015	Racenet et al.
8,775,196	B2	7/2014	Simpson et al.	9,043,027	B2	5/2015	Durant et al.
8,779,648	B2	7/2014	Giordano et al.	9,044,227	B2	6/2015	Shelton, IV et al.
8,790,253	B2	7/2014	Sunagawa et al.	9,044,244	B2	6/2015	Ludwin et al.
8,794,497	B2	8/2014	Zingman	9,044,261	B2	6/2015	Houser
8,795,001	B1	8/2014	Lam et al.	9,050,063	B2	6/2015	Roe et al.
8,799,008	B2	8/2014	Johnson et al.	9,050,083	B2	6/2015	Yates et al.
8,799,009	B2	8/2014	Mellin et al.	9,050,120	B2	6/2015	Swarup et al.
8,800,838	B2	8/2014	Shelton, IV	9,052,809	B2	6/2015	Vesto
8,801,703	B2	8/2014	Gregg et al.	9,055,035	B2	6/2015	Porsch et al.
8,814,996	B2	8/2014	Giurgiutiu et al.	9,055,870	B2	6/2015	Meador et al.
8,818,556	B2	8/2014	Sanchez et al.	9,060,770	B2	6/2015	Shelton, IV et al.
8,819,581	B2	8/2014	Nakamura et al.	9,060,775	B2	6/2015	Wiener et al.
8,820,603	B2	9/2014	Shelton, IV et al.	9,066,650	B2	6/2015	Sekiguchi
8,820,608	B2	9/2014	Miyamoto	9,072,523	B2	7/2015	Houser et al.
8,827,134	B2	9/2014	Viola et al.	9,072,535	B2	7/2015	Shelton, IV et al.
8,840,003	B2	9/2014	Morgan et al.	9,072,536	B2	7/2015	Shelton, IV et al.
D716,333	S	10/2014	Chotin et al.	9,078,653	B2	7/2015	Leimbach et al.
8,851,354	B2	10/2014	Swensgard et al.	9,078,727	B2	7/2015	Miller
8,852,174	B2	10/2014	Burbank	9,084,606	B2	7/2015	Greep
8,875,973	B2	11/2014	Whitman	9,089,360	B2	7/2015	Messery et al.
8,876,857	B2	11/2014	Burbank	9,095,362	B2	8/2015	Dachs, II et al.
8,882,662	B2	11/2014	Charles	9,095,367	B2	8/2015	Olson et al.
8,886,790	B2	11/2014	Harrang et al.	9,099,863	B2	8/2015	Smith et al.
8,893,949	B2	11/2014	Shelton, IV et al.	9,101,358	B2	8/2015	Kerr et al.
8,899,479	B2	12/2014	Cappuzzo et al.	9,101,359	B2	8/2015	Smith et al.
8,905,977	B2	12/2014	Shelton et al.	9,101,374	B1	8/2015	Hoch et al.
8,912,746	B2	12/2014	Reid et al.	9,106,270	B2	8/2015	Puterbaugh et al.
8,914,098	B2	12/2014	Brennan et al.	9,107,573	B2	8/2015	Birnkrant
8,917,513	B1	12/2014	Hazzard	9,107,662	B2	8/2015	Kostrzewski
8,918,207	B2	12/2014	Prisco	9,107,684	B2	8/2015	Ma
8,920,186	B2	12/2014	Shishikura	9,107,688	B2	8/2015	Kimball et al.
8,920,414	B2	12/2014	Stone et al.	9,107,689	B2	8/2015	Robertson et al.
8,920,433	B2	12/2014	Barrier et al.	9,107,694	B2	8/2015	Hendriks et al.
8,930,203	B2	1/2015	Kiaie et al.	9,111,548	B2	8/2015	Nandy et al.
8,930,214	B2	1/2015	Woolford	9,113,880	B2	8/2015	Zemlok et al.
8,931,679	B2	1/2015	Kostrzewski	9,114,494	B1	8/2015	Mah
8,936,614	B2	1/2015	Allen, IV	9,116,597	B1	8/2015	Gulasky
8,945,095	B2	2/2015	Blumenkranz et al.	9,119,617	B2	9/2015	Souls et al.
8,945,163	B2	2/2015	Voegele et al.	9,119,655	B2	9/2015	Bowling et al.
8,955,732	B2	2/2015	Zemlok et al.	9,119,657	B2	9/2015	Shelton, IV et al.
8,956,581	B2	2/2015	Rosenbaum et al.	9,123,155	B2	9/2015	Cunningham et al.
8,960,519	B2	2/2015	Whitman et al.	9,125,644	B2	9/2015	Lane et al.
8,960,520	B2	2/2015	McCuen	9,129,054	B2	9/2015	Nawana et al.
8,962,062	B2	2/2015	Podhajsky et al.	9,137,254	B2	9/2015	Bilbrey et al.
8,967,443	B2	3/2015	McCuen	9,138,129	B2	9/2015	Diolaiti
8,967,455	B2	3/2015	Zhou	9,138,225	B2	9/2015	Huang et al.
8,968,276	B2	3/2015	Zemlok et al.	9,149,322	B2	10/2015	Knowlton
8,968,296	B2	3/2015	McPherson	9,155,503	B2	10/2015	Cadwell
8,968,309	B2	3/2015	Roy et al.	9,160,853	B1	10/2015	Daddi et al.
8,968,312	B2	3/2015	Marczyk et al.	9,161,803	B2	10/2015	Yates et al.
8,968,337	B2	3/2015	Whitfield et al.	9,168,054	B2	10/2015	Turner et al.
8,968,358	B2	3/2015	Reschke	9,168,091	B2	10/2015	Janssen et al.
8,974,429	B2	3/2015	Gordon et al.	9,168,104	B2	10/2015	Dein
8,979,890	B2	3/2015	Boudreaux	9,179,912	B2	11/2015	Yates et al.
8,986,288	B2	3/2015	Konishi	9,183,723	B2	11/2015	Sherman et al.
8,986,302	B2	3/2015	Aldridge et al.	9,186,143	B2	11/2015	Timm et al.
8,989,903	B2	3/2015	Weir et al.	9,192,375	B2	11/2015	Skinlo et al.
8,991,678	B2	3/2015	Wellman et al.	9,192,447	B2	11/2015	Choi et al.
8,992,565	B2	3/2015	Brisson et al.	9,192,707	B2	11/2015	Gerber et al.
8,998,797	B2	4/2015	Omori	9,198,711	B2	12/2015	Joseph
9,002,518	B2	4/2015	Manzo et al.	9,202,078	B2	12/2015	Abuelsaad et al.
9,010,608	B2	4/2015	Casasanta, Jr. et al.	9,204,830	B2	12/2015	Zand et al.
9,010,611	B2	4/2015	Ross et al.	9,204,879	B2	12/2015	Shelton, IV
9,011,366	B2	4/2015	Dean et al.	9,204,995	B2	12/2015	Scheller et al.
9,011,427	B2	4/2015	Price et al.	9,211,120	B2	12/2015	Scheib et al.
9,016,539	B2	4/2015	Kostrzewski et al.	9,216,062	B2	12/2015	Duque et al.
9,017,326	B2	4/2015	DiNardo et al.	9,218,053	B2	12/2015	Komuro et al.
9,020,240	B2	4/2015	Pettersson et al.	9,220,502	B2	12/2015	Zemlok et al.
D729,267	S	5/2015	Yoo et al.	9,226,689	B2	1/2016	Jacobsen et al.
				9,226,751	B2	1/2016	Shelton, IV et al.
				9,226,766	B2	1/2016	Aldridge et al.
				9,226,767	B2	1/2016	Stulen et al.
				9,226,791	B2	1/2016	McCarthy et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

9,232,883	B2	1/2016	Ozawa et al.	9,439,736	B2	9/2016	Olson
9,237,891	B2	1/2016	Shelton, IV	9,445,764	B2	9/2016	Gross et al.
9,237,921	B2	1/2016	Messerly et al.	9,445,813	B2	9/2016	Shelton, IV et al.
9,241,728	B2	1/2016	Price et al.	9,450,701	B2	9/2016	Do et al.
9,241,730	B2	1/2016	Babaev	9,451,949	B2	9/2016	Gorek et al.
9,241,731	B2	1/2016	Boudreaux et al.	9,451,958	B2	9/2016	Shelton, IV et al.
9,247,996	B1	2/2016	Merana et al.	9,463,022	B2	10/2016	Swayze et al.
9,250,172	B2	2/2016	Harris et al.	9,463,646	B2	10/2016	Payne et al.
9,255,907	B2	2/2016	Heanue et al.	9,468,438	B2	10/2016	Baber et al.
9,265,429	B2	2/2016	St. Pierre et al.	9,474,565	B2	10/2016	Shikhman et al.
9,265,585	B2	2/2016	Wingardner et al.	D772,252	S	11/2016	Myers et al.
9,272,406	B2	3/2016	Aronhalt et al.	9,480,492	B2	11/2016	Aranyi et al.
9,277,956	B2	3/2016	Zhang	9,485,475	B2	11/2016	Speier et al.
9,277,961	B2	3/2016	Panescu et al.	9,486,271	B2	11/2016	Dunning
9,277,969	B2	3/2016	Brannan et al.	9,492,146	B2	11/2016	Kostrzewski et al.
9,280,884	B1	3/2016	Schultz et al.	9,492,237	B2	11/2016	Kang et al.
9,282,962	B2	3/2016	Schmid et al.	9,493,807	B2	11/2016	Little et al.
9,282,974	B2	3/2016	Shelton, IV	9,498,182	B2	11/2016	Case et al.
9,283,045	B2	3/2016	Rhee et al.	9,498,215	B2	11/2016	Duque et al.
9,283,054	B2	3/2016	Morgan et al.	9,498,231	B2	11/2016	Haider et al.
9,289,211	B2	3/2016	Williams et al.	9,516,239	B2	12/2016	Blanquart et al.
9,289,212	B2	3/2016	Shelton, IV et al.	9,519,753	B1	12/2016	Gerdeeman et al.
9,295,514	B2	3/2016	Shelton, IV et al.	9,522,003	B2	12/2016	Weir et al.
9,301,691	B2	4/2016	Hufnagel et al.	9,526,407	B2	12/2016	Hoeg et al.
9,301,753	B2	4/2016	Aldridge et al.	9,526,499	B2	12/2016	Kostrzewski et al.
9,301,759	B2	4/2016	Spivey et al.	9,526,587	B2	12/2016	Zhao et al.
9,301,810	B2	4/2016	Amiri et al.	9,532,827	B2	1/2017	Morgan et al.
9,302,213	B2	4/2016	Manahan et al.	9,532,845	B1	1/2017	Dossett et al.
9,307,894	B2	4/2016	von Grunberg et al.	9,539,007	B2	1/2017	Dhakad et al.
9,307,914	B2	4/2016	Fahey	9,539,020	B2	1/2017	Conlon et al.
9,307,986	B2	4/2016	Hall et al.	9,542,481	B2	1/2017	Halter et al.
9,314,246	B2	4/2016	Shelton, IV et al.	9,546,662	B2	1/2017	Shener-Irmakoglu et al.
9,314,308	B2	4/2016	Parihar et al.	9,549,781	B2	1/2017	He et al.
9,320,563	B2	4/2016	Brustad et al.	9,554,692	B2	1/2017	Levy
9,325,732	B1	4/2016	Stickle et al.	9,554,794	B2	1/2017	Baber et al.
9,326,767	B2	5/2016	Koch et al.	9,554,854	B2	1/2017	Yates et al.
9,326,770	B2	5/2016	Shelton, IV et al.	9,561,038	B2	2/2017	Shelton, IV et al.
9,331,422	B2	5/2016	Nazzaro et al.	9,561,045	B2	2/2017	Hinman et al.
9,332,987	B2	5/2016	Leimbach et al.	9,561,082	B2	2/2017	Yen et al.
9,333,042	B2	5/2016	Diolaiti et al.	9,561,982	B2	2/2017	Enicks et al.
9,336,385	B1	5/2016	Spencer et al.	9,566,708	B2	2/2017	Kurnianto
9,341,704	B2	5/2016	Picard et al.	9,572,592	B2	2/2017	Price et al.
9,345,481	B2	5/2016	Hall et al.	9,579,099	B2	2/2017	Penna et al.
9,345,490	B2	5/2016	Ippisch	9,579,503	B2	2/2017	McKinney et al.
9,345,546	B2	5/2016	Toth et al.	9,585,657	B2	3/2017	Shelton, IV et al.
9,345,900	B2	5/2016	Wu et al.	9,592,095	B2	3/2017	Panescu et al.
9,351,726	B2	5/2016	Leimbach et al.	9,597,081	B2	3/2017	Swayze et al.
9,351,727	B2	5/2016	Leimbach et al.	9,600,031	B2	3/2017	Kaneko et al.
9,358,003	B2	6/2016	Hall et al.	9,600,138	B2	3/2017	Thomas et al.
9,358,685	B2	6/2016	Meier et al.	9,603,024	B2	3/2017	Wang et al.
9,360,449	B2	6/2016	Durie	9,603,277	B2	3/2017	Morgan et al.
9,364,230	B2	6/2016	Shelton, IV et al.	D783,675	S	4/2017	Yagisawa et al.
9,364,231	B2	6/2016	Wenchell	D784,270	S	4/2017	Bhattacharya
9,364,249	B2	6/2016	Kimball et al.	9,610,114	B2	4/2017	Baxter, III et al.
9,364,294	B2	6/2016	Razzaque et al.	9,610,412	B2	4/2017	Zemlok et al.
9,370,400	B2	6/2016	Parihar	9,615,877	B2	4/2017	Tyrrell et al.
9,375,282	B2	6/2016	Nau, Jr. et al.	9,622,684	B2	4/2017	Wybo
9,375,539	B2	6/2016	Stearns et al.	9,622,808	B2	4/2017	Beller et al.
9,381,003	B2	7/2016	Todor et al.	9,628,501	B2	4/2017	Datta Ray et al.
9,381,058	B2	7/2016	Houser et al.	9,629,560	B2	4/2017	Joseph
9,386,984	B2	7/2016	Aronhalt et al.	9,629,623	B2	4/2017	Lytle, IV et al.
9,386,988	B2	7/2016	Baxter, III et al.	9,629,628	B2	4/2017	Aranyi
9,387,295	B1	7/2016	Mastri et al.	9,629,629	B2	4/2017	Leimbach et al.
9,393,017	B2	7/2016	Flanagan et al.	9,630,318	B2	4/2017	Ibarz Gabardos et al.
9,393,037	B2	7/2016	Olson et al.	9,636,112	B2	5/2017	Penna et al.
9,398,905	B2	7/2016	Martin	9,636,188	B2	5/2017	Gattani et al.
9,398,911	B2	7/2016	Auld	9,636,239	B2	5/2017	Durand et al.
9,402,629	B2	8/2016	Ehrenfels et al.	9,636,825	B2	5/2017	Penn et al.
9,414,776	B2	8/2016	Sillay et al.	9,641,596	B2	5/2017	Unagami et al.
9,414,940	B2	8/2016	Stein et al.	9,641,815	B2	5/2017	Richardson et al.
9,419,018	B2	8/2016	Sasagawa et al.	9,642,620	B2	5/2017	Baxter, III et al.
9,421,014	B2	8/2016	Ingmanson et al.	9,643,022	B2	5/2017	Mashiach et al.
9,433,470	B2	9/2016	Choi	9,649,110	B2	5/2017	Parihar et al.
9,439,622	B2	9/2016	Case et al.	9,649,111	B2	5/2017	Shelton, IV et al.
9,439,668	B2	9/2016	Timm et al.	9,649,126	B2	5/2017	Robertson et al.
				9,649,169	B2	5/2017	Cinquin et al.
				9,652,655	B2	5/2017	Satish et al.
				9,655,616	B2	5/2017	Aranyi
				9,656,092	B2	5/2017	Golden

(56)

## References Cited

## U.S. PATENT DOCUMENTS

9,662,116	B2	5/2017	Smith et al.	9,808,248	B2	11/2017	Hoffman
9,662,177	B2	5/2017	Weir et al.	9,808,249	B2	11/2017	Shelton, IV
9,668,729	B2	6/2017	Williams et al.	9,814,457	B2	11/2017	Martin et al.
9,668,732	B2	6/2017	Patel et al.	9,814,460	B2	11/2017	Kimsey et al.
9,668,765	B2	6/2017	Grace et al.	9,814,462	B2	11/2017	Woodard, Jr. et al.
9,671,860	B2	6/2017	Ogawa et al.	9,814,463	B2	11/2017	Williams et al.
9,675,264	B2	6/2017	Acquista et al.	9,820,699	B2	11/2017	Bingley et al.
9,675,354	B2	6/2017	Weir et al.	9,820,738	B2	11/2017	Lytle, IV et al.
9,681,870	B2	6/2017	Baxter, III et al.	9,820,741	B2	11/2017	Kostrzewski
9,686,306	B2	6/2017	Chizeck et al.	9,820,768	B2	11/2017	Gee et al.
9,687,230	B2	6/2017	Leimbach et al.	9,826,976	B2	11/2017	Parihar et al.
9,690,362	B2	6/2017	Leimbach et al.	9,826,977	B2	11/2017	Leimbach et al.
9,700,292	B2	7/2017	Nawana et al.	9,827,054	B2	11/2017	Richmond et al.
9,700,309	B2	7/2017	Jaworek et al.	9,827,059	B2	11/2017	Robinson et al.
9,700,312	B2	7/2017	Kostrzewski et al.	9,830,424	B2	11/2017	Dixon et al.
9,700,320	B2	7/2017	Dinardo et al.	9,833,241	B2	12/2017	Huitema et al.
9,706,993	B2	7/2017	Hessler et al.	9,833,254	B1	12/2017	Barral et al.
9,710,214	B2	7/2017	Lin et al.	9,839,419	B2	12/2017	Deck et al.
9,710,644	B2	7/2017	Reybok et al.	9,839,424	B2	12/2017	Zergiebel et al.
9,713,424	B2	7/2017	Spaide	9,839,428	B2	12/2017	Baxter, III et al.
9,713,503	B2	7/2017	Goldschmidt	9,839,467	B2	12/2017	Harper et al.
9,717,141	B1	7/2017	Tegg	9,839,470	B2	12/2017	Gilbert et al.
9,717,498	B2	8/2017	Aranyi et al.	9,839,487	B2	12/2017	Dachs, II
9,717,525	B2	8/2017	Ahluwalia et al.	9,844,321	B1	12/2017	Ekvall et al.
9,717,548	B2	8/2017	Couture	9,844,368	B2	12/2017	Boudreaux et al.
9,724,094	B2	8/2017	Baber et al.	9,844,369	B2	12/2017	Huitema et al.
9,724,100	B2	8/2017	Scheib et al.	9,844,374	B2	12/2017	Lytle, IV et al.
9,724,118	B2	8/2017	Schulte et al.	9,844,375	B2	12/2017	Overmyer et al.
9,733,663	B2	8/2017	Leimbach et al.	9,844,376	B2	12/2017	Baxter, III et al.
9,737,301	B2	8/2017	Baber et al.	9,844,379	B2	12/2017	Shelton, IV et al.
9,737,310	B2	8/2017	Whitfield et al.	9,848,058	B2	12/2017	Johnson et al.
9,737,335	B2	8/2017	Butler et al.	9,848,877	B2	12/2017	Shelton, IV et al.
9,737,355	B2	8/2017	Yates et al.	9,861,354	B2	1/2018	Saliman et al.
9,740,826	B2	8/2017	Raghavan et al.	9,861,363	B2	1/2018	Chen et al.
9,743,016	B2	8/2017	Nestares et al.	9,861,428	B2	1/2018	Trees et al.
9,743,929	B2	8/2017	Leimbach et al.	9,864,839	B2	1/2018	Baym et al.
9,743,946	B2	8/2017	Faller et al.	9,867,612	B2	1/2018	Parihar et al.
9,743,947	B2	8/2017	Price et al.	9,867,651	B2	1/2018	Wham
9,750,499	B2	9/2017	Leimbach et al.	9,867,670	B2	1/2018	Brannan et al.
9,750,500	B2	9/2017	Malkowski	9,867,914	B2	1/2018	Bonano et al.
9,750,522	B2	9/2017	Scheib et al.	9,872,609	B2	1/2018	Levy
9,750,523	B2	9/2017	Tsubuku	9,872,683	B2	1/2018	Hopkins et al.
9,750,563	B2	9/2017	Shikhman et al.	9,877,718	B2	1/2018	Weir et al.
9,753,135	B2	9/2017	Bosch	9,877,721	B2	1/2018	Schellin et al.
9,753,568	B2	9/2017	McMillen	9,883,860	B2	2/2018	Leimbach
9,757,126	B2	9/2017	Cappola	9,888,864	B2	2/2018	Rondoni et al.
9,757,128	B2	9/2017	Baber et al.	9,888,914	B2	2/2018	Martin et al.
9,757,142	B2	9/2017	Shimizu	9,888,919	B2	2/2018	Leimbach et al.
9,757,152	B2	9/2017	Ogilvie et al.	9,888,921	B2	2/2018	Williams et al.
9,763,741	B2	9/2017	Alvarez et al.	9,888,975	B2	2/2018	Auld
9,764,164	B2	9/2017	Wiener et al.	9,895,148	B2	2/2018	Shelton, IV et al.
9,770,541	B2	9/2017	Carr et al.	9,900,787	B2	2/2018	Ou
9,775,611	B2	10/2017	Kostrzewski	9,901,342	B2	2/2018	Shelton, IV et al.
9,777,913	B2	10/2017	Talbert et al.	9,901,406	B2	2/2018	State et al.
9,782,164	B2	10/2017	Mumaw et al.	9,905,000	B2	2/2018	Chou et al.
9,782,169	B2	10/2017	Kimsey et al.	9,907,196	B2	2/2018	Susini et al.
9,782,212	B2	10/2017	Wham et al.	9,907,550	B2	3/2018	Sniffin et al.
9,782,214	B2	10/2017	Houser et al.	9,913,642	B2	3/2018	Leimbach et al.
9,788,835	B2	10/2017	Morgan et al.	9,913,645	B2	3/2018	Zerkle et al.
9,788,836	B2	10/2017	Overmyer et al.	9,918,326	B2	3/2018	Gilson et al.
9,788,851	B2	10/2017	Dannaher et al.	9,918,730	B2	3/2018	Trees et al.
9,788,902	B2	10/2017	Inoue et al.	9,918,778	B2	3/2018	Walberg et al.
9,788,907	B1	10/2017	Alvi et al.	9,918,788	B2	3/2018	Paul et al.
9,795,436	B2	10/2017	Yates et al.	9,922,304	B2	3/2018	DeBusk et al.
9,797,486	B2	10/2017	Zergiebel et al.	9,924,941	B2	3/2018	Burbank
9,801,531	B2	10/2017	Morita et al.	9,924,944	B2	3/2018	Shelton, IV et al.
9,801,626	B2	10/2017	Parihar et al.	9,924,961	B2	3/2018	Shelton, IV et al.
9,801,627	B2	10/2017	Harris et al.	9,931,040	B2	4/2018	Homyk et al.
9,801,679	B2	10/2017	Trees et al.	9,931,118	B2	4/2018	Shelton, IV et al.
9,802,033	B2	10/2017	Hibner et al.	9,931,124	B2	4/2018	Gokharu
9,804,618	B2	10/2017	Leimbach et al.	9,936,863	B2	4/2018	Tesar
9,805,472	B2	10/2017	Chou et al.	9,936,942	B2	4/2018	Chin et al.
9,808,244	B2	11/2017	Leimbach et al.	9,936,955	B2	4/2018	Miller et al.
9,808,245	B2	11/2017	Richard et al.	9,936,961	B2	4/2018	Chien et al.
9,808,246	B2	11/2017	Shelton, IV et al.	9,937,012	B2	4/2018	Hares et al.
				9,937,014	B2	4/2018	Bowling et al.
				9,937,626	B2	4/2018	Rockrohr
				9,938,972	B2	4/2018	Walley
				9,943,230	B2	4/2018	Kaku et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

9,943,309	B2	4/2018	Shelton, IV et al.	10,102,926	B1	10/2018	Leonardi
9,943,312	B2	4/2018	Posada et al.	10,105,140	B2	10/2018	Malinouskas et al.
9,943,377	B2	4/2018	Yates et al.	10,105,142	B2	10/2018	Baxter, III et al.
9,943,379	B2	4/2018	Gregg, II et al.	10,105,470	B2	10/2018	Reasoner et al.
9,943,918	B2	4/2018	Grogan et al.	10,111,658	B2	10/2018	Chowaniec et al.
9,949,785	B2	4/2018	Price et al.	10,111,665	B2	10/2018	Aranyi et al.
9,962,157	B2	5/2018	Sapre	10,111,679	B2	10/2018	Baber et al.
9,968,355	B2	5/2018	Shelton, IV et al.	10,111,703	B2	10/2018	Cosman, Jr. et al.
9,974,595	B2	5/2018	Anderson et al.	D834,541	S	11/2018	You et al.
9,980,140	B1	5/2018	Spencer et al.	10,117,649	B2	11/2018	Baxter et al.
9,980,769	B2	5/2018	Trees et al.	10,117,651	B2	11/2018	Whitman et al.
9,980,778	B2	5/2018	Ohline et al.	10,117,702	B2	11/2018	Danziger et al.
9,987,000	B2	6/2018	Shelton, IV et al.	10,118,119	B2	11/2018	Sappok et al.
9,987,068	B2	6/2018	Anderson et al.	10,130,359	B2	11/2018	Hess et al.
9,987,072	B2	6/2018	McPherson	10,130,360	B2	11/2018	Olson et al.
9,990,856	B2	6/2018	Kuchenbecker et al.	10,130,361	B2	11/2018	Yates et al.
9,993,248	B2	6/2018	Shelton, IV et al.	10,130,367	B2	11/2018	Cappola et al.
9,993,258	B2	6/2018	Shelton, IV et al.	10,133,248	B2	11/2018	Fitzsimmons et al.
9,993,305	B2	6/2018	Andersson	10,135,242	B2	11/2018	Baber et al.
10,004,491	B2	6/2018	Martin et al.	10,136,887	B2	11/2018	Shelton, IV et al.
10,004,497	B2	6/2018	Overmyer et al.	10,136,891	B2	11/2018	Shelton, IV et al.
10,004,500	B2	6/2018	Shelton, IV et al.	10,136,949	B2	11/2018	Felder et al.
10,004,501	B2	6/2018	Shelton, IV et al.	10,136,954	B2	11/2018	Johnson et al.
10,004,527	B2	6/2018	Gee et al.	10,137,245	B2	11/2018	Melker et al.
10,004,557	B2	6/2018	Gross	10,143,526	B2	12/2018	Walker et al.
D822,206	S	7/2018	Shelton, IV et al.	10,143,948	B2	12/2018	Bonifas et al.
10,010,322	B2	7/2018	Shelton, IV et al.	10,147,148	B2	12/2018	Wu et al.
10,010,324	B2	7/2018	Huitema et al.	10,149,680	B2	12/2018	Parihar et al.
10,013,049	B2	7/2018	Leimbach et al.	10,152,789	B2	12/2018	Carnes et al.
10,016,199	B2	7/2018	Baber et al.	10,154,841	B2	12/2018	Weaner et al.
10,021,318	B2	7/2018	Hugosson et al.	10,159,044	B2	12/2018	Hrabak
10,022,090	B2	7/2018	Whitman	10,159,481	B2	12/2018	Whitman et al.
10,022,120	B2	7/2018	Martin et al.	10,159,483	B2	12/2018	Beckman et al.
10,022,391	B2	7/2018	Ruderman Chen et al.	10,164,466	B2	12/2018	Calderoni
10,022,568	B2	7/2018	Messerly et al.	10,166,025	B2	1/2019	Leimbach et al.
10,028,402	B1	7/2018	Walker	10,166,061	B2	1/2019	Berry et al.
10,028,744	B2	7/2018	Shelton, IV et al.	10,169,862	B2	1/2019	Andre et al.
10,028,761	B2	7/2018	Leimbach et al.	10,172,618	B2	1/2019	Shelton, IV et al.
10,028,788	B2	7/2018	Kang	10,172,687	B2	1/2019	Garbus et al.
10,034,704	B2	7/2018	Asher et al.	10,175,096	B2	1/2019	Dickerson
10,037,641	B2	7/2018	Hyde et al.	10,175,127	B2	1/2019	Collins et al.
10,037,715	B2	7/2018	Toly et al.	10,178,992	B2	1/2019	Wise et al.
D826,405	S	8/2018	Shelton, IV et al.	10,179,413	B2	1/2019	Rockrohr
10,039,546	B2	8/2018	Williams et al.	10,180,463	B2	1/2019	Beckman et al.
10,039,564	B2	8/2018	Hibner et al.	10,182,814	B2	1/2019	Okoniewski
10,039,565	B2	8/2018	Vezzu	10,182,816	B2	1/2019	Shelton, IV et al.
10,039,589	B2	8/2018	Virshek et al.	10,182,818	B2	1/2019	Hensel et al.
10,041,822	B2	8/2018	Zemlok	10,188,385	B2	1/2019	Kerr et al.
10,044,791	B2	8/2018	Kamen et al.	10,189,157	B2	1/2019	Schlegel et al.
10,045,704	B2	8/2018	Fagin et al.	10,190,888	B2	1/2019	Hryb et al.
10,045,776	B2	8/2018	Shelton, IV et al.	10,194,891	B2	2/2019	Jeong et al.
10,045,779	B2	8/2018	Savage et al.	10,194,907	B2	2/2019	Marczyk et al.
10,045,781	B2	8/2018	Cropper et al.	10,194,913	B2	2/2019	Nalagatla et al.
10,045,782	B2	8/2018	Murthy Aravalli	10,194,972	B2	2/2019	Yates et al.
10,045,813	B2	8/2018	Mueller	10,197,803	B2	2/2019	Badiali et al.
10,048,379	B2	8/2018	Markendorf et al.	10,198,965	B2	2/2019	Hart
10,052,044	B2	8/2018	Shelton, IV et al.	10,201,311	B2	2/2019	Chou et al.
10,052,102	B2	8/2018	Baxter, III et al.	10,201,349	B2	2/2019	Leimbach et al.
10,052,104	B2	8/2018	Shelton, IV et al.	10,201,364	B2	2/2019	Leimbach et al.
10,054,441	B2	8/2018	Schorr et al.	10,201,365	B2	2/2019	Boudreaux et al.
10,058,393	B2	8/2018	Bonutti et al.	10,205,708	B1	2/2019	Fletcher et al.
10,069,633	B2	9/2018	Gulati et al.	10,206,605	B2	2/2019	Shelton, IV et al.
10,076,326	B2	9/2018	Yates et al.	10,206,752	B2	2/2019	Hares et al.
10,080,618	B2	9/2018	Marshall et al.	10,213,201	B2	2/2019	Shelton, IV et al.
10,084,833	B2	9/2018	McDonnell et al.	10,213,203	B2	2/2019	Swayze et al.
D831,209	S	10/2018	Huitema et al.	10,213,266	B2	2/2019	Zemlok et al.
10,085,748	B2	10/2018	Morgan et al.	10,213,268	B2	2/2019	Dachs, II
10,085,749	B2	10/2018	Cappola et al.	10,219,491	B2	3/2019	Stiles, Jr. et al.
10,092,355	B1	10/2018	Hannaford et al.	10,220,522	B2	3/2019	Rockrohr
10,095,942	B2	10/2018	Mentese et al.	10,222,750	B2	3/2019	Bang et al.
10,097,578	B2	10/2018	Baldonado et al.	10,226,249	B2	3/2019	Jaworek et al.
10,098,527	B2	10/2018	Weisenburgh, II et al.	10,226,250	B2	3/2019	Beckman et al.
10,098,635	B2	10/2018	Burbank	10,226,254	B2	3/2019	Cabrera et al.
10,098,642	B2	10/2018	Baxter, III et al.	10,226,302	B2	3/2019	Lacal et al.
10,098,705	B2	10/2018	Brisson et al.	10,231,634	B2	3/2019	Zand et al.
				10,231,733	B2	3/2019	Ehrenfels et al.
				10,231,775	B2	3/2019	Shelton, IV et al.
				10,238,413	B2	3/2019	Hibner et al.
				10,245,027	B2	4/2019	Shelton, IV et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

10,245,028 B2	4/2019	Shelton, IV et al.	10,363,037 B2	7/2019	Aronhalt et al.
10,245,029 B2	4/2019	Hunter et al.	10,368,861 B2	8/2019	Baxter, III et al.
10,245,030 B2	4/2019	Hunter et al.	10,368,865 B2	8/2019	Harris et al.
10,245,033 B2	4/2019	Overmyer et al.	10,368,867 B2	8/2019	Harris et al.
10,245,037 B2	4/2019	Conklin et al.	10,368,876 B2	8/2019	Bhatnagar et al.
10,245,038 B2	4/2019	Hopkins et al.	10,368,894 B2	8/2019	Madan et al.
10,245,040 B2	4/2019	Milliman	10,368,903 B2	8/2019	Morales et al.
10,251,661 B2	4/2019	Collings et al.	10,376,263 B2	8/2019	Morgan et al.
10,251,725 B2	4/2019	Valentine et al.	10,376,305 B2	8/2019	Yates et al.
10,258,331 B2	4/2019	Shelton, IV et al.	10,376,337 B2	8/2019	Kilroy et al.
10,258,359 B2	4/2019	Kapadia	10,376,338 B2	8/2019	Taylor et al.
10,258,362 B2	4/2019	Conlon	10,378,893 B2	8/2019	Mankovskii
10,258,363 B2	4/2019	Worrell et al.	10,383,518 B2	8/2019	Abu-Tarif et al.
10,258,415 B2	4/2019	Harrah et al.	10,383,699 B2	8/2019	Kilroy et al.
10,258,418 B2	4/2019	Shelton, IV et al.	10,384,021 B2	8/2019	Koeth et al.
10,258,425 B2	4/2019	Mustufa et al.	10,386,990 B2	8/2019	Shikhman et al.
10,263,171 B2	4/2019	Wiener et al.	10,390,718 B2	8/2019	Chen et al.
10,265,004 B2	4/2019	Yamaguchi et al.	10,390,794 B2	8/2019	Kuroiwa et al.
10,265,035 B2	4/2019	Fehre et al.	10,390,825 B2	8/2019	Shelton, IV et al.
10,265,066 B2	4/2019	Measamer et al.	10,390,831 B2	8/2019	Holsten et al.
10,265,068 B2	4/2019	Harris et al.	10,390,895 B2	8/2019	Henderson et al.
10,265,072 B2	4/2019	Shelton, IV et al.	10,398,348 B2	9/2019	Osadchy et al.
10,265,090 B2	4/2019	Ingmanson et al.	10,398,434 B2	9/2019	Shelton, IV et al.
10,265,130 B2	4/2019	Hess et al.	10,398,517 B2	9/2019	Eckert et al.
10,271,840 B2	4/2019	Sapre	10,398,521 B2	9/2019	Itkowitz et al.
10,271,844 B2	4/2019	Valentine et al.	10,404,521 B2	9/2019	McChord et al.
10,271,850 B2	4/2019	Williams	10,404,801 B2	9/2019	March
10,271,851 B2	4/2019	Shelton, IV et al.	10,405,857 B2	9/2019	Shelton, IV et al.
D847,989 S	5/2019	Shelton, IV et al.	10,405,863 B2	9/2019	Wise et al.
10,278,698 B2	5/2019	Racenet	10,413,291 B2	9/2019	Worthington et al.
10,278,778 B2	5/2019	State et al.	10,413,293 B2	9/2019	Shelton, IV et al.
10,283,220 B2	5/2019	Azizian et al.	10,413,297 B2	9/2019	Harris et al.
10,285,694 B2	5/2019	Viola et al.	10,417,446 B2	9/2019	Takeyama
10,285,698 B2	5/2019	Cappola et al.	10,420,552 B2	9/2019	Shelton, IV et al.
10,285,700 B2	5/2019	Scheib	10,420,558 B2	9/2019	Nalagatla et al.
10,285,705 B2	5/2019	Shelton, IV et al.	10,420,559 B2	9/2019	Marczyk et al.
10,292,704 B2	5/2019	Harris et al.	10,420,620 B2	9/2019	Rockrohr
10,292,707 B2	5/2019	Shelton, IV et al.	10,420,865 B2	9/2019	Reasoner et al.
10,292,758 B2	5/2019	Boudreaux et al.	10,422,727 B2	9/2019	Pliskin
10,292,769 B1	5/2019	Yu	10,426,466 B2	10/2019	Contini et al.
10,292,771 B2	5/2019	Wood et al.	10,426,467 B2	10/2019	Miller et al.
10,293,129 B2	5/2019	Fox et al.	10,426,468 B2	10/2019	Contini et al.
10,299,792 B2	5/2019	Huitema et al.	10,426,471 B2	10/2019	Shelton, IV et al.
10,299,870 B2	5/2019	Connolly et al.	10,426,481 B2	10/2019	Aronhalt et al.
10,305,926 B2	5/2019	Mihan et al.	10,433,837 B2	10/2019	Worthington et al.
D850,617 S	6/2019	Shelton, IV et al.	10,433,844 B2	10/2019	Shelton, IV et al.
10,307,159 B2	6/2019	Harris et al.	10,433,849 B2	10/2019	Shelton, IV et al.
10,307,170 B2	6/2019	Parfett et al.	10,433,918 B2	10/2019	Shelton, IV et al.
10,307,199 B2	6/2019	Farritor et al.	10,441,279 B2	10/2019	Shelton, IV et al.
10,311,036 B1	6/2019	Hussam et al.	10,441,345 B2	10/2019	Aldridge et al.
10,313,137 B2	6/2019	Aarnio et al.	10,448,948 B2	10/2019	Shelton, IV et al.
10,314,577 B2	6/2019	Laurent et al.	10,448,950 B2	10/2019	Shelton, IV et al.
10,314,582 B2	6/2019	Shelton, IV et al.	10,456,137 B2	10/2019	Vendely et al.
10,321,907 B2	6/2019	Shelton, IV et al.	10,456,140 B2	10/2019	Shelton, IV et al.
10,321,964 B2	6/2019	Grover et al.	10,456,193 B2	10/2019	Yates et al.
10,327,764 B2	6/2019	Harris et al.	10,463,365 B2	11/2019	Williams
10,327,779 B2	6/2019	Richard et al.	10,463,367 B2	11/2019	Kostrzewski et al.
10,335,147 B2	7/2019	Rector et al.	10,463,371 B2	11/2019	Kostrzewski
10,335,149 B2	7/2019	Baxter, III et al.	10,463,436 B2	11/2019	Jackson et al.
10,335,180 B2	7/2019	Johnson et al.	10,470,762 B2	11/2019	Leimbach et al.
10,335,227 B2	7/2019	Heard	10,470,764 B2	11/2019	Baxter, III et al.
10,339,496 B2	7/2019	Matson et al.	10,470,768 B2	11/2019	Harris et al.
10,342,543 B2	7/2019	Shelton, IV et al.	10,470,791 B2	11/2019	Houser
10,342,602 B2	7/2019	Strobl et al.	10,471,254 B2	11/2019	Sano et al.
10,342,623 B2	7/2019	Huelman et al.	10,478,181 B2	11/2019	Shelton, IV et al.
10,343,102 B2	7/2019	Reasoner et al.	10,478,185 B2	11/2019	Nicholas
10,349,824 B2	7/2019	Claude et al.	10,478,189 B2	11/2019	Bear et al.
10,349,939 B2	7/2019	Shelton, IV et al.	10,478,190 B2	11/2019	Miller et al.
10,349,941 B2	7/2019	Marczyk et al.	10,478,544 B2	11/2019	Friederichs et al.
10,350,016 B2	7/2019	Burbank et al.	10,485,450 B2	11/2019	Gupta et al.
10,357,184 B2	7/2019	Crawford et al.	10,485,542 B2	11/2019	Shelton, IV et al.
10,357,246 B2	7/2019	Shelton, IV et al.	10,485,543 B2	11/2019	Shelton, IV et al.
10,357,247 B2	7/2019	Shelton, IV et al.	10,492,783 B2	12/2019	Shelton, IV et al.
10,362,179 B2	7/2019	Harris	10,492,784 B2	12/2019	Beardsley et al.
10,363,032 B2	7/2019	Scheib et al.	10,492,785 B2	12/2019	Overmyer et al.
			10,496,788 B2	12/2019	Amarasingham et al.
			10,498,269 B2	12/2019	Zemlok et al.
			10,499,847 B2	12/2019	Latimer et al.
			10,499,891 B2	12/2019	Chaplin et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

10,499,914	B2	12/2019	Huang et al.	10,631,858	B2	4/2020	Burbank
10,499,915	B2	12/2019	Aranyi	10,631,912	B2	4/2020	McFarlin et al.
10,499,994	B2	12/2019	Luks et al.	10,631,916	B2	4/2020	Horner et al.
10,507,068	B2	12/2019	Kopp et al.	10,631,917	B2	4/2020	Ineson
10,512,413	B2	12/2019	Schepis et al.	10,631,939	B2	4/2020	Dachs, II et al.
10,512,461	B2	12/2019	Gupta et al.	10,639,027	B2	5/2020	Shelton, IV et al.
10,512,499	B2*	12/2019	McHenry ..... A61B 18/1445	10,639,034	B2	5/2020	Harris et al.
10,512,514	B2	12/2019	Nowlin et al.	10,639,035	B2	5/2020	Shelton, IV et al.
10,517,588	B2	12/2019	Gupta et al.	10,639,036	B2	5/2020	Yates et al.
10,517,595	B2	12/2019	Hunter et al.	10,639,037	B2	5/2020	Shelton, IV et al.
10,517,596	B2	12/2019	Hunter et al.	10,639,039	B2	5/2020	Vendely et al.
10,517,686	B2	12/2019	Vokrot et al.	10,639,098	B2	5/2020	Cosman et al.
10,524,789	B2	1/2020	Swayze et al.	10,639,111	B2	5/2020	Kopp
10,531,579	B2	1/2020	Hsiao et al.	10,639,185	B2	5/2020	Agrawal et al.
10,531,874	B2	1/2020	Morgan et al.	10,653,413	B2	5/2020	Worthington et al.
10,531,929	B2	1/2020	Widenhouse et al.	10,653,476	B2	5/2020	Ross
10,532,330	B2	1/2020	Diallo et al.	10,653,489	B2	5/2020	Kopp
10,536,617	B2	1/2020	Liang et al.	10,656,720	B1	5/2020	Holz
10,537,324	B2	1/2020	Shelton, IV et al.	10,660,705	B2	5/2020	Piron et al.
10,537,325	B2	1/2020	Bakos et al.	10,667,809	B2	6/2020	Bakos et al.
10,537,351	B2	1/2020	Shelton, IV et al.	10,667,810	B2	6/2020	Shelton, IV et al.
10,542,978	B2	1/2020	Chowaniec et al.	10,667,811	B2	6/2020	Harris et al.
10,542,979	B2	1/2020	Shelton, IV et al.	10,667,877	B2	6/2020	Kapadia
10,542,982	B2	1/2020	Beckman et al.	10,674,897	B2	6/2020	Levy
10,542,991	B2	1/2020	Shelton, IV et al.	10,675,021	B2	6/2020	Harris et al.
D876,466	S	2/2020	Kobayashi et al.	10,675,023	B2	6/2020	Cappola
10,548,504	B2	2/2020	Shelton, IV et al.	10,675,024	B2	6/2020	Shelton, IV et al.
10,548,612	B2	2/2020	Martinez et al.	10,675,025	B2	6/2020	Swayze et al.
10,548,673	B2	2/2020	Harris et al.	10,675,026	B2	6/2020	Harris et al.
10,552,574	B2	2/2020	Sweeney	10,675,035	B2	6/2020	Zingman
10,555,675	B2	2/2020	Satish et al.	10,675,100	B2	6/2020	Frushour
10,555,748	B2	2/2020	Yates et al.	10,675,104	B2	6/2020	Kapadia
10,555,750	B2	2/2020	Conlon et al.	10,677,764	B2	6/2020	Ross et al.
10,555,769	B2	2/2020	Worrell et al.	10,679,758	B2	6/2020	Fox et al.
10,561,422	B2	2/2020	Schellin et al.	10,682,136	B2	6/2020	Harris et al.
10,561,471	B2	2/2020	Nichogi	10,682,138	B2	6/2020	Shelton, IV et al.
10,561,753	B2	2/2020	Thompson et al.	10,686,805	B2	6/2020	Reybok, Jr. et al.
10,568,625	B2	2/2020	Harris et al.	10,687,806	B2	6/2020	Shelton, IV et al.
10,568,626	B2	2/2020	Shelton, IV et al.	10,687,809	B2	6/2020	Shelton, IV et al.
10,568,632	B2	2/2020	Miller et al.	10,687,810	B2	6/2020	Shelton, IV et al.
10,568,704	B2	2/2020	Savall et al.	10,687,884	B2	6/2020	Wiener et al.
10,575,868	B2	3/2020	Hall et al.	10,687,905	B2	6/2020	Kostrzewski
10,582,928	B2	3/2020	Hunter et al.	10,695,055	B2	6/2020	Shelton, IV et al.
10,582,931	B2	3/2020	Mujawar	10,695,081	B2	6/2020	Shelton, IV et al.
10,582,964	B2	3/2020	Weinberg et al.	10,695,134	B2	6/2020	Barral et al.
10,586,074	B2	3/2020	Rose et al.	10,702,270	B2	7/2020	Shelton, IV et al.
10,588,623	B2	3/2020	Schmid et al.	10,702,271	B2	7/2020	Aranyi et al.
10,588,625	B2	3/2020	Weaner et al.	10,709,446	B2	7/2020	Harris et al.
10,588,629	B2	3/2020	Malinouskas et al.	10,716,489	B2	7/2020	Kalvoy et al.
10,588,630	B2	3/2020	Shelton, IV et al.	10,716,615	B2	7/2020	Shelton, IV et al.
10,588,631	B2	3/2020	Shelton, IV et al.	10,716,639	B2	7/2020	Kapadia et al.
10,588,632	B2	3/2020	Shelton, IV et al.	10,717,194	B2	7/2020	Griffiths et al.
10,588,711	B2	3/2020	DiCarlo et al.	10,722,222	B2	7/2020	Aranyi
10,592,067	B2	3/2020	Merdan et al.	10,722,233	B2	7/2020	Wellman
10,595,844	B2	3/2020	Nawana et al.	10,722,292	B2	7/2020	Arya et al.
10,595,882	B2	3/2020	Parfett et al.	D893,717	S	8/2020	Messery et al.
10,595,887	B2	3/2020	Shelton, IV et al.	10,729,458	B2	8/2020	Stoddard et al.
10,595,930	B2	3/2020	Scheib et al.	10,729,509	B2	8/2020	Shelton, IV et al.
10,595,952	B2	3/2020	Forrest et al.	10,733,267	B2	8/2020	Pedersen
10,602,007	B2	3/2020	Takano	10,736,219	B2	8/2020	Seow et al.
10,602,848	B2	3/2020	Magana	10,736,616	B2	8/2020	Scheib et al.
10,603,036	B2	3/2020	Hunter et al.	10,736,628	B2	8/2020	Yates et al.
10,603,128	B2	3/2020	Zergiebel et al.	10,736,629	B2	8/2020	Shelton, IV et al.
10,610,223	B2	4/2020	Wellman et al.	10,736,636	B2	8/2020	Baxter, III et al.
10,610,224	B2	4/2020	Shelton, IV et al.	10,736,705	B2	8/2020	Scheib et al.
10,610,286	B2	4/2020	Wiener et al.	10,743,872	B2	8/2020	Leimbach et al.
10,610,313	B2	4/2020	Bailey et al.	10,748,115	B2	8/2020	Laster et al.
10,617,412	B2	4/2020	Shelton, IV et al.	10,751,052	B2	8/2020	Stokes et al.
10,617,414	B2	4/2020	Shelton, IV et al.	10,751,136	B2	8/2020	Farritor et al.
10,617,482	B2	4/2020	Houser et al.	10,751,768	B2	8/2020	Hersey et al.
10,617,484	B2	4/2020	Kilroy et al.	10,755,813	B2	8/2020	Shelton, IV et al.
10,624,635	B2	4/2020	Harris et al.	D896,379	S	9/2020	Shelton, IV et al.
10,624,667	B2	4/2020	Faller et al.	10,758,229	B2	9/2020	Shelton, IV et al.
10,624,691	B2	4/2020	Wiener et al.	10,758,230	B2	9/2020	Shelton, IV et al.
10,631,423	B2	4/2020	Collins et al.	10,758,294	B2	9/2020	Jones
				10,758,310	B2	9/2020	Shelton, IV et al.
				10,765,376	B2	9/2020	Brown, III et al.
				10,765,424	B2	9/2020	Baxter, III et al.
				10,765,427	B2	9/2020	Shelton, IV et al.

(56)		References Cited					
		U.S. PATENT DOCUMENTS					
10,765,470	B2	9/2020	Yates et al.	10,912,619	B2	2/2021	Jarc et al.
10,772,630	B2	9/2020	Wixey	10,916,415	B2	2/2021	Karancsi et al.
10,772,651	B2	9/2020	Shelton, IV et al.	10,918,385	B2	2/2021	Overmyer et al.
10,772,673	B2	9/2020	Allen, IV et al.	10,930,400	B2	2/2021	Robbins et al.
10,772,688	B2	9/2020	Peine et al.	D914,878	S	3/2021	Shelton, IV et al.
10,779,818	B2	9/2020	Zemlok et al.	10,932,784	B2	3/2021	Mozdzierz et al.
10,779,821	B2	9/2020	Harris et al.	10,950,982	B2	3/2021	Regnier et al.
10,779,823	B2	9/2020	Shelton, IV et al.	11,000,276	B2	5/2021	Shelton, IV et al.
10,779,897	B2	9/2020	Rockrohr	11,051,817	B2	7/2021	Shelton, IV et al.
10,779,900	B2	9/2020	Pedros et al.	11,058,501	B2	7/2021	Tokarchuk et al.
10,783,634	B2	9/2020	Nye et al.	11,071,595	B2	7/2021	Johnson et al.
10,786,298	B2	9/2020	Johnson	11,141,213	B2	10/2021	Yates et al.
10,786,317	B2	9/2020	Zhou et al.	11,185,325	B2	11/2021	Shelton, IV et al.
10,786,327	B2	9/2020	Anderson et al.	11,218,822	B2	1/2022	Morgan et al.
10,792,038	B2	10/2020	Becerra et al.	D950,728	S	5/2022	Bakos et al.
10,792,118	B2	10/2020	Prpa et al.	D952,144	S	5/2022	Boudreaux
10,792,422	B2	10/2020	Douglas et al.	2001/0056237	A1	12/2001	Cane et al.
10,799,304	B2	10/2020	Kapadia et al.	2002/0049551	A1	4/2002	Friedman et al.
10,803,977	B2	10/2020	Sanmugalingham	2002/0052616	A1	5/2002	Wiener et al.
10,806,445	B2	10/2020	Penna et al.	2002/0072746	A1	6/2002	Lingenfelder et al.
10,806,453	B2	10/2020	Chen et al.	2002/0138642	A1	9/2002	Miyazawa et al.
10,806,454	B2	10/2020	Kopp	2002/0169584	A1	11/2002	Fu et al.
10,806,499	B2	10/2020	Castaneda et al.	2003/0009111	A1	1/2003	Cory et al.
10,806,506	B2*	10/2020	Gaspredes .....	2003/0018329	A1	1/2003	Hooven
10,806,532	B2	10/2020	Grubbs et al.	2003/0046109	A1	3/2003	Uchikubo
10,813,638	B2	10/2020	Shelton, IV et al.	2003/0069573	A1	4/2003	Kadhiresan et al.
10,813,703	B2	10/2020	Swayze et al.	2003/0093503	A1	5/2003	Yamaki et al.
10,818,383	B2	10/2020	Sharifi Sedeh et al.	2003/0114851	A1	6/2003	Truckai et al.
10,828,028	B2	11/2020	Harris et al.	2003/0130711	A1*	7/2003	Pearson .....
10,828,030	B2	11/2020	Weir et al.				A61B 18/1445
10,835,245	B2	11/2020	Swayze et al.	2003/0210812	A1	11/2003	Khamene et al.
10,835,246	B2	11/2020	Shelton, IV et al.	2003/0223877	A1	12/2003	Anstine et al.
10,835,247	B2	11/2020	Shelton, IV et al.	2004/0015053	A1	1/2004	Bieger et al.
10,842,473	B2	11/2020	Scheib et al.	2004/0078236	A1	4/2004	Stoodley et al.
10,842,490	B2	11/2020	DiNardo et al.	2004/0108825	A1	6/2004	Lee et al.
10,842,492	B2	11/2020	Shelton, IV et al.	2004/0199180	A1	10/2004	Knodel et al.
10,842,522	B2	11/2020	Messerly et al.	2004/0199659	A1	10/2004	Ishikawa et al.
10,842,523	B2	11/2020	Shelton, IV et al.	2004/0206365	A1	10/2004	Knowlton
10,842,575	B2	11/2020	Panescu et al.	2004/0229496	A1	11/2004	Robinson et al.
10,842,897	B2	11/2020	Schwartz et al.	2004/0243147	A1	12/2004	Lipow
D904,612	S	12/2020	Wynn et al.	2004/0243148	A1	12/2004	Wasielewski
10,849,697	B2	12/2020	Yates et al.	2004/0243435	A1	12/2004	Williams
10,849,700	B2	12/2020	Kopp et al.	2005/0020909	A1	1/2005	Moctezuma de la Barrera et al.
10,856,768	B2	12/2020	Osadchy et al.	2005/0020918	A1	1/2005	Wilk et al.
10,856,867	B2	12/2020	Shelton, IV et al.	2005/0021027	A1	1/2005	Shields et al.
10,856,868	B2	12/2020	Shelton, IV et al.	2005/0023324	A1	2/2005	Doll et al.
10,856,870	B2	12/2020	Harris et al.	2005/0063575	A1	3/2005	Ma et al.
10,863,984	B2	12/2020	Shelton, IV et al.	2005/0065438	A1	3/2005	Miller
10,864,037	B2	12/2020	Mun et al.	2005/0070800	A1	3/2005	Takahashi
10,864,050	B2	12/2020	Tabandeh et al.	2005/0100867	A1	5/2005	Hilscher et al.
10,872,684	B2	12/2020	McNutt et al.	2005/0131390	A1	6/2005	Heinrich et al.
10,881,399	B2	1/2021	Shelton, IV et al.	2005/0139629	A1	6/2005	Schwemberger et al.
10,881,401	B2	1/2021	Baber et al.	2005/0143759	A1	6/2005	Kelly
10,881,446	B2	1/2021	Strobl	2005/0149001	A1	7/2005	Uchikubo et al.
10,881,464	B2	1/2021	Odermatt et al.	2005/0149356	A1	7/2005	Cyr et al.
10,888,321	B2	1/2021	Shelton, IV et al.	2005/0165390	A1	7/2005	Mauti et al.
10,888,322	B2	1/2021	Morgan et al.	2005/0182655	A1	8/2005	Merzlak et al.
10,892,899	B2	1/2021	Shelton, IV et al.	2005/0192633	A1	9/2005	Montpetit
10,892,995	B2	1/2021	Shelton, IV et al.	2005/0203380	A1	9/2005	Sauer et al.
10,893,863	B2	1/2021	Shelton, IV et al.	2005/0203384	A1	9/2005	Sati et al.
10,893,864	B2	1/2021	Harris et al.	2005/0203504	A1	9/2005	Wham et al.
10,893,884	B2	1/2021	Stoddard et al.	2005/0222631	A1	10/2005	Dalal et al.
10,898,183	B2	1/2021	Shelton, IV et al.	2005/0228246	A1	10/2005	Lee et al.
10,898,186	B2	1/2021	Bakos et al.	2005/0228425	A1	10/2005	Boukhny et al.
10,898,189	B2	1/2021	McDonald, II	2005/0236474	A1	10/2005	Onuma et al.
10,898,280	B2	1/2021	Kopp	2005/0251233	A1	11/2005	Kanzius
10,898,622	B2	1/2021	Shelton, IV et al.	2005/0277913	A1	12/2005	McCary
10,902,944	B1	1/2021	Casey et al.	2006/0020272	A1	1/2006	Gildenberg
10,903,685	B2	1/2021	Yates et al.	2006/0025816	A1	2/2006	Shelton
10,905,415	B2	2/2021	DiNardo et al.	2006/0059018	A1	3/2006	Shiobara et al.
10,905,418	B2	2/2021	Shelton, IV et al.	2006/0069388	A1	3/2006	Truckai et al.
10,905,420	B2	2/2021	Jasemian et al.	2006/0079872	A1	4/2006	Eggleston
10,912,559	B2	2/2021	Harris et al.	2006/0079874	A1	4/2006	Faller et al.
10,912,567	B2	2/2021	Shelton, IV et al.	2006/0116908	A1	6/2006	Dew et al.
10,912,580	B2	2/2021	Green et al.	2006/0136622	A1	6/2006	Rouvelin et al.
				2006/0184160	A1	8/2006	Ozaki et al.
				2006/0241399	A1	10/2006	Fabian
				2006/0282009	A1	12/2006	Oberg et al.
				2007/0010838	A1	1/2007	Shelton et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2007/0016235	A1	1/2007	Tanaka et al.	2009/0299214	A1	12/2009	Wu et al.
2007/0016979	A1	1/2007	Damaj et al.	2009/0306581	A1	12/2009	Claus
2007/0027459	A1	2/2007	Horvath et al.	2009/0307681	A1	12/2009	Armado et al.
2007/0038080	A1	2/2007	Salisbury et al.	2009/0326321	A1	12/2009	Jacobsen et al.
2007/0049947	A1	3/2007	Menn et al.	2009/0326336	A1	12/2009	Lemke et al.
2007/0066970	A1	3/2007	Ineson	2010/0036374	A1	2/2010	Ward
2007/0078678	A1	4/2007	DiSilvestro et al.	2010/0036405	A1	2/2010	Giordano et al.
2007/0084896	A1	4/2007	Doll et al.	2010/0038403	A1	2/2010	D'Arcangelo
2007/0085528	A1	4/2007	Govari et al.	2010/0057106	A1	3/2010	Sorrentino et al.
2007/0156019	A1	7/2007	Larkin et al.	2010/0065604	A1	3/2010	Weng
2007/0167702	A1	7/2007	Hasser et al.	2010/0069939	A1	3/2010	Konishi
2007/0168461	A1	7/2007	Moore	2010/0069942	A1	3/2010	Shelton, IV
2007/0173803	A1	7/2007	Wham et al.	2010/0070417	A1	3/2010	Flynn et al.
2007/0175955	A1	8/2007	Shelton et al.	2010/0120266	A1	5/2010	Rimborg
2007/0179482	A1	8/2007	Anderson	2010/0132334	A1	6/2010	Duclos et al.
2007/0179508	A1	8/2007	Arndt	2010/0137845	A1	6/2010	Ramstein et al.
2007/0191713	A1	8/2007	Eichmann et al.	2010/0137886	A1	6/2010	Zergiebel et al.
2007/0203744	A1	8/2007	Scholl	2010/0168561	A1	7/2010	Anderson
2007/0225556	A1	9/2007	Ortiz et al.	2010/0179831	A1	7/2010	Brown et al.
2007/0225690	A1	9/2007	Sekiguchi et al.	2010/0191100	A1	7/2010	Anderson et al.
2007/0239028	A1	10/2007	Houser et al.	2010/0198200	A1	8/2010	Horvath
2007/0244478	A1	10/2007	Bahney	2010/0198248	A1	8/2010	Vakharia
2007/0249990	A1	10/2007	Cosmescu	2010/0204717	A1	8/2010	Knodel
2007/0270660	A1	11/2007	Caylor et al.	2010/0217991	A1	8/2010	Choi
2007/0282195	A1	12/2007	Masini et al.	2010/0234996	A1	9/2010	Schreiber et al.
2007/0282321	A1	12/2007	Shah et al.	2010/0235689	A1	9/2010	Tian et al.
2007/0282333	A1	12/2007	Fortson et al.	2010/0250571	A1	9/2010	Pierce et al.
2007/0293218	A1	12/2007	Meylan et al.	2010/0258327	A1	10/2010	Esenwein et al.
2008/0013460	A1	1/2008	Allen et al.	2010/0292535	A1	11/2010	Paskar
2008/0015664	A1	1/2008	Podhajsky	2010/0292684	A1	11/2010	Cybulski et al.
2008/0015912	A1	1/2008	Rosenthal et al.	2010/0301095	A1	12/2010	Shelton, IV et al.
2008/0033404	A1	2/2008	Romoda et al.	2011/0022032	A1	1/2011	Zemlok et al.
2008/0040151	A1	2/2008	Moore	2011/0036890	A1	2/2011	Ma
2008/0058593	A1	3/2008	Gu et al.	2011/0071530	A1	3/2011	Carson
2008/0059658	A1	3/2008	Williams	2011/0077512	A1	3/2011	Boswell
2008/0077158	A1	3/2008	Haider et al.	2011/0087238	A1	4/2011	Wang et al.
2008/0083414	A1	4/2008	Messerges	2011/0087502	A1	4/2011	Yelton et al.
2008/0091071	A1	4/2008	Kumar et al.	2011/0105895	A1	5/2011	Kornblau et al.
2008/0114212	A1	5/2008	Messerges	2011/0112569	A1	5/2011	Friedman et al.
2008/0114350	A1	5/2008	Park et al.	2011/0118708	A1	5/2011	Burbank et al.
2008/0129465	A1	6/2008	Rao	2011/0119075	A1	5/2011	Dhoble
2008/0140090	A1	6/2008	Aranyi et al.	2011/0125149	A1	5/2011	El-Galley et al.
2008/0167644	A1	7/2008	Shelton et al.	2011/0152712	A1	6/2011	Cao et al.
2008/0177258	A1	7/2008	Govari et al.	2011/0163147	A1	7/2011	Laurent et al.
2008/0177362	A1	7/2008	Phillips et al.	2011/0166883	A1	7/2011	Palmer et al.
2008/0200940	A1	8/2008	Eichmann et al.	2011/0196398	A1	8/2011	Robertson et al.
2008/0234708	A1	9/2008	Houser et al.	2011/0237883	A1	9/2011	Chun
2008/0235052	A1	9/2008	Node-Langlois et al.	2011/0251612	A1	10/2011	Faller et al.
2008/0255413	A1	10/2008	Zemlok et al.	2011/0264000	A1	10/2011	Paul et al.
2008/0262654	A1	10/2008	Omori et al.	2011/0264078	A1	10/2011	Lipow et al.
2008/0272172	A1	11/2008	Zemlok et al.	2011/0273465	A1	11/2011	Konishi et al.
2008/0281301	A1	11/2008	DeBoer et al.	2011/0278343	A1	11/2011	Knodel et al.
2008/0281678	A1	11/2008	Keuls et al.	2011/0290024	A1	12/2011	Lefler
2008/0296346	A1	12/2008	Shelton, IV et al.	2011/0295270	A1	12/2011	Giordano et al.
2008/0306759	A1	12/2008	Ilkin et al.	2011/0306840	A1	12/2011	Allen et al.
2008/0312953	A1	12/2008	Claus	2012/0012638	A1	1/2012	Huang et al.
2009/0017910	A1	1/2009	Rofougaran et al.	2012/0021684	A1	1/2012	Schultz et al.
2009/0030437	A1	1/2009	Houser et al.	2012/0022519	A1	1/2012	Huang et al.
2009/0036750	A1	2/2009	Weinstein et al.	2012/0029354	A1	2/2012	Mark et al.
2009/0036794	A1	2/2009	Stubhaug et al.	2012/0046662	A1	2/2012	Gilbert
2009/0043253	A1	2/2009	Podaima	2012/0059684	A1	3/2012	Hampapur et al.
2009/0046146	A1	2/2009	Hoyt	2012/0078247	A1	3/2012	Worrell et al.
2009/0048589	A1	2/2009	Takashino et al.	2012/0080336	A1	4/2012	Shelton, IV et al.
2009/0048611	A1	2/2009	Funda et al.	2012/0083786	A1	4/2012	Artale et al.
2009/0076409	A1	3/2009	Wu et al.	2012/0100517	A1	4/2012	Bowditch et al.
2009/0090763	A1	4/2009	Zemlok et al.	2012/0101488	A1	4/2012	Aldridge et al.
2009/0099866	A1	4/2009	Newman	2012/0116265	A1	5/2012	Houser et al.
2009/0114699	A1	5/2009	Viola	2012/0116381	A1	5/2012	Houser et al.
2009/0128084	A1	5/2009	Johnson et al.	2012/0116394	A1	5/2012	Timm et al.
2009/0182577	A1	7/2009	Squilla et al.	2012/0130217	A1	5/2012	Kauphusman et al.
2009/0206131	A1	8/2009	Weisenburgh, II et al.	2012/0145714	A1	6/2012	Farascioni et al.
2009/0217932	A1	9/2009	Voegelé	2012/0172696	A1	7/2012	Kallback et al.
2009/0234352	A1	9/2009	Behnke et al.	2012/0190981	A1	7/2012	Harris et al.
2009/0259149	A1	10/2009	Tahara et al.	2012/0191091	A1	7/2012	Allen
2009/0259221	A1	10/2009	Tahara et al.	2012/0191162	A1	7/2012	Villa
				2012/0197619	A1	8/2012	Namer Yelin et al.
				2012/0203067	A1	8/2012	Higgins et al.
				2012/0203785	A1	8/2012	Awada
				2012/0211542	A1	8/2012	Racenet

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0226150	A1	9/2012	Balicki et al.	2014/0243809	A1	8/2014	Gelfand et al.	
2012/0245958	A1	9/2012	Lawrence et al.	2014/0243811	A1	8/2014	Reschke et al.	
2012/0253329	A1	10/2012	Zemlok et al.	2014/0246475	A1	9/2014	Hall et al.	
2012/0253847	A1	10/2012	Dell'Anno et al.	2014/0249557	A1	9/2014	Koch et al.	
2012/0265555	A1	10/2012	Cappuzzo et al.	2014/0252064	A1	9/2014	Mozdzierz et al.	
2012/0292367	A1	11/2012	Morgan et al.	2014/0263541	A1	9/2014	Leimbach et al.	
2012/0319859	A1	12/2012	Taub et al.	2014/0263552	A1	9/2014	Hall et al.	
2013/0001121	A1	1/2013	Metzger	2014/0275760	A1	9/2014	Lee et al.	
2013/0006241	A1	1/2013	Takashino	2014/0276749	A1	9/2014	Johnson	
2013/0008677	A1	1/2013	Huifu	2014/0287393	A1	9/2014	Kumar et al.	
2013/0024213	A1	1/2013	Poon	2014/0303660	A1	10/2014	Boyden et al.	
2013/0046182	A1	2/2013	Hegg et al.	2014/0303990	A1	10/2014	Schoenefeld et al.	
2013/0046279	A1	2/2013	Niklewski et al.	2014/0336943	A1	11/2014	Pellini et al.	
2013/0046295	A1	2/2013	Kerr et al.	2014/0337052	A1	11/2014	Pellini et al.	
2013/0066647	A1	3/2013	Andrie et al.	2014/0364691	A1	12/2014	Krivopisk et al.	
2013/0090526	A1	4/2013	Suzuki et al.	2015/0006201	A1	1/2015	Pait et al.	
2013/0093829	A1	4/2013	Rosenblatt et al.	2015/0025549	A1	1/2015	Kilroy et al.	
2013/0096597	A1	4/2013	Anand et al.	2015/0032150	A1	1/2015	Ishida et al.	
2013/0116218	A1	5/2013	Kaplan et al.	2015/0051452	A1	2/2015	Ciaccio	
2013/0144284	A1	6/2013	Behnke, II et al.	2015/0051598	A1	2/2015	Orszulak et al.	
2013/0165776	A1	6/2013	Blomqvist	2015/0051617	A1	2/2015	Takemura et al.	
2013/0178853	A1	7/2013	Hyink et al.	2015/0053737	A1	2/2015	Leimbach et al.	
2013/0191647	A1	7/2013	Ferrara, Jr. et al.	2015/0053743	A1	2/2015	Yates et al.	
2013/0193188	A1	8/2013	Shelton, IV et al.	2015/0057675	A1	2/2015	Akeel et al.	
2013/0197531	A1	8/2013	Boukhny et al.	2015/0066000	A1	3/2015	An et al.	
2013/0206813	A1	8/2013	Nalagatla	2015/0070187	A1	3/2015	Wiesner et al.	
2013/0214025	A1	8/2013	Zemlok et al.	2015/0073400	A1*	3/2015	Sverdluk	A61B 18/082 606/28
2013/0253480	A1	9/2013	Kimball et al.	2015/0077528	A1	3/2015	Awdeh	
2013/0256373	A1	10/2013	Schmid et al.	2015/0083774	A1	3/2015	Measamer et al.	
2013/0267874	A1	10/2013	Marcotte et al.	2015/0108198	A1	4/2015	Estrella	
2013/0268283	A1	10/2013	Vann et al.	2015/0133945	A1	5/2015	Dushyant et al.	
2013/0277410	A1	10/2013	Fernandez et al.	2015/0136833	A1	5/2015	Shelton, IV et al.	
2013/0317837	A1	11/2013	Ballantyne et al.	2015/0140982	A1	5/2015	Postrel	
2013/0321425	A1	12/2013	Greene et al.	2015/0145682	A1	5/2015	Harris	
2013/0325809	A1	12/2013	Kim et al.	2015/0148830	A1	5/2015	Stulen et al.	
2013/0331873	A1	12/2013	Ross et al.	2015/0157354	A1*	6/2015	Bales, Jr.	A61B 50/20 606/169
2013/0331874	A1*	12/2013	Ross	2015/0173673	A1	6/2015	Toth et al.	
			..... A61B 17/320092	2015/0173756	A1	6/2015	Baxter, III et al.	
			606/169	2015/0182220	A1	7/2015	Yates et al.	
2013/0331875	A1	12/2013	Ross et al.	2015/0196295	A1	7/2015	Shelton, IV et al.	
2014/0001231	A1	1/2014	Shelton, IV et al.	2015/0199109	A1	7/2015	Lee	
2014/0001234	A1	1/2014	Shelton, IV et al.	2015/0202014	A1	7/2015	Kim et al.	
2014/0005640	A1	1/2014	Shelton, IV et al.	2015/0208934	A1	7/2015	Sztrubel et al.	
2014/0006132	A1	1/2014	Barker	2015/0223725	A1	8/2015	Engel et al.	
2014/0009894	A1	1/2014	Yu	2015/0223868	A1	8/2015	Brandt et al.	
2014/0013565	A1	1/2014	MacDonald et al.	2015/0237502	A1	8/2015	Schmidt et al.	
2014/0018788	A1	1/2014	Engelman et al.	2015/0238355	A1	8/2015	Vezzu et al.	
2014/0029411	A1	1/2014	Nayak et al.	2015/0272557	A1	10/2015	Overmyer et al.	
2014/0033926	A1	2/2014	Fassel et al.	2015/0272571	A1	10/2015	Leimbach et al.	
2014/0033762	A1	2/2014	Shelton, IV et al.	2015/0272580	A1	10/2015	Leimbach et al.	
2014/0066700	A1	3/2014	Wilson et al.	2015/0272582	A1	10/2015	Leimbach et al.	
2014/0073893	A1	3/2014	Bencini	2015/0272694	A1	10/2015	Charles	
2014/0074076	A1	3/2014	Gertner	2015/0282821	A1	10/2015	Look et al.	
2014/0081255	A1	3/2014	Johnson et al.	2015/0297200	A1	10/2015	Fitzsimmons et al.	
2014/0081659	A1	3/2014	Nawana et al.	2015/0297222	A1	10/2015	Huitema et al.	
2014/0084949	A1*	3/2014	Smith	2015/0297228	A1	10/2015	Huitema et al.	
			..... A61B 8/4281	2015/0297233	A1	10/2015	Huitema et al.	
			324/693	2015/0297311	A1	10/2015	Tesar	
2014/0087999	A1	3/2014	Kaplan et al.	2015/0302157	A1	10/2015	Collar et al.	
2014/0092089	A1	4/2014	Kasuya et al.	2015/0310174	A1	10/2015	Coudert et al.	
2014/0107697	A1	4/2014	Patani et al.	2015/0313538	A1	11/2015	Bechtel et al.	
2014/0108035	A1	4/2014	Akbay et al.	2015/0317899	A1	11/2015	Dumbauld et al.	
2014/0108983	A1	4/2014	William R. et al.	2015/0320423	A1	11/2015	Aranyi	
2014/0117256	A1	5/2014	Mueller et al.	2015/0324114	A1	11/2015	Hurley et al.	
2014/0121669	A1	5/2014	Claus	2015/0328474	A1	11/2015	Flyash et al.	
2014/0148729	A1	5/2014	Schmitz et al.	2015/0332003	A1	11/2015	Stamm et al.	
2014/0148803	A1	5/2014	Taylor	2015/0332196	A1	11/2015	Stiller et al.	
2014/0163359	A1	6/2014	Sholev et al.	2015/0335344	A1	11/2015	Aljuri et al.	
2014/0166724	A1	6/2014	Schellin et al.	2015/0374259	A1	12/2015	Garbey et al.	
2014/0171778	A1	6/2014	Tsusaka et al.	2016/0000437	A1	1/2016	Giordano et al.	
2014/0187856	A1	7/2014	Holoien et al.	2016/0001411	A1	1/2016	Alberti	
2014/0188440	A1	7/2014	Donhowe et al.	2016/0015471	A1	1/2016	Piron et al.	
2014/0194864	A1	7/2014	Martin et al.	2016/0022374	A1	1/2016	Haider et al.	
2014/0195052	A1	7/2014	Tsusaka et al.	2016/0034648	A1	2/2016	Mohlenbrock et al.	
2014/0204190	A1	7/2014	Rosenblatt, III et al.	2016/0038224	A1	2/2016	Couture et al.	
2014/0226572	A1	8/2014	Thota et al.	2016/0038253	A1	2/2016	Piron et al.	
2014/0243799	A1	8/2014	Parihar	2016/0048780	A1	2/2016	Sethumadhavan et al.	

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2016/0058439	A1	3/2016	Shelton, IV et al.	2017/0172550	A1	6/2017	Mukherjee et al.
2016/0066913	A1	3/2016	Swayze et al.	2017/0172565	A1	6/2017	Heneveld
2016/0078190	A1	3/2016	Greene et al.	2017/0172614	A1	6/2017	Scheib et al.
2016/0106516	A1	4/2016	Mesallum	2017/0173262	A1	6/2017	Veltz
2016/0106934	A1	4/2016	Hiraga et al.	2017/0177807	A1	6/2017	Fabian
2016/0121143	A1	5/2016	Mumaw et al.	2017/0196583	A1	7/2017	Sugiyama
2016/0157717	A1	6/2016	Gaster	2017/0196637	A1	7/2017	Shelton, IV et al.
2016/0158468	A1	6/2016	Tang et al.	2017/0202591	A1	7/2017	Shelton, IV et al.
2016/0166336	A1	6/2016	Razzaque et al.	2017/0202595	A1	7/2017	Shelton, IV
2016/0174998	A1	6/2016	Lal et al.	2017/0202607	A1	7/2017	Shelton, IV et al.
2016/0175025	A1	6/2016	Strobl	2017/0202608	A1	7/2017	Shelton, IV et al.
2016/0180045	A1	6/2016	Syed	2017/0209145	A1	7/2017	Swayze et al.
2016/0184054	A1	6/2016	Lowe	2017/0215944	A1	8/2017	Keffeler
2016/0192960	A1	7/2016	Bueno et al.	2017/0224332	A1	8/2017	Hunter et al.
2016/0206202	A1	7/2016	Frangioni	2017/0224334	A1	8/2017	Worthington et al.
2016/0206362	A1	7/2016	Mehta et al.	2017/0224428	A1	8/2017	Kopp
2016/0224760	A1	8/2016	Petak et al.	2017/0231627	A1	8/2017	Shelton, IV et al.
2016/0225551	A1	8/2016	Shedletsky	2017/0231628	A1	8/2017	Shelton, IV et al.
2016/0228061	A1	8/2016	Kallback et al.	2017/0245809	A1	8/2017	Ma et al.
2016/0228204	A1	8/2016	Quaid et al.	2017/0249431	A1	8/2017	Shelton, IV et al.
2016/0235303	A1	8/2016	Fleming et al.	2017/0249432	A1	8/2017	Grantcharov
2016/0242836	A1	8/2016	Eggers et al.	2017/0262604	A1	9/2017	Francois
2016/0249910	A1	9/2016	Shelton, IV et al.	2017/0265864	A1	9/2017	Hessler et al.
2016/0249920	A1	9/2016	Gupta et al.	2017/0265943	A1	9/2017	Sela et al.
2016/0270861	A1	9/2016	Guru et al.	2017/0273715	A1	9/2017	Piron et al.
2016/0278841	A1	9/2016	Panescu et al.	2017/0281171	A1	10/2017	Shelton, IV et al.
2016/0287312	A1	10/2016	Tegg et al.	2017/0281173	A1	10/2017	Shelton, IV et al.
2016/0287316	A1	10/2016	Worrell et al.	2017/0281186	A1	10/2017	Shelton, IV et al.
2016/0287912	A1	10/2016	Warnking	2017/0281189	A1	10/2017	Nalagatla et al.
2016/0292456	A1	10/2016	Dubey et al.	2017/0290585	A1	10/2017	Shelton, IV et al.
2016/0296246	A1	10/2016	Schaller	2017/0296169	A1	10/2017	Yates et al.
2016/0302210	A1	10/2016	Thornton et al.	2017/0296173	A1	10/2017	Shelton, IV et al.
2016/0310055	A1	10/2016	Zand et al.	2017/0296185	A1	10/2017	Swensgard et al.
2016/0310204	A1	10/2016	McHenry et al.	2017/0296213	A1	10/2017	Swensgard et al.
2016/0314716	A1	10/2016	Grubbs	2017/0303984	A1	10/2017	Malackowski
2016/0314717	A1	10/2016	Grubbs	2017/0304007	A1	10/2017	Piron et al.
2016/0321400	A1	11/2016	Durrant et al.	2017/0304020	A1	10/2017	Ng et al.
2016/0323283	A1	11/2016	Kang et al.	2017/0311777	A1	11/2017	Hirayama et al.
2016/0331460	A1	11/2016	Cheatham, III et al.	2017/0312456	A1	11/2017	Phillips
2016/0342753	A1	11/2016	Fezell	2017/0325876	A1	11/2017	Nakadate et al.
2016/0342916	A1	11/2016	Arceneaux et al.	2017/0325878	A1	11/2017	Messerly et al.
2016/0345857	A1	12/2016	Jensrud et al.	2017/0337043	A1	11/2017	Brincat et al.
2016/0345976	A1	12/2016	Gonzalez et al.	2017/0360358	A1	12/2017	Amiot et al.
2016/0350490	A1	12/2016	Martinez et al.	2017/0360499	A1	12/2017	Greep et al.
2016/0354160	A1	12/2016	Crowley et al.	2017/0367583	A1	12/2017	Black et al.
2016/0354162	A1	12/2016	Yen et al.	2017/0367695	A1	12/2017	Shelton, IV et al.
2016/0361070	A1	12/2016	Ardel et al.	2017/0367754	A1	12/2017	Narisawa
2016/0367305	A1	12/2016	Hareland	2017/0367771	A1	12/2017	Tako et al.
2016/0367401	A1	12/2016	Claus	2017/0367772	A1	12/2017	Gunn et al.
2016/0374710	A1	12/2016	Sinelnikov et al.	2017/0370710	A1	12/2017	Chen et al.
2016/0374723	A1	12/2016	Frankhouser et al.	2018/0008359	A1	1/2018	Randle
2016/0374762	A1	12/2016	Case et al.	2018/0011983	A1	1/2018	Zuhars et al.
2016/0379504	A1	12/2016	Bailey et al.	2018/0021058	A1	1/2018	Meglan
2017/0000516	A1	1/2017	Stulen et al.	2018/0042659	A1	2/2018	Rupp et al.
2017/0000542	A1*	1/2017	Yates ..... A61B 18/1206	2018/0050196	A1	2/2018	Pawsey et al.
2017/0000553	A1	1/2017	Wiener et al.	2018/0052971	A1	2/2018	Hanina et al.
2017/0027603	A1	2/2017	Pandey	2018/0055529	A1	3/2018	Messerly et al.
2017/0042604	A1	2/2017	McFarland et al.	2018/0065248	A1	3/2018	Barral et al.
2017/0068792	A1	3/2017	Reiner	2018/0078170	A1	3/2018	Panescu et al.
2017/0079530	A1	3/2017	DiMaio et al.	2018/0098816	A1	4/2018	Govari et al.
2017/0079730	A1	3/2017	Azizian et al.	2018/0108438	A1	4/2018	Ryan et al.
2017/0086829	A1	3/2017	Vendely et al.	2018/0110523	A1	4/2018	Shelton, IV
2017/0086930	A1	3/2017	Thompson et al.	2018/0116662	A1	5/2018	Shelton, IV et al.
2017/0105754	A1	4/2017	Boudreaux et al.	2018/0116735	A1	5/2018	Tierney et al.
2017/0116873	A1	4/2017	Lendvay et al.	2018/0122506	A1	5/2018	Grantcharov et al.
2017/0127499	A1	5/2017	Unoson et al.	2018/0125590	A1	5/2018	Giordano et al.
2017/0132374	A1	5/2017	Lee et al.	2018/0132895	A1	5/2018	Silver
2017/0132385	A1	5/2017	Hunter et al.	2018/0144243	A1	5/2018	Hsieh et al.
2017/0132785	A1	5/2017	Wshah et al.	2018/0153436	A1	6/2018	Olson
2017/0143284	A1	5/2017	Sehnert et al.	2018/0153574	A1	6/2018	Faller et al.
2017/0143442	A1	5/2017	Tesar et al.	2018/0153628	A1	6/2018	Grover et al.
2017/0156076	A1	6/2017	Eom et al.	2018/0153632	A1	6/2018	Tokarchuk et al.
2017/0164997	A1	6/2017	Johnson et al.	2018/0154297	A1	6/2018	Maletich et al.
2017/0165008	A1	6/2017	Finley	2018/0161062	A1	6/2018	Kaga et al.
2017/0165012	A1	6/2017	Chaplin et al.	2018/0161716	A1	6/2018	Li et al.
				2018/0165780	A1	6/2018	Romeo
				2018/0168575	A1	6/2018	Simms et al.
				2018/0168577	A1	6/2018	Aronhalt et al.
				2018/0168578	A1	6/2018	Aronhalt et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2018/0168579	A1	6/2018	Aronhalt et al.
2018/0168584	A1	6/2018	Harris et al.
2018/0168586	A1	6/2018	Shelton, IV et al.
2018/0168590	A1	6/2018	Overmyer et al.
2018/0168592	A1	6/2018	Overmyer et al.
2018/0168597	A1	6/2018	Fanelli et al.
2018/0168598	A1	6/2018	Shelton, IV et al.
2018/0168608	A1	6/2018	Shelton, IV et al.
2018/0168609	A1	6/2018	Fanelli et al.
2018/0168610	A1	6/2018	Shelton, IV et al.
2018/0168614	A1	6/2018	Shelton, IV et al.
2018/0168615	A1	6/2018	Shelton, IV et al.
2018/0168617	A1	6/2018	Shelton, IV et al.
2018/0168618	A1	6/2018	Scott et al.
2018/0168619	A1	6/2018	Scott et al.
2018/0168623	A1	6/2018	Simms et al.
2018/0168625	A1	6/2018	Posada et al.
2018/0168627	A1	6/2018	Weaner et al.
2018/0168628	A1	6/2018	Hunter et al.
2018/0168633	A1	6/2018	Shelton, IV et al.
2018/0168647	A1	6/2018	Shelton, IV et al.
2018/0168648	A1	6/2018	Shelton, IV et al.
2018/0168649	A1	6/2018	Shelton, IV et al.
2018/0168650	A1	6/2018	Shelton, IV et al.
2018/0168651	A1	6/2018	Shelton, IV et al.
2018/0172420	A1	6/2018	Hein et al.
2018/0177383	A1	6/2018	Noonan et al.
2018/0182475	A1	6/2018	Cossler et al.
2018/0193579	A1	7/2018	Hanrahan et al.
2018/0206884	A1	7/2018	Beaupre
2018/0206905	A1	7/2018	Batchelor et al.
2018/0211726	A1	7/2018	Courtemanche et al.
2018/0214025	A1	8/2018	Homyk et al.
2018/0221005	A1	8/2018	Hamel et al.
2018/0221598	A1	8/2018	Silver
2018/0228557	A1	8/2018	Darisse et al.
2018/0233222	A1	8/2018	Daley et al.
2018/0235719	A1	8/2018	Jarc
2018/0235722	A1	8/2018	Baghdadi et al.
2018/0242967	A1	8/2018	Meade
2018/0247128	A1	8/2018	Alvi et al.
2018/0247711	A1	8/2018	Terry
2018/0250086	A1	9/2018	Grubbs
2018/0263699	A1	9/2018	Murphy et al.
2018/0263710	A1	9/2018	Sakaguchi et al.
2018/0268320	A1	9/2018	Shekhar
2018/0271520	A1	9/2018	Shelton, IV et al.
2018/0271603	A1	9/2018	Nir et al.
2018/0289427	A1	10/2018	Griffiths et al.
2018/0294060	A1	10/2018	Kassab
2018/0296286	A1	10/2018	Peine et al.
2018/0303552	A1	10/2018	Ryan et al.
2018/0304471	A1	10/2018	Tokuchi
2018/0310935	A1	11/2018	Wixey
2018/0310986	A1	11/2018	Batchelor et al.
2018/0315492	A1	11/2018	Bishop et al.
2018/0317826	A1	11/2018	Muhsin et al.
2018/0317916	A1	11/2018	Wixey
2018/0333188	A1	11/2018	Nott et al.
2018/0333207	A1	11/2018	Moctezuma De la Barrera
2018/0333209	A1	11/2018	Frushour et al.
2018/0351987	A1	12/2018	Patel et al.
2018/0353186	A1	12/2018	Mozdzierz et al.
2018/0357383	A1	12/2018	Allen et al.
2018/0360454	A1	12/2018	Shelton, IV et al.
2018/0360456	A1	12/2018	Shelton, IV et al.
2018/0366213	A1	12/2018	Fidone et al.
2018/0368930	A1	12/2018	Esterberg et al.
2018/0369511	A1	12/2018	Zergiebel et al.
2019/0000446	A1	1/2019	Shelton, IV et al.
2019/0000478	A1	1/2019	Messerly et al.
2019/0000565	A1	1/2019	Shelton, IV et al.
2019/0000569	A1	1/2019	Crawford et al.
2019/0001079	A1	1/2019	Zergiebel et al.
2019/0005641	A1	1/2019	Yamamoto
2019/0006047	A1	1/2019	Gorek et al.
2019/0025040	A1	1/2019	Andreason et al.
2019/0036688	A1	1/2019	Wasily et al.
2019/0038335	A1	2/2019	Mohr et al.
2019/0038364	A1	2/2019	Enoki
2019/0046198	A1	2/2019	Stokes et al.
2019/0053801	A1	2/2019	Wixey et al.
2019/0053866	A1	2/2019	Seow et al.
2019/0059986	A1	2/2019	Shelton, IV et al.
2019/0069949	A1	3/2019	Vrba et al.
2019/0069964	A1	3/2019	Hagn
2019/0069966	A1	3/2019	Petersen et al.
2019/0070550	A1	3/2019	Lalomia et al.
2019/0070731	A1	3/2019	Bowling et al.
2019/0083190	A1	3/2019	Graves et al.
2019/0087544	A1	3/2019	Peterson
2019/0099221	A1	4/2019	Schmidt et al.
2019/0104919	A1	4/2019	Shelton, IV et al.
2019/0110828	A1	4/2019	Despatie
2019/0110855	A1	4/2019	Barral et al.
2019/0115108	A1	4/2019	Hegedus et al.
2019/0125320	A1	5/2019	Shelton, IV et al.
2019/0125321	A1	5/2019	Shelton, IV et al.
2019/0125324	A1	5/2019	Scheib et al.
2019/0125335	A1	5/2019	Shelton, IV et al.
2019/0125336	A1	5/2019	Deck et al.
2019/0125337	A1	5/2019	Shelton, IV et al.
2019/0125338	A1	5/2019	Shelton, IV et al.
2019/0125339	A1	5/2019	Shelton, IV et al.
2019/0125347	A1	5/2019	Stokes et al.
2019/0125348	A1	5/2019	Shelton, IV et al.
2019/0125352	A1	5/2019	Shelton, IV et al.
2019/0125353	A1	5/2019	Shelton, IV et al.
2019/0125354	A1	5/2019	Deck et al.
2019/0125355	A1	5/2019	Shelton, IV et al.
2019/0125356	A1	5/2019	Shelton, IV et al.
2019/0125357	A1	5/2019	Shelton, IV et al.
2019/0125358	A1	5/2019	Shelton, IV et al.
2019/0125359	A1	5/2019	Shelton, IV et al.
2019/0125360	A1	5/2019	Shelton, IV et al.
2019/0125361	A1	5/2019	Shelton, IV et al.
2019/0125377	A1	5/2019	Shelton, IV
2019/0125378	A1	5/2019	Shelton, IV et al.
2019/0125379	A1	5/2019	Shelton, IV et al.
2019/0125380	A1	5/2019	Hunter et al.
2019/0125383	A1	5/2019	Scheib et al.
2019/0125384	A1	5/2019	Scheib et al.
2019/0125385	A1	5/2019	Scheib et al.
2019/0125386	A1	5/2019	Shelton, IV et al.
2019/0125387	A1	5/2019	Parihar et al.
2019/0125388	A1	5/2019	Shelton, IV et al.
2019/0125389	A1	5/2019	Shelton, IV et al.
2019/0125430	A1	5/2019	Shelton, IV et al.
2019/0125431	A1	5/2019	Shelton, IV et al.
2019/0125432	A1	5/2019	Shelton, IV et al.
2019/0125454	A1	5/2019	Stokes et al.
2019/0125455	A1	5/2019	Shelton, IV et al.
2019/0125456	A1	5/2019	Shelton, IV et al.
2019/0125457	A1	5/2019	Parihar et al.
2019/0125458	A1	5/2019	Shelton, IV et al.
2019/0125459	A1	5/2019	Shelton, IV et al.
2019/0125476	A1	5/2019	Shelton, IV et al.
2019/0133703	A1	5/2019	Seow et al.
2019/0142449	A1	5/2019	Shelton, IV et al.
2019/0142535	A1	5/2019	Seow et al.
2019/0145942	A1	5/2019	Dutriez et al.
2019/0150975	A1	5/2019	Kawasaki et al.
2019/0159777	A1	5/2019	Ehrenfels et al.
2019/0159778	A1	5/2019	Shelton, IV et al.
2019/0162179	A1	5/2019	O'Shea et al.
2019/0163875	A1	5/2019	Allen et al.
2019/0167296	A1	6/2019	Tsubuku et al.
2019/0192044	A1	6/2019	Ravi et al.
2019/0192157	A1	6/2019	Scott et al.
2019/0192236	A1	6/2019	Shelton, IV et al.
2019/0200844	A1	7/2019	Shelton, IV et al.
2019/0200863	A1	7/2019	Shelton, IV et al.
2019/0200905	A1	7/2019	Shelton, IV et al.
2019/0200906	A1	7/2019	Shelton, IV et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2019/0200977	A1	7/2019	Shelton, IV et al.	2019/0201139	A1	7/2019	Shelton, IV et al.
2019/0200980	A1	7/2019	Shelton, IV et al.	2019/0201140	A1	7/2019	Yates et al.
2019/0200981	A1	7/2019	Harris et al.	2019/0201141	A1	7/2019	Shelton, IV et al.
2019/0200984	A1	7/2019	Shelton, IV et al.	2019/0201142	A1	7/2019	Shelton, IV et al.
2019/0200985	A1	7/2019	Shelton, IV et al.	2019/0201143	A1	7/2019	Shelton, IV et al.
2019/0200986	A1	7/2019	Shelton, IV et al.	2019/0201144	A1	7/2019	Shelton, IV et al.
2019/0200987	A1	7/2019	Shelton, IV et al.	2019/0201145	A1	7/2019	Shelton, IV et al.
2019/0200988	A1	7/2019	Shelton, IV	2019/0201146	A1	7/2019	Shelton, IV et al.
2019/0200996	A1	7/2019	Shelton, IV et al.	2019/0201158	A1	7/2019	Shelton, IV et al.
2019/0200997	A1	7/2019	Shelton, IV et al.	2019/0201159	A1	7/2019	Shelton, IV et al.
2019/0200998	A1	7/2019	Shelton, IV et al.	2019/0201594	A1	7/2019	Shelton, IV et al.
2019/0201020	A1	7/2019	Shelton, IV et al.	2019/0201597	A1	7/2019	Shelton, IV et al.
2019/0201021	A1	7/2019	Shelton, IV et al.	2019/0204201	A1	7/2019	Shelton, IV et al.
2019/0201023	A1	7/2019	Shelton, IV et al.	2019/0205001	A1	7/2019	Messerly et al.
2019/0201024	A1	7/2019	Shelton, IV et al.	2019/0205441	A1	7/2019	Shelton, IV et al.
2019/0201025	A1	7/2019	Shelton, IV et al.	2019/0205566	A1	7/2019	Shelton, IV et al.
2019/0201026	A1	7/2019	Shelton, IV et al.	2019/0205567	A1	7/2019	Shelton, IV et al.
2019/0201027	A1	7/2019	Shelton, IV et al.	2019/0206003	A1	7/2019	Harris et al.
2019/0201028	A1	7/2019	Shelton, IV et al.	2019/0206004	A1	7/2019	Shelton, IV et al.
2019/0201029	A1	7/2019	Shelton, IV et al.	2019/0206050	A1	7/2019	Yates et al.
2019/0201030	A1	7/2019	Shelton, IV et al.	2019/0206216	A1	7/2019	Shelton, IV et al.
2019/0201033	A1	7/2019	Yates et al.	2019/0206542	A1	7/2019	Shelton, IV et al.
2019/0201034	A1	7/2019	Shelton, IV et al.	2019/0206551	A1	7/2019	Yates et al.
2019/0201036	A1	7/2019	Nott et al.	2019/0206555	A1	7/2019	Morgan et al.
2019/0201037	A1	7/2019	Houser et al.	2019/0206556	A1	7/2019	Shelton, IV et al.
2019/0201038	A1	7/2019	Yates et al.	2019/0206561	A1	7/2019	Shelton, IV et al.
2019/0201039	A1	7/2019	Widenhouse et al.	2019/0206562	A1	7/2019	Shelton, IV et al.
2019/0201040	A1	7/2019	Messerly et al.	2019/0206563	A1	7/2019	Shelton, IV et al.
2019/0201041	A1	7/2019	Kimball et al.	2019/0206564	A1	7/2019	Shelton, IV et al.
2019/0201042	A1	7/2019	Nott et al.	2019/0206565	A1	7/2019	Shelton, IV
2019/0201043	A1	7/2019	Shelton, IV et al.	2019/0206569	A1	7/2019	Shelton, IV et al.
2019/0201044	A1	7/2019	Shelton, IV et al.	2019/0206576	A1	7/2019	Shelton, IV et al.
2019/0201045	A1	7/2019	Yates et al.	2019/0207911	A1	7/2019	Wiener et al.
2019/0201046	A1	7/2019	Shelton, IV et al.	2019/0208641	A1	7/2019	Yates et al.
2019/0201047	A1	7/2019	Yates et al.	2019/0224434	A1	7/2019	Silver et al.
2019/0201073	A1	7/2019	Nott et al.	2019/0254759	A1	8/2019	Azizian
2019/0201074	A1	7/2019	Yates et al.	2019/0261984	A1	8/2019	Nelson et al.
2019/0201075	A1	7/2019	Shelton, IV et al.	2019/0269476	A1	9/2019	Bowling et al.
2019/0201077	A1	7/2019	Yates et al.	2019/0272917	A1	9/2019	Couture et al.
2019/0201079	A1	7/2019	Shelton, IV et al.	2019/0274662	A1	9/2019	Rockman et al.
2019/0201080	A1	7/2019	Messerly et al.	2019/0274705	A1	9/2019	Sawhney et al.
2019/0201081	A1	7/2019	Shelton, IV et al.	2019/0274706	A1	9/2019	Nott et al.
2019/0201082	A1	7/2019	Shelton, IV et al.	2019/0274707	A1	9/2019	Sawhney et al.
2019/0201083	A1	7/2019	Shelton, IV et al.	2019/0274708	A1	9/2019	Boudreaux
2019/0201084	A1	7/2019	Shelton, IV et al.	2019/0274709	A1	9/2019	Scoggins
2019/0201085	A1	7/2019	Shelton, IV et al.	2019/0274710	A1	9/2019	Black
2019/0201086	A1	7/2019	Shelton, IV et al.	2019/0274712	A1	9/2019	Faller et al.
2019/0201087	A1	7/2019	Shelton, IV et al.	2019/0274713	A1	9/2019	Scoggins et al.
2019/0201088	A1	7/2019	Shelton, IV et al.	2019/0274714	A1	9/2019	Cut et al.
2019/0201089	A1	7/2019	Shelton, IV et al.	2019/0274716	A1	9/2019	Nott et al.
2019/0201090	A1	7/2019	Shelton, IV et al.	2019/0274717	A1	9/2019	Nott et al.
2019/0201091	A1	7/2019	Yates et al.	2019/0274718	A1	9/2019	Denzinger et al.
2019/0201092	A1	7/2019	Yates et al.	2019/0274719	A1	9/2019	Stulen
2019/0201102	A1	7/2019	Shelton, IV et al.	2019/0274720	A1	9/2019	Gee et al.
2019/0201104	A1	7/2019	Shelton, IV et al.	2019/0274749	A1	9/2019	Brady et al.
2019/0201105	A1	7/2019	Shelton, IV et al.	2019/0274750	A1	9/2019	Jayme et al.
2019/0201111	A1	7/2019	Shelton, IV et al.	2019/0274752	A1	9/2019	Denzinger et al.
2019/0201112	A1	7/2019	Wiener et al.	2019/0278262	A1	9/2019	Taylor et al.
2019/0201113	A1	7/2019	Shelton, IV et al.	2019/0282311	A1	9/2019	Nowlin et al.
2019/0201114	A1	7/2019	Shelton, IV et al.	2019/0290389	A1	9/2019	Kopp
2019/0201115	A1	7/2019	Shelton, IV et al.	2019/0298340	A1	10/2019	Shelton, IV et al.
2019/0201116	A1	7/2019	Shelton, IV et al.	2019/0298341	A1	10/2019	Shelton, IV et al.
2019/0201118	A1	7/2019	Shelton, IV et al.	2019/0298342	A1	10/2019	Shelton, IV et al.
2019/0201119	A1	7/2019	Harris et al.	2019/0298343	A1	10/2019	Shelton, IV et al.
2019/0201120	A1	7/2019	Shelton, IV et al.	2019/0298346	A1	10/2019	Shelton, IV et al.
2019/0201123	A1	7/2019	Shelton, IV et al.	2019/0298347	A1	10/2019	Shelton, IV et al.
2019/0201124	A1	7/2019	Shelton, IV et al.	2019/0298350	A1	10/2019	Shelton, IV et al.
2019/0201125	A1	7/2019	Shelton, IV et al.	2019/0298351	A1	10/2019	Shelton, IV et al.
2019/0201126	A1	7/2019	Shelton, IV et al.	2019/0298352	A1	10/2019	Shelton, IV et al.
2019/0201127	A1	7/2019	Shelton, IV et al.	2019/0298353	A1	10/2019	Shelton, IV et al.
2019/0201128	A1	7/2019	Yates et al.	2019/0298354	A1	10/2019	Shelton, IV et al.
2019/0201129	A1	7/2019	Shelton, IV et al.	2019/0298355	A1	10/2019	Shelton, IV et al.
2019/0201130	A1	7/2019	Shelton, IV et al.	2019/0298356	A1	10/2019	Shelton, IV et al.
2019/0201135	A1	7/2019	Shelton, IV et al.	2019/0298357	A1	10/2019	Shelton, IV et al.
2019/0201136	A1	7/2019	Shelton, IV et al.	2019/0298464	A1	10/2019	Abbott
2019/0201137	A1	7/2019	Shelton, IV et al.	2019/0298481	A1	10/2019	Rosenberg et al.
2019/0201138	A1	7/2019	Yates et al.	2019/0307520	A1	10/2019	Peine et al.
				2019/0311802	A1	10/2019	Kokubo et al.
				2019/0314015	A1	10/2019	Shelton, IV et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2019/0314016	A1	10/2019	Huitema et al.
2019/0314081	A1	10/2019	Brogna
2019/0320929	A1	10/2019	Spencer et al.
2019/0321117	A1	10/2019	Itkowitz et al.
2019/0333626	A1	10/2019	Mansi et al.
2019/0343594	A1	11/2019	Garcia Kilroy et al.
2019/0374140	A1	12/2019	Tucker et al.
2019/0374292	A1	12/2019	Barral et al.
2019/0378610	A1	12/2019	Barral et al.
2020/0000470	A1	1/2020	Du et al.
2020/0000509	A1	1/2020	Hayashida et al.
2020/0038120	A1	2/2020	Ziraknejad et al.
2020/0046353	A1	2/2020	Deck et al.
2020/0054317	A1	2/2020	Pisarnwongs et al.
2020/0054320	A1	2/2020	Harris et al.
2020/0054321	A1	2/2020	Harris et al.
2020/0054322	A1	2/2020	Harris et al.
2020/0054323	A1	2/2020	Harris et al.
2020/0054326	A1	2/2020	Harris et al.
2020/0054328	A1	2/2020	Harris et al.
2020/0054330	A1	2/2020	Harris et al.
2020/0078070	A1	3/2020	Henderson et al.
2020/0078071	A1	3/2020	Asher
2020/0078076	A1	3/2020	Henderson et al.
2020/0078077	A1	3/2020	Henderson et al.
2020/0078078	A1	3/2020	Henderson et al.
2020/0078079	A1	3/2020	Morgan et al.
2020/0078080	A1	3/2020	Henderson et al.
2020/0078081	A1	3/2020	Jayme et al.
2020/0078082	A1	3/2020	Henderson et al.
2020/0078089	A1	3/2020	Henderson et al.
2020/0078096	A1	3/2020	Barbagli et al.
2020/0078106	A1	3/2020	Henderson et al.
2020/0078110	A1	3/2020	Henderson et al.
2020/0078111	A1	3/2020	Oberkircher et al.
2020/0078112	A1	3/2020	Henderson et al.
2020/0078113	A1	3/2020	Sawhney et al.
2020/0078114	A1	3/2020	Asher et al.
2020/0078115	A1	3/2020	Asher et al.
2020/0078116	A1	3/2020	Oberkircher et al.
2020/0078117	A1	3/2020	Henderson et al.
2020/0078118	A1	3/2020	Henderson et al.
2020/0078119	A1	3/2020	Henderson et al.
2020/0078120	A1	3/2020	Aldridge et al.
2020/0081585	A1	3/2020	Petre et al.
2020/0090808	A1	3/2020	Carroll et al.
2020/0100825	A1	4/2020	Henderson et al.
2020/0100830	A1	4/2020	Henderson et al.
2020/0106220	A1	4/2020	Henderson et al.
2020/0162896	A1	5/2020	Su et al.
2020/0168323	A1	5/2020	Bullington et al.
2020/0178760	A1	6/2020	Kashima et al.
2020/0178971	A1	6/2020	Harris et al.
2020/0193600	A1	6/2020	Shameli et al.
2020/0197027	A1	6/2020	Hershberger et al.
2020/0203004	A1	6/2020	Shanbhag et al.
2020/0214699	A1	7/2020	Shelton, IV et al.
2020/0226751	A1	7/2020	Jin et al.
2020/0237372	A1	7/2020	Park
2020/0261075	A1	8/2020	Boudreaux et al.
2020/0261076	A1	8/2020	Boudreaux et al.
2020/0261077	A1	8/2020	Shelton, IV et al.
2020/0261078	A1	8/2020	Bakos et al.
2020/0261080	A1	8/2020	Bakos et al.
2020/0261081	A1	8/2020	Boudreaux et al.
2020/0261082	A1	8/2020	Boudreaux et al.
2020/0261083	A1	8/2020	Bakos et al.
2020/0261084	A1	8/2020	Bakos et al.
2020/0261085	A1	8/2020	Boudreaux et al.
2020/0261086	A1	8/2020	Zeiner et al.
2020/0261087	A1	8/2020	Timm et al.
2020/0261088	A1	8/2020	Harris et al.
2020/0261089	A1	8/2020	Shelton, IV et al.
2020/0275928	A1	9/2020	Shelton, IV et al.
2020/0275930	A1	9/2020	Harris et al.
2020/0281665	A1	9/2020	Kopp
2020/0305924	A1	10/2020	Carroll
2020/0305945	A1	10/2020	Morgan et al.
2020/0348662	A1	11/2020	Cella et al.
2020/0405304	A1	12/2020	Mozdzierz et al.
2020/0405375	A1	12/2020	Shelton, IV et al.
2021/0000555	A1	1/2021	Shelton, IV et al.
2021/0007760	A1	1/2021	Reisin
2021/0015568	A1	1/2021	Liao et al.
2021/0022731	A1	1/2021	Eisinger
2021/0022738	A1	1/2021	Weir et al.
2021/0022809	A1	1/2021	Crawford et al.
2021/0059674	A1	3/2021	Shelton, IV et al.
2021/0068834	A1	3/2021	Shelton, IV et al.
2021/0076966	A1	3/2021	Grantcharov et al.
2021/0128149	A1	5/2021	Whitfield et al.
2021/0153889	A1	5/2021	Nott et al.
2021/0169516	A1	6/2021	Houser et al.
2021/0176179	A1	6/2021	Shelton, IV
2021/0177452	A1	6/2021	Nott et al.
2021/0177489	A1	6/2021	Yates et al.
2021/0186454	A1	6/2021	Behzad et al.
2021/0192914	A1	6/2021	Shelton, IV et al.
2021/0201646	A1	7/2021	Shelton, IV et al.
2021/0205020	A1	7/2021	Shelton, IV et al.
2021/0205021	A1	7/2021	Shelton, IV et al.
2021/0205028	A1	7/2021	Shelton, IV et al.
2021/0205029	A1	7/2021	Wiener et al.
2021/0205030	A1	7/2021	Shelton, IV et al.
2021/0205031	A1	7/2021	Shelton, IV et al.
2021/0212602	A1	7/2021	Shelton, IV et al.
2021/0212694	A1	7/2021	Shelton, IV et al.
2021/0212717	A1	7/2021	Yates et al.
2021/0212719	A1	7/2021	Houser et al.
2021/0212770	A1	7/2021	Messerly et al.
2021/0212771	A1	7/2021	Shelton, IV et al.
2021/0212774	A1	7/2021	Shelton, IV et al.
2021/0212775	A1	7/2021	Shelton, IV et al.
2021/0212782	A1	7/2021	Shelton, IV et al.
2021/0219976	A1	7/2021	DiNardo et al.
2021/0220058	A1	7/2021	Messerly et al.
2021/0240852	A1	8/2021	Shelton, IV et al.
2021/0241898	A1	8/2021	Shelton, IV et al.
2021/0249125	A1	8/2021	Morgan et al.
2021/0251487	A1	8/2021	Shelton, IV et al.
2021/0259687	A1	8/2021	Gonzalez et al.
2021/0259697	A1	8/2021	Shelton, IV et al.
2021/0259698	A1	8/2021	Shelton, IV et al.
2021/0282780	A1	9/2021	Shelton, IV et al.
2021/0282781	A1	9/2021	Shelton, IV et al.
2021/0306176	A1	9/2021	Park et al.
2021/0315579	A1	10/2021	Shelton, IV et al.
2021/0315580	A1	10/2021	Shelton, IV et al.
2021/0315581	A1	10/2021	Shelton, IV et al.
2021/0315582	A1	10/2021	Shelton, IV et al.
2021/0322014	A1	10/2021	Shelton, IV et al.
2021/0322015	A1	10/2021	Shelton, IV et al.
2021/0322017	A1	10/2021	Shelton, IV et al.
2021/0322018	A1	10/2021	Shelton, IV et al.
2021/0322019	A1	10/2021	Shelton, IV et al.
2021/0322020	A1	10/2021	Shelton, IV et al.
2021/0336939	A1	10/2021	Wiener et al.
2021/0353287	A1	11/2021	Shelton, IV et al.
2021/0353288	A1	11/2021	Shelton, IV et al.
2021/0358599	A1	11/2021	Alvi et al.
2021/0361284	A1	11/2021	Shelton, IV et al.
2022/0000484	A1	1/2022	Shelton, IV et al.
2022/0054158	A1	2/2022	Shelton, IV et al.
2022/0079591	A1	3/2022	Bakos et al.
2022/0160438	A1	5/2022	Shelton, IV et al.
2022/0175374	A1	6/2022	Shelton, IV et al.

## FOREIGN PATENT DOCUMENTS

CN	101617950	A	1/2010
CN	104490448	B	3/2017
CN	206097107	U	4/2017
CN	108652695	A	10/2018
DE	2037167	A1	7/1980

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

DE	3016131	A1	10/1981
DE	3824913	A1	2/1990
DE	4002843	C1	4/1991
DE	102005051367	A1	4/2007
DE	102016207666	A1	11/2017
EP	0000756	B1	10/1981
EP	0408160	A1	1/1991
EP	0473987	A1	3/1992
EP	0929263	B1	7/1999
EP	1214913	A2	6/2002
EP	2730209	A1	5/2014
EP	2732772	A1	5/2014
EP	2942023	A2	11/2015
EP	3047806	A1	7/2016
EP	3056923	A1	8/2016
EP	3095399	A2	11/2016
EP	3120781	A2	1/2017
EP	3135225	A2	3/2017
EP	3141181	A1	3/2017
FR	2838234	A1	10/2003
GB	2509523	A	7/2014
JP	S5373315	A	6/1978
JP	2001029353	A	2/2001
JP	2007123394	A	5/2007
JP	2010057642	A	3/2010
JP	2017513561	A	6/2017
KR	20140104587	A	8/2014
KR	101587721	B1	1/2016
WO	WO-9734533	A1	9/1997
WO	WO-0024322	A1	5/2000
WO	WO-0108578	A1	2/2001
WO	WO-0112089	A1	2/2001
WO	WO-0120892	A2	3/2001
WO	WO-03079909	A2	10/2003
WO	WO-2007137304	A2	11/2007
WO	WO-2008053485	A1	5/2008
WO	WO-2008056618	A2	5/2008
WO	WO-2008069816	A1	6/2008
WO	WO-2008147555	A2	12/2008
WO	WO-2011112931	A1	9/2011
WO	WO-2013143573	A1	10/2013
WO	WO-2014031800	A1	2/2014
WO	WO-2014071184	A1	5/2014
WO	WO-2014134196	A1	9/2014
WO	WO-2015129395	A1	9/2015
WO	WO-2016100719	A1	6/2016
WO	WO-2016118752	A1	7/2016
WO	WO-2016206015	A1	12/2016
WO	WO-2017011382	A1	1/2017
WO	WO-2017011646	A1	1/2017
WO	WO-2017058617	A1	4/2017
WO	WO-2017058695	A1	4/2017
WO	WO-2017151996	A1	9/2017
WO	WO-2017189317	A1	11/2017
WO	WO-2017205308	A1	11/2017
WO	WO-2017210499	A1	12/2017
WO	WO-2017210501	A1	12/2017
WO	WO-2018116247	A1	6/2018
WO	WO-2018152141	A1	8/2018
WO	WO-2018176414	A1	10/2018

## OTHER PUBLICATIONS

Flores et al., "Large-scale Offloading in the Internet of Things," 2017 IEEE International Conference on Pervasive Computing and Communications Workshops (Percom Workshops), IEEE, pp. 479-484, Mar. 13, 2017.

Kalantarian et al., "Computation Offloading for Real-Time Health-Monitoring Devices," 2016 38th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE, pp. 4971-4974, Aug. 16, 2016.

Yuyi Mao et al., "A Survey on Mobile Edge Computing: The Communication Perspective," IEEE Communications Surveys & Tutorials, pp. 2322-2358, Jun. 13, 2017.

Khazaei et al., "Health Informatics for Neonatal Intensive Care Units: An Analytical Modeling Perspective," IEEE Journal of Translational Engineering in Health and Medicine, vol. 3, pp. 1-9, Oct. 21, 2015.

Benkmann et al., "Concept of iterative optimization of minimally invasive surgery," 2017 22nd International Conference on Methods and Models in Automation and Robotics (MMAR), IEEE pp. 443-446, Aug. 28, 2017.

Trautman, Peter, "Breaking the Human-Robot Deadlock: Surpassing Shared Control Performance Limits with Sparse Human-Robot Interaction," Robotics: Science and Systems XIII, pp. 1-10, Jul. 12, 2017.

Yang et al., "A dynamic strategy for packet scheduling and bandwidth allocation based on channel quality in IEEE 802.16e OFDMA system," Journal of Network and Computer Applications, vol. 39, pp. 52-60, May 2, 2013.

Takahashi et al., "Automatic smoke evacuation in laparoscopic surgery: a simplified method for objective evaluation," Surgical Endoscopy, vol. 27, No. 8, pp. 2980-2987, Feb. 23, 2013.

Miksch et al., "Utilizing temporal data abstraction for data validation and therapy planning for artificially ventilated newborn infants," Artificial Intelligence in Medicine, vol. 8, No. 6, pp. 543-576 (1996).

Horn et al., "Effective data validation of high-frequency data: Time-point-time-interval-, and trend-based methods," Computers in Biology and Medic, New York, NY, vol. 27, No. 5, pp. 389-409 (1997).

Stacey et al., "Temporal abstraction in intelligent clinical data analysis: A survey," Artificial Intelligence in Medicine, vol. 39, No. 1, pp. 1-24 (2006).

Zoccali, Bruno, "A Method for Approximating Component Temperatures at Altitude Conditions Based on CFD Analysis at Sea Level Conditions," (white paper), www.tdmginc.com, Dec. 6, 2018 (9 pages).

Slocinski et al., "Distance measure for impedance spectra for quantified evaluations," Lecture Notes on Impedance Spectroscopy, vol. 3, Taylor and Francis Group (Jul. 2012)—Book Not Attached.

Engel et al., "A safe robot system for craniofacial surgery," 2013 IEEE International Conference on Robotics and Automation (ICRA); May 6-10, 2013; Karlsruhe, Germany, vol. 2, Jan. 1, 2001, pp. 2020-2024.

Bonaci et al., "To Make a Robot Secure: An Experimental Analysis of Cyber Security Threats Against Teleoperated Surgical Robots," May 13, 2015. Retrieved from the Internet: URL:<https://arxiv.org/pdf/1504.04339v2.pdf> [retrieved on Aug. 24, 2019].

Homa Alemzadeh et al., "Targeted Attacks on Teleoperated Surgical Robots: Dynamic Model-Based Detection and Mitigation," 2016 46th Annual IEEE/IFIP International Conference on Dependable Systems and Networks (DSN), IEEE, Jun. 28, 2016, pp. 395-406.

Phumzile Malindi, "5. QoS in Telemedicine," "Telemedicine," Jun. 20, 2011, IntechOpen, pp. 119-138.

Staub et al., "Contour-based Surgical Instrument Tracking Supported by Kinematic Prediction," Proceedings of the 2010 3rd IEEE RAS & EMBS International Conference on Biomedical Robotics and Biomechatronics, Sep. 1, 2010, pp. 746-752.

Allan et al., "3-D Pose Estimation of Articulated Instruments in Robotic Minimally Invasive Surgery," IEEE Transactions on Medical Imaging, vol. 37, No. 5, May 1, 2018, pp. 1204-1213.

Kassahun et al., "Surgical Robotics Beyond Enhanced Dexterity Instrumentation: A Survey of the Machine Learning Techniques and their Role in Intelligent and Autonomous Surgical Actions." International Journal of Computer Assisted Radiology and Surgery, vol. 11, No. 4, Oct. 8, 2015, pp. 553-568.

Weede et al., "An Intelligent and Autonomous Endoscopic Guidance System for Minimally Invasive Surgery," 2013 IEEE International Conference on Robotics and Automation (ICRA), May 6-10, 2013. Karlsruhe, Germany, May 1, 2011, pp. 5762-5768.

Altenberg et al., "Genes of Glycolysis are Ubiquitously Overexpressed in 24 Cancer Classes," Genomics, vol. 84, pp. 1014-1020 (2004).

Harold I. Brandon and V. Leroy Young, Mar. 1997, Surgical Services Management vol. 3 No. 3. retrieved from the internet <[https://www.surgimedics.com/Research%20Articles/Electrosurgical%](https://www.surgimedics.com/Research%20Articles/Electrosurgical%20)

(56)

## References Cited

## OTHER PUBLICATIONS

20Plume/Characterization%20And%20Removal%20Of%20Electrosurgical%20Smoke.pdf> (Year: 1997).  
 Marshall Brain, How Microcontrollers Work, 2006, retrieved from the internet <<https://web.archive.org/web/20060221235221/http://electronics.howstuffworks.com/microcontroller.htm/printable>> (Year: 2006).  
 CRC Press, "The Measurement, Instrumentation and Sensors Handbook," 1999, Section VII, Chapter 41, Peter O'Shea, "Phase Measurement," pp. 1303-1321, ISBN 0-8493-2145-X.  
 Jiang, "'Sound of Silence': a secure indoor wireless ultrasonic communication system," Article, 2014, pp. 46-50, Snapshots of Doctoral Research at University College Cork, School of Engineering—Electrical & Electronic Engineering, UCC, Cork, Ireland.  
 Li, et al., "Short-range ultrasonic communications in air using quadrature modulation," Journal, Oct. 30, 2009, pp. 2060-2072, IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control, vol. 56, No. 10, IEEE.  
 Salamon, "AI Detects Polyps Better Than Colonoscopists" Online Article, Jun. 3, 2018, Medscape Medical News, Digestive Disease Week (DDW) 2018: Presentation 133.  
 Misawa, et al. "Artificial Intelligence-Assisted Polyp Detection for Colonoscopy: Initial Experience," Article, Jun. 2018, pp. 2027-2029, vol. 154, Issue 8, American Gastroenterology Association.  
 Dottorato, "Analysis and Design of the Rectangular Microstrip Patch Antennas for TM<sub>0n0</sub> operating mode," Article, Oct. 8, 2010, pp. 1-9, Microwave Journal.  
 Miller, et al., "Impact of Powered and Tissue-Specific Endoscopic Stapling Technology on Clinical and Economic Outcomes of Video-Assisted Thoracic Surgery Lobectomy Procedures: A Retrospective, Observational Study," Article, Apr. 2018, pp. 707-723, vol. 35 (Issue 5), Advances in Therapy.  
 Hsiao-Wei Tang, "ARCM", Video, Sep. 2012, YouTube, 5 screenshots, Retrieved from internet: <<https://www.youtube.com/watch?v=UldQxb3fRw&feature=youtu.be>>.  
 Giannios, et al., "Visible to near-infrared refractive properties of freshly-excised human-liver tissues: marking hepatic malignancies," Article, Jun. 14, 2016, pp. 1-10, Scientific Reports 6, Article No. 27910, Nature.  
 Vander Heiden, et al., "Understanding the Warburg effect: the metabolic requirements of cell proliferation," Article, May 22, 2009, pp. 1-12, vol. 324, Issue 5930, Science.  
 Hirayama et al., "Quantitative Metabolome Profiling of Colon and Stomach Cancer Microenvironment by Capillary Electrophoresis Time-of-Flight Mass Spectrometry," Article, Jun. 2009, pp. 4918-4925, vol. 69, Issue 11, Cancer Research.  
 Cengiz, et al., "A Tale of Two Compartments: Interstitial Versus Blood Glucose Monitoring," Article, Jun. 2009, pp. S11-S16, vol. 11, Supplement 1, Diabetes Technology & Therapeutics.  
 Shen, et al., "An iridium nanoparticles dispersed carbon based thick film electrochemical biosensor and its application for a single use, disposable glucose biosensor," Article, Feb. 3, 2007, pp. 106-113, vol. 125, Issue 1, Sensors and Actuators B: Chemical, Science Direct.  
 "ATM-MPLS Network Interworking Version 2.0, af-aic-0178.001" ATM Standard, the ATM Forum Technical Committee, published Aug. 2003.

IEEE Std 802.3-2012 (Revision of IEEE Std 802.3-2008, published Dec. 28, 2012).  
 IEEE Std No. 177, "Standard Definitions and Methods of Measurement for Piezoelectric Vibrators," published May 1966, the Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.  
 Shi et al., An intuitive control console for robotic surgery system, 2014, IEEE, p. 404-407 (Year: 2014).  
 Choi et al., A haptic augmented reality surgeon console for a laparoscopic surgery robot system, 2013, IEEE, p. 355-357 (Year: 2013).  
 Xie et al., Development of stereo vision and master-slave controller for a compact surgical robot system, 2015, IEEE, p. 403-407 (Year: 2015).  
 Sun et al., Innovative effector design for simulation training in robotic surgery, 2010, IEEE, p. 1735-1759 (Year: 2010).  
 Anonymous, "Internet of Things Powers Connected Surgical Device Infrastructure Case Study", Dec. 31, 2016 (Dec. 31, 2016), Retrieved from the Internet: URL:[https://www.cognizant.com/services-resources/150110\\_IoT\\_connected\\_surgical\\_devices.pdf](https://www.cognizant.com/services-resources/150110_IoT_connected_surgical_devices.pdf).  
 Draijer, Matthijs et al., "Review of laser pscckle contrast techniques for visualizing tissue perfusion," Lasers in Medical Science, Springer-Verlag, LO, vol. 24, No. 4, Dec. 3, 2008, pp. 639-651.  
 Roy D Cullum, "Handbook of Engineering Design", ISBN: 9780408005586, Jan. 1, 1988 (Jan. 1, 1988), XP055578597, ISBN: 9780408005586, 10-20, Chapter 6, p. 138, right-hand column, paragraph 3.  
 "Surgical instrumentation: the true cost of instrument trays and a potential strategy for optimization"; Mhlaba et al.; Sep. 23, 2015 (Year: 2015).  
 Nabil Simaan et al, "Intelligent Surgical Robots with Situational Awareness: From Good to Great Surgeons", DOI: 10.1115/1.2015-Sep-6 external link, Sep. 2015 (Sep. 2015), p. 3-6, Retrieved from the Internet: URL:<http://memagazineselect.asmedigitalcollection.asme.org/data/journals/meena/936888/me-2015-sep6.pdf> XP055530863.  
 Anonymous: "Titanium Key Chain Tool 1.1, Ultralight Multipurpose Key Chain Tool, Forward Cutting Can Opener—Vargo Titanium," vargooutdoors.com, Jul. 5, 2014 (Jul. 5, 2014), retrieved from the internet: <https://vargooutdoors.com/titanium-key-chain-tool-1-1.html>.  
 Anonymous: "Screwdriver—Wikipedia", en.wikipedia.org, Jun. 23, 2019, XP055725151, Retrieved from the Internet: URL:<https://en.wikipedia.org/w/index.php?title=Screwdriver&oldid=903111203> [retrieved on Mar. 20, 2021].  
 Nordlinger, Christopher, "The Internet of Things and the Operating Room of the Future," May 4, 2015, <https://medium.com/@chrisonordlinger/the-internet-of-things-and-the-operating-room-of-the-future-8999a143d7b1>, retrieved from the internet on Apr. 27, 2021, 9 pages.  
 Screen captures from YouTube video clip entitled "Four ways to use the Lego Brick Separator Tool," 2 pages, uploaded on May 29, 2014 by user "Sarah Lewis". Retrieved from internet: <https://www.youtube.com/watch?v=ucKiRD6U1LU> (Year: 2014).  
 Sorrells, P., "Application Note AN680. Passive RFID Basics," retrieved from <http://ww1.microchip.com/downloads/en/AppNotes/00680b.pdf> on Feb. 26, 2020, Dec. 31, 1998, pp. 1-7.  
 Lalys, et al., "Automatic knowledge-based recognition of low-level tasks in ophthalmological procedures", Int J Cars, vol. 8, No. 1, pp. 1-49, Apr. 19, 2012.

\* cited by examiner




FIG. 1




FIG. 2






FIG. 4




FIG. 5




FIG. 6




FIG. 7








FIG. 8C




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20






FIG. 21






FIG. 24






FIG. 25




$f$  sweep 55kHz--56kHz

FIG. 26



$f$  sweep 55kHz-56kHz


FIG. 27



$f$  sweep 55kHz-56kHz

FIG. 28

Z Scale: 500  $\Omega$ /div  
Y Scale: 500  $\mu$ s/div



OSC Voltage  
500mV

$f$  sweep 48kHz-62kHz

FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34

**VESSEL SENSING FOR ADAPTIVE  
ADVANCED HEMOSTASIS**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application claims the benefit of priority under 35 U.S.C. § 119(e) to U.S. Provisional Patent Application Ser. No. 62/640,417, titled TEMPERATURE CONTROL IN ULTRASONIC DEVICE AND CONTROL SYSTEM THEREFOR, filed Mar. 8, 2018, and to U.S. Provisional Patent Application Ser. No. 62/640,415, titled ESTIMATING STATE OF ULTRASONIC END EFFECTOR AND CONTROL SYSTEM THEREFOR, filed Mar. 8, 2018, the disclosure of each of which is herein incorporated by reference in its entirety.

BACKGROUND

In a surgical environment, smart energy devices may be needed in a smart energy architecture environment. Ultrasonic surgical devices, such as ultrasonic scalpels, are finding increasingly widespread applications in surgical procedures by virtue of their unique performance characteristics. Depending upon specific device configurations and operational parameters, ultrasonic surgical devices can provide substantially simultaneous transection of tissue and homeostasis by coagulation, desirably minimizing patient trauma. An ultrasonic surgical device may comprise a handpiece containing an ultrasonic transducer, and an instrument coupled to the ultrasonic transducer having a distally-mounted end effector (e.g., a blade tip) to cut and seal tissue. In some cases, the instrument may be permanently affixed to the handpiece. In other cases, the instrument may be detachable from the handpiece, as in the case of a disposable instrument or an interchangeable instrument. The end effector transmits ultrasonic energy to tissue brought into contact with the end effector to realize cutting and sealing action. Ultrasonic surgical devices of this nature can be configured for open surgical use, laparoscopic, or endoscopic surgical procedures including robotic-assisted procedures.

Ultrasonic energy cuts and coagulates tissue using temperatures lower than those used in electrosurgical procedures and can be transmitted to the end effector by an ultrasonic generator in communication with the handpiece. Vibrating at high frequencies (e.g., 55,500 cycles per second), the ultrasonic blade denatures protein in the tissue to form a sticky coagulum. Pressure exerted on tissue by the blade surface collapses blood vessels and allows the coagulum to form a hemostatic seal. A surgeon can control the cutting speed and coagulation by the force applied to the tissue by the end effector, the time over which the force is applied, and the selected excursion level of the end effector.

The ultrasonic transducer may be modeled as an equivalent circuit comprising a first branch having a static capacitance and a second “motional” branch having a serially connected inductance, resistance and capacitance that define the electromechanical properties of a resonator. Known ultrasonic generators may include a tuning inductor for tuning out the static capacitance at a resonant frequency so that substantially all of a generator’s drive signal current flows into the motional branch. Accordingly, by using a tuning inductor, the generator’s drive signal current represents the motional branch current, and the generator is thus able to control its drive signal to maintain the ultrasonic transducer’s resonant frequency. The tuning inductor may also transform the phase impedance plot of the ultrasonic

transducer to improve the generator’s frequency lock capabilities. However, the tuning inductor must be matched with the specific static capacitance of an ultrasonic transducer at the operational resonant frequency. In other words, a different ultrasonic transducer having a different static capacitance requires a different tuning inductor.

Additionally, in some ultrasonic generator architectures, the generator’s drive signal exhibits asymmetrical harmonic distortion that complicates impedance magnitude and phase measurements. For example, the accuracy of impedance phase measurements may be reduced due to harmonic distortion in the current and voltage signals.

Moreover, electromagnetic interference in noisy environments decreases the ability of the generator to maintain lock on the ultrasonic transducer’s resonant frequency, increasing the likelihood of invalid control algorithm inputs.

Electrosurgical devices for applying electrical energy to tissue in order to treat and/or destroy the tissue are also finding increasingly widespread applications in surgical procedures. An electrosurgical device may comprise a handpiece and an instrument having a distally-mounted end effector (e.g., one or more electrodes). The end effector can be positioned against the tissue such that electrical current is introduced into the tissue. Electrosurgical devices can be configured for bipolar or monopolar operation. During bipolar operation, current is introduced into and returned from the tissue by active and return electrodes, respectively, of the end effector. During monopolar operation, current is introduced into the tissue by an active electrode of the end effector and returned through a return electrode (e.g., a grounding pad) separately located on a patient’s body. Heat generated by the current flowing through the tissue may form hemostatic seals within the tissue and/or between tissues and thus may be particularly useful for sealing blood vessels, for example. The end effector of an electrosurgical device may also comprise a cutting member that is movable relative to the tissue and the electrodes to transect the tissue.

Electrical energy applied by an electrosurgical device can be transmitted to the instrument by a generator in communication with the handpiece. The electrical energy may be in the form of radio frequency (RF) energy. RF energy is a form of electrical energy that may be in the frequency range of 300 kHz to 1 MHz, as described in EN60601-2-2:2009+A11:2011, Definition 201.3.218—HIGH FREQUENCY. For example, the frequencies in monopolar RF applications are typically restricted to less than 5 MHz. However, in bipolar RF applications, the frequency can be almost any value. Frequencies above 200 kHz are typically used for monopolar applications in order to avoid the unwanted stimulation of nerves and muscles which would result from the use of low frequency current. Lower frequencies may be used for bipolar techniques if a risk analysis shows the possibility of neuromuscular stimulation has been mitigated to an acceptable level. Normally, frequencies above 5 MHz are not used in order to minimize the problems associated with high frequency leakage currents. It is generally recognized that 10 mA is the lower threshold of thermal effects on tissue.

During its operation, an electrosurgical device can transmit low frequency RF energy through tissue, which causes ionic agitation, or friction, in effect resistive heating, thereby increasing the temperature of the tissue. Because a sharp boundary may be created between the affected tissue and the surrounding tissue, surgeons can operate with a high level of precision and control, without sacrificing un-targeted adjacent tissue. The low operating temperatures of RF energy may be useful for removing, shrinking, or sculpting soft

tissue while simultaneously sealing blood vessels. RF energy may work particularly well on connective tissue, which is primarily comprised of collagen and shrinks when contacted by heat.

Due to their unique drive signal, sensing and feedback needs, ultrasonic and electro-surgical devices have generally required different generators. Additionally, in cases where the instrument is disposable or interchangeable with a hand-piece, ultrasonic and electro-surgical generators are limited in their ability to recognize the particular instrument configuration being used and to optimize control and diagnostic processes accordingly. Moreover, capacitive coupling between the non-isolated and patient-isolated circuits of the generator, especially in cases where higher voltages and frequencies are used, may result in exposure of a patient to unacceptable levels of leakage current.

Furthermore, due to their unique drive signal, sensing and feedback needs, ultrasonic and electro-surgical devices have generally required different user interfaces for the different generators. In such conventional ultrasonic and electro-surgical devices, one user interface is configured for use with an ultrasonic instrument whereas a different user interface may be configured for use with an electro-surgical instrument. Such user interfaces include hand and/or foot activated user interfaces such as hand activated switches and/or foot activated switches. As various aspects of combined generators for use with both ultrasonic and electro-surgical instruments are contemplated in the subsequent disclosure, additional user interfaces that are configured to operate with both ultrasonic and/or electro-surgical instrument generators also are contemplated.

Additional user interfaces for providing feedback, whether to the user or other machine, are contemplated within the subsequent disclosure to provide feedback indicating an operating mode or status of either an ultrasonic and/or electro-surgical instrument. Providing user and/or machine feedback for operating a combination ultrasonic and/or electro-surgical instrument will require providing sensory feedback to a user and electrical/mechanical/electromechanical feedback to a machine. Feedback devices that incorporate visual feedback devices (e.g., an LCD display screen, LED indicators), audio feedback devices (e.g., a speaker, a buzzer) or tactile feedback devices (e.g., haptic actuators) for use in combined ultrasonic and/or electro-surgical instruments are contemplated in the subsequent disclosure.

Other electrical surgical instruments include, without limitation, irreversible and/or reversible electroporation, and/or microwave technologies, among others. Accordingly, the techniques disclosed herein are applicable to ultrasonic, bipolar or monopolar RF (electro-surgical), irreversible and/or reversible electroporation, and/or microwave based surgical instruments, among others.

### SUMMARY

An aspect of an ultrasonic device may include an electromechanical ultrasonic system defined by a predetermined resonant frequency, the electromechanical ultrasonic system further having an ultrasonic transducer coupled to an ultrasonic blade. An aspect of a method of delivering energy to the ultrasonic device may include sensing, by a processor or control circuit, a vessel type in contact with the ultrasonic blade coupled to the ultrasonic transducer, determining, by the processor or control circuit, that the vessel type is either

a vein or an artery, and delivering, by the processor or control circuit, power to the ultrasonic transducer based on the vessel type.

In one aspect, the method may further include applying power to the ultrasonic transducer at a power level P for a period T based on the identified vessel, in which the power level P is different from a nominal power level P<sub>n</sub> and the period T is different from a nominal period T<sub>n</sub>.

In one aspect of the method, applying power to the ultrasonic transducer at a power level P for a period T may include applying power to the ultrasonic transducer at a power level P that is lower than the nominal power level P<sub>n</sub> for a period T that is longer than the nominal period T<sub>n</sub> when the identified vessel is a vein.

In one aspect of the method, applying power to the ultrasonic transducer at a power level P for a period T may include applying power to the ultrasonic transducer at a power level P that is greater than the nominal power level P<sub>n</sub> for a period T that is shorter than the nominal period T<sub>n</sub> when the identified vessel is an artery.

In one aspect of the method, determining, by the processor or control circuit, that the vessel type is either a vein or an artery may include measuring, by the processor or control circuit, a complex impedance of the ultrasonic transducer, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)},$$

receiving, by the processor or control circuit, a complex impedance measurement data point, comparing, by the processor or control circuit, the complex impedance measurement data point to a data point in a reference complex impedance characteristic pattern, classifying, by the processor or control circuit, the complex impedance measurement data point based on a result of the comparison analysis, and assigning, by the processor or control circuit, the vessel type based on the result of the comparison analysis.

In one aspect of the method, determining, by the processor or control circuit, that the vessel type is either a vein or an artery may include applying, by a drive circuit, a drive signal to the ultrasonic transducer, wherein the drive signal is a periodic signal defined by a magnitude and frequency, sweeping, by a processor or control circuit, the frequency of the drive signal from below resonance to above resonance of the electromechanical ultrasonic system, measuring and recording, by the processor or control circuit, impedance/admittance circle variables R<sub>e</sub>, G<sub>e</sub>, X<sub>e</sub>, and B<sub>e</sub>, comparing, by the processor or control circuit, measured impedance/admittance circle variables R<sub>e</sub>, G<sub>e</sub>, X<sub>e</sub>, and B<sub>e</sub> to reference impedance/admittance circle variables R<sub>ref</sub>, G<sub>ref</sub>, X<sub>ref</sub>, and B<sub>ref</sub> and determining, by the processor or control circuit, the vessel type based on the result of the comparison analysis.

An aspect of an ultrasonic device may include an electromechanical ultrasonic system defined by a predetermined resonant frequency, the electromechanical ultrasonic system having an ultrasonic transducer coupled to an ultrasonic blade. An aspect of method of applying energy to the ultrasonic device may include sensing, by the processor or control circuit, a vessel type in contact with an ultrasonic blade coupled to an ultrasonic transducer, determining, by the processor or control circuit, that the vessel type is either a vein or an artery, and applying, by the processor or control circuit, power to the ultrasonic transducer based on the vessel type.

5

In one aspect, the method may further include applying, by the processor or control circuit, a power level to achieve a targeted ultrasonic blade temperature for a vein when the identified vessel is a vein and receiving a feedback control, by the processor or control circuit, to maintain the targeted ultrasonic blade temperature for a vein.

In one aspect, the method may further include applying, by the processor or control circuit, a power level to achieve a targeted ultrasonic blade temperature for an artery when the identified vessel is an artery and receiving a feedback control, by the processor or control circuit, to maintain the targeted ultrasonic blade temperature for an artery.

In one aspect of the method, determining, by the processor or control circuit, that the vessel type is either a vein or an artery may include measuring, by the processor or control circuit, a complex impedance of the ultrasonic transducer, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)},$$

receiving, by the processor or control circuit, a complex impedance measurement data point, comparing, by the processor or control circuit, the complex impedance measurement data point to a data point in a reference complex impedance characteristic pattern, classifying, by the processor or control circuit, the complex impedance measurement data point based on a result of the comparison analysis, and assigning, by the processor or control circuit, the vessel type based on the result of the comparison analysis.

In one aspect of the method, determining, by the processor or control circuit, that the vessel type is either a vein or an artery may include applying, by a drive circuit, a drive signal to the ultrasonic transducer, wherein the drive signal is a periodic signal defined by a magnitude and frequency, sweeping, by a processor or control circuit, the frequency of the drive signal from below resonance to above resonance of the electromechanical ultrasonic system, measuring and recording, by the processor or control circuit, impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$ , comparing, by the processor or control circuit, measured impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$  to reference impedance/admittance circle variables  $R_{ref}$ ,  $G_{ref}$ ,  $X_{ref}$ , and  $B_{ref}$  and determining, by the processor or control circuit, the vessel type based on the result of the comparison analysis.

An aspect of an ultrasonic surgical instrument may include an ultrasonic electromechanical system having an ultrasonic transducer coupled to an ultrasonic blade via an ultrasonic waveguide and a generator configured to supply power to the ultrasonic transducer. An aspect of the generator includes a control circuit configured to sense a vessel type in contact with the ultrasonic blade coupled to the ultrasonic transducer, determine that the vessel type is either a vein or an artery, and deliver power to the ultrasonic transducer based on the vessel type.

In one aspect of the ultrasonic surgical instrument, the generator may include a control circuit further configured to apply power to the ultrasonic transducer at a power level P for a period T based on the identified vessel, wherein the power level P is different from a nominal power level Pn and the period T is different from a nominal period Tn.

In one aspect of the ultrasonic surgical instrument, the power level P is lower than the nominal power level Pn for a period T that is longer than the nominal period Tn when the identified vessel is a vein.

6

In one aspect of the ultrasonic surgical instrument, the power level P that is greater than the nominal power level Pn for a period T that is shorter than the nominal period Tn when the identified vessel is an artery.

In one aspect of the ultrasonic surgical instrument, the generator may include a control circuit further configured to measure a complex impedance of the ultrasonic transducer, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)},$$

receive a complex impedance measurement data point, compare the complex impedance measurement data point to a data point in a reference complex impedance characteristic pattern, classify the complex impedance measurement data point based on a result of the comparison analysis, and assign the vessel type based on the result of the comparison analysis.

In one aspect of the ultrasonic surgical instrument, the generator may include a control circuit further configured to cause a drive circuit to apply a drive signal to the ultrasonic transducer, wherein the drive signal is a periodic signal defined by a magnitude and frequency, sweep the frequency of the drive signal from below resonance to above resonance of the electromechanical ultrasonic system, measure and record impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$ , comparing measured impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$  to reference impedance/admittance circle variables  $R_{ref}$ ,  $G_{ref}$ ,  $X_{ref}$ , and  $B_{ref}$  and determining the vessel type based on the result of the comparison analysis.

An aspect of an ultrasonic surgical instrument may include an ultrasonic electromechanical system having an ultrasonic transducer coupled to an ultrasonic blade via an ultrasonic waveguide and a generator configured to supply power to the ultrasonic transducer. An aspect of the generator may include a control circuit configured to sense a vessel type in contact with an ultrasonic blade coupled to an ultrasonic transducer, determine that the vessel type is either a vein or an artery, and apply power to the ultrasonic transducer based on the vessel type.

In one aspect of the ultrasonic surgical instrument, the generator may include a control circuit further configured to apply a power level to achieve a targeted ultrasonic blade temperature for a vein when the identified vessel is a vein and receive a feedback control to maintain the targeted ultrasonic blade temperature for a vein.

In one aspect of the ultrasonic surgical instrument, the generator may include a control circuit further configured to apply a power level to achieve a targeted ultrasonic blade temperature for an artery when the identified vessel is an artery and receive a feedback control to maintain the targeted ultrasonic blade temperature for an artery.

In one aspect of the ultrasonic surgical instrument, the generator may include a control circuit further configured to measure a complex impedance of the ultrasonic transducer, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)},$$

receive a complex impedance measurement data point, compare the complex impedance measurement data point to a

data point in a reference complex impedance characteristic pattern, classify the complex impedance measurement data point based on a result of the comparison analysis, and assign the vessel type based on the result of the comparison analysis.

In one aspect of the ultrasonic surgical instrument, the generator may include a control circuit further configured to cause a drive circuit to apply a drive signal to the ultrasonic transducer, wherein the drive signal is a periodic signal defined by a magnitude and frequency, sweep the frequency of the drive signal from below resonance to above resonance of the electromechanical ultrasonic system, measure and record impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$ , compare measured impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$  to reference impedance/admittance circle variables  $R_{ref}$ ,  $G_{ref}$ ,  $X_{ref}$ , and  $B_{ref}$  and determine the vessel type based on the result of the comparison analysis.

## FIGURES

The features of various aspects are set forth with particularity in the appended claims. The various aspects, however, both as to organization and methods of operation, together with further objects and advantages thereof, may best be understood by reference to the following description, taken in conjunction with the accompanying drawings as follows.

FIG. 1 is a system configured to execute adaptive ultrasonic blade control algorithms in a surgical data network comprising a modular communication hub, in accordance with at least one aspect of the present disclosure.

FIG. 2 illustrates an example of a generator, in accordance with at least one aspect of the present disclosure.

FIG. 3 is a surgical system comprising a generator and various surgical instruments usable therewith, in accordance with at least one aspect of the present disclosure.

FIG. 4 is an end effector, in accordance with at least one aspect of the present disclosure.

FIG. 5 is a diagram of the surgical system of FIG. 3, in accordance with at least one aspect of the present disclosure.

FIG. 6 is a model illustrating motional branch current, in accordance with at least one aspect of the present disclosure.

FIG. 7 is a structural view of a generator architecture, in accordance with at least one aspect of the present disclosure.

FIGS. 8A-8C are functional views of a generator architecture, in accordance with at least one aspect of the present disclosure.

FIGS. 9A-9B are structural and functional aspects of a generator, in accordance with at least one aspect of the present disclosure.

FIG. 10 illustrates a control circuit configured to control aspects of the surgical instrument or tool, in accordance with at least one aspect of the present disclosure.

FIG. 11 illustrates a combinational logic circuit configured to control aspects of the surgical instrument or tool, in accordance with at least one aspect of the present disclosure.

FIG. 12 illustrates a sequential logic circuit configured to control aspects of the surgical instrument or tool, in accordance with at least one aspect of the present disclosure.

FIG. 13 illustrates one aspect of a fundamental architecture for a digital synthesis circuit such as a direct digital synthesis (DDS) circuit configured to generate a plurality of wave shapes for the electrical signal waveform for use in a surgical instrument, in accordance with at least one aspect of the present disclosure.

FIG. 14 illustrates one aspect of direct digital synthesis (DDS) circuit configured to generate a plurality of wave

shapes for the electrical signal waveform for use in surgical instrument, in accordance with at least one aspect of the present disclosure.

FIG. 15 illustrates one cycle of a discrete time digital electrical signal waveform, in accordance with at least one aspect of the present disclosure of an analog waveform (shown superimposed over a discrete time digital electrical signal waveform for comparison purposes), in accordance with at least one aspect of the present disclosure.

FIG. 16 is a diagram of a control system in accordance with one aspect of this disclosure.

FIG. 17 illustrates a proportional-integral-derivative (PID) controller feedback control system in accordance with one aspect of this disclosure.

FIG. 18 is an alternative system for controlling the frequency of an ultrasonic electromechanical system and detecting the impedance thereof, in accordance with at least one aspect of the present disclosure.

FIG. 19 is a spectra of the same ultrasonic device with a variety of different states and conditions of the end effector where phase and magnitude of the impedance of an ultrasonic transducer are plotted as a function of frequency, in accordance with at least one aspect of the present disclosure.

FIG. 20 is a graphical representation of a plot of a set of 3D training data S, where ultrasonic transducer impedance magnitude and phase are plotted as a function of frequency, in accordance with at least one aspect of the present disclosure.

FIG. 21 is a logic flow diagram depicting a control program or a logic configuration to determine jaw conditions based on the complex impedance characteristic pattern (fingerprint), in accordance with at least one aspect of the present disclosure.

FIG. 22 is a circle plot of complex impedance plotted as an imaginary component versus real components of a piezoelectric vibrator, in accordance with at least one aspect of the present disclosure.

FIG. 23 is a circle plot of complex admittance plotted as an imaginary component versus real components of a piezoelectric vibrator, in accordance with at least one aspect of the present disclosure.

FIG. 24 is a circle plot of complex admittance for a 55.5 kHz ultrasonic piezoelectric transducer.

FIG. 25 is a graphical display of an impedance analyzer showing impedance/admittance circle plots for an ultrasonic device with the jaw open and no loading where complex admittance is depicted in broken line and complex impedance is depicted in solid line, in accordance with at least one aspect of the present disclosure.

FIG. 26 is a graphical display of an impedance analyzer showing impedance/admittance circle plots for an ultrasonic device with the jaw clamped on dry chamois where complex admittance is depicted in broken line and complex impedance is depicted in solid line, in accordance with at least one aspect of the present disclosure.

FIG. 27 is a graphical display of an impedance analyzer showing impedance/admittance circle plots for an ultrasonic device with the jaw tip clamped on moist chamois where complex admittance is depicted in broken line and complex impedance is depicted in solid line, in accordance with at least one aspect of the present disclosure.

FIG. 28 is a graphical display of an impedance analyzer showing impedance/admittance circle plots for an ultrasonic device with the jaw fully clamped on moist chamois where complex admittance is depicted in broken line and complex impedance is depicted in solid line, in accordance with at least one aspect of the present disclosure.

FIG. 29 is a graphical display of an impedance analyzer showing impedance/admittance plots where frequency is swept from 48 kHz to 62 kHz to capture multiple resonances of an ultrasonic device with the jaw open where the rectangular overlay shown in broken line is to help see the circles, in accordance with at least one aspect of the present disclosure.

FIG. 30 is a logic flow diagram of a process depicting a control program or a logic configuration to determine jaw conditions based on estimates of the radius and offsets of an impedance/admittance circle, in accordance with at least one aspect of the present disclosure.

FIG. 31 is a logic flow diagram depicting a control program or a logic configuration of an adaptive process for identifying a hemostasis vessel, in accordance with at least one aspect of the present disclosure.

FIG. 32 is a graphical representation of ultrasonic transducer current profiles as a function of time for vein and artery vessel types, in accordance with at least one aspect of the present disclosure.

FIG. 33 is a logic flow diagram depicting a control program or a logic configuration of an adaptive process for identifying a hemostasis vessel, in accordance with at least one aspect of the present disclosure.

FIG. 34 is a graphical representation of ultrasonic transducer frequency profiles as a function of time for vein and artery vessel types, in accordance with at least one aspect of the present disclosure.

#### DESCRIPTION

Applicant of the present patent application also owns the following contemporaneously-filed U.S. patent applications, each of which is herein incorporated by reference in its entirety:

- U.S. patent application Ser. No. 16/144,335, titled METHODS FOR CONTROLLING TEMPERATURE IN ULTRASONIC DEVICE, now U.S. Pat. No. 11,259,830;
- U.S. patent application Ser. No. 16/144,345, titled ULTRASONIC SEALING ALGORITHM WITH TEMPERATURE CONTROL, now U.S. Patent Application Publication No. 2019/0274718;
- U.S. patent application Ser. No. 16/144,351, titled APPLICATION OF SMART ULTRASONIC BLADE TECHNOLOGY, now U.S. Patent Application Publication No. 2019/0274705;
- U.S. patent application Ser. No. 16/144,423, titled ADAPTIVE ADVANCED TISSUE TREATMENT PAD SAVER MODE, now U.S. Pat. No. 11,457,944;
- U.S. patent application Ser. No. 16/144,455, titled SMART BLADE TECHNOLOGY TO CONTROL BLADE INSTABILITY, now U.S. Pat. No. 11,344,326; and
- U.S. patent application Ser. No. 16/144,483, titled START TEMPERATURE OF BLADE, now U.S. Pat. No. 11,389,188.

Applicant of the present patent application also owns the following contemporaneously-filed U.S. patent applications, each of which is herein incorporated by reference in its entirety:

- U.S. patent application Ser. No. 16/144,383, titled METHODS FOR ESTIMATING AND CONTROLLING STATE OF ULTRASONIC END EFFECTOR, now U.S. Pat. No. 11,464,532;
- U.S. patent application Ser. No. 16/144,391, titled IN-THE-JAW CLASSIFIER BASED ON MODEL, now U.S. Patent Application Publication No. 16/144,391;

U.S. patent application Ser. No. 16/144,397, titled APPLICATION OF SMART BLADE TECHNOLOGY, now U.S. Pat. No. 11,399,858;

U.S. patent application Ser. No. 16/144,405, titled SMART BLADE AND POWER PULSING, now U.S. Pat. No. 11,337,746;

U.S. patent application Ser. No. 16/144,418, titled ADJUSTMENT OF COMPLEX IMPEDANCE TO COMPENSATE FOR LOST POWER IN AN ARTICULATING ULTRASONIC DEVICE, now U.S. Patent Application Publication No. 2019/0274662;

U.S. patent application Ser. No. 16/144,427, titled USING SPECTROSCOPY TO DETERMINE DEVICE USE STATE IN COMBO INSTRUMENT, now U.S. Pat. No. 11,534,196;

U.S. patent application Ser. No. 16/144,460, titled CALCIFIED VESSEL IDENTIFICATION, now U.S. Patent Application Publication No. 2019/0274713;

U.S. patent application Ser. No. 16/144,472, titled DETECTION OF LARGE VESSELS DURING PARENCHYMAL DISSECTION USING A SMART BLADE, now U.S. Patent Application Publication No. 2019/0274749;

U.S. patent application Ser. No. 16/144,478, titled SMART BLADE APPLICATION FOR REUSABLE AND DISPOSABLE DEVICES, now U.S. Patent Application Publication No. 2019/0274714;

U.S. patent application Ser. No. 16/144,486, titled LIVE TIME TISSUE CLASSIFICATION USING ELECTRICAL PARAMETERS, now U.S. Pat. No. 11,298,148; and

U.S. patent application Ser. No. 16/144,508, titled FINE DISSECTION MODE FOR TISSUE CLASSIFICATION, now U.S. Patent Application Publication No. 2019/0274752.

Applicant of the present application owns the following U.S. patent applications, filed on Sep. 10, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

- U.S. Provisional Patent Application Ser. No. 62/729,177, titled AUTOMATED DATA SCALING, ALIGNMENT, AND ORGANIZING BASED ON PREDEFINED PARAMETERS WITHIN A SURGICAL NETWORK BEFORE TRANSMISSION;
- U.S. provisional Patent Application Ser. No. 62/729,182, titled SENSING THE PATIENT POSITION AND CONTACT UTILIZING THE MONO-POLAR RETURN PAD ELECTRODE TO PROVIDE SITUATIONAL AWARENESS TO THE HUB;
- U.S. Provisional Patent Application Ser. No. 62/729,184, titled POWERED SURGICAL TOOL WITH A PREDEFINED ADJUSTABLE CONTROL ALGORITHM FOR CONTROLLING AT LEAST ONE END-EFFECTOR PARAMETER AND A MEANS FOR LIMITING THE ADJUSTMENT;
- U.S. Provisional Patent Application Ser. No. 62/729,183, titled SURGICAL NETWORK RECOMMENDATIONS FROM REAL TIME ANALYSIS OF PROCEDURE VARIABLES AGAINST A BASELINE HIGHLIGHTING DIFFERENCES FROM THE OPTIMAL SOLUTION;
- U.S. Provisional Patent Application Ser. No. 62/729,191, titled A CONTROL FOR A SURGICAL NETWORK OR SURGICAL NETWORK CONNECTED DEVICE THAT ADJUSTS ITS FUNCTION BASED ON A SENSED SITUATION OR USAGE;
- U.S. Provisional Patent Application Ser. No. 62/729,176, titled INDIRECT COMMAND AND CONTROL OF A FIRST OPERATING ROOM SYSTEM THROUGH THE

USE OF A SECOND OPERATING ROOM SYSTEM WITHIN A STERILE FIELD WHERE THE SECOND OPERATING ROOM SYSTEM HAS PRIMARY AND SECONDARY OPERATING MODES;

U.S. Provisional Patent Application Ser. No. 62/729,186, titled WIRELESS PAIRING OF A SURGICAL DEVICE WITH ANOTHER DEVICE WITHIN A STERILE SURGICAL FIELD BASED ON THE USAGE AND SITUATIONAL AWARENESS OF DEVICES; and

U.S. Provisional Patent Application Ser. No. 62/729,185, titled POWERED STAPLING DEVICE THAT IS CAPABLE OF ADJUSTING FORCE, ADVANCEMENT SPEED, AND OVERALL STROKE OF CUTTING MEMBER OF THE DEVICE BASED ON SENSED PARAMETER OF FIRING OR CLAMPING.

Applicant of the present application owns the following U.S. patent applications, filed on Aug. 28, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. patent application Ser. No. 16/115,214, titled ESTIMATING STATE OF ULTRASONIC END EFFECTOR AND CONTROL SYSTEM THEREFOR;

U.S. patent application Ser. No. 16/115,205, titled TEMPERATURE CONTROL OF ULTRASONIC END EFFECTOR AND CONTROL SYSTEM THEREFOR;

U.S. patent application Ser. No. 16/115,233, titled RADIO FREQUENCY ENERGY DEVICE FOR DELIVERING COMBINED ELECTRICAL SIGNALS;

U.S. patent application Ser. No. 16/115,208, titled CONTROLLING AN ULTRASONIC SURGICAL INSTRUMENT ACCORDING TO TISSUE LOCATION;

U.S. patent application Ser. No. 16/115,220, titled CONTROLLING ACTIVATION OF AN ULTRASONIC SURGICAL INSTRUMENT ACCORDING TO THE PRESENCE OF TISSUE;

U.S. patent application Ser. No. 16/115,232, titled DETERMINING TISSUE COMPOSITION VIA AN ULTRASONIC SYSTEM;

U.S. patent application Ser. No. 16/115,239, titled DETERMINING THE STATE OF AN ULTRASONIC ELECTROMECHANICAL SYSTEM ACCORDING TO FREQUENCY SHIFT;

U.S. patent application Ser. No. 16/115,247, titled DETERMINING THE STATE OF AN ULTRASONIC END EFFECTOR;

U.S. patent application Ser. No. 16/115,211, titled SITUATIONAL AWARENESS OF ELECTROSURGICAL SYSTEMS;

U.S. patent application Ser. No. 16/115,226, titled MECHANISMS FOR CONTROLLING DIFFERENT ELECTROMECHANICAL SYSTEMS OF AN ELECTROSURGICAL INSTRUMENT;

U.S. patent application Ser. No. 16/115,240, titled DETECTION OF END EFFECTOR EMERSION IN LIQUID;

U.S. patent application Ser. No. 16/115,249, titled INTERRUPTION OF ENERGY DUE TO INADVERTENT CAPACITIVE COUPLING;

U.S. patent application Ser. No. 16/115,256, titled INCREASING RADIO FREQUENCY TO CREATE PAD-LESS MONOPOLAR LOOP;

U.S. patent application Ser. No. 16/115,223, titled BIPOLAR COMBINATION DEVICE THAT AUTOMATICALLY ADJUSTS PRESSURE BASED ON ENERGY MODALITY; and

U.S. patent application Ser. No. 16/115,238, titled ACTIVATION OF ENERGY DEVICES.

Applicant of the present application owns the following U.S. patent applications, filed on Aug. 23, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. Provisional Patent Application No. 62/721,995, titled CONTROLLING AN ULTRASONIC SURGICAL INSTRUMENT ACCORDING TO TISSUE LOCATION;

U.S. Provisional Patent Application No. 62/721,998, titled SITUATIONAL AWARENESS OF ELECTROSURGICAL SYSTEMS;

U.S. Provisional Patent Application No. 62/721,999, titled INTERRUPTION OF ENERGY DUE TO INADVERTENT CAPACITIVE COUPLING;

U.S. Provisional Patent Application No. 62/721,994, titled BIPOLAR COMBINATION DEVICE THAT AUTOMATICALLY ADJUSTS PRESSURE BASED ON ENERGY MODALITY; and

U.S. Provisional Patent Application No. 62/721,996, titled RADIO FREQUENCY ENERGY DEVICE FOR DELIVERING COMBINED ELECTRICAL SIGNALS.

Applicant of the present application owns the following U.S. patent applications, filed on Jun. 30, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. Provisional Patent Application No. 62/692,747, titled SMART ACTIVATION OF AN ENERGY DEVICE BY ANOTHER DEVICE;

U.S. Provisional Patent Application No. 62/692,748, titled SMART ENERGY ARCHITECTURE; and

U.S. Provisional Patent Application No. 62/692,768, titled SMART ENERGY DEVICES.

Applicant of the present application owns the following U.S. patent applications, filed on Jun. 29, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. patent application Ser. No. 16/024,090, titled CAPACITIVE COUPLED RETURN PATH PAD WITH SEPARABLE ARRAY ELEMENTS;

U.S. patent application Ser. No. 16/024,057, titled CONTROLLING A SURGICAL INSTRUMENT ACCORDING TO SENSED CLOSURE PARAMETERS;

U.S. patent application Ser. No. 16/024,067, titled SYSTEMS FOR ADJUSTING END EFFECTOR PARAMETERS BASED ON PERIOPERATIVE INFORMATION;

U.S. patent application Ser. No. 16/024,075, titled SAFETY SYSTEMS FOR SMART POWERED SURGICAL STAPLING;

U.S. patent application Ser. No. 16/024,083, titled SAFETY SYSTEMS FOR SMART POWERED SURGICAL STAPLING;

U.S. patent application Ser. No. 16/024,094, titled SURGICAL SYSTEMS FOR DETECTING END EFFECTOR TISSUE DISTRIBUTION IRREGULARITIES;

U.S. patent application Ser. No. 16/024,138, titled SYSTEMS FOR DETECTING PROXIMITY OF SURGICAL END EFFECTOR TO CANCEROUS TISSUE;

U.S. patent application Ser. No. 16/024,150, titled SURGICAL INSTRUMENT CARTRIDGE SENSOR ASSEMBLIES;

U.S. patent application Ser. No. 16/024,160, titled VARIABLE OUTPUT CARTRIDGE SENSOR ASSEMBLY;

U.S. patent application Ser. No. 16/024,124, titled SURGICAL INSTRUMENT HAVING A FLEXIBLE ELECTRODE;

U.S. patent application Ser. No. 16/024,132, titled SURGICAL INSTRUMENT HAVING A FLEXIBLE CIRCUIT;  
 U.S. patent application Ser. No. 16/024,141, titled SURGICAL INSTRUMENT WITH A TISSUE MARKING ASSEMBLY;  
 U.S. patent application Ser. No. 16/024,162, titled SURGICAL SYSTEMS WITH PRIORITIZED DATA TRANSMISSION CAPABILITIES;  
 U.S. patent application Ser. No. 16/024,066, titled SURGICAL EVACUATION SENSING AND MOTOR CONTROL;  
 U.S. patent application Ser. No. 16/024,096, titled SURGICAL EVACUATION SENSOR ARRANGEMENTS;  
 U.S. patent application Ser. No. 16/024,116, titled SURGICAL EVACUATION FLOW PATHS;  
 U.S. patent application Ser. No. 16/024,149, titled SURGICAL EVACUATION SENSING AND GENERATOR CONTROL;  
 U.S. patent application Ser. No. 16/024,180, titled SURGICAL EVACUATION SENSING AND DISPLAY;  
 U.S. patent application Ser. No. 16/024,245, titled COMMUNICATION OF SMOKE EVACUATION SYSTEM PARAMETERS TO HUB OR CLOUD IN SMOKE EVACUATION MODULE FOR INTERACTIVE SURGICAL PLATFORM;  
 U.S. patent application Ser. No. 16/024,258, titled SMOKE EVACUATION SYSTEM INCLUDING A SEGMENTED CONTROL CIRCUIT FOR INTERACTIVE SURGICAL PLATFORM;  
 U.S. patent application Ser. No. 16/024,265, titled SURGICAL EVACUATION SYSTEM WITH A COMMUNICATION CIRCUIT FOR COMMUNICATION BETWEEN A FILTER AND A SMOKE EVACUATION DEVICE; and  
 U.S. patent application Ser. No. 16/024,273, titled DUAL IN-SERIES LARGE AND SMALL DROPLET FILTERS.

Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on Jun. 28, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. Provisional Patent Application Ser. No. 62/691,228, titled A METHOD OF USING REINFORCED FLEX CIRCUITS WITH MULTIPLE SENSORS WITH ELECTROSURGICAL DEVICES;  
 U.S. Provisional Patent Application Ser. No. 62/691,227, titled CONTROLLING A SURGICAL INSTRUMENT ACCORDING TO SENSED CLOSURE PARAMETERS;  
 U.S. Provisional Patent Application Ser. No. 62/691,230, titled SURGICAL INSTRUMENT HAVING A FLEXIBLE ELECTRODE;  
 U.S. Provisional Patent Application Ser. No. 62/691,219, titled SURGICAL EVACUATION SENSING AND MOTOR CONTROL;  
 U.S. Provisional Patent Application Ser. No. 62/691,257, titled COMMUNICATION OF SMOKE EVACUATION SYSTEM PARAMETERS TO HUB OR CLOUD IN SMOKE EVACUATION MODULE FOR INTERACTIVE SURGICAL PLATFORM;  
 U.S. Provisional Patent Application Ser. No. 62/691,262, titled SURGICAL EVACUATION SYSTEM WITH A COMMUNICATION CIRCUIT FOR COMMUNICATION BETWEEN A FILTER AND A SMOKE EVACUATION DEVICE; and

U.S. Provisional Patent Application Ser. No. 62/691,251, titled DUAL IN-SERIES LARGE AND SMALL DROPLET FILTERS.

Applicant of the present application owns the following U.S. Provisional Patent Application, filed on Apr. 19, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. Provisional Patent Application Ser. No. 62/659,900, titled METHOD OF HUB COMMUNICATION.

Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on Mar. 30, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. Provisional Patent Application No. 62/650,898 filed on Mar. 30, 2018, titled CAPACITIVE COUPLED RETURN PATH PAD WITH SEPARABLE ARRAY ELEMENTS;

U.S. Provisional Patent Application Ser. No. 62/650,887, titled SURGICAL SYSTEMS WITH OPTIMIZED SENSING CAPABILITIES;

U.S. Provisional Patent Application Ser. No. 62/650,882, titled SMOKE EVACUATION MODULE FOR INTERACTIVE SURGICAL PLATFORM; and

U.S. Provisional Patent Application Ser. No. 62/650,877, titled SURGICAL SMOKE EVACUATION SENSING AND CONTROLS

Applicant of the present application owns the following U.S. patent applications, filed on Mar. 29, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. patent application Ser. No. 15/940,641, titled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES;

U.S. patent application Ser. No. 15/940,648, titled INTERACTIVE SURGICAL SYSTEMS WITH CONDITION HANDLING OF DEVICES AND DATA CAPABILITIES;

U.S. patent application Ser. No. 15/940,656, titled SURGICAL HUB COORDINATION OF CONTROL AND COMMUNICATION OF OPERATING ROOM DEVICES;

U.S. patent application Ser. No. 15/940,666, titled SPATIAL AWARENESS OF SURGICAL HUBS IN OPERATING ROOMS;

U.S. patent application Ser. No. 15/940,670, titled COOPERATIVE UTILIZATION OF DATA DERIVED FROM SECONDARY SOURCES BY INTELLIGENT SURGICAL HUBS;

U.S. patent application Ser. No. 15/940,677, titled SURGICAL HUB CONTROL ARRANGEMENTS;

U.S. patent application Ser. No. 15/940,632, titled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD;

U.S. patent application Ser. No. 15/940,640, titled COMMUNICATION HUB AND STORAGE DEVICE FOR STORING PARAMETERS AND STATUS OF A SURGICAL DEVICE TO BE SHARED WITH CLOUD BASED ANALYTICS SYSTEMS;

U.S. patent application Ser. No. 15/940,645, titled SELF DESCRIBING DATA PACKETS GENERATED AT AN ISSUING INSTRUMENT;

U.S. patent application Ser. No. 15/940,649, titled DATA PAIRING TO INTERCONNECT A DEVICE MEASURED PARAMETER WITH AN OUTCOME;

U.S. patent application Ser. No. 15/940,654, titled SURGICAL HUB SITUATIONAL AWARENESS;

U.S. patent application Ser. No. 15/940,663, titled SURGICAL SYSTEM DISTRIBUTED PROCESSING;

U.S. patent application Ser. No. 15/940,668, titled AGGREGATION AND REPORTING OF SURGICAL HUB DATA;

U.S. patent application Ser. No. 15/940,671, titled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER;

U.S. patent application Ser. No. 15/940,686, titled DISPLAY OF ALIGNMENT OF STAPLE CARTRIDGE TO PRIOR LINEAR STAPLE LINE;

U.S. patent application Ser. No. 15/940,700, titled STERILE FIELD INTERACTIVE CONTROL DISPLAYS;

U.S. patent application Ser. No. 15/940,629, titled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS;

U.S. patent application Ser. No. 15/940,704, titled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT;

U.S. patent application Ser. No. 15/940,722, titled CHARACTERIZATION OF TISSUE IRREGULARITIES THROUGH THE USE OF MONO-CHROMATIC LIGHT REFRACTIVITY; and

U.S. patent application Ser. No. 15/940,742, titled DUAL CMOS ARRAY IMAGING.

U.S. patent application Ser. No. 15/940,636, titled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES;

U.S. patent application Ser. No. 15/940,653, titled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL HUBS;

U.S. patent application Ser. No. 15/940,660, titled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER;

U.S. patent application Ser. No. 15/940,679, titled CLOUD-BASED MEDICAL ANALYTICS FOR LINKING OF LOCAL USAGE TRENDS WITH THE RESOURCE ACQUISITION BEHAVIORS OF LARGER DATA SET;

U.S. patent application Ser. No. 15/940,694, titled CLOUD-BASED MEDICAL ANALYTICS FOR MEDICAL FACILITY SEGMENTED INDIVIDUALIZATION OF INSTRUMENT FUNCTION;

U.S. patent application Ser. No. 15/940,634, titled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEASURES;

U.S. patent application Ser. No. 15/940,706, titled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK; and

U.S. patent application Ser. No. 15/940,675, titled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES.

U.S. patent application Ser. No. 15/940,627, titled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

U.S. patent application Ser. No. 15/940,637, titled COMMUNICATION ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

U.S. patent application Ser. No. 15/940,642, titled CONTROLS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

U.S. patent application Ser. No. 15/940,676, titled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

U.S. patent application Ser. No. 15/940,680, titled CONTROLLERS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

U.S. patent application Ser. No. 15/940,683, titled COOPERATIVE SURGICAL ACTIONS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

U.S. patent application Ser. No. 15/940,690, titled DISPLAY ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; and

U.S. patent application Ser. No. 15/940,711, titled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS.

Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on Mar. 28, 2018, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. Provisional Patent Application Ser. No. 62/649,302, titled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES;

U.S. Provisional Patent Application Ser. No. 62/649,294, titled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD;

U.S. Provisional Patent Application Ser. No. 62/649,300, titled SURGICAL HUB SITUATIONAL AWARENESS;

U.S. Provisional Patent Application Ser. No. 62/649,309, titled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER;

U.S. Provisional Patent Application Ser. No. 62/649,310, titled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS;

U.S. Provisional Patent Application Ser. No. 62/649,291, titled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT;

U.S. Provisional Patent Application Ser. No. 62/649,296, titled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES;

U.S. Provisional Patent Application Ser. No. 62/649,333, titled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER;

U.S. Provisional Patent Application Ser. No. 62/649,327, titled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEASURES;

U.S. Provisional Patent Application Ser. No. 62/649,315, titled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK;

U.S. Provisional Patent Application Ser. No. 62/649,313, titled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES;

U.S. Provisional Patent Application Ser. No. 62/649,320, titled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

U.S. Provisional Patent Application Ser. No. 62/649,307, titled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; and

U.S. Provisional Patent Application Ser. No. 62/649,323, titled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS.

Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on Dec. 28, 2017, the disclosure of each of which is herein incorporated by reference in its entirety:

U.S. Provisional Patent Application Serial No. U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM;

U.S. Provisional Patent Application Ser. No. 62/611,340, titled CLOUD-BASED MEDICAL ANALYTICS; and

U.S. Provisional Patent Application Ser. No. 62/611,339, titled ROBOT ASSISTED SURGICAL PLATFORM.

Before explaining various aspects of surgical devices and generators in detail, it should be noted that the illustrative examples are not limited in application or use to the details of construction and arrangement of parts illustrated in the accompanying drawings and description. The illustrative examples may be implemented or incorporated in other aspects, variations and modifications, and may be practiced or carried out in various ways. Further, unless otherwise indicated, the terms and expressions employed herein have been chosen for the purpose of describing the illustrative examples for the convenience of the reader and are not for the purpose of limitation thereof. Also, it will be appreciated that one or more of the following-described aspects, expressions of aspects, and/or examples, can be combined with any one or more of the other following-described aspects, expressions of aspects and/or examples.

Various aspects are directed to improved ultrasonic surgical devices, electrosurgical devices and generators for use therewith. Aspects of the ultrasonic surgical devices can be configured for transecting and/or coagulating tissue during surgical procedures, for example. Aspects of the electrosurgical devices can be configured for transecting, coagulating, scaling, welding and/or desiccating tissue during surgical procedures, for example.

#### Adaptive Ultrasonic Blade Control Algorithms

In various aspects smart ultrasonic energy devices may comprise adaptive algorithms to control the operation of the ultrasonic blade. In one aspect, the ultrasonic blade adaptive control algorithms are configured to identify tissue type and adjust device parameters. In one aspect, the ultrasonic blade control algorithms are configured to parameterize tissue type. An algorithm to detect the collagen/elastic ratio of tissue to tune the amplitude of the distal tip of the ultrasonic blade is described in the following section of the present disclosure. Various aspects of smart ultrasonic energy devices are described herein in connection with FIGS. 1-2, for example. Accordingly, the following description of adaptive ultrasonic blade control algorithms should be read in conjunction with FIGS. 1-2 and the description associated therewith.

In certain surgical procedures it would be desirable to employ adaptive ultrasonic blade control algorithms. In one aspect, adaptive ultrasonic blade control algorithms may be employed to adjust the parameters of the ultrasonic device based on the type of tissue in contact with the ultrasonic blade. In one aspect, the parameters of the ultrasonic device may be adjusted based on the location of the tissue within the jaws of the ultrasonic end effector, for example, the location of the tissue between the clamp arm and the ultrasonic blade. The impedance of the ultrasonic transducer may be employed to differentiate what percentage of the tissue is located in the distal or proximal end of the end effector. The reactions of the ultrasonic device may be based on the tissue type or compressibility of the tissue. In another aspect, the parameters of the ultrasonic device may be adjusted based on the identified tissue type or parameterization. For example, the mechanical displacement amplitude of the distal tip of the ultrasonic blade may be tuned based on the ratio of collagen to elastin tissue detected during the tissue identification procedure. The ratio of collagen to elastin tissue may be detected using a variety of techniques including infrared (IR) surface reflectance and emissivity. Electrical continuity across a jaw equipped with

electrodes may be employed to determine what percentage of the jaw is covered with tissue.

FIG. 1 is a system **800** configured to execute adaptive ultrasonic blade control algorithms in a surgical data network comprising a modular communication hub, in accordance with at least one aspect of the present disclosure. In one aspect, the generator module **240** is configured to execute the adaptive ultrasonic blade control algorithm(s) **802** as described herein. In another aspect, the device/instrument **235** is configured to execute the adaptive ultrasonic blade control algorithm(s) **804** as described herein with reference to FIGS. 19-34. In another aspect, both the device/instrument **235** and the device/instrument **235** are configured to execute the adaptive ultrasonic blade control algorithms **802**, **804** as described herein with reference to FIGS. 19-34.

The generator module **240** may comprise a patient isolated stage in communication with a non-isolated stage via a power transformer. A secondary winding of the power transformer is contained in the isolated stage and may comprise a tapped configuration (e.g., a center-tapped or a non-center-tapped configuration) to define drive signal outputs for delivering drive signals to different surgical instruments, such as, for example, an ultrasonic surgical instrument, an RF electrosurgical instrument, and a multifunction surgical instrument which includes ultrasonic and RF energy modes that can be delivered alone or simultaneously. In particular, the drive signal outputs may output an ultrasonic drive signal (e.g., a 420V root-mean-square (RMS) drive signal) to an ultrasonic surgical instrument **241**, and the drive signal outputs may output an RF electrosurgical drive signal (e.g., a 100V RMS drive signal) to an RF electrosurgical instrument **241**. Aspects of the generator module **240** are described herein with reference to FIGS. 7-12.

The generator module **240** or the device/instrument **235** or both are coupled to the modular control tower **236** connected to multiple operating theater devices such as, for example, intelligent surgical instruments, robots, and other computerized devices located in the operating theater. In some aspects, a surgical data network may include a modular communication hub configured to connect modular devices located in one or more operating theaters of a healthcare facility, or any room in a healthcare facility specially equipped for surgical operations, to a cloud-based system (e.g., the cloud **204** that may include a remote server **213** coupled to a storage device).

Modular devices located in the operating theater may be coupled to the modular communication hub. The network hub and/or the network switch may be coupled to a network router to connect the devices to the cloud **204** or a local computer system. Data associated with the devices may be transferred to cloud-based computers via the router for remote data processing and manipulation. Data associated with the devices may also be transferred to a local computer system for local data processing and manipulation. Modular devices located in the same operating theater also may be coupled to a network switch. The network switch may be coupled to the network hub and/or the network router to connect to the devices to the cloud **204**. Data associated with the devices may be transferred to the cloud **204** via the network router for data processing and manipulation. Data associated with the devices may also be transferred to the local computer system for local data processing and manipulation.

It will be appreciated that cloud computing relies on sharing computing resources rather than having local servers or personal devices to handle software applications. The

word “cloud” may be used as a metaphor for “the Internet,” although the term is not limited as such. Accordingly, the term “cloud computing” may be used herein to refer to “a type of Internet-based computing,” where different services—such as servers, storage, and applications—are delivered to the modular communication hub and/or computer system located in the surgical theater (e.g., a fixed, mobile, temporary, or field operating room or space) and to devices connected to the modular communication hub and/or computer system through the Internet. The cloud infrastructure may be maintained by a cloud service provider. In this context, the cloud service provider may be the entity that coordinates the usage and control of the devices located in one or more operating theaters. The cloud computing services can perform a large number of calculations based on the data gathered by smart surgical instruments, robots, and other computerized devices located in the operating theater. The hub hardware enables multiple devices or connections to be connected to a computer that communicates with the cloud computing resources and storage.

FIG. 1 further illustrates some aspects of a computer-implemented interactive surgical system comprising a modular communication hub that may include the system 800 configured to execute adaptive ultrasonic blade control algorithms in a surgical data network. The surgical system may include at least one surgical hub in communication with a cloud 204 that may include a remote server 213. In one aspect, the computer-implemented interactive surgical system comprises a modular control tower 236 connected to multiple operating theater devices such as, for example, intelligent surgical instruments, robots, and other computerized devices located in the operating theater. The modular control tower 236 may comprise a modular communication hub coupled to a computer system. In some aspects, the modular control tower 236 is coupled to an imaging module that is coupled to an endoscope, a generator module 240 that is coupled to an energy device 241, and a smart device/instrument 235 optionally coupled to a display 237. The operating theater devices are coupled to cloud computing resources and data storage via the modular control tower 236. A robot hub 222 also may be connected to the modular control tower 236 and to the cloud computing resources. The devices/instruments 235, visualization systems 208, among others, may be coupled to the modular control tower 236 via wired or wireless communication standards or protocols, as described herein. The modular control tower 236 may be coupled to a hub display 215 (e.g., monitor, screen) to display and overlay images received from the imaging module, device/instrument display, and/or other visualization systems 208. The hub display 215 also may display data received from devices connected to the modular control tower in conjunction with images and overlaid images.

#### Generator Hardware

FIG. 2 illustrates an example of a generator 900, which is one form of a generator configured to couple to an ultrasonic instrument and further configured to execute adaptive ultrasonic blade control algorithms in a surgical data network comprising a modular communication hub as shown in FIG. 1. The generator 900 is configured to deliver multiple energy modalities to a surgical instrument. The generator 900 provides RF and ultrasonic signals for delivering energy to a surgical instrument either independently or simultaneously. The RF and ultrasonic signals may be provided alone or in combination and may be provided simultaneously. As noted above, at least one generator output can deliver

multiple energy modalities (e.g., ultrasonic, bipolar or monopolar RF, irreversible and/or reversible electroporation, and/or microwave energy, among others) through a single port, and these signals can be delivered separately or simultaneously to the end effector to treat tissue. The generator 900 comprises a processor 902 coupled to a waveform generator 904. The processor 902 and waveform generator 904 are configured to generate a variety of signal waveforms based on information stored in a memory coupled to the processor 902, not shown for clarity of disclosure. The digital information associated with a waveform is provided to the waveform generator 904 which includes one or more DAC circuits to convert the digital input into an analog output. The analog output is fed to an amplifier 906 for signal conditioning and amplification. The conditioned and amplified output of the amplifier 906 is coupled to a power transformer 908. The signals are coupled across the power transformer 908 to the secondary side, which is in the patient isolation side. A first signal of a first energy modality is provided to the surgical instrument between the terminals labeled ENERGY<sub>1</sub> and RETURN. A second signal of a second energy modality is coupled across a capacitor 910 and is provided to the surgical instrument between the terminals labeled ENERGY<sub>2</sub> and RETURN. It will be appreciated that more than two energy modalities may be output and thus the subscript “n” may be used to designate that up to n ENERGY<sub>n</sub> terminals may be provided, where n is a positive integer greater than 1. It also will be appreciated that up to “n” return paths RETURN<sub>n</sub> may be provided without departing from the scope of the present disclosure.

A first voltage sensing circuit 912 is coupled across the terminals labeled ENERGY<sub>1</sub> and the RETURN path to measure the output voltage therebetween. A second voltage sensing circuit 924 is coupled across the terminals labeled ENERGY<sub>2</sub> and the RETURN path to measure the output voltage therebetween. A current sensing circuit 914 is disposed in series with the RETURN leg of the secondary side of the power transformer 908 as shown to measure the output current for either energy modality. If different return paths are provided for each energy modality, then a separate current sensing circuit should be provided in each return leg. The outputs of the first and second voltage sensing circuits 912, 924 are provided to respective isolation transformers 928, 922 and the output of the current sensing circuit 914 is provided to another isolation transformer 916. The outputs of the isolation transformers 916, 928, 922 in the on the primary side of the power transformer 908 (non-patient isolated side) are provided to a one or more ADC circuit 926. The digitized output of the ADC circuit 926 is provided to the processor 902 for further processing and computation. The output voltages and output current feedback information can be employed to adjust the output voltage and current provided to the surgical instrument and to compute output impedance, among other parameters. Input/output communications between the processor 902 and patient isolated circuits is provided through an interface circuit 920. Sensors also may be in electrical communication with the processor 902 by way of the interface circuit 920.

In one aspect, the impedance may be determined by the processor 902 by dividing the output of either the first voltage sensing circuit 912 coupled across the terminals labeled ENERGY<sub>1</sub>/RETURN or the second voltage sensing circuit 924 coupled across the terminals labeled ENERGY<sub>2</sub>/RETURN by the output of the current sensing circuit 914 disposed in series with the RETURN leg of the secondary side of the power transformer 908. The outputs of the first and second voltage sensing circuits 912, 924 are provided to

separate isolations transformers **928**, **922** and the output of the current sensing circuit **914** is provided to another isolation transformer **916**. The digitized voltage and current sensing measurements from the ADC circuit **926** are provided to the processor **902** for computing impedance. As an example, the first energy modality ENERGY<sub>1</sub> may be ultrasonic energy and the second energy modality ENERGY<sub>2</sub> may be RF energy. Nevertheless, in addition to ultrasonic and bipolar or monopolar RF energy modalities, other energy modalities include irreversible and/or reversible electroporation and/or microwave energy, among others. Also, although the example illustrated in FIG. 2 shows a single return path RETURN may be provided for two or more energy modalities, in other aspects, multiple return paths RETURN<sub>n</sub> may be provided for each energy modality ENERGY<sub>n</sub>. Thus, as described herein, the ultrasonic transducer impedance may be measured by dividing the output of the first voltage sensing circuit **912** by the current sensing circuit **914** and the tissue impedance may be measured by dividing the output of the second voltage sensing circuit **924** by the current sensing circuit **914**.

As shown in FIG. 2, the generator **900** comprising at least one output port can include a power transformer **908** with a single output and with multiple taps to provide power in the form of one or more energy modalities, such as ultrasonic, bipolar or monopolar RF, irreversible and/or reversible electroporation, and/or microwave energy, among others, for example, to the end effector depending on the type of treatment of tissue being performed. For example, the generator **900** can deliver energy with higher voltage and lower current to drive an ultrasonic transducer, with lower voltage and higher current to drive RF electrodes for sealing tissue, or with a coagulation waveform for spot coagulation using either monopolar or bipolar RF electrosurgical electrodes. The output waveform from the generator **900** can be steered, switched, or filtered to provide the frequency to the end effector of the surgical instrument. The connection of an ultrasonic transducer to the generator **900** output would be preferably located between the output labeled ENERGY<sub>1</sub> and RETURN as shown in FIG. 2. In one example, a connection of RF bipolar electrodes to the generator **900** output would be preferably located between the output labeled ENERGY<sub>2</sub> and RETURN. In the case of monopolar output, the preferred connections would be active electrode (e.g., pencil or other probe) to the ENERGY<sub>2</sub> output and a suitable return pad connected to the RETURN output.

Additional details are disclosed in U.S. Patent Application Publication No. 2017/0086914, titled TECHNIQUES FOR OPERATING GENERATOR FOR DIGITALLY GENERATING ELECTRICAL SIGNAL WAVEFORMS AND SURGICAL INSTRUMENTS, which published on Mar. 30, 2017, which is herein incorporated by reference in its entirety.

As used throughout this description, the term “wireless” and its derivatives may be used to describe circuits, devices, systems, methods, techniques, communications channels, etc., that may communicate data through the use of modulated electromagnetic radiation through a non-solid medium. The term does not imply that the associated devices do not contain any wires, although in some aspects they might not. The communication module may implement any of a number of wireless or wired communication standards or protocols, including but not limited to W-Fi (IEEE 802.11 family), WiMAX (IEEE 802.16 family), IEEE 802.20, long term evolution (LTE), Ev-DO, HSPA+, HSDPA+, HSUPA+, EDGE, GSM, GPRS, CDMA, TDMA, DECT, Bluetooth, Ethernet derivatives thereof, as well as any other wireless

and wired protocols that are designated as 3G, 4G, 5G, and beyond. The computing module may include a plurality of communication modules. For instance, a first communication module may be dedicated to shorter range wireless communications such as Wi-Fi and Bluetooth and a second communication module may be dedicated to longer range wireless communications such as GPS, EDGE, GPRS, CDMA, WiMAX, LTE, Ev-DO, and others.

As used herein a processor or processing unit is an electronic circuit which performs operations on some external data source, usually memory or some other data stream. The term is used herein to refer to the central processor (central processing unit) in a system or computer systems (especially systems on a chip (SoCs)) that combine a number of specialized “processors.”

As used herein, a system on a chip or system on chip (SoC or SOC) is an integrated circuit (also known as an “IC” or “chip”) that integrates all components of a computer or other electronic systems. It may contain digital, analog, mixed-signal, and often radio-frequency functions—all on a single substrate. A SoC integrates a microcontroller (or microprocessor) with advanced peripherals like graphics processing unit (GPU), W-Fi module, or coprocessor. A SoC may or may not contain built-in memory.

As used herein, a microcontroller or controller is a system that integrates a microprocessor with peripheral circuits and memory. A microcontroller (or MCU for microcontroller unit) may be implemented as a small computer on a single integrated circuit. It may be similar to a SoC; an SoC may include a microcontroller as one of its components. A microcontroller may contain one or more core processing units (CPUs) along with memory and programmable input/output peripherals. Program memory in the form of Ferroelectric RAM, NOR flash or OTP ROM is also often included on chip, as well as a small amount of RAM. Microcontrollers may be employed for embedded applications, in contrast to the microprocessors used in personal computers or other general purpose applications consisting of various discrete chips.

As used herein, the term controller or microcontroller may be a stand-alone IC or chip device that interfaces with a peripheral device. This may be a link between two parts of a computer or a controller on an external device that manages the operation of (and connection with) that device.

Any of the processors or microcontrollers described herein, may be implemented by any single core or multicore processor such as those known under the trade name ARM Cortex by Texas Instruments. In one aspect, the processor may be an LM4F230H5QR ARM Cortex-M4F Processor Core, available from Texas Instruments, for example, comprising on-chip memory of 256 KB single-cycle flash memory, or other non-volatile memory, up to 40 MHz, a prefetch buffer to improve performance above 40 MHz, a 32 KB single-cycle serial random access memory (SRAM), internal read-only memory (ROM) loaded with StellarisWare® software, 2 KB electrically erasable programmable read-only memory (EEPROM), one or more pulse width modulation (PWM) modules, one or more quadrature encoder inputs (QEI) analog, one or more 12-bit Analog-to-Digital Converters (ADC) with 12 analog input channels, details of which are available for the product datasheet.

In one aspect, the processor may comprise a safety controller comprising two controller-based families such as TMS570 and RM4x known under the trade name Hercules ARM Cortex R4, also by Texas Instruments. The safety controller may be configured specifically for IEC 61508 and ISO 26262 safety critical applications, among others, to

provide advanced integrated safety features while delivering scalable performance, connectivity, and memory options.

Modular devices include the modules (as described in connection with FIG. 3, for example) that are receivable within a surgical hub and the surgical devices or instruments that can be connected to the various modules in order to connect or pair with the corresponding surgical hub. The modular devices include, for example, intelligent surgical instruments, medical imaging devices, suction/irrigation devices, smoke evacuators, energy generators, ventilators, insufflators, and displays. The modular devices described herein can be controlled by control algorithms. The control algorithms can be executed on the modular device itself, on the surgical hub to which the particular modular device is paired, or on both the modular device and the surgical hub (e.g., via a distributed computing architecture). In some exemplifications, the modular devices' control algorithms control the devices based on data sensed by the modular device itself (i.e., by sensors in, on, or connected to the modular device). This data can be related to the patient being operated on (e.g., tissue properties or insufflation pressure) or the modular device itself (e.g., the rate at which a knife is being advanced, motor current, or energy levels). For example, a control algorithm for a surgical stapling and cutting instrument can control the rate at which the instrument's motor drives its knife through tissue according to resistance encountered by the knife as it advances.

FIG. 3 illustrates one form of a surgical system 1000 comprising a generator 1100 and various surgical instruments 1104, 1106, 1108 usable therewith, where the surgical instrument 1104 is an ultrasonic surgical instrument, the surgical instrument 1106 is an RF electrosurgical instrument, and the multifunction surgical instrument 1108 is a combination ultrasonic/RF electrosurgical instrument. The generator 1100 is configurable for use with a variety of surgical instruments. According to various forms, the generator 1100 may be configurable for use with different surgical instruments of different types including, for example, ultrasonic surgical instruments 1104, RF electrosurgical instruments 1106, and multifunction surgical instruments 1108 that integrate RF and ultrasonic energies delivered simultaneously from the generator 1100. Although in the form of FIG. 3 the generator 1100 is shown separate from the surgical instruments 1104, 1106, 1108 in one form, the generator 1100 may be formed integrally with any of the surgical instruments 1104, 1106, 1108 to form a unitary surgical system. The generator 1100 comprises an input device 1110 located on a front panel of the generator 1100 console. The input device 1110 may comprise any suitable device that generates signals suitable for programming the operation of the generator 1100. The generator 1100 may be configured for wired or wireless communication.

The generator 1100 is configured to drive multiple surgical instruments 1104, 1106, 1108. The first surgical instrument is an ultrasonic surgical instrument 1104 and comprises a handpiece 1105 (HP), an ultrasonic transducer 1120, a shaft 1126, and an end effector 1122. The end effector 1122 comprises an ultrasonic blade 1128 acoustically coupled to the ultrasonic transducer 1120 and a clamp arm 1140. The handpiece 1105 comprises a trigger 1143 to operate the clamp arm 1140 and a combination of the toggle buttons 1134a, 1134b, 1134c to energize and drive the ultrasonic blade 1128 or other function. The toggle buttons 1134a, 1134b, 1134c can be configured to energize the ultrasonic transducer 1120 with the generator 1100.

The generator 1100 also is configured to drive a second surgical instrument 1106. The second surgical instrument

1106 is an RF electrosurgical instrument and comprises a handpiece 1107 (HP), a shaft 1127, and an end effector 1124. The end effector 1124 comprises electrodes in clamp arms 1142a, 1142b and return through an electrical conductor portion of the shaft 1127. The electrodes are coupled to and energized by a bipolar energy source within the generator 1100. The handpiece 1107 comprises a trigger 1145 to operate the clamp arms 1142a, 1142b and an energy button 1135 to actuate an energy switch to energize the electrodes in the end effector 1124.

The generator 1100 also is configured to drive a multifunction surgical instrument 1108. The multifunction surgical instrument 1108 comprises a handpiece 1109 (HP), a shaft 1129, and an end effector 1125. The end effector 1125 comprises an ultrasonic blade 1149 and a clamp arm 1146. The ultrasonic blade 1149 is acoustically coupled to the ultrasonic transducer 1120. The handpiece 1109 comprises a trigger 1147 to operate the clamp arm 1146 and a combination of the toggle buttons 1137a, 1137b, 1137c to energize and drive the ultrasonic blade 1149 or other function. The toggle buttons 1137a, 1137b, 1137c can be configured to energize the ultrasonic transducer 1120 with the generator 1100 and energize the ultrasonic blade 1149 with a bipolar energy source also contained within the generator 1100.

The generator 1100 is configurable for use with a variety of surgical instruments. According to various forms, the generator 1100 may be configurable for use with different surgical instruments of different types including, for example, the ultrasonic surgical instrument 1104, the RF electrosurgical instrument 1106, and the multifunction surgical instrument 1108 that integrates RF and ultrasonic energies delivered simultaneously from the generator 1100. Although in the form of FIG. 3 the generator 1100 is shown separate from the surgical instruments 1104, 1106, 1108, in another form the generator 1100 may be formed integrally with any one of the surgical instruments 1104, 1106, 1108 to form a unitary surgical system. As discussed above, the generator 1100 comprises an input device 1110 located on a front panel of the generator 1100 console. The input device 1110 may comprise any suitable device that generates signals suitable for programming the operation of the generator 1100. The generator 1100 also may comprise one or more output devices 1112. Further aspects of generators for digitally generating electrical signal waveforms and surgical instruments are described in US patent publication US-2017-0086914-A1, which is herein incorporated by reference in its entirety.

FIG. 4 is an end effector 1122 of the example ultrasonic device 1104, in accordance with at least one aspect of the present disclosure. The end effector 1122 may comprise a blade 1128 that may be coupled to the ultrasonic transducer 1120 via a wave guide. When driven by the ultrasonic transducer 1120, the blade 1128 may vibrate and, when brought into contact with tissue, may cut and/or coagulate the tissue, as described herein. According to various aspects, and as illustrated in FIG. 4, the end effector 1122 may also comprise a clamp arm 1140 that may be configured for cooperative action with the blade 1128 of the end effector 1122. With the blade 1128, the clamp arm 1140 may comprise a set of jaws. The clamp arm 1140 may be pivotally connected at a distal end of a shaft 1126 of the instrument portion 1104. The clamp arm 1140 may include a clamp arm tissue pad 1163, which may be formed from TEFLON® or other suitable low-friction material. The pad 1163 may be mounted for cooperation with the blade 1128, with pivotal movement of the clamp arm 1140 positioning the clamp pad 1163 in substantially parallel relationship to, and in contact

with, the blade **1128**. By this construction, a tissue bite to be clamped may be grasped between the tissue pad **1163** and the blade **1128**. The tissue pad **1163** may be provided with a sawtooth-like configuration including a plurality of axially spaced, proximally extending gripping teeth **1161** to enhance the gripping of tissue in cooperation with the blade **1128**. The clamp arm **1140** may transition from the open position shown in FIG. 4 to a closed position (with the clamp arm **1140** in contact with or proximity to the blade **1128**) in any suitable manner. For example, the handpiece **1105** may comprise a jaw closure trigger. When actuated by a clinician, the jaw closure trigger may pivot the clamp arm **1140** in any suitable manner.

The generator **1100** may be activated to provide the drive signal to the ultrasonic transducer **1120** in any suitable manner. For example, the generator **1100** may comprise a foot switch **1430** (FIG. 5) coupled to the generator **1100** via a footswitch cable **1432**. A clinician may activate the ultrasonic transducer **1120**, and thereby the ultrasonic transducer **1120** and blade **1128**, by depressing the foot switch **1430**. In addition, or instead of the foot switch **1430**, some aspects of the device **1104** may utilize one or more switches positioned on the handpiece **1105** that, when activated, may cause the generator **1100** to activate the ultrasonic transducer **1120**. In one aspect, for example, the one or more switches may comprise a pair of toggle buttons **1134**, **1134a**, **1134b** (FIG. 3), for example, to determine an operating mode of the device **1104**. When the toggle button **1134a** is depressed, for example, the ultrasonic generator **1100** may provide a maximum drive signal to the ultrasonic transducer **1120**, causing it to produce maximum ultrasonic energy output. Depressing toggle button **1134b** may cause the ultrasonic generator **1100** to provide a user-selectable drive signal to the ultrasonic transducer **1120**, causing it to produce less than the maximum ultrasonic energy output. The device **1104** additionally or alternatively may comprise a second switch to, for example, indicate a position of a jaw closure trigger for operating the jaws via the clamp arm **1140** of the end effector **1122**. Also, in some aspects, the ultrasonic generator **1100** may be activated based on the position of the jaw closure trigger, (e.g., as the clinician depresses the jaw closure trigger to close the jaws via the clamp arm **1140**, ultrasonic energy may be applied).

Additionally or alternatively, the one or more switches may comprise a toggle button **1134** that, when depressed, causes the generator **1100** to provide a pulsed output (FIG. 3). The pulses may be provided at any suitable frequency and grouping, for example. In certain aspects, the power level of the pulses may be the power levels associated with toggle buttons **1134a**, **1134b** (maximum, less than maximum), for example.

It will be appreciated that a device **1104** may comprise any combination of the toggle buttons **1134a**, **1134b**, **1134** (FIG. 3). For example, the device **1104** could be configured to have only two toggle buttons: a toggle button **1134a** for producing maximum ultrasonic energy output and a toggle button **1134** for producing a pulsed output at either the maximum or less than maximum power level per. In this way, the drive signal output configuration of the generator **1100** could be five continuous signals, or any discrete number of individual pulsed signals (1, 2, 3, 4, or 5). In certain aspects, the specific drive signal configuration may be controlled based upon, for example, EEPROM settings in the generator **1100** and/or user power level selection(s).

In certain aspects, a two-position switch may be provided as an alternative to a toggle button **1134** (FIG. 3). For example, a device **1104** may include a toggle button **1134a**

for producing a continuous output at a maximum power level and a two-position toggle button **1134b**. In a first detented position, toggle button **1134b** may produce a continuous output at a less than maximum power level, and in a second detented position the toggle button **1134b** may produce a pulsed output (e.g., at either a maximum or less than maximum power level, depending upon the EEPROM settings).

In some aspects, the RF electrosurgical end effector **1124**, **1125** (FIG. 3) may also comprise a pair of electrodes. The electrodes may be in communication with the generator **1100**, for example, via a cable. The electrodes may be used, for example, to measure an impedance of a tissue bite present between the clamp arm **1142a**, **1146** and the blade **1142b**, **1149**. The generator **1100** may provide a signal (e.g., a non-therapeutic signal) to the electrodes. The impedance of the tissue bite may be found, for example, by monitoring the current, voltage, etc. of the signal.

In various aspects, the generator **1100** may comprise several separate functional elements, such as modules and/or blocks, as shown in FIG. 5, a diagram of the surgical system **1000** of FIG. 3. Different functional elements or modules may be configured for driving the different kinds of surgical devices **1104**, **1106**, **1108**. For example an ultrasonic generator module may drive an ultrasonic device, such as the ultrasonic device **1104**. An electrosurgery/RF generator module may drive the electrosurgical device **1106**. The modules may generate respective drive signals for driving the surgical devices **1104**, **1106**, **1108**. In various aspects, the ultrasonic generator module and/or the electrosurgery/RF generator module each may be formed integrally with the generator **1100**. Alternatively, one or more of the modules may be provided as a separate circuit module electrically coupled to the generator **1100**. (The modules are shown in phantom to illustrate this option.) Also, in some aspects, the electrosurgery/RF generator module may be formed integrally with the ultrasonic generator module, or vice versa.

In accordance with the described aspects, the ultrasonic generator module may produce a drive signal or signals of particular voltages, currents, and frequencies (e.g. 55,500 cycles per second, or Hz). The drive signal or signals may be provided to the ultrasonic device **1104**, and specifically to the transducer **1120**, which may operate, for example, as described above. In one aspect, the generator **1100** may be configured to produce a drive signal of a particular voltage, current, and/or frequency output signal that can be stepped with high resolution, accuracy, and repeatability.

In accordance with the described aspects, the electrosurgery/RF generator module may generate a drive signal or signals with output power sufficient to perform bipolar electrosurgery using radio frequency (RF) energy. In bipolar electrosurgery applications, the drive signal may be provided, for example, to the electrodes of the electrosurgical device **1106**, for example, as described above. Accordingly, the generator **1100** may be configured for therapeutic purposes by applying electrical energy to the tissue sufficient for treating the tissue (e.g., coagulation, cauterization, tissue welding, etc.).

The generator **1100** may comprise an input device **2150** (FIG. 8B) located, for example, on a front panel of the generator **1100** console. The input device **2150** may comprise any suitable device that generates signals suitable for programming the operation of the generator **1100**. In operation, the user can program or otherwise control operation of the generator **1100** using the input device **2150**. The input device **2150** may comprise any suitable device that generates signals that can be used by the generator (e.g., by one

or more processors contained in the generator) to control the operation of the generator **1100** (e.g., operation of the ultrasonic generator module and/or electrosurgery/RF generator module). In various aspects, the input device **2150** includes one or more of: buttons, switches, thumbwheels, keyboard, keypad, touch screen monitor, pointing device, remote connection to a general purpose or dedicated computer. In other aspects, the input device **2150** may comprise a suitable user interface, such as one or more user interface screens displayed on a touch screen monitor, for example. Accordingly, by way of the input device **2150**, the user can set or program various operating parameters of the generator, such as, for example, current (I), voltage (V), frequency (f), and/or period (T) of a drive signal or signals generated by the ultrasonic generator module and/or electrosurgery/RF generator module.

The generator **1100** may also comprise an output device **2140** (FIG. 8B) located, for example, on a front panel of the generator **1100** console. The output device **2140** includes one or more devices for providing a sensory feedback to a user. Such devices may comprise, for example, visual feedback devices (e.g., an LCD display screen, LED indicators), audio feedback devices (e.g., a speaker, a buzzer) or tactile feedback devices (e.g., haptic actuators).

Although certain modules and/or blocks of the generator **1100** may be described by way of example, it can be appreciated that a greater or lesser number of modules and/or blocks may be used and still fall within the scope of the aspects. Further, although various aspects may be described in terms of modules and/or blocks to facilitate description, such modules and/or blocks may be implemented by one or more hardware components, e.g., processors, Digital Signal Processors (DSPs), Programmable Logic Devices (PLDs), Application Specific Integrated Circuits (ASICs), circuits, registers and/or software components, e.g., programs, subroutines, logic and/or combinations of hardware and software components.

In one aspect, the ultrasonic generator drive module and electrosurgery/RF drive module **1110** (FIG. 3) may comprise one or more embedded applications implemented as firmware, software, hardware, or any combination thereof. The modules may comprise various executable modules such as software, programs, data, drivers, application program interfaces (APIs), and so forth. The firmware may be stored in nonvolatile memory (NVM), such as in bit-masked read-only memory (ROM) or flash memory. In various implementations, storing the firmware in ROM may preserve flash memory. The NVM may comprise other types of memory including, for example, programmable ROM (PROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), or battery backed random-access memory (RAM) such as dynamic RAM (DRAM), Double-Data-Rate DRAM (DDRDRAM), and/or synchronous DRAM (SDRAM).

In one aspect, the modules comprise a hardware component implemented as a processor for executing program instructions for monitoring various measurable characteristics of the devices **1104**, **1106**, **1108** and generating a corresponding output drive signal or signals for operating the devices **1104**, **1106**, **1108**. In aspects in which the generator **1100** is used in conjunction with the device **1104**, the drive signal may drive the ultrasonic transducer **1120** in cutting and/or coagulation operating modes. Electrical characteristics of the device **1104** and/or tissue may be measured and used to control operational aspects of the generator **1100** and/or provided as feedback to the user. In aspects in which the generator **1100** is used in conjunction with the device

**1106**, the drive signal may supply electrical energy (e.g., RF energy) to the end effector **1124** in cutting, coagulation and/or desiccation modes. Electrical characteristics of the device **1106** and/or tissue may be measured and used to control operational aspects of the generator **1100** and/or provided as feedback to the user. In various aspects, as previously discussed, the hardware components may be implemented as DSP, PLD, ASIC, circuits, and/or registers. In one aspect, the processor may be configured to store and execute computer software program instructions to generate the step function output signals for driving various components of the devices **1104**, **1106**, **1108**, such as the ultrasonic transducer **1120** and the end effectors **1122**, **1124**, **1125**.

An electromechanical ultrasonic system includes an ultrasonic transducer, a waveguide, and an ultrasonic blade. The electromechanical ultrasonic system has an initial resonant frequency defined by the physical properties of the ultrasonic transducer, the waveguide, and the ultrasonic blade. The ultrasonic transducer is excited by an alternating voltage  $V_g(t)$  and current  $I_g(t)$  signal equal to the resonant frequency of the electromechanical ultrasonic system. When the electromechanical ultrasonic system is at resonance, the phase difference between the voltage  $V_g(t)$  and current  $I_g(t)$  signals is zero. Stated another way, at resonance the inductive impedance is equal to the capacitive impedance. As the ultrasonic blade heats up, the compliance of the ultrasonic blade (modeled as an equivalent capacitance) causes the resonant frequency of the electromechanical ultrasonic system to shift. Thus, the inductive impedance is no longer equal to the capacitive impedance causing a mismatch between the drive frequency and the resonant frequency of the electromechanical ultrasonic system. The system is now operating "off-resonance." The mismatch between the drive frequency and the resonant frequency is manifested as a phase difference between the voltage  $V_g(t)$  and current  $I_g(t)$  signals applied to the ultrasonic transducer. The generator electronics can easily monitor the phase difference between the voltage  $V_g(t)$  and current  $I_g(t)$  signals and can continuously adjust the drive frequency until the phase difference is once again zero. At this point, the new drive frequency is equal to the new resonant frequency of the electromechanical ultrasonic system. The change in phase and/or frequency can be used as an indirect measurement of the ultrasonic blade temperature.

As shown in FIG. 6, the electromechanical properties of the ultrasonic transducer may be modeled as an equivalent circuit comprising a first branch having a static capacitance and a second "motional" branch having a serially connected inductance, resistance and capacitance that define the electromechanical properties of a resonator. Known ultrasonic generators may include a tuning inductor for tuning out the static capacitance at a resonant frequency so that substantially all of generator's drive signal current flows into the motional branch. Accordingly, by using a tuning inductor, the generator's drive signal current represents the motional branch current, and the generator is thus able to control its drive signal to maintain the ultrasonic transducer's resonant frequency. The tuning inductor may also transform the phase impedance plot of the ultrasonic transducer to improve the generator's frequency lock capabilities. However, the tuning inductor must be matched with the specific static capacitance of an ultrasonic transducer at the operational resonance frequency. In other words, a different ultrasonic transducer having a different static capacitance requires a different tuning inductor.

FIG. 6 illustrates an equivalent circuit **1500** of an ultrasonic transducer, such as the ultrasonic transducer **1120**,

according to one aspect. The circuit **1500** comprises a first “motional” branch having a serially connected inductance  $L_s$ , resistance  $R_s$  and capacitance  $C_s$  that define the electro-mechanical properties of the resonator, and a second capacitive branch having a static capacitance  $C_0$ . Drive current  $I_g(t)$  may be received from a generator at a drive voltage  $V_g(t)$ , with motional current  $I_m(t)$  flowing through the first branch and current  $I_g(t) - I_m(t)$  flowing through the capacitive branch. Control of the electromechanical properties of the ultrasonic transducer may be achieved by suitably controlling  $I_g(t)$  and  $V_g(t)$ . As explained above, known generator architectures may include a tuning inductor  $L_t$  (shown in phantom in FIG. **6**) in a parallel resonance circuit for tuning out the static capacitance  $C_0$  at a resonant frequency so that substantially all of the generator’s current output  $I_g(t)$  flows through the motional branch. In this way, control of the motional branch current  $I_m(t)$  is achieved by controlling the generator current output  $I_g(t)$ . The tuning inductor  $L_t$  is specific to the static capacitance  $C_0$  of an ultrasonic transducer, however, and a different ultrasonic transducer having a different static capacitance requires a different tuning inductor  $L_t$ . Moreover, because the tuning inductor  $L_t$  is matched to the nominal value of the static capacitance  $C_0$  at a single resonant frequency, accurate control of the motional branch current  $I_m(t)$  is assured only at that frequency. As frequency shifts down with transducer temperature, accurate control of the motional branch current is compromised.

Various aspects of the generator **1100** may not rely on a tuning inductor  $L_t$  to monitor the motional branch current  $I_m(t)$ . Instead, the generator **1100** may use the measured value of the static capacitance  $C_0$  in between applications of power for a specific ultrasonic surgical device **1104** (along with drive signal voltage and current feedback data) to determine values of the motional branch current  $I_m(t)$  on a dynamic and ongoing basis (e.g., in real-time). Such aspects of the generator **1100** are therefore able to provide virtual tuning to simulate a system that is tuned or resonant with any value of static capacitance  $C_0$  at any frequency, and not just at a single resonant frequency dictated by a nominal value of the static capacitance  $C_0$ .

FIG. **7** is a simplified block diagram of one aspect of the generator **1100** for providing inductorless tuning as described above, among other benefits. FIGS. **8A-8C** illustrate an architecture of the generator **1100** of FIG. **7** according to one aspect. With reference to FIG. **7**, the generator **1100** may comprise a patient isolated stage **1520** in communication with a non-isolated stage **1540** via a power transformer **1560**. A secondary winding **1580** of the power transformer **1560** is contained in the isolated stage **1520** and may comprise a tapped configuration (e.g., a center-tapped or non-center tapped configuration) to define drive signal outputs **1600a**, **1600b**, **1600c** for outputting drive signals to different surgical devices, such as, for example, an ultrasonic surgical device **1104** and an electrosurgical device **1106**. In particular, drive signal outputs **1600a**, **1600b**, **1600c** may output a drive signal (e.g., a 420V RMS drive signal) to an ultrasonic surgical device **1104**, and drive signal outputs **1600a**, **1600b**, **1600c** may output a drive signal (e.g., a 100V RMS drive signal) to an electrosurgical device **1106**, with output **1600b** corresponding to the center tap of the power transformer **1560**. The non-isolated stage **1540** may comprise a power amplifier **1620** having an output connected to a primary winding **1640** of the power transformer **1560**. In certain aspects the power amplifier **1620** may comprise a push-pull amplifier, for example. The non-isolated stage **1540** may further comprise a programmable logic device **1660** for supplying a digital output to a digital-to-analog

converter (DAC) **1680**, which in turn supplies a corresponding analog signal to an input of the power amplifier **1620**. In certain aspects the programmable logic device **1660** may comprise a field-programmable gate array (FPGA), for example. The programmable logic device **1660**, by virtue of controlling the power amplifier’s **1620** input via the DAC **1680**, may therefore control any of a number of parameters (e.g., frequency, waveform shape, waveform amplitude) of drive signals appearing at the drive signal outputs **1600a**, **1600b**, **1600c**. In certain aspects and as discussed below, the programmable logic device **1660**, in conjunction with a processor (e.g., processor **1740** discussed below), may implement a number of digital signal processing (DSP)-based and/or other control algorithms to control parameters of the drive signals output by the generator **1100**.

Power may be supplied to a power rail of the power amplifier **1620** by a switch-mode regulator **1700**. In certain aspects the switch-mode regulator **1700** may comprise an adjustable buck regulator **1170**, for example. As discussed above, the non-isolated stage **1540** may further comprise a processor **1740**, which in one aspect may comprise a DSP processor such as an ADSP-21469 SHARC DSP, available from Analog Devices, Norwood, Mass., for example. In certain aspects the processor **1740** may control operation of the switch-mode power converter **1700** responsive to voltage feedback data received from the power amplifier **1620** by the processor **1740** via an analog-to-digital converter (ADC) **1760**. In one aspect, for example, the processor **1740** may receive as input, via the ADC **1760**, the waveform envelope of a signal (e.g., an RF signal) being amplified by the power amplifier **1620**. The processor **1740** may then control the switch-mode regulator **1700** (e.g., via a pulse-width modulated (PWM) output) such that the rail voltage supplied to the power amplifier **1620** tracks the waveform envelope of the amplified signal. By dynamically modulating the rail voltage of the power amplifier **1620** based on the waveform envelope, the efficiency of the power amplifier **1620** may be significantly improved relative to a fixed rail voltage amplifier scheme. The processor **1740** may be configured for wired or wireless communication.

In certain aspects and as discussed in further detail in connection with FIGS. **9A-9B**, the programmable logic device **1660**, in conjunction with the processor **1740**, may implement a direct digital synthesizer (DDS) control scheme to control the waveform shape, frequency and/or amplitude of drive signals output by the generator **1100**. In one aspect, for example, the programmable logic device **1660** may implement a DDS control algorithm **2680** (FIG. **9A**) by recalling waveform samples stored in a dynamically-updated look-up table (LUT), such as a RAM LUT which may be embedded in an FPGA. This control algorithm is particularly useful for ultrasonic applications in which an ultrasonic transducer, such as the ultrasonic transducer **1120**, may be driven by a clean sinusoidal current at its resonant frequency. Because other frequencies may excite parasitic resonances, minimizing or reducing the total distortion of the motional branch current may correspondingly minimize or reduce undesirable resonance effects. Because the waveform shape of a drive signal output by the generator **1100** is impacted by various sources of distortion present in the output drive circuit (e.g., the power transformer **1560**, the power amplifier **1620**), voltage and current feedback data based on the drive signal may be input into an algorithm, such as an error control algorithm implemented by the processor **1740**, which compensates for distortion by suitably pre-distorting or modifying the waveform samples stored in the LUT on a dynamic, ongoing basis (e.g., in

real-time). In one aspect, the amount or degree of pre-distortion applied to the LUT samples may be based on the error between a computed motional branch current and a desired current waveform shape, with the error being determined on a sample-by sample basis. In this way, the pre-distorted LUT samples, when processed through the drive circuit, may result in a motional branch drive signal having the desired waveform shape (e.g., sinusoidal) for optimally driving the ultrasonic transducer. In such aspects, the LUT waveform samples will therefore not represent the desired waveform shape of the drive signal, but rather the waveform shape that is required to ultimately produce the desired waveform shape of the motional branch drive signal when distortion effects are taken into account.

The non-isolated stage **1540** may further comprise an ADC **1780** and an ADC **1800** coupled to the output of the power transformer **1560** via respective isolation transformers **1820**, **1840** for respectively sampling the voltage and current of drive signals output by the generator **1100**. In certain aspects, the ADCs **1780**, **1800** may be configured to sample at high speeds (e.g., 80 Msps) to enable oversampling of the drive signals. In one aspect, for example, the sampling speed of the ADCs **1780**, **1800** may enable approximately 200× (depending on drive frequency) oversampling of the drive signals. In certain aspects, the sampling operations of the ADCs **1780**, **1800** may be performed by a single ADC receiving input voltage and current signals via a two-way multiplexer. The use of high-speed sampling in aspects of the generator **1100** may enable, among other things, calculation of the complex current flowing through the motional branch (which may be used in certain aspects to implement DDS-based waveform shape control described above), accurate digital filtering of the sampled signals, and calculation of real power consumption with a high degree of precision. Voltage and current feedback data output by the ADCs **1780**, **1800** may be received and processed (e.g., FIFO buffering, multiplexing) by the programmable logic device **1660** and stored in data memory for subsequent retrieval by, for example, the processor **1740**. As noted above, voltage and current feedback data may be used as input to an algorithm for pre-distorting or modifying LUT waveform samples on a dynamic and ongoing basis. In certain aspects, this may require each stored voltage and current feedback data pair to be indexed based on, or otherwise associated with, a corresponding LUT sample that was output by the programmable logic device **1660** when the voltage and current feedback data pair was acquired. Synchronization of the LUT samples and the voltage and current feedback data in this manner contributes to the correct timing and stability of the pre-distortion algorithm.

In certain aspects, the voltage and current feedback data may be used to control the frequency and/or amplitude (e.g., current amplitude) of the drive signals. In one aspect, for example, voltage and current feedback data may be used to determine impedance phase, e.g., the phase difference between the voltage and current drive signals. The frequency of the drive signal may then be controlled to minimize or reduce the difference between the determined impedance phase and an impedance phase setpoint (e.g., 0°), thereby minimizing or reducing the effects of harmonic distortion and correspondingly enhancing impedance phase measurement accuracy. The determination of phase impedance and a frequency control signal may be implemented in the processor **1740**, for example, with the frequency control signal being supplied as input to a DDS control algorithm implemented by the programmable logic device **1660**.

The impedance phase may be determined through Fourier analysis. In one aspect, the phase difference between the generator voltage  $V_g(t)$  and generator current  $I_g(t)$  driving signals may be determined using the Fast Fourier Transform (FFT) or the Discrete Fourier Transform (DFT) as follows:

$$V_g(t) = A_1 \cos(2\pi f_0 t + \varphi_1)$$

$$I_g(t) = A_2 \cos(2\pi f_0 t + \varphi_2)$$

$$V_g(f) = \frac{A_1}{2} (\delta(f - f_0) + \delta(f + f_0)) \exp(j2\pi f \frac{\varphi_1}{2\pi f_0})$$

$$I_g(f) = \frac{A_2}{2} (\delta(f - f_0) + \delta(f + f_0)) \exp(j2\pi f \frac{\varphi_2}{2\pi f_0})$$

Evaluating the Fourier Transform at the frequency of the sinusoid yields:

$$V_g(f_0) = \frac{A_1}{2} \delta(0) \exp(j\varphi_1) \quad \arg V(f_0) = \varphi_1$$

$$I_g(f_0) = \frac{A_2}{2} \delta(0) \exp(j\varphi_2) \quad \arg I(f_0) = \varphi_2$$

Other approaches include weighted least-squares estimation, Kalman filtering, and space-vector-based techniques. Virtually all of the processing in an FFT or DFT technique may be performed in the digital domain with the aid of the 2-channel high speed ADC **1780**, **1800**, for example. In one technique, the digital signal samples of the voltage and current signals are Fourier transformed with an FFT or a DFT. The phase angle  $\varphi$  at any point in time can be calculated by:

$$\varphi = 2\pi f t + \varphi_0$$

where  $\varphi$  is the phase angle,  $f$  is the frequency,  $t$  is time, and  $\varphi_N$  is the phase at  $t=0$ .

Another technique for determining the phase difference between the voltage  $V_g(t)$  and current  $I_g(t)$  signals is the zero-crossing method and produces highly accurate results. For voltage  $V_g(t)$  and current  $I_g(t)$  signals having the same frequency, each negative to positive zero-crossing of voltage signal  $V_g(t)$  triggers the start of a pulse, while each negative to positive zero-crossing of current signal  $I_g(t)$  triggers the end of the pulse. The result is a pulse train with a pulse width proportional to the phase angle between the voltage signal and the current signal. In one aspect, the pulse train may be passed through an averaging filter to yield a measure of the phase difference. Furthermore, if the positive to negative zero crossings also are used in a similar manner, and the results averaged, any effects of DC and harmonic components can be reduced. In one implementation, the analog voltage  $V_g(t)$  and current  $I_g(t)$  signals are converted to digital signals that are high if the analog signal is positive and low if the analog signal is negative. High accuracy phase estimates require sharp transitions between high and low. In one aspect, a Schmitt trigger along with an RC stabilization network may be employed to convert the analog signals into digital signals. In other aspects, an edge triggered RS flip-flop and ancillary circuitry may be employed. In yet another aspect, the zero-crossing technique may employ an eXclusive OR (XOR) gate.

Other techniques for determining the phase difference between the voltage and current signals include Lissajous figures and monitoring the image; methods such as the three-voltmeter method, the crossed-coil method, vector

voltmeter and vector impedance methods; and using phase standard instruments, phase-locked loops, and other techniques as described in Phase Measurement, Peter O'Shea, 2000 CRC Press LLC, <<http://www.engnetbase.com>>, which is incorporated herein by reference.

In another aspect, for example, the current feedback data may be monitored in order to maintain the current amplitude of the drive signal at a current amplitude setpoint. The current amplitude setpoint may be specified directly or determined indirectly based on specified voltage amplitude and power setpoints. In certain aspects, control of the current amplitude may be implemented by control algorithm, such as, for example, a proportional-integral-derivative (PID) control algorithm, in the processor 1740. Variables controlled by the control algorithm to suitably control the current amplitude of the drive signal may include, for example, the scaling of the LUT waveform samples stored in the programmable logic device 1660 and/or the full-scale output voltage of the DAC 1680 (which supplies the input to the power amplifier 1620) via a DAC 1860.

The non-isolated stage 1540 may further comprise a processor 1900 for providing, among other things, user interface (UI) functionality. In one aspect, the processor 1900 may comprise an Atmel AT91 SAM9263 processor having an ARM 926EJ-S core, available from Atmel Corporation, San Jose, Calif., for example. Examples of UI functionality supported by the processor 1900 may include audible and visual user feedback, communication with peripheral devices (e.g., via a Universal Serial Bus (USB) interface), communication with a foot switch 1430, communication with an input device 2150 (e.g., a touch screen display) and communication with an output device 2140 (e.g., a speaker). The processor 1900 may communicate with the processor 1740 and the programmable logic device (e.g., via a serial peripheral interface (SPI) bus). Although the processor 1900 may primarily support UI functionality, it may also coordinate with the processor 1740 to implement hazard mitigation in certain aspects. For example, the processor 1900 may be programmed to monitor various aspects of user input and/or other inputs (e.g., touch screen inputs 2150, foot switch 1430 inputs, temperature sensor inputs 2160) and may disable the drive output of the generator 1100 when an erroneous condition is detected.

In certain aspects, both the processor 1740 (FIGS. 7, 8A) and the processor 1900 (FIGS. 7, 8B) may determine and monitor the operating state of the generator 1100. For processor 1740, the operating state of the generator 1100 may dictate, for example, which control and/or diagnostic processes are implemented by the processor 1740. For processor 1900, the operating state of the generator 1100 may dictate, for example, which elements of a user interface (e.g., display screens, sounds) are presented to a user. The processors 1740, 1900 may independently maintain the current operating state of the generator 1100 and recognize and evaluate possible transitions out of the current operating state. The processor 1740 may function as the master in this relationship and determine when transitions between operating states are to occur. The processor 1900 may be aware of valid transitions between operating states and may confirm if a particular transition is appropriate. For example, when the processor 1740 instructs the processor 1900 to transition to a specific state, the processor 1900 may verify that the requested transition is valid. In the event that a requested transition between states is determined to be invalid by the processor 1900, the processor 1900 may cause the generator 1100 to enter a failure mode.

The non-isolated stage 1540 may further comprise a controller 1960 (FIGS. 7, 8B) for monitoring input devices 2150 (e.g., a capacitive touch sensor used for turning the generator 1100 on and off, a capacitive touch screen). In certain aspects, the controller 1960 may comprise at least one processor and/or other controller device in communication with the processor 1900. In one aspect, for example, the controller 1960 may comprise a processor (e.g., a Mega168 8-bit controller available from Atmel) configured to monitor user input provided via one or more capacitive touch sensors. In one aspect, the controller 1960 may comprise a touch screen controller (e.g., a QT5480 touch screen controller available from Atmel) to control and manage the acquisition of touch data from a capacitive touch screen.

In certain aspects, when the generator 1100 is in a "power off" state, the controller 1960 may continue to receive operating power (e.g., via a line from a power supply of the generator 1100, such as the power supply 2110 (FIG. 7) discussed below). In this way, the controller 1960 may continue to monitor an input device 2150 (e.g., a capacitive touch sensor located on a front panel of the generator 1100) for turning the generator 1100 on and off. When the generator 1100 is in the "power off" state, the controller 1960 may wake the power supply (e.g., enable operation of one or more DC/DC voltage converters 2130 (FIG. 7) of the power supply 2110) if activation of the "on/off" input device 2150 by a user is detected. The controller 1960 may therefore initiate a sequence for transitioning the generator 1100 to a "power on" state. Conversely, the controller 1960 may initiate a sequence for transitioning the generator 1100 to the "power off" state if activation of the "on/off" input device 2150 is detected when the generator 1100 is in the "power on" state. In certain aspects, for example, the controller 1960 may report activation of the "on/off" input device 2150 to the processor 1900, which in turn implements the necessary process sequence for transitioning the generator 1100 to the "power off" state. In such aspects, the controller 1960 may have no independent ability for causing the removal of power from the generator 1100 after its "power on" state has been established.

In certain aspects, the controller 1960 may cause the generator 1100 to provide audible or other sensory feedback for alerting the user that a "power on" or "power off" sequence has been initiated. Such an alert may be provided at the beginning of a "power on" or "power off" sequence and prior to the commencement of other processes associated with the sequence.

In certain aspects, the isolated stage 1520 may comprise an instrument interface circuit 1980 to, for example, provide a communication interface between a control circuit of a surgical device (e.g., a control circuit comprising handpiece switches) and components of the non-isolated stage 1540, such as, for example, the programmable logic device 1660, the processor 1740 and/or the processor 1900. The instrument interface circuit 1980 may exchange information with components of the non-isolated stage 1540 via a communication link that maintains a suitable degree of electrical isolation between the stages 1520, 1540, such as, for example, an infrared (IR)-based communication link. Power may be supplied to the instrument interface circuit 1980 using, for example, a low-dropout voltage regulator powered by an isolation transformer driven from the non-isolated stage 1540.

In one aspect, the instrument interface circuit 1980 may comprise a programmable logic device 2000 (e.g., an FPGA) in communication with a signal conditioning circuit

2020 (FIG. 7 and FIG. 8C). The signal conditioning circuit 2020 may be configured to receive a periodic signal from the programmable logic device 2000 (e.g., a 2 kHz square wave) to generate a bipolar interrogation signal having an identical frequency. The interrogation signal may be generated, for example, using a bipolar current source fed by a differential amplifier. The interrogation signal may be communicated to a surgical device control circuit (e.g., by using a conductive pair in a cable that connects the generator 1100 to the surgical device) and monitored to determine a state or configuration of the control circuit. For example, the control circuit may comprise a number of switches, resistors and/or diodes to modify one or more characteristics (e.g., amplitude, rectification) of the interrogation signal such that a state or configuration of the control circuit is uniquely discernible based on the one or more characteristics. In one aspect, for example, the signal conditioning circuit 2020 may comprise an ADC for generating samples of a voltage signal appearing across inputs of the control circuit resulting from passage of interrogation signal therethrough. The programmable logic device 2000 (or a component of the non-isolated stage 1540) may then determine the state or configuration of the control circuit based on the ADC samples.

In one aspect, the instrument interface circuit 1980 may comprise a first data circuit interface 2040 to enable information exchange between the programmable logic device 2000 (or other element of the instrument interface circuit 1980) and a first data circuit disposed in or otherwise associated with a surgical device. In certain aspects, for example, a first data circuit 2060 may be disposed in a cable integrally attached to a surgical device handpiece, or in an adaptor for interfacing a specific surgical device type or model with the generator 1100. In certain aspects, the first data circuit may comprise a non-volatile storage device, such as an electrically erasable programmable read-only memory (EEPROM) device. In certain aspects and referring again to FIG. 7, the first data circuit interface 2040 may be implemented separately from the programmable logic device 2000 and comprise suitable circuitry (e.g., discrete logic devices, a processor) to enable communication between the programmable logic device 2000 and the first data circuit. In other aspects, the first data circuit interface 2040 may be integral with the programmable logic device 2000.

In certain aspects, the first data circuit 2060 may store information pertaining to the particular surgical device with which it is associated. Such information may include, for example, a model number, a serial number, a number of operations in which the surgical device has been used, and/or any other type of information. This information may be read by the instrument interface circuit 1980 (e.g., by the programmable logic device 2000), transferred to a component of the non-isolated stage 1540 (e.g., to programmable logic device 1660, processor 1740 and/or processor 1900) for presentation to a user via an output device 2140 and/or for controlling a function or operation of the generator 1100. Additionally, any type of information may be communicated to first data circuit 2060 for storage therein via the first data circuit interface 2040 (e.g., using the programmable logic device 2000). Such information may comprise, for example, an updated number of operations in which the surgical device has been used and/or dates and/or times of its usage.

As discussed previously, a surgical instrument may be detachable from a handpiece (e.g., instrument 1106 may be detachable from handpiece 1107) to promote instrument interchangeability and/or disposability. In such cases,

known generators may be limited in their ability to recognize particular instrument configurations being used and to optimize control and diagnostic processes accordingly. The addition of readable data circuits to surgical device instruments to address this issue is problematic from a compatibility standpoint, however. For example, it may be impractical to design a surgical device to maintain backward compatibility with generators that lack the requisite data reading functionality due to, for example, differing signal schemes, design complexity and cost. Other aspects of instruments address these concerns by using data circuits that may be implemented in existing surgical instruments economically and with minimal design changes to preserve compatibility of the surgical devices with current generator platforms.

Additionally, aspects of the generator 1100 may enable communication with instrument-based data circuits. For example, the generator 1100 may be configured to communicate with a second data circuit (e.g., a data circuit) contained in an instrument (e.g., instrument 1104, 1106 or 1108) of a surgical device. The instrument interface circuit 1980 may comprise a second data circuit interface 2100 to enable this communication. In one aspect, the second data circuit interface 2100 may comprise a tri-state digital interface, although other interfaces may also be used. In certain aspects, the second data circuit may generally be any circuit for transmitting and/or receiving data. In one aspect, for example, the second data circuit may store information pertaining to the particular surgical instrument with which it is associated. Such information may include, for example, a model number, a serial number, a number of operations in which the surgical instrument has been used, and/or any other type of information. Additionally or alternatively, any type of information may be communicated to the second data circuit for storage therein via the second data circuit interface 2100 (e.g., using the programmable logic device 2000). Such information may comprise, for example, an updated number of operations in which the instrument has been used and/or dates and/or times of its usage. In certain aspects, the second data circuit may transmit data acquired by one or more sensors (e.g., an instrument-based temperature sensor). In certain aspects, the second data circuit may receive data from the generator 1100 and provide an indication to a user (e.g., an LED indication or other visible indication) based on the received data.

In certain aspects, the second data circuit and the second data circuit interface 2100 may be configured such that communication between the programmable logic device 2000 and the second data circuit can be effected without the need to provide additional conductors for this purpose (e.g., dedicated conductors of a cable connecting a handpiece to the generator 1100). In one aspect, for example, information may be communicated to and from the second data circuit using a one-wire bus communication scheme implemented on existing cabling, such as one of the conductors used transmit interrogation signals from the signal conditioning circuit 2020 to a control circuit in a handpiece. In this way, design changes or modifications to the surgical device that might otherwise be necessary are minimized or reduced. Moreover, because different types of communications can be implemented over a common physical channel (either with or without frequency-band separation), the presence of a second data circuit may be “invisible” to generators that do not have the requisite data reading functionality, thus enabling backward compatibility of the surgical device instrument.

In certain aspects, the isolated stage **1520** may comprise at least one blocking capacitor **2960-1** (FIG. **8C**) connected to the drive signal output **1600b** to prevent passage of DC current to a patient. A single blocking capacitor may be required to comply with medical regulations or standards, for example. While failure in single-capacitor designs is relatively uncommon, such failure may nonetheless have negative consequences. In one aspect, a second blocking capacitor **2960-2** may be provided in series with the blocking capacitor **2960-1**, with current leakage from a point between the blocking capacitors **2960-1**, **2960-2** being monitored by, for example, an ADC **2980** for sampling a voltage induced by leakage current. The samples may be received by the programmable logic device **2000**, for example. Based on changes in the leakage current (as indicated by the voltage samples in the aspect of FIG. **7**), the generator **1100** may determine when at least one of the blocking capacitors **2960-1**, **2960-2** has failed. Accordingly, the aspect of FIG. **7** may provide a benefit over single-capacitor designs having a single point of failure.

In certain aspects, the non-isolated stage **1540** may comprise a power supply **2110** for outputting DC power at a suitable voltage and current. The power supply may comprise, for example, a 400 W power supply for outputting a 48 VDC system voltage. As discussed above, the power supply **2110** may further comprise one or more DC/DC voltage converters **2130** for receiving the output of the power supply to generate DC outputs at the voltages and currents required by the various components of the generator **1100**. As discussed above in connection with the controller **1960**, one or more of the DC/DC voltage converters **2130** may receive an input from the controller **1960** when activation of the "on/off" input device **2150** by a user is detected by the controller **1960** to enable operation of, or wake, the DC/DC voltage converters **2130**.

FIGS. **9A-9B** illustrate certain functional and structural aspects of one aspect of the generator **1100**. Feedback indicating current and voltage output from the secondary winding **1580** of the power transformer **1560** is received by the ADCs **1780**, **1800**, respectively. As shown, the ADCs **1780**, **1800** may be implemented as a 2-channel ADC and may sample the feedback signals at a high speed (e.g., 80 Msps) to enable oversampling (e.g., approximately 200x oversampling) of the drive signals. The current and voltage feedback signals may be suitably conditioned in the analog domain (e.g., amplified, filtered) prior to processing by the ADCs **1780**, **1800**. Current and voltage feedback samples from the ADCs **1780**, **1800** may be individually buffered and subsequently multiplexed or interleaved into a single data stream within block **2120** of the programmable logic device **1660**. In the aspect of FIGS. **9A-9B**, the programmable logic device **1660** comprises an FPGA.

The multiplexed current and voltage feedback samples may be received by a parallel data acquisition port (PDAP) implemented within block **2144** of the processor **1740**. The PDAP may comprise a packing unit for implementing any of a number of methodologies for correlating the multiplexed feedback samples with a memory address. In one aspect, for example, feedback samples corresponding to a particular LUT sample output by the programmable logic device **1660** may be stored at one or more memory addresses that are correlated or indexed with the LUT address of the LUT sample. In another aspect, feedback samples corresponding to a particular LUT sample output by the programmable logic device **1660** may be stored, along with the LUT address of the LUT sample, at a common memory location. In any event, the feedback samples may be stored such that

the address of the LUT sample from which a particular set of feedback samples originated may be subsequently ascertained. As discussed above, synchronization of the LUT sample addresses and the feedback samples in this way contributes to the correct timing and stability of the pre-distortion algorithm. A direct memory access (DMA) controller implemented at block **2166** of the processor **1740** may store the feedback samples (and any LUT sample address data, where applicable) at a designated memory location **2180** of the processor **1740** (e.g., internal RAM).

Block **2200** of the processor **1740** may implement a pre-distortion algorithm for pre-distorting or modifying the LUT samples stored in the programmable logic device **1660** on a dynamic, ongoing basis. As discussed above, pre-distortion of the LUT samples may compensate for various sources of distortion present in the output drive circuit of the generator **1100**. The pre-distorted LUT samples, when processed through the drive circuit, will therefore result in a drive signal having the desired waveform shape (e.g., sinusoidal) for optimally driving the ultrasonic transducer.

At block **2220** of the pre-distortion algorithm, the current through the motional branch of the ultrasonic transducer is determined. The motional branch current may be determined using Kirchhoff's Current Law based on, for example, the current and voltage feedback samples stored at memory location **2180** (which, when suitably scaled, may be representative of  $I_g$  and  $V_g$  in the model of FIG. **6** discussed above), a value of the ultrasonic transducer static capacitance  $C_0$  (measured or known a priori) and a known value of the drive frequency. A motional branch current sample for each set of stored current and voltage feedback samples associated with a LUT sample may be determined.

At block **2240** of the pre-distortion algorithm, each motional branch current sample determined at block **2220** is compared to a sample of a desired current waveform shape to determine a difference, or sample amplitude error, between the compared samples. For this determination, the sample of the desired current waveform shape may be supplied, for example, from a waveform shape LUT **2260** containing amplitude samples for one cycle of a desired current waveform shape. The particular sample of the desired current waveform shape from the LUT **2260** used for the comparison may be dictated by the LUT sample address associated with the motional branch current sample used in the comparison. Accordingly, the input of the motional branch current to block **2240** may be synchronized with the input of its associated LUT sample address to block **2240**. The LUT samples stored in the programmable logic device **1660** and the LUT samples stored in the waveform shape LUT **2260** may therefore be equal in number. In certain aspects, the desired current waveform shape represented by the LUT samples stored in the waveform shape LUT **2260** may be a fundamental sine wave. Other waveform shapes may be desirable. For example, it is contemplated that a fundamental sine wave for driving main longitudinal motion of an ultrasonic transducer superimposed with one or more other drive signals at other frequencies, such as a third order harmonic for driving at least two mechanical resonances for beneficial vibrations of transverse or other modes, could be used.

Each value of the sample amplitude error determined at block **2240** may be transmitted to the LUT of the programmable logic device **1660** (shown at block **2280** in FIG. **9A**) along with an indication of its associated LUT address. Based on the value of the sample amplitude error and its associated address (and, optionally, values of sample amplitude error for the same LUT address previously received),

the LUT **2280** (or other control block of the programmable logic device **1660**) may pre-distort or modify the value of the LUT sample stored at the LUT address such that the sample amplitude error is reduced or minimized. It will be appreciated that such pre-distortion or modification of each LUT sample in an iterative manner across the entire range of LUT addresses will cause the waveform shape of the generator's output current to match or conform to the desired current waveform shape represented by the samples of the waveform shape LUT **2260**.

Current and voltage amplitude measurements, power measurements and impedance measurements may be determined at block **2300** of the processor **1740** based on the current and voltage feedback samples stored at memory location **2180**. Prior to the determination of these quantities, the feedback samples may be suitably scaled and, in certain aspects, processed through a suitable filter **2320** to remove noise resulting from, for example, the data acquisition process and induced harmonic components. The filtered voltage and current samples may therefore substantially represent the fundamental frequency of the generator's drive output signal. In certain aspects, the filter **2320** may be a finite impulse response (FIR) filter applied in the frequency domain. Such aspects may use the Fast Fourier Transform (FFT) of the output drive signal current and voltage signals. In certain aspects, the resulting frequency spectrum may be used to provide additional generator functionality. In one aspect, for example, the ratio of the second and/or third order harmonic component relative to the fundamental frequency component may be used as a diagnostic indicator.

At block **2340** (FIG. 9B), a root mean square (RMS) calculation may be applied to a sample size of the current feedback samples representing an integral number of cycles of the drive signal to generate a measurement  $I_{rms}$  representing the drive signal output current.

At block **2360**, a root mean square (RMS) calculation may be applied to a sample size of the voltage feedback samples representing an integral number of cycles of the drive signal to determine a measurement  $V_{rms}$  representing the drive signal output voltage.

At block **2380**, the current and voltage feedback samples may be multiplied point by point, and a mean calculation is applied to samples representing an integral number of cycles of the drive signal to determine a measurement  $P_r$  of the generator's real output power.

At block **2400**, measurement  $P_a$  of the generator's apparent output power may be determined as the product  $V_{rms} \cdot I_{rms}$ .

At block **2420**, measurement  $Z_m$  of the load impedance magnitude may be determined as the quotient  $V_{rms}/I_{rms}$ .

In certain aspects, the quantities  $I_{rms}$ ,  $V_{rms}$ ,  $P_r$ ,  $P_a$  and  $Z_m$  determined at blocks **2340**, **2360**, **2380**, **2400** and **2420** may be used by the generator **1100** to implement any of a number of control and/or diagnostic processes. In certain aspects, any of these quantities may be communicated to a user via, for example, an output device **2140** integral with the generator **1100** or an output device **2140** connected to the generator **1100** through a suitable communication interface (e.g., a USB interface). Various diagnostic processes may include, without limitation, handpiece integrity, instrument integrity, instrument attachment integrity, instrument overload, approaching instrument overload, frequency lock failure, over-voltage condition, over-current condition, over-power condition, voltage sense failure, current sense failure, audio indication failure, visual indication failure, short circuit condition, power delivery failure, or blocking capacitor failure, for example.

Block **2440** of the processor **1740** may implement a phase control algorithm for determining and controlling the impedance phase of an electrical load (e.g., the ultrasonic transducer) driven by the generator **1100**. As discussed above, by controlling the frequency of the drive signal to minimize or reduce the difference between the determined impedance phase and an impedance phase setpoint (e.g.,  $0^\circ$ ), the effects of harmonic distortion may be minimized or reduced, and the accuracy of the phase measurement increased.

The phase control algorithm receives as input the current and voltage feedback samples stored in the memory location **2180**. Prior to their use in the phase control algorithm, the feedback samples may be suitably scaled and, in certain aspects, processed through a suitable filter **2460** (which may be identical to filter **2320**) to remove noise resulting from the data acquisition process and induced harmonic components, for example. The filtered voltage and current samples may therefore substantially represent the fundamental frequency of the generator's drive output signal.

At block **2480** of the phase control algorithm, the current through the motional branch of the ultrasonic transducer is determined. This determination may be identical to that described above in connection with block **2220** of the pre-distortion algorithm. The output of block **2480** may thus be, for each set of stored current and voltage feedback samples associated with a LUT sample, a motional branch current sample.

At block **2500** of the phase control algorithm, impedance phase is determined based on the synchronized input of motional branch current samples determined at block **2480** and corresponding voltage feedback samples. In certain aspects, the impedance phase is determined as the average of the impedance phase measured at the rising edge of the waveforms and the impedance phase measured at the falling edge of the waveforms.

At block **2520** of the of the phase control algorithm, the value of the impedance phase determined at block **2500** is compared to phase setpoint **2540** to determine a difference, or phase error, between the compared values.

At block **2560** (FIG. 9A) of the phase control algorithm, based on a value of phase error determined at block **2520** and the impedance magnitude determined at block **2420**, a frequency output for controlling the frequency of the drive signal is determined. The value of the frequency output may be continuously adjusted by the block **2560** and transferred to a DDS control block **2680** (discussed below) in order to maintain the impedance phase determined at block **2500** at the phase setpoint (e.g., zero phase error). In certain aspects, the impedance phase may be regulated to a  $0^\circ$  phase setpoint. In this way, any harmonic distortion will be centered about the crest of the voltage waveform, enhancing the accuracy of phase impedance determination.

Block **2580** of the processor **1740** may implement an algorithm for modulating the current amplitude of the drive signal in order to control the drive signal current, voltage and power in accordance with user specified setpoints, or in accordance with requirements specified by other processes or algorithms implemented by the generator **1100**. Control of these quantities may be realized, for example, by scaling the LUT samples in the LUT **2280** and/or by adjusting the full-scale output voltage of the DAC **1680** (which supplies the input to the power amplifier **1620**) via a DAC **1860**. Block **2600** (which may be implemented as a PID controller in certain aspects) may receive, as input, current feedback samples (which may be suitably scaled and filtered) from the memory location **2180**. The current feedback samples may be compared to a "current demand"  $I_d$  value dictated by the

controlled variable (e.g., current, voltage or power) to determine if the drive signal is supplying the necessary current. In aspects in which drive signal current is the control variable, the current demand  $I_d$  may be specified directly by a current setpoint **2620A** ( $I_{sp}$ ). For example, an RMS value of the current feedback data (determined as in block **2340**) may be compared to user-specified RMS current setpoint  $I_{sp}$  to determine the appropriate controller action. If, for example, the current feedback data indicates an RMS value less than the current setpoint  $I_{sp}$ , LUT scaling and/or the full-scale output voltage of the DAC **1680** may be adjusted by the block **2600** such that the drive signal current is increased. Conversely, block **2600** may adjust LUT scaling and/or the full-scale output voltage of the DAC **1680** to decrease the drive signal current when the current feedback data indicates an RMS value greater than the current setpoint  $I_{sp}$ .

In aspects in which the drive signal voltage is the control variable, the current demand  $I_d$  may be specified indirectly, for example, based on the current required to maintain a desired voltage setpoint **2620B** ( $V_{sp}$ ) given the load impedance magnitude  $Z_m$  measured at block **2420** (e.g.  $I_d = V_{sp}/Z_m$ ). Similarly, in aspects in which drive signal power is the control variable, the current demand  $I_d$  may be specified indirectly, for example, based on the current required to maintain a desired power setpoint **2620C** ( $P_{sp}$ ) given the voltage  $V_{rms}$  measured at blocks **2360** (e.g.  $I_d = P_{sp}/V_{rms}$ ).

Block **2680** (FIG. 9A) may implement a DDS control algorithm for controlling the drive signal by recalling LUT samples stored in the LUT **2280**. In certain aspects, the DDS control algorithm may be a numerically-controlled oscillator (NCO) algorithm for generating samples of a waveform at a fixed clock rate using a point (memory location)-skipping technique. The NCO algorithm may implement a phase accumulator, or frequency-to-phase converter, that functions as an address pointer for recalling LUT samples from the LUT **2280**. In one aspect, the phase accumulator may be a D step size, modulo N phase accumulator, where D is a positive integer representing a frequency control value, and N is the number of LUT samples in the LUT **2280**. A frequency control value of  $D=1$ , for example, may cause the phase accumulator to sequentially point to every address of the LUT **2280**, resulting in a waveform output replicating the waveform stored in the LUT **2280**. When  $D>1$ , the phase accumulator may skip addresses in the LUT **2280**, resulting in a waveform output having a higher frequency. Accordingly, the frequency of the waveform generated by the DDS control algorithm may therefore be controlled by suitably varying the frequency control value. In certain aspects, the frequency control value may be determined based on the output of the phase control algorithm implemented at block **2440**. The output of block **2680** may supply the input of DAC **1680**, which in turn supplies a corresponding analog signal to an input of the power amplifier **1620**.

Block **2700** of the processor **1740** may implement a switch-mode converter control algorithm for dynamically modulating the rail voltage of the power amplifier **1620** based on the waveform envelope of the signal being amplified, thereby improving the efficiency of the power amplifier **1620**. In certain aspects, characteristics of the waveform envelope may be determined by monitoring one or more signals contained in the power amplifier **1620**. In one aspect, for example, characteristics of the waveform envelope may be determined by monitoring the minima of a drain voltage (e.g., a MOSFET drain voltage) that is modulated in accordance with the envelope of the amplified signal. A minima voltage signal may be generated, for example, by a voltage

minima detector coupled to the drain voltage. The minima voltage signal may be sampled by ADC **1760**, with the output minima voltage samples being received at block **2720** of the switch-mode converter control algorithm. Based on the values of the minima voltage samples, block **2740** may control a PWM signal output by a PWM generator **2760**, which, in turn, controls the rail voltage supplied to the power amplifier **1620** by the switch-mode regulator **1700**. In certain aspects, as long as the values of the minima voltage samples are less than a minima target **2780** input into block **2720**, the rail voltage may be modulated in accordance with the waveform envelope as characterized by the minima voltage samples. When the minima voltage samples indicate low envelope power levels, for example, block **2740** may cause a low rail voltage to be supplied to the power amplifier **1620**, with the full rail voltage being supplied only when the minima voltage samples indicate maximum envelope power levels. When the minima voltage samples fall below the minima target **2780**, block **2740** may cause the rail voltage to be maintained at a minimum value suitable for ensuring proper operation of the power amplifier **1620**.

FIG. 10 illustrates a control circuit **500** configured to control aspects of the surgical instrument or tool according to one aspect of this disclosure. The control circuit **500** can be configured to implement various processes described herein. The control circuit **500** may comprise a microcontroller comprising one or more processors **502** (e.g., microprocessor, microcontroller) coupled to at least one memory circuit **504**. The memory circuit **504** stores machine-executable instructions that, when executed by the processor **502**, cause the processor **502** to execute machine instructions to implement various processes described herein. The processor **502** may be any one of a number of single-core or multicore processors known in the art. The memory circuit **504** may comprise volatile and non-volatile storage media. The processor **502** may include an instruction processing unit **506** and an arithmetic unit **508**. The instruction processing unit may be configured to receive instructions from the memory circuit **504** of this disclosure.

FIG. 11 illustrates a combinational logic circuit **510** configured to control aspects of the surgical instrument or tool according to one aspect of this disclosure. The combinational logic circuit **510** can be configured to implement various processes described herein. The combinational logic circuit **510** may comprise a finite state machine comprising a combinational logic **512** configured to receive data associated with the surgical instrument or tool at an input **514**, process the data by the combinational logic **512**, and provide an output **516**.

FIG. 12 illustrates a sequential logic circuit **520** configured to control aspects of the surgical instrument or tool according to one aspect of this disclosure. The sequential logic circuit **520** or the combinational logic **522** can be configured to implement various processes described herein. The sequential logic circuit **520** may comprise a finite state machine. The sequential logic circuit **520** may comprise a combinational logic **522**, at least one memory circuit **524**, and a clock **529**, for example. The at least one memory circuit **524** can store a current state of the finite state machine. In certain instances, the sequential logic circuit **520** may be synchronous or asynchronous. The combinational logic **522** is configured to receive data associated with the surgical instrument or tool from an input **526**, process the data by the combinational logic **522**, and provide an output **528**. In other aspects, the circuit may comprise a combination of a processor (e.g., processor **502**, FIG. 13) and a finite state machine to implement various processes herein. In

other aspects, the finite state machine may comprise a combination of a combinational logic circuit (e.g., combinational logic circuit **510**, FIG. **14**) and the sequential logic circuit **520**.

In one aspect, the ultrasonic or high-frequency current generators of the surgical system **1000** may be configured to generate the electrical signal waveform digitally using a predetermined number of phase points stored in a lookup table to digitize the wave shape. The phase points may be stored in a table defined in a memory, a field programmable gate array (FPGA), or any suitable non-volatile memory. FIG. **13** illustrates one aspect of a fundamental architecture for a digital synthesis circuit such as a direct digital synthesis (DDS) circuit **4100** configured to generate a plurality of wave shapes for the electrical signal waveform. The generator software and digital controls may command the FPGA to scan the addresses in the lookup table **4104** which in turn provides varying digital input values to a DAC circuit **4108** that feeds a power amplifier. The addresses may be scanned according to a frequency of interest. Using such a lookup table **4104** enables generating various types of wave shapes that can be fed into tissue or into a transducer, an RF electrode, multiple transducers simultaneously, multiple RF electrodes simultaneously, or a combination of RF and ultrasonic instruments. Furthermore, multiple lookup tables **4104** that represent multiple wave shapes can be created, stored, and applied to tissue from a generator.

The waveform signal may be configured to control at least one of an output current, an output voltage, or an output power of an ultrasonic transducer and/or an RF electrode, or multiples thereof (e.g. two or more ultrasonic transducers and/or two or more RF electrodes). Further, where the surgical instrument comprises ultrasonic components, the waveform signal may be configured to drive at least two vibration modes of an ultrasonic transducer of the at least one surgical instrument. Accordingly, a generator may be configured to provide a waveform signal to at least one surgical instrument wherein the waveform signal corresponds to at least one wave shape of a plurality of wave shapes in a table. Further, the waveform signal provided to the two surgical instruments may comprise two or more wave shapes. The table may comprise information associated with a plurality of wave shapes and the table may be stored within the generator. In one aspect or example, the table may be a direct digital synthesis table, which may be stored in an FPGA of the generator. The table may be addressed by anyway that is convenient for categorizing wave shapes. According to one aspect, the table, which may be a direct digital synthesis table, is addressed according to a frequency of the waveform signal. Additionally, the information associated with the plurality of wave shapes may be stored as digital information in the table.

The analog electrical signal waveform may be configured to control at least one of an output current, an output voltage, or an output power of an ultrasonic transducer and/or an RF electrode, or multiples thereof (e.g., two or more ultrasonic transducers and/or two or more RF electrodes). Further, where the surgical instrument comprises ultrasonic components, the analog electrical signal waveform may be configured to drive at least two vibration modes of an ultrasonic transducer of the at least one surgical instrument. Accordingly, the generator circuit may be configured to provide an analog electrical signal waveform to at least one surgical instrument wherein the analog electrical signal waveform corresponds to at least one wave shape of a plurality of wave shapes stored in a lookup table **4104**. Further, the analog electrical signal waveform provided to the two surgical

instruments may comprise two or more wave shapes. The lookup table **4104** may comprise information associated with a plurality of wave shapes and the lookup table **4104** may be stored either within the generator circuit or the surgical instrument. In one aspect or example, the lookup table **4104** may be a direct digital synthesis table, which may be stored in an FPGA of the generator circuit or the surgical instrument. The lookup table **4104** may be addressed by anyway that is convenient for categorizing wave shapes. According to one aspect, the lookup table **4104**, which may be a direct digital synthesis table, is addressed according to a frequency of the desired analog electrical signal waveform. Additionally, the information associated with the plurality of wave shapes may be stored as digital information in the lookup table **4104**.

With the widespread use of digital techniques in instrumentation and communications systems, a digitally-controlled method of generating multiple frequencies from a reference frequency source has evolved and is referred to as direct digital synthesis. The basic architecture is shown in FIG. **13**. In this simplified block diagram, a DDS circuit is coupled to a processor, controller, or a logic device of the generator circuit and to a memory circuit located in the generator circuit of the surgical system **1000**. The DDS circuit **4100** comprises an address counter **4102**, lookup table **4104**, a register **4106**, a DAC circuit **4108**, and a filter **4112**. A stable clock  $f_c$  is received by the address counter **4102** and the register **4106** drives a programmable-read-only-memory (PROM) which stores one or more integral number of cycles of a sinewave (or other arbitrary waveform) in a lookup table **4104**. As the address counter **4102** steps through memory locations, values stored in the lookup table **4104** are written to the register **4106**, which is coupled to the DAC circuit **4108**. The corresponding digital amplitude of the signal at the memory location of the lookup table **4104** drives the DAC circuit **4108**, which in turn generates an analog output signal **4110**. The spectral purity of the analog output signal **4110** is determined primarily by the DAC circuit **4108**. The phase noise is basically that of the reference clock  $f_c$ . The first analog output signal **4110** output from the DAC circuit **4108** is filtered by the filter **4112** and a second analog output signal **4114** output by the filter **4112** is provided to an amplifier having an output coupled to the output of the generator circuit. The second analog output signal has a frequency  $f_{out}$ .

Because the DDS circuit **4100** is a sampled data system, issues involved in sampling must be considered: quantization noise, aliasing, filtering, etc. For instance, the higher order harmonics of the DAC circuit **4108** output frequencies fold back into the Nyquist bandwidth, making them unfilterable, whereas, the higher order harmonics of the output of phase-locked-loop (PLL) based synthesizers can be filtered. The lookup table **4104** contains signal data for an integral number of cycles. The final output frequency  $f_{out}$  can be changed changing the reference clock frequency  $f_c$  or by reprogramming the PROM.

The DDS circuit **4100** may comprise multiple lookup tables **4104** where the lookup table **4104** stores a waveform represented by a predetermined number of samples, wherein the samples define a predetermined shape of the waveform. Thus multiple waveforms having a unique shape can be stored in multiple lookup tables **4104** to provide different tissue treatments based on instrument settings or tissue feedback. Examples of waveforms include high crest factor RF electrical signal waveforms for surface tissue coagulation, low crest factor RF electrical signal waveform for deeper tissue penetration, and electrical signal waveforms

that promote efficient touch-up coagulation. In one aspect, the DDS circuit 4100 can create multiple wave shape lookup tables 4104 and during a tissue treatment procedure (e.g., “on-the-fly” or in virtual real time based on user or sensor inputs) switch between different wave shapes stored in separate lookup tables 4104 based on the tissue effect desired and/or tissue feedback. Accordingly, switching between wave shapes can be based on tissue impedance and other factors, for example. In other aspects, the lookup tables 4104 can store electrical signal waveforms shaped to maximize the power delivered into the tissue per cycle (i.e., trapezoidal or square wave). In other aspects, the lookup tables 4104 can store wave shapes synchronized in such way that they make maximizing power delivery by the multifunction surgical instrument of surgical system 1000 while delivering RF and ultrasonic drive signals. In yet other aspects, the lookup tables 4104 can store electrical signal waveforms to drive ultrasonic and RF therapeutic, and/or sub-therapeutic, energy simultaneously while maintaining ultrasonic frequency lock. Custom wave shapes specific to different instruments and their tissue effects can be stored in the non-volatile memory of the generator circuit or in the non-volatile memory (e.g., EEPROM) of the surgical system 1000 and be fetched upon connecting the multifunction surgical instrument to the generator circuit. An example of an exponentially damped sinusoid, as used in many high crest factor “coagulation” waveforms is shown in FIG. 15.

A more flexible and efficient implementation of the DDS circuit 4100 employs a digital circuit called a Numerically Controlled Oscillator (NCO). A block diagram of a more flexible and efficient digital synthesis circuit such as a DDS circuit 4200 is shown in FIG. 14. In this simplified block diagram, a DDS circuit 4200 is coupled to a processor, controller, or a logic device of the generator and to a memory circuit located either in the generator or in any of the surgical instruments of surgical system 1000. The DDS circuit 4200 comprises a load register 4202, a parallel delta phase register 4204, an adder circuit 4216, a phase register 4208, a lookup table 4210 (phase-to-amplitude converter), a DAC circuit 4212, and a filter 4214. The adder circuit 4216 and the phase register 4208 form part of a phase accumulator 4206. A clock frequency  $f_c$  is applied to the phase register 4208 and a DAC circuit 4212. The load register 4202 receives a tuning word that specifies output frequency as a fraction of the reference clock frequency signal  $f_c$ . The output of the load register 4202 is provided to the parallel delta phase register 4204 with a tuning word M.

The DDS circuit 4200 includes a sample clock that generates the clock frequency  $f_c$ , the phase accumulator 4206, and the lookup table 4210 (e.g., phase to amplitude converter). The content of the phase accumulator 4206 is updated once per clock cycle  $f_c$ . When time the phase accumulator 4206 is updated, the digital number, M, stored in the parallel delta phase register 4204 is added to the number in the phase register 4208 by the adder circuit 4216. Assuming that the number in the parallel delta phase register 4204 is 00 . . . 01 and that the initial contents of the phase accumulator 4206 is 00 . . . 00. The phase accumulator 4206 is updated by 00 . . . 01 per clock cycle. If the phase accumulator 4206 is 32-bits wide, 232 clock cycles (over 4 billion) are required before the phase accumulator 4206 returns to 00 . . . 00, and the cycle repeats.

A truncated output 4218 of the phase accumulator 4206 is provided to a phase-to amplitude converter lookup table 4210 and the output of the lookup table 4210 is coupled to a DAC circuit 4212. The truncated output 4218 of the phase accumulator 4206 serves as the address to a sine (or cosine)

lookup table. An address in the lookup table corresponds to a phase point on the sinewave from 0° to 360°. The lookup table 4210 contains the corresponding digital amplitude information for one complete cycle of a sinewave. The lookup table 4210 therefore maps the phase information from the phase accumulator 4206 into a digital amplitude word, which in turn drives the DAC circuit 4212. The output of the DAC circuit is a first analog signal 4220 and is filtered by a filter 4214. The output of the filter 4214 is a second analog signal 4222, which is provided to a power amplifier coupled to the output of the generator circuit.

In one aspect, the electrical signal waveform may be digitized into 1024 ( $2^{10}$ ) phase points, although the wave shape may be digitized is any suitable number of  $2^n$  phase points ranging from 256 ( $2^8$ ) to 281,474,976,710,656 ( $2^{48}$ ), where n is a positive integer, as shown in TABLE 1. The electrical signal waveform may be expressed as  $A_n(e_n)$ , where a normalized amplitude  $A_n$  at a point n is represented by a phase angle  $\theta_n$  is referred to as a phase point at point n. The number of discrete phase points n determines the tuning resolution of the DDS circuit 4200 (as well as the DDS circuit 4100 shown in FIG. 13).

TABLE 1 specifies the electrical signal waveform digitized into a number of phase points.

TABLE 1

N	Number of Phase Points $2^n$
8	256
10	1,024
12	4,096
14	16,384
16	65,536
18	262,144
20	1,048,576
22	4,194,304
24	16,777,216
26	67,108,864
28	268,435,456
...	...
32	4,294,967,296
...	...
48	281,474,976,710,656
...	...

The generator circuit algorithms and digital control circuits scan the addresses in the lookup table 4210, which in turn provides varying digital input values to the DAC circuit 4212 that feeds the filter 4214 and the power amplifier. The addresses may be scanned according to a frequency of interest. Using the lookup table enables generating various types of shapes that can be converted into an analog output signal by the DAC circuit 4212, filtered by the filter 4214, amplified by the power amplifier coupled to the output of the generator circuit, and fed to the tissue in the form of RF energy or fed to an ultrasonic transducer and applied to the tissue in the form of ultrasonic vibrations which deliver energy to the tissue in the form of heat. The output of the amplifier can be applied to an RF electrode, multiple RF electrodes simultaneously, an ultrasonic transducer, multiple ultrasonic transducers simultaneously, or a combination of RF and ultrasonic transducers, for example. Furthermore, multiple wave shape tables can be created, stored, and applied to tissue from a generator circuit.

With reference back to FIG. 13, for n=32, and M=1, the phase accumulator 4206 steps through  $2^{32}$  possible outputs before it overflows and restarts. The corresponding output wave frequency is equal to the input clock frequency divided

by  $2^{32}$ . If  $M=2$ , then the phase register **4106** “rolls over” twice as fast, and the output frequency is doubled. This can be generalized as follows.

For a phase accumulator **4206** configured to accumulate  $n$ -bits ( $n$  generally ranges from 24 to 32 in most DDS systems, but as previously discussed  $n$  may be selected from a wide range of options), there are  $2^n$  possible phase points. The digital word in the delta phase register,  $M$ , represents the amount the phase accumulator is incremented per clock cycle. If  $f_c$  is the clock frequency, then the frequency of the output sinewave is equal to:

$$f_0 = \frac{M \cdot f_c}{2^n}$$

The above equation is known as the DDS “tuning equation.” Note that the frequency resolution of the system is equal to

$$\frac{f_0}{2^n}$$

For  $n=32$ , the resolution is greater than one part in four billion. In one aspect of the DDS circuit **4200**, not all of the bits out of the phase accumulator **4206** are passed on to the lookup table **4210**, but are truncated, leaving only the first **13** to **15** most significant bits (MSBs), for example. This reduces the size of the lookup table **4210** and does not affect the frequency resolution. The phase truncation only adds a small but acceptable amount of phase noise to the final output.

The electrical signal waveform may be characterized by a current, voltage, or power at a predetermined frequency. Further, where any one of the surgical instruments of surgical system **1000** comprises ultrasonic components, the electrical signal waveform may be configured to drive at least two vibration modes of an ultrasonic transducer of the at least one surgical instrument. Accordingly, the generator circuit may be configured to provide an electrical signal waveform to at least one surgical instrument wherein the electrical signal waveform is characterized by a predetermined wave shape stored in the lookup table **4210** (or lookup table **4104** FIG. 13). Further, the electrical signal waveform may be a combination of two or more wave shapes. The lookup table **4210** may comprise information associated with a plurality of wave shapes. In one aspect or example, the lookup table **4210** may be generated by the DDS circuit **4200** and may be referred to as a direct digital synthesis table. DDS works by first storing a large repetitive waveform in onboard memory. A cycle of a waveform (sine, triangle, square, arbitrary) can be represented by a predetermined number of phase points as shown in TABLE 1 and stored into memory. Once the waveform is stored into memory, it can be generated at very precise frequencies. The direct digital synthesis table may be stored in a non-volatile memory of the generator circuit and/or may be implemented with a FPGA circuit in the generator circuit. The lookup table **4210** may be addressed by any suitable technique that is convenient for categorizing wave shapes. According to one aspect, the lookup table **4210** is addressed according to a frequency of the electrical signal waveform. Additionally, the information associated with the plurality of wave shapes may be stored as digital information in a memory or as part of the lookup table **4210**.

In one aspect, the generator circuit may be configured to provide electrical signal waveforms to at least two surgical instruments simultaneously. The generator circuit also may be configured to provide the electrical signal waveform, which may be characterized two or more wave shapes, via an output channel of the generator circuit to the two surgical instruments simultaneously. For example, in one aspect the electrical signal waveform comprises a first electrical signal to drive an ultrasonic transducer (e.g., ultrasonic drive signal), a second RF drive signal, and/or a combination thereof. In addition, an electrical signal waveform may comprise a plurality of ultrasonic drive signals, a plurality of RF drive signals, and/or a combination of a plurality of ultrasonic and RF drive signals.

In addition, a method of operating the generator circuit according to the present disclosure comprises generating an electrical signal waveform and providing the generated electrical signal waveform to any one of the surgical instruments of surgical system **1000**, where generating the electrical signal waveform comprises receiving information associated with the electrical signal waveform from a memory. The generated electrical signal waveform comprises at least one wave shape. Furthermore, providing the generated electrical signal waveform to the at least one surgical instrument comprises providing the electrical signal waveform to at least two surgical instruments simultaneously.

The generator circuit as described herein may allow for the generation of various types of direct digital synthesis tables. Examples of wave shapes for RF/Electrosurgery signals suitable for treating a variety of tissue generated by the generator circuit include RF signals with a high crest factor (which may be used for surface coagulation in RF mode), a low crest factor RF signals (which may be used for deeper tissue penetration), and waveforms that promote efficient touch-up coagulation. The generator circuit also may generate multiple wave shapes employing a direct digital synthesis lookup table **4210** and, on the fly, can switch between particular wave shapes based on the desired tissue effect. Switching may be based on tissue impedance and/or other factors.

In addition to traditional sine/cosine wave shapes, the generator circuit may be configured to generate wave shape(s) that maximize the power into tissue per cycle (i.e., trapezoidal or square wave). The generator circuit may provide wave shape(s) that are synchronized to maximize the power delivered to the load when driving RF and ultrasonic signals simultaneously and to maintain ultrasonic frequency lock, provided that the generator circuit includes a circuit topology that enables simultaneously driving RF and ultrasonic signals. Further, custom wave shapes specific to instruments and their tissue effects can be stored in a non-volatile memory (NVM) or an instrument EEPROM and can be fetched upon connecting any one of the surgical instruments of surgical system **1000** to the generator circuit.

The DDS circuit **4200** may comprise multiple lookup tables **4104** where the lookup table **4210** stores a waveform represented by a predetermined number of phase points (also may be referred to as samples), wherein the phase points define a predetermined shape of the waveform. Thus multiple waveforms having a unique shape can be stored in multiple lookup tables **4210** to provide different tissue treatments based on instrument settings or tissue feedback. Examples of waveforms include high crest factor RF electrical signal waveforms for surface tissue coagulation, low crest factor RF electrical signal waveform for deeper tissue penetration, and electrical signal waveforms that promote

efficient touch-up coagulation. In one aspect, the DDS circuit **4200** can create multiple wave shape lookup tables **4210** and during a tissue treatment procedure (e.g., “on-the-fly” or in virtual real time based on user or sensor inputs) switch between different wave shapes stored in different lookup tables **4210** based on the tissue effect desired and/or tissue feedback. Accordingly, switching between wave shapes can be based on tissue impedance and other factors, for example. In other aspects, the lookup tables **4210** can store electrical signal waveforms shaped to maximize the power delivered into the tissue per cycle (i.e., trapezoidal or square wave). In other aspects, the lookup tables **4210** can store wave shapes synchronized in such way that they make maximizing power delivery by any one of the surgical instruments of surgical system **1000** when delivering RF and ultrasonic drive signals. In yet other aspects, the lookup tables **4210** can store electrical signal waveforms to drive ultrasonic and RF therapeutic, and/or sub-therapeutic, energy simultaneously while maintaining ultrasonic frequency lock. Generally, the output wave shape may be in the form of a sine wave, cosine wave, pulse wave, square wave, and the like. Nevertheless, the more complex and custom wave shapes specific to different instruments and their tissue effects can be stored in the non-volatile memory of the generator circuit or in the non-volatile memory (e.g., EEPROM) of the surgical instrument and be fetched upon connecting the surgical instrument to the generator circuit. One example of a custom wave shape is an exponentially damped sinusoid as used in many high crest factor “coagulation” waveforms, as shown in FIG. **43**.

FIG. **15** illustrates one cycle of a discrete time digital electrical signal waveform **4300**, in accordance with at least one aspect of the present disclosure of an analog waveform **4304** (shown superimposed over the discrete time digital electrical signal waveform **4300** for comparison purposes). The horizontal axis represents Time (t) and the vertical axis represents digital phase points. The digital electrical signal waveform **4300** is a digital discrete time version of the desired analog waveform **4304**, for example. The digital electrical signal waveform **4300** is generated by storing an amplitude phase point **4302** that represents the amplitude per clock cycle  $T_{clk}$  over one cycle or period  $T_o$ . The digital electrical signal waveform **4300** is generated over one period  $T_o$  by any suitable digital processing circuit. The amplitude phase points are digital words stored in a memory circuit. In the example illustrated in FIGS. **13**, **14**, the digital word is a six-bit word that is capable of storing the amplitude phase points with a resolution of 26 or 64 bits. It will be appreciated that the examples shown in FIGS. **13**, **14** is for illustrative purposes and in actual implementations the resolution can be much higher. The digital amplitude phase points **4302** over one cycle  $T_o$  are stored in the memory as a string of string words in a lookup table **4104**, **4210** as described in connection with FIGS. **13**, **14**, for example. To generate the analog version of the analog waveform **4304**, the amplitude phase points **4302** are read sequentially from the memory from 0 to  $T_o$  per clock cycle  $T_{clk}$  and are converted by a DAC circuit **4108**, **4212**, also described in connection with FIGS. **13**, **14**. Additional cycles can be generated by repeatedly reading the amplitude phase points **4302** of the digital electrical signal waveform **4300** the from 0 to  $T_o$  for as many cycles or periods as may be desired. The smooth analog version of the analog waveform **4304** is achieved by filtering the output of the DAC circuit **4108**, **4212** by a filter **4112**, **4214** (FIGS. **13** and **14**). The filtered analog output signal **4114**, **4222** (FIGS. **13** and **14**) is applied to the input of a power amplifier.

FIG. **16** is a diagram of a control system **12950** that may be implemented as a nested PID feedback controller. A PID controller is a control loop feedback mechanism (controller) to continuously calculate an error value as the difference between a desired set point and a measured process variable and applies a correction based on proportional, integral, and derivative terms (sometimes denoted P, I, and D respectively). The nested PID controller feedback control system **12950** includes a primary controller **12952**, in a primary (outer) feedback loop **12954** and a secondary controller **12955** in a secondary (inner) feedback loop **12956**. The primary controller **12952** may be a PID controller **12972** as shown in FIG. **17**, and the secondary controller **12955** also may be a PID controller **12972** as shown in FIG. **17**. The primary controller **12952** controls a primary process **12958** and the secondary controller **12955** controls a secondary process **12960**. The output **12966** of the primary process **12958** is subtracted from a primary set point  $SP_1$  by a first summer **12962**. The first summer **12962** produces a single sum output signal which is applied to the primary controller **12952**. The output of the primary controller **12952** is the secondary set point  $SP_2$ . The output **12968** of the secondary process **12960** is subtracted from the secondary set point  $SP_2$  by a second summer **12964**.

FIG. **17** illustrates a PID feedback control system **12970** according to one aspect of this disclosure. The primary controller **12952** or the secondary controller **12955**, or both, may be implemented as a PID controller **12972**. In one aspect, the PID controller **12972** may comprise a proportional element **12974** (P), an integral element **12976** (I), and a derivative element **12978** (D). The outputs of the P, I, D elements **12974**, **12976**, **12978** are summed by a summer **12986**, which provides the control variable  $p(t)$  to the process **12980**. The output of the process **12980** is the process variable  $y(t)$ . A summer **12984** calculates the difference between a desired set point  $r(t)$  and a measured process variable  $y(t)$ , received by feedback loop **12982**. The PID controller **12972** continuously calculates an error value  $e(t)$  (e.g., difference between closure force threshold and measured closure force) as the difference between a desired set point  $r(t)$  (e.g., closure force threshold) and a measured process variable  $y(t)$  (e.g., velocity and direction of closure tube) and applies a correction based on the proportional, integral, and derivative terms calculated by the proportional element **12974** (P), integral element **12976** (I), and derivative element **12978** (D), respectively. The PID controller **12972** attempts to minimize the error  $e(t)$  over time by adjustment of the control variable  $p(t)$  (e.g., velocity and direction of the closure tube).

In accordance with the PID algorithm, the “P” element **12974** accounts for present values of the error. For example, if the error is large and positive, the control output will also be large and positive. In accordance with the present disclosure, the error term  $e(t)$  is the difference between the desired closure force and the measured closure force of the closure tube. The “I” element **12976** accounts for past values of the error. For example, if the current output is not sufficiently strong, the integral of the error will accumulate over time, and the controller will respond by applying a stronger action. The “D” element **12978** accounts for possible future trends of the error, based on its current rate of change. For example, continuing the P example above, when the large positive control output succeeds in bringing the error closer to zero, it also puts the process on a path to large negative error in the near future. In this case, the derivative turns negative and the D module reduces the strength of the action to prevent this overshoot.

It will be appreciated that other variables and set points may be monitored and controlled in accordance with the feedback control systems **12950**, **12970**. For example, the adaptive closure member velocity control algorithm described herein may measure at least two of the following parameters: firing member stroke location, firing member load, displacement of cutting element, velocity of cutting element, closure tube stroke location, closure tube load, among others.

FIG. **18** is an alternative system **132000** for controlling the frequency of an ultrasonic electromechanical system **132002** and detecting the impedance thereof, in accordance with at least one aspect of the present disclosure. The system **132000** may be incorporated into a generator. A processor **132004** coupled to a memory **132026** programs a programmable counter **132006** to tune to the output frequency  $f_o$  of the ultrasonic electromechanical system **132002**. The input frequency is generated by a crystal oscillator **132008** and is input into a fixed counter **132010** to scale the frequency to a suitable value. The outputs of the fixed counter **132010** and the programmable counter **132006** are applied to a phase/frequency detector **132012**. The output of the phase/frequency detector **132012** is applied to an amplifier/active filter circuit **132014** to generate a tuning voltage  $V_t$  that is applied to a voltage controlled oscillator **132016** (VCO). The VCO **132016** applies the output frequency  $f_o$  to an ultrasonic transducer portion of the ultrasonic electromechanical system **132002**, shown here modeled as an equivalent electrical circuit. The voltage and current signals applied to the ultrasonic transducer are monitored by a voltage sensor **132018** and a current sensor **132020**.

The outputs of the voltage and current sensors **132018**, **132020** are applied to another phase/frequency detector **132022** to determine the phase angle between the voltage and current as measured by the voltage and current sensors **132018**, **132020**. The output of the phase/frequency detector **132022** is applied to one channel of a high speed analog to digital converter **132024** (ADC) and is provided to the processor **132004** therethrough. Optionally, the outputs of the voltage and current sensors **132018**, **132020** may be applied to respective channels of the two-channel ADC **132024** and provided to the processor **132004** for zero crossing, FFT, or other algorithm described herein for determining the phase angle between the voltage and current signals applied to the ultrasonic electromechanical system **132002**.

Optionally the tuning voltage  $V_t$ , which is proportional to the output frequency  $f_o$ , may be fed back to the processor **132004** via the ADC **132024**. This provides the processor **132004** with a feedback signal proportional to the output frequency  $f_o$  and can use this feedback to adjust and control the output frequency  $f_o$ .

Estimating the State of the Jaw (Pad Burn Through, Staples, Broken Blade, Bone in Jaw, Tissue in Jaw)

A challenge with ultrasonic energy delivery is that ultrasonic acoustics applied on the wrong materials or the wrong tissue can result in device failure, for example, clamp arm pad burn through or ultrasonic blade breakage. It is also desirable to detect what is located in the jaws of an end effector of an ultrasonic device and the state of the jaws without adding additional sensors in the jaws. Locating sensors in the jaws of an ultrasonic end effector poses reliability, cost, and complexity challenges.

Ultrasonic spectroscopy smart blade algorithm techniques may be employed for estimating the state of the jaw (clamp

arm pad burn through, staples, broken blade, bone in jaw, tissue in jaw, back-cutting with jaw closed, etc.) based on the impedance

$$Z_g(t) = \frac{V_g(t)}{I_g(t)}$$

of an ultrasonic transducer configured to drive an ultrasonic transducer blade, in accordance with at least one aspect of the present disclosure. The impedance  $Z_g(t)$ , magnitude  $|Z|$ , and phase  $\varphi$  are plotted as a function of frequency  $f$ .

Dynamic mechanical analysis (DMA), also known as dynamic mechanical spectroscopy or simply mechanical spectroscopy, is a technique used to study and characterize materials. A sinusoidal stress is applied to a material, and the strain in the material is measured, allowing the determination of the complex modulus of the material. The spectroscopy as applied to ultrasonic devices includes exciting the tip of the ultrasonic blade with a sweep of frequencies (compound signals or traditional frequency sweeps) and measuring the resulting complex impedance at each frequency. The complex impedance measurements of the ultrasonic transducer across a range of frequencies are used in a classifier or model to infer the characteristics of the ultrasonic end effector. In one aspect, the present disclosure provides a technique for determining the state of an ultrasonic end effector (clamp arm, jaw) to drive automation in the ultrasonic device (such as disabling power to protect the device, executing adaptive algorithms, retrieving information, identifying tissue, etc.).

FIG. **19** is a spectra **132030** of an ultrasonic device with a variety of different states and conditions of the end effector where the impedance  $Z_g(t)$ , magnitude  $|Z|$ , and phase  $\varphi$  are plotted as a function of frequency  $f$ , in accordance with at least one aspect of the present disclosure. The spectra **132030** is plotted in three-dimensional space where frequency (Hz) is plotted along the x-axis, phase (Rad) is plotted along the y-axis, and magnitude (Ohms) is plotted along the z-axis.

Spectral analysis of different jaw bites and device states produces different complex impedance characteristic patterns (fingerprints) across a range of frequencies for different conditions and states. Each state or condition has a different characteristic pattern in 3D space when plotted. These characteristic patterns can be used to estimate the condition and state of the end effector. FIG. **19** shows the spectra for air **132032**, clamp arm pad **132034**, chamois **132036**, staple **132038**, and broken blade **132040**. The chamois **132036** may be used to characterize different types of tissue.

The spectra **132030** can be evaluated by applying a low-power electrical signal across the ultrasonic transducer to produce a non-therapeutic excitation of the ultrasonic blade. The low-power electrical signal can be applied in the form of a sweep or a compound Fourier series to measure the impedance

$$Z_g(t) = \frac{V_g(t)}{I_g(t)}$$

across the ultrasonic transducer at a range of frequencies in series (sweep) or in parallel (compound signal) using an FFT.

For each characteristic pattern, a parametric line can be fit to the data used for training using a polynomial, a Fourier series, or any other form of parametric equation as may be dictated by convenience. A new data point is then received and is classified by using the Euclidean perpendicular distance from the new data point to the trajectory that has been fitted to the characteristic pattern training data. The perpendicular distance of the new data point to each of the trajectories (each trajectory representing a different state or condition) is used to assign the point to a state or condition.

The probability distribution of distance of each point in the training data to the fitted curve can be used to estimate the probability of a correctly classified new data point. This essentially constructs a two-dimensional probability distribution in a plane perpendicular to the fitted trajectory at each new data point of the fitted trajectory. The new data point can then be included in the training set based on its probability of correct classification to make an adaptive, learning classifier that readily detects high-frequency changes in states but adapts to slow occurring deviations in system performance, such as a device getting dirty or the pad wearing out.

FIG. 20 is a graphical representation of a plot 132042 of a set of 3D training data set (S), where ultrasonic transducer impedance  $Z_g(t)$ , magnitude  $|Z|$ , and phase  $\varphi$  are plotted as a function of frequency  $f$ , in accordance with at least one aspect of the present disclosure. The 3D training data set (S) plot 132042 is graphically depicted in three-dimensional space where phase (Rad) is plotted along the x-axis, frequency (Hz) is plotted along the y-axis, magnitude (Ohms) is plotted along the z-axis, and a parametric Fourier series is fit to the 3D training data set (S). A methodology for classifying data is based on the 3D training data set (S) used to generate the plot 132042.

The parametric Fourier series fit to the 3D training data set (S) is defined by:

$$\vec{p} = \vec{a}_0 + \sum_{n=1}^{\infty} \left( \vec{a}_n \cos \frac{n\pi t}{L} + \vec{b}_n \sin \frac{n\pi t}{L} \right)$$

For a new point  $\vec{z}$ , the perpendicular distance from  $\vec{p}$  to  $\vec{z}$  is found by:

$$D = \|\vec{p} - \vec{z}\|$$

When:

$$\frac{\partial D}{\partial T} = 0$$

Then:

$$D = D_{\perp}$$

A probability distribution of D can be used to estimate the probability of a data point  $\vec{z}$  belonging to the group S.

Control

Based on the classification of data measured before, during, or after activation of the ultrasonic transducer/

ultrasonic blade, a variety of automated tasks and safety measures can be implemented. Similarly, the state of the tissue located in the end effector and temperature of the ultrasonic blade also can be inferred to some degree, and used to better inform the user of the state of the ultrasonic device or protect critical structures, etc. Temperature control of an ultrasonic blade is described in commonly owned U.S. Provisional Patent Application No. 62/640,417, filed Mar. 8, 2018, titled TEMPERATURE CONTROL IN ULTRASONIC DEVICE AND CONTROL SYSTEM THEREFOR, which is incorporated herein by reference in its entirety.

Similarly, power delivery can be reduced when there is a high probability that the ultrasonic blade is contacting the clamp arm pad (e.g., without tissue in between) or if there is a probability that the ultrasonic blade has broken or that the ultrasonic blade is touching metal (e.g., a staple). Furthermore, back-cutting can be disallowed if the jaw is closed and no tissue is detected between the ultrasonic blade and the clamp arm pad.

Integration of Other Data to Improve Classification

This system can be used in conjunction with other information provided by sensors, the user, metrics on the patient, environmental factors, etc., by combing the data from this process with the aforementioned data using probability functions and a Kalman filter. The Kalman filter determines the maximum likelihood of a state or condition occurring given a plethora of uncertain measurements of varying confidence. Since this method allows for an assignment of probability to a newly classified data point, this algorithm's information can be implemented with other measures or estimates in a Kalman filter.

FIG. 21 is a logic flow diagram 132044 depicting a control program or a logic configuration to determine jaw conditions based on the complex impedance characteristic pattern (fingerprint), in accordance with at least one aspect of the present disclosure. Prior to determining jaw conditions based on the complex impedance characteristic pattern (fingerprint), a database is populated with reference complex impedance characteristic patterns or a training data sets (S) that characterize various jaw conditions, including, without limitation, air 132032, clamp arm pad 132034, chamois 132036, staple 132038, broken blade 132040, as shown in FIG. 19, and a variety of tissue types and conditions. The chamois dry or wet, full byte or tip, may be used to characterize different types of tissue. The data points used to generate reference complex impedance characteristic patterns or a training data set (S) are obtained by applying a sub-therapeutic drive signal to the ultrasonic transducer, sweeping the driving frequency over a predetermined range of frequencies from below resonance to above resonance, measuring the complex impedance at each of the frequencies, and recording the data points. The data points are then fit to a curve using a variety of numerical methods including polynomial curve fit, Fourier series, and/or parametric equation. A parametric Fourier series fit to the reference complex impedance characteristic patterns or a training data set (S) is described herein.

Once the reference complex impedance characteristic patterns or a training data sets (S) are generated, the ultrasonic instrument measures new data points, classifies the new points, and determines whether the new data points should be added to the reference complex impedance characteristic patterns or a training data sets (S).

Turning now to the logic flow diagram of FIG. 21, in one aspect, the control circuit measures 132046 a complex impedance of an ultrasonic transducer, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)}$$

The control circuit receives 132048 a complex impedance measurement data point and compares 132050 the complex impedance measurement data point to a data point in a reference complex impedance characteristic pattern. The control circuit classifies 132052 the complex impedance measurement data point based on a result of the comparison analysis and assigns 132054 a state or condition of the end effector based on the result of the comparison analysis.

In one aspect, the control circuit receives the reference complex impedance characteristic pattern from a database or memory coupled to the processor. In one aspect, the control circuit generates the reference complex impedance characteristic pattern as follows. A drive circuit coupled to the control circuit applies a nontherapeutic drive signal to the ultrasonic transducer starting at an initial frequency, ending at a final frequency, and at a plurality of frequencies therebetween. The control circuit measures the impedance of the ultrasonic transducer at each frequency and stores a data point corresponding to each impedance measurement. The control circuit curve fits a plurality of data points to generate a three-dimensional curve of representative of the reference complex impedance characteristic pattern, wherein the magnitude  $|Z|$  and phase  $\varphi$  are plotted as a function of frequency  $f$ . The curve fitting includes a polynomial curve fit, a Fourier series, and/or a parametric equation.

In one aspect, the control circuit receives a new impedance measurement data point and classifies the new impedance measurement data point using a Euclidean perpendicular distance from the new impedance measurement data point to a trajectory that has been fitted to the reference complex impedance characteristic pattern. The control circuit estimates a probability that the new impedance measurement data point is correctly classified. The control circuit adds the new impedance measurement data point to the reference complex impedance characteristic pattern based on the probability of the estimated correct classification of the new impedance measurement data point. In one aspect, the control circuit classifies data based on a training data set (S), where the training data set (S) comprises a plurality of complex impedance measurement data, and curve fits the training data set (S) using a parametric Fourier series, wherein S is defined herein and wherein the probability distribution is used to estimate the probability of the new impedance measurement data point belonging to the group S.

State of Jaw Classifier Based on Model

There has been an existing interest in classifying matter located within the jaws of an ultrasonic device including tissue types and condition. In various aspects, it can be shown that with high data sampling and sophisticated pattern recognition this classification is possible. The approach is based on impedance as a function of frequency, where magnitude, phase, and frequency are plotted in 3D the patterns look like ribbons as shown in FIGS. 19 and 20 and the logic flow diagram of FIG. 21. This disclosure provides

an alternative smart blade algorithm approach that is based on a well-established model for piezoelectric transducers.

By way of example, the equivalent electrical lumped parameter model is known to be an accurate model of the physical piezoelectric transducer. It is based on the Mittag-Leffler expansion of a tangent near a mechanical resonance. When the complex impedance or the complex admittance is plotted as an imaginary component versus a real component, circles are formed. FIG. 22 is a circle plot 132056 of complex impedance plotted as an imaginary component versus real components of a piezoelectric vibrator, in accordance with at least one aspect of the present disclosure. FIG. 23 is a circle plot 132058 of complex admittance plotted as an imaginary component versus real components of a piezoelectric vibrator, in accordance with at least one aspect of the present disclosure. The circles depicted in FIGS. 22 and 23 are taken from the IEEE 177 Standard, which is incorporated herein by reference in its entirety. Tables 1-4 are taken from the IEEE 177 Standard and disclosed herein for completeness.

The circle is created as the frequency is swept from below resonance to above resonance. Rather than stretching the circle out in 3D, a circle is identified and the radius (r) and offsets (a, b) of the circle are estimated. These values are then compared with established values for given conditions. These conditions may be: 1) open nothing in jaws, 2) tip bite 3) full bite and staple in jaws. If the sweep generates multiple resonances, circles of different characteristics will be present for each resonance. Each circle will be drawn out before the next if the resonances are separated. Rather than fitting a 3D curve with a series approximation, the data is fitted with a circle. The radius (r) and offsets (a, b) can be calculated using a processor programmed to execute a variety of mathematical or numerical techniques described below. These values may be estimated by capturing an image of a circle and, using image processing techniques, the radius (r) and offsets (a, b) that define the circle are estimated.

FIG. 24 is a circle plot 132060 of complex admittance for a 55.5 kHz ultrasonic piezoelectric transducer for lumped parameters inputs and outputs specified hereinbelow. Values for a lumped parameter model were used to generate the complex admittance. A moderate load was applied in the model. The obtained admittance circle generated in Math-Cad is shown in FIG. 24. The circle plot 132060 is formed when the frequency is swept from 54 to 58 kHz.

The lumped parameter input values are:

$$C_o = 3.0 \text{ nF}$$

$$C_s = 8.22 \text{ pF}$$

$$L_s = 1.0 \text{ H}$$

$$R_s = 450 \Omega$$

The outputs of the model based on the inputs are:

$$am = \frac{D \cdot C - B \cdot C}{A \cdot C - B^2} = 1.013 \cdot 10^3$$

$$bm = \frac{A \cdot E - B \cdot D}{A \cdot C - B^2} = -954.585$$

$$rm = \frac{1}{f_{pts}} \left( \sum_i^{f_{ps}} \sqrt{((Z_{out1,i} - am)^2 + (Z_{out2,i} - bm)^2)} \right) = 1.012 \cdot 10^3$$

The output values are used to plot the circle plot **132060** shown in FIG. **24**. The circle plot **132060** has a radius (r) and the center **132062** is offset (a, b) from the origin **132064** as follows:

$$r=1.012 \cdot 10^3$$

$$a=1.013 \cdot 10^3$$

$$b=-954.585$$

The summations A-E specified below are needed to estimate the circle plot **132060** plot for the example given in FIG. **24**, in accordance with at least one aspect of the present disclosure. Several algorithms exist to calculate a fit to a circle. A circle is defined by its radius (r) and offsets (a, b) of the center from the origin:

$$r^2=(x-a)^2+(y-b)^2$$

The modified least squares method (Umbach and Jones) is convenient in that there a simple close formed solution for a, b, and r.

$$\hat{a} = \frac{DC - BE}{AC - B^2}$$

$$\hat{b} = \frac{AE - BD}{AC - B^2}$$

$$\hat{r} = \frac{1}{n} \sum_{i=1}^n \sqrt{(x_i - \hat{a})^2 + (y_i - \hat{b})^2}$$

The caret symbol over the variable “a” indicates an estimate of the true value. A, B, C, D, and E are summations of various products which are calculated from the data. They are included herein for completeness as follows:

$$A := fpts \cdot \sum_i (Zout_{1,i})^2 - \left( \sum_i (Zout_{1,i}) \right)^2 = 5.463 \cdot 10^{10}$$

B :=

$$fpts \sum_i (Zout_{1,i} \cdot Zout_{2,i}) - \left( \sum_i (Zout_{1,i}) \right) \cdot \left( \sum_i (Zout_{2,i}) \right) = 5.461 \cdot 10^7$$

$$C := fpts \sum_i (Zout_{2,i})^2 - \left( \sum_i (Zout_{2,i}) \right)^2 = 5.445 \cdot 10^{10}$$

$$D := 0.5 \cdot \left( fpts \sum_i (Zout_{1,i} \cdot (Zout_{2,i})^2) - \left( \sum_i (Zout_{1,i}) \right) \cdot \left( \sum_i (Zout_{2,i})^2 \right) \right) +$$

$$fpts \sum_i (Zout_{1,i}^3) - \left( \sum_i (Zout_{1,i}) \right) \cdot \left( \sum_i (Zout_{1,i})^2 \right) = 5.529 \cdot 10^3$$

$$E := 0.5 \cdot \left( fpts \sum_i (Zout_{2,i} \cdot (Zout_{1,i})^2) - \left( \sum_i (Zout_{2,i}) \right) \cdot \left( \sum_i (Zout_{1,i})^2 \right) \right) +$$

$$fpts \sum_i (Zout_{2,i}^3) - \left( \sum_i (Zout_{2,i}) \right) \cdot \left( \sum_i (Zout_{2,i})^2 \right) = -5.192 \cdot 10^{13}$$

Z1,i is a first vector of the real components referred to as conductance;

Z2,i is a second of the imaginary components referred to as susceptance; and

Z3,i is a third vector that represents the frequencies at which admittances are calculated.

This disclosure will work for ultrasonic systems and may possibly be applied to electrosurgical systems, even though electrosurgical systems do not rely on a resonance.

FIGS. **25-29** illustrate images taken from an impedance analyzer showing impedance/admittance circle plots for an ultrasonic device with the end effector jaw in various open or closed configurations and loading. The circle plots in solid line depict impedance and the circle plots in broken lines depict admittance, in accordance with at least one aspect of the present disclosure. By way of example, the impedance/admittance circle plots are generated by connecting an ultrasonic device to an impedance analyzer. The display of the impedance analyzer is set to complex impedance and complex admittance, which can be selectable from the front panel of the impedance analyzer. An initial display may be obtained with the jaw of the ultrasonic end effector in an open position and the ultrasonic device in an unloaded state, as described below in connection with FIG. **25**, for example. The autoscale display function of the impedance analyzer may be used to generate both the complex impedance and admittance circle plots. The same display is used for subsequent runs of the ultrasonic device with different loading conditions as shown in the subsequent FIGS. **25-29**. A LabVIEW application may be employed to upload the data files. In another technique, the display images may be captured with a camera, such as a smartphone camera, like an iPhone or Android. As such, the image of the display may include some “keystone-ing” and in general may not appear to be parallel to the screen. Using this technique, the circle plot traces on the display will appear distorted in the captured image. With this approach, the material located in the jaws of the ultrasonic end effector can be classified.

The complex impedance and complex admittance are just the reciprocal of one another. No new information should be added by looking at both. Another consideration includes determining how sensitive the estimates are to noise when using complex impedance or complex admittance.

In the examples illustrated in FIGS. **25-29**, the impedance analyzer is set up with a range to just capture the main resonance. By scanning over a wider range of frequencies more resonances may be encountered and multiple circle plots may be formed. An equivalent circuit of an ultrasonic transducer may be modeled by a first “motional” branch having a serially connected inductance Ls, resistance Rs and capacitance Cs that define the electromechanical properties of the resonator, and a second capacitive branch having a static capacitance C0. In the impedance/admittance plots shown in FIGS. **25-29** that follow, the values of the components of the equivalent circuit are:

$$Ls=L1=1.1068 \text{ H}$$

$$Rs=R1=311.352\Omega$$

$$Cs=C1=7.43265 \text{ pF}$$

$$C0=C0=3.64026 \text{ nF}$$

The oscillator voltage applied to the ultrasonic transducer is 500 mV and the frequency is swept from 55 kHz to 56 kHz. The impedance (Z) scale is 200 Ω/div and the admittance (Y) scale is 500 μS/div. Measurements of values that may characterize the impedance (Z) and admittance (Y) circle plots may be obtained at the locations on the circle plots as indicated by an impedance cursor and an admittance cursor.

State of Jaw: Open with No Loading

65

FIG. **25** is a graphical display **132066** of an impedance analyzer showing complex impedance (Z)/admittance (Y)

circle plots **132068**, **132070** for an ultrasonic device with the jaw open and no loading where a circle plot **132068** in solid line depicts complex impedance and a circle plot **132070** in broken line depicts complex admittance, in accordance with at least one aspect of the present disclosure. The oscillator voltage applied to the ultrasonic transducer is 500 mV and the frequency is swept from 55 kHz to 56 kHz. The impedance (Z) scale is 200  $\Omega$ /div and the admittance (Y) scale is 500  $\mu$ S/div. Measurements of values that may characterize the complex impedance (Z) and admittance (Y) circle plots **132068**, **132070** may be obtained at locations on the circle plots **132068**, **132070** as indicated by the impedance cursor **132072** and the admittance cursor **132074**. Thus, the impedance cursor **132072** is located at a portion of the impedance circle plot **132068** that is equivalent to about 55.55 kHz, and the admittance cursor **132074** is located at a portion of the admittance circle plot **132070** that is equivalent to about 55.29 kHz. As depicted in FIG. 25, the position of the impedance cursor **132072** corresponds to values of:

$$R=1.66026\Omega$$

$$X=-697.309\Omega$$

Where R is the resistance (real value) and X is the reactance (imaginary value). Similarly, the position of the admittance cursor **132074** corresponds to values of:

$$G=64.0322 \mu\text{S}$$

$$B=1.63007 \text{ mS}$$

Where G is the conductance (real value) and B is susceptance (imaginary value).

State of Jaw: Clamped on Dry Chamois

FIG. 26 is a graphical display **132076** of an impedance analyzer showing complex impedance (Z)/admittance (Y) circle plots **132078**, **132080** for an ultrasonic device with the jaw of the end effector clamped on dry chamois where the impedance circle plot **132078** is shown in solid line and the admittance circle plot **132080** is shown in broken line, in accordance with at least one aspect of the present disclosure. The voltage applied to the ultrasonic transducer is 500 mV and the frequency is swept from 55 kHz to 56 kHz. The impedance (Z) scale is 200  $\Omega$ /div and the admittance (Y) scale is 500  $\mu$ S/div.

Measurements of values that may characterize the complex impedance (Z) and admittance (Y) circle plots **132078**, **132080** may be obtained at locations on the circle plots **132078**, **132080** as indicated by the impedance cursor **132082** and the admittance cursor **132084**. Thus, the impedance cursor **132082** is located at a portion of the impedance circle plot **132078** that is equivalent to about 55.68 kHz, and the admittance cursor **132084** is located at a portion of the admittance circle plot **132080** that is equivalent to about 55.29 kHz. As depicted in FIG. 26, the position of the impedance cursor **132082** corresponds to values of:

$$R=434.577\Omega$$

$$X=-758.772\Omega$$

Where R is the resistance (real value) and X is the reactance (imaginary value).

Similarly, the position of the admittance cursor **132084** corresponds to values of:

$$G=85.1712 \mu\text{S}$$

$$B=1.49569 \text{ mS}$$

Where G is the conductance (real value) and B is susceptance (imaginary value).

State of Jaw: Tip Clamped on Moist Chamois

FIG. 27 is a graphical display **132086** of an impedance analyzer showing complex impedance (Z)/admittance (Y) circle plots **132098**, **132090** for an ultrasonic device with the jaw tip clamped on moist chamois where the impedance circle plot **132088** is shown in solid line and the admittance circle plot **132090** is shown in broken line, in accordance with at least one aspect of the present disclosure. The voltage applied to the ultrasonic transducer is 500 mV and the frequency is swept from 55 kHz to 56 kHz. The impedance (Z) scale is 200  $\Omega$ /div and the admittance (Y) scale is 500  $\mu$ S/div.

Measurements of values that may characterize the complex impedance (Z) and complex admittance (Y) circle plots **132088**, **132090** may be obtained at locations on the circle plots **132088**, **132090** as indicated by the impedance cursor **132092** and the admittance cursor **132094**. Thus, the impedance cursor **132092** is located at a portion of the impedance circle plot **132088** that is equivalent to about 55.68 kHz, and the admittance cursor **132094** is located at a portion of the admittance circle plot **132090** that is equivalent to about 55.29 kHz. As depicted in FIG. 28, the impedance cursor **132092** corresponds to values of:

$$R=445.259\Omega$$

$$X=-750.082\Omega$$

Where R is the resistance (real value) and X is the reactance (imaginary value). Similarly, the admittance cursor **132094** corresponds to values of:

$$G=96.2179 \mu\text{S}$$

$$B=1.50236 \text{ mS}$$

Where G is the conductance (real value) and B is susceptance (imaginary value).

State of Jaw: Fully Clamped on Moist Chamois

FIG. 28 is a graphical display **132096** of an impedance analyzer showing complex impedance (Z)/admittance (Y) circle plots **132098**, **132100** for an ultrasonic device with the jaw fully clamped on moist chamois where the impedance circle plot **132098** is shown in solid line and the admittance circle plot **132100** is shown in broken line, in accordance with at least one aspect of the present disclosure. The voltage applied to the ultrasonic transducer is 500 mV and the frequency is swept from 55 kHz to 56 kHz. The impedance (Z) scale is 200  $\Omega$ /div and the admittance (Y) scale is 500  $\mu$ S/div.

Measurements of values that may characterize the impedance and admittance circle plots **132098**, **132100** may be obtained at locations on the circle plots **132098**, **1332100** as indicated by the impedance cursor **132102** and admittance cursor **132104**. Thus, the impedance cursor **132102** is located at a portion of the impedance circle plot **132098** equivalent to about 55.63 kHz, and the admittance cursor **132104** is located at a portion of the admittance circle plot **132100** equivalent to about 55.29 kHz. As depicted in FIG. 28, the impedance cursor **132102** corresponds to values of R, the resistance (real value, not shown), and X, the reactance (imaginary value, also not shown).

61

Similarly, the admittance cursor **132104** corresponds to values of:

$$G=137.272 \mu\text{S}$$

$$B=1.48481 \text{ mS}$$

Where G is the conductance (real value) and B is susceptance (imaginary value).

State of Jaw: Open with No Loading

FIG. 29 is a graphical display **132106** of an impedance analyzer showing impedance (Z)/admittance (Y) circle plots where frequency is swept from 48 kHz to 62 kHz to capture multiple resonances of an ultrasonic device with the jaw open and no loading where the area designated by the rectangle **132108** shown in broken line is to help see the impedance circle plots **132110a**, **132110b**, **132110c** shown in solid line and the admittance circle plots **132112a**, **132112b**, **132112c**, in accordance with at least one aspect of the present disclosure. The voltage applied to the ultrasonic transducer is 500 mV and the frequency is swept from 48 kHz to 62 kHz. The impedance (Z) scale is 500 Ω/div and the admittance (Y) scale is 500 μS/div.

Measurements of values that may characterize the impedance and admittance circle plots **132110a-c**, **132112a-c** may be obtained at locations on the impedance and admittance circle plots **132110a-c**, **132112a-c** as indicated by the impedance cursor **132114** and the admittance cursor **132116**. Thus, the impedance cursor **132114** is located at a portion of the impedance circle plots **132110a-c** equivalent to about 55.52 kHz, and the admittance cursor **132116** is located at a portion of the admittance circle plot **132112a-c** equivalent to

62

about 59.55 kHz. As depicted in FIG. 29, the impedance cursor **132114** corresponds to values of:

$$R=1.86163 \text{ k}\Omega$$

$$X=-536.229\Omega$$

Where R is the resistance (real value) and X is the reactance (imaginary value). Similarly, the admittance cursor **132116** corresponds to values of:

$$G=649.956 \mu\text{S}$$

$$B=2.51975 \text{ mS}$$

Where G is the conductance (real value) and B is susceptance (imaginary value).

Because there are only 400 samples across the sweep range of the impedance analyzer, there are only a few points about a resonance. So, the circle on the right side becomes choppy. But this is only due to the impedance analyzer and the settings used to cover multiple resonances.

When multiple resonances are present, there is more information to improve the classifier. The circle plots **132110a-c**, **132112a-c** fit can be calculated for each as encountered to keep the algorithm running fast. So once there is a cross of the complex admittance, which implies a circle, during the sweep, a fit can be calculated.

Benefits include in-the-jaw classifier based on data and a well-known model for ultrasonic systems. Count and characterizations of circles are well known in vision systems. So data processing is readily available. For example, a closed form solution exists to calculate the radius and axes' offsets for a circle. This technique can be relatively fast.

TABLE 2 is a list of symbols used for lumped parameter model of a piezoelectric transducer (from IEEE 177 Standard).

TABLE 2

Symbols	Meaning	SI Units	References		
			Equations	Tables	Figures
$B_p$	Equivalent parallel susceptance of vibrator	mho		2	
$C_0$	Shunt (parallel) capacitance in the equivalent electric circuit	farad	2, 3, 4, 8	5	1, 4
$C_1$	Motional capacitance in the equivalent electric circuit	farad	2, 3, 4, 6, 8, 9	5	1, 4
f	Frequency	hertz			3
$f_a$	Antiresonance frequency, zero susceptance	hertz		2, 4	2, 3
$f_m$	Frequency of maximum admittance (minimum impedance)	hertz		2, 4	2, 3
$f_n$	Frequency of minimum admittance (maximum impedance)	hertz		2, 4	2, 3
$f_p$	Parallel resonance frequency	hertz	2, 3	2, 4	2
$(\text{lossless}) = \frac{1}{2\pi \sqrt{L_1 \frac{C_1 C_0}{C_1 + C_0}}}$					
$f_r$	Resonance frequency, zero substance	hertz		2, 4	2, 3
$f_B$	Motional (series) resonance frequency $\frac{1}{2}$	hertz	2, 3, 6, 7, 9, 11a, 11b, 11c,	2, 4	2, 3, 6, 8

TABLE 2-continued

Symbols	Meaning	SI Units	References		
			Equations	Tables	Figures
$G_p$	Equivalent parallel conductance of vibrator		1		
$L_1$	Motional inductance in the equivalent electric circuit	henry	8, 9		1, 4, 5
M	Figure of merit of a vibrator =	dimensionless	10, 11a,	3, 4, 5	
	$\frac{Q}{r}$		11b		
	$M = \frac{1}{\omega_s C_0 R_1}$				
Q	Quality factor	dimensionless	12	3	6, 8
	$Q = \frac{\omega_s L_1}{R_1} = \frac{1}{\omega_s C_1 R_1} = rM$				
r	Capacitance ratio $r = \frac{C_0}{C_1}$	dimensionless	2, 3, 10, 11	2, 3, 4, 5	8
$R_e$	Impedance at zero phase angle near antiresonance	ohm			2, 3
$R_e$	Equivalent series resistance of vibrator	ohm			1, 2
$R_r$	Impedance at $f_r$ , zero phase angle	ohm			2, 3
$R_1$	Motional resistance in the equivalent electric circuit	ohm	4, 8, 10, 11a, 11b, 11c, 12	2, 5	1, 3, 4, 6, 7, 8
$X_e$	Equivalent series reactance of vibrator	ohm			1, 2
$X_0$	Reactance of shunt (parallel) capacitance at series resonance = $\frac{1}{\omega_s C_0}$	ohm	1, 4, 5	5	3, 7
$X_1$	Reactance of motional (series) arm of vibrator $X_1 = \omega L_1 - \frac{1}{\omega C_1}$	ohm		2	2
Y	Admittance of vibrator	mho	1		
	$Y = G_p + j B_p = \frac{1}{Z}$				
$Y_m$	Maximum admittance of vibrator	mho			3
$Y_n$	Minimum admittance of vibrator	mho			3
Z	Impedance of vibrator $Z = R_e + j X_e$	ohm	1		
$Z_m$	Minimum impedance of vibrator	ohm			3
$Z_n$	Maximum impedance of vibrator	ohm			3
	Absolute value of impedance of vibrator $Z = \sqrt{R_e^2 + X_e^2}$	ohm		2	2
	Absolute value of impedance at $f_m$ (minimum impedance)	ohm			2
	Absolute value of impedance at $f_n$ (maximum impedance)	ohm			2
$\delta$	Normalized damping factor $\delta = \omega_s C_0 R_1$	dimensionless	1	2	

TABLE 2-continued

Symbols	Meaning	SI Units	References		
			Equations	Tables	Figures
$\Omega$	Normalized frequency factor $\Omega = \frac{f^2 - f_s^2}{f_p^2 - f_s^2}$	dimensionless	1	2	
$\omega$	Circular (angular) frequency $\omega = 2\pi f$	hertz		2	
$\omega_s$	Circular frequency at motional resonance $\omega_s = 2\pi f_s$	hertz			

TABLE 3 is a list of symbols for the transmission network (from IEEE 177 Standard).

TABLE 3

Symbols	Meaning	SI Units	References		
			Equations	Tables	Figures
b	Normalized compensation factor $1 - \frac{1}{4\pi^2 f_s^2 C_0 L_0}$	dimensionless	4, 10	5	
B	Normalized admittance factor	dimensionless	10	5	
C	Normalized admittance factor	dimensionless	10	5	
$C_{A-B}$	Stray capacitance between the terminals A-B (Figure 4)	farad			
$C_L$	Load capacitance	farad	6		4
$C_T$	Shunt capacitance terminating transmission circuit	farad	4, 10	5	4
$C_{L1}$	Load capacitance	farad	7		
$C_{L2}$	Load capacitance	farad	7		
$e_2$	Output voltage of transmission network	volt			4
$f_{mT}$	Frequency of maximum transmission	hertz	10		
$F_{sL1}$	Motional resonance frequency of combination of vibrator and $C_{L1}$	hertz	7		
$F_{sL2}$	Motional resonance frequency of combination of vibrator and $C_{L2}$	hertz	7		
$i_1$	Input current to transmission network	ampere			4
$L_0$	Compensation inductance shunting vibrator	henry			4
$M_T$	Figure of merit of termination $= \frac{1}{2\pi f_s C_T R_T} = \frac{X_T}{R_T}$	dimensionless	4, 10	5	
$R_T$	Shunt resistance termination of transmission network	ohm	4, 11a, 11b, 11c, 12	5	4, 6, 7, 8
$R_{sL2}$	Standard resistor	ohm	4, 5	5	7
S	Detector sensitivity smallest detectable current change/ current	dimensionless	12		6
x	Normalized frequency factor $x = \frac{f^2}{f_s^2} - 1 = \frac{\Omega}{r}$	dimensionless	12		
$X_{A-B}$	Reactance of stray capacitance $C_{A-B}$	ohm			

TABLE 3-continued

Symbols	Meaning	SI Units	References		
			Equations	Tables	Figures
$X_T$	Reactance of $C_T$ at the motional resonance  frequency $X_T = \frac{1}{2\pi f_s C_T}$	ohm	4	5	
$X_{mT}$	Normalized frequency factor at the frequency of maximum transmission	dimensionless		5	
$\Delta C_L$	$\Delta C_L = C_{L2} - C_{L1}$	farad	6, 7		
$\Delta f$	$\Delta f_1 = f_{sL1} - f_{sL2}$	hertz	6, 7		6, 8
$\Delta f_1$	$\Delta f_1 = f_{sL1} - f_s$	hertz	6, 7		
$\Delta f_2$	$\Delta f_1 = f_{sL2} - f_s$	hertz	6, 7		

\*Refers to real roots; complex roots to be disregarded.

TABLE 4 is a list of solutions for various characteristic frequencies (from IEEE 177 Standard).

Solutions for the Various Characteristic Frequencies

TABLE 4

Characteristic Frequencies	Meaning	Condition	Constituent Equation for Frequency	Root	57 IEEE 14.S1 <sup>1</sup>
$f_m$	Frequency of maximum admittance (minimum impedance)	= 0	$-2\delta^2(\Omega + r) - 2\Omega r(1 - \Omega) - \Omega^2 = 0$	lower*	$f_m$
$f_a$	Motional (series) resonance frequency	$X_1 = 0$	$\Omega = 0$		$f_a$
$f_r$	Resonance frequency	$X_e = B_p = 0$	$\Omega(1 - \Omega) - \delta^2 = 0$	lower	$f_r$
$f_a$	Antiresonance frequency	$X_e = B_p = 0$	$\Omega(1 - \Omega) - \delta^2 = 0$	upper	$f_a$
$f_p$	Parallel resonance frequency (lossless)	$  = \infty   R_1 = 0$	$\Omega = 1$		$f_p$
$f_n$	Frequency of minimum admittance (maximum impedance)	= 0	$-2\delta^2(\Omega + r) - 2\Omega r(1 - \Omega) - \Omega^2 = 0$	upper*	$f_n$

\*Refers to real roots; complex roots to be disregarded

TABLE 5 is a list of losses of three classes of piezoelectric materials.

TABLE 5

Type of Piezoelectric Vibrator	Minimum Values for the Ratio $Q^2/r$ to be Expected for Various Types of Piezoelectric Vibrators		
	$Q = Mr$	r	$Q^2/r$ min
Piezoelectric Ceramics	90-500	2-40	200
Water-Soluble Piezoelectric Crystals	200-50,000	3-500	80
Quartz	$10^4-10^7$	100-50,000	2000

TABLE 6 illustrates jaw conditions, estimated parameters of a circle based on real time measurements of complex impedance/admittance, radius (re) and offsets (ae and be) of the circle represented by measured variables Re, Ge, Xe, Be, and parameters of a reference circle plots, as described in FIGS. 25-29, based on real time measurements of complex impedance/admittance, radius (rr) and offsets (ar, br) of the reference circle represented by reference variables Rref,

Gref, Xref, Bref. These values are then compared with established values for given conditions. These conditions may be: 1) open with nothing in jaws, 2) tip bite 3) full bite and staple in jaws. The equivalent circuit of the ultrasonic transducer was modeled as follows and the frequency was swept from 55 kHz to 56 kHz:

$Ls=L1=1.1068$  H

$Rs=R1=311.352\Omega$

$Cs=C1=7.43265$  pF and

$C0=C0=3.64026$  nF

TABLE 6

Reference	Reference Circle Plot			
	$R_{ref}(\Omega)$	$G_{ref}(\mu S)$	$X_{ref}(\Omega)$	$B_{ref}(mS)$
Jaw open and no loading	1.66026	64.0322	-697.309	1.63007
Jaw clamped on dry chamois	434.577	85.1712	-758.772	1.49569

TABLE 6-continued

Reference	Reference Circle Plot			
	$R_{ref}(\Omega)$	$G_{ref}(\mu S)$	$X_{ref}(\Omega)$	$B_{ref}(mS)$
Jaw Conditions				
Jaw tip clamped on moist chamois	445.259	96.2179	-750.082	1.50236
Jaw fully clamped on moist chamois		137.272		1.48481

In use, the ultrasonic generator sweeps the frequency, records the measured variables, and determines estimates Re, Ge, Xe, Be. These estimates are then compared to reference variables Rref, Gref, Xref, Bref stored in memory (e.g., stored in a look-up table) and determines the jaw conditions. The reference jaw conditions shown in TABLE 6 are examples only. Additional or fewer reference jaw conditions may be classified and stored in memory. These variables can be used to estimate the radius and offsets of the impedance/admittance circle.

FIG. 30 is a logic flow diagram 132120 of a process depicting a control program or a logic configuration to determine jaw conditions based on estimates of the radius (r) and offsets (a, b) of an impedance/admittance circle, in accordance with at least one aspect of the present disclosure. Initially a data base or lookup table is populated with reference values based on reference jaw conditions as described in connection with FIGS. 25-29 and TABLE 6. A reference jaw condition is set and the frequency is swept from a value below resonance to a value above resonance. The reference values Rref, Gref, Xref, Bref that define the corresponding impedance/admittance circle plot are stored in a database or lookup table. During use, under control of a control program or logic configuration a control circuit of the generator or instrument causes the frequency to sweep 132122 from below resonance to above resonance. The control circuit measures and records 132124 (e.g., stores in memory) the variables Re, Ge, Xe, Be that define the corresponding impedance/admittance circle plot and compares 132126 them to the reference values Rref, Gref, Xref, Bref stored in the database or lookup table. The control circuit determines 132128, e.g., estimates, the end effector jaw conditions based on the results of the comparison.

Vessel Sensing for Adaptive Advanced Hemostasis

In various aspects, the present disclosure provides adaptive vessel sealing modes. In one aspect, the ultrasonic instrument can deliver ultrasonic energy uniquely for veins as opposed to arteries.

In another aspect, the present disclosure provides a technique for identifying the jaw contents of an ultrasonic device. Using this approach, a vessel clamped in the jaw is identified as either a vein or an artery, which can be characterized as differences in vessel wall and pressure. Knowing that a vessel is a vein or an artery can be used to activate a unique advanced hemostasis cycle for each type. A vein requires more time and lower temperature due to the thinner vessel walls, so an advanced hemostasis cycle will include lower current and longer time in the vessel sealing portion of the cycle.

FIG. 31 is a logic flow diagram 132230 depicting a control program or a logic configuration of an adaptive process for identifying a hemostasis vessel, in accordance with at least one aspect of the present disclosure. In accordance with the process, a control circuit of the generator or

instrument senses 132232 the vessel located in the jaw of the ultrasonic device using any of the smart blade algorithm techniques for estimating or classifying the state of the jaw of an ultrasonic device described in connection with FIGS. 19-21 under the heading ESTIMATING THE STATE OF THE JAW (PAD BURN THROUGH, STAPLES, BROKEN BLADE, BONE IN JAW, TISSUE IN JAW and/or FIGS. 22-30 under the heading STATE OF JAW CLASSIFIER BASED ON MODEL and/or techniques for estimating the temperature of the ultrasonic blade are described in related U.S. Provisional Patent Application No. 62/640,417, titled TEMPERATURE CONTROL IN ULTRASONIC DEVICE AND CONTROL SYSTEM THEREFOR, to Nott et al, which is incorporated herein by reference in its entirety. When a vein is sensed 132234 or an artery is sensed 132236, the control circuit receives a command for sealing either a vein or an artery and activates 132238 an advanced hemostasis algorithm based on the type of vessel sensed. In one aspect, the command may be originated by a user from a button located on the instrument to activate the appropriate advanced hemostasis algorithm. In other aspects, the command may be originated automatically based on tissue characterization algorithms.

When a vein is sensed 132234, the control circuit executes 132240 a first algorithm that can seal slower at a lower power level and lower ultrasonic blade temperature. Accordingly, to treat a vein, the control circuit controls the generator to output a lower power P1 and activates the generator for a longer time T1.

When an artery is sensed 132236, the control circuit executes 132242 a second algorithm that can seal faster at a higher power level and higher ultrasonic blade temperature. Accordingly, to treat an artery, the control circuit controls the generator to output higher power P2 and activates the generator for a shorter time T2.

FIG. 32 is a graphical representation 132250 of ultrasonic transducer current profiles as a function of time for vein and artery vessel types, in accordance with at least one aspect of the present disclosure. The vertical axis is generator output current (I) delivered to the ultrasonic transducer and the horizontal axis is time (sec). With reference also to FIG. 31, the first curve 132252 represents a vein and is treated with lower power (P1 at I1) and longer period (T1) and the second curve 132254 represents an artery and is treated with higher power (P2 at I2) applied for a shorter period (T2) relative to the first curve 132252.

In another aspect, the present disclosure provides a technique for delivering ultrasonic transducer current (I) in a feedback control loop to achieve a targeted frequency which is associated with a desired ultrasonic blade temperature. When sealing a vein, for example, the feedback control loop will drive to a higher targeted frequency which corresponds to a cooler ultrasonic blade temperature that is suitable (and may be ideal) for sealing the vein. An artery would be driven to a slightly lower frequency target associated with a hotter ultrasonic blade temperature.

FIG. 33 is a logic flow diagram 132260 depicting a control program or a logic configuration of an adaptive process for identifying a hemostasis vessel, in accordance with at least one aspect of the present disclosure. In accordance with the process, a control circuit of the generator or instrument senses 132262 the vessel in the jaw using any of the smart blade algorithm techniques for estimating or classifying the state of the jaw of an ultrasonic device described in connection with FIGS. 19-21 under the heading ESTIMATING THE STATE OF THE JAW (PAD BURN THROUGH, STAPLES, BROKEN BLADE, BONE IN

JAW, TISSUE IN JAW and/or FIGS. 22-30 under the heading STATE OF JAW CLASSIFIER BASED ON MODEL and/or techniques for estimating the temperature of the ultrasonic blade are described in related U.S. Provisional Patent Application No. 62/640,417, titled TEMPERATURE CONTROL IN ULTRASONIC DEVICE AND CONTROL SYSTEM THEREFOR, to Nott et al, which is incorporated herein by reference in its entirety.

When a vein is sensed 132264, the control circuit executes a first algorithm to supply 132268 current to the ultrasonic transducer to achieve a targeted seal temperature for a vein. A feedback control loop estimates the temperature of the ultrasonic blade and adjusts the current delivered to the ultrasonic transducer to control the temperature of the ultrasonic blade. When an artery is sensed 132266, the control circuit executes a second algorithm to supply 132269 current to the ultrasonic transducer to achieve a targeted seal temperature for an artery. A feedback control loop estimates the temperature of the ultrasonic blade and adjusts the current delivered to the ultrasonic transducer to control the temperature of the ultrasonic blade.

FIG. 34 is a graphical representation 132270 of ultrasonic transducer frequency profiles as a function of time for vein and artery vessel types, in accordance with at least one aspect of the present disclosure. The vertical axis represents the frequency (kHz) of the signal applied to the ultrasonic transducer and the horizontal axis represents time (sec). The first curve 132272 represents a vein. A vein requires a cooler ultrasonic blade temperature to effect a seal. The first algorithm controls the temperature of the ultrasonic blade by setting the frequency applied to the ultrasonic transducer to a higher frequency and controls current delivered to the ultrasonic transducer to maintain the set frequency. The second curve 132274 represents an artery. An artery requires a hotter ultrasonic blade temperature to effect a seal. The second algorithm controls the temperature of the ultrasonic blade by setting the frequency applied to the ultrasonic transducer to a lower frequency and controls current delivered to the ultrasonic transducer to maintain the set frequency.

While several forms have been illustrated and described, it is not the intention of the applicant to restrict or limit the scope of the appended claims to such detail. Numerous modifications, variations, changes, substitutions, combinations, and equivalents to those forms may be implemented and will occur to those skilled in the art without departing from the scope of the present disclosure. Moreover, the structure of each element associated with the described forms can be alternatively described as a means for providing the function performed by the element. Also, where materials are disclosed for certain components, other materials may be used. It is therefore to be understood that the foregoing description and the appended claims are intended to cover all such modifications, combinations, and variations as falling within the scope of the disclosed forms. The appended claims are intended to cover all such modifications, variations, changes, substitutions, modifications, and equivalents.

The foregoing detailed description has set forth various forms of the devices and/or processes via the use of block diagrams, flowcharts, and/or examples. Insofar as such block diagrams, flowcharts, and/or examples contain one or more functions and/or operations, it will be understood by those within the art that each function and/or operation within such block diagrams, flowcharts, and/or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any

combination thereof. Those skilled in the art will recognize that some aspects of the forms disclosed herein, in whole or in part, can be equivalently implemented in integrated circuits, as one or more computer programs running on one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (e.g., as one or more programs running on one or more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and or firmware would be well within the skill of one of skill in the art in light of this disclosure. In addition, those skilled in the art will appreciate that the mechanisms of the subject matter described herein are capable of being distributed as one or more program products in a variety of forms, and that an illustrative form of the subject matter described herein applies regardless of the particular type of signal bearing medium used to actually carry out the distribution.

Instructions used to program logic to perform various disclosed aspects can be stored within a memory in the system, such as dynamic random access memory (DRAM), cache, flash memory, or other storage. Furthermore, the instructions can be distributed via a network or by way of other computer readable media. Thus a machine-readable medium may include any mechanism for storing or transmitting information in a form readable by a machine (e.g., a computer), but is not limited to, floppy diskettes, optical disks, compact disc, read-only memory (CD-ROMs), and magneto-optical disks, read-only memory (ROMs), random access memory (RAM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), magnetic or optical cards, flash memory, or a tangible, machine-readable storage used in the transmission of information over the Internet via electrical, optical, acoustical or other forms of propagated signals (e.g., carrier waves, infrared signals, digital signals, etc.). Accordingly, the non-transitory computer-readable medium includes any type of tangible machine-readable medium suitable for storing or transmitting electronic instructions or information in a form readable by a machine (e.g., a computer).

As used in any aspect herein, the term "control circuit" may refer to, for example, hardwired circuitry, programmable circuitry (e.g., a computer processor comprising one or more individual instruction processing cores, processing unit, processor, microcontroller, microcontroller unit, controller, digital signal processor (DSP), programmable logic device (PLD), programmable logic array (PLA), or field programmable gate array (FPGA)), state machine circuitry, firmware that stores instructions executed by programmable circuitry, and any combination thereof. The control circuit may, collectively or individually, be embodied as circuitry that forms part of a larger system, for example, an integrated circuit (IC), an application-specific integrated circuit (ASIC), a system on-chip (SoC), desktop computers, laptop computers, tablet computers, servers, smart phones, etc. Accordingly, as used herein "control circuit" includes, but is not limited to, electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program (e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at

least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of random access memory), and/or electrical circuitry forming a communications device (e.g., a modem, communications switch, or optical-electrical equipment). Those having skill in the art will recognize that the subject matter described herein may be implemented in an analog or digital fashion or some combination thereof.

As used in any aspect herein, the term “logic” may refer to an app, software, firmware and/or circuitry configured to perform any of the aforementioned operations. Software may be embodied as a software package, code, instructions, instruction sets and/or data recorded on non-transitory computer readable storage medium. Firmware may be embodied as code, instructions or instruction sets and/or data that are hard-coded (e.g., nonvolatile) in memory devices.

As used in any aspect herein, the terms “component,” “system,” “module” and the like can refer to a computer-related entity, either hardware, a combination of hardware and software, software, or software in execution.

As used in any aspect herein, an “algorithm” refers to a self-consistent sequence of steps leading to a desired result, where a “step” refers to a manipulation of physical quantities and/or logic states which may, though need not necessarily, take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It is common usage to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. These and similar terms may be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities and/or states.

A network may include a packet switched network. The communication devices may be capable of communicating with each other using a selected packet switched network communications protocol. One example communications protocol may include an Ethernet communications protocol which may be capable permitting communication using a Transmission Control Protocol/Internet Protocol (TCP/IP). The Ethernet protocol may comply or be compatible with the Ethernet standard published by the Institute of Electrical and Electronics Engineers (IEEE) titled “IEEE 802.3 Standard”, published in December, 2008 and/or later versions of this standard. Alternatively or additionally, the communication devices may be capable of communicating with each other using an X.25 communications protocol. The X.25 communications protocol may comply or be compatible with a standard promulgated by the International Telecommunication Union-Telecommunication Standardization Sector (ITU-T). Alternatively or additionally, the communication devices may be capable of communicating with each other using a frame relay communications protocol. The frame relay communications protocol may comply or be compatible with a standard promulgated by Consultative Committee for International Telegraph and Telephone (CCITT) and/or the American National Standards Institute (ANSI). Alternatively or additionally, the transceivers may be capable of communicating with each other using an Asynchronous Transfer Mode (ATM) communications protocol. The ATM communications protocol may comply or be compatible with an ATM standard published by the ATM Forum titled “ATM-MPLS Network Interworking 2.0” published August 2001, and/or later versions of this standard. Of course, different and/or after-developed connection-oriented network communication protocols are equally contemplated herein.

Unless specifically stated otherwise as apparent from the foregoing disclosure, it is appreciated that, throughout the foregoing disclosure, discussions using terms such as “processing,” “computing,” “calculating,” “determining,” “displaying,” or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

One or more components may be referred to herein as “configured to,” “configurable to,” “operable/operative to,” “adapted/adaptable,” “able to,” “conformable/conformed to,” etc. Those skilled in the art will recognize that “configured to” can generally encompass active-state components and/or inactive-state components and/or standby-state components, unless context requires otherwise.

The terms “proximal” and “distal” are used herein with reference to a clinician manipulating the handle portion of the surgical instrument. The term “proximal” refers to the portion closest to the clinician and the term “distal” refers to the portion located away from the clinician. It will be further appreciated that, for convenience and clarity, spatial terms such as “vertical,” “horizontal,” “up,” and “down” may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute.

Those skilled in the art will recognize that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to claims containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations.

In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and

75

C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that typically a disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms unless context dictates otherwise. For example, the phrase “A or B” will be typically understood to include the possibilities of “A” or “B” or “A and B.”

With respect to the appended claims, those skilled in the art will appreciate that recited operations therein may generally be performed in any order. Also, although various operational flow diagrams are presented in a sequence(s), it should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently. Examples of such alternate orderings may include overlapping, interleaved, interrupted, reordered, incremental, preparatory, supplemental, simultaneous, reverse, or other variant orderings, unless context dictates otherwise. Furthermore, terms like “responsive to,” “related to,” or other past-tense adjectives are generally not intended to exclude such variants, unless context dictates otherwise.

It is worthy to note that any reference to “one aspect,” “an aspect,” “an exemplification,” “one exemplification,” and the like means that a particular feature, structure, or characteristic described in connection with the aspect is included in at least one aspect. Thus, appearances of the phrases “in one aspect,” “in an aspect,” “in an exemplification,” and “in one exemplification” in various places throughout the specification are not necessarily all referring to the same aspect. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner in one or more aspects.

Any patent application, patent, non-patent publication, or other disclosure material referred to in this specification and/or listed in any Application Data Sheet is incorporated by reference herein, to the extent that the incorporated materials is not inconsistent herewith. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

In summary, numerous benefits have been described which result from employing the concepts described herein. The foregoing description of the one or more forms has been presented for purposes of illustration and description. It is not intended to be exhaustive or limiting to the precise form disclosed. Modifications or variations are possible in light of the above teachings. The one or more forms were chosen and described in order to illustrate principles and practical application to thereby enable one of ordinary skill in the art to utilize the various forms and with various modifications as are suited to the particular use contemplated. It is intended that the claims submitted herewith define the overall scope.

76

Various aspects of the subject matter described herein are set out in the following numbered examples:

## Example 1

A method of delivering energy to an ultrasonic device, the ultrasonic device comprising an electromechanical ultrasonic system defined by a predetermined resonant frequency, the electromechanical ultrasonic system further comprising an ultrasonic transducer coupled to an ultrasonic blade, the method comprising:

sensing, by a processor or control circuit, a vessel type in contact with the ultrasonic blade coupled to the ultrasonic transducer;

determining, by the processor or control circuit, that the vessel type is either a vein or an artery; and

delivering, by the processor or control circuit, power to the ultrasonic transducer based on the vessel type.

## Example 2

The method of Example 1, further comprising:

applying power to the ultrasonic transducer at a power level P for a period T based on the identified vessel, wherein the power level P is different from a nominal power level P<sub>n</sub> and the period T is different from a nominal period T<sub>n</sub>.

## Example 3

The method of Example 2, wherein applying power to the ultrasonic transducer at a power level P for a period T comprises applying power to the ultrasonic transducer at a power level P that is lower than the nominal power level P<sub>n</sub> for a period T that is longer than the nominal period T<sub>n</sub> when the identified vessel is a vein.

## Example 4

The method of Example 2, wherein applying power to the ultrasonic transducer at a power level P for a period T comprises applying power to the ultrasonic transducer at a power level P that is greater than the nominal power level P<sub>n</sub> for a period T that is shorter than the nominal period T<sub>n</sub> when the identified vessel is an artery.

## Example 5

The method of any one or more of Examples 1 through 4, wherein determining, by the processor or control circuit, that the vessel type is either a vein or an artery comprises:

measuring, by the processor or control circuit, a complex impedance of the ultrasonic transducer, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)};$$

receiving, by the processor or control circuit, a complex impedance measurement data point;

comparing, by the processor or control circuit, the complex impedance measurement data point to a data point in a reference complex impedance characteristic pattern;

classifying, by the processor or control circuit, the complex impedance measurement data point based on a result of the comparison analysis; and

77

assigning, by the processor or control circuit, the vessel type based on the result of the comparison analysis.

Example 6

The method of any one or more of Examples 1 through 4, wherein determining, by the processor or control circuit, that the vessel type is either a vein or an artery comprises:

applying, by a drive circuit, a drive signal to the ultrasonic transducer, wherein the drive signal is a periodic signal defined by a magnitude and frequency;

sweeping, by a processor or control circuit, the frequency of the drive signal from below resonance to above resonance of the electromechanical ultrasonic system;

measuring and recording, by the processor or control circuit, impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$ ;

comparing, by the processor or control circuit, measured impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$  to reference impedance/admittance circle variables  $R_{ref}$ ,  $G_{ref}$ ,  $X_{ref}$ , and  $B_{ref}$ ; and

determining, by the processor or control circuit, the vessel type based on the result of the comparison analysis.

Example 7

A method of applying energy to an ultrasonic device, the ultrasonic device comprising an electromechanical ultrasonic system defined by a predetermined resonant frequency, the electromechanical ultrasonic system comprising an ultrasonic transducer coupled to an ultrasonic blade, the method comprising:

sensing, by the processor or control circuit, a vessel type in contact with an ultrasonic blade coupled to an ultrasonic transducer;

determining, by the processor or control circuit, that the vessel type is either a vein or an artery; and

applying, by the processor or control circuit, power to the ultrasonic transducer based on the vessel type.

Example 8

The method of Example 7, further comprising:

applying, by the processor or control circuit, a power level to achieve a targeted ultrasonic blade temperature for a vein when the identified vessel is a vein; and

receiving a feedback control, by the processor or control circuit, to maintain the targeted ultrasonic blade temperature for a vein.

Example 9

The method of Example 7, comprising:

applying, by the processor or control circuit, a power level to achieve a targeted ultrasonic blade temperature for an artery when the identified vessel is an artery; and

receiving a feedback control, by the processor or control circuit, to maintain the targeted ultrasonic blade temperature for an artery.

Example 10

The method of any one or more of Examples 7 through 9, wherein determining, by the processor or control circuit, that the vessel type is either a vein or an artery comprises:

78

measuring, by the processor or control circuit, a complex impedance of the ultrasonic transducer, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)}$$

receiving, by the processor or control circuit, a complex impedance measurement data point;

comparing, by the processor or control circuit, the complex impedance measurement data point to a data point in a reference complex impedance characteristic pattern;

classifying, by the processor or control circuit, the complex impedance measurement data point based on a result of the comparison analysis; and

assigning, by the processor or control circuit, the vessel type based on the result of the comparison analysis.

Example 11

The method of any one or more of Examples 7 through 9, wherein determining, by the processor or control circuit, that the vessel type is either a vein or an artery comprises:

applying, by a drive circuit, a drive signal to the ultrasonic transducer, wherein the drive signal is a periodic signal defined by a magnitude and frequency;

sweeping, by a processor or control circuit, the frequency of the drive signal from below resonance to above resonance of the electromechanical ultrasonic system;

measuring and recording, by the processor or control circuit, impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$ ;

comparing, by the processor or control circuit, measured impedance/admittance circle variables  $R_e$ ,  $G_e$ ,  $X_e$ , and  $B_e$  to reference impedance/admittance circle variables  $R_{ref}$ ,  $G_{ref}$ ,  $X_{ref}$ , and  $B_{ref}$ ; and

determining, by the processor or control circuit, the vessel type based on the result of the comparison analysis.

Example 12

An ultrasonic surgical instrument comprising: an ultrasonic electromechanical system comprising an ultrasonic transducer coupled to an ultrasonic blade via an ultrasonic waveguide; and

a generator configured to supply power to the ultrasonic transducer, wherein the generator comprises a control circuit configured to:

sense a vessel type in contact with the ultrasonic blade coupled to the ultrasonic transducer;

determine that the vessel type is either a vein or an artery; and

deliver power to the ultrasonic transducer based on the vessel type.

Example 13

The ultrasonic surgical instrument of Example 12, wherein the generator comprises a control circuit further configured to apply power to the ultrasonic transducer at a power level P for a period T based on the identified vessel, wherein the power level P is different from a nominal power level Pn and the period T is different from a nominal period Tn.

79

Example 14

The ultrasonic surgical instrument of Example 13, wherein the power level P is lower than the nominal power level P<sub>n</sub> for a period T that is longer than the nominal period T<sub>n</sub> when the identified vessel is a vein.

Example 15

The ultrasonic surgical instrument of Example 13, wherein the power level P that is greater than the nominal power level P<sub>n</sub> for a period T that is shorter than the nominal period T<sub>n</sub> when the identified vessel is an artery.

Example 16

The ultrasonic surgical instrument of any one or more of Examples 12 through 15, wherein the generator comprises a control circuit further configured to:

measure a complex impedance of the ultrasonic transducer, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)}$$

receive a complex impedance measurement data point; compare the complex impedance measurement data point to a data point in a reference complex impedance characteristic pattern;

classify the complex impedance measurement data point based on a result of the comparison analysis; and

assign the vessel type based on the result of the comparison analysis.

Example 17

The ultrasonic surgical instrument of any one or more of Examples 12 through 16, wherein the generator comprises a control circuit further configured to:

cause a drive circuit to apply a drive signal to the ultrasonic transducer, wherein the drive signal is a periodic signal defined by a magnitude and frequency;

sweep the frequency of the drive signal from below resonance to above resonance of the electromechanical ultrasonic system;

measure and record impedance/admittance circle variables R<sub>e</sub>, G<sub>e</sub>, X<sub>e</sub>, and B<sub>e</sub>;

comparing measured impedance/admittance circle variables R<sub>e</sub>, G<sub>e</sub>, X<sub>e</sub>, and B<sub>e</sub> to reference impedance/admittance circle variables R<sub>ref</sub>, G<sub>ref</sub>, X<sub>ref</sub>, and B<sub>ref</sub>; and

determining the vessel type based on the result of the comparison analysis.

Example 18

An ultrasonic surgical instrument comprising: an ultrasonic electromechanical system comprising an ultrasonic transducer coupled to an ultrasonic blade via an ultrasonic waveguide; and

a generator configured to supply power to the ultrasonic transducer, wherein the generator comprises a control circuit configured to:

sense a vessel type in contact with an ultrasonic blade coupled to an ultrasonic transducer;

80

determine that the vessel type is either a vein or an artery; and apply power to the ultrasonic transducer based on the vessel type.

Example 19

The ultrasonic surgical instrument of Example 18, wherein the generator comprises a control circuit further configured to:

apply a power level to achieve a targeted ultrasonic blade temperature for a vein when the identified vessel is a vein; and

receive a feedback control to maintain the targeted ultrasonic blade temperature for a vein.

Example 20

The ultrasonic surgical instrument of Example 18, wherein the generator comprises a control circuit further configured to:

apply a power level to achieve a targeted ultrasonic blade temperature for an artery when the identified vessel is an artery; and

receive a feedback control to maintain the targeted ultrasonic blade temperature for an artery.

Example 21

The ultrasonic surgical instrument of any one or more of Examples 18 through 20, wherein the generator comprises a control circuit further configured to:

measure a complex impedance of the ultrasonic transducer, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)}$$

receive a complex impedance measurement data point; compare the complex impedance measurement data point to a data point in a reference complex impedance characteristic pattern;

classify the complex impedance measurement data point based on a result of the comparison analysis; and

assign the vessel type based on the result of the comparison analysis.

Example 22

The ultrasonic surgical instrument of any one or more of Examples 18 through 21, wherein the generator comprises a control circuit further configured to:

cause a drive circuit to apply a drive signal to the ultrasonic transducer, wherein the drive signal is a periodic signal defined by a magnitude and frequency;

sweep the frequency of the drive signal from below resonance to above resonance of the electromechanical ultrasonic system;

measure and record impedance/admittance circle variables R<sub>e</sub>, G<sub>e</sub>, X<sub>e</sub>, and B<sub>e</sub>;

compare measured impedance/admittance circle variables R<sub>e</sub>, G<sub>e</sub>, X<sub>e</sub>, and B<sub>e</sub> to reference impedance/admittance circle variables R<sub>ref</sub>, G<sub>ref</sub>, X<sub>ref</sub>, and B<sub>ref</sub>; and determine, the vessel type based on the result of the comparison analysis.

81

The invention claimed is:

1. A method of delivering energy to an ultrasonic device, the ultrasonic device comprising an electromechanical ultrasonic system defined by a predetermined resonant frequency, the electromechanical ultrasonic system further comprising an ultrasonic transducer coupled to an ultrasonic blade, the method comprising:

measuring, by a control circuit, a complex impedance of the ultrasonic transducer at a frequency  $f$ , wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)};$$

receiving, by the control circuit, a complex impedance measurement data point comprising an impedance magnitude  $|Z|$ , an impedance phase  $\varphi$ , and the frequency  $f$ ;

calculating, by the control circuit, a Euclidean distance between the complex impedance measurement data point and a data point in a reference complex impedance characteristic pattern;

classifying, by the control circuit, the complex impedance measurement data point based on the Euclidean distance;

assigning, by the control circuit, a vessel type in contact with the ultrasonic blade coupled to the ultrasonic transducer based on the Euclidean distance, wherein the vessel type is either a vein or an artery;

delivering, by the control circuit, power to the ultrasonic transducer based on the vessel type; and

applying power, by the control circuit, to the ultrasonic transducer at a power level  $P$  for a period  $T$  based on the assigned vessel type, wherein the power level  $P$  is different from a nominal power level  $P_n$  and the period  $T$  is different from a nominal period  $T_n$ ,

thereby sealing and cutting a vessel having the vessel type.

2. The method of claim 1, wherein applying power to the ultrasonic transducer at a power level  $P$  for a period  $T$  comprises applying power to the ultrasonic transducer at a power level  $P$  that is lower than the nominal power level  $P_n$  for a period  $T$  that is longer than the nominal period  $T_n$  when the assigned vessel type is a vein.

3. The method of claim 1, wherein applying power to the ultrasonic transducer at a power level  $P$  for a period  $T$  comprises applying power to the ultrasonic transducer at a power level  $P$  that is greater than the nominal power level  $P_n$  for a period  $T$  that is shorter than the nominal period  $T_n$  when the assigned vessel type is an artery.

4. A method of applying energy to an ultrasonic device, the ultrasonic device comprising an electromechanical ultrasonic system defined by a predetermined resonant frequency, the electromechanical ultrasonic system comprising an ultrasonic transducer coupled to an ultrasonic blade, the method comprising:

measuring, by a control circuit, a complex impedance of the ultrasonic transducer at a frequency  $f$ , wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)};$$

82

receiving, by the control circuit, a complex impedance measurement data point comprising an impedance magnitude  $|Z|$ , an impedance phase  $\varphi$ , and the frequency  $f$ ;

calculating, by the control circuit, a Euclidean distance between the complex impedance measurement data point and a data point in a reference complex impedance characteristic pattern;

classifying, by the control circuit, the complex impedance measurement data point based on the Euclidean distance;

assigning, by the control circuit, a vessel type in contact with the ultrasonic blade coupled to the ultrasonic transducer based on the Euclidean distance, wherein the vessel type is either a vein or an artery; and

applying, by the control circuit, power to the ultrasonic transducer at a power level  $P$  for a period  $T$  based on the assigned vessel type, wherein the power level  $P$  is different from a nominal power level  $P_n$  and the period  $T$  is different from a nominal period  $T_n$  based on the vessel type,

thereby sealing and cutting a vessel having the vessel type.

5. The method of claim 4, further comprising: applying, by the control circuit, a power level to achieve a targeted ultrasonic blade temperature for a vein when the assigned vessel type is a vein; and

receiving a feedback control, by the control circuit, to maintain the targeted ultrasonic blade temperature for the vein.

6. The method of claim 4, comprising: applying, by the control circuit, a power level to achieve a targeted ultrasonic blade temperature for an artery when the assigned vessel type is an artery; and receiving a feedback control, by the control circuit, to maintain the targeted ultrasonic blade temperature for the artery.

7. An ultrasonic surgical instrument comprising: an ultrasonic electromechanical system comprising an ultrasonic transducer coupled to an ultrasonic blade via an ultrasonic waveguide; and

a generator configured to supply power to the ultrasonic transducer, wherein the generator comprises a control circuit configured to:

measure a complex impedance of the ultrasonic transducer at a frequency  $f$ , wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)};$$

receive a complex impedance measurement data point comprising an impedance magnitude  $|Z|$ , an impedance phase  $\varphi$ , and the frequency  $f$ ;

calculate a Euclidean distance between the complex impedance measurement data point and a data point in a reference complex impedance characteristic pattern;

classify the complex impedance measurement data point based on the Euclidean distance;

assign a vessel type in contact with the ultrasonic blade coupled to the ultrasonic transducer based on the Euclidean distance, wherein

the vessel type is either a vein or an artery;

83

deliver power to the ultrasonic transducer based on the vessel type; and  
 apply power to the ultrasonic transducer at a power level P for a period T based on the assigned vessel type, wherein the power level P is different from a nominal power level P<sub>n</sub> and the period T is different from a nominal period T<sub>n</sub>, to thereby seal and cut a vessel having the vessel type.

8. The ultrasonic surgical instrument of claim 7, wherein the power level P is lower than the nominal power level P<sub>n</sub> for a period T that is longer than the nominal period T<sub>n</sub> when the assigned vessel type is a vein.

9. The ultrasonic surgical instrument of claim 7, wherein the power level P that is greater than the nominal power level P<sub>n</sub> for a period T that is shorter than the nominal period T<sub>n</sub> when the assigned vessel type is an artery.

10. An ultrasonic surgical instrument comprising:  
 an ultrasonic electromechanical system comprising an ultrasonic transducer coupled to an ultrasonic blade via an ultrasonic waveguide; and  
 a generator configured to supply power to the ultrasonic transducer,  
 wherein the generator comprises a control circuit configured to:  
 measure a complex impedance of the ultrasonic transducer at a frequency f, wherein the complex impedance is defined as

$$Z_g(t) = \frac{V_g(t)}{I_g(t)}$$

receive a complex impedance measurement data point comprising an impedance magnitude |Z|, an impedance phase φ, and the frequency f;

84

calculate a Euclidean distance between the complex impedance measurement data point and a data point in a reference complex impedance characteristic pattern;

classify the complex impedance measurement data point based on the Euclidean distance;

assign a vessel type in contact with the ultrasonic blade coupled to the ultrasonic transducer based on the Euclidean distance, wherein

the vessel type is either a vein or an artery; and  
 apply power to the ultrasonic transducer at a power level P for a period T based on the assigned vessel type, wherein the power level P is different from a nominal power level P<sub>n</sub> and the period T is different from a nominal period T<sub>n</sub> based on the vessel type to thereby seal and cut a vessel having the vessel type.

11. The ultrasonic surgical instrument of claim 10, wherein the generator comprises a control circuit further configured to:

apply a power level to achieve a targeted ultrasonic blade temperature for a vein when the assigned vessel type is a vein; and

receive a feedback control to maintain the targeted ultrasonic blade temperature for the vein.

12. The ultrasonic surgical instrument of claim 10, wherein the generator comprises a control circuit further configured to:

apply a power level to achieve a targeted ultrasonic blade temperature for an artery when the assigned vessel type is an artery; and

receive a feedback control to maintain the targeted ultrasonic blade temperature for the artery.

\* \* \* \* \*