US 20110004825A1

(19) **United States**

(12) **Patent Application Publication**

Wallaert

(10) **Pub. No.: US 2011/0004825 A1**

(43) **Pub. Date: Jan. 6, 2011**

(54) **DISPLAY APPARATUS AND METHOD HAVING MULTIPLE DAY PROGRAMMING CAPABILITY FOR AN ENVIRONMENTAL CONTROL SYSTEM**

(75) Inventor: **Timothy E. Wallaert**, Wylie, TX (US)

Correspondence Address:
HITT GAINES P.C.
P.O. BOX 832570
RICHARDSON, TX 75083 (US)

(73) Assignee: **Lennox Industries, Incorporated**, Richardson, TX (US)

(21) Appl. No.: **12/885,084**

(22) Filed: **Sep. 17, 2010**

Related U.S. Application Data

(63) Continuation of application No. 12/197,078, filed on Aug. 22, 2008.


Publication Classification

(51) **Int. Cl.**
G06F 3/048 (2006.01)
G06F 3/01 (2006.01)

(52) **U.S. Cl.** **715/702**; 715/764

(57) **ABSTRACT**

A display apparatus for a control unit in an environmental control system; the display apparatus including: a display area presenting a plurality of first loci, a plurality of second loci and at least one third locus; each respective first locus of the plurality of first loci being responsive to pressure for effecting a respective response; each respective second locus of the plurality of second loci presenting information using a fixed segment data format; at least one third locus of the at least one third locus presenting information using a dot matrix data format; the display apparatus configured to allow multiple days to be programmed with a single button.





12
10
18
20_1
20_2
20_3
20_4
20_5
20_n
22_m
SAVE
22_6
EDIT NEXT
22_5
ENTER SLEEP
22_4
CLEAN RETURN
22_3
LEAVE
22_2
BACK WAKE
22_1
CANCEL EDIT
34
36_t
36_4
36_3
36_2
36_1
14
26_s
OPTIONS
26_2
SCHEDULE
26_1
HOME
SET AT °
HEAT
40_1
SET AT °
COOL
40_2
40_3
40_4
40_u
30
32
MON TUE WED THU FRI SAT SUN
MODE
HEAT COOL AUTO OFF EM HEAT
24_1
FAN
ON AUTO CIRC
24_2
SCHED
ON OFF
24_r
16

FIG. 1



12
10
20_1
20_2
20_3
20_4
18
26_s
OPTIONS
26_2
SCHEDULE
26_1
HOME
SET AT 68°
HEAT
SET AT 80°
COOL
40_1
40_2
30
40_4
72°
40_u
OUTDOOR TEMP 40° F
THU MAR 06 6:16AM
MODE
AUTO
FAN
AUTO
SCHED
ON
24_r
14
16

FIG. 2



12
10
20_1
20_2
20_3
20_4
20_5
20_n
18
SET AT
68°
HEAT
SET AT
80°
COOL
40_1
40_2
30
72°
HOLD SETTING UNTIL
10:50AM
OCT 10
OPTIONS
SCHEDULE
HOME
MODE
AUTO
FAN
AUTO
SCHED
ON
CANCEL
SAVE
22_m
22_5
22_3
22_1
14
16

FIG. 3



12
10
18
HOME
SCHEDULE
OPTIONS
26_2
SET AT
68°
HEAT
40_1
SET AT
80°
COOL
40_2
30
MON TUE WED THU FRI SAT SUN
WAKE PERIOD BEGINS
6:00AM
FAN
AUTO
EDIT
WAKE
LEAVE
RETURN
SLEEP
NEXT
22_1
22_2
22_3
22_4
22_5
22_6
14
16

FIG. 4



12
10
20_5
20_n
18
26_s
OPTIONS
SCHEDULE
HOME
30
REMINDERS
USER SETTINGS
ENTER
22_5
CLEAN
22_4
14
16

FIG. 5



12
10
20_5
20_n
18
26_s
OPTIONS
SCHEDULE
HOME
30
REPLACE MEDIA FILTER
DUE MON MAY 18 09
EDIT
22_6
14
BACK
22_2
16

FIG. 6



12
10
18
HOME
SCHEDULE
OPTIONS
30
ABC HTG AND A/C
555-555-1212
EDIT
22_6
BACK
22_2
14
16

FIG. 7



12
10
20_1
20_2
20_3
20_4
18
SET AT
68°
HEAT
SET AT
80°
COOL
40_1
40_2
30
OPTIONS
SCHEDULE
HOME
72°
OUTDOOR TEMP 40F
THU MAR 06 6:16AM
MODE
AUTO
FAN
AUTO
SCHED
ON
24_1
16
14

FIG. 8



12
10
20_1
20_2
20_3
20_4
20_5
20_n
18
SET AT 68° HEAT
SET AT 80° COOL
72°
30
HOLD SETTING UNTIL
OCT 10
10:50AM
SAVE
22_m
22_5
22_3
22_1
14
HOME
SCHEDULE
OPTIONS
MODE
AUTO
FAN
AUTO
SCHED
ON
CANCEL
24_1
16

FIG. 9



12
10
20_1
20_2
20_3
20_4
18
HOME
SCHEDULE
OPTIONS
SET AT 68°
HEAT
SET AT 80°
COOL
40_1
40_2
30
72°
OUTDOOR TEMP 40° F
THU MAR 06 6:16AM
MODE
AUTO
FAN
AUTO
SCHED
ON
24_1
24_2
24_r
16
14

FIG. 10



12
10
18
HOME
SCHEDULE
OPTIONS
SET AT
68°
HEAT
SET AT
80°
COOL
40 1
40 2
30
MON TUE WED THU FRI
WAKE PERIOD BEGINS
6:00AM
FAN
AUTO
EDIT
WAKE
LEAVE
RETURN
SLEEP
NEXT
22 1
22 2
22 3
22 4
22 5
22 6
14
16
24 2

FIG. 11



12
10
18
20_1
20_2
20_3
20_4
20_5
20_n
HOME
SCHEDULE
OPTIONS
SET AT
68°
HEAT
40_1
SET AT
80°
COOL
40_2
30
MON TUE WED THU FRI
WAKE PERIOD BEGINS
6:00AM
FAN
AUTO
24_2
16
CANCEL
WAKE
LEAVE
RETURN
SLEEP
NEXT
SAVE
22_1
22_2
22_3
22_4
22_5
22_6
22_m
14

FIG. 12



12
10
20_1
20_2
20_3
20_4
18
SET AT
68°
HEAT
SET AT
80°
COOL
40_1
40_2
30
OPTIONS
SCHEDULE
HOME
72°
OUTDOOR TEMP 40° F
THU MAR 06 6:16AM
14
MODE
AUTO
FAN
AUTO
SCHED
ON
24_1
24_2
24_r
16

FIG. 13



12
10
18
20_1
20_2
20_3
20_4
20_5
20_n
SAVE
22_m
SET AT
68
HEAT
SET AT
80
COOL
40_1
40_2
30
OPTIONS
SCHEDULE
HOME
72
HOLD SETTING UNTIL
10:50AM
OCT 10
22_5
14
22_3
MODE
AUTO
FAN
AUTO
SCHED
ON
CANCEL
22_1
24_1
24_2
24_r
16

FIG. 14



12
10
20_1
20_2
20_3
20_4
18
SET AT 68° HEAT
SET AT 80° COOL
OPTIONS
SCHEDULE
HOME
72°
30
OUTDOOR TEMP 40° F
THU MAR 06 6:16AM
MODE
AUTO
FAN
AUTO
SCHED
ON
14
16

FIG. 15



12
10
20_5
20_n
18
HOME
SCHEDULE
OPTIONS
30
USER SETTINGS
INSTALLER SETTINGS
ENTER
22_5
CLEAN
22_4
14
16

FIG. 16



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
30
HUMIDITY SETTING
BACKLIGHT SETTING
ENTER
22_5
14
BACK
22_2
16

FIG. 17



12
10
20_5
20_n
SAVE
22_m
18
OPTIONS
SCHEDULE
HOME
30
39%
HUM SETPOINT
DEFAULT (45%)
14
CANCEL
22_1
16

FIG. 18



12
10
20_5
20_n
SAVE
22_m
18
OPTIONS
SCHEDULE
HOME
30
HUM SETPOINT
DEFAULT (45%)
35%
14
CANCEL
22_1
16

FIG. 19



12
10
18
HOME
SCHEDULE
OPTIONS
SET AT 68° HEAT
SET AT 80° COOL
72°
30
OUTDOOR TEMP 40° F
THU MAR 06 6:16AM
MODE
AUTO
FAN
AUTO
SCHED
ON
14
16

FIG. 20



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
30
REMINDERS
USER SETTINGS
ENTER
22_5
CLEAN
22_4
14
16

FIG. 21



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
30
REPLACE MEDIA FILTER
DUE MON MAY 18 09
EDIT
22_6
14
BACK
22_2
16

FIG. 22



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
30
CALENDAR TIME
RUN TIME
ENTER
22_5
14
CANCEL
22_1
16

FIG. 23



12
10
18
HOME
SCHEDULE
OPTIONS
30
REPLACE MEDIA FILTER
RESET (15 MON) EDIT
CANCEL
22_1
22_3
22_5
14
16

FIG. 24



12
10
20_5
20_n
SAVE
22_m
18
OPTIONS
SCHEDULE
HOME
30
REPLACE MEDIA FILTER
15 MON
OTHER
14
22_3
CANCEL
22_1
16

FIG. 25



12
10
18
HOME
SCHEDULE
OPTIONS
SET AT °
HEAT
SET AT °
COOL
30
REPLACE MEDIA FILTER
RESET
REMIND
MODE
AUTO
FAN
AUTO
SCHED
ON
22 5
22 2
14
16

FIG. 26



12
10
18
HOME
SCHEDULE
OPTIONS
SET AT 68° HEAT
SET AT 80° COOL
72°
30
OUTDOOR TEMP 40° F
THU MAR 06 6:16AM
MODE
AUTO
FAN
AUTO
SCHED
ON
14
16

FIG. 27



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
30
REMINDERS
USER SETTINGS
ENTER
22_5
CLEAN
22_4
14
16

FIG. 28




FIG. 29



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
26_1
30
REMINDERS
USER SETTINGS
ENTER
22_5
CLEAN
22_4
14
16

FIG. 30



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
26_1
30
USER SETTINGS
INSTALLER SETTINGS
ENTER
22_5
CLEAN
22_4
14
16

FIG. 31



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
26_1
30
DATE/TIME
F OR C
ENTER
22_5
BACK
22_2
14
16

FIG. 32



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
26_1
30
DISPLAY INFO
FAN CIRCULATE
ENTER
22_5
BACK
22_2
14
16

FIG. 33



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
26_1
30
DISPLAY INFO
OUTDOOR TEMP
ENTER
22_5
14
BACK
22_2
16

FIG. 34



12
10
20_5
20_n
SAVE
22_m
18
OPTIONS
SCHEDULE
HOME
26_1
30
DISPLAY INFO
DEFAULT (OFF)
ON
14
CANCEL
22_1
16

FIG. 35



12
10
20_1
20_2
20_3
20_4
18
SET AT 78° HEAT
SET AT 80° COOL
30
OUTDOOR TEMP 40° F
THU MAR 06 6:16AM
72°
OPTIONS
SCHEDULE
HOME
MODE
AUTO
FAN
AUTO
SCHED
ON
14
16

FIG. 36



12
10
18
HOME
SCHEDULE
OPTIONS
SET AT 78° HEAT
SET AT 80° COOL
72°
30
HEATING
THU MAR 06 6:16AM
MODE
AUTO
FAN
AUTO
SCHED
ON
14
16

FIG. 37



12
10
18
HOME
SCHEDULE
OPTIONS
SET AT 78° HEAT
SET AT 80° COOL
72°
30
INDOOR RH 45%
THU MAR 06 6:16AM
MODE
AUTO
FAN
AUTO
SCHED
ON
14
16

FIG. 38



12
10
18
HOME
SCHEDULE
OPTIONS
MODE
AUTO
FAN
AUTO
SCHED
ON
72°
SET AT 68° HEAT
SET AT 80° COOL
30
OUTDOOR TEMP 40° F
THU MAR 06 6:16AM
14
16

FIG. 39



12
10
18
HOME
SCHEDULE
OPTIONS
30
INSTALLER SETTINGS
CLEAN
ENTER
22 4
22 5
14
16

FIG. 40



12
10
18
HOME
SCHEDULE
OPTIONS
30
MUST BE SET BY
QUALIFIED PERSON
ENTER
22_5
14
CANCEL
22_1
16

FIG. 41



12
10
18
OPTIONS
SCHEDULE
HOME
30
CUSTOM REMINDER 1
CUSTOM REMINDER 2
ENTER
22_5
14
BACK
22_2
16

FIG. 42



12
10
18
OPTIONS
SCHEDULE
HOME
30
CUSTOM REMINDER 1
MY BDAY REMINDER
EDIT
22_6
BACK
22_2
14
16

FIG. 43



12
10
18
HOME
SCHEDULE
OPTIONS
30
CUSTOM REMINDER 1
MY BDAY REMINDER
SAVE
NEXT
BACK
CANCEL
22m
226
222
221
14
16

FIG. 44



12
10
18
HOME
SCHEDULE
OPTIONS
SET AT 68° HEAT
SET AT 80° COOL
72°
30
OUTDOOR TEMP 40° F
THU MAR 06 6:16AM
MODE
AUTO
FAN
AUTO
SCHED
ON
14
16

FIG. 45



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
30
SYSTEM SETUP
OUTDOOR SENSOR
ENTER
22_5
14
BACK
22_2
16

FIG. 46



12
10
20_5
20_n
SAVE
22_m
18
OPTIONS
SCHEDULE
HOME
30
NON HEAT PUMP
ELECTRIC
14
CANCEL
22_1
16

FIG. 47



12
10
20_5
20_n
SAVE
22_m
18
OPTIONS
SCHEDULE
HOME
30
COMPRESSOR STAGES
1
14
CANCEL
22_1
16

FIG. 48



12
10
20_5
20_n
SAVE
22_m
18
OPTIONS
SCHEDULE
HOME
30
INDOOR HEAT STAGES
1
14
CANCEL
22_1
16

FIG. 49



12
10
20_5
20_n
18
OPTIONS
SCHEDULE
HOME
30
STG 1 DIFF
CUSTOM REMINDER 1
ENTER
22_5
14
BACK
22_2
16

FIG. 50



100
102
START
104
PROVIDE DISPLAY AREA
106
PRESENT FIRST LOCI IN DISPLAY AREA
108
PRESENT SECOND LOCI IN DISPLAY AREA
110
PRESENT AT LEAST ONE THIRD LOCUS IN DISPLAY AREA
112
CONFIGURE FIRST LOCI FOR RESPONSE TO PRESSURE FOR EFFECTING AN INPUT
114
CONFIGURE SECOND LOCI FOR PRESENTING INFO USING FIXED SEGMENT DATA FORMAT
116
CONFIGURE THIRD LOCUS(I) FOR PRESENTING INFO USING DOT MATRIX DATA FORMAT
118
END

FIG. 51

DISPLAY APPARATUS AND METHOD HAVING MULTIPLE DAY PROGRAMMING CAPABILITY FOR AN ENVIRONMENTAL CONTROL SYSTEM

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is a continuation of U.S. patent application Ser. No. 12/197,078, filed by Thorson, et al., on Aug. 22, 2008, entitled "Display Apparatus and Method for a Control Unit for an Environmental Control System," commonly assigned with this application and incorporated herein by reference. This application is also related to U.S. patent application Ser. No. 12/197,127, filed by Mirza on Aug. 22, 2008, entitled "Display Apparatus and Method for Entering a Reminder in a Control Unit for an Environmental Control System," commonly assigned herewith and incorporated herein by reference.

TECHNICAL FIELD

[0002] This application is directed to heating ventilating air conditioning (HVAC) system controller devices, and especially to a display apparatus and method having multiple day programming capability for an environmental control system.

BACKGROUND

[0003] HVAC systems have become more complex in recent years. Control units for use with HVAC systems have not been sufficiently detailed and varied in the information provided for a user to permit efficient use of features of the HVAC system. Complexity in programming and displaying information has caused some confusion to the extent that some users do not employ all of the features of an HVAC system, or find that the employment of some features is cumbersome.

[0004] Some attempts at facilitating the interface between a user and an HVAC control unit have involved limiting flexibility in the programming or display capabilities of the control unit. Such oversimplification of a control unit may also limit employment of features or capabilities of a HVAC system.

SUMMARY

[0005] One aspect provides a display apparatus for a control unit in an environmental control system. In one embodiment, the apparatus includes: a display area presenting a plurality of first loci, a plurality of second loci and at least one third locus; each respective first locus of the plurality of first loci being responsive to pressure for effecting a respective response; each respective second locus of the plurality of second loci presenting information using a fixed segment data format; at least one third locus of the at least one third locus presenting information using a dot matrix data format; the display apparatus configured to allow multiple days to be programmed with a single button.

[0006] Another aspect provides a touchscreen input apparatus for an environmental control system. In one embodiment, the apparatus includes: a display area having a plurality of touch-sensitive input loci, at least one first display locus and at least one second display locus; the at least one first display locus presenting information using a fixed segment data format; the at least one second display locus presenting information using a dot matrix data format; the touchscreen input apparatus configured to allow multiple days to be programmed with a single button.

[0007] Yet another aspect provides a method for entering input to an environmental control system. In one embodiment, the method includes: (a) providing a display area; (b) in no particular order: (1) presenting a plurality of first loci in the display area; (2) presenting a plurality of second loci in the display area; and (3) presenting at least one third locus in the display area; and (c) in no particular order: (1) configuring each respective first locus of the plurality of first loci for being responsive to pressure for effecting a respective the input; (2) configuring each respective second locus of the plurality of second loci presenting information using a fixed segment data format; (3) configuring at least one third locus of the at least one third locus presenting information using a dot matrix data format; and (4) allowing multiple days to be programmed with a single button.

BRIEF DESCRIPTION

[0008] Reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

[0009] FIG. **1** is a plan view of a thermostat display configured according to the teachings of the present invention;

[0010] FIG. **2** is a first view of the display illustrating features associated with the HOME Tab;

[0011] FIG. **3** is a second view of the display illustrating features associated with the HOME Tab;

[0012] FIG. **4** is a view of the display illustrating features associated with the SCHEDULE Tab;

[0013] FIG. **5** is a first view of the display illustrating features associated with the OPTIONS Tab;

[0014] FIG. **6** is a second view of the display illustrating features associated with the OPTIONS Tab;

[0015] FIG. **7** is a third view of the display illustrating features associated with the OPTIONS Tab;

[0016] FIG. **8** is a first view of the display illustrating programming steps associated with Mode of operation;

[0017] FIG. **9** is a second view of the display illustrating programming steps associated with Mode of operation;

[0018] FIG. **10** is a first view of the display illustrating programming steps associated with operation Schedule;

[0019] FIG. **11** is a second view of the display illustrating programming steps associated with operation Schedule;

[0020] FIG. **12** is a third view of the display illustrating programming steps associated with operation Schedule;

[0021] FIG. **13** is a first view of the display illustrating programming steps associated with Temporary/Vacation Hold;

[0022] FIG. **14** is a second view of the display illustrating programming steps associated with Temporary/Vacation Hold;

[0023] FIG. **15** is a first view of the display illustrating programming steps associated with Humidity Settings;

[0024] FIG. **16** is a second view of the display illustrating programming steps associated with Humidity Settings;

[0025] FIG. **17** is a third view of the display illustrating programming steps associated with Humidity Settings;

[0026] FIG. **18** is a fourth view of the display illustrating programming steps associated with Humidity Settings;

[0027] FIG. **19** is a fifth view of the display illustrating programming steps associated with Humidity Settings;

[0028] FIG. **20** is a first view of the display illustrating programming steps associated with Setting Service Reminders;

[0029] FIG. **21** is a second view of the display illustrating programming steps associated with Setting Service Reminders;

[0030] FIG. **22** is a third view of the display illustrating programming steps associated with Setting Service Reminders;

[0031] FIG. **23** is a fourth view of the display illustrating programming steps associated with Setting Service Reminders;

[0032] FIG. **24** is a fifth view of the display illustrating programming steps associated with Setting Service Reminders;

[0033] FIG. **25** is a sixth view of the display illustrating programming steps associated with Setting Service Reminders;

[0034] FIG. **26** is a seventh view of the display illustrating programming steps associated with Setting Service Reminders;

[0035] FIG. **27** is a first view of the display illustrating programming steps associated with the Clean Screen Feature;

[0036] FIG. **28** is a second view of the display illustrating programming steps associated with the Clean Screen Feature;

[0037] FIG. **29** is a third view of the display illustrating programming steps associated with the Clean Screen Feature;

[0038] FIG. **30** is a first view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters;

[0039] FIG. **31** is a second view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters;

[0040] FIG. **32** is a third view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters;

[0041] FIG. **33** is a fourth view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters;

[0042] FIG. **34** is a fifth view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters;

[0043] FIG. **35** is a sixth view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters;

[0044] FIG. **36** is a first view of the display illustrating toggling among displays of certain parameters;

[0045] FIG. **37** is a second view of the display illustrating toggling among displays of certain parameters;

[0046] FIG. **38** is a third view of the display illustrating toggling among displays of certain parameters;

[0047] FIG. **39** is a first view of the display illustrating programming steps associated with displays of custom reminders;

[0048] FIG. **40** is a second view of the display illustrating programming steps associated with displays of custom reminders;

[0049] FIG. **41** is a third view of the display illustrating programming steps associated with displays of custom reminders;

[0050] FIG. **42** is a fourth view of the display illustrating programming steps associated with displays of custom reminders;

[0051] FIG. **43** is a fifth view of the display illustrating programming steps associated with displays of custom reminders;

[0052] FIG. **44** is a sixth view of the display illustrating programming steps associated with displays of custom reminders;

[0053] FIG. **45** is a first view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system;

[0054] FIG. **46** is a second view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system;

[0055] FIG. **47** is a third view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system;

[0056] FIG. **48** is a fourth view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system;

[0057] FIG. **49** is a fifth view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system;

[0058] FIG. **50** is a sixth view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system; and

[0059] FIG. **51** is a flow chart illustrating the method of the present invention.

DETAILED DESCRIPTION

[0060] FIG. **1** is a plan view of a thermostat display configured according to the teachings of the present invention. In FIG. **1**, a thermostat display **10** may be appropriate for use with a control unit in an environmental control system such as, by way of example and not by way of limitation, a Heating Ventilating Air Conditioning (HVAC) system. Display **10** may include a plurality of touch responsive loci configured to respond to pressure applied to respective touch responsive loci for effecting respective responses.

[0061] In the exemplary display **10** illustrated FIG. **1**, touch responsive loci **12** may be generally indicated by delineated directional areas $\mathbf{20}_1$, $\mathbf{20}_2$, $\mathbf{20}_3$, $\mathbf{20}_4$, $\mathbf{20}_5$, $\mathbf{20}_n$ annotated with directional symbols indicating alteration or adjustment of a parameter up or down. Actuation may be carried out in any known manner, preferably by pressing or depressing an individual locus $\mathbf{20}_n$ in the manner of a touch screen input device known by those skilled in the art of design of control devices for HVAC systems. The indicator "n" is employed to signify that there can be any number of delineated directional areas in display **10**. The inclusion of six delineated directional areas $\mathbf{20}_1$, $\mathbf{20}_2$, $\mathbf{20}_3$, $\mathbf{20}_4$, $\mathbf{20}_5$, $\mathbf{20}_n$, in FIG. **1** is illustrative only and does not constitute any limitation regarding the number of delineated directional areas that may be included in the display of the present invention.

[0062] Display **10** may include additional touch responsive first loci **14** generally indicated by functional action areas $\mathbf{22}_1$, $\mathbf{22}_2$, $\mathbf{22}_3$, $\mathbf{22}_4$, $\mathbf{22}_5$, $\mathbf{22}_6$, $\mathbf{22}_m$ annotated to indicate specified actions or functions that may be effected by actuating a respective area. Action area $\mathbf{22}_1$ permits effecting a "CANCEL" or "EDIT" action or function. Action area $\mathbf{22}_2$ permits effecting a "BACK" or "WAKE" action or function. Action area $\mathbf{22}_3$ permits effecting a "LEAVE" action or function. Action area $\mathbf{22}_4$ permits effecting a "CLEAN" or "RETURN" action or function. Action area $\mathbf{22}_5$ permits effecting an "ENTER" or "SLEEP" action or function. Action area $\mathbf{22}_6$ permits effecting an "EDIT" or "NEXT" action or function.

Action area 22_m permits effecting a "SAVE" action or function. The indicator "m" is employed to signify that there can be any number of functional action areas in display **10**. The inclusion of seven functional action areas 22_1, 22_2, 22_3, 22_4, 22_5, 22_6, 22_m in FIG. **1** is illustrative only and does not constitute any limitation regarding the number of functional action areas that may be included in the display of the present invention.

[0063] Display **10** may include additional touch responsive loci **16** generally indicated by mode controlling areas 24_1, 24_2, 24_r annotated to indicate specified modes or controls that may be effected by actuating a respective area. Mode controlling area 24_1 permits effecting a "HEAT" mode, a "COOL" mode, an "AUTO" mode, an "OFF" mode or an "EM HEAT" (emergency heat) mode. Mode controlling area 24_2 permits effecting a fan mode of "ON", "AUTO" or "CIRC" (circulate). Mode controlling area 24_r permits effecting a schedule mode of "ON" or "OFF". Actuation may be carried out in any known manner, preferably by pressing or depressing an individual locus 24_2 in the manner of a touch screen input device known by those skilled in the art of design of control devices for HVAC systems. The indicator "r" is employed to signify that there can be any number of mode controlling areas in display **10**. The inclusion of three mode controlling areas 24_1, 24_2, 24_r in FIG. **1** is illustrative only and does not constitute any limitation regarding the number of mode controlling areas that may be included in the display of the present invention.

[0064] Display **10** may include additional touch responsive loci **18** generally indicated by tab selecting areas 26_1, 26_2, 26_s annotated to indicate specified separate control menus or tabs that may be effected by actuating a respective area. Tab selecting area 26_1 permits selecting a "HOME" menu or tab. Tab selecting area 26_2 permits selecting a "SCHEDULE" menu or tab. Tab selecting area 26_s permits selecting an "OPTIONS" menu or tab. Actuation may be carried out in any known manner, preferably by pressing or depressing an individual locus 26_m in the manner of a touch screen input device known by those skilled in the art of design of control devices for HVAC systems. The indicator "s" is employed to signify that there can be any number of tab selecting areas in display **10**. The inclusion of three tab selecting areas 26_1, 26_2, 26_s in FIG. **1** is illustrative only and does not constitute any limitation regarding the number of tab selecting areas that may be included in the display of the present invention.

[0065] Touch responsive areas **12**, **14**, **16**, **18** may be configured using fixed segment display technology. Fixed segment display technology generally results in clear, crisp, well-defined displayed information. However, fixed segment display technology is generally inflexible and resistant to change. Fixed segment display technology is not readily amenable to presenting custom messages or similar ad hoc information displays. Displays employing fixed segment display technology do not permit in-the-field changes in displayed information to accommodate differing needs among different users.

[0066] Display **10** may include a display locus **30** configured to employ dot matrix display technology. Dot matrix display technology is readily accepting of changes so that customizable messages or other information may be presented using dot matrix display technology responsive to changes entered by a user. Display locus **30** may include a message zone **32** for display of customized messages, alerts or other displays. Display locus **30** may further include touch responsive loci **34**, generally indicated by customizable selecting areas 36_1, 36_2, 36_3, 36_4, 36_t annotated to indicate specified separate control functions or selections that may be effected by pressing or otherwise actuating a respective area. Each of customizable selecting areas 36_1, 36_2, 36_3, 36_4, 36_t may be programmed to effect a predetermined response in reaction to pressure applied to a respective customizable area. The particular response to touching may be indicated by a customized message in display area **30** using dot matrix display technology. The indicator "t" is employed to signify that there can be any number of customizable selecting areas in display **10**. The inclusion of five customizable selecting areas 36_1, 36_2, 36_3, 36_4, 36_t in FIG. **1** is illustrative only and does not constitute any limitation regarding the number of customizable selecting areas that may be included in the display of the present invention. Alternatively, selecting areas 36_1, 36_2, 36_3, 36_4, 36_t may be non-responsive to touch but may be employed to effect labeling of associated touch-responsive areas located substantially adjacent to selecting areas 36_1, 36_2, 36_3, 36_4, 36_t. By way of example and not by way of limitation, selecting area 36_1 may be employed to label functional area 22_2 for use as a selecting button associated with an element displayed in message zone **32**. Selecting area 36_2 may be employed to label functional area 22_3 for use as a selecting button associated with an element displayed in message zone **32**. Selecting area 36_3 may be employed to label functional area 22_4 for use as a selecting button associated with an element displayed in message zone **32**. Selecting area 36_4 may be employed to label functional area 22_5 for use as a selecting button associated with an element displayed in message zone **32**. Selecting area 36_t may be employed to label functional area 22_6 for use as a selecting button associated with an element displayed in message zone **32**.

[0067] Other areas of display **10** may be configured for display only without providing a coincident touch sensitive area for receiving user inputs such as, by way of example and not by way of limitation, display-only areas 40_1, 40_2, 40_3, 40_4, 40_u. Display-only areas 40_1, 40_2, 40_3, 40_4, 40_u may employ any display technology, but preferably employ fixed segment display technology. By way of example and not by way of limitation, display-only area **40** may display up to two digits indicating a set temperature for a HEAT mode of operation, display-only area 40_2 may display up to two digits indicating a set temperature for a COOL mode of operation, display-only area 40_3 may display an "F" indicator indicating degrees Fahrenheit or a "C" indicator indicating degrees Celsius, and display-only areas 40_4, 40_u may cooperate to display up to two digits indicating an extant indoor temperature. The indicator "u" is employed to signify that there can be any number of display-only areas in display **10**. The inclusion of five display-only areas 40_1, 40_2, 40_3, 40_4, 40_u in FIG. **1** is illustrative only and does not constitute any limitation regarding the number of display-only areas that may be included in the display of the present invention.

[0068] Day-of-week indicators "MON" (Monday), "TUE" (Tuesday), "WED" (Wednesday), "THU" (Thursday), "FRI" (Friday), "SAT" (Saturday) and "SUN" (Sunday) are illustrated as being included within message zone **32**and configured using dot-matrix display format. Day-of-week indicators may be situated outside of message zone **32** and configured using fixed segment display format if desired.

[0069] Employment of fixed segment display technology and dot matrix display technology in display **10** permits designing display **10** so that frequently used controls and

associated information displays such as, by way of example and not by way of limitation, controls and information related with touch responsive loci **12**, **14**, **16**, **18** may be rendered in highly readable fixed segments. Mixing display technologies also permits dynamic information to be rendered in dot matrix display technology to present customizable text messages clearly understandable by a user and instructive to a user.

[0070] By way of example and not by way of limitation, system status indications on prior art thermostat display units have typically been effected using fixed indicators such as a light indicator, a code display or a fixed Liquid Crystal Display (LCD) text. Such fixed indicators are not generally descriptive so that a user, such as a homeowner, may be left wanting more information than is provided by the indicator. This may be the case when a "trouble" indicator such as a lighted or blinking Light Emitting Diode (LED) indicator is actuated, but no indication of the exact problem is available without consulting a user's manual. Further, because the indicators are in fixed positions on the display screen there is not a single place on the screen or other user interface that one can always look at to determine whether there are any problems. An indicator of system status could be located anywhere on the display screen making it difficult to review system status. Difficulty in reviewing system status may create a possibility of a critical message being inadvertently overlooked.

[0071] Providing a variable display area such as display area using a technology permitting variation of information presented permits a user to look to a particular area of display **10**, such as display area **30**, to quickly and assuredly determine whether the system is operating properly and, if not, what the nature of an extant problem may be.

[0072] FIG. **2** is a first view of the display illustrating features associated with the HOME Tab. In FIG. **2**, HOME tab selecting area $\mathbf{26}_1$ is depressed or otherwise actuated to orient display **10** in an exemplary "HOME" configuration. Display **10** is preferably configured with a backlit screen with adjustable brightness and presents large graphics so as to be easy to read and easy to use.

[0073] A user's depressing or otherwise actuating HOME tab selecting area $\mathbf{26}_1$ configures display **10** for displaying current system operations including, by way of example and not by way of limitation, display of indoor temperature (display only areas $\mathbf{40}_4$, $\mathbf{40}_u$) and heating and cooling set points (display only areas $\mathbf{40}_1$, $\mathbf{40}_2$) and permits a user to make adjustments to system operation. The HOME tab may be actuated automatically pursuant to satisfying predetermined conditions. By way of example and not by way of limitation, the HOME tab may be actuated when there is a period of inactivity (e.g., 60 seconds) while a user is on either the SCHEDULE tab or the OPTIONS tab In the "HOME" configuration illustrated in FIG. **2**, touch responsive loci **12** are partially presented to provide directional areas $\mathbf{20}_1$, $\mathbf{20}_2$, $\mathbf{20}_3$, $\mathbf{20}_4$; touch responsive loci **14** are generally not presented to a user; touch responsive loci **16** are generally fully presented (touch responsive loci **16** are represented in FIG. **2** as having experienced selection by a user to establish an AUTO Mode with Fan in AUTO and Schedule ON); and touch responsive loci **18** are generally fully presented as having experienced selection by a user to establish the HOME configuration.

[0074] Providing a "file folder" type of display organization using TABS selectable by depressing or otherwise activating tab selecting areas $\mathbf{26}_1$, $\mathbf{26}_2$, $\mathbf{26}_s$ avoids cluttering display **10** with menu selections that are not relevant to an extant selection task. As prior art thermostat control displays added more and more capability to control an associated HVAC system, the number of buttons and menu screens became more and more complicated. A result was complex control or programming procedures that were cumbersome to execute, even with the aid of an associated user's manual. Providing TABS improves intuitive easy navigating among functions programmable or selectable using display **10**. Grouping configuration and control options on logical TABS on the user interface, i.e., display **10**, provides a user with displays familiar to users, especially to users having experience dealing with such software programs as MS Excel® (a trademark of Microsoft Corporation) and various web browser programs. Tabbed interface permits users to quickly navigate to and control features of a system.

[0075] If an outdoor temperature sensor is installed (not shown in FIG. **2**), display area **30** may display outdoor temperature, or relative humidity, or both outdoor temperature and relative humidity (only outdoor temperature is illustrated as displayed in FIG. **2**), along with accompanying information such as, by way of example and not by way of limitation, date and time.

[0076] By way of example and not by way of limitation, display **10** may be operated in the HOME configuration illustrated in FIG. **2** to permit a user to actuate the SCHED button $\mathbf{24}_r$ to select SCHED ON so that the controlled system (not shown in FIG. **2**) will follow a pre-programmed schedule. A user may again depress or otherwise actuate the SCHED button to select SCHED OFF for non-programmed, manual system operation.

[0077] Prior art thermostat controls generally always have a pre-programmed operation running so that heating and cooling set points are changed according to pre-programmed settings when a predetermined time is reached. If a user wished to disable the pre-programmed operation using a prior art thermostat control the user was required to put the thermostat in a "permanent hold" state. The term "permanent hold" proved to be confusing to many users. Further, if a user wished to change temperature setting of a thermostat control there was a requirement that the user perform another permanent hold regarding the newly set temperature set point. In short, the process for changing a programmed temperature was sometimes cumbersome, frustrating and confusing to users. Providing a SCHED button permitting a user to easily press a single button for placing a system in a SCHED ON mode for following a pre-programmed schedule or in a SCHED OFF mode for non-programmed, manual operation is intuitively easy for a user to understand and carry out.

[0078] FIG. **3** is a second view of the display illustrating features associated with the HOME Tab. In FIG. **3**, display **10** remains in the HOME tab but is additionally configured for effecting a Temporary Schedule Hold setting. Display **10** may be configured so that while in the HOME tab, anytime a temperature set point (displayed at display-only areas $\mathbf{40}_1$, $\mathbf{40}_2$ is changed, a display is presented in display area **30** relating to setting a Temperature Schedule Hold mode of operation. In the Temporary Schedule Hold mode the HOME tab display is altered somewhat to provide selection buttons within display area **30** for effecting a Temporary Schedule Hold entry. Specifically, touch responsive loci are oriented to present a CANCEL button $\mathbf{22}_1$, a Time Selecting button $\mathbf{22}_3$ (labeled in cooperation with display area **30**), a Date Selecting button $\mathbf{22}_5$ (labeled in cooperation with display area **30**), an UP arrow $\mathbf{20}_5$, a DOWN arrow $\mathbf{20}_n$ and a SAVE button $\mathbf{22}_m$.

[0079] Additionally, in the Temporary Schedule Hold mode, display area **30** displays a time and date until which a temporary hold is to be maintained. Selectively actuating Time Selecting button $\mathbf{22}_3$ or Date Selecting button $\mathbf{22}_5$ permits a user to pause a pre-programmed schedule for a time set using Time Selecting button $\mathbf{22}_3$ or Date Selecting button $\mathbf{22}_5$ to set the time and date it is desired that the pre-programmed schedule is to resume. By way of example and not by way of limitation, a temporary schedule hold may be imposed for a time interval ranging from a few hours up to forty-five days.

[0080] FIG. **4** is a view of the display illustrating features associated with the SCHEDULE Tab. In FIG. **4**, SCHEDULE tab selecting area $\mathbf{26}_2$ is depressed or otherwise actuated to orient display **10** in an exemplary "SCHEDULE" configuration. A user's depressing or otherwise actuating SCHEDULE tab selecting area $\mathbf{26}_2$ configures display **10** for displaying a programming screen to permit a user to select temperatures for certain times of day such as, by way of example and not by way of limitation, time of waking (WAKE time), time of leaving one's house for work (LEAVE time), time returning to house after work (RETURN time) and time of going to sleep (SLEEP time).

[0081] Display **10** may permit a user to schedule or program events for an entire week, as indicated by inclusion of all days of the week in display area **30**. Alternately, selected subsets of the week may be programmed separately such as, by way of example and not by way of limitation, scheduling events according to the same schedule for a Monday-Friday workweek with a different schedule set for weekends. Another choice may be for a user to schedule events for each individual day of the week. Opting among subsets of a week for scheduling may be effected by depressing or otherwise actuating the NEXT button $\mathbf{22}_6$ among touch responsive loci **14**.

[0082] In the "SCHEDULE" configuration illustrated in FIG. **4**, touch responsive loci **12** are generally not presented to a user; touch responsive loci **14** are generally presented to a user as described in connection with FIG. **1** (functional action areas $\mathbf{22}_1$, $\mathbf{22}_2$, $\mathbf{22}_3$, $\mathbf{22}_4$, $\mathbf{22}_5$, $\mathbf{22}_6$) with no SAVE button ($\mathbf{22}_m$) presented. In this SCHEDULE configuration functional action areas are as labeled in the bottom portion of areas illustrated in FIG. **1**. Thus, functional action area $\mathbf{22}_1$ affects an EDIT function, functional action area $\mathbf{22}_2$ affects a WAKE time setting; functional action area $\mathbf{22}_3$ affects a LEAVE time setting, functional action area $\mathbf{22}_4$ affects a RETURN time setting; functional action area $\mathbf{22}_5$ affects a SLEEP time setting and functional action area $\mathbf{22}_6$ affects a NEXT function. Touch responsive loci **16** are generally presented only in terms of a FAN mode selection button with the Fan in AUTO in FIG. **4**. Touch responsive loci **18** are generally fully presented as having experienced selection by a user to establish the SCHEDULE configuration.

[0083] FIG. **5** is a first view of the display illustrating features associated with the OPTIONS Tab. FIG. **6** is a second view of the display illustrating features associated with the OPTIONS Tab. FIG. **7** is a third view of the display illustrating features associated with the OPTIONS Tab. Regarding FIGS. **5-7** together, OPTIONS tab selecting area $\mathbf{26}_s$ is depressed or otherwise actuated to orient display **10** in an exemplary "OPTIONS" configuration. A user's depressing or otherwise actuating OPTIONS tab selecting area $\mathbf{26}_s$ configures display **10** for displaying a scrolling list of adjustable settings.

[0084] In the "OPTIONS" configuration illustrated in FIGS. **5-7**, touch responsive loci **12** are generally presented to a user as described in connection with FIG. **1** only in so far as two selecting or scrolling buttons are represented, such as delineated directional areas $\mathbf{20}_5$, $\mathbf{20}_n$. Touch responsive loci **14**are generally presented to a user as described in connection with FIG. **1** only in so far as two functional action areas $\mathbf{22}_4$, $\mathbf{22}_5$ are represented. In this OPTIONS configuration functional action areas are as labeled in the top portion of areas illustrated in FIG. **1**. Thus, functional action area $\mathbf{22}_4$ affects a CLEAN function, functional action area $\mathbf{22}_5$ affects an ENTER function. Touch responsive loci **16** are generally not presented to a user. Touch responsive loci **18** are generally fully presented as having experienced selection by a user to establish the OPTIONS configuration.

[0085] By way of example and not by way of limitation, a user may employ delineated directional areas $\mathbf{20}_5$, $\mathbf{20}_n$ to scroll through a list of adjustable settings presented in display area (FIG. **5**). Adjustable settings are highlighted or otherwise differentiated from other adjustable settings as each becomes available for selection. When a desired adjustable setting is highlighted or otherwise indicated as available for selection, a user may depress or otherwise actuate the ENTER button $\mathbf{22}_5$ to select the adjustable setting to be adjusted. Other sub-lists may be displayed. Eventually a user will be able to indicate and select a particular setting for adjustment, the user may then depress or otherwise actuate the ENTER button $\mathbf{22}_5$ to select the indicated setting for adjustment and then delineated directional areas $\mathbf{20}_5$, $\mathbf{20}_n$ may be employed to adjust the setting upward or downward until the desired setting level is achieved.

[0086] By way of example and not by way of limitation, one may scroll to a setting USER SETTINGS, select USER SETTINGS and be presented with a sub-list or sub-lists that ultimately permit a user to establish settings such as Date, Time, Events per Day, Backlight Intensity, Backlight Setting or Security Lock.

[0087] Similarly a user may scroll to a setting REMINDERS, select REMINDERS and ultimately select from a series of service, parts replacement, maintenance or custom reminders (FIG. **6**). As the function of display **10** changes, (e.g., selecting an adjustable setting (FIG. **5**) or displaying a reminder (FIG. **6**)) the particular respective functional areas $\mathbf{22}_m$ presented to a user may change. FIG. **6** illustrates that functional areas $\mathbf{22}_2$ (BACK) and $\mathbf{22}_6$ (EDIT) may be presented to a user while viewing reminder messages. The selected reminders may be displayed in display area **30** when display **10** is in the HOME configuration (FIG. **2**).

[0088] As indicated in FIG. **7**, contact information relating to one's HVAC dealer or repair facility may be selected while in the OPTIONS configuration and may appear on display **10** in the HOME configuration when a critical system error occurs. Prior art thermostat display units typically are provided with an adhesive sticker or decal for adhering to the housing of the thermostat with contact information relating to a HVAC dealer or repair facility. Homeowners sometimes regard such stickers as unsightly and remove them. If their system needs service, there is a problem determining how to contact the repair facility.

[0089] Entering appropriate service and repair contact information in memory of a thermostat permits its display of the information without requiring a sticker. Further, the system may be programmed to recognize circumstances under

which it would be advisable to contact a repair facility and automatically display the contact information when such circumstances occur.

[0090] More than one message may be displayed in display area **30** using a "slide show" technique successively displaying each message for a predetermined time, using a "scrolling" display by which the message displays are rolled by for a viewer's perusal or using another multi-message display technique.

[0091] FIG. **8** is a first view of the display illustrating programming steps associated with Mode of operation. FIG. **9** is a second view of the display illustrating programming steps associated with Mode of operation. Regarding FIGS. **8-9** together, a user may touch display **10** generally anywhere to activate the backlight and render display **10** easy to read.

[0092] In programming heating and cooling set point temperatures in a system using display **10**, a user places display **10** in a HOME configuration substantially as described above in connection with FIG. **2**. To set or program a temperature, a user may press the MODE button $\mathbf{24}_1$ repeatedly to select a choice of system operation (i.e., HEAT, COOL, AUTO, OFF, EM HEAT). AUTO allows the thermostat unit to automatically switch between heating and cooling as dictated by the indoor temperature. EM HEAT (Emergency Heat) is used to disable heat pump operation on very cold days and use electric strip heating or fossil fuel heating instead.

[0093] A user may press UP arrow $\mathbf{20}_1$ or DOWN arrow $\mathbf{20}_2$ to program a desired heating set point (displayed at display-only area $\mathbf{40}_1$). A user may press UP arrow $\mathbf{20}_3$ or DOWN arrow $\mathbf{20}_4$ to program a desired cooling set point (displayed at display-only area $\mathbf{40}_2$). A user may press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to program a desired time (selected by time selection button $\mathbf{22}_3$) and date (selected by date selection button $\mathbf{22}_5$) the user desires that the schedule resume (displayed at display area **30**).

[0094] FIG. **10** is a first view of the display illustrating programming steps associated with operation Schedule. FIG. **11** is a second view of the display illustrating programming steps associated with operation Schedule. FIG. **12** is a third view of the display illustrating programming steps associated with operation Schedule. Regarding FIGS. **10-12** together, a user may touch display **10** generally anywhere to activate the backlight and render display **10** easy to read.

[0095] In programming a schedule in a system using display **10**, a user places display **10** in a SCHEDULE configuration substantially as described above in connection with FIG. **4**. In the SCHEDULE configuration display **10** may appear substantially as presented in FIG. **11**. To set or program a schedule, a user may press EDIT button $\mathbf{22}_1$ and then press NEXT button $\mathbf{22}_6$ repeatedly to select a grouping of days displayed in display area **30**. When the desired grouping of days is displayed, a user may press WAKE button $\mathbf{22}_2$, LEAVE button $\mathbf{22}_3$, RETURN button $\mathbf{22}_4$ or SLEEP button $\mathbf{22}_5$ to select an event to be programmed. After selecting an event to be programmed and pressing EDIT button $\mathbf{22}_1$, display **10** may appear substantially as presented in FIG. **12**.

[0096] A user may thereafter use UP arrows $\mathbf{20}_1$, $\mathbf{20}_3$ or DOWN arrows $\mathbf{20}_2$, $\mathbf{20}_4$ to select a desired temperature set point for the selected event. A user may then press FAN button $\mathbf{24}_2$ repeatedly to select a desired fan mode for the selected event. A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to set a start time for the selected event. Another event may be selected for programming by pressing or otherwise actuating an appropriate functional area: WAKE button $\mathbf{22}_2$, LEAVE button $\mathbf{22}_3$, RETURN button $\mathbf{22}_4$ or SLEEP button $\mathbf{22}_5$. A user may press SAVE button $\mathbf{22}_m$ when all events and days are programmed as desired. Pressing HOME Tab $\mathbf{26}_1$ returns display **10** to the main screen (see FIG. **2**). A user must ensure that SCHED button $\mathbf{24}_r$ is set to ON so that the system will follow the programmed events just entered.

[0097] Prior art thermostat control devices generally require a user to navigate through a menu of day groupings to program such as, by way of example and not by way of limitation, M-SUN (Monday-Sunday), M-F (Monday-Friday), SA (Saturday), SUN Sunday), and other similar day groupings. Some prior art thermostat control devices require a user to select multiple days on different buttons or select each day for separate programming treatment. Display **10** permits a user to select among predetermined day groupings using a single button (e.g., NEXT button $\mathbf{22}_6$). Each press or other actuation of NEXT button $\mathbf{22}_6$ presents a different group of days to be programmed in display area **30** offering a quick and easy way for a user to select which group of days is desired for programming without having to navigate confusing menus or make multiple selections on different buttons.

[0098] FIG. **13** is a first view of the display illustrating programming steps associated with Temporary/Vacation Hold. FIG. **14** is a second view of the display illustrating programming steps associated with Temporary/Vacation Hold. Regarding FIGS. **13-14** together, a user may touch display **10** generally anywhere to activate the backlight and render display **10** easy to read.

[0099] In programming a Temporary/Vacation Hold in a system using display **10**, a user places display **10** in a HOME configuration substantially as described above in connection with FIG. **2**. In the HOME configuration display **10** may appear substantially as presented in FIG. **13**. To set or program a Temporary/Vacation Hold, a user may press UP arrow $\mathbf{20}_1$ or DOWN arrow $\mathbf{20}_2$ to program a desired heating set point (displayed at display-only area $\mathbf{40}_1$). A user may press UP arrow $\mathbf{20}_3$ or DOWN arrow $\mathbf{20}_4$ to program a desired cooling set point (displayed at display-only area $\mathbf{40}_2$). Adjusting either of the heating set point or the cooling set point will cause display **10** to present display area **30** substantially as illustrated in FIG. **14**. A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to program a desired time (selected by time selection button $\mathbf{22}_3$) and date (selected by date selection button $\mathbf{22}_5$) the user desires that the programmed schedule will resume (displayed at display area **30**). Display **10** may be configured so that skipping the step of programming a desired date a time for desired resumption of the programmed schedule may result in the set point temperatures entered above for Temporary/Vacation Hold will hold for a predetermined time such as, by way of example and not by way of limitation, three hours before resuming the programmed schedule. A user may press SAVE button $\mathbf{22}_m$ to save the set point temperatures, time and date to resume, entered above for Temporary % Vacation Hold. The Temporary % Vacation Hold may be cancelled at any time by pressing SCHED button $\mathbf{24}_r$.

[0100] FIG. **15** is a first view of the display illustrating programming steps associated with Humidity Settings. FIG. **16** is a second view of the display illustrating programming steps associated with Humidity Settings. FIG. **17** is a third view of the display illustrating programming steps associated with Humidity Settings. FIG. **18** is a fourth view of the display illustrating programming steps associated with Humidity Settings. FIG. **19** is a fifth view of the display illustrating programming steps associated with Humidity Settings.

Regarding FIGS. **15-19** together, a user may touch display **10** generally anywhere to activate the backlight and render display **10** easy to read (FIG. **15**).

[0101] In programming Humidity Settings in a system using display **10**, a user places display **10** in an OPTION configuration substantially as described above in connection with FIGS. **5-7**. In the OPTIONS configuration display **10** may appear substantially as presented in FIG. **16**. To set or program Humidity Settings, a user may press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of adjustable settings presented in display area **30** (FIG. **16**). Adjustable settings are highlighted or otherwise differentiated from other adjustable settings as each becomes available for selection. A user may be presented with a plurality of displayed settings for selection, may scroll among the displayed settings using UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ and may select USER SETTINGS by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when USER SETTINGS is highlighted. A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of user setting alternatives presented in display area **30** (FIG. **17**). A user may then select HUMIDITY SETTING by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when HUMIDITY SETTING is highlighted. Thereafter, a user may press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to select a desired relative humidity set point (FIG. **18**). A user may press or otherwise actuate SAVE button $\mathbf{22}_m$ to save the selected relative humidity set point (FIG. **19**).

[0102] FIG. **20** is a first view of the display illustrating programming steps associated with Setting Service Reminders. FIG. **21** is a second view of the display illustrating programming steps associated with Setting Service Reminders. FIG. **22** is a third view of the display illustrating programming steps associated with Setting Service Reminders. FIG. **23** is a fourth view of the display illustrating programming steps associated with Setting Service Reminders. FIG. **24** is a fifth view of the display illustrating programming steps associated with Setting Service Reminders. FIG. **25** is a sixth view of the display illustrating programming steps associated with Setting Service Reminders. FIG. **26** is a seventh view of the display illustrating programming steps associated with Setting Service Reminders. Regarding FIGS. **20-26** together, a user may touch display **10** generally anywhere to activate the backlight and render display **10** easy to read (FIG. **20**).

[0103] In programming a Service Reminder in a system using display **10**, a user places display **10** in an OPTION configuration substantially as described above in connection with FIGS. **5-7**. In the OPTIONS configuration display **10** may appear substantially as presented in FIG. **21**. To set or program a Service Reminder, a user may press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of adjustable settings presented in display area **30** (FIG. **21**). Adjustable settings are highlighted or otherwise differentiated from other adjustable settings as each becomes available for selection. A user may select REMINDERS by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when REMINDERS is highlighted. A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of reminder alternatives presented in display area **30** (FIG. **22**). By way of example and not by way of limitation, a user may then select REPLACE MEDIA FILTER by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when REPLACE MEDIA FILTER is displayed in display area **30** (FIG. **22**).

[0104] Thereafter, a user may press EDIT button $\mathbf{22}_6$ to select a first editable element associated with REPLACE MEDIA FILTER. A user may use arrows $\mathbf{20}_5$, $\mathbf{20}_n$ to select whether it is desired to modify or edit CALENDAR TIME or RUN TIME, and press ENTER button $\mathbf{22}_5$ to complete the selection of CALENDAR TIME or RUN TIME (FIG. **23**).

[0105] A user may thereafter press or otherwise actuate RESET button $\mathbf{22}_3$ or EDIT button $\mathbf{22}_5$ (labeled in cooperation with display area **30**) and use arrows $\mathbf{20}_5$, $\mathbf{20}_n$ to set time for the service reminder being programmed (FIG. **24**). By way of example and not by way of limitation one may set the time for a reminder for a period ranging from one month to twenty-four months (FIG. **25**). A user may thereafter press SAVE button to save the programming steps entered. Pressing or otherwise actuating HOME tab $\mathbf{26}_1$ returns display **10** to its HOME configuration (FIG. **26**). Service reminders are displayed in display area **30** in the HOME configuration at the programmed date.

[0106] Display **10** permits resetting a reminder, such as a service reminder, directly from display screen **10** without having to go to a special set-up or configuration screen. With many prior art thermostat devices one must dismiss and reset (or at least reset) the reminder using a special set-up or configuration screen requiring a user manual to know how to perform the operation. Often a homeowner does not know how to carry out this programming evolution so the service reminder message is never reset and the feature is rendered substantially useless. Display **10** permits resetting the reminder time interval directly when it appears on display **30** using a reset button $\mathbf{22}_5$ (FIG. **26**; labeled in cooperation with display area **30**) without having to go to little used and unfamiliar special set-up or configuration screen. This direct reset capability increases usability of the feature.

[0107] A reminder button $\mathbf{22}_2$ (FIG. **26**; labeled in connection with display area **30**) permits a user to direct the system served by a thermostat using display **10** to remind the user at a later time of the need for a service such as, by way of example and not by way of limitation, redisplaying the reminder message, displaying the reminder message in a flashing mode, emitting an audible alert or another reminder technique. This "Remind Later" feature may be useful when a homeowner does not have a replacement filter handy when the reminder is first displayed. The "Remind Later" feature permits a user to dismiss a reminder temporarily without having to reset the reminder or having to see the reminder displayed continuously until reset. The remind period may be a predetermined maximum time such as, by way of example and not by way of limitation, seven days.

[0108] Prior art thermostat control devices generally require a user to enter a reminder interval or delay using a code corresponding to a time, such as a number of days. The time code is commonly provided in a user manual and is likely not something the user remembers. The capability to enter reminder delay interval or other time in terms of a number of months (or other predetermined time interval) in display **10** is a significant improvement in convenience and ease of use for a user.

[0109] Display **10** could be provided with access to a stored calendar. Such a stored calendar could be contained within a processor device associated with a control device operating with display **10** (not shown in detail in FIGS. **1-51**). In such an arrangement, a user could select a "calendar function" and scroll through calendars to select a particular date for a reminder to be displayed.

[0110] FIG. **27** is a first view of the display illustrating programming steps associated with the Clean Screen Feature.

FIG. **28** is a second view of the display illustrating programming steps associated with the Clean Screen Feature. FIG. **29** is a third view of the display illustrating programming steps associated with the Clean Screen Feature. Regarding FIGS. **27-29** together, a user may touch display **10** generally anywhere to activate the backlight and render display **10** easy to read (FIG. **27**).

[0111] In setting up a CLEAN SCREEN configuration in a system using display **10**, a user places display **10** in an OPTION configuration substantially as described above in connection with FIGS. **5-7**. In the OPTIONS configuration display **10** may appear substantially as presented in FIG. **28**. To set up a CLEAN SCREEN configuration, a user may press CLEAN button $\mathbf{22}_4$. The CLEAN SCREEN configuration thus set up deactivates all touch responsive loci for touch screen entry to display **10** for a predetermined period such as, by way of example and not by way of limitation, thirty seconds. By deactivating the touch responsive loci of display **10** one may be able to clean the screen without inadvertently providing input signals to the system supported and controlled by the thermostat device using display **10** (not shown in FIG. **27-29**). Pressing or otherwise activating CLEAN button $\mathbf{22}_4$ again may provide additional time for cleaning the screen. Display **10** may indicate remaining time for duration of the CLEAN SCREEN configuration as at locus **42** (FIG. **29**).

[0112] FIG. **30** is a first view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters. FIG. **31** is a second view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters. FIG. **32** is a third view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters. FIG. **33** is a fourth view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters. FIG. **34** is a fifth view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters. FIG. **35** is a sixth view of the display illustrating programming steps associated with turning ON or OFF of display of certain parameters. Regarding FIGS. **30-35** together, in programming display **10** to turn ON or OFF the display of certain parameters, a user places display **10** in an OPTION configuration substantially as described above in connection with FIGS. **5-7**. In the OPTIONS configuration display **10** may appear substantially as presented in FIG. **30**. A user may press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of adjustable settings presented in display area **30** (FIG. **30**). Adjustable settings are highlighted or otherwise differentiated from other adjustable settings as each becomes available for selection. A user may select USER SETTINGS by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when USER SETTINGS is highlighted. A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of USER SETTINGS alternatives presented in display area **30** (FIG. **32**). A user may then select DISPLAY INFO by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when DISPLAY INFO is displayed in display area **30** (FIG. **33**). A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of DISPLAY INFO alternatives presented in display area **30** (FIG. **34**). A user may then select OUTDOOR TEMP (by way of example and not by way of limitation) by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when OUTDOOR TEMP is displayed in display area **30** (FIG. **34**). A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through an ON alternative and an OFF alternative presented in display area **30** (FIG. **35**). A user may then select ON (by way of example and not by way of limitation) by pressing or otherwise actuating SAVE button $\mathbf{22}_m$ when ON is displayed in display area **30** (FIG. **35**).

[0113] If no outdoor sensor is installed in the system controlled by a thermostat employing display **10**, a message "OUTDOOR SENSOR REQUIRED" may be displayed when the ON alternative is selected.

[0114] A user may select which parameters are displayed on the screen of display **10**. This capability may reduce the amount of clutter on the screen and may make display **10** more readable. By way of example and not by way of limitation, a user can select whether or not to display indoor relative humidity or outside temperature.

[0115] FIG. **36** is a first view of the display illustrating toggling among displays of certain parameters. FIG. **37** is a second view of the display illustrating toggling among displays of certain parameters. FIG. **38** is a third view of the display illustrating toggling among displays of certain parameters. FIGS. **30-35** illustrate programming steps associated with turning ON or OFF of display of certain parameters, as discussed above. FIGS. **36-38** illustrate the result of programming steps carried out to effect toggling among displays of certain parameters.

[0116] Regarding FIGS. **30-38** together, in turning on toggling among displays of certain parameters, a user places display **10** in an OPTION configuration substantially as described above in connection with FIGS. **5-7**. In the OPTIONS configuration display **10** may appear substantially as presented in FIG. **30**. A user may press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of adjustable settings presented in display area **30** (FIG. **30**). Adjustable settings are highlighted or otherwise differentiated from other adjustable settings as each becomes available for selection. A user may select USER SETTINGS by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when USER SETTINGS is highlighted. A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of USER SETTINGS alternatives presented in display area **30** (FIG. **32**). A user may then select DISPLAY INFO by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when DISPLAY INFO is displayed in display area **30** (FIG. **33**). A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of DISPLAY INFO alternatives presented in display area **30** (FIG. **34**). A user may then select OUTDOOR TEMP (by way of example and not by way of limitation) by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when OUTDOOR TEMP is displayed in display area **30** (FIG. **34**). A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through an ON alternative and an OFF alternative presented in display area **30** (FIG. **35**). A user may then select ON (by way of example and not by way of limitation) by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when ON is displayed in display area **30** (FIG. **35**) and press SAVE (button $\mathbf{22}_m$; see FIG. **1**). If no outdoor sensor is installed in the system controlled by a thermostat employing display **10**, a message "OUTDOOR SENSOR REQUIRED" may be displayed when the ON alternative is selected.

[0117] A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to again select DISPLAY INFO by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when DISPLAY INFO is displayed in display area **30** (FIG. **33**). A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of DISPLAY INFO alternatives presented in

display area **30** (FIG. **34**). A user may then select INDOOR RH (by way of further example and not by way of limitation) by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when INDOOR RH is displayed in display area **30**. A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through an ON alternative and an OFF alternative presented in display area **30** (FIG. **35**). A user may then select ON (by way of example and not by way of limitation) by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when ON is displayed in display area **30** (FIG. **35**) and press SAVE (button $\mathbf{22}_m$).

[0118] A user may thereafter press or otherwise activate HOME tab $\mathbf{26}_1$ and observe display area **30** presenting messages as illustrated in FIGS. **36-38** in a repeating sequence, or toggling, display.

[0119] With the variable display capability of display area **30**, fixed portions of display **10** need not be dedicated to displaying information. Information can be programmed to rotate or toggle automatically in display area **30**.

[0120] FIG. **39** is a first view of the display illustrating programming steps associated with displays of custom reminders. FIG. **40** is a second view of the display illustrating programming steps associated with displays of custom reminders. FIG. **41** is a third view of the display illustrating programming steps associated with displays of custom reminders. FIG. **42** is a fourth view of the display illustrating programming steps associated with displays of custom reminders. FIG. **43** is a fifth view of the display illustrating programming steps associated with displays of custom reminders. FIG. **44** is a sixth view of the display illustrating programming steps associated with displays of custom reminders. Regarding FIGS. **39-44** together, a user may touch display **10** generally anywhere to activate the backlight and render display **10** easy to read (FIG. **39**).

[0121] In programming a Custom Reminder in a system using display **10**, a user places display **10** in an OPTION configuration substantially as described above in connection with FIGS. **5-7**. In the OPTIONS configuration display **10** may appear substantially as presented in FIG. **40**. To set or program a Custom Reminder, a user may press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of adjustable settings presented in display area **30** (FIG. **40**). Adjustable settings are highlighted or otherwise differentiated from other adjustable settings as each becomes available for selection. A user may be presented with a plurality of displayed settings for selection, may scroll among the displayed settings using UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ and may select INSTALLER SETTINGS by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when INSTALLER SETTINGS is highlighted. FIG. **41** is presented to warn a user that installer settings must be set by a qualified user. A user may then press ENTER button $\mathbf{22}_5$ to advance to installer settings. A user may be presented with a plurality of displayed INSTALLER SETTINGS for selection, may scroll among the displayed INSTALLER SETTINGS to scroll to a list of reminder alternatives presented in display area **30** (FIG. **42**). A user may then select CUSTOM REMINDER **1** by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when CUSTOM REMINDER **1** is displayed in display area **30** (FIG. **42**).

[0122] Thereafter, a user may press EDIT button $\mathbf{22}_6$ and press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through alphanumeric characters displayed (FIGS. **43**, **44**). When a desired alphanumeric character is displayed in display area **30**, a user may press or otherwise activate NEXT button $\mathbf{22}_6$ to select a subsequent character. BACK button $\mathbf{22}_2$ may be employed to return to a previously selected character if desired (FIG. **43**). When the desired annotation has been selected for CUSTOM REMINDER **1**, a user may press or otherwise activate SAVE button $\mathbf{22}_m$ to save the Custom Reminder for display. Date and time for display may be entered as selectable characters in response to prompting by display **10** (not shown in detail in FIGS. **39-44**).

[0123] Installing HVAC contractors, dealers or other installing personnel typically offer users such as homeowners various routine services such as, by way of example and not by way of limitation, duct cleaning, cleaning outside portions of HVAC units, system checkups and similar services. Prior art HVAC system control displays do not provide users with reminders of such services other than the installer or dealer calling the user when the scheduled service is due or sending a reminder post card. Display **10** permits programming reminders so that a contractor, installer or dealer can add a custom reminder that is specific to the service offered. Once set up, display **10** may display the reminder message in a manner similar to other reminders, such as a reminder to check filters.

[0124] FIG. **45** is a first view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system. FIG. **46** is a second view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system. FIG. **47** is a third view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system. FIG. **48** is a fourth view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system. FIG. **49** is a fifth view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system. FIG. **50** is a sixth view of the display illustrating programming steps associated with hiding display of menu items not relevant to a user's extant system. Regarding FIGS. **45-50** together, a user may touch display **10** generally anywhere to activate the backlight and render display **10** easy to read (FIG. **45**).

[0125] In programming to hide display of selected menu items in a system using display **10**, a user places display **10** in an OPTION configuration substantially as described above in connection with FIGS. **5-7**. In the OPTIONS configuration display **10** may appear substantially as presented in FIG. **46**. To hide display of a selected menu item, a user may press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of adjustable settings presented in display area **30**. Adjustable settings are highlighted or otherwise differentiated from other adjustable settings as each becomes available for selection. A user may select INSTALLER SETTINGS by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when INSTALLER SETTINGS is highlighted. FIG. **41** may be presented at this juncture to warn a user that installer settings must be set by a qualified user. A user may then press ENTER button $\mathbf{22}_5$ to advance to installer settings. A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of INSTALLER SETTINGS presented in display area **30** (FIG. **46**). A user may then select SYSTEM SETUP by pressing or otherwise actuating ENTER button $\mathbf{22}_5$ when SYSTEM SETUP is displayed in display area **30** (FIG. **46**). A user may then press UP arrow $\mathbf{20}_5$ or DOWN arrow $\mathbf{20}_n$ to scroll through a list of SYSTEM SETUP choices presented in display area **30** (FIG. **47**). A user may then select NON HEAT

PUMP by pressing or otherwise actuating SAVE button 22_m when NON HEAT PUMP is displayed in display area **30** (FIG. **47**).

[0126] A user may then press UP arrow 20_5 or DOWN arrow 20_n to scroll through a list of NON HEAT PUMP choices presented in display area **30** (FIG. **47**). A user may then select ELECTRIC (indicating an electric system is controlled by a thermostat employing display **10** rather than a gas system) by pressing or otherwise actuating ENTER button 22_5 when ELECTRIC is displayed in display area **30** (FIG. **47**).

[0127] After indicating that the system is an ELECTRIC system, a user may be again be presented with a list of SYSTEM SETUP choices presented in display area **30**. A user may scroll among the displayed settings using UP arrow 20_5 or DOWN arrow 20_n and may then select COMPRESSOR STAGES by pressing or otherwise actuating ENTER button 22_5 when COMPRESSOR STAGES is displayed in display area **30** (FIG. **48**). A user may then press UP arrow 20_5 or DOWN arrow 20_n to scroll through a list of COMPRESSOR STAGES choices presented in display area **30**. A user may then select "1" (indicating that the system controlled by a thermostat employing display **10** has a single compressor stage) by pressing or otherwise actuating SAVE button 22_m when "1" is displayed in display area **30** (FIG. **48**).

[0128] A message INDOOR HEAT STAGES may thereafter be displayed in display area **30** (FIG. **49**), and a user may then press UP arrow 20_5 or DOWN arrow 20_n to scroll through a list of INDOOR HEAT STAGES choices presented in display area **30**. A user may then select "1" (indicating that the system controlled by a thermostat employing display **10** has a single indoor heat stage) by pressing or otherwise actuating SAVE button 22_m when "1" is displayed in display area **30** (FIG. **49**). A user may then depress BACK button 22_2, followed by UP arrow 20_5 or DOWN arrow 20_n to scroll through a list of selections until STG **1** DIFF appears in display area **30** (FIG. **50**) and is selected by pressing or otherwise actuating ENTER button 22_5.

[0129] This exemplary set of selections (FIGS. **45-50**) would be appropriate, by way of example and not by way of limitation, when a system controlled by a thermostat employing display **10** is a non heat pump system providing electric heat and having a one-stage compressor and one stage of indoor heat. In such an exemplary system, menu items such as, by way of example and not by way of limitation, STG **2** DIFF and STG **3** DIFF would be hidden and not displayed to a user.

[0130] Prior art HVAC system controller displays typically present all menu items regardless of whether the physical equipment is connected or otherwise installed or included with the system being controlled. This display of menu items with which a user may be unfamiliar (because the user may have no need to deal with the menu item) may be confusing and worrisome to a user. The user—whether a dealer or a homeowner—may be led to mistakenly believe that there is a need to set a control parameter for something that does not exist in the system at hand.

[0131] Providing a capability to hide menu items not associated with a system at hand, as described in connection with FIGS. **45-50**, removes irrelevant distractions not associated with equipment installed. By way of example and not by way of limitation, if a dealer configures a system for a single stage furnace no options will be displayed that pertain to second stage settings. By way of further example and not by way of limitation, if a system has not been configured with a humidifier, then no humidification settings will be displayed.

[0132] FIG. **51** is a flow chart illustrating the method of the present invention. In FIG. **51**, a method **100** for entering input to an environmental control system begins at a START locus **102**. Method **100** continues with providing a display area, as indicated by a block **104**.

[0133] Method **100** continues with, in no particular order: (1) presenting a plurality of first loci in the display area, as indicated by a block **106**; (2) presenting a plurality of second loci in the display area, as indicated by a block **108**; and (3) presenting at least one third locus in the display area, as indicated by a block **110**.

[0134] Method **100** continues with, in no particular order: (1) configuring each respective first locus of the plurality of first loci for being responsive to pressure for effecting a respective input, as indicated by a block **112**; (2) configuring each respective second locus of the plurality of second loci presenting information using a fixed segment data format, as indicated by a block **114**; and (3) configuring at least one third locus of the at least one third locus presenting information using a dot matrix data format, as indicated by a block **116**. Method **100** terminates at an END locus **118**.

[0135] Display **10** avoids requiring a user to navigate to system settings by entering a configuration mode, selecting a configuration or other code to configure and then entering or selecting a configuration parameter. Display **10** also avoids requiring a user having to "drill down" through layers of menus by pressing a "next" or "back" button to enter a configuration mode, select a configuration or other code to configure and enter or select a configuration parameter, as is required when operating prior art HVAC control devices. In contrast, display **10** permits a user to scroll through a list of menu items until a desired programmable item is displayed. Thereafter, a user can enter parameters desired for effecting programming of the desired item in real text without having to deal with configuration codes, a user's manual or similar complications.

[0136] Those skilled in the art to which this application relates will appreciate that other and further additions, deletions, substitutions and modifications may be made to the described embodiments.

What is claimed is:

1. A display apparatus for a control unit in an environmental control system; the display apparatus comprising: a display area presenting a plurality of first loci, a plurality of second loci and at least one third locus; each respective first locus of said plurality of first loci being responsive to pressure for effecting a respective response; each respective second locus of said plurality of second loci presenting information using a fixed segment data format; at least one third locus of said at least one third locus presenting information using a dot matrix data format; said display apparatus configured to allow multiple days to be programmed with a single button.

2. A display apparatus for a control unit in an environmental control system as recited in claim **1** wherein at least one said respective first locus overlaps with at least one said respective second locus.

3. A display apparatus for a control unit in an environmental control system as recited in claim **1** wherein at least one said respective first locus overlaps with at least one said respective third locus.

4. A display apparatus for a control unit in an environmental control system as recited in claim **2** wherein at least one said respective first locus overlaps with at least one said respective third locus.

5. A display apparatus for a control unit in an environmental control system as recited in claim **2** wherein each said respective first locus is substantially aligned with a respective said second locus.

6. A display apparatus for a control unit in an environmental control system as recited in claim **4** wherein each said respective first locus is substantially aligned with a respective said second locus.

7. A display apparatus for a control unit in an environmental control system as recited in claim **1** wherein said display area is configured for selectively populating said respective second loci with display information.

8. A display apparatus for a control unit in an environmental control system as recited in claim **1** wherein said display area is configured for selectively populating said respective second loci with display information.

9. A display apparatus for a control unit in an environmental control system as recited in claim **1** wherein said display area is configured for selectively populating said respective third loci with display information.

10. A display apparatus for a control unit in an environmental control system as recited in claim **8** wherein said display area is configured for selectively populating said respective third loci with display information.

11. A touchscreen input apparatus for an environmental control system; the apparatus comprising: a display area having a plurality of touch-sensitive input loci, at least one first display locus and at least one second display locus; said at least one first display locus presenting information using a fixed segment data format; said at least one second display locus presenting information using a dot matrix data format; said touchscreen input apparatus configured to allow multiple days to be programmed with a single button.

12. A touchscreen input apparatus for an environmental control system as recited in claim **11** wherein at least one respective touch-sensitive input locus of said plurality of touch-sensitive input loci overlaps with at least one respective first display locus of said at least one first display locus.

13. A touchscreen input apparatus for an environmental control system as recited in claim **12** wherein at least one respective touch-sensitive input locus of said plurality of touch-sensitive input loci overlaps with at least one respective second display locus of said at least one second display locus.

14. A touchscreen input apparatus for an environmental control system as recited in claim **11** wherein each said respective touch-sensitive input locus is substantially aligned with a respective said first display locus.

15. A touchscreen input apparatus for an environmental control system as recited in claim **12** wherein each said respective touch-sensitive input locus is substantially aligned with a respective said first display locus.

16. A touchscreen input apparatus for an environmental control system as recited in claim **11** wherein said display area is configured for selectively populating at least one selected first display locus of said at least one first display locus with display information.

17. A touchscreen input apparatus for an environmental control system as recited in claim **11** wherein said display area is configured for selectively populating at least one selected second display locus of said at least one second display locus with display information.

18. A touchscreen input apparatus for an environmental control system as recited in claim **16** wherein said display area is configured for selectively populating at least one selected second display locus of said at least one second display locus with display information.

19. A method for entering input to an environmental control system; the method comprising: (a) providing a display area; (b) in no particular order: (1) presenting a plurality of first loci in said display area; (2) presenting a plurality of second loci in said display area; and (3) presenting at least one third locus in said display area; and (c) in no particular order: (1) configuring each respective first locus of said plurality of first loci for being responsive to pressure for effecting a respective said input; (2) configuring each respective second locus of said plurality of second loci presenting information using a fixed segment data format; (3) configuring at least one third locus of said at least one third locus presenting information using a dot matrix data format; and (4) allowing multiple days to be programmed with a single button.

20. A method for entering input to an environmental control system as recited in claim **19** wherein said display area is configured for selectively populating said respective second loci with display information, and wherein said display area is configured for selectively populating said respective third loci with display information.

* * * * *