



US 2019003373A1

(19) **United States**

(12) **Patent Application Publication**

REGNER et al.

(10) **Pub. No.: US 2019/0003373 A1**

(43) **Pub. Date: Jan. 3, 2019**

(54) **AIR HANDLING IN A HEAVY-DUTY  
OPPOSED-PISTON ENGINE**

(71) Applicant: **ACHATES POWER, INC.**, San Diego, CA (US)

(72) Inventors: **GERHARD REGNER**, San Diego, CA (US); **MICHAEL CHIANG**, San Diego, CA (US)

(73) Assignee: **ACHATES POWER, INC.**, San Diego, CA (US)

(21) Appl. No.: **15/775,346**

(22) PCT Filed: **Dec. 2, 2016**

(86) PCT No.: **PCT/US2016/064766**

§ 371 (c)(1),

(2) Date: **May 10, 2018**

**Related U.S. Application Data**

(60) Provisional application No. 62/264,022, filed on Dec. 7, 2015, provisional application No. 62/279,284, filed on Jan. 15, 2016.

**Publication Classification**

(51) **Int. Cl.**

**F02B 25/08** (2006.01)

**F02B 37/00** (2006.01)

**F02B 37/013** (2006.01)

**F02B 37/16** (2006.01)

**F02B 37/18** (2006.01)

**F02B 75/28** (2006.01)

**F02M 26/08** (2006.01)

**F02M 26/09** (2006.01)

**F02D 41/00** (2006.01)

(52) **U.S. Cl.**

CPC ..... **F02B 25/08** (2013.01); **F02B 37/004**

(2013.01); **F02B 37/013** (2013.01); **F02B**

**37/16** (2013.01); **F02B 37/18** (2013.01); **F02D**

**2200/101** (2013.01); **F02M 26/08** (2016.02);


**F02M 26/09** (2016.02); **F02D 41/0007**


(2013.01); **F02D 2200/04** (2013.01); **F02B**

**75/282** (2013.01)


**ABSTRACT**

An air handling arrangement in a two-stroke cycle, opposed-piston engine with uniflow scavenging and constructed for heavy-duty operation includes sequentially arranged turbochargers in series with a supercharger, in some aspects, the air handling system is equipped with an EGR channel.





**FIG. 1**  
(Prior Art)



**FIG. 2**  
(Prior Art)




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7

FIG. 8



## AIR HANDLING IN A HEAVY-DUTY OPPOSED-PISTON ENGINE

### PRIORITY

[0001] This application claims priority to U.S. Provisional Application No. 62/264,022 filed on Dec. 7, 2015, and to U.S. Provisional Application No. 62/279,284 filed on Jan. 15, 2016.

### RELATED APPLICATIONS

[0002] This application contains subject matter related to that of commonly-owned U.S. patent application Ser. No. 14/039,856, filed Sep. 27, 2013, and published as US 2014/0026563 and commonly-owned PCT application US2015/015365, filed Feb. 11, 2015, which claims priority to U.S. 61/939,170, filed Feb. 12, 2014.

### FIELD OF THE INVENTION

[0003] The field is two-stroke cycle, uniflow-scavenged, opposed-piston engines. More specifically the application relates to air handling for opposed-piston engines by means of a multi-stage arrangement of turbochargers provided in series with a supercharger to provide a variable flow of charge air with minimal pumping loss.

### BACKGROUND

[0004] A two-stroke cycle engine is an internal combustion engine that completes a cycle of operation with a single complete rotation of a crankshaft and two strokes of a piston connected to the crankshaft. The strokes are typically denoted as compression and power strokes. One example of a two-stroke cycle engine is an opposed-piston engine in which two pistons are disposed head-to-head in the bore of a cylinder for reciprocating movement in opposing directions. The cylinder has longitudinally-spaced inlet and exhaust ports formed in the cylinder sidewall near respective ends of the cylinder. Each of the opposed pistons controls a respective one of the ports, opening the port as it moves toward a bottom dead center (BDC) location during a power stroke (also called an expansion stroke), and closing the port as it moves from BDC toward a top dead center (TDC) location during a compression stroke. One of the ports provides passage for the products of combustion out of the bore, the other serves to admit charge air into the bore; these are respectively termed the "exhaust" and "intake" ports. In a uniflow-scavenged opposed-piston engine, charge air entering a cylinder through the intake port displaces exhaust gas flowing out of the exhaust port, thus gas flows through the cylinder in one direction ("uniflow")—from intake port to exhaust port.

[0005] Gas, including charge air, exhaust products, and mixtures thereof, is transported through the engine's cylinders via an air handling system. The air handling system may be equipped for exhaust gas recirculation ("EGR") to reduce undesirable compounds produced by combustion. As the engine cycles, the air handling control mechanism governs gas flow by operating the air handling system in response to engine operating conditions and operator commands.

[0006] In a two-stroke, uniflow-scavenged, opposed-piston engine a continuous positive pressure differential must exist from the intake ports to the exhaust ports in order to maintain the desired unidirectional flow of gas in the cyl-

inder. Further, a high air mass density must be provided to the intake ports because of the short time that they are open; this need is especially acute during engine start and acceleration. Typically, these needs are met by provision of a fast acting, positive-displacement pump in the charge air channel, just upstream from the engine's intake ports. This role is typically filled by a supercharger (or blower) which is driven mechanically from an engine crankshaft, either by direct connection, as with a belt, chain, or gear, or by way of a single-speed, multiple-speed, or continuously variable drive. Frequently, a turbocharger, powered by exhaust energy, is placed ahead (upstream) of the supercharger in order to increase the density of intake air fed into the supercharger.

[0007] Two-stroke cycle, opposed-piston engines provide superior power densities and brake thermal efficiencies as compared to their four-stroke counterparts. To date these engines have been used successfully in stationary applications and in aircraft, maritime vessels, locomotives, and tracked military vehicles.

[0008] It is desirable to achieve similar benefits by use of opposed-piston engines in modern heavy duty vehicles. Heavy duty vehicles may be defined in the US as vehicles of GVWR (gross vehicle weight rating) of above 8,500 pounds, according to Federal regulations, and above 14,000 pounds in California. Similar definitions and classifications are used in other countries to define heavy duty vehicles. Trucks and busses are examples of heavy duty vehicles. In this disclosure, opposed-piston engines designed and/or built to power heavy-duty vehicles are referred as "heavy duty" opposed-piston engines. A heavy-duty opposed-piston engine must be able to deliver sufficient power under specified efficiency and emission standards in the normal conditions encountered during operation of a heavy duty vehicle.

[0009] The Commer TS3 engine represents one successful application of an opposed-piston engine design to a medium-duty commercial truck. The air handling configuration of the TS3 engine was not turbocharged; however, it was supercharged, with a three-lobe, crankshaft-driven, Roots-type blower feeding air at high speed to the engine. Depending on the model, displacement of the TS3 engine varied from 3.26 to 3.52 liters, and power output varied from 78.3 to 107.4 KW. According to Pirault and Flint, the TS3 was powerful, delivering "probably 50% greater torque than from equivalent displacement, naturally-aspirated four-stroke diesel truck engines of that period." (*OPPOSED PISTON ENGINES, Evolution, Use, and Future Applications*, by J-P. Pirault and M. Flint, SAE International, Warrendale Pa., 2010, p. 144).

[0010] Two-stroke cycle engines with large displacements and high power ratings must be equipped with air handling systems capable of pumping large amounts of densified air. It is desirable that the air handling system of a heavy duty opposed-piston engine be able to maintain a desirable scavenge ratio ( $M_{scavenged}/M_{delivered}$ ) and high brake thermal efficiency when the engine experiences a steep increase in torque demand, as when accelerating from low engine speed while heavily loaded, or encountering a steep hill. A supercharger is typically used to move charge air to engine intake ports quickly enough to maintain the scavenge ratio, but running it hard for a long period increases pumping loss, which reduces the engine's brake thermal efficiency.

[0011] In order to meet boost requirements of a heavy-duty two-stroke cycle, uniflow-scavenged, opposed-piston

engine, without excessive pumping loss, it is desirable to reduce reliance on a supercharger in the air handling system by way of a sequential turbocharger in series with the supercharger.

#### SUMMARY

[0012] The invention is directed to an air handling system of a two-stroke cycle, uniflow-scavenged, opposed-piston engine, which includes a supercharger in fluid communication with one or more intake ports of the engine and a sequential turbocharger in series with the supercharger. The sequential turbocharger includes a first stage for low pressure operation, a second stage for high pressure operation, and at least one valve-controlled bypass circuit to engage or disengage the second stage. In some instances, a second valve-controlled bypass circuit may be provided to engage or disengage the first stage. The sequential turbocharger provides compressed charge air to the supercharger as needed during engine operation. In normal and transient engine operating conditions, the second stage may be bypassed while the first stage operates. When high pressure ratios are needed, the second stage is engaged, thereby adding a further stage of charge air compression, which increases the pressure of the charge air input to the supercharger, and thereby the mass of charge air delivered ( $M_{delivered}$ ) to the intake ports.

[0013] In some aspects, the air handling system may be equipped with an EGR loop. In some further aspects, the EGR loop may include one of a low pressure EGR loop upstream of the sequential turbocharger, a mid-pressure EGR loop between the first and second turbocharger stages, and a high pressure EGR loop between the second stage and the supercharger. Further, the air handling system may be equipped with one or more of the low pressure EGR loop, the mid-pressure EGR loop, and the high pressure EGR loop.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The below-described drawings are meant to illustrate principles and examples of the invention. They are not meant to be limiting; and they are not necessarily to scale.

[0015] FIG. 1 is a schematic diagram of a prior art two-stroke cycle, opposed-piston engine with uniflow scavenging, and is appropriately labeled "Prior Art".

[0016] FIG. 2 is a schematic diagram showing details of a prior art air handling system for an opposed-piston engine, and is appropriately labeled "Prior Art".

[0017] FIG. 3 is a schematic diagram showing details of an air handling system for a two-stroke cycle, opposed-piston engine according to a first embodiment.

[0018] FIG. 4 is a schematic diagram showing details of an air handling system for a two-stroke cycle, opposed-piston engine according to a second embodiment.

[0019] FIG. 5 is a schematic diagram showing details of an air handling system for a two-stroke cycle, opposed-piston engine according to a third embodiment.

[0020] FIG. 6 is a schematic diagram showing details of an air handling system for a two-stroke cycle, opposed-piston engine according to a fourth embodiment.

[0021] FIG. 7 is a schematic diagram showing details of an air handling system for a two-stroke cycle, opposed-piston engine according to a fifth embodiment.

[0022] FIG. 8. is a schematic diagram showing details of a control mechanization for an air handling system according the invention

#### DETAILED DESCRIPTION

[0023] In this disclosure, "fuel" is any fuel that can be used in an opposed-piston engine. The fuel may be a relatively homogeneous composition, or a blend. For example, the fuel may comprise diesel fuel, natural gas, gasoline, or another equivalent fuel ignitable by compression, pilot, and/or spark ignition. Further, the descriptions contemplate ignition resulting from compression of an air/fuel mixture; however in some instances it may be desirable to provide additional mechanisms, such as glow plugs, spark plugs, pilot injections, or laser circuits to assist compression ignition.

[0024] According to this disclosure, fuel is injected into compressed air in a combustion chamber formed between the end surfaces of opposed pistons when the pistons are at or near TDC locations. In other aspects, injection may occur earlier in the compression stroke, soon after closure of both ports. The air is preferably pressurized ambient air; however, it may include other components such as exhaust gases or other diluents. In any such case, the pressurized air delivered to an intake port is referred to as "charge air."

[0025] According to this disclosure, the opposed-piston engine is provided with an engine control mechanism—a computer-based system that includes one or more electronic control units coupled to associated sensors, actuators, and other machine devices throughout the engine that govern the operations of various engine systems, including the air handling system, a fuel system, a cooling system, a lubrication system, and other engine systems. The engine control elements that govern the air handling system are referred to collectively as the "air handling control mechanization".

[0026] Opposed-Piston Architecture and Operation: FIGS. 1 and 2 illustrate a prior art turbocharged, two-stroke cycle, opposed-piston engine 10 with uniflow scavenging. The engine 10 has at least one ported cylinder 50. For example, the engine may have one ported cylinder, two ported cylinders, three ported cylinders, or four or more ported cylinders. Each ported cylinder 50 has a bore 52 and longitudinally-spaced exhaust and intake ports 54 and 56 formed or machined near respective ends of a cylinder sidewall. Each of the exhaust and intake ports 54 and 56 includes one or more circumferential arrays of openings in which adjacent openings are separated by a solid portion of the cylinder sidewall called a "bridge". In some descriptions, each opening is referred to as a "port"; however, the construction of circumferential arrays of such "ports" is no different than the port constructions shown in FIG. 1. Pistons 60 and 62 are slidably disposed in the bore 52 with their end surfaces 61 and 63 opposing one another. The piston 60 controls the exhaust port 54, and the piston 62 controls the intake port 56. In the example shown, the engine 10 further includes at least one crankshaft; preferably, the engine includes two crankshafts 71 and 72. In the example shown, the exhaust pistons 60 of the engine are coupled to the crankshaft 71, and the intake pistons 62 to the crankshaft 72.

[0027] As the pistons 60 and 62 near TQC, a combustion chamber is defined in the bore 52 between the end surfaces 61 and 63 of the pistons. Combustion timing is frequently referenced to a point in a compression cycle where minimum combustion chamber volume occurs; this point is

referred to as “minimum volume.” Fuel is injected directly into cylinder space located between the end surfaces **61** and **63**. In some instances injection occurs at or near minimum volume; in other instances, injection may occur before minimum volume. Fuel is injected through fuel injector nozzles **68** and **70** positioned in respective openings through the sidewall of the cylinder **50**. Preferably, the fuel injector nozzles **68** and **70** are positioned to inject respective sprays of fuel in opposing radial directions of the bore **52**. The fuel mixes with charge air admitted into the bore **52** through the intake port **56**. As the air-fuel mixture is compressed between the end surfaces **61** and **63**, the compressed air reaches a temperature that causes the fuel to ignite: combustion follows.

[0028] The engine **10** includes an air handling system **80** that manages the transport of charge air provided to, and exhaust gasses produced by, the engine **10**. A representative air handling system construction includes a charge air channel and an exhaust channel. In the air handling system **80**, a charge air source receives inlet air and processes it into charge air. The charge air channel receives the charge air and transports it to the at least one intake port of the engine. The exhaust channel transports exhaust products from the at least one exhaust port of the engine for delivery to other exhaust components.

[0029] The air handling system **80** includes a turbocharger **120** with a turbine **121** and a compressor **122** that rotate on a common shaft **123**. The turbine **121** is in fluid communication with the exhaust subsystem and the compressor **122** is in fluid communication with the charge air subsystem. The turbocharger **120** extracts energy from exhaust gas that exits the exhaust ports **54** and flows into an exhaust channel **124** from an exhaust manifold, plenum, or chest **125** (collectively, “exhaust manifold”, for convenience) that collects exhaust gasses output through the exhaust ports **54**. In this regard, the turbine **121** is rotated by exhaust gas passing through it to an exhaust outlet channel **128**. This rotates the compressor **122**, causing it to generate charge air by compressing fresh air. The charge air channel **126** includes the compressor, a supercharger **110**, and an intake manifold, plenum, or chest **130** (collectively, “intake manifold”, for convenience). The charge air channel may further include at least one charge air cooler (hereinafter, “cooler”) to receive and cool the charge air before delivery to the intake port or ports of the engine. The charge air output by the compressor **122** flows through the charge air channel **126** to a cooler **127**, whence it is pumped by the supercharger **110** to the intake ports. Charge air compressed by the supercharger **110** is output to the intake manifold **130**. The intake ports **56** receive charge air pumped by the supercharger **110**, through the intake manifold **130**. A second cooler **129** may be provided between the output of the supercharger **110** and the input to the intake manifold **130**.

[0030] In some aspects, the air handling system **80** may be equipped to reduce NOx emissions produced by combustion by recirculating a portion of the exhaust gas produced by combustion through the ported cylinders of the engine. The recirculated exhaust gas is mixed with charge air to lower peak combustion temperatures, which reduces production of NOx. This process is referred to as exhaust gas recirculation (“EGR”). The EGR construction shown obtains a portion of the exhaust gasses flowing from the port **54** during scavenging and transports them via an EGR channel **131** external to the cylinder into the incoming stream of inlet air in the

charge air subsystem. The recirculated exhaust gas flows through the EGR channel **131** under the control of a valve **138** (this valve may also be referred to as the “EGR valve”).

[0031] FIG. 2 shows the air handling system **80** in greater detail. In this regard, the charge air subsystem provides air to the compressor **122** via an air filter **150**. As the compressor **122** rotates, compressed air flows from the compressor’s outlet, through the charge air channel **126**, and into the inlet **151** of the supercharger **110**. Charge air pumped by the supercharger **110** flows through the supercharger’s outlet **152** into the intake manifold **130**. Pressurized charge air is delivered from the intake manifold **130** to the intake ports of the cylinders **50**, which are supported in an engine block **160**. A second cooler **129** may be provided in the charge air subsystem, in series between the output of the supercharger **110** and the intake manifold **130**.

[0032] Exhaust gasses from the exhaust ports of the cylinders **50** flow from the exhaust manifold **125** into the inlet of the turbine **121**, and from the turbine’s outlet into the exhaust outlet channel **128**. In some instances, one or more after treatment devices **162** are provided in the exhaust channel **128**. Exhaust may be recirculated via a high-pressure EGR channel **131** which obtains exhaust from the channel **124** at a point between the exhaust manifold **125** and the input to the turbine **121** and delivers exhaust for mixing with fresh charge air at a point between the output of the compressor **122** and the supercharger input **151**. Alternatively (or additionally), exhaust may be recirculated via a low-pressure EGR channel **131<sub>LP</sub>** which obtains exhaust at a point between the exhaust outlet **128** and the output of the turbine **121** and delivers exhaust for mixing with fresh charge air upstream of the input to the compressor **122**. Presuming that the air handling system includes a high-pressure EGR channel, a portion of the exhaust flowing out of the manifold **125** is recirculated through the EGR channel **131**, under control of the EGR valve **138**. The EGR channel **131** is coupled to the charge air subsystem via the EGR mixer **163**. In some instances, although not necessarily, an EGR cooler **164** is provided in the EGR channel **131**, in series between the EGR valve **138** and the EGR mixer **163**. In other instances, there may be no cooler in the EGR channel **131**. As per FIG. 2, a low-pressure EGR channel may be similarly constructed.

[0033] The air handling system **80** is equipped for control of gas flow at separate control points in the charge air and exhaust subsystems. In the charge air channel, charge air flow and boost pressure are controlled by operation of a recirculation channel **165** coupling the outlet **152** of the supercharger to the supercharger’s inlet **151**. In some instances, the channel **165** may be referred to as a “bypass channel” or a “shunt channel.” The recirculation channel **165** shunts charge air flow from the outlet **152** to the inlet **151** of the supercharger according to the setting of a recirculation valve **166**. The recirculation channel enables control of the flow of charge air into, and thus the pressure in, the intake manifold **130**. Other valves may be provided at other control points in the air handling system. Such other valves may include, without limitation, back pressure and wastegate valves associated with the turbine, bypass valves associated with coolers, and possibly, other valves.

[0034] In some instances, additional control of gas flow (and pressure) is provided by way of a variable-speed supercharger and/or a variable-geometry turbine. Thus, in some aspects the supercharger **110** may be coupled by a

drive mechanism (“drive”) to one of the crankshafts or another rotating element of the engine, to be driven thereby. The drive may comprise a single-speed transmission, a stepwise transmission, or a continuously variable transmission (CVT), device, with a clutch, in which cases, charge air flow, and boost pressure, may be varied by varying the speed of the supercharger. In other instances, the supercharger may be a single-speed device with or without a clutch. In those aspects where the turbine is a variable-geometry device it has an effective opening size that may be varied in response to changing speeds and loads of the engine.

[0035] Air Handling in a Heavy-Duty, Opposed-Piston Engine: The invention is directed principally to aspects of an air handling system in an opposed-piston engine with the understanding that these aspects may be combined with other systems and functions such as fuel injection, cooling, lubrication, on-board diagnostics, and so on, in the opposed-piston engine.

[0036] An air handling system of a heavy-duty, two-stroke cycle, uniflow-scavenged, opposed-piston engine in which a supercharger provides boost and drives uniflow scavenging during engine operation is illustrated by embodiments shown in FIGS. 3-7, in which an air handling system according to FIG. 2 is modified according to this disclosure.

[0037] In these embodiments, a two-stroke cycle, uniflow-scavenged opposed piston engine includes at least one cylinder with a bore, longitudinally-separated exhaust and intake ports, and a pair of pistons disposed in the bore for opposing movements therein, in which movement of a first piston of the pair of pistons controls the exhaust port and movement of the second piston of the pair of pistons controls the intake port. The supercharger is disposed in fluid communication with the intake ports of the engine to provide a continuous positive pressure differential from the intake port to the exhaust port so as to maintain a unidirectional flow of gas from the intake to the exhaust port during two-stroke operation of the engine. A multi-stage turbocharger arrangement (which is sometimes called a “sequential turbocharger”) comprises at least two turbochargers disposed in series. Each turbocharger includes a turbine and a compressor that turn on a common shaft. The compressors of the turbochargers are arranged in series with the supercharger such that the compressor outlet of a first turbocharger is in fluid communication with the compressor inlet of a second turbocharger and the compressor outlet of the second turbocharger is in fluid communication with the inlet of the supercharger. The turbines of the first and second turbochargers are arranged in series with the exhaust ports of the engine such that the turbine inlet of the second turbocharger is in fluid communication with the exhaust ports and the turbine inlet of the first turbocharger is in fluid communication with the turbine outlet of the second turbocharger.

[0038] In each embodiment, the air handling system is configured with a mass air flow path (called a “charge air channel”) comprising a supercharger having an outlet coupled to one or more cylinder intake ports and one or more turbocharger compressors to provide compressed air to an intake of the supercharger. Some of the embodiments further comprise an EGR loop.

[0039] First Air Handling Embodiment: A first air handling embodiment according to the invention is shown in FIG. 3. The embodiment includes a two-stroke cycle, uniflow-scavenged, opposed-piston engine 302. The engine 302 includes one or more cylinders as per the cylinder 50 in

FIGS. 1 and 8. Fuel, coolant, and lubrication are provided to the engine although the systems for doing so are not shown. The engine 302 is equipped with an air handling system 300. The air handling system 300 transports fresh air into, and exhaust out of, the engine 302. The air handling system 300 includes a supercharger 305 in fluid communication with one or more intake ports (not shown) of the engine 302 and a sequential turbocharger 306 in series with the supercharger 305.

[0040] The supercharger 305 includes an inlet 307 and an outlet 309. Desirably, the outlet 309 is coupled to a charge air cooler (CAC) 310 through which charge air is fed to an intake manifold (not shown) of the engine 301. The supercharger 305 is a positive displacement device, driven by a crankshaft of the engine 302; in some aspects, the supercharger is operated by a supercharger drive 315 that is coupled directly, or indirectly, to the crankshaft. Preferably, the drive 315 includes, or is associated with, a clutch mechanism that couples the drive to, and decouples the drive from, the crankshaft. When the drive is coupled to the crankshaft, the supercharger operates, accelerating (boosting) a flow of pressurized charge air produced by the sequential turbocharger 306 to the intake ports 56. Otherwise, when the drive is uncoupled, the supercharger ceases being driven by the crankshaft. A supercharger recirculation channel 313 including a supercharger recirculation (SC RECIRC) valve 311 is connected between the inlet 307 and outlet 309 of the supercharger 305. When the supercharger 305 is driven, opening the valve 311 causes recirculation of pressurized charge air from the outlet to the inlet of the supercharger, which enables modulation of boost. When the supercharger is not driven, opening the valve 311 enables pressurized charge air to bypass the supercharger and flow to the intake ports 56.

[0041] The sequential turbocharger 306 includes a first stage turbocharger 312 for low pressure operation, a second stage turbocharger 314 for high pressure operation, and a valve-controlled bypass circuit 316 to engage or disengage the second stage turbocharger 314. The first stage turbocharger 312 includes a low pressure compressor and a low pressure turbine that turn on a common shaft. The second stage turbocharger 314 includes a high pressure compressor and a high pressure turbine that turn on a common shaft. In some cases, the first and second stage turbochargers are referred to respectively as “large” and “small” turbochargers. The valve-controlled bypass circuit 316 includes a compressor (COMP) bypass valve 316c connected between the inlet and outlet of the high pressure compressor and a turbine (TURBO) bypass valve 316t connected between the inlet and outlet of the high pressure turbine.

[0042] The first air handling embodiment includes a charge air channel 320 comprising the low pressure compressor, the high pressure compressor, and the supercharger 305. Unpressurized fresh air enters the charge air channel via an air inlet, and passes through an air filter 322 to the inlet of the low pressure compressor. The outlet of the low pressure compressor is coupled to the inlet of the high pressure compressor. In some aspects, the charge air channel 320 includes a charge air cooler (CAC) 323 positioned between the outlet of the low pressure compressor and the inlet of the high pressure compressor. In these cases, the compressor bypass valve 316c is connected between the inlet of the CAC 323 and the outlet of the high pressure compressor. In the charge air channel 320, the outlet of the

high pressure compressor is coupled to the inlet **307** of the supercharger **305**. In some aspects, the charge air channel **320** includes a CAC **325** positioned between the outlet of the high pressure compressor and the inlet **307** of the supercharger **305**. Pressurized charge air for combustion in the engine **302** flows from the outlet **309** of the supercharger **305** through an intake manifold (not shown) to the inlet ports of the engine.

[0043] The first air handling embodiment includes an exhaust channel **340** comprising the low pressure turbine and the high pressure turbine. The outlet of the high pressure turbine is coupled to the inlet of the low pressure turbine. The outlet of the low pressure turbine is coupled to an exhaust outlet from which exhaust is vented to the atmosphere. In some instances, the exhaust channel may include one or more after treatment devices **342** downstream of the first turbocharger **312**, coupled to the outlet of the low pressure turbine. Exhaust gas produced by combustion in the engine **302** flows into the exhaust channel **340** from an exhaust manifold (not shown) to the inlet of the high pressure turbine. Exhaust gas flowing in the exhaust channel **240** drives the low pressure and high pressure turbines.

[0044] Additional Embodiments: In some instances the air handling system of FIG. 3 may be equipped with an exhaust gas recirculation (EGR) loop operable to circulate a portion of the exhaust gasses produced by the engine to the charge air channel. In this regard, each of second, third, fourth, and fifth air handling embodiments according to the invention includes charge air and exhaust channels as shown in FIG. 3, with an EGR loop. In each case, the EGR loop comprises an inlet connected to the exhaust channel **340**, an outlet connected to the charge air channel **320**, and an EGR valve between the EGR loop inlet and the EGR loop outlet.

[0045] In the second embodiment, which is illustrated in FIG. 4, a high pressure EGR loop **400** comprises a loop inlet **402**, a loop outlet **403**, and an EGR valve **405** between the loop inlet and the loop outlet. The loop inlet **402** is coupled to the exhaust channel **340**, upstream of the turbine of the second turbocharger **314**, between the manifold outlet of the engine **302** and the turbine bypass valve **316t**. The loop outlet **403** is coupled to the charge air channel **320**, downstream of the compressor of the second turbocharger **314**, between compressor bypass valve **316c** and the inlet of the CAC **325**.

[0046] In the third embodiment, which is illustrated in FIG. 5, a mid-pressure EGR loop **500** comprises a loop inlet **502**, a loop outlet **503**, and an EGR valve **505** between the loop inlet and the loop outlet. The loop inlet **502** is coupled to the exhaust channel **340**, between the turbine bypass valve **316t** and the inlet of the low pressure turbine. The loop outlet **503** is coupled to the charge air channel **320**, between the inlet of the CAC **323** and the outlet of the low pressure compressor. In addition, since it is desirable to cool the recirculated exhaust, the CAC **323** can be made continuously available for this purpose, in which case the CAC **325** becomes redundant when the high pressure compressor is bypassed. In this case, the compressor bypass valve **316c** is connected between the inlet of the high pressure compressor and the outlet of the CAC **325**.

[0047] In the fourth embodiment, which is illustrated in FIG. 6, a low pressure EGR loop **600** comprises a loop inlet **602**, a loop outlet **603**, an EGR valve **605** between the inlet and outlet, and an EGR cooler **607** downstream of the EGR valve **605**. The loop inlet **602** is coupled to the exhaust

channel **340**, downstream of the outlet of the low pressure turbine. In those instances in which the exhaust channel **340** comprises after treatment devices **342**, the loop inlet **602** is coupled to the exhaust channel **340**, between the outlet of the low pressure turbine and the after treatment devices **342**. The loop outlet **603** is coupled to the charge air channel **320**, upstream of the inlet of the low pressure compressor. In those instances in which the charge air channel **320** comprises an air filter **322**, the loop outlet **603** is coupled to the charge air channel **320**, between the inlet of the low pressure compressor and the air filter. The EGR valve **605** is disposed in the EGR loop **600**, between the loop inlet **602** and the EGR cooler **607**. In this embodiment, the compressor bypass valve **316c** may be connected so as to bypass the CAC **323** and the high pressure compressor as shown in FIGS. 3 and 4, or the high pressure compressor and the CAC **325** as shown in FIGS. 5 and 6.

[0048] The fifth embodiment, shown in FIG. 7, is a variant of the second embodiment shown in FIG. 4. In this embodiment, a second valve-controlled bypass circuit **330** is provided to engage or disengage the first stage turbocharger. The second bypass circuit **330** includes a compressor (COMP) bypass valve **330c** associated with the first turbocharger (**312**) and disposed in parallel with the compressor of the first turbocharger. The compressor bypass valve **(330c)** has a closed setting that causes unpressurized fresh air from the air inlet to pass through the compressor of the first turbocharger (**312**) and an open setting that directs the unpressurized fresh air past the compressor. In a preferred embodiment, the compressor bypass valve **(330c)** is connected between the inlet of the low pressure compressor and the outlet of the charge air cooler **323**. In this embodiment, the COMP bypass valve **316c** is connected between the inlet and the outlet of the high pressure compressor.

[0049] The second bypass circuit **330** further includes a turbine (TURBO) bypass valve **330t** associated with the first turbocharger (**312**) and disposed in parallel with the turbine of the first turbocharger (**312**). The turbine bypass valve **(330t)** has a closed setting that causes exhaust gasses to pass through the turbine of the second turbocharger (**314**) and an open setting that directs exhaust gasses past the turbine of the turbine of the first turbocharger (**312**). The turbine bypass valve **(330t)** is connected between the inlet and outlet of the low pressure turbine.

[0050] The fifth embodiment is particularly useful in the case where recirculated exhaust is transported through the high pressure EGR loop **400** and the high pressure turbine is a variable-geometry (VGT) turbine device; the additional bypass circuit **330** enables the achievement of a desired scavenging ratio at a particular engine operating point while remaining below a peak cylinder pressure limit.

[0051] Air Handling Control Mechanization: As per FIG. 8, control of the gas transport configuration of the air handling system **300** is implemented by a control mechanization that includes a programmed ECU (engine control unit) **740**, air handling algorithms executed on the ECU, air handling valves **311**, **316c**, and **316t**, **330c**, and **330t**, and engine sensors. In some aspects, the air handling control mechanization may further comprise the supercharger drive **315** and, possibly, other drives controlling geometries of the low and high pressure turbines. Air handling system control is exercised by varying the settings of the air handling valves. In this regard, for example, the recirculation valve **311** is associated with the supercharger so as to enable the

ECU 740 to control the flow of charge air through the supercharger 305. The supercharger recirculation valve 311 bleeds pressurized charge air produced by the supercharger 305 through a recirculation channel 313 that connects the outlet 309 with the inlet 307 so as to modulate charge air pressure, and dampen surges, at the intake ports 56 of the engine 302. The compressor bypass valve 316c and the turbine bypass valve 316t are associated with the second stage turbocharger 314 which enables the ECU 740 to control the mass of charge air provided to the supercharger as needed for boosting in response to sudden increases in demand for engine torque; in the fifth embodiment of FIG. 7, additional control is provided by compressor bypass valve 330c and the turbine bypass valve 330t.

[0052] The compressor bypass valve 316c is disposed in parallel with the compressor of the second turbocharger 314 and has a closed setting that causes pressurized air from the compressor of the first turbocharger 312 to pass through the compressor of the second turbocharger 314, and an open setting that directs pressurized air from the compressor of the first turbocharger 312 past the compressor of the second turbocharger 314 to the inlet 307 of the supercharger 305 (either directly as per the third and fourth embodiments, or via the CAC 325 as per the first and second embodiments).

[0053] The turbine bypass valve 316t is disposed in parallel with the turbine of the second turbocharger 314 and has a closed setting that causes exhaust gasses from the exhaust ports of the engine to pass through the turbine of the second turbocharger 314, and has an open setting that directs exhaust gasses from the exhaust ports 56 past the turbine of the second turbocharger 314 to the turbine of the first turbocharger 312.

[0054] In the fifth embodiment shown in FIG. 7, the compressor bypass valve 330c is disposed in parallel with the compressor of the first turbocharger 312 and the charge air cooler 323 and has a closed setting that causes fresh air from the ambient environment to pass through the compressor of the first turbocharger 312, and an open setting that directs fresh air from the ambient environment to the compressor inlet of the second turbocharger 314. The turbine bypass valve 330t is disposed in parallel with the turbine of the first turbocharger 312 and has a closed setting that causes exhaust gasses to pass through the turbine of the first turbocharger 312, and has an open setting that directs exhaust gasses past the turbine of the second turbocharger 314 to the after treatment devices 342.

[0055] For fast, precise automatic operation, it is preferred that these and other air handling valves be high-speed, computer-controlled devices, with step-wise or continuously-variable settings. The ECU 740 is in control communication with actuators (not seen) that operate the air handling valves in response to ECU-issued control signals.

[0056] The ECU 740 monitors air handling system operating conditions by way of various sensors. In this regard, for example, supercharger intake and outlet charge air pressures may be measured with gas pressure sensors. Air mass flow into the charge air subsystem may be measured by a mass airflow (MAF) sensor upstream of the low pressure compressor; exhaust mass flow in the EGR channel may be measured by a sensor downstream of the EGR valve; and gas temperature at the supercharger inlet may be measured by a gas temperature sensor. In particular, the ECU 740 detects charge air pressure at the intake manifold 130 by way of a gas pressure sensor P. In addition, the ECU 740 detects

engine speed and crankshaft angle (CA) by means of a speed sensor 749 that engages one of the crankshafts of the engine. Using a number of factors, the ECU 740 calculates engine load. The engine load factors may include, for example fuel flow, accelerator/throttle position, engine speed, environmental conditions, and possibly, other factors. Using programmed control modules, the ECU 740 operates the engine in a steady-state mode with an algorithm implemented in a steady-state module 751, in a transient mode with an algorithm implemented in a transient module 752, and in other modes.

[0057] As per FIGS. 3 and 8 the high pressure stage and the low pressure stage of the sequential turbocharger 306 are capable of being operated to vary the mass air pressure delivered to the supercharger 305 by way of the ECU 740 operating the air handling valves 316c and 316t and the air handling valves 330c and 330t. With respect to the exhaust channel 340, when the valve 316t is actuated to be fully closed, the exhaust produced by combustion in the engine 302 drives the high pressure turbine; when the valve 316t is actuated to be fully open, the exhaust bypasses the high pressure turbine. In either case, the exhaust flows to and drives the low pressure turbine. However, in the first case the energy of the exhaust is divided between the high and low pressure turbines, while in the second case, the low pressure turbine receives all of the exhaust energy.

[0058] With respect to the charge air channel 320, air is received and compressed by the low pressure compressor. Compressed air produced by the low pressure compressor flows toward the inlet of the high pressure compressor. When the valve 316c is fully closed, all of the compressed air produced by the low pressure compressor is further compressed by the high pressure compressor, thus elevating the charge air pressure beyond that normally produced by the low pressure stage. When the valve 316c is fully open, the compressed air exiting the low pressure compressor bypasses the high pressure compressor. In both cases, compressed charge air flows to and is accelerated by the supercharger 305. However, when the charge air is compressed by both compressors, it has a higher pressure (and therefore, a higher mass) than when it is compressed only by the low pressure compressor. Thus, it is the case that the charge air input to the supercharger has a higher mass, and the mass of charge air delivered for combustion (Mdelivered) is higher, when both compressors are on line. As a result, the supercharger does not have to be driven as hard to provide boost in response to as when fed by a single compressor. Consequently, pumping loss attributable to supercharger operation during high torque demand can be reduced.

[0059] Preferably, the bypass valves 316c and 316t are operated together by the ECU 740 (as are the bypass valves 330c and 330t) in order to smoothly respond to changes in torque demand. Given step-wise or continuously variable operation of the air-handling valves, the high-pressure turbocharger 314 can be progressively (and smoothly) transitioned into and out of operation. Thus, for low load, low engine speeds as would be encountered in a steady-state mode of operation, the ECU 740 keeps the bypass valves fully open, thereby bypassing the high pressure turbocharger 314 and allowing the low pressure turbocharger 312 alone to compress air for provision to the supercharger 305. When torque demand rises steeply enough that increasing engine speed and load cause a shift to a transient mode of engine operation, the ECU 740 causes the bypass valves to close,

thereby eliciting a quick response by the high pressure turbocharger to the requirement for boost in (Mdelivered). During transient operation, the ECU **740** sets the bypass valves **316c** and **316t** (and/or the bypass valves **330c** and **330t**) as appropriate for the level of boost needed. Then, as the torque demand diminishes (as indicated by a reduction in engine speed and load) the ECU **740** progressively resets the bypass valves when engine speed/load causes a transition back to the steady-state mode of operation.

**[0060]** Here, the role of the charge air coolers may be more clearly understood. As compressed air is passed along the compressors and the supercharger in the charge air channel, its mass begins to decrease due to expansion caused by the increase in temperature that accompanies the increase in pressure. Passage through a charge air cooler reduces the temperature of the compressed air, thereby maintaining its mass.

**[0061]** As indicated by FIGS. 4-8, control of NOx may be maintained in the heavy-duty air handling embodiment of FIG. 3 by adapting the steady state and transient algorithms executed by the ECU **740** to include modulation of the recirculated exhaust in any one, or any combination of the high pressure, mid-pressure, and low pressure EGR loops by control of the EGR valve or valves.

**[0062]** Although this disclosure describes particular air handling embodiments for a heavy duty two-stroke cycle, uniflow-scavenged, opposed-piston engine, these embodiments are set forth merely as examples of underlying principles of this disclosure. Thus, the embodiments are not to be considered in any limiting sense.

1. A two-stroke cycle, uniflow-scavenged, opposed-piston engine (**80**, **302**), comprising:

one or more cylinders (**50**), each cylinder comprising a bore (**52**), longitudinally-separated exhaust and intake ports (**54** and **56**), and a pair of pistons (**60** and **62**) disposed in the bore for opposing movements therein, in which movement of a first piston of the pair of pistons controls the exhaust port and movement of the second piston of the pair of pistons controls the intake port;

a supercharger (**305**) disposed in fluid communication with the intake ports (**56**) to provide a continuous positive pressure differential from the intake ports (**56**) to the exhaust ports (**54**) so as to maintain a unidirectional flow of gas from the intake ports to the exhaust ports during two-stroke operation of the engine; characterized by:

a sequential turbocharger (**306**), including a first turbocharger (**312**) and a second turbocharger (**314**), each of the turbochargers including a turbine and a compressor, in which the compressors of the first and second turbochargers are arranged in series with the supercharger (**305**) such that the compressor of the first turbocharger (**312**) is in fluid communication with the compressor of the second turbocharger (**314**) and the compressor of the second turbocharger (**314**) is in fluid communication with the supercharger (**305**), and the turbines of the first and second turbochargers are arranged in series with the exhaust ports (**54**) such that the turbine of the second turbocharger (**314**) is in fluid communication with the exhaust ports (**54**) and the turbine of the first turbocharger (**312**) is in fluid communication with the turbine of the second turbocharger (**314**);

a compressor bypass valve (**316c**) associated with the second turbocharger (**314**) and disposed in parallel with the compressor of the second turbocharger, the compressor bypass valve (**316c**) having a closed setting that causes pressurized air from the compressor of the first turbocharger (**312**) to pass through the compressor of the second turbocharger (**314**) and an open setting that directs pressurized air from the compressor of the first turbocharger (**312**) past the compressor of the second turbocharger (**314**) to an inlet of the supercharger (**305**); and,

a turbine bypass valve (**316t**) associated with the second turbocharger (**314**) and disposed in parallel with the turbine of the second turbocharger (**314**), the turbine bypass valve (**316t**) having a closed setting that causes exhaust gasses from the exhaust ports (**54**) to pass through the turbine of the second turbocharger (**314**) and an open setting that directs exhaust gasses from the exhaust ports (**54**) past the turbine of the second turbocharger (**314**) to the turbine of the first turbocharger (**312**).

2. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 1, in which the first turbocharger is a low pressure turbocharger and the second turbocharger is a high pressure turbocharger.

3. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 2, further comprising:

a charge air channel (**320**) including the series arrangement of the compressors of the first and second turbochargers and the supercharger which is operable to generate charge air for provision to the intake ports; and an EGR loop (**400**, **500**, **600**) operable to circulate a portion of the exhaust gasses to the charge air channel.

4. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 3, the EGR loop comprising one or more of a low pressure EGR loop (**600**), a mid-pressure EGR loop (**500**), and a high-pressure EGR loop (**400**).

5. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 1, further comprising:

a charge air channel (**320**) including the series arrangement of the compressors of the first and second turbochargers and the supercharger which is operable to generate charge air for provision to the intake ports; and an EGR loop (**400**, **500**, **600**) operable to circulate a portion of the exhaust gasses to the charge air channel.

6. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 5, the EGR loop comprising one or more of a low pressure EGR loop (**600**) upstream of the sequential turbocharger, a mid-pressure EGR loop (**500**) between the first and second turbochargers, and a high pressure EGR loop (**400**) between the second turbocharger and the supercharger.

7. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 1, further comprising:

a recirculation channel (**313**) coupling an outlet of the supercharger to an inlet of the supercharger; and, a supercharger recirculation valve (**311**) in the recirculation channel.

8. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 7, in which the first turbocharger is a low pressure turbocharger and the second turbocharger is a high pressure turbocharger.

9. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 8, further comprising:

a charge air channel (320) including the series arrangement of the compressors of the first and second turbochargers and the supercharger, which is operable to generate charge air for provision to the intake ports (56); and

an EGR loop (400, 500, 600) operable to circulate a portion of the exhaust gasses to the charge air channel.

10. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 9, the EGR loop comprising one or more of a low pressure EGR loop (600), a mid-pressure EGR loop (500), and a high-pressure EGR loop (400).

11-12. (canceled)

13. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 7, further comprising a programmed engine control unit (ECU) (740) coupled to control settings of the compressor bypass valve (316c), the turbine bypass valve (316t), and the supercharger recirculation valve (311) in response to engine speed and intake port pressure.

14. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 13, in which the first turbocharger is a low pressure turbocharger and the second turbocharger is a high pressure turbocharger.

15. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 14, further comprising:

a charge air channel (320) including the series arrangement of the compressors of the first and second turbochargers and the supercharger which is operable to generate charge air for provision to the intake ports (56); and

an EGR loop (400, 500, 600) operable to circulate a portion of the exhaust gasses to the charge air channel.

16. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 15, the EGR loop comprising one or more of a low pressure EGR loop (600), a mid-pressure EGR loop (500), and a high-pressure EGR loop (400).

17. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 1, further comprising:

a compressor bypass valve (330c) associated with the first turbocharger (312) and disposed in parallel with the compressor of the first turbocharger, the compressor bypass valve (330c) having a closed setting that causes unpressurized fresh air from an air inlet to pass through the compressor of the first turbocharger (312) and an open setting that directs the unpressurized fresh air past the compressor of the first turbocharger (312); and, a turbine bypass valve (330t) associated with the first turbocharger (312) and disposed in parallel with the turbine of the first turbocharger (312), the turbine bypass valve (330t) having a closed setting that causes exhaust gasses to pass through the turbine of the second turbocharger (314) and an open setting that directs exhaust gasses past the turbine of the turbine of the first turbocharger (312).

18. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of claim 17, further comprising:

a charge air channel (320) including the series arrangement of the compressors of the first and second turbochargers and the supercharger to generate charge air for provision to the intake ports; an exhaust channel (340) including the series arrangement of the turbines of the first and second turbochargers to transport exhaust from the exhaust ports (54); and, an EGR loop (400) having an inlet (402) in the exhaust channel upstream of an inlet of the turbine of the second turbocharger (314) and having an outlet (403) in the charge air channel downstream of the compressor of the second turbocharger (314).

19. The two-stroke cycle, uniflow-scavenged, opposed-piston engine of any one of claims 1, 5, 7, and 17, further comprising an exhaust channel (340) including the series arrangement of the turbines of the first and second turbochargers and one or more after treatment devices (342) downstream of the turbine of the first turbocharger (312).

\* \* \* \* \*