




(86) Date de dépôt PCT/PCT Filing Date: 2003/10/02
 (87) Date publication PCT/PCT Publication Date: 2004/04/22
 (85) Entrée phase nationale/National Entry: 2005/03/21
 (86) N° demande PCT/PCT Application No.: US 2003/031359
 (87) N° publication PCT/PCT Publication No.: 2004/032759
 (30) Priorité/Priority: 2002/10/04 (60/416,330) US

(51) Cl.Int.⁷/Int.Cl.⁷ A61B 17/06
 (71) Demandeur/Applicant:
 TYCO HEALTHCARE GROUP LP, US
 (72) Inventeur/Inventor:
 CUNNINGHAM, SCOTT, US
 (74) Agent: MCFADDEN, FINCHAM

(54) Titre : AIGUILLE A EXTREMITE POINTUE
 (54) Title: SHARPOINT NEEDLE



(57) Abrégé/Abstract:

A surgical needle includes an elongated needle body defining a longitudinal axis, and having a main shaft, a needle end adjacent the main shaft, and a needle tip extending from the needle end and having an extreme needle point. The needle end includes a plurality of concave surfaces extending from the needle tip to the main shaft. The needle tip includes a plurality of concave surfaces extending from the needle point to intersect the concave surfaces of the needle end. The concave surfaces of the needle end are obliquely arranged relative to the longitudinal axis at a first angle. The concave surfaces of the needle tip are obliquely arranged relative to the longitudinal axis at a second angle greater than the first angle. The elongated needle body includes cutting edges disposed along lines of intersection of the concave surfaces of the needle end with the concave surfaces of the needle tip. The needle end includes four intersecting concave surfaces and defines a generally diamond-shape in cross-section along an axis transverse to the longitudinal axis. The needle end defines a maximum cross-sectional dimension greater than a corresponding maximum cross-sectional dimension of the main shaft. The needle tip may include four intersecting concave surfaces and define a general diamond shape cross-section.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/032759 A1

(51) International Patent Classification⁷: **A61B 17/06**

(21) International Application Number:
PCT/US2003/031359

(22) International Filing Date: 2 October 2003 (02.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/416,330 4 October 2002 (04.10.2002) US

(71) Applicant: **TYCO HEALTHCARE GROUP LP**
[US/US]; 150 Glover Avenue, Norwalk, CT 06856 (US).

(72) Inventor: **CUNNINGHAM, Scott**; 10 Verdena Court,
Cheshire, CT 06410 (US).

(74) Agent: **FARBER, Mark**; Tyco Health Care Group, LP,
150 Glover Avenue, Norwalk, CT 06856 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SHARPOINT NEEDLE



(57) Abstract: A surgical needle includes an elongated needle body defining a longitudinal axis, and having a main shaft, a needle end adjacent the main shaft, and a needle tip extending from the needle end and having an extreme needle point. The needle end includes a plurality of concave surfaces extending from the needle tip to the main shaft. The needle tip includes a plurality of concave surfaces extending from the needle point to intersect the concave surfaces of the needle end. The concave surfaces of the needle end are obliquely arranged relative to the longitudinal axis at a first angle. The concave surfaces of the needle tip are obliquely arranged relative to the longitudinal axis at a second angle greater than the first angle. The elongated needle body includes cutting edges disposed along lines of intersection of the concave surfaces of the needle end with the concave surfaces of the needle tip. The needle end includes four intersecting concave surfaces and defines a generally diamond-shape in cross-section along an axis transverse to the longitudinal axis. The needle end defines a maximum cross-sectional dimension greater than a corresponding maximum cross-sectional dimension of the main shaft. The needle tip may include four intersecting concave surfaces and define a general diamond shape cross-section.

WO 2004/032759 A1

SHARPOINT NEEDLE

5

BACKGROUND

Technical Field

The present disclosure relates to a surgical suturing needle for suturing cutaneous and subcutaneous tissue, and in particular, relates to a surgical needle having a multifaceted penetrating needle end characterized by enhanced penetrability and needle hardness.

10

Background of Related Art

Suturing needles for applying sutures, or stitches, by hand in cutaneous and subcutaneous tissue are well known in the art. Typically, the suturing needles are used to close wounds or adjoin adjacent tissue, often at the conclusion of a surgical procedure. Suturing needles are usually made from a cut blank of material such as stainless steel. The cut blank is metal-worked using well known machining techniques to form the suturing needle. The needle generally includes a shaft, a rear end portion with an aperture or channel to secure a suture thread and a needle head at a front end portion for puncturing skin and passing through tissue. The needle head typically incorporates a sharpened needle tip at its distal end and cutting edges. Alternatively, the needle tip may be of a tapered configuration. Straight and curved needles including multiple curved configurations are also known in the art.

15
20

An important consideration in the design of surgical suturing needles is needle sharpness. Sharper needles require less force to penetrate tissue and thus cause less tissue trauma. In addition, a sharper needle reduces fatigue on the needle itself, making it less likely to bend or break during suturing. Needle sharpness is typically defined in terms of "penetration force"--the force necessary for a needle to puncture, or penetrate, the tissue. The penetration force is primarily determined by the design and sharpness of the needle point and the cutting edges formed on the needle head. Needle sharpness is also affected by drag force on the needle as it travels through the tissue. The drag force also depends upon the design and sharpness of the needle, and the presence of a lubricating coating.

Another important consideration in needle design and manufacture is to maximize resistance to bending or breakage during use. The strength of a suturing needle is a measure of its ability to resist bending and is determined by such factors as (a) the material of fabrication, (b) the cross-sectional shape of the needle, and (c) the heat treatment applied to the needle during manufacturing. Needle strength should be balanced by needle ductility, which is defined in terms of the ability of the needle to be reshaped after it flexes from its original shape. A surgical needle with good strength characteristics but little or no ductility can be brittle, and may snap and break during use. It is generally known that in working with a metallic material, as the strength of the material increases the ductility will decrease. Therefore, it is desirable to carefully balance the strength and ductility characteristics of a suturing needle.

SUMMARY

Accordingly, the present disclosure is directed to a surgical needle, which includes an elongated needle body defining a longitudinal axis. The elongated needle body includes a main shaft, a needle end adjacent the main shaft, and a needle tip extending from the needle end and
5 *having an extreme needle point. The needle end includes a plurality of concave surfaces* extending from the needle tip to the main shaft. The needle tip includes a plurality of concave surfaces extending from the needle point to intersect the concave surfaces of the needle end. The concave surfaces of the needle end are obliquely arranged relative to the longitudinal axis at a first angle. The concave surfaces of the needle tip are obliquely arranged relative to the longitudinal
10 axis at a second angle greater than the first angle. The elongated needle body includes cutting edges disposed along lines of intersection of the concave surfaces of the needle end with the concave surfaces of the needle tip.

In a preferred embodiment, the needle end includes four intersecting concave surfaces and defines a generally diamond-shape in cross-section along an axis transverse to the
15 longitudinal axis. The needle end defines a maximum cross-sectional dimension greater than a corresponding maximum cross-sectional dimension of the main shaft. The needle tip may include four intersecting concave surfaces.

The main shaft of the needle end may be curved along the longitudinal axis of the needle body or straight. The main shaft further includes means for attaching a suture.

20 In another embodiment, a surgical needle includes an elongated needle body defining a longitudinal axis, and having a main shaft, a needle end adjacent the main shaft, and a needle tip contiguously extending from the needle end and having an extreme needle point. The

needle end includes at least three non-linear intersecting surfaces extending from the needle tip to the main shaft. The needle tip includes at least three non-linear intersecting surfaces extending from the needle point to the needle end and intersecting the at least three non-linear surfaces of the needle end. The at least three non-linear surfaces of the needle end define cutting edges along

5 lines of intersection of adjacent surfaces thereof. The at least three non-linear surfaces of the needle tip define cutting edges along lines of intersection of adjacent surfaces thereof.

The at least three non-linear intersecting surfaces of the needle end and the at least three non-linear intersecting surfaces of the needle tip define cutting edges along lines of intersection thereof.

10 In a preferred embodiment, the needle end includes four non-linear surfaces and the needle tip includes four non-linear surfaces. The four non-linear surfaces of each of the needle end and the needle tip are generally concave.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the disclosure and, together with a general description of the disclosure given above, and the detailed description of the embodiment(s) given below, serve to explain the principles of the disclosure, wherein:

FIG. 1 is a perspective view of the surgical needle in accordance with the principles of the present disclosure;

FIG. 2 is a side plan view of the surgical needle of FIG. 1;

FIG. 3 is an enlarged top plan view illustrating the configuration of the needle end and the needle tip;

FIG. 4 is a cross-sectional view of the needle end of the surgical needle taken along the lines 4-4 of FIG. 3;

FIG. 5 is a cross-sectional view of the needle end taken along the lines 5-5 of FIG. 3;

FIG. 6 is a cross-sectional view of the needle tip taken along the lines 6-6 of FIG. 3;

FIG. 7 is a side plan view of the needle end and the needle tip;

FIG. 8 is an isolated side view adjacent the needle tip;

FIG. 9 is a top plan view of the needle end and the needle tip;

FIG. 10 is an isolated top view adjacent the needle tip;

FIG. 11 is a cross-sectional view taken along the lines 11-11 of FIG. 9;

FIGS. 12-13 are photomicrographs of the needle end and the needle tip; and

FIG. 14 is a flow chart depicting the manufacturing process of the surgical needle.

DESCRIPTION OF PREFERRED EMBODIMENTS

Preferred embodiment(s) of the surgical needle of the present disclosure will now
5 be described in detail with reference to the drawings wherein like reference numerals identify
similar or like elements throughout the several views. As used herein, the term “distal” refers to
that portion which is further from the user, while the term “proximal” refers to that portion which
is closest to the user.

Referring now to FIGS. 1-3, the surgical needle of the present disclosure is
10 illustrated. Surgical needle 10 includes elongated needle body 12. Needle body 12 includes main
shaft 14, needle end 16 extending from the main shaft 14 and needle tip 18 adjacent the needle
end 16. Needle body 12 may be curved along its length through an arc of curvature ranging from
about 30° to about 270°. Alternatively, needle body 12 may be straight. Needle body 12 defines
longitudinal axis “y” which extends along the length of the needle body 12 and transverse axes “x”
15 and “z”. Transverse axes “x” and “z” correspond to the height and width dimensions of needle
body 12.

With reference to FIGS. 2-4, in conjunction with FIG. 1, main shaft 14 of needle
body 12 is four sided consisting of opposed planar surfaces 20 interconnected by arcuate side
surfaces 22. Main shaft 14 defines a height “H” (corresponding to an x-dimension) (FIG. 2) and a
20 width “W” (corresponding to a z-dimension) (FIG. 3). The preferred height to width ratio H/W
ranges from about 0.50 - 1.00, preferably about 0.75. This pronounced ratio greatly increases the
strength of the needle. The cross-section of main shaft 14 facilitates handling by the surgeon and

manipulation with a needle holder, e.g., needle forceps. Main shaft 14 may also be square in cross-section or circular.

Main shaft 14 includes means for attaching a suture to needle 10. The preferred means includes an enclosed channel 24 (FIG. 1) dimensioned for reception of a suture end of a suture. A blind hole maybe used alternatively for suture reception. Channel 24 or hole may be closed about the suture end through conventional swaging or crimping processes to secure the suture to elongated needle body 12. The dimensioning of channel 24 or hole of main shaft 14 may be selected to provide for permanent (non-detachable) or detachable securement of the suture to needle body 12. The type of securement effectuated is also dependent upon the swaging force employed during the attachment process. It is further envisioned that main shaft 14 may be provided with a U-shaped channel. Alternatively, adhesive suture attachment methodologies are also envisioned.

Referring now to FIGS. 2, 3 and 5, needle end 16 will be discussed in detail. Needle end 16 includes an enlarged needle head which is advantageously dimensioned to reduce the penetration force required to penetrate tissue while optimizing needle strength. Specifically, needle end 16 includes a plurality of concave surfaces 26 obliquely arranged relative to the longitudinal axis "y" contiguously extending and outwardly tapering from needle tip 18 to main shaft 14. Preferably four concave surfaces 26 are provided to provide a general diamond shape cross-section as depicted in FIG. 5. Adjacent concave surfaces 26 define cutting edges 28 along their lines of intersection. The maximum cross-sectional dimension of needle end 16 is along its approximate mid-section (along lines 5-5 of FIG. 3) and defines a width "W1" greater than a corresponding maximum width "W" of main shaft 14. A preferred ratio of "W1"/W ranges from

about 1.5 - 2.00, preferably about 1.75.

Referring now to FIGS. 2, 3 and 6-11, needle tip 18 will be discussed. Needle tip 18 includes a plurality (preferably four) of concave surfaces 30 arranged at an oblique angle relative to the axis "y" of the needle and intersecting to define a general diamond shape in cross-
5 section best depicted in FIG. 11. Adjacent concave surfaces 30 define cutting edges 32 along their lines of intersection. Preferably, concave surfaces 30 taper outwardly relative to axis "y" at an angle which is greater than the angle of taper of concave surfaces 26 of needle end 16.

Concave surfaces 30 of needle tip 18 extend from extreme needle point 34 to concave surfaces 26 of needle end 16 to provide four additional cutting edges 36 at the respective lines of intersection.

10

As appreciated, by virtue of the configuration of needle end 16 and needle tip 18 at least 12 cutting edges for penetrating tissue are provided, i.e., four cutting edges 30 within needle tip 18, four cutting edges 28 within needle end 16 and four cutting edges 36 at the intersection of the needle tip 18 and the needle end 16. This multiple cutting edge arrangement in combination
15 with the "hollow ground" or concave geometry of surfaces 26, 30 greatly enhances passage of the needle through tissue.

Further details of the surgical needle 10 may be appreciated by reference to the photomicrographs of FIGS. 12-13.

The surgical suturing needle of the present disclosure possesses attributes of
20 primary significance in suturing needles. Specifically, by virtue of the multiple cutting edges, the needle possesses superior needle sharpness and also demonstrates superior strength. Moreover, the cutting edges 28 extend to the widest part of needle end 16 thereby slicing, in conjunction

with the remaining edges 32, 36, the tissue as it passes through and providing an opening which is slightly larger than the cross-section of main shaft 14, consequently, significantly reducing the drag force and permitting the shaft 14 to easily pass through the tissue. The flattened cross-section of the main shaft 14 also produces a profile conducive to continued passage of the needle
5 through the tissue.

The choice of materials of surgical needle 10 is made to optimize strength, ductility and resistance to bending or breaking of the needle. However, as noted, the cross-sectional shape and dimensions of the needle contributes significantly to the physical characteristics of the needle. Preferred materials include stainless steel such as series "300" stainless steels, which typically have
10 tensile strengths of between 325,000-350,000 lbs/in.^{sup.2}, attain their high strength from undergoing cold working as the material is converted from an ingot to wire of the desired diameter.

Surgical needle 10 is manufactured through conventional cutting, coining, grinding and/or swaging processes, and may be heat treated to further enhance its strength and resistance
15 to bending.

Needle 10 is manufactured in accordance with the needle process flow described in the flow chart of FIG. 14. Specifically, the steps of manufacture are performed in the sequence of operations inclusive of operation numbers 100-280 described in the needle process flow. These operations include, inter-alia, coining the needle point, flat pressing the needle body, curving the
20 needle, removing excess flash material, electropolishing and coating.

It will be understood that various modifications may be made to the embodiments disclosed herein. Therefore, the above description should not be construed as limiting, but merely

as exemplifications of preferred embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

WHAT IS CLAIMED IS:

1. A surgical needle, which comprises:

an elongated needle body defining a longitudinal axis, the elongated needle body including a main shaft, a needle end adjacent the main shaft, and a needle tip extending from the
5 needle end and having an extreme needle point, the needle end including a plurality of concave surfaces extending from the needle tip to the main shaft, the needle tip including a plurality of concave surfaces extending from the needle point to intersect the concave surfaces of the needle end.

10 2. The surgical needle according to claim 1 wherein the concave surfaces of the needle end are obliquely arranged relative to the longitudinal axis at a first angle.

3. The surgical needle according to claim 2 wherein the concave surfaces of the needle tip are obliquely arranged relative to the longitudinal axis at a second angle greater than
15 the first angle.

4. The surgical needle according to claim 1 further including cutting edges disposed along lines of intersection of the concave surfaces of the needle end with the concave surfaces of the needle tip.

20 5. The surgical needle according to claim 4 wherein the needle end includes four intersecting concave surfaces.

6. The surgical needle according to claim 5 wherein the needle end defines a generally diamond-shape in cross-section along an axis transverse to the longitudinal axis.

5 7. The surgical needle according to claim 6 wherein the needle end defines a maximum cross-sectional dimension greater than a corresponding maximum cross-sectional dimension of the main shaft.

10 8. The surgical needle according to claim 1 wherein the needle tip includes four intersecting concave surfaces.

9. The surgical needle according to claim 8 wherein the needle tip defines a generally diamond-shape in cross-section along an axis transverse to the longitudinal axis.

15 10. The surgical needle according to claim 1 wherein the main shaft is curved along the longitudinal axis of the needle body.

11. The surgical needle according to 1 wherein the main shaft includes means for attaching a suture.

20

12. A surgical needle, which comprises:
an elongated needle body defining a longitudinal axis, the elongated needle body

including a main shaft, a needle end adjacent the main shaft, and a needle tip contiguously extending from the needle end and having an extreme needle point, the needle end including at least three non-linear intersecting surfaces extending from the needle tip to the main shaft, the needle tip including at least three non-linear intersecting surfaces extending from the needle point
5 to the needle end and intersecting the at least three non-linear surfaces of the needle end.

13. The surgical needle according to claim 12 wherein the at least three non-linear surfaces of the needle end define cutting edges along lines of intersection of adjacent surfaces thereof.

10

14. The surgical needle according to claim 12 wherein the at least three non-linear surfaces of the needle tip define cutting edges along lines of intersection of adjacent surfaces thereof.

15. The surgical needle according to claim 14 wherein the at least three non-linear intersecting surfaces of the needle end and the at least three non-linear intersecting surfaces of the needle tip define cutting edges along lines of intersection thereof.

16. The surgical needle according to claim 15 wherein the needle end includes
20 four non-linear surfaces.

17. The surgical needle according to claim 16 wherein the needle tip includes

four non-linear surfaces.

18. The surgical needle according to claim 17 wherein the four non-linear surfaces of each of the needle end and the needle tip are generally concave.

5

19. The surgical needle according to claim 12 wherein the at least three non-linear surfaces of each of the needle end and the needle tip are generally concave.




FIG. 2

FIG. 1




FIG. 3




FIG. 4 FIG. 5 FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 13




FIG. 12

Straighten and Cut to Length	100
Coin Point (ceat flash)	110
Form Body (flat press)	120
Form Channel Notch	130
Curve Needle	140
In Process QC	150
Clean Needle	160
Attach to Strip	170
Heat Treat	180
In Process QC	190
Chemical removal of Flash	200
Electro Polish	210
Clean Needle - rinse	220
In Process QC	230
Silicone Coating	240
Remove from Strip	250
Final QA	260
Packaging	270
Overhead	280

FIG. 14

