



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2608715 A1 2006/09/28

(21) **2 608 715**

(12) **DEMANDE DE BREVET CANADIEN**
CANADIAN PATENT APPLICATION

(13) **A1**

(86) Date de dépôt PCT/PCT Filing Date: 2006/05/19
(87) Date publication PCT/PCT Publication Date: 2006/09/28
(85) Entrée phase nationale/National Entry: 2007/11/16
(86) N° demande PCT/PCT Application No.: EP 2006/062439
(87) N° publication PCT/PCT Publication No.: 2006/100313
(30) Priorités/Priorities: 2005/05/20 (FR0505120);
2005/05/20 (EP05104321.4); 2005/11/08 (US60/734,659);
2005/11/08 (US60/734,637); 2005/11/08 (US60/734,658);
2005/11/08 (US60/734,634); 2005/11/08 (US60/734,627);
2005/11/08 (US60/734,636); 2005/11/08 (US60/734,657);
2005/11/08 (US60/734,635)

(51) Cl.Int./Int.Cl. *C07C 29/62*(2006.01),
C07C 31/36(2006.01), *C07C 31/42*(2006.01)

(71) Demandeur/Applicant:
SOLVAY (SOCIETE ANONYME), BE

(72) Inventeurs/Inventors:
KRAFFT, PHILIPPE, BE;
GILBEAU, PATRICK, BE;
BALTHASART, DOMINIQUE, BE;
SMETS, VALENTINE, BE


(74) Agent: ROBIC

(54) Titre : PROCEDE DE FABRICATION D'UNE CHLORHYDRINE

(54) Title: METHOD FOR MAKING A CHLOROHYDRIN

(57) Abrégé/Abstract:

The invention concerns a method for making a chlorhydrin including the following steps: (a) reacting a polyhydroxylated aliphatic hydrocarbon, an ester of polyhydroxylated hydrocarbon, or a mixture thereof, and a chlorinating agent and an organic acid to obtain a mixture containing chlorhydrin and chlorhydrin esters; (b) subjecting at least part of the mixture obtained at step (a) to one or more treatments in steps subsequent to step (a); (c) adding polyhydroxylated aliphatic hydrocarbon at least at one of the steps subsequent to step (a), so that it reacts, at a temperature not less than 20 °C, with the chlorhydrin esters so as to form at least partly polyhydroxylated aliphatic hydrocarbon esters.



(12) DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITÉ DE COOPÉRATION
EN MATIÈRE DE BREVETS (PCT)(19) Organisation Mondiale de la Propriété
Intellectuelle
Bureau international(43) Date de la publication internationale
28 septembre 2006 (28.09.2006)

PCT

(10) Numéro de publication internationale
WO 2006/100313 A3

(51) Classification internationale des brevets :
C07C 29/62 (2006.01) *C07C 31/42* (2006.01)
C07C 31/36 (2006.01)

(21) Numéro de la demande internationale :
PCT/EP2006/062439

(22) Date de dépôt international : 19 mai 2006 (19.05.2006)

(25) Langue de dépôt : français

(26) Langue de publication : français

(30) Données relatives à la priorité :

05104321.4	20 mai 2005 (20.05.2005)	EP
0505120	20 mai 2005 (20.05.2005)	FR
60/734,635	8 novembre 2005 (08.11.2005)	US
60/734,657	8 novembre 2005 (08.11.2005)	US
60/734,636	8 novembre 2005 (08.11.2005)	US
60/734,627	8 novembre 2005 (08.11.2005)	US
60/734,634	8 novembre 2005 (08.11.2005)	US
60/734,658	8 novembre 2005 (08.11.2005)	US
60/734,637	8 novembre 2005 (08.11.2005)	US
60/734,659	8 novembre 2005 (08.11.2005)	US

(71) Déposant (pour tous les États désignés sauf US) :
SOLVAY (Société Anonyme) [BE/BE]; Rue du Prince Albert, 33, B-1050 Brussels (BE).

(72) Inventeurs; et

(75) Inventeurs/Déposants (pour US seulement) : **KRAFFT, Philippe** [FR/BE]; Avenue Simonne, 21a, B-1640 Rhode Saint Genèse (BE). **GILBEAU, Patrick** [BE/BE]; Chemin de la Fontenelle, 20, B-7090 Braine-le-Comte (BE). **BALTHASART, Dominique** [BE/BE]; Rue Du Château Beyaerd, 150, B-1120 Bruxelles (BE). **SMETS, Valentine** [BE/BE]; 27, Avenue Charles Gilisquet, B-1030 Bruxelles (BE).

(74) Mandataires : **VANDE GUCHT, Anne** etc.; **SOLVAY** (Société Anonyme), Intellectual Property Department, Rue De Ransbeek, 310, B-1120 Brussels (BE).

(81) États désignés (sauf indication contraire, pour tout titre de protection nationale disponible) : AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) États désignés (sauf indication contraire, pour tout titre de protection régionale disponible) : ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), eurasien (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), européen (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Publiée :
— avec rapport de recherche internationale
— avant l'expiration du délai prévu pour la modification des revendications, sera republiée si des modifications sont reçues
— sur requête du déposant, avant l'expiration du délai mentionné à l'article 21.2)a)

(88) Date de publication du rapport de recherche internationale: 9 novembre 2006

En ce qui concerne les codes à deux lettres et autres abréviations, se référer aux "Notes explicatives relatives aux codes et abréviations" figurant au début de chaque numéro ordinaire de la Gazette du PCT.

(54) Title: METHOD FOR MAKING A CHLOROHYDRIN

(54) Titre : PROCEDE DE FABRICATION D'UNE CHLORHYDRINE

WO 2006/100313 A3

(57) **Abstract:** The invention concerns a method for making a chlorohydrin including the following steps: (a) reacting a polyhydroxylated aliphatic hydrocarbon, an ester of polyhydroxylated hydrocarbon, or a mixture thereof, and a chlorinating agent and an organic acid to obtain a mixture containing chlorohydrin and chlorohydrin esters; (b) subjecting at least part of the mixture obtained at step (a) to one or more treatments in steps subsequent to step (a); (c) adding polyhydroxylated aliphatic hydrocarbon at least at one of the steps subsequent to step (a), so that it reacts, at a temperature not less than 20 °C, with the chlorohydrin esters so as to form at least partly polyhydroxylated aliphatic hydrocarbon esters.

(57) **Abbrégé :** Procédé de fabrication d'une chlorhydrine comprenant les étapes suivantes: (a) on fait réagir un hydrocarbure aliphatique polyhydroxylé, un ester d'un hydrocarbure aliphatique polyhydroxylé, ou un mélange d'entre eux, avec un agent de chloration et un acide organique de façon à obtenir un mélange contenant de la chlorhydrine et des esters de la chlorhydrine; (b) on soumet au moins une partie du mélange obtenu à l'étape (a) à un ou plusieurs traitements dans des étapes ultérieures à l'étape (a); (c) on ajoute de l'hydrocarbure aliphatique polyhydroxylé à au moins une des étapes ultérieures à l'étape (a), pour qu'il réagisse, à une température supérieure ou égale à 20°C, avec les esters de la chlorhydrine de façon à former au moins partiellement des esters de l'hydrocarbure aliphatique polyhydroxylé.

METHOD FOR MAKING A CHLOROHYDRIN

The present patent application claims the benefit of patent application FR 05.05120 and of patent application EP 05104321.4, both filed on 20 May 2005, and of provisional US patent applications 60/734659, 60/734627, 60/734657, 60/734658, 60/734635, 60/734634, 60/734637 and 60/734636, all filed on 8 November 2005, the content of all of which is incorporated here by reference.

The present invention relates to a process for preparing a chlorhydrin.

Chlorhydrins are reaction intermediates in the preparation of epoxides.

10 Dichloropropanol, for example, is a reaction intermediate in the preparation of epichlorohydrin and of epoxy resins (Kirk-Othmer Encyclopedia of Chemical Technology, Fourth Edition, 1992, Vol. 2, page 156, John Wiley & Sons, Inc.).

According to known processes it is possible to obtain dichloropropanol in particular by hypochlorinating allyl chloride, by chlorinating allyl alcohol and by hydrochlorinating glycerol. This latter process has the advantage that the dichloropropanol can be obtained starting from fossil raw materials or from renewable raw materials, and it is known that natural petrochemical resources, from which the fossil materials are obtained, such as petroleum, natural gas or coal, for example, are limited in their terrestrial availability.

20 International application WO 2005/021476 describes a process for preparing dichloropropanol by reacting glycerol with gaseous hydrogen chloride in the presence of acetic acid as catalyst. The dichloropropanol is separated off by distillation. Application WO 2005/054167 of SOLVAY SA describes a process for preparing dichloropropanol by reacting glycerol with hydrogen chloride in the presence of an acid such as adipic acid as catalyst. The dichloropropanol is again separated off by distillation. In both processes the presence of dichloropropanol esters does not make it possible to optimize the step of separating the dichloropropanol and the other constituents of the reaction mixture.

The aim of the invention is to provide a process for preparing a chlorhydrin that does not exhibit these drawbacks.

30 The invention accordingly provides a process for preparing a chlorhydrin, comprising the following steps :

(a) a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof is reacted with a chlorinating agent and an organic acid so as to give a mixture containing the chlorohydrin and esters of the chlorohydrin

5 (b) at least part of the mixture obtained in step (a) is subjected to one or more treatments in steps subsequent to step (a)

(c) polyhydroxylated aliphatic hydrocarbon is added to at least one of the steps subsequent to step (a), so as to react, at a temperature greater than or equal to 20°C, with the esters of the chlorohydrin, so as to form, at least partly, esters of the polyhydroxylated aliphatic hydrocarbon.

10

It has been found that the addition of the polyhydroxylated aliphatic hydrocarbon to step (c), subsequent to the transesterification reaction between the polyhydroxylated aliphatic hydrocarbon and the esters of the chlorohydrin,

15 exhibits the following advantages, among others :

1) an increase in the yield of the separation process subsequent to the formation of an additional amount of the chlorohydrin

2) a reduction in the losses of catalyst present in step (a) of the process according to the invention, when the organic acid catalyzes the reaction of step (a)

20 3) a reduction of the losses of chlorinating agent optionally present in the mixture obtained in step (a).

25 The term " polyhydroxylated aliphatic hydrocarbon " refers to a hydrocarbon which contains at least two hydroxyl groups attached to two different saturated carbon atoms. The polyhydroxylated aliphatic hydrocarbon may contain, but is not limited to, from 2 to 60 carbon atoms.

30 Each of the carbons of a polyhydroxylated aliphatic hydrocarbon bearing the hydroxyl functional group (OH) cannot possess more than one OH group and must have sp³ hybridization. The carbon atom carrying the OH group may be primary, secondary or tertiary. The polyhydroxylated aliphatic hydrocarbon used in the present invention must contain at least two sp³-hybridized carbon atoms carrying an OH group. The polyhydroxylated aliphatic hydrocarbon includes any hydrocarbon containing a vicinal diol (1,2-diol) or a vicinal triol (1,2,3-triol), including the higher, vicinal or contiguous orders of these repeating units. The definition of the polyhydroxylated aliphatic hydrocarbon also 35 includes, for example, one or more 1,3-, 1,4-, 1,5- and 1,6-diol functional groups. The polyhydroxylated aliphatic hydrocarbon may also be a polymer

such as polyvinyl alcohol. Geminal diols, for example, are excluded from this class of polyhydroxylated aliphatic hydrocarbons.

The polyhydroxylated aliphatic hydrocarbons may contain aromatic moieties or heteroatoms, including, for example, heteroatoms of halogen, 5 sulphur, phosphorus, nitrogen, oxygen, silicon and boron type, and mixtures thereof.

Polyhydroxylated aliphatic hydrocarbons which can be used in the present invention comprise, for example, 1,2-ethanediol (ethylene glycol), 1,2-propanediol (propylene glycol), 1,3-propanediol, 1-chloro-2,3-propanediol 10 (chloropropanediol), 2-chloro-1,3-propanediol (chloropropanediol), 1,4-butanediol, 1,5-pantanediol, cyclohexanediols, 1,2-butanediol, 1,2-cyclohexanedimethanol, 1,2,3-propanetriol (also known as "glycerol" or "glycerin"), and mixtures thereof. With preference the polyhydroxylated aliphatic hydrocarbon used in the present invention includes, for example, 15 1,2-ethanediol, 1,2-propanediol, 1,3-propanediol, chloropropanediol and 1,2,3-propanetriol, and mixtures of at least two thereof. More preferably the polyhydroxylated aliphatic hydrocarbon used in the present invention includes, for example, 1,2-ethanediol, 1,2-propanediol, chloropropanediol and 20 1,2,3-propanetriol, and mixtures of at least two thereof. 1,2,3-Propanetriol or glycerol is the most preferred.

The esters of the polyhydroxylated aliphatic hydrocarbon may be present in the polyhydroxylated aliphatic hydrocarbon and/or may be produced in the process for preparing the chlorohydrin and/or may be prepared prior to the process for preparing the chlorohydrin. Examples of esters of the 25 polyhydroxylated aliphatic hydrocarbon comprise ethylene glycol monoacetate, propanediol monoacetates, glycerol monoacetates, glycerol monostearates, glycerol diacetates and mixtures thereof.

The term "chlorohydrin" is used here in order to describe a compound containing at least one hydroxyl group and at least one chlorine atom attached to 30 different saturated carbon atoms. A chlorohydrin which contains at least two hydroxyl groups is also a polyhydroxylated aliphatic hydrocarbon. Accordingly the starting material and the product of the reaction may each be chlorohydrins. In that case the "product" chlorohydrin is more chlorinated than the starting chlorohydrin, in other words has more chlorine atoms and fewer hydroxyl 35 groups than the starting chlorohydrin. Preferred chlorohydrins are chloroethanol, chloropropanol, chloropropanediol, dichloropropanol and

mixtures of at least two thereof. Dichloropropanol is particularly preferred. Chlorohydrins which are more particularly preferred are 2-chloroethanol, 1-chloropropan-2-ol, 2-chloropropan-1-ol, 1-chloropropane-2,3-diol, 2-chloropropane-1,3-diol, 1,3-dichloropropan-2-ol, 2,3-dichloropropan-1-ol and mixtures of at least two thereof.

5 The polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon, or the mixture thereof in the process according to the invention may be obtained starting from fossil raw materials or starting from renewable raw materials, preferably starting from renewable raw materials.

10 By fossil raw materials are meant materials obtained from the processing of petrochemical natural resources, such as petroleum, natural gas and coal, for example. Among these materials preference is given to organic compounds containing 2 and 3 carbon atoms. When the polyhydroxylated aliphatic hydrocarbon is glycerol, allyl chloride, allyl alcohol and "synthetic" glycerol are particularly preferred. By "synthetic" glycerol is meant a glycerol generally obtained from petrochemical resources. When the polyhydroxylated aliphatic hydrocarbon is ethylene glycol, ethylene and "synthetic" ethylene glycol are particularly preferred. By "synthetic" ethylene glycol is meant an ethylene glycol generally obtained from petrochemical resources. When the 15 polyhydroxylated aliphatic hydrocarbon is propylene glycol, propylene and "synthetic" propylene glycol are particularly preferred. By "synthetic" propylene glycol is meant a propylene glycol generally obtained from petrochemical resources.

20

25 By renewable raw materials are meant materials obtained from the processing of renewable natural resources. Among these materials preference is given to "natural" ethylene glycol, "natural" propylene glycol and "natural" glycerol. "Natural" ethylene glycol, propylene glycol and glycerol are obtained for example by conversion of sugars by thermochemical processes, it being possible for these sugars to be obtained starting from biomass, as described in 30 "Industrial Bioproducts : Today and Tomorrow", Energetics, Incorporated for the U.S. Department of Energy, Office of Energy Efficiency and Renewable Energy, Office of the Biomass Program, July 2003, pages 49, 52 to 56. One of these processes is, for example, the catalytic hydrogenolysis of sorbitol obtained by thermochemical conversion of glucose. Another process is, for example, the 35 catalytic hydrogenolysis of xylitol obtained by hydrogenation of xylose. The xylose may for example be obtained by hydrolysis of the hemicellulose present

in maize fibres. By "natural glycerol" or "glycerol obtained from renewable raw materials" is meant, in particular, glycerol obtained during the production of biodiesel or else glycerol obtained during conversions of animal or vegetable oils or fats in general, such as saponification, transesterification or hydrolysis reactions.

5 Among the oils which can be used to prepare natural glycerol, mention may be made of all common oils, such as palm oil, palm kernel oil, copra oil, babassu oil, former or new (low erucic acid) colza oil, sunflower oil, maize oil, castor oil and cotton oil, peanut oil, soya bean oil, linseed oil and crambe oil, and 10 all oils obtained, for example, from sunflower plants or colza plants obtained by genetic modification or hybridization.

It is also possible to employ used frying oils, various animal oils, such as fish oils, tallow, lard and even squaring greases.

15 Among the oils used mention may also be made of oils which have been partly modified by means, for example, of polymerization or oligomerization, such as, for example, the "stand oils" of linseed oil and of sunflower oil, and blown vegetable oils.

20 A particularly suitable glycerol may be obtained during the conversion of animal fats. Another particularly suitable glycerol may be obtained during the production of biodiesel. A third, very suitable glycerol may be obtained during the conversion of animal or vegetable oils or fats by transesterification in the presence of a heterogeneous catalyst, as described in documents FR 2752242, FR 2869612 and FR 2869613. More specifically, the heterogeneous catalyst is selected from mixed oxides of aluminium and zinc, mixed oxides of zinc and 25 titanium, mixed oxides of zinc, titanium and aluminium, and mixed oxides of bismuth and aluminium, and the heterogeneous catalyst is employed in the form of a fixed bed. This latter process can be a process for producing biodiesel.

30 In the process for preparing a chlorohydrin according to the invention, the polyhydroxylated aliphatic hydrocarbon may be as described in the patent application entitled "Process for preparing chlorohydrin by converting polyhydroxylated aliphatic hydrocarbons", filed in the name of SOLVAY SA on the same day as the present application, and the content of which is incorporated here by reference.

35 Particular mention is made of a process for preparing a chlorohydrin wherein a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof whose total metal

content, expressed in elemental form, is greater than or equal to 0.1 $\mu\text{g}/\text{kg}$ and less than or equal to 1000 mg/kg is reacted with a chlorinating agent.

In the process according to the invention it is preferred to use glycerol obtained starting from renewable raw materials.

5 In the process for preparing a chlorohydrin according to the invention, the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof may be a crude product or a purified product, such as are specifically disclosed in application WO 2005/054167 of SOLVAY SA, from page 2 line 8 to page 4 line 2.

10 In the process for preparing a chlorohydrin according to the invention, the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof may have an alkali metal and/or alkaline earth metal content of less than or equal to 5 g/kg , as described in the application entitled "Process for preparing a chlorohydrin by chlorinating a 15 polyhydroxylated aliphatic hydrocarbon", filed in the name of SOLVAY SA on the same day as the present application, and whose content is incorporated here by reference. The alkali metals may be selected from lithium, sodium, potassium, rubidium and cesium and the alkaline earth metals may be selected from magnesium, calcium, strontium and barium.

20 In the process according to the invention, the alkali metal and/or alkaline earth metal content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is less than or equal to 5 g/kg , often less than or equal to 1 g/kg , more particularly less than or equal to 0.5 g/kg and in certain cases less than or equal to 0.01 g/kg . The alkali 25 metal and/or alkaline earth metal content of the glycerol is generally greater than or equal to 0.1 $\mu\text{g}/\text{kg}$.

In the process according to the invention the alkali metals are generally lithium, sodium, potassium and cesium, often sodium and potassium, and frequently sodium.

30 In the process for preparing a chlorohydrin according to the invention, the lithium content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is generally less than or equal to 1 g/kg , often less than or equal to 0.1 g/kg and more particularly less than or equal to 2 mg/kg . This content is generally greater than or equal to 35 0.1 $\mu\text{g}/\text{kg}$.

In the process according to the invention, the sodium content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is generally less than or equal to 1 g/kg, often less than or equal to 0.1 g/kg and more particularly less than or equal to 5 2 mg/kg. This content is generally greater than or equal to 0.1 μ g/kg.

In the process according to the invention, the potassium content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is generally less than or equal to 1 g/kg, often less than or equal to 0.1 g/kg and more particularly less than or equal to 10 2 mg/kg. This content is generally greater than or equal to 0.1 μ g/kg.

In the process according to the invention, the rubidium content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is generally less than or equal to 1 g/kg, often less than or equal to 0.1 g/kg and more particularly less than or equal to 15 2 mg/kg. This content is generally greater than or equal to 0.1 μ g/kg.

In the process according to the invention, the cesium content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is generally less than or equal to 1 g/kg, often less than or equal to 0.1 g/kg and more particularly less than or equal to 20 2 mg/kg. This content is generally greater than or equal to 0.1 μ g/kg.

In the process according to the invention the alkaline earth metal elements are generally magnesium, calcium, strontium and barium, often magnesium and calcium and frequently calcium.

In the process according to the invention, the magnesium content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is generally less than or equal to 1 g/kg, often less than or equal to 0.1 g/kg and more particularly less than or equal to 25 2 mg/kg. This content is generally greater than or equal to 0.1 μ g/kg.

In the process according to the invention, the calcium content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is generally less than or equal to 1 g/kg, often less than or equal to 0.1 g/kg and more particularly less than or equal to 30 2 mg/kg. This content is generally greater than or equal to 0.1 μ g/kg.

In the process according to the invention, the strontium content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is generally less than or equal to 1 g/kg,

often less than or equal to 0.1 g/kg and more particularly less than or equal to 2 mg/kg. This content is generally greater than or equal to 0.1 μ g/kg.

5 In the process according to the invention, the barium content of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is generally less than or equal to 1 g/kg, often less than or equal to 0.1 g/kg and more particularly less than or equal to 2 mg/kg. This content is generally greater than or equal to 0.1 μ g/kg.

10 In the process according to the invention the alkali and/or alkaline earth metals are generally present in the form of salts, frequently in the form of chlorides, sulphates and mixtures thereof. Sodium chloride is the most often encountered.

15 In the process for preparing a chlorohydrin according to the invention, the chlorinating agent may be as described in application WO 2005/054167 of SOLVAY SA, from page 4 line 25 to page 6 line 2.

20 In the process for preparing a chlorohydrin according to the invention, the chlorinating agent may be hydrogen chloride as described in application WO 2005/054167 of SOLVAY SA, from page 4 line 30 to page 6 line 2.

25 Particular mention is made of a chlorinating agent, which may be aqueous hydrochloric acid or hydrogen chloride which is preferably anhydrous. The hydrogen chloride may originate from a process of pyrolysing organic chlorine compounds, such as, for example, from vinyl chloride preparation, from a process for preparing 4,4-methylenediphenyl diisocyanate (MDI) or toluene diisocyanate (TDI), from metal pickling processes or from the reaction of an inorganic acid such as sulphuric or phosphoric acid with a metal chloride such as sodium chloride, potassium chloride or calcium chloride.

30 In one advantageous embodiment of the process for preparing a chlorohydrin according to the invention, the chlorinating agent is gaseous hydrogen chloride or an aqueous solution of hydrogen chloride, or a combination of the two.

35 In the process for preparing a chlorohydrin according to the invention, the hydrogen chloride may be an aqueous solution of hydrogen chloride or of the hydrogen chloride, preferably anhydrous, obtained from plant for preparing allyl chloride and/or for preparing chloromethanes and/or for chlorinolysis and/or for high-temperature oxidation of chlorine compounds, as described in the application entitled "Process for preparing a chlorohydrin by reacting a polyhydroxylated aliphatic hydrocarbon with a chlorinating agent", filed in the

name of SOLVAY SA on the same day as the present application, and the content of which is incorporated here by reference.

Particular mention is made of a process for preparing a chlorohydrin from a polyhydroxylated aliphatic hydrocarbon, from an ester of a polyhydroxylated aliphatic hydrocarbon or from a mixture thereof, and from a chlorinating agent, the chlorinating agent comprising at least one of the following compounds : nitrogen, oxygen, hydrogen, chlorine, an organic hydrocarbon compound, an organic halogen compound, an organic oxygen compound and a metal.

Particular mention is made of an organic hydrocarbon compound selected from saturated and unsaturated aliphatic and aromatic hydrocarbons and mixtures thereof.

Particular mention is made of an unsaturated aliphatic hydrocarbon selected from acetylene, ethylene, propylene, butene, propadiene, methylacetylene and mixtures thereof, of a saturated aliphatic hydrocarbon selected from methane, ethane, propane, butane and mixtures thereof and of an aromatic hydrocarbon which is benzene.

Particular mention is made of an organic halogen compound which is an organic chlorine compound selected from chloromethanes, chloroethanes, chloropropanes, chlorobutanes, vinyl chloride, vinylidene chloride, monochloropropenes, perchloroethylene, trichloroethylene, chlorobutadienes, chlorobenzenes and mixtures thereof.

Particular mention is made of an organic halogen compound which is an organic fluorine compound selected from fluoromethanes, fluoroethanes, vinyl fluoride, vinylidene fluoride and mixtures thereof.

Particular mention is made of an organic oxygen compound selected from alcohols, chloroalcohols, chloroethers and mixtures thereof.

Particular mention is made of a metal selected from alkali metals, alkaline earth metals, iron, nickel, copper, lead, arsenic, cobalt, titanium, cadmium, antimony, mercury, zinc, selenium, aluminium, bismuth and mixtures thereof.

Mention is made more particularly of a process wherein the chlorinating agent is obtained at least partly from a process for preparing allyl chloride and/or a process for preparing chloromethanes and/or a process of chlorinolysis and/or a process for oxidizing chlorine compounds at a temperature greater than or equal to 800°C.

In one advantageous embodiment of the process for preparing a chlorohydrin according to the invention, the hydrogen chloride is an aqueous solution of hydrogen chloride, and does not contain gaseous hydrogen chloride.

In the process for preparing a chlorohydrin according to the invention, the reaction of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof with the chlorinating agent may be carried out in a reactor as described in application WO 2005/054167 of SOLVAY SA on page 6 lines 3 to 23.

Mention is made particularly of plant made of or covered with materials which are resistant, under the conditions of the reaction, to the chlorinating agents, in particular to hydrogen chloride. Mention is made more particularly of plant made of enamelled steel or of tantalum.

In the process for preparing a chlorohydrin according to the invention, the reaction of the polyhydroxylated aliphatic hydrocarbon, the ester of the polyhydroxylated aliphatic hydrocarbon or the mixture thereof with the chlorinating agent may be carried out in apparatus which is made of or covered with materials that are resistant to chlorinating agents, as described in the patent application entitled "Process for preparing a chlorohydrin in corrosion-resistant apparatus", filed in the name of SOLVAY SA on the same day as the present application, and the content of which is incorporated here by reference.

Particular mention is made of a process for preparing a chlorohydrin that includes a step in which a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof is subjected to reaction with a chlorinating agent containing hydrogen chloride and to at least one other step carried out in an apparatus made of or covered with materials resistant to the chlorinating agent, under the conditions in which that step is realized. Mention is made more particularly of metallic materials such as enamelled steel, gold and tantalum and of non-metallic materials such as high-density polyethylene, polypropylene, poly(vinylidene fluoride), polytetrafluoroethylene, perfluoroalkoxyalkanes and poly(perfluoropropyl vinyl ether), polysulphones and polysulphides, and unimpregnated and impregnated graphite.

In the process for preparing a chlorohydrin according to the invention, the reaction of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof with the chlorinating agent may be carried out in a reaction medium as described in the

application entitled "Continuous process for preparing chlorohydrins", filed in the name of SOLVAY SA on the same day as the present application, and the content of which is incorporated here by reference.

Particular mention is made of a continuous process for producing
5 chlorohydrin in which a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof is reacted with a chlorinating agent and an organic acid in a liquid reaction medium whose steady-state composition comprises polyhydroxylated aliphatic hydrocarbon and esters of polyhydroxylated aliphatic hydrocarbon for which the sum of the
10 amounts, expressed in moles of polyhydroxylated aliphatic hydrocarbon, is greater than 1.1 mol % and less than or equal to 30 mol %, the percentage being based on the organic part of the liquid reaction medium.

The organic part of the liquid reaction medium consists of all of the
15 organic compounds of the liquid reaction medium, in other words the compounds whose molecule contains at least one carbon atom.

In the process for preparing a chlorohydrin according to the invention, the reaction of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof and the chlorinating agent may be carried out in the presence of a catalyst as described in
20 application WO 2005/054167 of SOLVAY SA from page 6 line 28 to page 8 line 5.

Mention is made particularly of a catalyst based on a carboxylic acid or on a carboxylic acid derivative having an atmospheric boiling point of greater than or equal to 200°C, especially adipic acid and derivatives of adipic acid.

25 In the process for preparing a chlorohydrin according to the invention, the reaction of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof and the chlorinating agent may be carried out at a catalyst concentration, temperature and pressure and for residence times as described in the application
30 WO 2005/054167 of SOLVAY SA from page 8 line 6 to page 10 line 10.

Mention is made particularly of a temperature of at least 20°C and not more than 160°C, of a pressure of at least 0.3 bar and not more than 100 bar and of a residence time of at least 1 h and not more than 50 h.

35 In the process for preparing a chlorohydrin according to the invention, the reaction of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof with the

chlorinating agent may be carried out in the presence of a solvent as described in application WO 2005/054167 of SOLVAY SA at page 11 lines 12 to 36.

Mention is made particularly of organic solvents such as a chlorinated organic solvent, an alcohol, a ketone, an ester or an ether, a non-aqueous solvent 5 which is miscible with the polyhydroxylated aliphatic hydrocarbon, such as chloroethanol, chloropropanol, chloropropanediol, dichloropropanol, dioxane, phenol, cresol and mixtures of chloropropanediol and dichloropropanol, or heavy products of the reaction such as at least partially chlorinated and/or esterified oligomers of the polyhydroxylated aliphatic hydrocarbon.

10 In the process for preparing a chlorohydrin according to the invention, the reaction of the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof with the chlorinating agent may be carried out in the presence of a liquid phase comprising heavy compounds other than the polyhydroxylated aliphatic 15 hydrocarbon, as described in the application entitled "Process for preparing a chlorohydrin in a liquid phase", filed in the name of SOLVAY SA on the same day as the present application, and the content of which is incorporated here by reference.

Particular mention is made of a process for preparing a chlorohydrin 20 wherein a polyhydroxylated aliphatic hydrocarbon, an ester of polyhydroxylated aliphatic hydrocarbon or a mixture thereof is subjected to reaction with a chlorinating agent in the presence of a liquid phase comprising heavy compounds other than the polyhydroxylated aliphatic hydrocarbon and having a boiling temperature under a pressure of 1 bar absolute of at least 15°C more than 25 the boiling temperature of the chlorohydrin under a pressure of 1 bar absolute.

In the process for preparing a chlorohydrin according to the invention the reaction of the polyhydroxylated aliphatic hydrocarbon, an ester of the polyhydroxylated aliphatic hydrocarbon or a mixture thereof with the chlorinating agent is preferably carried out in a liquid reaction medium. The 30 liquid reaction medium may be a single-phase or multi-phase medium.

The liquid reaction medium is composed of all of the dissolved or dispersed solid compounds, dissolved or dispersed liquid compounds and dissolved or dispersed gaseous compounds at the temperature of the reaction.

The reaction medium comprises the reactants, the catalyst, the solvent, the 35 impurities present in the reactants, in the solvent and in the catalyst, the reaction intermediates, the products and the by-products of the reaction.

By reactants are meant the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon and the chlorinating agent.

Among the impurities present in the polyhydroxylated aliphatic hydrocarbon mention may be made of carboxylic acids, salts of carboxylic acids, 5 esters of fatty acid with the polyhydroxylated aliphatic hydrocarbon, esters of fatty acids with the alcohols used in the transesterification, and inorganic salts such as alkali metal or alkaline earth metal sulphates and chlorides.

When the polyhydroxylated aliphatic hydrocarbon is glycerol, the 10 impurities in the glycerol that may be mentioned include carboxylic acids, salts of carboxylic acids, fatty acid esters such as mono-, di- and triglycerides, esters of fatty acids with the alcohols used in the transesterification and inorganic salts such as alkali metal or alkaline earth metal sulphates and chlorides.

Among the reaction intermediates mention may be made of 15 monochlorohydrins of the polyhydroxylated aliphatic hydrocarbon and their esters and/or polyesters, the esters and/or polyesters of the polyhydroxylated aliphatic hydrocarbon and the esters of polychlorohydrins.

When the chlorohydrin is dichloropropanol, the reaction intermediates that 20 may be mentioned include glycerol monochlorohydrin and its esters and/or polyesters, the esters and/or polyesters of glycerol and the esters of dichloropropanol.

The ester of polyhydroxylated aliphatic hydrocarbon may therefore be, at each instance, a reactant, an impurity of the polyhydroxylated aliphatic hydrocarbon or a reaction intermediate.

By products of the reaction are meant the chlorohydrin and water. The 25 water may be the water formed in the chlorination reaction and/or water introduced into the process, for example via the polyhydroxylated aliphatic hydrocarbon and/or the chlorinating agent, as described in the application WO 2005/054167 of SOLVAY SA at page 2 lines 22 to 28 to page 3 lines 20 to 25, at page 5 lines 7 to 31 and at page 12 lines 14 to 19.

30 Among the by-products mention may be made for example of the partially chlorinated and/or esterified oligomers of the polyhydroxylated aliphatic hydrocarbon.

When the polyhydroxylated aliphatic hydrocarbon is glycerol, the by-products that may be mentioned include, for example, the partially chlorinated 35 and/or esterified oligomers of glycerol.

The reaction intermediates and the by-products may be formed in the different steps of the process, such as, for example, during the step of preparing the chlorohydrin and during the steps of separating off the chlorohydrin.

The liquid reaction mixture may therefore contain the polyhydroxylated 5 aliphatic hydrocarbon, the chlorinating agent in solution or dispersion in the form of bubbles, the catalyst, the solvent, the impurities present in the reactants, in the solvent and in the catalyst, such as dissolved or solid salts, for example, the reaction intermediates, the products and the by-products of the reaction.

Steps (a), (b) and (c) of the process according to the invention may be 10 carried out in batch mode or in continuous mode. Preference is given to carrying out all of the steps in continuous mode.

In the process according to the invention, the separation of the chlorohydrin and of the other compounds from the reaction mixture may be carried out in accordance with the methods as described in the application 15 WO 2005/054167 of SOLVAY SA from page 12 line 1 to page 16 line 35 and page 18 lines 6 to 13. These other compounds are those mentioned above and include unconsumed reactants, the impurities present in the reactants, the catalyst, the solvent, the reaction intermediates, the water and the by-products of the reaction.

20 Particular mention is made of separation by azeotropic distillation of a water/chlorohydrin/chlorinating agent mixture under conditions which minimize the losses of chlorinating agent, followed by isolation of the chlorohydrin by phase separation.

In the process for preparing a chlorohydrin according to the invention, the 25 isolation of the chlorohydrin and of the other compounds from the reaction mixture may be carried out in accordance with methods of the kind described in patent application EP 05104321.4, filed in the name of SOLVAY SA on 20/05/2005 and the content of which is incorporated here by reference.

Particular mention is made of a separation method including at least one 30 separating operation intended to remove the salt from the liquid phase.

Particular mention is made of a process for preparing a chlorohydrin by reacting a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof with a chlorinating agent wherein the polyhydroxylated aliphatic hydrocarbon, an ester of the 35 polyhydroxylated aliphatic hydrocarbon or a mixture thereof that is used comprises at least one solid or dissolved metal salt, the process including a

separation operation intended to remove part of the metal salt. Mention is made more particularly of a process for preparing a chlorohydrin by reacting a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof with a chlorinating agent wherein the

5 polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof that is used comprises at least one chloride and/or a sodium and/or potassium sulphate and in which the separating operation intended to remove part of the metal salt is a filtering operation. Particular mention is also made of a process for preparing a chlorohydrin wherein (a) a

10 polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof is subjected to reaction with a chlorinating agent in a reaction mixture, (b) continuously or periodically, a fraction of the reaction mixture containing at least water and the chlorohydrin is removed, (c) at least a part of the fraction obtained in step (b) is introduced into a distillation

15 step and (d) the reflux ratio of the distillation step is controlled by providing water to the said distillation step. Mention is made very particularly of a process for preparing a chlorohydrin wherein (a) a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof is subjected to reaction with hydrogen chloride in a reaction mixture, (b)

20 continuously or periodically, a fraction of the reaction mixture containing at least water and chlorohydrin is removed, (c) at least part of the fraction obtained in step (b) is introduced into a distillation step in which the ratio between the hydrogen chloride concentration and the water concentration in the fraction introduced into the distillation step is smaller than the hydrogen chloride/water

25 concentration ratio in the binary azeotropic hydrogen chloride/water composition at the distillation temperature and pressure.

In the process for preparing a chlorohydrin according to the invention, the separation of the chlorohydrin and the other compounds from the reaction mixture from chlorination of the polyhydroxylated aliphatic hydrocarbon may be carried out in accordance with methods as described in the application entitled "Process for preparing a chlorohydrin starting from a polyhydroxylated aliphatic hydrocarbon", filed in the name of SOLVAY SA on the same day as the present application, and the content of which is incorporated here by reference.

35 Particular mention is made of a process for preparing chlorohydrin by reacting a polyhydroxylated aliphatic hydrocarbon, an ester of a

polyhydroxylated aliphatic hydrocarbon or a mixture thereof with a chlorinating agent in a reactor which is supplied with one or more liquid streams containing less than 50 % by weight of the polyhydroxylated aliphatic hydrocarbon, of the ester of polyhydroxylated aliphatic hydrocarbon or of the mixture thereof relative to the weight of the entirety of the liquid streams introduced into the reactor.

More particular mention is made of a process comprising the following steps : (a) a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof is reacted with a chlorinating agent so as to give at least one mixture containing the chlorohydrin, water and the chlorinating agent, (b) at least a fraction of the mixture formed in step (a) is removed, and (c) the fraction removed in step (b) is subjected to an operation of distillation and/or stripping wherein the polyhydroxylated aliphatic hydrocarbon is added in order to isolate, from the fraction removed in step (b), a mixture containing water and the chlorohydrin and exhibiting a reduced chlorinating agent content as compared with the fraction removed in step (b).

In the process for preparing a chlorohydrin according to the invention, the separation of the chlorohydrin and of the other compounds from the reaction mixture from chlorination of the polyhydroxylated aliphatic hydrocarbon may be carried out in accordance with methods as described in the application entitled "Process for converting polyhydroxylated aliphatic hydrocarbons into chlorohydrins", filed in the name of SOLVAY SA on the same day as the present application, and the content of which is incorporated here by reference. Particular mention is made of a process for preparing a chlorohydrin that comprises the following steps : (a) a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof is reacted with a chlorinating agent so as to give a mixture containing the chlorohydrin, chlorohydrin esters and water, (b) at least a fraction of the mixture obtained in step (a) is subjected to a distillation and/or stripping treatment so as to give a portion concentrated in water, in chlorohydrin and in chlorohydrin esters, and (c) at least a fraction of the portion obtained in step (b) is subjected to a separating operation in the presence of at least one additive so as to obtain a moiety concentrated in chlorohydrin and in chlorohydrin esters and containing less than 40 % by weight of water.

The separating operation is more particularly a decantation.

In the process for preparing a chlorohydrin according to the invention, the isolation and the treatment of the other compounds of the reaction mixture may be carried out in accordance with methods as described in the application entitled "Process for preparing a chlorohydrin by chlorinating a 5 polyhydroxylated aliphatic hydrocarbon", filed in the name of SOLVAY SA on the same day as the present application. A preferred treatment consists in subjecting a fraction of the by-products of the reaction to a high-temperature oxidation.

Particular mention is made of a process for preparing a chlorohydrin that 10 comprises the following steps : (a) a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof whose alkali metal and/or alkaline earth metal content is less than or equal to 5 g/kg, an chlorinating agent and an organic acid are reacted so as to give a mixture containing at least the chlorohydrin and by-products, (b) at least a portion of the 15 mixture obtained in step (a) is subjected to one or more treatments in steps subsequent to step (a), and (c) at least one of the steps subsequent to step (a) consists in an oxidation at a temperature greater than or equal to 800°C. More particular mention is made of a process wherein, in the subsequent step, a portion of the mixture obtained in step (a) is removed and this portion is 20 subjected to oxidation at a temperature greater than or equal to 800°C in the course of the removal. Particular mention is also made of a process wherein the treatment of step (b) is a separating operation selected from decantation, filtration, centrifugation, extraction, washing, evaporation, stripping, distillation, and adsorption operations or the combinations of at least two of these operations.

25 In the process according to the invention, when the chlorohydrin is chloropropanol, it is generally employed in the form of a mixture of compounds comprising the isomers of 1-chloropropan-2-ol and 2-chloropropan-1-ol. This mixture generally contains more than 1 % by weight of the two isomers, preferably more than 5 % by weight and particularly more than 50 %. The 30 mixture commonly contains less than 99.9 % by weight of the two isomers, preferably less than 95 % by weight and more particularly less than 90 % by weight. The other constituents of the mixture may be compounds originating from the processes for preparing the chloropropanol, such as residual reactants, reaction by-products, solvents and, in particular, water.

35 The mass ratio of the isomers, 1-chloropropan-2-ol and 2-chloropropan-1-ol, is commonly greater than or equal to 0.01, preferably

greater than or equal to 0.4. This ratio is commonly less than or equal to 99 and preferably less than or equal to 25.

In the process according to the invention, when the chlorohydrin is chloroethanol, it is generally employed in the form of a mixture of compounds comprising the 2-chloroethanol isomer. This mixture generally contains more than 1 % by weight of the isomer, preferably more than 5 % by weight and particularly more than 50 %. The mixture commonly contains less than 99.9 % by weight of the isomer, preferably less than 95 % by weight and more particularly less than 90 % by weight. The other constituents of the mixture may 10 be compounds originating from the processes for preparing the chloroethanol, such as residual reactants, reaction by-products, solvents and, in particular, water.

In the process according to the invention, when the chlorohydrin is chloropropanediol, it is generally employed in the form of a mixture of 15 compounds comprising the isomers of 1-chloropropane-2,3-diol and 2-chloropropane-1,3-diol. This mixture generally contains more than 1 % by weight of the two isomers, preferably more than 5 % by weight and particularly more than 50 %. The mixture commonly contains less than 99.9 % by weight of the two isomers, preferably less than 95 % by weight and more particularly less 20 than 90 % by weight. The other constituents of the mixture may be compounds originating from the processes for preparing the chloropropanediol, such as residual reactions, reaction by-products, solvents and, in particular, water.

The mass ratio between the 1-chloropropane-2,3-diol and 25 2-chloropropane-1,3-diol isomers is commonly greater than or equal to 0.01, preferably greater than or equal to 0.4. This ratio is commonly less than or equal to 99 and preferably less than or equal to 25.

In the process according to the invention, when the chlorohydrin is dichloropropanol, it is generally employed in the form of a mixture of 30 compounds comprising the isomers of 1,3-dichloropropan-2-ol and 2,3-dichloropropan-1-ol. This mixture generally contains more than 1 % by weight of the two isomers, preferably more than 5 % by weight and in particular more than 50 %. The mixture commonly contains less than 99.9 % by weight of the two isomers, preferably less than 95 % by weight and more particularly less than 90 % by weight. The other constituents of the mixture may be compounds 35 originating from the processes for preparing the dichloropropanol, such as residual reactants, reaction by-products, solvents and, in particular, water.

The mass ratio between the 1,3-dichloropropan-2-ol and 2,3-dichloropropan-1-ol isomers is commonly greater than or equal to 0.01, often greater than or equal to 0.4, frequently greater than or equal to 1.5, preferably greater than or equal to 3.0, more preferably greater than or equal to 5 7.0 and with very particular preference greater than or equal to 20.0. This ratio is commonly less than or equal to 99 and preferably less than or equal to 25.

In the process for preparing a chlorohydrin according to the invention, the organic acid may be a product originating from the process for preparing the polyhydroxylated aliphatic hydrocarbon or a product not originating from this 10 process. In this latter case the product in question may be an organic acid which is used in order to catalyse the reaction of the polyhydroxylated aliphatic hydrocarbon with the chlorinating agent. The organic acid may also be a mixture of an organic acid originating from the process for preparing the polyhydroxylated aliphatic hydrocarbon, and an organic acid not originating 15 from the process for preparing the polyhydroxylated aliphatic hydrocarbon.

In the process according to the invention, the esters of the polyhydroxylated aliphatic hydrocarbon may originate from the reaction between the polyhydroxylated aliphatic hydrocarbon and the organic acid, before, during or within the steps which follow the reaction with the chlorinating 20 agent.

In the process according to the invention, the esters of the chlorohydrin may originate from the reaction of the chlorohydrin with the organic acid in the course of the step of preparing the chlorohydrin. The organic acid is as defined above.

25 The amount of chlorohydrin in the mixture containing the chlorohydrin and esters of the chlorohydrin is generally greater than or equal to 2 % by weight, often greater than or equal to 4 % by weight and more specifically greater than or equal to 8 % by weight. Said amount is generally less than or equal to 50 % by weight, often less than or equal to 45 % by weight and more 30 specifically less than or equal to 40 % by weight.

The amount of esters of the chlorohydrin in the mixture containing the chlorohydrin and esters of the chlorohydrin, expressed in % by weight of the chlorohydrin, is generally greater than or equal to 1 % by weight, often greater than or equal to 2 % by weight and more specifically greater than or equal to 35 3 % by weight. Said amount is generally less than or equal to 30 % by weight, often less than or equal to 25 % by weight and more specifically less than or

equal to 20 % by weight.

The mixture containing the chlorohydrin and esters of the chlorohydrin may also contain compounds other than the chlorohydrin and the esters of the chlorohydrin, as defined above, and, among others, the polyhydroxylated 5 aliphatic hydrocarbon, by-products, the chlorinating agent, the organic acid used in step (a) of the process according to the invention, and the solvent optionally used.

The amount of these other compounds in the mixture containing the chlorohydrin and the esters of the chlorohydrin is generally less than or equal to 10 95% by weight, often less than or equal to 90 % by weight and more specifically less than or equal to 80 % by weight. Said amount is generally greater than or equal to 20 % by weight, often greater than or equal to 30 % by weight and more specifically greater than or equal to 40 % by weight.

Step (c) of the process according to the invention is preferably carried out 15 without supplying chlorinating agent other than residues of chlorinating agent which have possibly not reacted in step (a).

Step (c) of the process according to the invention is carried out at a temperature greater than or equal to 20°C, preferably greater than or equal to 20 40°C, more preferably greater than or equal to 60°C and with very particular preference greater than or equal to 100°C. This temperature is generally less or equal to 180°C, preferably less than or equal to 175°C and with particular preference less than or equal to 160°C.

Step (c) of the process according to the invention is generally carried out at an absolute pressure greater than or equal to 0.01 bar, preferably greater than or 25 equal to 0.05 bar and with particular preference greater than or equal to 0.1 bar. This pressure is generally less than or equal to 50 bar, preferably less than or equal to 10 bar and with particular preference less than or equal to 5 bar.

The duration of step (c) of the process according to the invention is generally greater than or equal to 2 min, preferably greater than or equal to 5 min 30 and with very particular preference greater than or equal to 10 min. This duration is generally less than or equal to 20 h, preferably less than or equal to 5 h and with very particular preference less than or equal to 2 h.

The molar ratio between the polyhydroxylated aliphatic hydrocarbon and the esters of the chlorohydrin in step (c) of the process according to the 35 invention is generally greater than or equal to 0.01 mol/mol, preferably greater than or equal to 0.02 mol/mol and with very particular preference greater than or

equal to 0.05 mol/mol. Said molar ratio is generally less than or equal to 20 mol/mol, preferably less than or equal to 10 mol/mol and with very particular preference less than or equal to 5 mol/mol.

Without wishing to be tied by any theoretical explanation, it is thought that 5 the polyhydroxylated aliphatic hydrocarbon reacts at least partly with the esters of chlorohydrin present in the mixture obtained in step (a), so as to form the chlorohydrin and esters of the polyhydroxylated aliphatic hydrocarbon. By "partly" is meant that the part of esters of the chlorohydrin which reacts with the polyhydroxylated aliphatic hydrocarbon during step (c) is at least 1 mol % of the 10 esters of the chlorohydrin present prior to the addition of the polyhydroxylated aliphatic hydrocarbon, preferably at least 2 mol % and with very particular preference at least 5 mol %.

Without wishing to be tied by any theoretical explanation, it is thought that, when the organic acid used in step (a) is a catalyst for the reaction between 15 the polyhydroxylated aliphatic hydrocarbon and the chlorinating agent, said acid is located initially at least partly in the esters of the chlorohydrin that are formed in step (a) and finally at least partly in the esters of the polyhydroxylated aliphatic hydrocarbon that are formed in the course of step (c). It is also thought that said acid is more readily separable from the chlorohydrin when the acid is in 20 the form of esters of the polyhydroxylated aliphatic hydrocarbon than when it is in the form of esters of the chlorohydrin. Its recycling to step (a) of the process according to the invention is facilitated as a result.

The esters of the polyhydroxylated aliphatic hydrocarbon may be present in step (a) of the process according to the invention.

Without wishing to be tied by any theoretical explanation, it is thought that 25 the solubility of the chlorinating agent in the fraction of the mixture withdrawn in step (a) is higher after the addition of the polyhydroxylated aliphatic hydrocarbon, and that the separation of the chlorinating agent and of the chlorohydrin is facilitated as a result.

The treatments in the steps subsequent to step (a) may be intended to 30 separate the chlorohydrin from the other compounds of the reaction mixture, and the addition of the polyhydroxylated aliphatic hydrocarbon may be made before or during these treatments. These treatments may be, for example, evaporation, stripping or distillation operations.

In a first embodiment of the process for preparing a chlorohydrin according to the invention, a fraction of the mixture obtained in step (a) is

withdrawn and, during its withdrawal, the polyhydroxylated aliphatic hydrocarbon is added thereto, so as to give a treated fraction.

In a first variant of this first embodiment, the fraction thus treated may be subjected to at least one subsequent separating operation, such as an evaporation, 5 stripping or distillation operation.

In a second variant of this first embodiment, the fraction thus treated may be subjected to an evaporation treatment in an evaporator, optionally in the presence of a gaseous stream, so as to remove the compounds which are more volatile than the chlorhydrin and than the esters of the chlorhydrin, and to 10 obtain a part concentrated with chlorhydrin and with esters of the chlorhydrin, and polyhydroxylated aliphatic hydrocarbon is added to the evaporator.

In a third variant of this first embodiment, the fraction thus treated may be subjected to a stripping and/or distillation treatment in a stripping and/or distillation column, so as to give a part concentrated with chlorhydrin, and 15 polyhydroxylated aliphatic hydrocarbon is added to the stripping and/or distillation column.

In a fourth variant, the fraction thus treated may be subjected to an evaporation treatment in an evaporator, optionally in the presence of a gaseous stream, so as to remove the compounds which are more volatile than the 20 chlorhydrin and than the esters of the chlorhydrin and to obtain a part concentrated with chlorhydrin and with esters of the chlorhydrin, and polyhydroxylated aliphatic hydrocarbon is added to the evaporator, and the part concentrated with chlorhydrin and with esters of the chlorhydrin may be subsequently subjected to a stripping and/or distillation treatment in a stripping 25 and/or distillation column so as to give a part concentrated with chlorhydrin, and polyhydroxylated aliphatic hydrocarbon is added to the stripping and/or distillation column.

In a second embodiment of the process for preparing the chlorhydrin, a fraction of the mixture obtained in step (a) is withdrawn, this fraction is 30 subjected to an evaporation treatment in an evaporator, optionally in the presence of a gaseous stream, so as to remove the compounds which are more volatile than the chlorhydrin and than the esters of the chlorhydrin, and to give a part concentrated with chlorhydrin and with esters of the chlorhydrin, and polyhydroxylated aliphatic hydrocarbon is added to the evaporator.

In a first variant of this second embodiment, the part concentrated with chlorhydrin and with esters of the chlorhydrin may be subjected to at least one subsequent separating operation, such as a stripping and/or distillation operation.

In a second variant of this second embodiment, the part concentrated with 5 chlorhydrin and with esters of the chlorhydrin may be subjected to a stripping and/or distillation treatment in a stripping and/or distillation column so as to give a part concentrated with chlorhydrin, and polyhydroxylated aliphatic hydrocarbon is added to the stripping and/or distillation column.

In a third embodiment of the process for preparing the chlorhydrin, a 10 fraction of the mixture obtained in step (a) is withdrawn, this fraction is subjected to a stripping and/or distillation treatment in a stripping and/or distillation column so as to give a portion concentrated with chlorhydrin, and the polyhydroxylated aliphatic hydrocarbon is added to the distillation column.

By evaporation is meant the separation of a substance by heating, 15 optionally under reduced pressure.

By stripping is meant the separation of a substance by entrainment by means of the vapour of a body which does not dissolve said substance. In the process according to the invention, said body may be any compound which is inert to the chlorhydrin, such as, for example, water vapour, air, nitrogen and 20 carbon dioxide. These same compounds may constitute the gaseous stream which is optionally present in the evaporation treatment.

By distillation is meant the direct passage from the liquid state to the gaseous state, followed by condensation of the vapours obtained. By fractional distillation is meant a series of distillations carried out on the vapours 25 successively condensed. Fractional distillation treatment is preferred.

The stripping and distillation treatments may be combined, for example in a stripping column surmounted by a distilling section.

The addition of the polyhydroxylated aliphatic hydrocarbon may be made 30 at any location on the stripping and/or distillation column. Preference is given to adding the polyhydroxylated aliphatic hydrocarbon at a level higher than the level at which the fraction of mixture withdrawn in step (a) is supplied. Without wishing to be tied by a theoretical explanation, it is thought that this procedure allows the contact time between the polyhydroxylated aliphatic hydrocarbon and the esters of the chlorhydrin to be prolonged and hence allows the formation of 35 the chlorhydrin and of esters of the polyhydroxylated aliphatic hydrocarbon.

These treatments may be conducted in batch mode or in continuous mode. Continuous mode is preferred.

At the outcome of the treatments, at least one first part enriched with chlorohydrin and at least one second part depleted in chlorohydrin and in esters 5 of the chlorohydrin and enriched with esters of the polyhydroxylated aliphatic hydrocarbon is recovered.

The amount of chlorohydrin in the first part is generally greater than or equal to 10 % by weight, often greater than or equal to 15 % by weight and more specifically greater than or equal to 20 %. This amount is generally less than or 10 equal to 99.9 % by weight, often less than or equal to 99.5 % by weight and more specifically less than or equal to 99 % by weight.

The amount of esters of the chlorohydrin in the second part, expressed in percent by weight of the chlorohydrin, is generally less than or equal to 25 % by weight, often less than or equal to 20 % by weight. This amount is generally 15 greater than or equal to 0.5 % by weight, often greater than or equal to 1 % by weight and more specifically greater than or equal to 2 % by weight.

The amount of esters of the polyhydroxylated aliphatic hydrocarbon in the second part, expressed in percent by weight of the polyhydroxylated aliphatic hydrocarbon, is generally greater than or equal to 0.2 % by weight, often greater 20 than or equal to 0.5 % by weight and more specifically greater than or equal to 1 % by weight. This amount is generally less than or equal to 15 % by weight, often less than or equal to 10 % by weight and more specifically less than or equal to 5 % by weight.

The second part may optionally be recycled to step (a) of the process 25 according to the invention.

The chlorohydrin obtained in the process according to the invention may include a heightened amount of halogenated ketones, in particular of chloroacetone, as described in the patent application FR 05.05120 of 20/05/2005, filed in the name of the applicant, and the content of which is 30 incorporated here by reference. The halogenated ketone content may be reduced by subjecting the chlorohydrin obtained in the process according to the invention to an azeotropic distillation in the presence of water or by subjecting the chlorohydrin to a dehydrochlorination treatment as described in this application from page 4 line 1 to page 6 line 35.

35 Particular mention is made of a process for preparing an epoxide wherein halogenated ketones are formed as by-products and which comprises at least one

treatment of removal of at least a portion of the halogenated ketones formed. Mention is made more particularly of a process for preparing an epoxide by dehydrochlorinating a chlorohydrin of which at least one fraction is prepared by chlorinating a polyhydroxylated aliphatic hydrocarbon, an ester of a

5 polyhydroxylated aliphatic hydrocarbon or a mixture thereof, a treatment of dehydrochlorination and a treatment by azeotropic distillation of a water/halogenated ketone mixture, which are intended to remove at least a portion of the halogenated ketones formed, and a process for preparing epichlorohydrin wherein the halogenated ketone formed is chloroacetone.

10 The chlorohydrin obtained in the process according to the invention may be subjected to a dehydrochlorination reaction in order to produce an epoxide, as described in the patent applications WO 2005/054167 and FR 05.05120, both filed in the name of SOLVAY SA.

15 The term "epoxide" is used herein to describe a compound containing at least one oxygen bridged on a carbon-carbon bond. Generally speaking, the carbon atoms of the carbon-carbon bond are adjacent and the compound may contain atoms other than carbon atoms and oxygen atoms, such as hydrogen atoms and halogens. The preferred epoxides are ethylene oxide, propylene oxide and epichlorohydrin.

20 The dehydrochlorination of the chlorohydrin may be carried out as described in the application entitled "Process for preparing an epoxide starting from a polyhydroxylated aliphatic hydrocarbon and a chlorinating agent", filed in the name of SOLVAY SA on the same day as the present application, and the content of which is incorporated here by reference.

25 Particular mention is made of a process for preparing an epoxide wherein a reaction mixture resulting from the reaction between a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof with a chlorinating agent, the reaction mixture containing at least 10 g of chlorohydrin per kg of reaction mixture, is subjected to a

30 subsequent chemical reaction without intermediate treatment.

Mention is also made of the preparation of an epoxide that comprises the following steps : (a) a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof is reacted with a chlorinating agent and an organic acid so as to form the chlorohydrin and

35 chlorohydrin esters in a reaction mixture containing the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon,

water, the chlorinating agent and the organic acid, the reaction mixture containing at least 10 g of chlorohydrin per kg of reaction mixture, (b) at least a fraction of the reaction mixture obtained in step (a), this fraction having the same composition as the reaction mixture obtained in step (a), is subjected to 5 one or more treatments in steps subsequent to step (a), and (c) a basic compound is added to at least one of the steps subsequent to step (a) in order to react at least partly with the chlorohydrin, the chlorohydrin esters, the chlorinating agent and the organic acid so as to form the epoxide and salts.

10 The process for preparing the chlorohydrin according to the invention may be integrated within an overall plan for preparation of an epoxide, as described in the application entitled "Process for preparing an epoxide starting from a chlorohydrin", filed in the name of SOLVAY SA on the same day as the present application, and the content of which is incorporated here by reference.

15 Particular mention is made of a process for preparing an epoxide that comprises at least one step of purification of the epoxide formed, the epoxide being at least partly prepared by a process of dehydrochlorinating a chlorohydrin, the latter being at least partly prepared by a process of chlorinating a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof.

20 When the chlorohydrin is dichloropropanol, the process according to the invention may be followed by preparation of epichlorohydrin by dehydrochlorination of dichloropropanol, and the epichlorohydrin may be used in the production of epoxy resins.

25 In the process according to the invention, when the polyhydroxylated aliphatic hydrocarbon is glycerol, it may contain glycerol esters as defined earlier on above. The invention likewise provides a process for preparing dichloropropanol, comprising the following steps :

- (a) glycerol and/or glycerol esters are/is reacted with hydrogen chloride or hydrochloric acid and an organic acid so as to give a mixture containing dichloropropanol and dichloropropanol esters
- (b) glycerol is added to the fraction obtained in step (a), so as to react at least partly with the dichloropropanol esters so as to form, at least partly, glycerol esters.

35 Figure 1 shows a particular scheme of plant which can be used for implementing the separation process according to the invention.

A reactor (4) is supplied in continuous mode or in batch mode with the polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof via line (1), and with catalyst via line (2); the chlorinating agent is supplied in continuous mode or in batch mode via line (3);

5 a distillation column (6) is supplied via line (5) with vapours produced in reactor (4); a stream is taken off from column (6) via line (7) and is introduced into a condenser (8); and the stream obtained from the condenser is introduced via line (9) into a phase separator (10), in which the aqueous and organic phases are separated. A fraction of the separated aqueous phase is optionally recycled

10 via line (11) to the top of the column in order to maintain the reflux. Fresh water may be added via line (12) to the top of the column in order to maintain the reflux. The production of the chlorohydrin is distributed between the organic phase taken off via line (14) and the aqueous phase taken off via line (13). The residue from column (6) may be recycled to reactor (4) via line (15). A fraction

15 of the heavy products is taken off from reactor (4) via the purge (16) and is introduced via line (17) into an evaporator (18), in which a partial evaporation operation is carried out, for example, by heating or by gas scavenging with nitrogen or with water vapour; the gaseous phase containing the majority of the chlorinating agent from stream (17) is recycled via line (19) to column (6) or via

20 line (20) to reactor (4); a distillation or stripping column (22) is supplied with the liquid phase coming from evaporator (18) via line (21); line (21) and/or distillation column (22) and/or evaporator (18) and/or line (17) are supplied with polyhydroxylated aliphatic hydrocarbon via, respectively, line (32) and/or line (31) and/or line (33) and/or line (34); the majority of the chlorohydrin is

25 collected at the top of column (22) via line (23), and the residue, which contains the esters of the polyhydroxylated aliphatic hydrocarbon, is introduced via line (24) into the filtering unit (25), in which the liquid and solid phases are separated; and the liquid phase is recycled via line (26) to reactor (4). The solid may be taken off from filtering unit (25) via line (27) in the form of a solid or a

30 solution. Solvents may be added to filtering unit (25) via lines (28) and (29) for the washing and/or dissolving of the solid, and may be taken off via line (27). Optionally a stream is taken off from purge (16) and introduced via line (30) into the filtering column (25). Evaporator (18) and distillation column (22) are in that case short-circuited. In another option, where it is not necessary to remove

35 a solid compound from the process, the liquid taken off at the bottom of

column (22) is directly returned via line (33) to reactor (4). Filtering unit (25) and the lines connected to it are in that case no longer indispensable.

In the process according to the invention, the polyhydroxylated aliphatic hydrocarbon is preferably glycerol and the chlorohydrin is preferably 5 dichloropropanol.

The examples below are intended to illustrate the invention without, however, imposing any limitation thereon.

Example 1 (not in accordance with the invention)

A reaction mixture containing 61 g of dichloropropanol, 20.5 g of 10 monochlorohydrin of glycerol (MCG), 0.7 g of glycerol (GLC), 6.3 g of adipic acid, 0.4 g of chlorinated diglycerol, 23.3 g of dichloropropanol adipate, 42 g of MCG adipate, 1.6 g of GLC adipate, 4.9 g of water and 0.3 g of HCl was subjected to evaporation on a rotary evaporator at 165°C under 0.04 bar. After 45 minutes, 61 g of the dichloropropanol were recovered in the evaporated 15 liquid, and 6 g of dichloropropanol and 12 g of dichloropropanol adipate in the residue. 2 g of glycerol adipate were recovered in the residue.

Example 2 (in accordance with the invention)

A reaction mixture containing 61 g of dichloropropanol, 20.5 g of MCG, 0.7 g of GLC, 6.3 g of adipic acid, 0.4 g of chlorinated diglycerol, 23.3 g of 20 dichloropropanol adipate, 42 g of MCG adipate, 1.6 g of GLC adipate, 4.9 g of water and 0.3 g of HCl is admixed with 19 g of glycerol before being subjected to evaporation on a rotary evaporator at 165°C under 0.04 bar. After 45 minutes, 69 g of the dichloropropanol are recovered in the evaporated liquid, and there remain 4 g of dichloropropanol and also a trace of dichloropropanol adipate in 25 the residue. 22 g of glycerol adipate are found in the residue.

CLAIMS

1. Process for preparing a chlorohydrin, comprising the following steps :
 - (a) a polyhydroxylated aliphatic hydrocarbon, an ester of a polyhydroxylated aliphatic hydrocarbon or a mixture thereof is reacted with a chlorinating agent and an organic acid so as to give a mixture containing the chlorohydrin and esters of the chlorohydrin
 - (b) at least part of the mixture obtained in step (a) is subjected to one or more treatments in steps subsequent to step (a)
 - (c) polyhydroxylated aliphatic hydrocarbon is added to at least one of the steps subsequent to step (a), so as to react, at a temperature greater than or equal to 20°C, with the esters of the chlorohydrin, so as to form, at least partly, esters of the polyhydroxylated aliphatic hydrocarbon.
2. Process according to Claim 1, according to which, in the subsequent step, a fraction of the mixture obtained in step (a) is withdrawn and during the withdrawal the polyhydroxylated aliphatic hydrocarbon is added to said fraction.
3. Process according to Claim 1 or 2, according to which, in the subsequent step, a fraction of the mixture obtained in step (a) is withdrawn, this fraction is subjected to an evaporation treatment (I) in an evaporator, optionally in the presence of a gaseous stream, so as to remove the compounds more volatile than the chlorohydrin and than the esters of the chlorohydrin and to obtain a part concentrated with chlorohydrin and with esters of the chlorohydrin, and the polyhydroxylated aliphatic hydrocarbon is added to the withdrawn fraction of the mixture, prior to the evaporation treatment, and/or to the evaporator at a level higher than the level at which said evaporator is supplied with the fraction withdrawn in step (a).
4. Process according to Claim 1 or 2, according to which, in the subsequent step, a fraction of the mixture obtained in step (a) is withdrawn, this fraction is subjected to a stripping and/or distillation treatment (II) in a stripping and/or distillation column, so as to give a portion concentrated with chlorohydrin, and the polyhydroxylated aliphatic hydrocarbon is added to the withdrawn fraction of the mixture, prior to the stripping and/or distillation

treatment, and/or to the stripping and/or distillation column at a level higher than the level at which said column is supplied with the fraction withdrawn in step (a).

5. Process according to Claim 3, according to which, in the subsequent step, a section of the part concentrated with chlorohydrin and with esters of the chlorohydrin, obtained in the treatment (I), is withdrawn, this section is subjected to a stripping and/or distillation treatment in a stripping and/or distillation column (III), and the polyhydroxylated aliphatic hydrocarbon is added to the withdrawn section, prior to the stripping and/or distillation treatment, and/or to the stripping and/or distillation column at a level higher than the level at which said column is supplied with the part withdrawn in the treatment (I).

10 6. Process according to any one of Claims 1 to 5, wherein the reaction of the polyhydroxylated aliphatic hydrocarbon with the esters of the chlorohydrin is carried out at a temperature greater than or equal to 40°C and less than or equal to 180°C, at an absolute pressure greater than or equal to 0.01 bar and less than or equal to 50 bar, for a time greater than or equal to 2 min and less than or equal to 20 h and at a molar ratio between the polyhydroxylated aliphatic hydrocarbon and the esters of the chlorohydrin which is greater than or equal to 0.01 and less than or equal to 20 mol/mol.

15 7. Process according to any one of Claims 1 to 6, wherein the polyhydroxylated aliphatic hydrocarbon, the ester of polyhydroxylated aliphatic hydrocarbon or the mixture thereof is obtained starting from renewable raw materials.

20 8. Process according to any one of Claims 1 to 7, wherein the chlorinating agent is a combination of gaseous hydrogen chloride with an aqueous solution of hydrogen chloride, or is an aqueous solution of hydrogen chloride.

25 9. Process according to any one of Claims 1 to 8 according to which, at the outcome of the subsequent treatments, at least a first part enriched with chlorohydrin and at least a second part depleted in chlorohydrin and in chlorohydrin esters and enriched with esters of the polyhydroxylated aliphatic hydrocarbon are recovered, and wherein the second part is recycled to step (a).

10. Process according to any one of Claims 1 to 9, according to which the polyhydroxylated aliphatic hydrocarbon is selected from ethylene glycol, propylene glycol, chloropropanediol, glycerol and mixtures of at least two thereof.

5 11. Process according to any one of Claims 1 to 10, according to which the chlorohydrin is selected from chloroethanol, chloropropanol, chloropropanediol, dichloropropanol and mixtures of at least two thereof.

10 12. Process according to Claim 10 or 11, according to which the polyhydroxylated aliphatic hydrocarbon is glycerol and the chlorohydrin is dichloropropanol.

13. Process according to Claim 12, followed by preparation of epichlorohydrin by dehydrochlorination of dichloropropanol.

14. Process according to Claim 13, wherein the epichlorohydrin is used in the preparation of epoxy resins.

15 15. Process for preparing dichloropropanol, comprising the following steps :

(a) glycerol and/or glycerol esters are/reacted with hydrogen chloride or hydrochloric acid and an organic acid so as to give a mixture containing dichloropropanol and dichloropropanol esters

20 (b) glycerol is added to at least one fraction of the mixture obtained in step (a), so as to react at least partly with the dichloropropanol esters so as to form, at least partly, glycerol esters.

Figure 1

