

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C02F 1/467	A1	(11) International Publication Number: WO 96/12677 (43) International Publication Date: 2 May 1996 (02.05.96)
(21) International Application Number: PCT/US95/13377 (22) International Filing Date: 19 October 1995 (19.10.95) (30) Priority Data: 08/326,339 20 October 1994 (20.10.94) US (71) Applicant: AQUA-ION SYSTEMS [US/US]; 2569 E. Nichols Avenue, Littleton, CO 80122 (US). (72) Inventor: JOHNSON, Dennis, E., J.; 8530 Windfall Way, Colorado Springs, CO 80908 (US). (74) Agent: DE ANGELI, Michael; Suite 330, 1901 Research Boulevard, Rockville, MD 20850 (US).		(81) Designated States: AU, BR, CA, CN, JP, KR, RU, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG). Published <i>With international search report.</i>

(54) Title: GAS ION PLASMA AND METAL ION DISINFECTION OF WATER**(57) Abstract**

A system for disinfecting water streams comprises a source of ionized plasma, that is, a stream of air including ionized oxygen and nitrogen gas molecules, including ozone, and an additional source of metal ions. The gas plasma is introduced into the water stream upstream of the metal ion stream to produce a variety of oxidizing, coagulating, and disinfecting reactions. Further, the metal ions combine with the gas ions to form additionally known disinfectant compounds. The source of ionized gas molecules is an ultraviolet lamp juxtaposed to a coil providing electric and/or magnetic fields, to excite and ionize oxygen and nitrogen molecules of the air. The sacrificial electrodes may comprise alloy members of the metal elements to be provided to the water stream. A DC potential applied to the electrodes is uniformly reversed at intervals, to encourage sacrificial erosion thereof. The system may be provided as a retrofit disinfectant, coagulation, and purification plant for swimming pools or like closed loop domestic or industrial water systems, or used for non-chemical treatment of drinking water and/or non-chemical purification treatment for environmental water purification and safe discharge applications, replacing chlorination and other conventional chemical coagulation treatments.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

**Gas Ion Plasma and Metal Ion
Disinfection of Water**

Inventor: Dennis E.J. Johnson

Field of the Invention

This invention relates to apparatus and methods for treating contaminated water while avoiding conventional chemical treatments. More particularly, the invention provides methods and apparatus for oxidizing and
5 coagulating contaminants in water, followed by their removal, thus disinfecting the water, while avoiding the introduction of large quantities of toxic chemicals such as chlorine or polymeric chemical coagulants into the water stream.

Background of the Invention

10 The treatment of water to kill biological contaminants, such as algae, bacteria, viruses, and the like, and to coagulate and remove these pollutants, as well as non-biological particulates, contaminant metals, and the
15 like, and in particular, to disinfect water for drinking or to "decontaminate" water for safe environmental discharge, has a long history. Nonetheless, the practice of water treatment continues to evolve as new discoveries are made.

Typical prior practices comprise addition of chlorine
20 to the water stream, to kill bacteria, algae, viruses, and the like, along with addition of anionic or cationic polymeric coagulants. Electrostatic interaction between the contaminants and the coagulants tends to coagulate the contaminants into particles large enough to be removed by
25 filtration or settling.

As of the filing of this application, it appears very likely that the practice of chemical chlorination, long the

preferred method of disinfecting drinking, industrial, and swimming pool water streams and the like, will be banned or severely restricted within the next few years.

5 Accordingly, a substantial need exists for methods of removing contaminants from water avoiding chlorine or other chemicals thought to be toxic. More specifically, a need exists for methods of water treatment and disinfection not involving introduction of chlorine or additional toxic chemical treatment substances into the water stream.

10 Preferably, any water treatment method replacing chlorination and other chemical treatment would be economically practiced, and apparatus for its practice would be available as a unit for retrofitting systems now employing chlorination and chemical treatment, such as
15 swimming pool disinfecting systems, drinking water processing plants, and/or industrial wastewater treatment systems. In this connection, while the present invention is described herein primarily as a replacement for chlorination and chemical treatment in connection with
20 swimming pool, drinking water, and/or industrial water streams, and the like, the present invention may find application in many other water streams where purification and disinfection must be accomplished without chemical coagulant treatments.

25 The present inventor has been working in the field of purification of contaminated water systems without employment of chlorine and chemical treatments or the like for some years. See U.S. patents 4,562,286 and 4,655,933 to the present inventor and Scott J. Johnson. These
30 patents both recognize that a water stream can be purified by introduction of ionized oxygen tending to oxidize various pollutants, and teach further that ionized oxygen can be produced by exposing atmospheric air to ultraviolet light, particularly in the presence of permanent magnets.

U.S. patent 4,562,014 to the inventor herein discloses a system for introducing oxidant gases such as ionized oxygen into a water stream. A venturi is employed for dispersing the gas in the liquid stream; thorough mixing of the gas and liquid streams is encouraged by the drop in pressure after the venturi. The teachings of this patent are employed in the present invention, as will be apparent from the discussion below.

U.S. patent 4,382,866, also to the present inventor, shows a system for performing electrochemical filtration to remove flocculated or coagulated pollutants from a contaminated water stream.

Copending U.S. patent application Serial No. 08/200,749 in the name of the present inventor and another discloses further improvements in the removal of contaminants from water streams by encouraging flocculation thereof, such that physical separation is then possible. The teachings of copending Serial No. 08/200,749 may be employed together with the teachings of the present invention, where the nature of the contaminated water stream indicates that both techniques may be of use.

Objects of the Invention

It is therefore an object of the invention to provide a system for removal of pollutants, impurities, organics, and other undesirable components of a water stream, avoiding addition of significant quantities of chlorine and/or other toxic or undesirable foreign chemical treatment components into the water stream.

It is a further object of the invention to provide a system for the treatment of water wherein disinfectant and coagulating compounds are formed by reaction in situ, greatly increasing the efficiency of production and employment of such synthesized disinfecting and coagulating compounds.

It is a further object of the invention to provide an apparatus for treatment of water for certain specified process streams, such as swimming pool filtration and disinfection water streams, drinking water filtration and disinfection water streams, and/or industrial wastewater, which can be retrofit as a direct replacement for preexisting chlorination or like chemical treatment equipment.

Summary of the Invention

The above objects of the invention and needs of the art, and others which will appear as the discussion below proceeds, are satisfied by the present invention, which in a typical embodiment comprises a source of oxygen and nitrogen ion molecules, as well as increased quantities of paramagnetic oxygen molecules, thus producing a stream of ionized plasma from the air, a source of a stream of ionized metal atoms such as copper, silver, and stannous atoms, a source of free electrons, and means for mixing the streams of ionized gas, electrons, and ionized metal atoms with the water stream to be treated. The result is that known disinfectant compounds such as the algicide copper nitrate (Cu^+NO_3^-), the bactericide silver nitrate (Ag^+NO_3^-), and the viricide and fungicide stannous tartrate ($\text{Sn}^{++}\text{C}_4\text{H}_4\text{O}_6^{--}$), are produced in situ, at high efficiency. Accordingly, algae, bacteria, viruses, and fungi are destroyed by biocidal compounds formed directly in the water stream. The fact that ions are added to the water stream in quantity encourages electrostatic attraction of the various components and their coagulation, allowing removal by settling or filtration.

In a preferred embodiment, a plasma, that is, a stream of ionized gas molecules, is produced by exposing a stream of atmospheric air to a lamp emitting both ultraviolet and infrared radiation, while providing one or both of electric

and magnetic fields in the vicinity of the lamp. Preferably, the lamp drive current is pulsed periodically; also preferably, conditions are such that free electrons are provided as well. The stream of air, including a substantial plasma fraction of paramagnetic oxygen, ionized oxygen and nitrogen gas molecules, and free electrons, is introduced into the water stream by connecting the exposure chamber in which the plasma is formed to an area of low pressure in the water stream, typically formed by a venturi through which the water stream passes.

Metal ions are added to the water stream, having had the ionized gas molecules introduced thereto, by passing the stream between electrically charged electrodes comprising atoms of the metal ions to be added. In a preferred embodiment, the electrodes may simply be cast of a mixture of stannous, copper, and silver metals in the desired proportions. A DC voltage, the polarity of which is alternated at intervals on the order of one or several minutes, is applied across the electrodes, so that an electric field exists therebetween, causing sacrificial decomposition of the electrodes, and providing further energy driving the desired reactions. Ionized metal atoms are detached from the electrodes and entrained in the water stream, for immediate synthesis reaction with the ionized molecules of oxygen and nitrogen entering from the stream of air. The result is that various coagulant and disinfectant compounds are formed in situ in the water, tending to coagulate and disinfect the various contaminant constituents of the water stream to be treated. The water stream may then be recirculated in a reactor tank for a period on the order of minutes, to ensure substantially complete coagulation and/or disinfection, and is then filtered to remove the killed organics as well as any coagulated particulates or flocculated solids.

Brief Description of the Drawings

The invention will be better understood if reference is made to the accompanying drawings, in which:

5 Fig. 1 shows a block diagram of an overall system for non-chemical treatment of water according to the invention;

Fig. 2 shows a perspective view of a first embodiment of an ionized gas source for providing a stream of ionized gas atoms;

10 Fig. 3 shows a cross-section taken along the line 3-3 of Fig. 2;

Fig. 4 shows an enlarged view of an assembly of an ultraviolet lamp and coil used in one embodiment of the ionized gas source according to the invention;

15 Fig. 5 shows a schematic diagram of circuitry supplying the ultraviolet lamp and coil with electrical power;

20 Fig. 6 is a cross-sectional view through two identical assemblies of a second embodiment of an ionized gas source, again comprising a coil surrounding an ultraviolet lamp in an exposure chamber;

25 Fig. 7 shows a perspective cutaway view of a portion of the system, illustrating the venturi at which the ionized gas stream is added to the water stream, and the electrodes whereby metal ions are added to the water stream for reaction with the ionized gas atoms; and

Fig. 8 shows a preferred construction of the ion addition system of Fig. 7.

Description of the Preferred Embodiment

30 Fig. 1 depicts an overall block diagram view of a typical closed-cycle water system including water treatment according to the invention, such as environmental decontamination treatment, swimming pool water disinfection systems, and the like. As indicated above, the invention may find significant initial wide-spread use in replacement

of presently existing chlorination and chemical coagulation and purification plants for swimming pools, and the invention will be described in that environment. However, it should be appreciated that the invention has use in treatment of many other sorts of contaminated water streams as well, including treatment of drinking water, and treatment of water prior to environmental discharge in systems not recycling water.

Referring to Fig. 1, a fixed quantity of water is continually supplied to and removed from an end use 10, such as a swimming pool, drinking water source, industrial water stream, or any contaminated body of water, from which a stream of water is periodically withdrawn, treated, disinfected, and reused. According to the invention, a stream 12 of air including a substantial fraction of ionized oxygen and nitrogen gas molecules and free electrons, or "plasma", is added to the stream of water from the end use 10 at a venturi eductor 14. The stream 12 of air including ionized gas molecules is provided by an ionized gas source 18 powered by an AC power supply 16. Differing embodiments of the ionized gas source 18 are discussed below in connection with Figs. 2 - 5 and 6.

A stream of metal ions from a source 20 is then introduced into the mixed stream of water from end use 10 and air including ionized molecules from source 18. In one embodiment, detailed below in connection with Figs. 7 and 8, the source 20 of metal ions may comprise a pair of charged metallic electrodes 52 exposed directly to the water stream. The electrodes 52 are formed of the metals to be added to the water stream, and are connected to a source 22 of DC potential, the polarity of which is preferably reversed at intervals on the order of one to several minutes. Accordingly, an electric field exists between the electrodes 52, which accordingly behave as sacrificial electrodes, i.e., individual atoms of the

electrodes enter the water stream. According to an important aspect of the invention, the ionized metallic atoms from the electrodes 22 chemically react with the ionized gas molecules of the plasma 12, largely in the region between and surrounding the electrodes 52, forming a variety of biocidal disinfectant metal ion compounds, killing various organic substances in the water.

For example, electrodes suitable for use in swimming pool and typical environmental water treatment applications may comprise stannous, silver, and copper metals in the relative proportions 5:10:85 respectively by weight. The plasma stream 12 of air including ionized atoms may include various ionized forms of nitrogen, oxygen, ozone, free electrons, and combinations thereof, as discussed further below. The ionized gas atoms of the plasma stream 12 react with the oppositely ionized metal ions from the electrodes to form a number of beneficial water treatment compounds. Included in these are $\text{Sn}^{++}\text{C}_4\text{H}_4\text{O}^{--}_6$, a known viricide and fungicide; Cu^+NO^-_3 , a known algicide; and Ag^+NO^-_3 , a known bactericide. Therefore, according to the invention, by combining the water stream to be treated with specific metal ions and an ionized plasma of oxygen and nitrogen gas molecules and electrons, algae, bacteria, viruses, fungi, and other organic contaminants are destroyed in the water stream without addition of undesirable chemicals. Further, as the gas plasma and ions are charged, a strong electrostatic coagulant effect is provided. Disinfection and coagulation according to the invention are accomplished at very high efficiency due to the strong oxidizing and coagulation capability of the ionized oxygen/nitrogen plasma ion gas species. Further, as the disinfectant compounds are formed in situ, that is, in the very water stream to be treated, no processing or handling steps or the like are required, simplifying the apparatus required, while the ionized gas and metal ions have very limited

opportunity to recombine or otherwise lose their disinfectant and coagulant efficiency.

After the water stream has been combined with the plasma stream at 14 and with the metal ions at 20, the water stream may be stored in a reactor tank 24 if necessary to provide sufficient retention time for the disinfectant reactions to be completed. Typically, reactor tank 24 would only be used in certain industrial and environmental water treatment applications and will not be necessary in a swimming pool water recycling and disinfecting system. The water stream is then filtered as indicated at 26 to remove the killed organics as well as any coagulated particulates or the like from the water stream, after which the water stream may be returned to the end use 10. A pump 28 may be provided to motivate water through the system as needed.

In a specific example, in order to retrofit a disinfectant system according to the invention in place of the chlorination plant of a conventional swimming pool or drinking water treatment system, the chlorination plant is simply replaced with a venturi eductor device 14, at which the plasma stream 12 is mixed with the water stream, and a sacrificial electrode metal ion addition unit 20, at which the metallic ions are added to the water stream. The replacement process is quite straightforward and readily accomplished.

In this connection, it will be appreciated that adding the plasma stream 12 at the venturi eductor 14 is highly useful in that the conduit 29 carrying the plasma stream 12 can be connected to the venturi just after the point of minimum cross-sectional area, such that the plasma stream will be exposed to a partial vacuum. See Fig. 7. Accordingly, the ionized plasma gas stream will be drawn into and mixed thoroughly with the water stream without necessity of an additional pump or the like, simplifying

and reducing the cost of the system and rendering its retrofit to preexisting swimming pool disinfectant system, and other types of environmental water treatment applications, very convenient.

5 Figs. 2-5 show a first embodiment of an ionized gas source 18 suitable for use in systems having relatively small to moderate water treatment demand. Figs. 2-4 illustrate the physical embodiment of the device, and Fig. 5 shows typical power supply connections. As indicated
10 above, the basic components of the ionized gas source 18 are means for confining a quantity of atmospheric air in a reaction zone in which the air is exposed to radiation from a suitable ultraviolet lamp while simultaneously experiencing one or both of electric and magnetic fields,
15 in order to ionize the highest possible percentage of the oxygen and nitrogen atoms in the passing airflow.

In the Figs. 2-5 embodiment, a stream of air is drawn into a sealed boxlike container 30 through air intake openings 32 in its lid fitted with glass wool or other
20 filters 34, such that an air flow path is established from the air intakes 32, through an exposure zone in the box 30, to an exit tube 44 connected by conduit 29 (Fig. 7) to the venturi eductor 14. Within the box 30 are disposed one or more "low pressure" mercury vapor ultraviolet lamps 36 each
25 surrounded by a coil 42 providing electric and magnetic fields above and below the lamp along the lengthwise axis. As is well known, such lamps emit ionizing ultraviolet radiation in the 184 and 254 nm wavelength bands, as well as emitting additional wide bandwidth infrared radiation.
30 The ultraviolet radiation is particularly suitable for ionizing oxygen in the air and some fraction of the nitrogen, while the infrared radiation may additionally ionize nitrogen. Each lamp 36 is surrounded by an axial wire strip coil 42 typically comprising a number of
35 parallel conductors (see Fig. 5), which when energized

provide an electric and/or magnetic field in the vicinity of the corresponding ionizing lamp 36.


As shown in Fig. 4, each ultraviolet lamp 36 may be disposed within a hollow plastic coil support tube 38, drilled with holes 40 to allow ready passage of air. An axial coil 42 is assembled over the tube 38 and comprises one or more conductors for carrying a current and thereby emitting an electric and/or magnetic field in the vicinity of the lamp 36. For example, in the embodiment of Figs. 4 and 5, the coil 42 may comprise a number of parallel thin (e.g. 22 gauge) stainless steel wires, spaced from one another by insulative plastic material woven into a flat narrow band, so that a relatively large current can be passed from one end of the coil to the other. When the lamp 36 is energized and electrical power is supplied to the coil 42, atmospheric air within the coil 42 is subjected to relatively intense radiation from the lamp, including both short wavelength ultraviolet and infrared radiation, and also to an electric and/or magnetic field. The proportions of electric and magnetic field strength are generally responsive to the exact configuration of the coil. The flow rate of air through the exposure zone defined by container 30 is controlled such that the average residence time of atmospheric air passing in the vicinity in the vicinity of the lamp and coil combinations is on the order of several minutes. A substantial fraction of the oxygen and nitrogen molecules of the air in the vicinity of the assembly of the lamp and coil are ionized under these conditions.

Fig. 5 shows a schematic diagram of a typical lamp and coil circuit suitable for practice of the invention. As indicated, AC power is supplied at line connection 16 and the coil 42 is in series with the lamp power supply 64. Power supply 64 preferably comprises a solid state power supply providing pulsating "bursts" of current to lamp 36;

pulsing the current results in shorter and more intense UV energy being produced below 180 nm. In the embodiment of the invention shown by Figs. 2-4, up to four twelve-inch 20 watt low pressure mercury vapor lamps may be provided, each
5 powered by an individual power supply. Each lamp power supply provides pulsating electrical power that averages 90 volts at 250 milliamps and 60 Hz; typically, the voltage and current are both controlled to periodically exceed their average values by 30%. More particularly, by thus
10 pulsing the power supplied to the lamp, the filaments never cool fully but remain hot, such that a substantial fraction of energy is UV of less than 180 nm wavelength. Such low pressure mercury vapor lamps are further stimulated by such pulsating current to emit a substantial fraction of
15 increased short wavelength ultraviolet energy in the 160-185 nm range, with further components in the 250-265 nm range, and with additional wide bandwidth infrared energy as well. As noted above, it is generally understood that ultraviolet radiation effectively stimulates ionization of
20 oxygen, and nitrogen to a lesser degree, while infrared radiation further stimulates ionization of nitrogen. Furthermore, exposure of atmospheric oxygen to radiation and electric and magnetic fields increases the normal paramagnetism of the oxygen molecules, increasing the
25 chemical activity thereof, particularly while disposed in the electric field between the charged metal ion electrodes 52.

Without intending to limit the scope of the claims appended hereto to any particular theory of operation, it
30 is believed that a number of distinct ionic species are produced in the plasma gas source 18, each of which may contribute separately and beneficially to water treatment by oxidation and coagulation of contaminants, further resulting in disinfection as provided by the system of the
35 invention. In a first reaction, nitrogen molecules are

understood to be ionized and energized by ultraviolet and infrared radiation, and are further energized by the surrounding electric and magnetic fields, to generate ionized nitrogen and release a free electron according to the following equation:



The ionized nitrogen gas thus provided assists in coagulation of waterborne contaminant debris and particles, if any are present; equally important, this reaction releases an additional free electron (e^-) which may further assist in a variety of oxygen gas generation and ionization reactions.

A further reaction which is thought to occur is the generation of singlet molecular oxygen (O_2^{a-}) according to the following equation:



Those of skill in the art will recognize that this equation indicates that oxygen ions (O_2^-) as well as partially negatively charged dipoles (O_2^{a-}), that is, singlet molecular oxygen, are formed in the presence of pulsating ultraviolet radiation and the electric and magnetic fields provided according to the invention. The negatively charged oxygen ions and partially charged singlet molecular oxygen stimulate coagulation, oxidation, and/or carboxylation of any particulate debris or contaminants present, and may oxidize and destruct various contaminant species for removal.

As mentioned, the oxygen and nitrogen ions react with the stream of metallic species added by the electrode unit as discussed above to form additional specific chemical disinfectant molecules.

Test results demonstrating the generation of singlet molecular oxygen by apparatus generally as described herein, and the efficiency of singlet molecular oxygen in

water purification according to the invention, are provided in Appendix I, attached hereto and forming a part of this application. Further test results are available which demonstrate the generation of highly reactive species of paramagnetic molecular oxygen.

As the ionized oxygen molecules collide with one another, ozone (O_3) is also formed in the plasma. Ozone is known to be highly reactive and destructive to organic molecules, as discussed in applicant's prior patents referred to above. Further, polar combinations of two oxygen atoms with one nitrogen atom are also formed, and are also useful in contributing to the molecular destruction of organic contaminants. Pulsating the lamp current, providing additional UV photon energy in the 160 to 180 nm range, also results in the production of more highly paramagnetic oxygen ions.

It can thus be seen that stimulation of the molecules of the atmospheric air by simultaneous exposure to ultraviolet and infrared radiation of a variety of wavelengths and to electric and/or magnetic field energy promotes the formation of various reactive species of both nitrogen and oxygen ions, which in turn make a direct contribution to purification of water streams according to the invention, and also react with one another and with metallic ions, as discussed further below, to provide an additional disinfectant water treatment effect. The free electrons released by ionization of the nitrogen molecules further tend to stimulate higher ionized states of plasma ion oxygen.

The additional chemical disinfectant compounds which are desirably formed include, but are not limited to, the known bactericide $Ag^+NO_3^-$, $Cu^+NO_3^-$, known to be algicidal, and the known fungicide and viricide $Sn^{++}C_4H_4O_6^{--}$. These compounds may be formed in situ by disposing electrodes of copper, silver, and stannous materials in the

proportions desired in the water stream, as indicated in Fig. 7, and supplying suitable power thereto. Power supply 22 applies DC power, typically 12 volts at one ampere, across the two electrodes, while the mixed stream of ionized gas and water to be disinfected flows therebetween. An electric field thus exists between the charged electrodes 52; and the electrodes 52 are sacrificial in that over time their materials erode away, giving up individual metallic atoms to the water stream. These atoms will be ionized, depending on the charge applied, and will combine with the nitrogen and oxygen ions in the water stream, having been introduced at inlet 50, to form the disinfectant compounds mentioned above in situ. However, it is to be understood that other compounds might also be formed, and that the electrodes may include other metals. Further, it is not necessary to the utility of the invention that the disinfectant compounds be formed in precise proportions or the like.

As indicated in Fig. 7, the stream of air including plasma, again, a variety of ionized gas atoms and free electrons, is introduced by conduit 29 into the water stream at 50, just downstream of the throat of venturi 14. The advantage of so doing is that the gas stream experiences a reduced pressure, i.e., a partial vacuum, and hence will be drawn into and mixed with the water stream, establishing an air flow path from the air intake 32 (Fig. 2) through the exposure zone to the venturi 14.

In one convenient method of fabrication of the sacrificial ionizer (see Fig. 8), the electrodes 52 may simply be supported in the water stream by being mechanically fastened to a PVC plastic pipe cap 51 threaded into a tee fitting 53 interposed in the line.

Preferably, the polarity of the DC potential applied to electrodes 52 is reversed at intervals, e.g. on the order of one to two minutes, so that the rate of sacrifice

is even; if the DC polarity were not periodically reversed, one electrode would erode much faster than the other. The shape of the electrodes, as illustrated in Figs. 7 and 8, wherein a generally semi-circular notch 52a is formed at the free end of each of the two electrodes 52 in the water stream, is also significant; it has been found that provision of the notches 52a tends to equalize the rate of sacrificial erosion of the electrode material along the length of the electrodes. In a prior design, wherein the electrodes were square-ended, the electrode materials tended to be sacrificially eroded from the tips of the electrodes much more quickly than near their support ends, so that they became tapered over time.

It will be appreciated by those of skill in the art that in many circumstances it is desirable to control the rate of addition of chemical species to a reaction such that the reaction is stoichiometric, or nearly so. However, stoichiometry is not necessary in the present reaction. The rate of addition of ionized gas atoms in the plasma is estimated to be typically one hundred times the stoichiometric rate at which the metal atoms of the electrodes are eroded away. The rate of supply of addition of ionized gas is proportional to the power supplied to the lamp power supplies and coils, while the rate of erosion of the electrodes 52 is proportional to the rate of supply of current to the electrodes. These rates may be controlled responsive to the amount of pollutants to be removed from the water stream. Typical gas flow rates in a small to moderate demand installation may be one to five CFM, while electrodes weighing on the order of 1 kg each may last six months to a year if 12 VDC is supplied at one ampere.

Where a greater quantity of water is to be disinfected and treated, a second embodiment of the ionized gas source 18 according to the invention may be employed. An example of this embodiment of this element of the invention shown

in Fig. 6 includes two thirty-six-inch 150 watt low pressure mercury vapor ultraviolet lamps 66; lamps 66 and the associated components may be multiplied according to the total water treatment and disinfectant demand. Each lamp 66 is located inside a plastic tube 68 sealed at one end 70 and open at the other, to create an air intake 71 which will typically be provided with a filter 73. Within each plastic tube 68 is a carbon steel tube 72 which serves to support a coil 74 of wire helically wrapped once along the length of tube 72 parallel to the axis of the UV lamp 66. Accordingly, as indicated in connection with the embodiment of the reactor shown in Figs. 2 - 4, the UV lamp 66 is surrounded by a coil 74 providing an electric and/or magnetic field in the vicinity of the lamp. Preferably each coil is in series with a corresponding solid state lamp power supply 75, as indicated. Typical 150 watt lamp power supplies provide pulsating current averaging 180 VAC at 750 milliamps; as above, typically the power is pulsed such that the voltage and current both periodically increase by 30% from their average values. The plastic tubes 68 are typically 2 1/2" OD, to receive the carbon steel tubes 72, having the coils 74 wrapped therearound, with the UV lamps 66 within the carbon steel tubes 72 such that an exposure zone is defined within each tube. The upper outlet of each plastic tube 68 is connected to venturi 14 (Fig. 1), such that an air stream is drawn along an air flow path from the lower ends of the tubes. Air in the exposure zone is subjected to UV radiation and substantial magnetic and electric fields for a residence time determined by the flow rate of the air through the tubes. As above, the residence time of the air in the exposure zone defined by the interior of the tubes 72 is preferably on the order of 1-2 minutes.

In both embodiments of the lamps and power supplies, under certain circumstances, the lamp current can be

conveniently pulsed, providing ignition current to the lamp filaments and generating increased ionizing energy from the lamp. In particular, where the heater filaments 63 provided at either end of conventional low pressure ultraviolet lamps 36 (see Fig. 5) are located within the magnetic field provided by the corresponding coil, the lamp may be extinguished regularly, e.g. corresponding to the 60 Hz line frequency. This has the effect of causing the heater filaments 63 to be pulsed repetitively and rapidly, and accordingly to emit a greater proportion of ionizing radiation in the ultraviolet range of 160 to 180 nm wavelength, as well as more infrared, than if the lamp 36 were steadily lit. As noted above, such short-wavelength UV ionizes oxygen very effectively, while infrared radiation can be particularly useful in ionizing nitrogen. As the nitrogen is ionized, free electrons are produced which may further assist in oxygen gas ionization. Accordingly, there may be water streams wherein the specific configuration of the lamp and coil combination can desirably be configured to pulse the lamp current, optimizing both oxygen and nitrogen gas ion production.

The scaling of the components of the system to suit the amount of water to be processed and the amount of water treatment and disinfection needed thereby responsive to the particular process treatment required is within the skill of the art. In a relatively small system, two of the twelve-inch, 20 watt lamps of the Figs. 2 - 4 embodiment may be provided in container 30, supplying the ionized gas plasma thus produced to a single venturi, just upstream of a single pair of electrodes. In a system requiring more treatment and disinfection, four of the 20 watt lamps of the Figs. 2 - 4 embodiment may be provided in a single container 30, and their output split between two venturis and two pairs of electrodes. In an industrial or larger environmental system requiring still higher levels of water

treatment and disinfection, a pair of the much larger 150 watt lamps as shown in Fig. 6 may be employed, and the plasma produced thereby split between two venturis feeding two pairs of electrodes. Other modifications are, of course, within the skill of the art.

While a number of preferred embodiments of the invention and alternative configurations thereof have been disclosed, these are not intended to be limiting of the invention, but merely as exemplary thereof. The invention is to be limited only by the following claims.

WHAT IS CLAIMED IS:

1. A method for removing pollutants, impurities, organics, and other undesirable components from a water stream, comprising the steps of:

defining a stream of atmospheric air;

5 simultaneously exposing said stream of atmospheric air to radiation of predetermined wavelength and energy content, and to one or both of electric and magnetic fields, whereby a stream of air including a substantial fraction of ionized gas molecules is generated;

10 introducing said stream of air including ionized gas molecules to said water stream;

providing a stream of ions of elements which, when chemically combined with the ions of said stream of ionized gas molecules, form compounds having one or more of bactericidal, viricidal, algicidal and fungicidal disinfection properties;

15 mixing said water stream, having had said stream of air including ionized gas molecules introduced thereinto, with said stream of ions of elements, under conditions such that one or more of said compounds are formed, and such that one or more of bacteria, viruses, algae, and fungi in said water stream are killed; and

20 filtering said water stream after said mixing step, to remove said killed bacteria, viruses, algae, and fungi therefrom.

2. The method of claim 1, wherein said water stream is mixed with said stream of ions of elements by exposing said water stream to charged metallic electrodes formed of said elements.

3. The method of claim 2, wherein said electrodes comprise stannous, silver, and copper metals, in

proportions selected responsive to the characteristics of the water stream.

5 4. The method of claim 3, wherein the stannous, silver, and copper metals of said electrodes are provided in the approximate proportions of 5:10:85 respectively by weight, for treatment of contaminated water as typically encountered in swimming pool water streams or other environmental water treatment streams.

5 5. The method of claim 3, wherein the ionized gas molecules formed include one or more of O_2^- , N_2^+ , O_2 , and O_3 ions, whereby one or more of $Cu^+NO_3^-$, algicide, $Ag^+NO_3^-$, bactericide, and $Sn^{++}C_4H_4O_6^{--}$, fungicide and viricide disinfectant compounds are formed.

6. The method of claim 2, wherein at least two said electrodes are provided, and a DC potential, the polarity of which is reversed at intervals, is applied across said electrodes.

5 7. The method of claim 6, wherein current at approximately one ampere and 12 VDC is applied across said electrodes, and comprising the further step of reversing the polarity of said current at intervals on the order of two minutes.

5 8. The method of claim 1, wherein said water stream is passed through a venturi, producing a reduced pressure point downstream thereof, and said stream of air including ionized gas molecules is introduced at or near said reduced pressure point.

9. The method of claim 1, wherein said stream of air including ionized gas molecules is generated by defining an

5 atmospheric air flow path from an intake through an exposure zone to a point at which said stream of air is introduced into said water stream, and wherein said step of exposing said air to radiation of predetermined wavelength and energy content and to one or both of electric and magnetic fields is performed in said exposure zone, whereby said ionized gas molecules are generated.

10. The method of claim 9, wherein said radiation of predetermined frequency includes at least ultraviolet radiation of approximately 160 - 185 nm wavelength.

11. The method of claim 10, wherein said radiation of predetermined frequency further includes ultraviolet radiation of approximately 250 - 265 nm wavelength.

12. The method of claim 10, wherein said radiation of predetermined frequency further includes infrared radiation.

5 13. The method of claim 9, wherein said air being exposed to radiation of predetermined wavelength and energy content is further exposed to one or both of electric and magnetic fields by application of a suitable alternating-current drive signal to coil means substantially enclosing one or more elongated lamps emitting said radiation.

14. The method of claim 13, wherein said coil means comprises a helical coil wrapped lengthwise about a metallic tube enclosing each said elongated lamp.

15. The method of claim 13, wherein said coil means comprises a number of spaced metallic wires extending lengthwise along each said elongated lamp.

16. The method of claim 9, comprising the further step of controlling the flow rate of air along said atmospheric air flow path such that said air remains in said exposure zone for an average residence time on the order of one to two minutes.

17. Apparatus for removing pollutants, impurities, organics, and other undesirable components from a water stream, comprising:

means for defining a stream of atmospheric air;

means for simultaneously exposing said stream of atmospheric air to radiation of predetermined wavelength and energy content, and to one or both of electric and magnetic fields, whereby a stream of air including ionized gas molecules is generated;

means for introducing said stream of air including ionized gas molecules to said water stream;

means for providing a stream of ions of elements which, when chemically combined with said ionized gas molecules, form compounds having one or more of bactericidal, viricidal, algicidal and fungicidal disinfection properties;

means for mixing said water stream, having had said stream of ionized gas molecules introduced therein, with said stream of ions of elements under circumstances such that one or more of bacteria, viruses, algae, and fungi in said water stream are killed; and

means for filtering said water stream after said exposure step, to remove said killed bacteria, viruses, algae, and fungi therefrom.

18. The apparatus of claim 17, wherein said means for mixing said water stream with a stream of ions of elements comprises at least a pair of oppositely-charged metallic

5 electrodes formed of said elements, and means for directly exposing said water stream to said electrodes.

19. The apparatus of claim 18, wherein said electrodes are formed of stannous, silver, and copper metals, in proportions selected responsive to the characteristics of the water stream.

20. The apparatus of claim 19, wherein said stannous, silver, and copper metals of said electrodes are provided in the proportions of 5:10:85 by weight respectively, for treatment of water streams as typically encountered in swimming pool, drinking water, industrial water purification, and other types of environmental water treatment applications.

21. The apparatus of claim 18, further comprising means for applying a DC potential, the polarity of which is reversed at intervals, across said electrodes.

22. The apparatus of claim 17, wherein said means for defining a stream of air comprises means for defining an atmospheric air flow path from an intake, through an exposure zone, to a point at which said stream of air is mixed with said water stream, and wherein said means for exposure of said air to radiation of predetermined wavelength and energy content, and to one or both of electric and magnetic fields are located in said exposure zone, whereby a stream of air including ionized gas plasma molecules is generated.

23. The apparatus of claim 22, wherein said means for exposure of said air to radiation of predetermined frequency comprises an elongated lamp emitting ultraviolet

5 radiation of at least approximately 160 - 185 nm wavelength.

24. The apparatus of claim 23, wherein said lamp further emits ultraviolet radiation in the 250 - 265 nm range, and infrared radiation.

5 25. The apparatus of claim 17, wherein said means for simultaneously exposing said air to radiation of predetermined wavelength and energy content and to one or both of electric and magnetic fields comprises coil means substantially enclosing one or more elongated lamps emitting said radiation, and power supply means for application of a suitable alternating-current drive signal to said coil means.

26. The apparatus of claim 25, further comprising power supply means for supplying pulsed power to said lamps.

27. The apparatus of claim 25, wherein said pulsation is synchronized to the AC power waveform supplying power to said power supply means.

28. The apparatus of claim 25, wherein said coil means comprises a helical coil wrapped lengthwise about a metallic tube enclosing each said elongated lamp.

29. The apparatus of claim 25, wherein said coil means comprises a number of spaced metallic wires extending lengthwise along each said elongated lamp.

30. The apparatus of claim 22, further comprising a venturi through which said water stream flows, such that said stream experiences negative relative pressure in the

vicinity of said venturi, and conduit means connecting said
5 exposure zone to the point at which said stream experiences
negative relative pressure, such that said stream of
ionized gas molecules is drawn into and mixed with said
water stream.

31. The apparatus of claim 22, wherein said means for
defining an atmospheric air flow path from an intake,
through an exposure zone, to a point at which said air
stream is mixed with said water stream comprises a sealed
5 container having an air intake opening and an exit port,
and conduit means connected between said exit port and said
point at which said air stream is mixed with said water
stream, said exposure zone being located in said
container.

32. The apparatus of claim 31, wherein said container
comprises one or more elongated tubular members for
receiving elongated lamps emitting said radiation, the
intake of each container being located at one end of each
5 said tubular member, and the conduit means being connected
to the opposite end thereof.

33. The apparatus of claim 31, wherein said container
comprises a sealed box for receiving one or more elongated
lamps emitting said radiation, and means for defining an
air flow path through said box from an intake to an exit
5 port thereof, located such that air flowing along said
defined flow path is exposed to radiation from said one or
more lamps for a predetermined minimum average residence
time.

34. A water treatment and disinfecting system for
retrofit applications and the like, comprising;

means for ionizing gas molecules in an atmospheric air stream and supplying said air stream to an outlet;

5 a conduit comprising a venturi, for being interposed in a preexisting water line, said venturi having a throat and an inlet connected to the outlet of said means for ionizing, said inlet being disposed downstream of the throat of said venturi, whereby said air stream is drawn
10 into and mixed with water flowing in said water line by negative relative pressure experienced at said inlet in said venturi;

at least one pair of electrodes disposed in said conduit downstream of said inlet in said venturi, whereby
15 ionized gas molecules in said air stream having been mixed with said water stream are exposed to said electrodes;

power supply means for applying a DC potential across said electrodes; and

further power supply means for driving said means for
20 ionizing gas molecules.

35. The system of claim 34 wherein said means for ionizing gas molecules comprises at least one ultraviolet lamp and at least one coil means connected to said further power supply means and disposed in a container, such that
5 a stream of atmospheric air drawn through said container experiences an average residence time in the vicinity of said ionizing lamp and said coil means for at least on the order of one minute, whereby a significant fraction of the atoms of said air stream are ionized thereby.

36. The system of claim 35 wherein plural combinations each of a lamp and a coil means are provided in a single container.

37. The system of claim 35 wherein said ultraviolet lamp is elongated, and said coil means comprises a

continuous conductor wrapped helically around said elongated ultraviolet lamp.

5 38. The system of claim 35 wherein said ultraviolet lamp is elongated, and said coil means comprises a plurality of individual wires running generally parallel to the direction of elongation of said elongated ultraviolet lamp.

5 39. The system of claim 34 wherein the material of said electrodes is selected from stannous, silver, and copper metals, combinations thereof, and other metals selected responsive to the composition of the water stream to be purified and the material to be disinfected therein.

5 40. The system of claim 39 wherein said electrodes each comprise elongated members having one free end exposed to the stream of water to be treated, and an opposite end connected to said power supply means, and wherein said free end of each electrode is notched inward in a semi-circular concave manner.

41. The system of claim 34, wherein said power supply means applying DC power to said electrodes is controlled such that the polarity applied to the electrodes is reversed at intervals on the order of one minute.

42. The apparatus of claim 35, wherein said further power supply means for supplying power to said lamp provides pulsed power, such that said lamp is periodically extinguished and reilluminated.

43. A method for disinfecting a water stream, comprising the steps of:

exposing a stream of atmospheric air to an
electromagnetic field and radiation, such that a fraction
5 of nitrogen molecules of said air are ionized; and
mixing said stream of air with said generated ionized
nitrogen molecules therein with said water stream.

44. A method for disinfection of a water stream,
comprising the steps of:

exposing a stream of atmospheric air to an
electromagnetic field and radiation, such that a fraction
5 of oxygen molecules of said air are ionized; and
mixing said stream of air with said generated ionized
oxygen molecules therein with said water stream.

45. The method of claim 44 wherein said ionized
oxygen molecules include one or more species of singlet
molecular oxygen and ozone.

46. A method for treatment of a water stream,
comprising the steps of:

exposing a stream of atmospheric air to an
electromagnetic field and radiation, such that a fraction
5 of oxygen molecules of said atmospheric air exhibit
increased paramagnetic properties as compared to natural
background levels of paramagnetism exhibited by atmospheric
oxygen molecules; and

mixing said stream of air with said generated
10 accelerated paramagnetic oxygen molecules therein with said
water stream.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/13377

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : CO2F 1/467

US CL : 210/695

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : Please See Extra Sheet.

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
NONE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 4,655,933 (JOHNSON ET AL.) 07 APRIL 1987, SEE ENTIRE DOCUMENT	1-46
Y	US, A, 4,936,979 (BROWN) 26 JUNE 1990, SEE ENTIRE DOCUMENT	1-42
Y	US, A, 4,492,618 (EDER) 08 JANUARY 1985, SEE ENTIRE DOCUMENT	1-42
Y	US, A, 3,697,420 (BLAISDELL ET AL.) 10 OCTOBER 1972, SEE ENTIRE DOCUMENT	13-15, 25-29, 35-38
Y	US, A, 4,640,782 (BURLESON) 03 FEBRUARY 1987, SEE ENTIRE DOCUMENT	8, 30, 34-42
Y, P	US, A, 5,443,719 (JOHNSON ET AL.) 22 AUGUST 1995, SEE ENTIRE DOCUMENT	8, 13-15, 25-30, 34-46

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	* T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* A* document defining the general state of the art which is not considered to be of particular relevance	* X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* E* earlier document published on or after the international filing date	* Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* &*	document member of the same patent family
* O* document referring to an oral disclosure, use, exhibition or other means		
* P* document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search
31 JANUARY 1996

Date of mailing of the international search report
15 FEB 1996

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231
Facsimile No. (703) 305-3230

Authorized officer
PETER A. HRUSKOCI
Telephone No. 703-308-3839

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/13377

B. FIELDS SEARCHED

Minimum documentation searched

Classification System: U.S.

210/695, 721, 748, 752, 758, 764, 192, 198.1, 205, 243; 204/149, 150, 152, 293; 422/ 22, 24, 29, 186.07, 186.1, 186.12, 186.15, 186.3