US 20020174296A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2002/0174296 A1

Ulrich et al. (43) Pub. Date: Nov. 21, 2002

(54) DISK REPLACEMENT VIA HOT SWAPPING WITH VARIABLE PARITY

(76) Inventors: **Thomas R. Ulrich**, Rancho Santa Margarita, CA (US); **James R. Schweitzer**, Huntington Beach, CA (US); **Gregory D. Bolstad**, Tustin, CA (US); **Jay G. Randall**, Newport Beach, CA (US); **John R. Staub**, Newport Beach, CA (US); **Wilbur George Priester**, Westminster, CA (US)

Correspondence Address:
KNOBBE MARTENS OLSON & BEAR LLP
620 NEWPORT CENTER DRIVE
SIXTEENTH FLOOR
NEWPORT BEACH, CA 92660 (US)

(21) Appl. No.: **10/060,939**

(22) Filed: **Jan. 29, 2002**

Related U.S. Application Data

(60) Provisional application No. 60/264,671, filed on Jan. 29, 2001. Provisional application No. 60/264,694, filed on Jan. 29, 2001. Provisional application No. 60/264,672, filed on Jan. 29, 2001. Provisional application No. 60/264,673, filed on Jan. 29, 2001. Provisional application No. 60/264,670, filed on Jan. 29, 2001. Provisional application No. 60/264,669, filed on Jan. 29, 2001. Provisional application No. 60/264,668, filed on Jan. 29, 2001. Provisional application No. 60/302,424, filed on Jun. 29, 2001.

Publication Classification

(51) **Int. Cl.**[7] **G06F 12/16**

(52) **U.S. Cl.** **711/114**; 711/170; 709/203; 707/200

(57) ABSTRACT

A system and method for enhanced disk replacement via hot swapping with variable parity is described. The system and method operate on a computer storage system that includes a plurality of disk drives for storing distributed parity groups. Each distributed parity group includes storage blocks. The storage blocks include one or more data blocks and a parity block that is associated with the one or more data blocks. Each of the storage blocks is stored on a separate disk drive such that no two storage blocks from a given parity set reside on the same disk drive. The computer storage system further includes file system metadata to describe a location of each of the storage blocks. The computer storage system further includes a resource-allocation module to recognize a new disk drive that is hot-swapped into the plurality of disk drives during file system operation and to use the new disk drive to store one or more storage blocks.




110
C
C
C
C
C
C
C
C
C
120
COMMUNICATION FABRIC
130
131
132
133
134
135
S3
S4
S5
S6
150
151
140
141
160
100

FIG. 1


140
DATA
222
221
221
FIBRE CHANNEL
FIBRE CHANNEL
220
FC-API
DISK POLLING
280
260
JI
255
DSO
FS
245
250
CSO
270
CLIENT POLLING
240
SI
205
232
10/100T ETHERNET
GIGABIT ETHERNET
231
230
290
ADMIN INTERFACE
CI
286
285
FC-API
210
FIBRE CHANNEL
FIBRE CHANNEL
211
211
120
COMMUNICATION WITH OTHER SERVER NODES
COMMUNICATION WITH OTHER SERVER NODES
110
CI
201

FIG. 2


G-NODE TABLE
CONTAINS INFORMATION ABOUT FILE ATTRIUTES
(SEE FIGURE 6)
330
POINTS TO A G-NODE
320
GEE TABLE
CONTAINS INFORMATION ABOUT FILE BLOCK LOCATION
(SEE FIGURE 5)
POINTS TO A GEE-STRING
310
FILENAME TABLE
CONTAINS INFORMATION ABOUT FILE NAMES
(SEE FIGURE4)
POINTS TO A CHILD GNID INDEX
POINTS TO THE FILE'S GNODE AND TO THE PARENT'S G-NODE
POINTS TO A GEE
POINTS TO A CACHE NODE
CACHE NODE TABLE
CONTAINS INFORMATION ABOUT CACHED FILE BLOCK
(SEE FIGURE 8)
350
POINTS TO A FILENAME ENTRY
GNID TABLE
CONTAINS INFORMATION ABOUT DIRECTORY STRUCTURE
(SEE FIGURE 7)
340
OTHER SERVERS' G-NODE TABLES (FOR CHILD FILES STORED ON OTHER SERVERS)

FIG.3


310
ARRAY INDEX
411
412
413
410
414
421
422
423
420
424
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
<SOS>
CSUM
3
'D'
'o'
'e'
<SOS>
csum
6
'T'
'h'
'o'
'm'
'a'
's'
ARRAY INDEX
85
86
87
88
89
90
91
92
93
94
95
96
97
<DS>
CSUM
4
'F'
'r'
'o'
'g'
<SOS>
csum
2
'l'
't'
<SOS>
431
432
433
434
430
441
442
443
444
440

FIG. 4


320
590
591
592
500
550
551
552
INDEX
G-CODE
DATA
FILE LOGICAL BLOCK
45 GNODE GNODE=67, EXTENT=2, ROOT=TRUE
46 DATA DISK LOGICAL BLOCKS: 456,457 DRIVE 13 1
47 DATA DISK LOGICAL BLOCKS: 667,668 DRIVE 15 2
48 DATA DISK LOGICAL BLOCKS: 112,113 DRIVE 19 3
49 PARITY DISK LOGICAL BLOCKS: 554,555 DRIVE 2
50 DATA DISK LOGICAL BLOCKS: 458,459 DRIVE 13 4
51 DATA DISK LOGICAL BLOCKS: 669,670 DRIVE 15 5
52 DATA DISK LOGICAL BLOCKS: 119,120 DRIVE 19 6
53 PARITY DISK LOGICAL BLOCKS: 556,557 DRIVE 2
54 LINK INDEX 76
... ...
76 GNODE GNODE=67, EXTENT=3, ROOT=FALSE
77 DATA DISK LOGICAL BLOCKS: 460,461,462 DRIVE 13 7
78 DATA DISK LOGICAL BLOCKS: 671,672,673 DRIVE 15 8
79 PARITY DISK LOGICAL BLOCKS: 121,122,123 DRIVE 19
80 LINK INDEX 88
... ...
88 GNODE GNODE=67, EXTENT=3, ROOT=FALSE
89 DATA DISK LOGICAL BLOCKS: 463,464,465 DRIVE 13 9
90 DATA DISK LOGICAL BLOCKS: 674,675,676 DRIVE 15 10
91 PARITY DISK LOGICAL BLOCKS: 124,125,126 DRIVE 19
92 GNODE GNODE=43, EXTENT=4, ROOT=FALSE
... ...
510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529

FIG. 5


ATTRIBUTE DATA
602
FILE ATTRIBUTE-TYPE
604
FILE ATTRIBUTE-MODE
606
FILE ATTRIBUTE-LINKS
608
FILE ATTRIBUTE-UID
610
FILE ATTRIBUTE-GID
612
FILE ATTRIBUTE-SIZE
614
FILE ATTRIBUTE-USED
620
FILE ATTRIBUTE-FILEID
622
FILE ATTRIBUTE-ATIME
624
FILE ATTRIBUTE-MTIME
626
FILE ATTRIBUTE-CTIME
628
CHILD GNID INDEX
630
GEE INDEX-LAST USED
631
GEE OFFSET-LAST USED
632
GEE INDEX-MIDPOINT
633
GEE OFFSET-MIDPOINT
634
GEE INDEX-TAIL
635
GEE OFFSET-TAIL
636
GEE INDEX-ROOT
638
GNODE STATUS
640
QUICK SHOT STATUS
642
QUICK SHOT LINK
600

FIG. 6


700
STATUS
PARENT GNODE PTR
SIBLING GNID-PTR
GNODE PTR
FILENAME PTR
FORBI GNID PTR
BCKBIGNID PTR
710
711
712
713
720
730
740
750
760
770
780

FIG. 7


DATAGEE
810
815
PREVPTR
820
NEXTPTR
825
CACHEBLOCKADDR
830
READCT
835
CACHETIME
840
REGENERATED
845
CACHEBLOCKHIADDR
850
CACHEBLOCKLOADDR
800

FIG. 8A


350
NORMAL LIST
MOST RECENTLY USED
LAST RECENTLY USED
860
875
880
READ LIST
870
READ LIST CACHE NODES ARE RETURNED TO "TOP" OF NORMAL LIST
NORMAL LIST CACHE NODES MAY COME FROM ANYWHERE ON NORMAL LIST
WRITE LIST
865
WRITE LIST CACHE NODES ARE RETURNED TO "TOP" OF NORMAL LIST
NORMAL LIST CACHE NODES MAY COME FROM ANYWHERE ON NORMAL LIST

FIG. 8B


900
910
911
912
920
921
922
923
LOCKSTATUS
TIMEOUTCT
NEXT
PENDING
MODE
ACCESS
CLIENTLD
UID
OFFSET
LENGTH
EXCLUSIVE
SVID
930
931
932
933
934
935
936
937
938
939
940
941
942
943

FIG. 9


1050
CLIENTID
COUNTER
ITLINK
GTLINK
STACKNEXT
STACKPREV
1030
1020
1040
1010
1000
1001
1002
1003
1004

FIG. 10


1130
1120
1110
1100
1105
1106

FIG. 11


1200
1210
STATUS
1220
INTENT TYPE
1230
GOAL BUFFER INDEX
1240
SPARE
1250
DRIVE SECTOR
1260
DRIVE
1270
INTENT DATA

FIG. 12


1300
1310
1320
1330
RECOMMENDED NIC
SERVER ID OF THE FILE'S PRIMARY OWNER
GNODE INDEX
BIT31
BIT29
BIT23
BIT0

FIG. 13


1410
1420
"AAAAA"
123
1
1300
1320
1330
CLIENT
110
130
GNODE TABLE
GNID TABLE
SERVER"123"
1430
602
330
628
636
340
740
750
760
FILENAME TABLE
310
1442
1432
1436
1438
1446
1448
1440
1444
GEE TABLE
590
591
320
1460
CACHE
1456
1458
1450
1452
GNODE
GNODE=9,ROOT=T
CACHE DATA
7
CACHE NODE TABLE
350
W
FILE DATA
1454
132
SERVER"X"

FIG. 14A


1410
1420
"AAAAA"
123
9
1300
1321
1331
CLIENT
110
130
SERVER"123"
GNODE TABLE
GNID TABLE
FILENAME TABLE
1430
602
330
628
636
340
740
750
760
310
1442
0
1
NFDIR
3
2
9
NFREG
2
1432
1448
1436
1440
4
6
123,9
"DE"
"ABCD"
"AAAAA"
1438
1446
GEE TABLE
590
591
320
GNODE
GRADE=9,ROOT=T
CACHE DATA
7
1450
1452
CACHE NODE TABLE
CACHE
1456
1458
W
FILE DATA
350
1454
DISK ARRAY
140

FIG. 14B


1500
START
1505
DOES CLIENT HAVE DESIRED FILE'S FILE HANDLE ?
1510
NO
CLIENT AND SERVER PERFORM FILE HANDLE LOOK-UP (SEE FIGURE 16)
1515
YES
CLIENT SENDS FILE ACCESS REQUEST TO SERVER INDICATED IN FILE HANDLE
1520
SERVER ACCESSES GNODE INDICATED IN FILE HANDLE
1525
SERVER ACCESSES APPROPRIATE GEE INDICATED IN GNODE
1530
IS GNODE CACHE PARITY OR CACHE DATA ?
1535
NO
SERVER CACHES FILE DATA FROM DISK (SEE FIGURE 17)
1540
YES
SERVER ACCESSES CACHE NODE INDICATED IN GEE
1545
SERVER MANIPULATES CACHE NODES AS NEEDED
1550
SERVER ACCESSES FILE DATA IN CACHE LOCATION INDICATED IN CACHE NODE
1555
SERVER PERFORMS DESIRED OPERATION ON FILE DATA
1560
END
1570

FIG. 15


1600
START
1605
CLIENT SENDS LOOK-UP REQUEST TO SERVER
1610
SERVER ACCESSES GNODE INDICATED IN LOOK-UP REQUEST
1615
SERVER USERS CHILD GNID INDEX IN GNODE TO ACCESS THE DIRECTORY'S GNID-STRING
1620
SERVER CALCULATES CHECKSUM AND FILENAME LENGTH FOR DESIRED NEXT PATHNAME COMPONENT
1625
SERVER USES FILENAME PTRFIELD IN GNID TO ACCESS FILENAME ENTRY
1630
IS CHECKSUM FROM FILENAME ENTRY GREATER THAN CHECKSUM FROM LOOK UP REQUEST ?
1635
YES
RETURN ERROR MESSAGE TO CLIENT: FILE NOT FOUND
1640
NO
DO CHECKSUMS AND FILENAME LENGTHS MATCH ?
1645
YES
DO FILENAMES MATCH ?
1650
YES
RETURN FILE HANDLE TO CLIENT
1655
NO
NO
ACCESS NEXT GNID ON GNID-STRING
1660
END-FILE HANDLE LOOK-UP
1665

FIG. 16


1540
START
1705
IDENTIFY LEAST RECENTLY USED CACHE NODE
1710
WRITE ASSOCIATED FILE DATA FROM CACHE TO DISK
1720
RETURN DATA GEE FROM CACHE NODE TO GEE TABLE
1730
COPY DATA GEE FOR NEW DATA INTO CACHE NODE
1740
COPY NEW DATA FROM DISK TO CACHE
1750
END
1760

FIG. 17


1800
START
1805
CLIENT SENDS FILE ALLOCATION REQUEST INCLUDING PARENT DIRECTORY'S FILE HANDLE AND FILENAME OF DESIRED FILE
1810
SERVER INDICATED IN PARENT'S FILE HANDLE RECEIVES REQUEST
1815
PARENT SERVER USES WORKLOAD STATISTICS FROM OTHER SERVER NODES TO DECIDE: WILL "PARENT" SERVER OWN THE NEW FILE ?
1820
NO
YES
"PARENT" SERVER SENDS REQUEST FOR FILE ALLOCATION TO A "SECOND" SERVER
1850
"SECOND" SERVER ALLOCATES NEW GNODE AND FILENAME ENTRY AND CREATES A NEW FILE
1855
"SECOND" SERVER SENDS FILE HANDLE FOR NEW FILE BACK TO "PARENT" SERVER
1860
"PARENT" SERVER ALLOCATES NEW GNODE AND CREATES NEW FILE
1830
"PARENT" SERVER CREATES NEW GNID AND FILENAME ENTRY
1835
"PARENT" SERVER SENDS FILE HANDLE FOR NEW FILE TO REQUESTING CLIENT
1840
END
1845

FIG. 18


600
1920
CACHED GNODE-C
....
CACHED GNODE-2
CACHED GNODE-1
CACHED GNODE-0
NOT IN CACHE
1900
GNR(N)
....
GNR(11)
GNR(10)
GNR(9)
GNR(8)
GNR(7)
GNR(6)
GNR(5)
GNR(4)
GNR(3)
GNR(2)
GNR(1)
GNR(0)
GNODE REDIRECTORS (GNR)
1910
FILE HANDLE IS THIS INDEX

FIG. 19


2010
STATUS
2020
LINKING INFORMATION
2030
GNODE
2040
FILE LOCATION DATA
128 BYTES
16K BYTES

FIG.20A


2004
SGLL
2009
GSPLB
SGL
2003
2000
SG
2008
GSPB
SGG
2002
GSP
2007
1910
GNR
SGD
2001
2006
GEE
DATA
2005

FIG. 20B


CONVENTIONAL RAID MAPPING
(PRIOR ART)
DISK ARRAY
DISK 0
DISK 1
DISK 2
DISK 3
DISK 4
DISK 5
DISK 6
DISK 7
DISK 8
DISK 9
DISK 10
DISK 11
2115
2110
DRIVE#
0 1 2 3 4 5 6 7 8 9 10 PARITY
2130
2120
STRIPE
0
1
2
3
4
5
6
7
8
9
N
STRIPE 2
STRIPE 3
STRIPE 4

FIG. 21



FIG. 22A



FIG. 22B


2320
FILE#1
DATA 1 DATA 2 DATA 5 DATA 6 DATA 7
2330
DATA 3 DATA 4
2335
DATA 1 DATA 2 PARITY 1-2
2330
2337
DATA 3 PARITY 3-4
DATA 4
DATA 5 DATA 6 DATA 7 PARITY 5-7
2340
FILE#2
DATA 1 DATA 2
2330
DATA 3 DATA 4
2335
DATA 1 DATA 2 PARITY 1-2
2330 2337
DATA 3 DATA 4 PARITY 3-4
2305
DISK NUMBER
2310
2300
LOGICAL BLOCK OR CLUSTER
0 1 2 3 4 5 6 7 8 9 10 11
2337
2337

FIG. 23


2400
CLIENT STORAGE REQUEST
2410
DATA
2415
RECEIVE DATA FROM CLIENT
2420
ANALYZE DATA/ DETERMINE BLOCK DISTRIBUTION
2430
PARSE INTO DATA BLOCK(S)
2440
DETERMINE PARITY GROUP ARRANGEMENT
2450
CALCULATE PARITY BLOCKS
2460
DETERMINE BLOCK DISTRIBUTION FOR STORAGE
2470
STORE BLOCKS
2480

FIG. 24A


2405
CLIENT STORAGE REQUEST
2410
ANALYZE DATA/ DETERMINE BLOCK DISTRIBUTION
2430
PARSE INTO DATA BLOCK(S)
2440
DETERMINE PARITY GROUP ARRANGEMENT
2450
DETERMINE BLOCK DISTRIBUTION FOR STORAGE
2470
2415
DATA
RECEIVE DATA FROM CLIENT
2420
CALCULATE PARITY BLOCKS
2460
STORE BLOCKS
2480

FIG. 24B


2320
FILE#1
DATA 1 DATA 2 DATA 5 DATA 6 DATA 7
2330
DATA 1 3
DATA 1 4
2335
DATA 1 DATA 2 PARITY 1-2
DATA 5 DATA 6 DATA 7 PARITY 5-7
2330
2337
DATA 1 3
PARITY 1 3-4
DATA 1 4
2340
FILE#2
DATA 2 1
DATA 2 2
2330
DATA 2 3
DATA 2 4
2335
DATA 2 1 DATA 2 2 PARITY 1-2 2
DATA 2 3 DATA 4 PARITY 2 3-4
2330 2337
2305
2310
2300
DISK NUMBER
0 1 2 3 4 5 6 7 8 9 10 11
LOGICAL DISK BLOCK OR CLUSTER
0 1 2 3 4 5 6 7 8 9 10 11 12 N
2337
2337
2490

FIG. 25



FIG. 26A



FIG. 26B


2530
DISK ARRAY INITIALIZATION USING GEE TABLE SPACE ALLOCATION
2532
2534
2536
2542
INDEX
G-CODE
DATA
...
45 GNODE EXTENT=2
46 DATA BLOCKS 456,457:DRIVE 13
47 DATA BLOCKS 667,668:DRIVE 15
48 DATA BLOCKS 112,113:DRIVE 19
49 PARITY BLOCKS 554,555:DRIVE 2
2538
2540
76 GNODE EXTENT=2
77 DATA BLOCKS 460,461,462:DRIVE 13
78 DATA BLOCKS 671,672,673:DRIVE 15
79 PARITY BLOCKS 121,122,123:DRIVE 19
2538
2540
88 GNODE EXTENT=2
89 DATA BLOCKS 463,464,465:DRIVE 2
90 DATA BLOCKS 674,675,676:DRIVE 5
91 PARITY BLOCKS 124,125,126:DRIVE 13
2540

FIG. 27


2448
ARRAY PREPARATION/ G-TABLE FORMATTING
DETERMINE DISK CHARACTERISTICS
2550
DETERMINE BLOCK/PARITY GROUP ALLOTMENT
2555
DETERMINE MAPPING/CREATE GEE TABLE
2560
DATA STORAGE/GEE TABLE UPDATES
2575

FIG. 28


2605
2600
FILE
LB1 LB2 LB3 LB4 LB5 LB6 LB7 LB8 LB9 LB10
2610
2610
2617
2620
LB-1 LB-2 LB-3 PARITY1-3 LB-4 LB-5 LB-6 PARITY4-6
2615
2617
LB-7 LB-8 PARITY7-8 LB-9 LB-10 PARITY9-10
2615
2530
2532
2534
2536
INDEX
G-CODE
DATA
2635
2542
2637
FILE LOGICAL BLOCK
2630
2538
2660
2640
2661
2650
2632
2615
2655
2656
2657
2658
2627
2628
2629
45 GNODE GNODE=67,EXTENT=2,ROOT=TRUE
46 DATA BLOCKS 456,457:DRIVE 13 1
47 DATA BLOCKS 667,668:DRIVE 15 2
48 DATA BLOCKS 112,113:DRIVE 19 3
49 PARITY BLOCKS 554,555:DRIVE 2 4
50 DATA BLOCKS 458,459:DRIVE 13 5
51 DATA BLOCKS 669,670:DRIVE 15 6
52 DATA BLOCKS 114,115:DRIVE 19
53 PARITY BLOCKS 556,557:DRIVE 2
54 LINK INDEX 76
76 GNODE GNODE=67, EXTENT=3, ROOT=FALSE
77 DATA BLOCKS 460,461,462:DRIVE 13 7
78 DATA BLOCKS 671,672,673:DRIVE 15 8
79 PARITY BLOCKS 121,122,123:DRIVE 19
80 LINK INDEX 88
88 GNODE GNODE=67, EXTENT=2, ROOT=FALSE
89 DATA BLOCKS 463,464,465:DRIVE 2 9
90 DATA BLOCKS 674,675,676:DRIVE 5 10
91 PARITY BLOCKS 124,125,126:DRIVE 13

FIG.29


DRIVE FAILURE RECOVERY MECHANISM
140
2305
2335
DISK0
DISK1
DISK2
DISK3
DISK4
DISK5
DISK6
DISK7
DISK8
DISK9
DISK10
DISK11
DATA 1 1
DATA 1 2
PARITY 1 1-2
3072
LOSS OF DATA INTEGRITY
3074
RECOVER AND REDISTRIBUTE
DATA 1 2-REC
3076
SECOND DRIVE FAILURE
3078
DATA 1 1-REC
NOMINAL OPERATION MAINTAINED

FIG. 30


3172
DATA RECOVERY PROCESS
IDENTIFY DATA OR DRIVE FAULT/ DETERMINE AFFECTED BLOCKS
3175
DETERMINE ASSOCIATED PARITY GROUP
3177
IDENTIFY AFFECTED BLOCKS IN G-TABLE
3179
DETERMINE AVAILABLE DISK SPACE
3180
UPDATE G-TABLE/REBUILD DATA
3181

FIG. 31



FIG. 32A



FIG. 32B


3360
RECEIVE FILE DATA
3361
ASSESS FILE DATA CHARACTERISTICS
3363
IDENTIFY AVAILABLE PARITY GROUP CONFIGURATIONS
3365
SELECT PARITY GROUP CONFIGURATION BASED ON UTILIZATION CHARACTISTICS
3367
STORE FILE DATA IN SELECTED PARITY GROUP
3369

FIG.33

FIG.34A



FIG.34B



FIG.34C





FIG. 35A

FIG. 35B




3600
MONITOR PARITY GROUP AVAILABILITY
3602
NO
3604
PARITY GROUP DEPLETION OBSERVED ?
YES
ASSESS PARITY GROUP STATISTICS
3606
REDISTRIBUTE PARITY GROUPS
3608

FIG.36


3490
OCCUPIED
9200 GROUPS
8200 GROUPS
9200 GROUPS
4500 GROUPS
+2000 GROUPS OF 4-BLOCK PARITY
-3200 GROUPS OF 1-BLOCK PARITY
EQUIVALENT SPACE OF 1200 GROUPS OF 1-BLOCK PARITY FREED
1200
3492
REMAINING FREE/AVAILABLE
5400 GROUPS
1800 GROUPS
800 GROUPS
300 GROUPS
OPTIMIZATION
3785
3490
REMAINING FREE/AVAILABLE
OCCUPIED
3492
3480
4 BLOCK PARITY 2800 GROUPS 7200 GROUPS
3481
3 BLOCK PARITY 1800 GROUPS 8200 GROUPS
3482
2 BLOCK PARITY 800 GROUPS 9200 GROUPS
3483
1 BLOCK PARITY 2300 GROUPS 7700 GROUPS

FIG. 37


3800
PERFORM FILE OPERATONS
3851
COLLECT RESOURCE UTILIZATION STATISTICS
3854
COLLECT FILE ACCESS STATISTICS
3852
PREDICT FUTURE FILE AND RESOURCE UTILIZATION (WORKLOAD)
3856
WORKLOAD DISTRIBUTION
3858
CONTENT DISTRIBUTION
3860

FIG. 38


3900
CLIENTS
110
120
COMMUNICATION FABRIC
3905
3910
3915
F1
F2
F3
F4
F5
FAST SMALL SF1
FAST AVERAGE SF2
AVERAGE LARGE
FAST SMALL SF3
FAST LARGE SF1'
FAST LARGE SF2'
DEFECTIVE
NEW SLOW LARGE
3920
3922
VERY FAST SMALL LF1
VERY FAST SMALL LF2
VERY FAST SMALL LF3
RESOURCE
3924
SLOW LARGE
SLOW LARGE
RESOURCE
SLOW LARGE
3926
SLOW VERY LARGE
TAPE DRIVE
FAST LARGE
3928

FIG. 39


4005
SERVER INTERFACE
4010
FILE SYSTEM
4008
4012
4014
4016
NETWORK DRIVERS AND STACKS
INTER-NODE COMM
BACKUP
ADMIN INTERFACE
PROTOCOL INTERPRETER
PROTOCOL INTERPRETER
SERVER MANAGER
REQUEST PROCESSING
DATA AND METADATA MGMT
STORAGE MGMT
NETWORK DRIVER
OBJECT POSITIONER
4018
4025
OBJECT POSITIONING PLAN
4000
4020
LOAD BALANCING DATA
F1 LOAD BALANCING DATA
F2 LOAD
F4 LOAD
F5 LOAD
F3 LOAD BALANCING DATA
STATISTICS

FIG. 40


F3 OBJECT
POSITIONING PLAN
•PUSH LF TO F4–F5 CLUSTER
•ISSUE FILE HANDLE FOR LF=STALE
•IF REQUESTED,
•SEND ACCEPTANCE FOR COPY OF SF TO F1
•CREATE COPY OF SF
•SEND FILE HANDLE OF SF TO F1
4025

FIG. 41


110
CLIENTS
4214
NETWORK INTERFACE
NETWORK INTERFACE
4218
4201
DATA/PARITY CACHE RAM A NON VOLATILE
DATA/PARITY CACHE RAM B NON VOLATILE
4220
DATA ENGINE
4205
4210
CPU(S)
NETWORK BUS
4216
FILE SYSTEM METADATA RAM NON VOLATILE
4202
STORAGE BUS
4212
STORAGE INTERFACE
STORAGE INTERFACE
140, 141
DISKS
130

FIG. 42


4220
DATA CACHE RAM B
4320
CACHE CONTROLLER
4331
4333
4343
4301
4201
4202
4302
NETWORK BUS A
EXTERNAL BUS INTERFACE
CACHE READ BUFFER
CACHE WRITE BUFFER
CACHE WRITE BUFFER
FEED BACK BUFFER
CACHE WRITE BUFFER
CACHE READ BUFFER
4335
4339
4341
4349
PARITY ENGINE
PARITY ENGINE
4337
4380
4347
4345
EXT BUS WRITE BUFFER
CONTROL LOGIC
EXT BUS WRITE BUFFER
4336
4346
4334
4342
4344
EXT BUS WRITE BUFFER
EXT BUS WRITE BUFFER
4332
4338
4340
4348
PARITY ENGINE
PARITY ENGINE
4330
4310
CACHE READ BUFFER
CACHE WRITE BUFFER
CACHE WRITE BUFFER
FEED BACK BUFFER
CACHE WRITE BUFFER
CACHE READ BUFFER
ASIC
CACHE CONTROLLER
4318
4218
DATA CACHE RAM A
EXTERNAL BUS INTERFACE
NETWORK BUS B

FIG. 43


PCI MAP
BLOCK SIZE
OPCODE
SPARE
PARITY INDEX
SPARE
RAM ADR
63.....62,61.....59,58.....56,55.....51,50.....35,34,.32, 31.....0
4400

FIG. 44

DISK REPLACEMENT VIA HOT SWAPPING WITH VARIABLE PARITY

REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority benefit under 35 U.S.C. §119(e) from all of the following U.S. Provisional Applications, the contents of which are hereby incorporated by reference in their entirety:

[0002] U.S. Provisional Application No. 60/264,671, filed Jan. 29, 2001, titled "DYNAMICALLY DISTRIBUTED FILE SYSTEM";

[0003] U.S. Provisional Application No. 60/264,694, filed Jan. 29, 2001, titled "A DATA PATH ACCELERATOR ASIC FOR HIGH PERFORMANCE STORAGE SYSTEMS";

[0004] U.S. Provisional Application No. 60/264,672, filed Jan. 29, 2001, titled "INTEGRATED FILE SYSTEM/PARITY DATA PROTECTION";

[0005] U.S. Provisional Application No. 60/264,673, filed Jan. 29, 2001, titled "DISTRIBUTED PARITY DATA PROTECTION";

[0006] U.S. Provisional Application No. 60/264,670, filed Jan. 29, 2001, titled "AUTOMATIC IDENTIFICATION AND UTILIZATION OF RESOURCES IN A DISTRIBUTED FILE SERVER";

[0007] U.S. Provisional Application No. 60/264,669, filed Jan. 29, 2001, titled "DATA FLOW CONTROLLER ARCHITECTURE FOR HIGH PERFORMANCE STORAGE SYSTEMS";

[0008] U.S. Provisional Application No. 60/264,668, filed Jan. 29, 2001, titled "ADAPTIVE LOAD BALANCING FOR A DISTRIBUTED FILE SERVER"; and

[0009] U.S. Provisional Application No. 60/302,424, filed Jun. 29, 2001, titled "DYNAMICALLY DISTRIBUTED FILE SYSTEM".

BACKGROUND OF THE INVENTION

[0010] 1. Field of the Invention

[0011] This invention relates to the field of data storage and management. More particularly, this invention relates to high-performance mass storage systems and methods for data storage, backup, and recovery.

[0012] 2. Description of the Related Art

[0013] In modern computer systems, collections of data are usually organized and stored as files. A file system allows users to organize, access, and manipulate these files and also performs administrative tasks such as communicating with physical storage components and recovering from failure. The demand for file systems that provide high-speed, reliable, concurrent access to vast amounts of data for large numbers of users has been steadily increasing in recent years. Often such systems use a Redundant Array of Independent Disks (RAID) technology, which distributes the data across multiple disk drives, but provides an interface that appears to users as one, unified disk drive system, identified by a single drive letter. In a RAID system that includes more than one array of disks, each array is often identified by a unique drive letter, and in order to access a given file, a user must correctly identify the drive letter for the disk array on which the file resides. Any transfer of files from one disk array to another and any addition of new disk arrays to the system must be made known to users so that they can continue to correctly access the files.

[0014] RAID systems effectively speed up access to data over single-disk systems, and they allow for the regeneration of data lost due to a disk failure. However, they do so by rigidly prescribing the configuration of system hardware and the block size and location of data stored on the disks. Demands for increases in storage capacity that are transparent to the users or for hardware upgrades that lack conformity with existing system hardware cannot be accommodated, especially while the system is in use. In addition, such systems commonly suffer from the problem of data fragmentation, and they lack the flexibility necessary to intelligently optimize use of their storage resources.

[0015] RAID systems are designed to provide high-capacity data storage with built-in reliability mechanisms able to automatically reconstruct and restore saved data in the event of a hardware failure or data corruption. In conventional RAID technology, techniques including spanning, mirroring, and duplexing are used to create a data storage device from a plurality of smaller single disk drives with improved reliability and storage capacity over conventional disk systems. RAID systems generally incorporate a degree of redundancy into the storage mechanism to permit saved data to be reconstructed in the event of single (or sometimes double) disk failure within the disk array. Saved data is further stored in a predefined manner that is dependent on a fixed algorithm to distribute the information across the drives of the array. The manner of data distribution and data redundancy within the disk array impacts the performance and usability of the storage system and may result in substantial tradeoffs between performance, reliability, and flexibility.

[0016] A number of RAID configurations have been proposed to map data across the disks of the disk array. Some of the more commonly recognized configurations include RAID-1, RAID-2, RAID-3, RAID-4, and RAID-5.

[0017] In most RAID systems, data is sequentially stored in data stripes and a parity block is created for each data stripe. The parity block contains information derived from the sequence and composition of the data stored in the associated data stripe. RAID arrays can reconstruct information stored in a particular data stripe using the parity information, however, this configuration imposes the requirement that records span across all drives in the array resulting in a small stripe size relative to the stored record size.

[0018] **FIG. 21** illustrates the data mapping approach used in many conventional RAID storage device implementations. Although the diagram corresponds most closely to RAID-3 or RAID-4 mapping schemas, other RAID configurations are organized in a similar manner. As previously indicated, each RAID configuration uses a striped disk array **2110** that logically combines two or more disk drives **2115** into a single storage unit. The storage space of each drive **2115** is organized by partitioning the space on the drives into stripes **2120** that are interleaved so that the available storage space is distributed evenly across each drive.

[0019] Information or files are stored on the disk array **2110**. Typically, the writing of data to the disks occurs in a parallel manner to improve performance. A parity block is constructed by performing a logical operation (exclusive OR) on the corresponding blocks of the data stripe to create a new block of data representative of the result of the logical operation. The result is termed a parity block and is written to a separate area **2130** within the disk array. In the event of data corruption within a particular disk of the array 10, the parity information is used to reconstruct the data using the information stored in the parity block in conjunction with the remaining non-corrupted data blocks.

[0020] In the RAID architecture, multiple disks a typically mapped to a single 'virtual disk'. Consecutive blocks of the virtual disk are mapped by a strictly defined algorithm to a set of physical disks with no file level awareness. When the RAID system is used to host a conventional file system, it is the file system that maps files to the virtual disk blocks where they may be mapped in a sequential or non-sequential order in a RAID stripe. The RAID stripe may contain data from a single file or data from multiple files if the files are small or the file system is highly fragmented.

[0021] The aforementioned RAID architecture suffers from a number of drawbacks that limit its flexibility and scalability for use in reliable storage systems. One problem with existing RAID systems is that the data striping is designed to be used in conjunction with disks of the same size. Each stripe occupies a fixed amount of disk space and the total number of stripes allowed in the RAID system is limited by the capacity of the smallest disk in the array. Any additional space that may be present on drives having a capacity larger than the smallest drive goes unused as the RAID system lacks the ability to use the additional space. This further presents a problem in upgrading the storage capacity of the RAID system, as all of the drives in the array must be replaced with larger capacity drives if additional storage space is desired. Therefore, existing RAID systems are inflexible in -terms of their drive composition, increasing the cost and inconvenience to maintain and upgrade the storage system.

[0022] A further problem with conventional RAID arrays resides in the rigid organization of data on the disks of the RAID array. As previously described, this organization typically does not use available disk space in an efficient manner. These systems further utilize a single fixed block size to store data which is implemented with the restriction of sequential file storage along each disk stripe. Data storage in this manner is typically inefficient as regions or gaps of disk space may go unused due to the file organization restrictions. Furthermore, the fixed block size of the RAID array is not able to distinguish between large files, which benefit from larger block size, and smaller files, which benefit from smaller block size for more efficient storage and reduced wasted space.

[0023] Although conventional RAID configurations are characterized as being fault-tolerant, this capability is typically limited to single disk failures. Should more than one (or two) disk fail or become inoperable within the RAID array before it can be replaced or repaired there is the potential for data loss. This problem again arises from the rigid structure of data storage within the array that utilizes sequential data striping. This problem is further exacerbated by the lack of ability of the RAID system to flexibly redistribute data to other disk areas to compensate for drive faults. Thus, when one drive becomes inoperable within the array, the likelihood of data loss increases significantly until the drive is replaced resulting in increased maintenance and monitoring requirements when using conventional RAID systems.

[0024] With respect to conventional data storage systems or other computer networks, conventional load balancing includes a variety of drawbacks. For example, decisions relating to load balancing are typically centralized in one governing process, one or more system administrators, or combinations thereof. Accordingly, such systems have a single point of failure, such as the governing process or the system administrator. Moreover, load balancing occurs only when the centralized process or system administrator can organize performance data, make a decision, and then transmit that decision throughout the data storage system or computer network. This often means that the such load balancing can be slow to react, difficult to optimize for a particular server, and difficult to scale as the available resources expand or contract. In addition, conventional load balancing typically is limited to balancing processing and communications activity between servers only.

SUMMARY OF THE INVENTION

[0025] The present invention solves these and other problems by providing a dynamically distributed file system that accommodates current demands for high capacity, throughput, and reliability, while presenting to the users a single-file-system interface that appears to include every file in the system on a single server or drive. In this way, the file system is free to flexibly, transparently, and on-the-fly distribute and augment physical storage of the files in any manner that suits its needs, across disk drives, and across servers, and users can freely access any file without having specific knowledge of the files current physical location.

[0026] One embodiment includes a storage device and architecture which possesses features such as transparent scalability where disks of non-identical capacity can be fully-utilized without the "dead-space" restrictions associated with conventional disk arrays. In one embodiment a flexible storage space allocation system handles storing large and small file types to improve disk space utilization. In another embodiment an improved method for maintaining data integrity overcomes the single drive (or double) fault limitation of conventional systems in order to increase storage reliability while at the same time reducing maintenance and monitoring requirements.

[0027] In one embodiment, distributed parity groups (DPG) are integrated into the distributed file storage system technology. This architecture provides capabilities for optimizing the use of disk resources by moving frequently and infrequently accessed data blocks between drives so as to maximize the throughput and capacity utilization of each drive.

[0028] In one embodiment, the architecture supports incorporation of new disk drives without significant reconfiguration or modification of the exiting distributed file storage system to provide improved reliability, flexibility, and scalability. Additionally, the architecture permits the removal of arbitrary disk drives from the distributed file storage system and automatically redistributes the contents of these drives to other available drives as necessary.

[0029] The distributed file storage system can proactively position objects for initial load balancing, such as, for example, to determine where to place a particular new object. Additionally, the distributed file storage system can continue to proactively position objects, thereby accomplishing active load balancing for the existing objects throughout the system. According to one embodiment, one or more filters may be applied during initial and/or active load balancing to ensure one or a small set of objects are not frequently transferred, or churned, throughout the resources of the system.

[0030] As used herein, load balancing can include, among other things, capacity balancing, throughput balancing, or both. Capacity balancing seeks balance in storage, such as the number of objects, the number of Megabytes, or the like, stored on particular resources within the distributed file storage system. Throughput balancing seeks balance in the number of transactions processed, such as, the number of transactions per second, the number of Megabytes per second, or the like, handled by particular resources within the distributed file storage system. According to one embodiment, the distributed file storage system can position objects to balance capacity, throughput, or both, between objects on a resource, between resources, between the servers of a cluster of resources, between the servers of other clusters of resources, or the like.

[0031] The distributed file storage system can comprise resources, such as servers or clusters, which can seek to balance the loading across the system by reviewing a collection of load balancing data from itself, one or more of the other servers in the system, or the like. The load balancing data can include object file statistics, server profiles, predicted file accesses, or the like. A proactive object positioner associated with a particular server can use the load balancing data to generate an object positioning plan designed to move objects, replicate objects, or both, across other resources in the system. Then, using the object positioning plan, the resource or other resources within the distributed file storage system can execute the plan in an efficient manner.

[0032] According to one embodiment, each server pushes objects defined by that server's respective portion of the object positioning plan to the other servers in the distributed file storage system. By employing the servers to individually push objects based on the results of their object positioning plan, the distributed file storage system provides a server-, process-, and administrator-independent approach to object positioning, and thus load balancing, within the distributed file storage system.

[0033] In one embodiment, the network file storage system includes a first file server operably connected to a network fabric; a second file server operably connected to the network fabric; first file system information loaded on the first file server; and second file system information loaded on the second file server, the first file system information and the second file system information configured to allow a client computer operably connected to the network fabric to locate files stored by the first file server and files stored by the second file server without prior knowledge as to which file server stores the files. In one embodiment, the first file system information includes directory information that describes a directory structure of a portion of the network file system whose directories are stored on the first file server, the directory information includes location information for a first file, the location information includes a server id that identifies at least the first file server or the second file server.

[0034] In one embodiment, the network file storage system loads first file system metadata on a first file server operably connected to a network fabric; loads second file system metadata on a second file server connected to the network fabric, the first file system metadata and the second file system metadata include information to allow a client computer operably connected to the network fabric to locate a file stored by the first file server or stored by the second file server without prior knowledge as to which file server stores the file.

[0035] In one embodiment, the network file storage system performs a file handle lookup on a computer network file system by: sending a root-directory lookup request to a first file server operably connected to a network fabric; receiving a first lookup response from the first file server, the first lookup response includes a server id of a second file server connected to the network fabric; sending a directory lookup request to the second file server; and receiving a file handle from the second file server.

[0036] In one embodiment, the network file storage system allocates space by: receiving a file allocation request in a first file server, the first file server owning a parent directory that is to contain a new file, the file allocation request includes a file handle of the parent directory; determining a selected file server from a plurality of file servers; sending a file allocation request from the first server to the selected server; creating metadata entries for the new file in file system data managed by the selected file server; generating a file handle for the new file; sending the file handle to the first file server; and creating a directory entry for the new file in the parent directory.

[0037] In one embodiment, the network file storage system includes: a first file server operably connected to a network fabric; a second file server operably connected to the network fabric; first file system information loaded on the first file server; and second file system information loaded on the second file server, the first file system information and the second file system information configured to allow a client computer operably connected to the network fabric to locate files owned by the first file server and files owned by the second file server without prior knowledge as to which file server owns the files, the first file server configured to mirror at least a portion of the files owned by the second file server, the first file server configured to store information sufficient to regenerate the second file system information, and the second file server configured to store information sufficient to regenerate the first file system information.

[0038] In one embodiment, the network file storage system: loads first file system metadata on a first file server operably connected to a network fabric; loads second file system metadata on a second file server connected to the network fabric, the first file system metadata and the second file system metadata include information to allow a client computer operably connected to the network fabric to locate a file stored by the first file server or stored by the second file server without prior knowledge as to which file server stores

the file; maintains information on the second file server to enable the second file server to reconstruct an information content of the first file system metadata; and maintains information on the first file server to enable the first file server to reconstruct an information content of the second file system metadata.

[0039] In one embodiment the computer network file storage system is fault-tolerant and includes: a first file server operably connected to a network fabric; a second file server operably connected to the network fabric; a first disk array operably coupled to the first file server and to the second file server, a second disk array operably coupled to the first file server and to the second file server; first file system information loaded on the first file server, the first file system information including a first intent log of proposed changes to the first metadata; second file system information loaded on the second file server, the second file system information including a second intent log of proposed changes to the second metadata, the first file server having a copy of the second intent log, the second file server maintaining a copy of the first intent log, thereby allowing the first file server to access files on the second disk array in the event of a failure of the second file server.

[0040] In one embodiment, a distributed file storage system provides hot-swapping of file servers by: loading first file system metadata on a first file server operably connected to a network fabric, the first file system operably connected to a first disk drive and a second disk drive; loading second file system metadata on a second file server connected to the network fabric, the second file system operably connected to the first disk drive and to the second disk drive; copying a first intent log from the first file server to a backup intent log on the second file server, the first intent log providing information regarding future changes to information stored on the first disk drive; and using the backup intent log to allow the second file server to make changes to the information stored on the first disk drive.

[0041] In one embodiment, a distributed file storage system includes: a first file server operably connected to a network fabric; a file system includes first file system information loaded on the first file server, the file system configured to create second file system information on a second file server that comes online sometime after the first file server has begun servicing file requests, the file system configured to allow a requester to locate files stored by the first file server and files stored by the second file server without prior knowledge as to which file server stores the files.

[0042] In one embodiment, a distributed file storage system adds servers during ongoing file system operations by: loading first file system metadata on a first file server operably connected to a network fabric; creating at least one new file on a second file server that comes online while the first file server is servicing file requests, the at least one new file created in response to a request issued to the first file server, the distributed file system configured to allow a requester to locate files stored by the first file server and files stored by the second file server without prior knowledge as to which file server stores the files.

[0043] In one embodiment, a distributed file storage system includes: first metadata managed primarily by a first file server operably connected to a network fabric, the first metadata includes first file location information, the first file location information includes at least one server id; and second metadata managed primarily by a second file server operably connected to the network fabric, the second metadata includes second file location information, the second file location information includes at least one server identifier, the first metadata and the second metadata configured to allow a requester to locate files stored by the first file server and files stored by the second file server in a directory structure that spans the first file server and the second file server.

[0044] In one embodiment, a distributed file storage system stores data by: creating first file system metadata on a first file server operably connected to a network fabric, the first file system metadata describing at least files and directories stored by the first file server; creating second file system metadata on a second file server connected to the network fabric, the second file system metadata describing at least files and directories stored by the second file server, the first file system metadata and the second file system metadata includes directory information that spans the first file server and the second file server, the directory information configured to allow a requestor to find a location of a first file catalogued in the directory information without prior knowledge as to a server location of the first file.

[0045] In one embodiment, a distributed file storage system balances the loading of servers and the capacity of drives associated with the servers, the file system includes: a first disk drive including a first unused capacity; a second disk drive including a second unused capacity, wherein the second unused capacity is smaller than the first unused capacity; a first server configured to fill requests from clients through access to at least the first disk drive; and a second server configured to fill requests from clients through access to at least the second disk drive, and configured to select an infrequently accessed file from the second disk drive and push the infrequently accessed files to the first disk drive, thereby improving a balance of unused capacity between the first and second disk drives without substantially affecting a loading for each of the first and second servers.

[0046] In one embodiment, a distributed file storage system includes: a first file server operably connected to a network fabric; a second file server operably connected to the network fabric; first file system information loaded on the first file server; and second file system information loaded on the second file server, the first file system information and the second file system information configured to allow a client computer operably connected to the network fabric to locate files stored by the first file server and files stored by the second file server without prior knowledge as to which file server stores the files.

[0047] In one embodiment, a data engine offloads data transfer operations from a server CPU. In one embodiment, the server CPU queues data operations to the data engine.

[0048] In one embodiment, a distributed file storage system includes: a plurality of disk drives for storing parity groups, each parity group includes storage blocks, the storage blocks includes one or more data blocks and a parity block associated with the one or more data blocks, each of the storage blocks stored on a separate disk drive such that no two storage blocks from a given parity set reside on the

same disk drive, wherein file system metadata includes information to describe the number of data blocks in one or more parity groups.

[0049] In one embodiment, a distributed file storage system stores data by: determining a size of a parity group in response to a write request, the size describing a number of data blocks in the parity group; arranging at least a portion of data from the write request according to the data blocks; computing a parity block for the parity group; storing each of the data blocks on a separate disk drive such that no two data blocks from the parity group reside on the same disk drive; and storing each the parity block on a separate disk drive that does not contain any of the data blocks.

[0050] In one embodiment, a distributed file storage system includes: a plurality of disk drives for storing parity groups, each parity group includes storage blocks, the storage blocks includes one or more data blocks and a parity block associated with the one or more data blocks, each of the storage blocks stored on a separate disk drive such that no two storage blocks from a given parity set reside on the same disk drive; a redistribution module to dynamically redistribute parity groups by combining some parity groups to improve storage efficiency.

[0051] In one embodiment, a distributed file storage system stores data by: determining a size of a parity group in response to a write request, the size describing a number of data blocks in the parity group; arranging at least a portion of data from the write request according to the data blocks; computing a parity block for the parity group; storing each of the data blocks on a separate disk drive such that no two data blocks from the parity group reside on the same disk drive; storing the parity block on a separate disk drive that does not contain any of the data blocks; and redistributing the parity groups to improve storage efficiency.

[0052] In one embodiment, a distributed file storage system includes: a plurality of disk drives for storing parity groups, each parity group includes storage blocks, the storage blocks includes one or more data blocks and a parity block associated with the one or more data blocks, each of the storage blocks stored on a separate disk drive such that no two storage blocks from a given parity set reside on the same disk drive; and a recovery module to dynamically recover data lost when at least a portion of one disk drive in the plurality of disk drives becomes unavailable, the recovery module configured to produce a reconstructed block by using information in the remaining storage blocks of a parity set corresponding to an unavailable storage block, the recovery module further configured to split the parity group corresponding to an unavailable storage block into two parity groups if the parity group corresponding to an unavailable storage block spanned all of the drives in the plurality of disk drives.

[0053] In one embodiment, a distributed file storage system stores data by: determining a size of a parity group in response to a write request, the size describing a number of data blocks in the parity group; arranging at least a portion of data from the write request according to the data blocks; computing a parity block for the parity group; storing each of the data blocks on a separate disk drive such that no two data blocks from the parity group reside on the same disk drive; storing the parity block on a separate disk drive that does not contain any of the data blocks; reconstructing lost data by using information in the remaining storage blocks of a parity set corresponding to an unavailable storage block to produce a reconstructed parity group; splitting the reconstructed parity group corresponding to an unavailable storage block into two parity groups if the reconstructed parity group is too large to be stored on the plurality of disk drives.

[0054] In one embodiment, a distributed file storage system integrates parity group information into file system metadata.

BRIEF DESCRIPTION OF THE DRAWINGS

[0055] These and other aspects, advantages, and novel features of the invention will become apparent upon reading the following detailed description and upon reference to the accompanying drawings:

[0056] **FIG. 1** is a general overview of a distributed file storage system showing clients, a communication fabric, and a plurality of servers with associated disk arrays.

[0057] **FIG. 2** is a block diagram of a server node.

[0058] **FIG. 3** is a block diagram of five metadata structures and connections between the five metadata structures.

[0059] **FIG. 4** shows an example portion of a Filename Table.

[0060] **FIG. 5** shows an example of a Gee-string stored in a Gee Table.

[0061] **FIG. 6** shows one embodiment of the structure of a G-node.

[0062] **FIG. 7** shows one embodiment of the structure of a Gnid-string.

[0063] **FIG. 8A** shows one embodiment of the structure of a Cache Node.

[0064] **FIG. 8B** shows a conceptual division of a Cache Node Table into three lists.

[0065] **FIG. 9** shows a sample portion of a lock string.

[0066] **FIG. 10** shows one embodiment of Refresh Nodes configured as a binary tree.

[0067] **FIG. 11** shows one embodiment of Refresh Nodes configured as a doubly-linked list

[0068] **FIG. 12** shows one embodiment of the structure of an Intent Log Entry.

[0069] **FIG. 13** shows one embodiment of the structure of a file handle.

[0070] **FIG. 14A** is a block diagram depicting one embodiment of a file handle look-up process.

[0071] **FIG. 14B** is a block diagram depicting one embodiment of a file access process.

[0072] **FIG. 15** is a flow chart depicting one embodiment of performing a file access.

[0073] **FIG. 16** is a flow chart depicting one embodiment of performing a file handle look-up.

[0074] **FIG. 17** is a flow chart depicting one embodiment of caching file data.

[0075] **FIG. 18** is a flow chart depicting one embodiment of file allocation.

[0076] **FIG. 19** shows one embodiment of Super G-nodes.

[0077] **FIG. 20A** shows one embodiment of a Super G-node.

[0078] **FIG. 20B** shows one embodiment of a scheme to use Super G-nodes to hold metadata for files of widely varying sizes.

[0079] **FIG. 21** illustrates a conventional disk array that incrementally stripes data in a RAID mapping architecture.

[0080] **FIG. 22A** illustrates one embodiment of a distributed file storage system.

[0081] **FIG. 22B** illustrates another embodiment of a distributed file storage system having built in data redundancy.

[0082] **FIG. 23** illustrates a distributed file storage mechanism.

[0083] **FIG. 24A** illustrates a data and parity information storage method.

[0084] **FIG. 24B** illustrates another data and parity information storage method.

[0085] **FIG. 25** illustrates another embodiment of a distributed file storage system having a variable capacity disk array.

[0086] **FIG. 26A** illustrates an embodiment of variable block number parity groups.

[0087] **FIG. 26B** illustrates an embodiment of variable size parity groups.

[0088] **FIG. 27** illustrates one embodiment of a G-table used to determine parity group mapping.

[0089] **FIG. 28** illustrates a method for storing data in the distributed file storage system.

[0090] **FIG. 29** illustrates another embodiment of a G-table mapping structure.

[0091] **FIG. 30** illustrates one embodiment of a fault-tolerant restoration process.

[0092] **FIG. 31** illustrates a method for recovering corrupted or lost data in the distributed file storage system.

[0093] **FIG. 32A** illustrates one embodiment of a variably sized parity group used to store files.

[0094] **FIG. 32B** illustrates another embodiment of a variably sized parity group used to store files.

[0095] **FIG. 33** illustrates a data storage process used by the distributed file storage system.

[0096] FIGS. **34**A-C illustrate a parity set redistribution process.

[0097] **FIG. 35A** illustrates one embodiment of a parity group dissolution process.

[0098] **FIG. 35B** illustrates one embodiment of a parity group consolidation process.

[0099] **FIG. 36** illustrates a parity group monitoring process.

[0100] **FIG. 37** illustrates a parity group optimization/defragmentation process.

[0101] **FIG. 38** illustrates a load balancing method used by the distributed file storage system.

[0102] **FIG. 39** depicts a block diagram of an exemplary embodiment of servers and disk arrays of a distributed file storage system, which highlights the proactive object positioning of aspects of an exemplary embodiment of the invention.

[0103] **FIG. 40** depicts a block diagram of an exemplary server of **FIG. 39**, according to aspects of an exemplary embodiment of the invention.

[0104] **FIG. 41** depicts an object positioning plan for Server F3 of **FIG. 39**, according to aspects of an exemplary embodiment of the invention.

[0105] **FIG. 42** is a block diagram of a server that provides efficient processing of data transfers between one or more client computers and one or more disk drives.

[0106] **FIG. 43** is a block diagram of a data engine.

[0107] **FIG. 44** is a map of data fields in a 64-bit data transfer instruction to the data engine for use with a 64-bit PCI bus.

DETAILED DESCRIPTION

[0108] Introduction

[0109] As data storage requirements increase, it is desirable to be able to easily increase the data storage capacity and/or performance of a data storage system. That is, it is desirable to be able to increase the available capacity and performance of a storage system without modifying the configuration of the clients accessing the system. For example, in a typical Personal Computer (PC) network environment, if a database accesses a network drive "M", it is desirable to be able to add storage to this drive, all the while still calling the drive "M", as opposed to adding, say, drives "N", "O", and "P" as storage requirements increase. In some cases, having to switch from a single drive "M" to four drives, "M", "N", "O", "P" is a mere nuisance. However, in some cases such a change requires significant reconfiguration of client configurations. In other cases, such a change requires modification of existing application software, and in some instances such a change simply will not work with the application being used.

[0110] The objective for more capacity can be met in some storage systems by adding additional disk drives to the system. However, this may not result in increasing performance. In fact, adding additional drives may cause a significant decrease in performance. This is because: (1) if more ports are not added to the system when new drives are added, the performance decreases because now more data is available (and presumably being accessed) through the same performance ports; and (2) the controller managing the file system metadata has more operations to perform and can become a bottleneck. Adding drives to existing systems may also limited by physical form factors. That is to say, that some systems have physical limits to how many drives can be added.

[0111] In one embodiment, the system described herein provides a Distributed File Storage System (DFSS) that can scale disk capacity, scale data throughput (e.g., megabytes per second of data delivery); and scale transaction processing throughput (e.g., processing of file system metadata). In one embodiment, the system also provides load balancing such that the scaled components handle the workload with improved efficiency. In one embodiment, the DFSS is dynamically distributed. In one embodiment, the DFSS allows the integration of multiple servers so that the aggregation of servers appears to a client as a single storage device. With the DFSS, multiple servers can access and control the same disk array, separate disk arrays, or both simultaneously. The DFSS is designed so that each server can continue to read and write data to the drives it controls even when other controllers in the DFSS fail. The DFSS also provides a mechanism for balancing the load on the controllers and the drives.

[0112] In one embodiment, the DFSS is designed such that when multiple controllers are controlling a single array of disk drives (also called a drive array), some or all of the servers connected to the drive array have valid copies of the file system metadata describing the data on that drive array. This means that each server has direct access to all of the file system metadata for one or more of the drive arrays it can access. Thus: (1) a server can continue to operate normally if the other servers in the system fail; and (2) there is little or no performance degradation due to one server polling another server regarding location of data on drive arrays. The DFSS provides inter-server communication to maintains synchronization of the file system metadata. The DFSS is designed such that a server can read from more than one drive array and can read from drive arrays maintained by another server. In one embodiment, only one controller attached to a particular drive array has write privileges for that particular drive array at a given time.

[0113] The DFSS maintains a description of which servers have read and write privileges to a file represented by a file handle passed to the client. When the client looks up a file handle, the client is informed of its options regarding which servers it may read the data from (which is typically several) and which one server it needs to use to write data. In addition, since the servers typically have multiple network interface cards (ports) to the client network, the file handle also includes data which suggests to the client which port is likely to be the least utilized.

[0114] The DFSS is also designed such that when there are multiple servers, which are not sharing the same drive arrays, the drive arrays are seamlessly integrated. For example, suppose a system has 4 servers (numbered S1, S2, S3, and S4) and two drive arrays, numbered (A1, and A2). Further suppose that S1 and S2 control A1 and that S3 and S4 control A2. The DFSS allows for a directory on A1 to have children on A2. In fact, the file system keeps track of usage statistics, and if A2 is less utilized than A1, the file system will automatically create the next files on A2 instead of A1. The DFSS provides coordination between the servers to allow this level of integration.

[0115] Because each server has a complete set of metadata for each drive array it can access, a particular server can continue to operate even if other servers fail. The DFSS includes a mechanism for determining if a controller has failed and a mechanism for transferring write privileges in such cases. Clearly if all controllers attached to a given drive array fail, the data on that drive array will become inaccessible. However, the capability to support multiple controllers for each drive array greatly reduces the likelihood of such an event. If all such controllers for a drive array fail, read and write operations on the remaining controller/drive arrays continue unhindered.

[0116] The DFSS can perform load balancing at three levels. First, when a directory lookup is performed, the file system encodes within the file handle the lesser-used network interface to provide balancing of network interface resources. Second, when a new file is created, it is created on lesser-used drives and owned by a lesser-used server. Third, dynamic analysis of loading conditions is performed to identify under-utilized and over-utilized drives. In response, the file system in some cases redistributes the parity groups across the drives in the existing drive array for more optimum usage of parity checking, and in other cases the file system moves files to lesser used drive arrays.

[0117] Many data storage systems are designed with the twin goals of providing fast access to data and providing protection against loss of data due to the failure of physical storage media. Prior art solutions typically relied on Redundant Arrays of Independent Disks (RAID). By having the data striped across multiple drives, the data can be accessed faster because the slow process of retrieving data from disk is done in parallel, with multiple drives accessing their data at the same time. By allocating an additional disk for storing parity information, if any one disk fails, the data in the stripe can be regenerated from the remaining drives in the stripe.

[0118] While this approach has proven effective in many applications, it does have a few fundamental limitations, one of this is that there is a rigid algorithm for mapping addresses from the file system to addresses on the drives in the array. Hence stripes are created and maintained in a rigid manner, according to a predetermined equation. An unfortunate side effect results from this limitation. There is no mechanism from keeping data from a particular file from becoming highly fragmented, meaning that although the data could actually fit in a single stripe, the data could actually be located in many of stripes (this situation can be particularly acute when multiple clients are writing to a file system).

[0119] In one embodiment, the DFSS abandons the notion of having a rigid algorithm to map from addresses in the file system to drive addresses. Instead, DFSS uses Distributed Parity Groups (DPGs) to perform the mapping. Data blocks in the DPGs are mapped via a mapping table (or a list of tables) rather than a fixed algorithm, and the blocks are linked together via a table of linked lists. As discussed below, the DPG mapping can be maintained separately or can be integrated into the file system metadata.

[0120] Initially the mapping is somewhat arbitrary and is based on the expectation that the drives will be accessed evenly. However, the system keeps track of drive usage frequency. As patterns of usage are established, blocks are copied from frequently accessed drives to infrequently accessed drives. Once the copy is complete, the blocks are remapped to point to the new copies.

[0121] The disk drives are viewed as consisting of a collection of blocks. The block size is typically an integer multiple of the drive sector size. The drive sector size is a characteristic of the drives, and is the minimum size of data that can be written to the drives. For most Fibre Channel drives, the sector size is 512 bytes.

[0122] In one embodiment, the blocks are grouped via a G-Table. The G-table is a collection of Gees, which represent the individual blocks and their linkage. Each Gee contains a code that identifies what that the Gee's purpose is (e.g., linkage or representing data). Gees for a DPG strung together into a G-group. The entire G-table is cached, either in whole or in part, in Random Access Memory (RAM). Individual Gees are modified in cache to indicate when a specific block of data is in cache. This provides a straightforward way to be assured that if any client has caused disk data to be cached, any other client seeking that same data will be directed to the already cached data.

[0123] RAID systems are implemented independently from the file system. That is, from the file system's point of view, the array looks like one big disk. Hence stripes are created and maintained without any knowledge of the data they contain. Two unfortunate side effects result from this limitation. First, there is no mechanism from keeping data from a particular file from becoming highly fragmented, meaning that although the data could actually fit in a single stripe, the data could actually be located many stripes (this situation can be particularly acute when multiple clients are writing to files). The can result in each drive doing hundreds of seeks, while a smarter system could do just one. This is significant because the seek is the slowest operation related to accessing data on disks.

[0124] Second, when a drive fails, the data on that drive must be regenerated on a replacement drive exactly as it was on the failed drive. This means that if, for example, a server that has only 10% of its disk space currently used, can only regenerate the data onto a replacement drive (or a hot spare) even though there is more than enough disk space to regenerate the data onto the other disks. For remote installations, if a hot spare is used, once one failure occurs, the hot spare is used and the system can no longer tolerate another failure until the bad drive is replaced. Of curse this could be lessened by the usage of multiple hot spares, but that significantly increases the amount of disk storage that is not being used and merely "waiting in the wings".

[0125] In one embodiment, the DFSS management of the DPGs is integrated into the file system, thus making the file system "aware" of the DPGs and how data blocks from a file are collected into parity groups. Making the file system aware of the DPGs allows the file servers in the DFSS to more intelligently use the disk arrays than a RAID system would. With the DPG system, the file system has knowledge of the drive arrays and therefore reduces the kind of fragmenting that is typical of RAID systems.

[0126] Furthermore, in the event of a failure of one drive in the DFSS, the data from the failed drive can be redistributed across the remaining drives in a disk array. For example, suppose a file contained a DPG having a length (also known as a "span") of 9 (data spread across 9 drives, where 8 drives contain the data blocks and the ninth drive contains the parity block). When one drive fails, the data can be regenerated and redistributed using a DPG of span 8. Note that without knowledge of which blocks are associated with which files, this redistribution is not possible, because the file must still have the same number of total blocks, but when the span is reduced from 9 to 8, there is an orphan block of 1 which must be still associated with the file. This orphan is associated with another DPG in the same file. This association is not possible without knowledge of the file. Alternatively, if there are at least ten disks in the disk array, the data can be regenerated and redistributed using a DPG span of 9, omitting the failed drive. Thus, the integration of DPG management into the file system provides flexibility not available in a conventional RAID system.

[0127] Sine the DFSS has full knowledge of the file system, the DFSS has knowledge of which blocks on the disks are not used. This allows the DFSS to identify heavily used disks and redistribute data from heavily-used disks to unused blocks on lesser-used blocks.

[0128] Storage system capability is typically measured in capacity, bandwidth, and the number of operations per second that can be processed. It is desirable to be able to easily scale a storage system, that is, to be able to easily increase the storage capacity, the bandwidth, or the operations per second capacity of the storage system. Storage system capacity is scaled by adding disk drives or to replace disk drive with drives having greater capacity. To increase storage system bandwidth or transactions per second capacity, it is typically necessary to add servers. It is desirable to be able to add and utilize these resources with little or no user intervention or configuration.

[0129] In one embodiment, the DFSS can automatically identify and utilize available resources, including disk drives and servers. Two features are used realize this: 1) detecting the addition of disk drives and/or servers; and 2) a automatically initializing and incorporating newly added disk drives and/or servers. The same mechanisms that are used to detect newly-added resources can also be used to support the deletion of resources.

[0130] With regard to detection of new resources, modern, high performance networking technologies such as Fibre Channel and Gigabit Ethernet supply methods for determining what devices are connected to the network. By storing the device map, and periodically querying the network for an updated device map, the presence of new devices can be determined. New devices are added to the appropriate server resource map.

[0131] In one embodiment, a resource manager in the DFSS provides the capability to incorporate the new resources automatically. The resource manager keeps track of available disk resources, as measured in available disk devices and the available free blocks on each disk. The resource manager keeps track of the available servers and the unutilized capacity, in terms of bandwidth and transactions per second, of each server. When new resources are added to the DFSS, the resource manager incorporates the additions into a resource database.

[0132] The resource manager works in conjunction with aspects of the DFSS to dynamically allocate storage and controller resources to files. When the DFSS needs to create a new file, or extend an already created file, it coordinates with the resource manager to create a DPG of the appropriate size. A similar approach is followed by the DFSS in the selection of which server to use in the creation of a new file.

[0133] The resource manager approach also supports a load balancing capability. Load balancing is useful in a distributed file system to spread the workload relatively uniformly across all of the available resources (e.g., across disks, network interfaces, and servers). The ability to proactively relocate file data is a tool that can be used to support load balancing by moving file data from over-utilized resources to under-utilized resources. In one embodiment, the resource manager supports load balancing by incorporating resource usage predictions.

[0134] In the DFSS, the server workload includes communication with client machines, reading and writing files from disks, managing file metadata, and managing server resources such as storage capacity. The workload is divided up among the server hardware resources. If the workload is evenly divided, the resulting performance will be improved. Thus, one key to performance is intelligent resource management. In one embodiment, resource management involves adaptive load balancing of server workloads. Prior art distributed file system technologies do not offer an effective method of performing load balancing in the face of a dynamic load environment and thus cannot provide optimum performance.

[0135] In one embodiment adaptive load balancing is based on the implementation of two mechanisms. First, a mechanism is provided to predict the future server workload. Second, a mechanism is provided to reallocate distributed server resources in response to the predicted workload.

[0136] Prediction of the future workload has several aspects. The first of these aspects is the past history of server workload, in terms if file access statistics, server utilization statistics, and network utilization statistics. The loading prediction mechanism uses these statistics (with an appropriate filter applied) to generate predictions for future loading. As a very simple example, a file that has experienced heavy sequential read activity in the past few minutes will likely continue to experience heavy sequential read access for the next few minutes.

[0137] The predictions for future workload can be used to proactively manage resources to improve performance and capacity usage. One mechanism used to reallocate server workload is the movement and replication of content (files) such that server and storage utilization is balanced and the direction of client accesses to available servers is balanced. Some degree of cooperation from client machines can be used to provide more effective load balancing, but client cooperation is not strictly required.

[0138] A file server contains a number of hardware resources, including controllers, storage elements (disks), and network elements. In the configuration used by the DFSS, multiple client machines are connected through a (possibly redundant) client network to one or more server clusters. Each server cluster has one or more servers and a disk storage pool.

[0139] Software resident on each server collects statistics regarding file accesses and server resource utilization. This includes information regarding the access frequency, access bandwidth and access locality for the individual files, the loading of each disk controller and disk storage element in terms of CPU utilization, data transfer bandwidth, transactions per second, and the loading of each network element in terms of network latency and data transfer bandwidth.

[0140] The collected statistics are subjected to various filter operations, which results in a prediction of filture file and resource utilization (i.e., workload). This prediction can also be modified by server configuration data which has been provided in advance by a system administrator, and explicit "hints" regarding future file and/or resource usage which can be provided directly from a client machine.

[0141] The predicted workload is then used to develop a plan that where to move content (files) between storage elements and where to direct client accesses to controllers in such a manner that the overall workload is distributed as evenly as possible, resulting in best overall load balance and distributed server performance. The predicted workload can be used to perform the following specific types of load balancing:

[0142] 1) Client Network Load Balancing, which includes managing client requests to the extent possible such that the client load presented to the servers in a cluster, and the load present to the network ports within each cluster is evenly balanced.

[0143] 2) Intra-Cluster Storage Load Balancing, which includes of the movement of data between the disks connected to a controller cluster such that the disk bandwidth loading among each of the drives in an array, and the network bandwidth among network connecting disk arrays to servers is balanced. There are two goals. The first goal is to achieve relatively uniform bandwidth loading for each storage sub-network. The second goal is to achieve relatively uniform bandwidth loading for each individual disk drive. This is accomplished by moving relatively infrequently accessed material to drives with frequently accessed material.

[0144] 3) Inter-Node Storage Load Balancing, which includes the movement of data between drives connected to different clusters to equalize disk access load between clusters. This is done at a higher cost than Intra-Node Drive Load Balancing, as file data must actually be copied between controllers over the client network.

[0145] 4) Intra-Node Storage Capacity Balancing, which includes movement of data between the disks connected to a server (or servers in a cluster) to balance disk storage utilization among each of the drives.

[0146] 5) Inter-Node Storage Capacity Balancing, which includes movement of data between drives connected to different servers to equalize overall disk storage utilization among the different servers. This is done at a higher cost than Intra-Node Drive Capacity Balancing, as file data must actually be copied between controllers over the network.

[0147] 6) File Replication Load Balancing, which includes load balancing though file replication. This is an extension of Inter-Node Drive Load Balancing. High usage files are replicated so that multiple controller clusters have one or more that one local (read-only) copy. This allows the workload associated with these heavily-accessed files to be distributed across a larger set of disks and servers.

[0148] Disks and servers in the DFSS can be "hot swapped" and "hot added" (meaning they can be replaced or added while the DFSS is online and servicing file requests. Disks in a disk array need not match in capacity or throughput. Extra capacity is automatically detected, configured, and used. Data is redistributed in the background (both across servers and across DPGs) to improve system performance. Hot adding of servers allows for increased file operations per second and file system capacity. Hot-added servers are automatically configured and used.

[0149] In one embodiment, servers are arranged in clusters that operate as redundant groups (typically as redundant pairs). In normal operation, the servers in a cluster operate in parallel. Each acts as a primary server for a portion of the file system. Each server in a cluster maintains a secondary copy of the metadata and intent log of the other's primary file system metadata and intent log. The intent log tracks differences between metadata stored in memory (e.g., metadata in a metadata cache) and metadata stored on disk. Upon failure of a server in the cluster, the server remaining server (or servers) will pick up the workload of the failed server with no loss of metadata or transactions.

[0150] Each server in a high-performance data storage system includes storage controller hardware and storage controller software to manage an array of disk drives. Typically, a large number of disk drives are used in a high performance storage system, and the storage system in turn is accessed by a large number of client machines. This places a large workload on the server hardware and server software. It is therefore important that the servers operate in an efficient manner so that they do not become a bottleneck in the storage system. In one embodiment, a high-performance data path is provided in the server so that data can efficiently be moved between the client machines and disks with a minimum amount of software intervention.

[0151] Prior art approaches for server and storage controllers tend to be software intensive. Specifically, a programmable CPU in the server becomes involved in the movement of data between the client and the disks in the disk array. This limits the performance of the storage system because the server CPU becomes a bottleneck. While current approaches may have a certain degree of hardware acceleration, such as XOR parity operations associated with RAID, these minimal acceleration techniques do not adequately offload the server CPU.

[0152] In one embodiment, the DFSS uses a server architecture that largely separates the data path from the control message path. Control messages (e.g. file read/write commands from clients) are routed to a host CPU in the server. The host CPU processes the commands, and sets up the network and storage interfaces as required to complete the data transfer operations associated with the commands. The data transfer operations, once scheduled with the network and storage interfaces can be completed without further CPU involvement, thus significantly offloading the host CPU. In one embodiment, a data flow architecture packages instructions with data as it flows between the network interfaces and data cache memories.

[0153] The server hardware and software perform the functions of interfacing with client via the network interfaces, servicing client file operation requests, setting up disk read and write operations needed to service these requests, and updating the file metadata as necessary to manage the files stored on disk.

[0154] The controller hardware provides a control flow path from the network and storage interfaces to the host CPU. The host CPU is responsible for controlling these interfaces and dealing with the high level protocols necessary for client communications. The host CPU also has a non-volatile metadata cache for storing file system metadata.

[0155] A separate path for data flow is provided that connects the network and storage interfaces with a non-volatile data cache. In one embodiment, the separate path for data flow is provided by a data engine. The data path is used for bulk data transfer between the network and storage interfaces. As an example of the data path operation, consider a client file read operation. A client read request is received on one of the network interfaces and is routed to the host CPU. The host CPU validates the request, and determines from the request which data is desired. The request will typically specify a file to be read, and the particular section of data within the file. The host CPU will use file metadata to determine if the data is already present in the data cache memory, or if it must be retrieved from the disks. If the data is in the data cache, the CPU will queue a transfer with the network interface to transfer the data directly from the data cache to the requesting client, with no further CPU intervention required. If the data is not in the data cache, the CPU will queue one or more transfers with the storage interfaces to move the data from disk to the data cache, again without any further CPU intervention. When the data is in the data cache, the CPU will queue a transfer on the network interface to move the data to the requesting client, again with no further CPU intervention.

[0156] One aspect of this autonomous operation is that the CPU schedules data movement operations by merely writing an entry onto a network or storage interface queue. The data engine and the network and storage interfaces are connected by busses that include address and data buses. In one embodiment, the network or storage interface does the actual data movement (or sequence of data movements) independently of the CPU by encoding an instruction code in the address bus that connects the data engine to the interface. The instruction code is set up by the host CPU when the transfer is queued, and can specify that data is to be written or read to one or both of the cache memories. In addition, it can specify that an operation such as a parity XOR operation or a data conversion operation be performed on the data while it is in transit. Because instructions are queued with the data transfers, the host CPU can queue hundreds or thousands of instructions in advance with each interface, and all of these can be can be completed asynchronously and autonomously. The data flow architecture described above can also be used as a bridge between different networking protocols.

[0157] As described above, the data engine offloads the host CPU direct involvement in the movement of data from the client to the disks and vice-versa. The data engine can be a general purpose processor, digital signal processor, programmable FPGA, other forms of soft or hard programmable logic, or a fully custom ASIC.

[0158] The data engine provides the capability for autonomous movement of data between client network interfaces and data cache memory, and between disk network interfaces and cache memory. The server CPU involvement is merely in initializing the desired transfer operations. The data engine supports this autonomy by combining an asynchronous data flow architecture, a high-performance data path than can operate independently of the server CPU data paths, and a data cache memory subsystem. The data engine also implements the parity generation functions required to support a RAID-style data protection scheme.

[0159] The data engine is data-flow driven. That is, the instructions for the parallel processing elements are embedded in data packets that are fed to the data engine and to the various functional blocks within the data engine.

[0160] In one embodiment, the data engine has four principal interfaces: two data cache RAM interfaces, and two external bus interfaces. Other versions of the data engine can have a different number of interfaces depending on performance goals.

[0161] A data path exits between each network interface and each cache interface. In each of these data path is a processing engine that controls data movement between the interfaces as well as operations that can be performed on the data as it moves between the interfaces. These processing engines are data-flow driven as described above.

[0162] The processing engine components that are used to perform these functions include an external bus write buffer, a feedback buffer, a cache read buffer, a cache write buffer, a parity engine, and the associated controller logic that controls these elements. The buffer elements are memories of appropriate sizes that smooth the data flow between the external interfaces, the parity engines, and the caches.

[0163] The data engine is used to provide a data path between client network interface and storage network interface controllers. The network interface controllers may support Fibre Channel, Ethernet, Infiniband, or other high performance networking protocols. One or more host CPUs schedule network transfers by queuing the data transfer operations on the network interfaces controllers. The network interface controllers then communicate directly with the data engine to perform the data transfer operations, completely autonomously from any additional CPU involvement. The data transfer operations may require only the movement of data, or they may combine the movement of data with other operations that must be performed on the data in transit.

[0164] The processing engines in the data engine can perform five principal operations, as well as a variety of support operations. The principal operations are: read from cache; write to cache; XOR write to cache; write to one cache with XOR write to other cache; write to both caches.

[0165] The data-flow control structure of the data engine reduces the loading placed on the server CPU. Once data operations are queued, the server CPU does not need to be directly involved in the movement of data, in the operations that are performed on data, or the management of a data transfer.

[0166] **FIG. 1** shows a general overview of a Distributed File Storage System (DFSS) **100** that operates on a computer network architecture. One or more clients **110** operating on one or more different platforms are connected to a plurality of servers **130**, **131**, **132**, **133134**, **135**, by way of a communication fabric **120**. In one embodiment, the communication fabric **120** is a Local Area Network (LAN). In one embodiment, the communication fabric **120** is a Wide Area Network (WAN) using a communication protocol such as, for example, Ethernet, Fibre Channel, Asynchronous Transfer Mode (ATM), or other appropriate protocol. The communication fabric **120** provides a way for a client **110** to connect to one or more servers **130-135**.

[0167] The number of servers included in the DFSS **100** is variable. However, for the purposes of this description, their structure, configuration, and functions are similar enough that the description of one server **130** is to be understood to apply to all **130-135**. In the descriptions of other elements of the figure that are similarly duplicated in the DFSS **100**, a description of one instance of an element is similarly to be understood to apply to all instances.

[0168] The server **130** is connected to a disk array **140** that stores a portion of the files of the. distributed file storage system. Together, the server-disk array pair **130,140** can be considered to be one server node **150**. The disks in the disk array **140** can be Integrated Drive Electronics (IDE) disks, Fibre Channel disks, Small Computer Systems Interface (SCSI) disks, InfiniBand disks, etc. The present disclosure refers to disks in the disk array **140** by way of example and not by way of limitation. Thus, for example the "disks" can be many types of information storage devices, including, for example, disk drives, tape drives, backup devices, memories, other computers, computer networks, etc.

[0169] In one embodiment, one or more server nodes **150**, **151** are grouped into a cluster **160** of server nodes. In one embodiment, each server **130** in the cluster **160** is connected not only to its own disk array **140**, but also to the disk array(s) **141** of the other server(s), **131** of the cluster **160**. Among other advantages conferred by this redundant connection is the provision of alternate server paths for reading a popular file or a file on a busy server node. Additionally, allowing servers **130**, **131** to access all disk arrays **140**, **141** of a cluster **160** provides the assurance that if one server **130** of a cluster **160** should fail, access to the files on its associated disk array **140** is not lost, but can be provided seamlessly by the other servers **131** of the cluster **160**.

[0170] In one embodiment, files that are stored on the disk array **140** of one server node **150** are mirrored on the disk array(s) **141** of each server node **151** in the cluster **160**. In such an embodiment, if the disk array **140** should become unusable, the associated server **130** will still be able to access copies of its files on the other disk array(s) **141** of the cluster **160**.

[0171] As shown in **FIG. 1**, the server **130** is associated with the disk array **140** that can include multiple disk drives of various sizes and capacities. Thus, the DFSS **100** allows for much more flexibility than many conventional multi-disk file storage systems that require strict conformity amongst the disk arrays of the system. Among other advantages conferred by this flexibility is the ability to upgrade portions of the system hardware without having to upgrade all portions uniformly and simultaneously.

[0172] In many conventional networked storage systems, a user on a client needs to know and to specify the server that holds a desired file. In the DFSS **100** described in **FIG. 1**, although the files of the file system can be distributed across a plurality of server nodes, this distribution does not require a user on a client system **110** to know a priori which server has a given file. That is, to a user, it appears as if all files of the system **100** exist on a single server. One advantage of this type of system is that new clusters **160** and/or server nodes **150** can be added to the DFSS **100** while still maintaining the appearance of a single file system.

[0173] **FIG. 2** is a block diagram showing one embodiment **200** of the server node **150** in the DFSS **100**. As in **FIG. 1**, the server node **150** includes the server **130** and the disk array **140** or other data storage device.

[0174] The server **130** includes a server software module **205**. The server software module **205** includes server interface (SI) software **240** for handling communications to and from clients **110**, file system (FS) software **250** for managing access, storage, and manipulation of the files, and a JBOD (Just a Bunch of Disks) interface (JI) **260** for handling communications with the disk array **140** and with other disk arrays of the cluster **160**. Communications between the server interface **240** and the file system **250** take place using a Client Server Object **245**. Communications between the file system **250** and the JBOD interface **260** take place using a Disk Service Object **255**. In one embodiment, as depicted in **FIG. 2**, the software of the file system **250** resides principally on the servers **130**, **131**, while the file data is stored on standard persistent storage on the disk arrays **140**, **141** of the DFSS **100**.

[0175] The server software module **205** also includes a polling module **270** for polling clients **110** of the DFSS **100** and a polling module **280** for polling disk arrays **140** of the DFSS **100**.

[0176] In the embodiment **200** shown in **FIG. 2**, the server **130** includes a Fibre Channel Application Programming Interface (FC-API) **210** with two Fibre Channel ports **211** for communicating via the fabric **120** with the client **110** and with other server(s) **151** of the cluster **160**. The FC-API **210** also communicates with the server interface **240** and with the client polling module **270** in the server software module **205**.

[0177] The server **130** includes an FC-API **220** with two Fibre Channel ports **221** for communicating with the disk array **140** and with other disk arrays of its cluster **160**. The FC-API **220** may communicate with the disk array **140** via a communication fabric **222**, as shown in **FIG. 2**. The FC-API **220** may also communicate with the disk array **140** directly. The FC-API **220** also communicates with the JBOD interface **260** and with the disk polling module **280** in the server software module **205**.

[0178] The server **130** includes an Ethernet interface **230** with two Ethernet ports **231**, **232** configured to handle Gigabit Ethernet or **10**/lOOT Ethernet. The Ethernet interface **230** communicates with the server interface **240** in the server software module **205**. In **FIG. 2**, the Gigabit Ethernet port **231** communicates with one or more Ethernet clients **285** of the DFSS **100**. The Ethernet clients **285** include an installable client interface software component **286** that communicates with the client's operating system and with the Ethernet interface **230** of the server node **150**. In **FIG. 2**, the Ethernet port **232** communicates with an administrative interface system **290**.

[0179] To improve performance for certain implementations, a small file system software layer may also exist on clients **110**, as shown in the embodiment **200** shown in **FIG. 2**, where the client system **110** includes an installable software component called the Client Interface (CI) **201** that communicates with both the client's operating system and, via the communication fabric **120**, with a server node **150** of the DFSS **100**.

[0180] The functions of the FC-API modules **210**, **220** and the Ethernet interface **230** may alternatively be handled by other communication protocols.

[0181] Overview of Metadata Structures

[0182] In order to perform normal file system operations, such as, for example, creating and deleting files, allowing clients to read and write files, caching file data, and keeping track of file permissions, while also providing the flexibility mentioned above, a cluster **160** maintains metadata about the files stored on its disk arrays **140**, **141**. The metadata comprises information about file attributes, file directory structures, physical storage locations of the file data, administrative information regarding the files, as well as other types of information. In various embodiments, the file metadata can be stored in a variety of data structures that are configured in a variety of interconnected configurations, without departing from the spirit of the distributed file system. **FIG. 3** is a block diagram that shows one embodiment of a configuration comprising five metadata structures and connections between them. Each of these structures, the data they hold, and how the structures are used are described in greater detail below.

[0183] Referring to **FIG. 3, a** Filename Table **310** includes a collection of filenames for both files stored on the server node **150** as well as files that are children of directories stored on the server node **150**.

[0184] A G-node Table **330** includes a collection of G-nodes, where each G-node contains data related to attributes of a file. A one-to-one correspondence exists between the G-nodes and files stored on the server node **150**.

[0185] A Gee Table **320** holds data about the physical locations of the file blocks on the disk array **140**. The Gee Table **320** additionally includes pointers to each associated G-node in the G-node Table **330**, and each G-node in the G-node Table **330** includes a pointer to an associated portion of the Gee Table **320**.

[0186] A Gnid Table **340** on the server node **150** includes Gnid-strings that hold data describing the directory structure of that portion of the file system **250** whose directories are stored on the server node **150**. A one-to-one correspondence exists between the Gnid-strings and directory files stored on the server node **150**. Gnid-strings are collections of Gnids, which hold information about individual files that exist within a given directory. The file system **250** allows files within a directory to be stored on a cluster that is different from the cluster on which the parent directory is stored. Therefore, Gnids within a Gnid-string on the server node **150** can represent files that are stored on clusters other than the current cluster **160**.

[0187] Each Gnid includes several pointers. A Gnid in the Gnid Table **340** includes a pointer to an associated filename for the file represented by the Gnid. Because the Filename Table **310** includes filenames for both files stored on the server node **150** as well as files that are children of directories stored on the server node **150**, all Gnids on the server node **150** point to the Filename Table **310** on the server node **150**.

[0188] A Gnid in the Gnid Table **340** includes a pointer to its parent directory's G-node in the G-node Table **330**, and a parent directory's G-node includes a pointer to the beginning of its associated Gnid-string in the Gnid Table **340**.

[0189] Each Gnid also includes a pointer to its own G-node. Since a Gnid can represent a file that is stored on another cluster **160** of the file system **250**, a pointer to the Gnid's own G-node can point to the G-node Table **330** on another server node of the file system **250**.

[0190] A Cache Node Table **350** includes the Cache Nodes that hold information about the physical locations of file blocks that have been cached, including a pointer to a cache location as well as a pointer to a non-volatile location of the data on the disk array **140**. A pointer to a Cache Node exists in the Gee Table **320** for every associated data block that has been cached. Similarly, a pointer exists in the Cache Node to a location in the Gee Table **320** associated with a disk storage location for an associated data block.

[0191] Mirroring of Metadata Structures

[0192] To review the description from **FIG. 1**, in one embodiment, the servers **130, 131** of a cluster **160** are able to access files stored on all the disk array(s) **140, 141** of the cluster **160**. In one embodiment, all server nodes **150, 151** of a cluster **160** have copies of the same Filename Table **310**, Gee Table **320**, G-node Table **330**, and Gnid Table **340**.

[0193] In embodiments where files, as well as metadata, are mirrored across the server nodes **150, 151** of a cluster **160**, a different Gee Table **320** exists for each disk array **140, 141** within a cluster **160**, since the Gee Table **320** holds information about the physical storage locations of the files on a given disk array, and since the disk arrays **140, 141** within a given cluster **160** are not constrained to being identical in capacity or configuration. In such an embodiment, the servers **130, 131** within the cluster **160** have copies of both the Gee Table **320** for a first disk array **140** and the Gee Table **320** for each additional disk array **141** of the cluster.

[0194] In one embodiment, in order to enhance both the security of the metadata and efficient access to the metadata, each server node **150, 151** stores a copy of the Filename Table **310**, the G-node Table **330**, the Gnid Table **340**, and the Gee Table **320** in both non-volatile memory (for security) and in volatile memory (for fast access). Changes made to the volatile versions of the metadata structures **310, 320, 330, 340** are periodically sent to the non-volatile versions for update.

[0195] In one embodiment, the server nodes **150, 151** in the cluster **160** do not have access to one another's cache memory. Therefore, unlike the four metadata structures **310, 320, 330**, and **340** already described, the Cache Node Table **350** is not replicated across the server nodes **150, 151** of the cluster **160**. Instead, the Cache Node Table **350** stored in volatile memory on a first server **130** refers to the file blocks cached on the first the server **130**, and the Cache Node Table **350** stored in volatile memory on a second server **131** refers to file blocks cached on the second server **131**.

[0196] Division of Metadata Ownership

[0197] In one embodiment, the metadata structures described in FIGS. **3** are duplicated across the server nodes **150, 151** of the cluster **160**, allowing access to a set of shared files and associated metadata to all servers in the cluster **160**. All of the server nodes **150, 151** in the cluster **160** can access the files stored within the cluster **160**, and all are considered to be "owners" of the files. Various schemes can be employed in order to prevent two or more servers **130, 131** from altering the same file simultaneously. For example, in embodiments where the cluster **160** includes two server nodes **150** and **151**, one such scheme is to conceptually divide each of the duplicated metadata structures in half and to assign write privileges (or "primary ownership") for one half of each structure to each server node **150, 151** of the cluster **160**. Only the server node **150** that that is primary owner of the metadata for a particular file has write privileges for the file. The other server node(s) **151** of the cluster **160** are known as "secondary owners" of the file, and they are allowed to access the file for read operations.

[0198] In a failure situation, when the server **130** determines that its counterpart **131** is not functional, the server **130** can assume primary ownership of all portions of the metadata structures **310, 320, 330, 340** and all associated files owned by the server **131**, thus allowing operation of the file system **250** to continue without interruption. In one embodiment, if a server in cluster **160** having more than two servers experiences a failure, then primary ownership of the failed server's files and metadata can be divided amongst the remaining servers of the cluster.

[0199] Filename Table

[0200] **FIG. 4** shows a sample portion of the Filename Table **310**. In one embodiment, the Filename Table **310** on the server **130** contains Filename Entries **410, 420, 430, 440** for files which are either stored in the disk array **140** or are parented by a directory file in the disk array **140**. In one embodiment, the Filename Table **310** is stored as an array. In **FIG. 4, a**'Start of String' (SOS) marker **411** marks the beginning of the Filename Entry **410**, and a character string **414** holds characters of the filename, "Doe." In one embodiment, a checksum **412** for the string **414** is also included in the Filename Entry **410**. In one embodiment, a filename length count **413** representing the length of the string **414**, shown in **FIG. 4** to have a value of "3," is included in the Filename Entry **410**. The checksum **412** and the filename length count **413** advantageously allow for an expedited search of the Filename Table **310**.

[0201] A 'Start of String' (SOS) marker **421** marks the beginning of the Filename Entry **420** with a checksum **422**, a filename length count **423** of "6," and a character string **424** holding the filename "Thomas."

[0202] A 'Deleted String' (DS) marker **431** marks the beginning of the Filename Entry **430** with a checksum **432**, a filename length count **433** of "4," and a character string **434** holding the filename "Frog."

[0203] A 'Start of String' (SOS) marker **441** marks the beginning of the Filename Entry **440** with a checksum **442**, a filename length count **443** of "2," and a character string **444** holding the filename "It."

[0204] Comparing the checksums **412**, **422**, **432**, **442** and the filename length counts **413**, **423**, **433**, **443** of each Filename Entry **410**, **420**, **430**, **440** to those calculated for a desired filename provides a quick way to eliminate most Filename Entries in the Filename Table **310** before having to make a character-by-character comparison of the character strings **414**, **424**, **434**, **444**.

[0205] Another advantage of including the filename length counts **413**, **423**, **433**, **443** applies when deleting a Filename Entry **410**, **420**, **430**, **440** from the Filename Table **310**. Replacing the 'Start of String' (SOS) marker **411**, **421**, **441** with a 'Deleted String' (DS) marker **431**, as in the Filename Entry **430**, signals that the corresponding file is no longer stored on the disk array **140**, even if the remainder of the Filename Entry **432-434** remains unchanged. The filename length **433** accurately represents the length of the "deleted" string **434**, and when a new filename of the same length (or shorter) is to be added to the table **310**, the new name and checksum (and filename length count, if necessary) can be added into the slot left by the previous filename.

[0206] Gee Table

[0207] The file system **250** divides files into one or more file logical blocks for storage. Each file logical block is stored in a cluster of one or more disk logical blocks on the disk array **140**. Although the file system **250** retains many of the advantages of a conventional file system implemented on RAID (Redundant Array of Independent Disks), including the distribution of files across multiple disk drives and the use of parity blocks to enhance error checking and error correcting, unlike many RAID systems, the file system **250** does not restrict file logical blocks to one uniform size. File logical blocks of data and parity logical blocks can be the size of any integer multiple of a disk logical block. This variability of file logical block size allows for flexibility in allocating disk space and, thus, for optimized use of system resources.

[0208] In the file system **250**, the size of a file logical block is described by its integer multiple, called its extent, in disk logical blocks. For example, a file logical block with an extent of 3 is stored in a cluster of 3 disk logical blocks on the disk array **140**.

[0209] The Gee Table **320** stores metadata describing the disk logical block locations on the disk array **140** for each file logical block of the files.

[0210] **FIG. 5** shows one embodiment of a Gee Table **320** that is implemented as a flat array. Each indexed row **510-529** of the Gee Table **320** is called a Gee. In **FIG. 5**, Gees **510-528** relate to a single file that is divided into ten file logical blocks. Such a set of Gees **510-528**, which together describe the logical location of a single file on the disk array **140**, is known as a Gee-string **500**. A Gee-string is made up of one or more Gee-groups. Each Gee-group is a set of contiguous Gees that all relate to a single file. In **FIG. 5**, the Gee-string **500** includes three Gee-groups, **550**, **551**, and **552**. The Gee **529** relates to a separate file, as will be explained in more detail below.

[0211] In one embodiment, the Gees **510-529** include a G-code field **590** and a Data field **591**. The G-code field **590** in the Gees **510-529** indicates the type of data that is included in the Data field **591**. In **FIG. 5**, four types of G-codes **590** are depicted: "G-NODE,""DATA,""PARITY," and "LINK."

[0212] In one embodiment, the G-code **590** of "G-NODE" indicates that the Gee is a first Gee of a Gee-group. For example, the first Gee of the Gee-group **550** is a G-NODE Gee **510**. Similarly, the first Gee of the Gee-groups **551** and **552** are also G-NODE Gees **520**, **525**.

[0213] The Data field **591** of a G-NODE Gee can include a pointer to the file's G-node in the G-node Table **330** and information about whether this is the first (or Root) G-NODE Gee of the file's Gee-string **500**. The Data field **591** of a G-NODE Gee can also include information about the extent, or size, of the logical disk block clusters for the file logical blocks of the Gee-group, as will be described in greater detail below.

[0214] In **FIG. 5**, the Data fields **591** of the G-NODE Gees **510**, **520**, and **525** contain a reference to G-node index "67," indicating that they all relate to the file associated with the G-node at index "67" of the G-node Table **330**. That is, they all relate to portions of the same file. The Data field **591** of the Gee **529** refers to the G-node index "43," indicating that it relates to a different file.

[0215] Of the G-NODE Gees **510**, **520**, **525**, only the first Gee **510** contains an indication that it is a Root Gee, meaning that it is the first Gee of the Gee-string **500**. The Gee **529** is a G-NODE Gee, indicating that it is a first Gee of a Gee-group (the remainder of which is not shown), and the Data field **591** of the Gee **529** also indicates that the Gee **529** is not a Root Gee for its Gee-string.

[0216] Following the G-NODE Gee in a Gee-group are Gees representing one or more Distributed Parity Groups (DPGs) **560**, **561**, **52**, **563**. A DPG is set of one or more contiguous DATA Gees followed by an associated PARITY Gee. A DATA Gee is a Gee with a G-code **590** of "DATA" that lists disk logical block(s) where a file logical block is stored. For example, in **FIG. 5**, the Gees **511-513**, **515-517**, **521-522**, and **526-527** are all DATA Gees, and each is associated with one file logical block **592**.

[0217] A PARITY Gee is a Gee with a G-code **590** of "PARITY." Each PARITY Gee lists disk logical block location(s) for a special type of file logical block that contains redundant parity data used for error checking and error correcting one or more associated file logical blocks. A PARITY Gee is associated with the contiguous DATA Gees that immediately precede the PARITY Gee. A set of contiguous DATA Gees and the PARITY Gee that follows them are known collectively as a Distributed Parity Group **560**, **561**, **562**, **563**.

[0218] For example, in **FIG. 5**, the PARITY Gee **514** is associated with the DATA Gees **510-513**, and together they form the Distributed Parity Group **560**. Similarly, the PARITY Gee **518** is associated with the DATA Gees **515-517**, and together they form the Distributed Parity Group **561**. The PARITY Gee **523** is associated with the DATA Gees **521-522**, which together form the Distributed Parity Group **562**, and the PARITY Gee **528** is associated with the DATA Gees **526-527**, which together form the Distributed Parity Group **563**.

[0219] The size of a disk logical block cluster described by a DATA Gee or a PARITY Gee, as measured in number of disk logical blocks, matches the extent listed in the previous G-NODE Gee. In the example of **FIG. 5**, the G-NODE Gee **510** defines an extent size of 2, and each DATA and PARITY Gee **511-518** of the two Distributed Parity Groups **560, 561** of the Gee-group **550** lists two disk logical block locations. Similarly, G-NODE Gee **520** of the second Gee-group **551** defines an extent size of 3, and each DATA and PARITY Gee **521-523** of the Gee-group **551** lists three disk logical block locations. G-NODE Gee **525** of the third Gee-group **552** defines an extent size of 3, and each DATA and PARITY Gee **526-528** of the Gee-group **552** lists three disk logical block locations.

[0220] If a Gee-group is not the last Gee-group in its Gee-string, then a mechanism exists to logically link the last Gee in the Gee-group to the next Gee-group of the Gee-string. LINK Gees **519, 524** have the G-code **590** of "LINK" and a listing in their respective Data fields **591** that provides the index of the next Gee-group of the Gee-string **500**. For example, the Gee **519** is the last Gee of Gee-group **550**, and its Data field **591** includes the starting index "76" of the next Gee-group **551** of the Gee-string **500**. The Gee **524** is the last Gee of Gee-group **551**, and its Data field **591** includes the starting index "88" of the next Gee-group **552** of the Gee-string **500**. Since the Gee-group **552** does not include a LINK Gee, it is understood that Gee-group **552** is the last Gee-group of the Gee-string **500**.

[0221] A G-code **590** of "FREE" (not shown in **FIG. 5**) indicates that the Gee has never yet been allocated and has not been associated with any disk logical location(s) for storing a file logical block. A G-code **590** of "AVAIL" (not shown in **FIG. 5**) indicates that the Gee has been previously allocated to a cluster of disk logical block(s) for storing a file logical block, but that the Gee is now free to accept a new assignment. Two situations in which a Gee is assigned the G-code of "AVAIL" are: after the deletion of the associated file logical block; and after transfer of the file to another server in order to optimize load balance for the file system **250**.

[0222] A G-code of "CACHE DATA" indicates that the disk logical block cluster associated with the Gee (which was previously a DATA Gee) has been cached. A G-code of "CACHE PARITY" indicates that the disk logical block cluster associated with this Gee (which was previously a PARITY Gee) has been cached. The CACHE DATA and CACHE PARITY G-codes will be described in greater detail when Cache Nodes and the Cache Node Table are described in connection with **FIG. 8A** below.

[0223] G-node Table

[0224] The G-node Table **330** is a collection of G-nodes, where each G-node includes attribute information relating to one file. Attribute information can include, but is not restricted to: information about physical properties of the file (such as, for example, its size and physical location on disk); information about the file's relationships to other files and systems (such as, for example, permissions associated with the file and server identification numbers for the primary and secondary owners of the file); and information about access patterns associated with the file (such as, for example, time of the last file access and time of the last file modification).

[0225] In addition to file attribute information, a G-node provides links to the root Gee and a midpoint Gee of the file's Gee-string in the Gee Table **320**. If the file is a directory file, its G-node also contains a pointer to the beginning of the Gnid-string that describes the files contained in the directory, as will be explained with reference to **FIG. 7** below.

[0226] In one embodiment, the G-node Table **330** is implemented as a flat array.

[0227] **FIG. 6** shows one embodiment of information that can be included in a G-node **600**. A File Attribute-type field **602** designates a file as belonging to a supported file type. For example, in one embodiment, NFNON indicates that the G-node is not currently associated with a file, NFREG indicates that the associated file is a regular file, NFDIR indicates that the associated file is a directory, NFLINK indicates that an associated file is a symbolic link that points to another file.

[0228] A File Attribute-mode field **604** gives information regarding access permissions for the file.

[0229] A File Attribute-links field **606** designates the number of directory entries for a file in the file system **250**. This number can be greater than one if the file is the child of more than one directory, or if the file is known by different names within the same directory.

[0230] A File Attribute-uid field **608** designates a user ID for a file's user/owner.

[0231] A File Attribute-gid field **610** designates a group ID of a file's user/owner.

[0232] A File Attribute-size field **612** designates a size in bytes of a given file.

[0233] A File Attribute-used field **614** designates an amount of disk space used by a file.

[0234] A File Attribute-fileId field **620** designates a file ID.

[0235] A File Attribute-atime field **622** designates the time of the last access to the file.

[0236] A File Attribute-mtime field **624** designates the time of the last modification to the file.

[0237] A File Attribute-ctime field **626** designates the time of the last modification to a G-node (excluding updates to the atime field **622** and to the mtime field **624**).

[0238] If a file is a directory file rather than a data file, then its Child Gnid Index field **628** is an index for the oldest child in an associated Gnid-string (to be described in greater detail with reference to **FIG. 7** below); otherwise, this field is not used.

[0239] A Gee Index-Last Used field **630** and a Gee Offset-Last Used field **631** together designate a location of a most recently accessed Gee **510** for a given file. These attributes can be used to expedite sequential reading of blocks of a file.

[0240] A Gee Index-Midpoint field **632** and a Gee Offset-Midpoint field **633** together point to a middle Gee **510** of the Gee-string **500**. Searching for a Gee for a given file block can be expedited using these two fields in the following way: if a desired block number is greater than the block number

of the midpoint Gee, then sequential searching can begin at the midpoint of the Gee-string **500** rather than at its beginning.

[**0241**] A Gee Index-Tail field **634** and a Gee Offset-Tail field **635** together point to the last Gee **528** of the Gee-string **500**. New data can easily be appended to the end of a file using the pointers **634** and **635**.

[**0242**] A Gee Index-Root field **636** is an index of the root Gee **510** of a Gee-string for an associated file.

[**0243**] A G-node Status field **638** indicates whether the G-node is being used or is free for allocation.

[**0244**] A Quick Shot Status field **640** and a Quick Shot Link field **642** are used when a "snapshot" of the file system **250** is taken to allow for online updates and/or verification of the system that does not interrupt client access to the files. During a "snapshot," copies of some portions of the system are made in order to keep a record of the system's state at one point in time, without interfering with the operation of the system. In some embodiments, more than one Quickshot can be maintained at a given time. The Quick Shot Status field **640** indicates whether the G-node was in use at the time of the "snapshot" and, therefore, if it has been included in the "snapshot." If the G-node has been included in the "snapshot," the Quick Shot Link field **642** provides a link to the newly allocated copy of the G-node.

[**0245**] In one embodiment, a bit-mask is associated with each element with the file system **250** identifying any of a number of Quickshot instances to which the element belongs. When a Quickshot is requested, a task can set the bit for every element, holding the file system at bay for a minimum amount of time. Thus, capturing the state of a file system comprises identifying elements in the file system as being protected, rather than actually copying any elements at the time of the Quickshot.

[**0246**] In one embodiment, the file system uses a copy-on-write mechanism so that data is not overwritten; new blocks are used for new data, and the metadata is updated to point to the new data. Thus, a minimum of overhead is required to maintain a Quickshot. If a block is being written and the file system element being modified has a bit set indicating that it is protected by a Quickshot, the metadata is copied to provide a Quickshot version of the metadata, which is distinct from the main operating system. Then, the write operation continues normally.

[**0247**] Gnid Table

[**0248**] Files in the file system **250** are distributed across a plurality of server nodes **150** while still appearing to clients **110** as a single file system. According to different embodiments, files can be distributed in a variety of ways. Files can be distributed randomly, or according to a fixed distribution algorithm, or in a manner that enhances load balancing across the system, or in other ways.

[**0249**] In one embodiment, the files of a given directory need not be stored physically within the same cluster as the cluster that stores the directory file itself. Nor does one large table or other data structure exist which contains all directory structure information for the entire file system **250**. Instead, directory structure information is distributed throughout the file system **250**, and each server node **150** is responsible for storing information about the directories that it stores and about the child files of those directories.

[**0250**] In one embodiment, server nodes of the DFSS **100** hold directory structure information for only the directory files that are stored on the server node and for the child files of those directories, that is, the files one level down from the parent directory. In another embodiment, server nodes of the DFSS **100** hold directory structure information for each directory file stored on the server node and for files from a specified number of additional levels below the parent directory in the file system's directory structure.

[**0251**] In one embodiment, an exception to the division of responsibility described above is made for the directory structure information for a "root" directory of the file system **250**. The "root" directory is a directory that contains every directory as a sub-directory and, thus, every file in the file system **250**. In this case, every server in the file system **250** can have a copy of the directory structure information for the "root" directory as well as for its own directories, so that a search for any file of unknown location can be initiated at the "root" directory level by any server of the file system **250**. In another embodiment, the directory structure information for the "root" directory is stored only in the cluster that stores the "root" directory, and other clusters include only a pointer to the "root" directory.

[**0252**] The Gnid Table **340** on the server node **150** defines a structure for directory files that reside on the server node **150**. The Gnid Table **340** comprises Gnid-strings, which, in one embodiment, are linked lists implemented within a flat array. In one embodiment, a Gnid-string exists for each directory file on the server node **150**. Individual elements of a Gnid-string are called Gnids, and a Gnid represents a child file of a given parent directory.

[**0253**] **FIG. 7** shows the structure of one embodiment of a Gnid-string **700**. In this embodiment, the Gnid-string **700** for a directory file is a linked list of Gnids **710-713**, where each Gnid represents one file in the directory. In one embodiment, in order to expedite searching the Gnid-string **700** for a given Gnid, the Gnids are kept in ascending order of the checksums **412**, **422**, **442** of the files' filenames **410**, **420**, **440**, such that the Gnid with the smallest checksum is first in the Gnid-string **700**. When a new file is added to a directory, a Gnid for the newly added file is inserted into the appropriate location in the Gnid-string **700**. Search algorithms that increase the efficiency of a search can exploit this sorted arrangement of Gnids **710-713** within a Gnid-string **700**.

[**0254**] Since Gnids share a common structure, a description of one Gnid **710** is to be understood to describe the structure of all other Gnids **711-713** as well.

[**0255**] The Gnid **710** includes, but is not restricted to, seven fields **720**, **730**, **740**, **750**, **760**, **770**, and **780**. A Status field **720** indicates whether the Gnid **710** is a first Gnid (GNID_OLDEST) in the Gnid-string **700**, a last Gnid (GNID_YOUNGEST) in the Gnid-string **700**, a Gnid that is neither first nor last (GNID_SIBLING) in the Gnid-string **700**, or a Gnid that is not currently in use (GNID_FREE).

[**0256**] A Parent G-node Ptr field **730** is a pointer to the G-node for the file's parent directory in the G-node Table **330**.

[0257] A Sibling Gnid Ptr field **740** is a pointer to the next Gnid **711** on the Gnid-string **700**. In the embodiment described above, the Sibling Gnid Ptr field **740** points to the Gnid within the Gnid-string **700** that has the next largest checksum **412**, **422**, **442** value. A NULL value for the Sibling Gnid Ptr field **740** indicates that the Gnid is the last Gnid of the Gnid-string **700**.

[0258] A G-node Ptr field **750** is a pointer to the file's G-node **600**, indicating both the server node that is primary owner of the file and the file's index into the G-node Table **330** on that server node.

[0259] A Filename Ptr field **760** is a pointer to the file's Filename Entry in the Filename Table **310**.

[0260] A ForBiGnid Ptr field **770** is a pointer used for skipping ahead in the Gnid-string **700**, and a BckBiGnid Ptr field **780** is a pointer for skipping backward in the Gnid-string **700**. In one embodiment, the fields **770** and **780** can be used to link the Gnids into a binary tree structure, or one of its variants, also based on checksum size, thus allowing for fast searching of the Gnid-string **700**.

[0261] Cache Node Table

[0262] The Cache Node Table **350** stores metadata regarding which data blocks are currently cached as well as which data blocks have been most recently accessed. The Cache Node Table **350** is integrated with the file system **250** by way of a special type of Gee **510** in the Gee Table **320**. When a data block is cached, a copy of its associated DATA Gee **511-513**, **515-517**, **521-522**, **526-527**, which describes the location of the data on the disk array **140**, is sent to the Cache Node Table **350**, where it is held until the associated data is released from the cache. Meanwhile, the DATA Gee **511-513**, **515-517**, **521-522**, **526-527** in the Gee Table **320** is modified to become a CACHE DATA Gee; its G-Code **590** is changed from DATA to CACHE DATA, and instead of listing a data block's location on disk **140**, the Data field **591** of the Gee now indicates a location in the Cache Node Table **350** where a copy of the original DATA Gee **511-513**, **515-517**, **521-522**, **526-527** was sent and where information about the data block's current location in cache can be found.

[0263] In one embodiment, the Cache Node Table **350** is implemented as a list of fixed length Cache Nodes, where a Cache Node is associated with each Gee **511-513**, **515-517**, **521-522**, **526-527** whose data has been cached. The structure of one embodiment of a Cache Node **800** is described in **FIG. 8A**.

[0264] Referring to **FIG. 8A**, the Cache Node **800** is shown to include nine fields. A Data Gee field **810** is a copy of the DATA Gee **511-513**, **515-517**, **521-522**, **526-527** from the Gee Table **320** that allows disk location information to be copied back into the Gee Table **320** when the associated data block is released from cache. A PrevPtr field **815** holds a pointer to the previous Cache Node in the Cache Node Table **350**. A NextPtr field **820** holds a pointer to the next Cache Node in the Cache Node Table **350**. In one embodiment, the Cache Node Table **350** is implemented as a flat array, in which case the PrevPtr **815** and NextPtr **820** fields can hold indices of a previous and a next item in the table. A CacheBlockAddr field **825** holds a pointer to a location in cache where the associated data has been cached. A ReadCt field **830** is a counter of the number of clients currently reading the associated data block. A CacheTime field **835** holds a time that the associated cache contents were last updated. A Regenerated field **840** holds a flag indicating that the associated cache contents have been regenerated. A CacheBlockHiAddr field **845** and a CacheBlockLoAddr field **850** hold a "high water mark" and "low water mark" of the data in a cache block. These "water marks" can be used to demarcate a range of bytes within a cache block so that if a write operation has been performed on a subset of a cache block's bytes, then when the new data is being written to disk, it is possible to copy only relevant or necessary bytes to the disk.

[0265] In one embodiment, the Cache Node Table **350** is conceptually divided into three lists, as depicted in **FIG. 8B**. A Normal List **860** includes all the Cache Nodes **800** in the Cache Node Table **350** which are associated with cached data that is not currently in use. A Write List **865** holds the Cache Nodes **800** of data blocks that have been modified and that are waiting to be written to disk. A Read List **870** holds the Cache Nodes **800** of data blocks that are currently being read by one or more clients.

[0266] When existing cached data is needed for a write or a read operation, the associated Cache Node **800** can be "removed" from the Normal List **860** and "linked" to the Write List **865** or the Read List **870**, as appropriate. The Cache Nodes **800** in each of the lists **860**, **865**, **870** can be linked by using the PrevPtr **815** and NextPtr **820** fields. The Cache Nodes **800** of data blocks that are being written to can be "moved" from the Normal List **860** to the Write List **865** until an associated data block stored on the disk array **140** is updated. The Cache Nodes **800** of data blocks that are being read can be similarly "moved" to the Read list by resetting the links of the PrevPtr **815** and NextPtr **820** fields.

[0267] The Cache Nodes **800** of data blocks that are being read can additionally have their ReadCt field **830** incremented, so that a count may be kept of the number of clients currently reading a given data block. If additional clients simultaneously read the same file, the server **130** increments the Cache Node's ReadCt field **830** and the Cache Node **800** can stay in the Read List **870**. As each client finishes reading, the ReadCt **830** is appropriately decremented. When all clients have finished reading the file block and the ReadCt field **830** has been decremented back to a starting value, such as **0**, then the Cache Node **800** is returned to the Normal List **860**.

[0268] In one embodiment, the server **130** that wishes to access an existing Cache Node **800** for a read or a write operation can "take" the desired Cache Node **800** from any position in the Normal List **860**, as needed. The Cache Nodes **800** from the Write List **865** whose associated data have already been written to disk are returned to a "top" position **875** of the Normal List **860**. Similarly, when no clients are currently reading the cached data associated with a given the Cache Node **800** on the Read List **870**, the Cache Node **800** is returned to the "top" position **875** of the Normal List **860**. In this way, a most recently accessed Cache Node **800** amongst the Cache Nodes **800** on the Normal List **860** will be at the "top" position **875**, and a least recently accessed the Cache Node **800** will be at a "bottom" position **880**.

[0269] In one embodiment, if space in the cache is needed for a new data block when all of the Cache Nodes **800** have been assigned, then the Cache Node **800** in the "bottom" position **880** is selected to be replaced. To do so, the cached data associated with the "bottom" Cache Node **880** can be written to a disk location specified in the DataGee field **810** of the "bottom" Cache Node **880**, and the DataGee **810** from the "bottom" Cache Node **880** is returned to its location in the Gee Table **320**. The "bottom" Cache Node **880** can then be overwritten by data for a new data block.

[0270] In one embodiment, the server nodes **150**, **151** in the cluster **160** do not have access to one another's cache memory. Therefore, unlike the metadata structures described in FIGS. **4-7**, the Cache Node Table **350** is not replicated across the servers **130**, **131** of the cluster **160**.

[0271] Lock Nodes and Refresh Nodes

[0272] In addition to the metadata structures described above in connection with FIGS. **3-8**, other metadata structures can be used to enhance the security and the efficiency of the file system **250**. Two metadata structures, a Lock Node Table and a Refresh Node Table, assist with the management of "shares" and "locks" placed on the files of the server node **150**. A share or a lock represents a client's request to limit access by other clients to a given file or a portion of a file. Depending on its settings, as will be described in greater detail below, a share or a lock prevents other client processes from obtaining or changing the file, or some portion of the file, while the share or lock is in force. When a client requests a share or a lock, it can either be granted, or, if it conflicts with a previously granted share or lock, it can be given a "pending" status until the original share or lock is completed.

[0273] Information about current shares and locks placed on a server node's files is stored in a Lock Node Table. A Lock Node Table includes Lock Strings, where each Lock String describes the current and pending shares and locks for a given file.

[0274] **FIG. 9** shows the structure of one embodiment of a Lock String **900**. The Lock String **900** includes five nodes **911**,**912**, **921**, **922**, and **923**. The first two nodes **911** and **912** are Share Nodes **910**. The next three nodes **921-923** are Lock Nodes **920**. As shown in **FIG. 9**, in one embodiment, Share Nodes **910** precede Lock Nodes **920** in the Lock String **900**.

[0275] The Share Nodes **910** have eight fields **930-937**, and the Lock Nodes **920** have ten fields **930-933** and **938-943**. In **FIG. 9**, the first four fields of both the Share Nodes **910** and the Lock Nodes **920** are the same, and as such, a description of one shall be understood to apply to both Share Nodes and Lock Nodes.

[0276] A lockStatus field **930** indicates whether the node is of type SHARE or LOCK, or if it is currently an unused FREE node. A SHARE node represents a current or pending share request. A share applies to an entire file, and, if granted, it specifies the read and write permissions for both a requesting client and for all other clients in the system. A LOCK node represents a current or pending lock request. A lock applies to a specified byte range within a file, and, if granted, it guarantees that no other client process will be able to access the same range to write, read or read/write, depending on the values in the other fields, while the lock is in effect.

[0277] A timeoutCt field **931** helps to ensure that locks and shares are not inadvertently left in effect past their intended time, due to error, failure of a requesting client process, or other reason. Locks automatically "time out" after a given length of time unless they are "refreshed" periodically.

[0278] A next field **932** points to the next node in the Lock String **900**. A pending field **933** indicates whether the lock or share represented by the node is active or pending.

[0279] The fields **934-937** of **FIG. 9** contain additional information useful to the Share Nodes **910**. An access field **935** indicates the kind of access to the file that the client desires. In one embodiment, the access field **935** may take on one of four possible values: 0 indicates that no access to the file is required; 1 indicates that read only access is required; 2 indicates that only write access is required; and 3 indicates that read and write access to the file are both required.

[0280] A mode field **934** indicates the level of access to the file that another client process will be permitted while the share is in effect. In one embodiment, the mode field **934** can take on one of four possible values: 0 indicates that all access by other client processes is permitted; 1 indicates that access to read the file is denied to other client processes; 2 indicates that access to write to the file is denied to other client processes; and 3 indicates that both read and write access are denied to other client processes.

[0281] A clientID field **936** identifies the client that requested the share. A uid field **937** identifies the user on the client that has requested the share or lock.

[0282] Fields **938-943** of **FIG. 9** contain additional information useful to Lock Nodes **920**. An offset field **938** indicates the starting point of the byte range within the file where the lock is in effect. A length field **939** indicates the length of the segment (beginning at the offset point) that is affected by the lock. In one embodiment, Lock Nodes **920** are kept ordered within the Lock String **900** according to their offset field **938**.

[0283] An exclusive field **940** indicates whether the lock is exclusive or non-exclusive. An exclusive lock, sometimes called a write lock, is used to guarantee that the requesting process is the only process with access to that part of the file for either reading or writing. A non-exclusive lock, often called a read lock, is used to guarantee that no one else may write to the byte range while the requesting the process is using it, although reading the file is permitted to other clients.

[0284] A clientID field **941** identifies the client that requested the lock. A uid field **942** identifies the user on the client that is requesting the lock. A svid field **943** identifies the process that is requesting the lock.

[0285] In one embodiment, a Refresh Node Table is used to detect clients who hold locks or shares on files and who are no longer in communication with the DFSS **100**. A Refresh Node is created for each client that registers a lock or share. **FIGS. 10 and 11** depict examples of how Refresh Nodes can be configured as a binary tree and as a doubly-linked list, respectively. Based on the task at hand and on the links used for traversal, both structures can exist simultaneously for the same set of Refresh Nodes, as will be explained in greater detail below.

[0286] Referring to **FIG. 10**, six Refresh Nodes **1000**, **1010**, **1020**, **1030**, **1040**, and **1050** are shown configured as a binary tree. The structure of each Refresh Node is the same, and it is to be understood that a detailed description of one Refresh Node **1000** applies also to the other Refresh Nodes **1010**, **1020**, **1030**, **1040** of **FIG. 10**. In one embodiment, the Refresh Node **1000** includes six fields. A clientID field **1001** identifies a client who has registered at least one current lock or share. A counter field **1002** maintains a counter that, in one embodiment, is originally set to a given start value and is periodically decremented until a "refresh" command comes from the client to request that the counter be returned to its full original value. If the counter field **1002** is allowed to decrement to a specified minimum value before a "refresh" command is received from the identified client **1001**, then all locks and shares associated with the client **1001** are considered to have "timed out," and they are removed from their respective Lock Strings **900**.

[0287] In one embodiment, Refresh Nodes are allocated from a flat array of Refresh Nodes. The Refresh Nodes can be linked and accessed in a variety of ways, depending on the task at hand, with the help of pointer fields located in each node. For example, when a "refresh" command arrives from the client **110**, it is advantageous to be able to quickly locate the Refresh Node **1000** with the associated clientID field **1001** in order to reset its counter field **1002**. A binary tree structure, as shown in the example of **FIG. 10**, can allow for efficient location of the Refresh Node **1000** with the given clientID field **1001** value if the nodes of the tree are organized based on the clientID field **1001** values. In such a case, a left link field **1003** (ltLink) and a right link field **1004** (rtLink), pointing to the Refresh Node's left and right child, respectively, provide links for traversal of the tree using conventional algorithms for traversing a binary tree.

[0288] In one embodiment, unused Refresh Nodes **1100**, **1110**, **1120**, **1130** in the flat array are kept in a doubly-linked Free List, such as the one depicted in **FIG. 11**, for ease of allocation and de-allocation. In one embodiment, used Refresh Nodes are kept in a doubly-linked list, called a Used List. With this structure, decrementing the counter field **1002** of each Refresh Node that is currently in use can be carried out efficiently. In **FIG. 11, a** stackNext field **1105** and a stackprev field **1106** of the Refresh Node **110** together allow for doubly-linked traversal of the Refresh Nodes of the Free List and the Used List. When a new Refresh Node is needed, it can be removed from the Free List and linked to both the Used List and the binary tree by the appropriate setting of the link fields **1003**, **1004**, **1105**, and **1106**.

[0289] Intent Log

[0290] In one embodiment, the Filename Table **310**, the G-node Table **330**, the Gee Table **320** and the Gnid Table **340** are cached as well as being stored on the disk array **140**. In one embodiment, when the server **130** changes a portion of the metadata in cache, an entry is made into an Intent Log in non-volatile memory, such as flash memory or battery-backed RAM. The Intent Log Entry documents the intention to update both the version of the metadata stored on the disk array **140** and any mirrored version(s) of the metadata on other server nodes **151** of the cluster **160**. The Intent Log provides protection against inconsistencies resulting from a power loss before or during an update.

[0291] The following is a list of steps that show the general use of the Intent Log:

[0292] 1. Cached metadata is updated at the time of the original change.

[0293] 2. An intention to update the disk version of the metadata is put into the Intent Log.

[0294] 3. A copy of the intention is transmitted to other server nodes of the cluster.

[0295] 4. The intention to write metadata to disk on the first server node is executed.

[0296] 5. The intention to write metadata to disk on the other server nodes is executed.

[0297] 6. The Intent Log Entry on the first server is deleted.

[0298] 7. Notice of the first server's Intent Log Entry is sent to the other server nodes.

[0299] **FIG. 12** shows the structure of an Intent Log Entry **1200**. In one embodiment, the Entry **1200** includes seven fields. A status field **1210** designates whether the intention is FREE, WAITING, or ACTIVE. An intentType field **1220** designates the type of metadata that is to be updated. For example, the update may apply to a G-node, a Gnid, a Gee, a Filename Entry, or to a file's last access time (aTime). A goalBufferIndex field **1230** points to an entry in a Goal Buffer that is used to verify the update. Field **1240** is a spare field that helps align the fields to a 64 bit boundary. A driveSector field **1250** and a drive field **1260** identify the location on disk where the update is to be made. An intentData field **1270** holds the data of the update.

[0300] File Handle

[0301] A file handle is provided to clients by the DFSS **100** for use when requesting access to a file. Each file handle uniquely identifies one file. The DFSS **100** treats both normal data files and directories as files, and provides file handles for both. In the description that follows, the term "file" may apply to either a data file or a directory file, unless specifically limited in the text.

[0302] **FIG. 13** shows the structure of one embodiment of a file handle **1300** as a 32-bit number with three fields. A Recommended NIC field **1310** indicates which of a server's Network Interface Connections (NICs) is recommended for accessing the file associated with the file handle **1300**. Fibre Channel typically provides two ports per server; accordingly, in one embodiment, the Recommended NIC field **1310** is one bit in size.

[0303] A ServerID field **1320** identifies, by means of a server identification number (ServerID), the primary owner of the associated file. The inclusion of the file owner's ServerID **1320** in the file handle **1300** enables a user on the client **110** to access a file in the distributed file system **250** without needing to knowing explicitly which server node is holding the desired file. Using the file handle **1300** to request a file from the file system software **250** allows the file system software **250** to direct the request to the appropriate server. By contrast, conventional UNIX file handles do not include information regarding the server storing a file, and they are therefore not able to accommodate the level of transparent file access provided in the file system software **250**.

[0304] In one embodiment, clusters **160** include only two server nodes **150**, **151**, and the ServerID of the file's secondary owner can be obtained by "flipping" the least significant bit of the field **1320**. This ability is useful when the primary owner **150** is very busy and must issue a "retry later" response to a client's request to read a file. In return, the client **110** can temporarily change the ServerID in the file's file handle **1300** and re-send the read request to the file's secondary owner **151**. Similar accommodations can be made for clusters of more than two server nodes.

[0305] A G-node Index field **1330** provides an index into the file's G-node in the G-node Table **330** on the server identified in the ServerID field **1320**.

[0306] In one embodiment, the file handle for a given file does not change unless the file is moved to another server node or unless its G-node location is changed. Thus, the file handle is relatively persistent over time, and clients can advantageously store the file handles of previously accessed files for use in subsequent accesses.

[0307] File Handle Look-Up

[0308] In order to access a desired file, the client **110** sends the file's file handle **1300** and a request for file access to the file system **250**. As was illustrated in the embodiment shown in **FIG. 13**, the file handle **1300** of a given file comprises information to identify the server that stores the file and the location of the file's G-node **600** in the G-node Table **330**. With the information found in the G-node **600**, as described in the example of **FIG. 6**, the desired file can be located and accessed.

[0309] The file handle **1300** for a given file remains relatively static over time, and, typically, the client **110** stores the file handles **1300** of files that it has already accessed for use in subsequent access requests. If the client **110** does not have a desired file's file handle **1300**, the client **110** can request a file handle look-up from the file system **250** to determine the needed file handle **1300**.

[0310] In one embodiment of a file handle look-up process, the DFSS **100** accepts the file handle **1300** of a parent directory along with the filename of a desired child file, and the DFSS **100** returns the file handle **1300** for the desired child file. If the client **110** does not know the file handle **1300** for the desired file's parent directory, then the client **110** can use the file handle **1300** for any directory along the pathname of the desired file and can request a file handle look-up for the next component on the desired pathname. The client **110** can then iteratively request a file handle look-up for each next component of the pathname, until the desired file's file handle **1300** is returned.

[0311] For example, if the client **110** desires the file handle **1300** for a file whose pathname is "root/WorkFiles/PatentApps/DesiredFile" and if the client **110** has the file handle **1300** for the parent "Patent Apps" directory, then the client **110** can send the look-up request with the "PatentApps" file handle **1300** to get the "DesiredFile" file handle **1300**. If the client initially has no file handle **1300** for the parent "PatentApps" directory, but does have the file handle **1300** for the "WorkFiles" directory, then the client **110** can send a first look-up request with the known "WorkFiles" file handle **1300** together with the filename for the "PatentApps" directory. The DFSS **100** returns the file handle for the "PatentApps" directory. Since the client **110** still does not have the needed "DesiredFile" file handle **1300**, the client **110** can send a second file handle look-up request, this time using the newly received "PatentApps" file handle and the "DesiredFile" filename. In response, the file system **250** returns the "DesiredFile" file handle **1300**. In this way, beginning with the file handle **1300** for any file along the pathname of a desired file, the file handle **1300** for the desired file can eventually be ascertained.

[0312] In one embodiment, when the client **110** first accesses the file system **250**, the client **110** is provided with one file handle **1300**, namely the file handle for a "root" directory. The "root" directory is the directory that contains all other directories, and is therefore the first component on the pathname of every file in the system. Thus, if need be, the client **110** can begin the look-up process for any file's file handle **1300** with a look-up request that comprises the "root" file handle and the filename of the next component of the desired file's pathname. The final file handle returned will provide the client with the information needed to accurately locate the desired file.

[0313] **FIG. 14A** shows an example of the file handle look-up procedure in which the client **110** has a file handle **1300** for a desired file's parent directory and needs a file handle for the desired file itself. The client **110** initiates a look-up for the desired file handle by sending a look-up request **1410** that comprises a filename **1420** of the desired file and the file handle **1300** of the parent directory. The ServerID field **1320** in the file handle **1300** identifies the server **130** of the node **150** where the parent directory is stored, and the file system software **250** directs the look-up request **1410** to the identified server **130**. The G-node index field **1330** stores an index for the parent directory's G-node in the G-node Table **330** on the identified server.

[0314] In this example, the filename **1420** of the desired file is "AAAAA." The ServerID field **1320** indicates that the parent directory is stored on the server **130** with ServerID "123," and the G-node index field **1330** shows that a G-node for the parent directory can be found at index location "1" in the G-node Table **330**.

[0315] When the server **130** receives the look-up request **1410**, the server **130** uses information in the G-node index field **1330** of the file handle **1300** to access a G-node **1432** at index location "1."

[0316] As described above, the G-node **600** acts as a repository of general information regarding a file. In the example illustrated in **FIG. 14A**, the File Attribute-type field **602** of the G-node **1432**, namely "NFDIR," indicates that the file associated with the G-node **1432** is a directory, not a regular data file.

[0317] As described earlier, the Gnid-string **700** holds information about the children files of a given directory. The Child Gnid Index **628** in G-node **1432** points to a first Gnid **1436** in the directory's Gnid-string **700**. The server **130** searches for the desired data file amongst the children files of the parent directory by searching the corresponding Gnids on the directory's Gnid-string. The server **130** uses the Filename Ptr fields **760** of each Gnid **710** to access the associated file's filename entry **410** for comparison with the filename **1420** of the desired file.

[0318] In **FIG. 14A**, the Child Gnid Index field **628** of G-node **1432** indicates a value of "3," and the server **130** accesses the Gnid **1436** at index location "3" in the Gnid Table **340**. To determine a filename associated with the Gnid **1436**, the server **130** uses the Filename Ptr field **760** to access the Filename Entry **1438** associated with the Gnid **1436** at index "3." To ascertain if the filename stored at the Filename Entry **1438** matches the filename **1420** in the look-up request **1410**, the server **130** first compares the checksum and filename length count of the filename **1420** in the look-up request **1410** with the checksum **412** and the filename length count **413** stored in the Filename Entry **1438** in the Filename Table **310**. (Note: These checksums and filename lengths are not shown explicitly in **FIGS. 14A and 14B**.) If the aforementioned checksums and filename length counts match, the server **130** proceeds with a character-by-character comparison of the character string **1420** in the look-up request **1410** and the filename **414** in the Filename Entry **1438**.

[0319] If a mismatch is encountered during the comparisons, as is the case in **FIG. 14A**, where the Filename Entry **1438** holds a filename of "ABCD" and length "4" while the desired filename of "AAAAA" has a length of "5," then the current Gnid is eliminated from consideration. After encountering a mismatch for the Gnid **1436** at index "3," the server **130** continues to traverse the Gnid-string **700** by using the Sibling Gnid Ptr field **740** in the current Gnid **1436** as an index pointer.

[0320] The Sibling Gnid Ptr field **740** of the Gnid **1436** holds a value of "4," indicating that a next Gnid **1440** can be found at index location "4" of the Gnid Table **340**. When the checksum and name length for the desired filename **1420** do not match those from a Filename Entry **1442**"DE" found at index location "0" of the Filename Table **310**, the server **130** again eliminates the current Gnid from consideration.

[0321] The server **130** again uses the Sibling Gnid Ptr field **740** as a pointer, this time from the Gnid **1440** at index location "4" to a Gnid **1444** at index location "6" in the Gnid Table **340**. Following the Filename Ptr **760** of the Gnid **1444** to Filename Entry **1446** and performing the aforementioned checksum, filename length, and filename comparisons reveals that the desired filename **1420** and Filename Entry filename **1446** do match. The server **130** therefore determines that this Gnid **1444** is associated with the desired file.

[0322] In order to send the desired file handle **1300**, which comprises the ServerID **1320** and G-node Table index **1330** for the desired file, to the requesting client **110**, the server **130** accesses the G-node Ptr field **750** of the current Gnid **1444**. The G-node **600** of a file is stored on the server node **150** where the file is stored, which is not necessarily the same server node that holds its parent directory. The G-node Ptr field **750** provides both the ServerID of the server that is the file's primary owner and an index that identifies the file's G-node **1448** in the primary owner's G-node Table **330**.

[0323] In the example of **FIG. 14A**, the contents of the G-node Ptr field **750** show that the desired G-node **1448** exists at location "9" in the G-node table **330** on the same server **130**, namely the server with ServerID "123." However, it would also be possible for the G-node Ptr field **750** to contain an index to a G-node Table **330** on another server **132**, in which case, the file handle **1300** would include the ServerID of the server **132** holding the file and its G-node **600**. (This possibility is indicated by the dotted arrow **1460** pointing from the G-node Ptr field **750** to another server **132** of the DFSS **100**.) Thus, the information in the G-node Ptr field **750** allows the server **130** to provide the client **110** with both a ServerID **1320** and with the G-node Index **1330** needed to create the file handle **1300** for the desired file. The file handle **1300** for the desired file can be sent back to the client **110** for use in future access of the desired file, and the process of file handle look-up is complete.

[0324] **FIG. 14B** shows one example of a file access operation, illustrated using the same context as was used in **FIG. 14A**. Here, the client **110** already has a file handle **1301** for the desired file, so an access request **1411** can be sent directly to the file system **250**. As previously disclosed, the user on the client **110** has no need to be aware of the specific server node **150** that will be accessed. This information is embedded in the desired file's file handle **1301**.

[0325] The server **130**, indicated in a ServerID field **1321**, accesses the G-node **1448** at index "9" as indicated in a G-node index field **1331** of the file handle **1301**.

[0326] As disclosed above, the Gee Table **320** holds information about the physical storage locations of a file's data and parity blocks on the disk array **140**. The Gee Table **320** also holds information that helps locate blocks of data that have been copied to cache. A Gee holds storage location information about one block of data. Gees for a given file are linked together to form the gee-string **500**. A first Gee of the gee-string **500** is called the root of the gee-string **500**.

[0327] The Gee Index-Root field **636** of the G-node **1448** provides an index to a root Gee **1450** in the Gee Table **320**. Reading the data field **591** of the Gee **1450** confirms that this Gee is a root Gee and that it is associated with the G-node **1448** at index location "9." The server **130** continues reading the gee-string at the next contiguous Gee **1452** in the Gee Table **320**. Reading the G-code **590** of the Gee **1452** with its value of "CACHE DATA" reveals that this Gee represents data that has been cached.

[0328] As disclosed above, the Cache Node Table **350** holds information that allows the server **130** to access a file block's location in cache **1456**. Reading the Data Field **591** of a next Gee **1452** provides a pointer to an appropriate cache node **1454** of the Cache Node Table **350**. The cache node **1454** holds the CacheBlockAddr field **825** which points to a location **1458** in cache **1456** of the data associated with the Gee **1452**. The cache node **1454** also holds a copy of the associated Gee **1452** from the Gee Table **320** in the Data Gee field **810** until the associated data block **1458** is no longer stored in cache. The Data Gee field **810** also provides a pointer to the location of the associated file data stored on the server node's disk array **140**. By following the pointers from the file handle **1301** to the G-node **1448** at index location "9", on to the Gees **1450** and **1452** at index locations "2" and "3," on to the Cache Node **1454** at index location "7," and finally on to cache location "w"**1458**, the data originally requested by the client **110** can be accessed for reading, writing, or other operations, and the process of file access is complete.

[0329] FIGS. **15-17** present a set of interrelated flow charts that illustrate the process of file access, including file handle look-up, if necessary.

[0330] Referring to **FIG. 15, a** process **1500** of accessing a file is described, beginning with the request for a file handle look-up, through the use of the file system's metadata structures, to final access of the file data in cache.

[0331] Beginning at a start state **1505**, the process **1500** moves to a state **1510** where the client **110** determines whether it has the file handle **1300** for a file that it wishes to access.

[0332] If the client **110** does not have the desired file handle **1300**, the process **1500** moves to a state **1515**, where the client **110** and one or more servers of the DFSS **100** perform a file handle look-up, as will be described in greater detail with reference to **FIG. 16**.

[0333] Returning to the state **1510**, if the client **110** determines that it does have the desired file handle **1300**, then the process **1500** moves on to a state **1520** where the client **110** sends the file access request **1411** to the server **130** indicated in the file handle **1300**.

[0334] From state **1520**, the process **1500** moves to a state **1525** where the server **130** accesses a G-node **600** indicated in the file handle **1300**.

[0335] Moving on to a state **1530**, the server **130** uses a pointer in the G-node **600** to access an appropriate Gee in the Gee Table **320**. Several possibilities exist for appropriate gees, depending on the current access needs of the server **130**. For example, in the embodiment of the G-node **600** described in **FIG. 6**, seven fields **630-636** relate to pointers to the Gee Table **320**. The Gee Index—Root field **636** is an index to the root Gee, which can be used, for example, when reading from the beginning of a file is desired. Fields **634** and **635** together point to the last Gee of a file, which can be used, for example, when appending new data to the end of a file. Fields **630** and **631** together point to a most recently used Gee for the file, which can be used, for example, for sequential access to the gees of a file. Fields **632** and **633** together point to a middle Gee for the gee-string **500** which can be used, for example, when access to the middle, or second half, of the file is desired.

[0336] After accessing an appropriate Gee in the state **1530**, the process **1500** moves on to a state **1535** where the server **130** reads the G-code field **590** in order to determine if the data represented by the Gee has already been cached. If the G-code **590** holds a value other than "CACHE DATA" or "CACHE PARITY," the server **130** assumes that the desired data has not yet been cached, and the process **1500** moves to a state **1540** where the desired data is sent to cache. The state **1540** is described in greater detail in connection with **FIG. 17** below.

[0337] Returning to the state **1535**, if the server **130** determines that the G-code **590** holds a value of "CACHE DATA" or "CACHE PARITY," the server **130** assumes that the desired data has already been cached. The process **1500** then moves on to a state **1545** where the server **130** accesses the cache node **800** indicated in the gee's data field **591**.

[0338] From the state **1545**, the process **1500** moves on to a state **1550** where the server **130** manipulates the accessed cache node **800** as needed according to the description of **FIG. 8B**. For example, if the cache node **800** is currently on the Normal List **860**, and the client **110** has requested to read the data block, the server **130** can increment the cache node's ReadCt field **830** and move it to the Read List **870**.

[0339] Once the Cache Node **800** is properly updated, the process **1500** moves from the state **1550** to a state **1555** where the server **130** accesses the file block data in the cache location indicated in the Cache Node **800**. From here, the process **1500** moves on to a state **1560** where the server **130** performs a desired operation on the cached data block. From the state **1560**, the process **1500** moves on to a state **1570** where accessing the file is complete.

[0340] In **FIG. 15**, the process **1500** reaches the state **1515** only if the client **110** does not have a file handle **1300** for the desired file. Referring to the embodiment of the file handle **1300** illustrated in **FIG. 13**, the file handle **1300** for a given file comprises, among other possible fields, a ServerID field **1320** identifying the server **130** that stores the data and metadata for a file, as well as a G-node Index field **1330** that indicates the G-node **600** of the given file on that identified server **130**.

[0341] **FIG. 16** is a flow chart that describes in more detail how the process of the state **1515** carries out a file handle look-up. The look-up process **1515** begins with a look-up request that comprises the file handle **1300** for a directory on the pathname of the desired file and continues on through each component of the pathname, retrieving a file handle for each, until a file handle for the desired file itself is returned to the client **110**.

[0342] The "root" directory is the first component of the pathname for every file in the file system, and, if necessary, the client **110** can begin the process of file handle look-up **1515** with the file handle of the "root" directory. In one embodiment, every client has at least the file handle **1300** for a "root" directory for the file system **250**. For example, the "root" directory can be known to reside on the server **130** with ServerID number 0, and its G-node **600** can be known to reside at index 0 of the G-node Table **330** on Server 0. However, it may also be that at the beginning of the look-up process **1515**, the client **110** has the file handle **1300** for the desired file's parent directory or for another directory on the pathname of the file, and that by beginning with one of these directories "closer" to the file itself, the look-up process may be shortened.

[0343] Beginning at a start state **1605**, the process **1515** moves to a state **1610** where the client **110** sends the look-up request **1410** comprising the file handle **1300** for a directory and the filename **1420** of a desired next component. The look-up request **1410** is sent to a server **1300** indicated in the file handle **1300** field of the look-up request **1410**. The process **1515** next moves to a state **1615**, where the server **130** accesses a G-node **600** indicated in the file handle **1300** of the look-up request **1410**.

[0344] Moving on to a state **1620**, the server **130** uses the ChildGnidIndex field **628** in the G-node **600** to access a first Gnid **710** in the directory's Gnid-string **700**. As described in connection with the embodiment shown in **FIG. 7**, the Gnid-string **700** is a linked list of Gnids **710**, with one Gnid **710** for each child file in a parent directory.

[0345] Moving on to a state **1625**, the server **130** calculates a checksum and filename length for the filename **1420** of the next desired pathname component that was sent by the client **110** in the look-up request **1410**. Having a checksum and filename length for a desired file allows the server **130** to expedite searching for a matching Filename Entry because comparison of checksums and comparison of filename lengths can be accomplished much more quickly than a character-by-character comparison of the filenames them-

selves. Performing the first two types of comparisons before embarking on the character-by-character comparison allows the server **130** to eliminate any Filename Entries whose checksum and filename length do not match, before performing the more costly character-by-character filename comparison.

[**0346**] Moving on to a state **1630**, the server **130** uses the FilenamePtr field **760** of the currently accessed Gnid **710** to locate the associated Filename Entry **410** in the Filename Table **310**. Moving on to a state **1635**, the server **130** determines if the checksum **412** stored in the currently accessed Filename Entry **410** is greater than the checksum calculated in the state **1625**.

[**0347**] As described in connection with **FIG. 7**, in one embodiment, Gnids **710** are stored in the Gnid-string **700** in order of checksum **412** values calculated for their associated character strings **414**, with the Gnid **710** having the smallest checksum **412** value coming first. This ordering of Gnids **710** by checksum **412** value allows the server **130** to determine whether a desired filename may still exist on the given Gnid-string **700**. In this embodiment, if, in the state **1635**, the server **130** determines that the checksum **412** found in the currently accessed Filename Entry **410** is greater than the checksum calculated in the state **1625**, then a Gnid **710** for the desired file (with the lower checksum) cannot exist on the currently accessed Gnid-string **700**. In this case, the process **1515** moves on to a state **1640**, where it reports a File-Not-Found Error to the client **110**.

[**0348**] Returning to the state **1635**, if the server **130** determines that a checksum found in a currently accessed Filename Entry is greater than the checksum calculated in state **1625**, then the process **1515** moves on to a state **1645**.

[**0349**] In the state **1645**, the server **130** determines if the checksums and the filename lengths from the two sources match. If either the checksums or the filename lengths (or both) do not match, then this Filename Entry can be ascertained not to be associated with the client's desired file, and the process **1515** moves on to a state **1660**. In the state **1660**, the server **130** uses the SiblingGnidPtr **740** in the current Gnid **710** to access the next Gnid in the current Gnid-string.

[**0350**] Returning to the state **1645**, if the server **130** determines that the checksums and filename lengths do match, then this Filename Entry **410** cannot yet be eliminated, and the process **1645** moves on to a state **1650**, where the server **130** performs a character-by-character comparison of the two filenames.

[**0351**] If, in the state **1650**, the server **130** determines that the two filenames do not match, then, as was the case in state **1645**, this Filename Entry can be ascertained not to be associated with the client's desired file. In this case, the process **1515** moves on to a state **1660**, where the server **130** uses a SiblingGnidPtr **740** in the current Gnid to access a next Gnid **711** in the current Gnid-string **700**.

[**0352**] From the state **1660**, the process **1515** returns to the state **1630**, and the server **130** uses the Filename Ptr field **760** of the newly accessed Gnid **711** to access an associated Filename Entry in the File Table **310**. This loop through the states **1630**, **1635**, **1645**, **1660** (and possibly **1650**) continues until a Filename Entry and associated Gnid for the desired file is found or until an error is encountered.

[**0353**] If, in the state **1650**, the server **130** determines that the filenames do match, then the process **1515** has identified a Filename Entry and an associated Gnid that corresponds to the desired file. In this case, the process **1515** moves on to a state **1655**, where the server **130** sends the desired file handle **1300** information back to the client **110**. Moving on to a state **1665**, the file handle look-up process **1515** is complete. The process **1500** from **FIG. 15** then proceeds from the state **1515** back to the state **1510** and continues as described in the explanation of **FIG. 15**.

[**0354**] **FIG. 17** presents a more detailed description of the state **1540** from **FIG. 15**, in which uncached data that has been requested for access by the client **110** is copied into cache memory. The process **1540** of caching file data begins in a start state **1705** and proceeds from there to a state **1710**, where the server **130** identifies the least recently used cache node **880**. In one embodiment of the file system **250**, when the three-list scheme described in **FIG. 8B** is used, the server **130** can easily identify the least recently used cache node **880** because it is a "last" cache node on the Normal List **860** of the scheme.

[**0355**] Moving on to a state **1720**, the server **130** writes the associated file data from its volatile location in cache to its non-volatile location on disk array **140**, which is indicated in the DataGee field **810** of the cache node **800**.

[**0356**] Moving on to a state **1730**, the server **130** copies the DataGee field **810** from the cache node **800** back to its original position in the Gee Table **320**, changing the G-code **590** back from "CACHE DATA" to "DATA" or from "CACHE PARITY" to "PARITY," indicating that the associated data is no longer cached.

[**0357**] Moving on to a state **1740**, the server **130** overwrites the DataGee field **810** in the cache node **800** with a Gee from the Gee Table **320** that is associated with a new file block to be cached.

[**0358**] Moving on to a state **1750**, the server **130** caches the new file block from disk to a cache location associated with the cache node.

[**0359**] Moving on to a state **1760**, the process **1540** of caching file data is complete, and the process **1500** in **FIG. 15** can proceed from the state **1540** on to the state **1545** to continue the task of accessing a file.

[**0360**] Referring to **FIG. 18, a** process of file allocation **1800** is shown in flowchart form. The process **1800** begins in a start state **1805** and moves to a state **1810** where the client **110** send a file allocation request that includes a filename for a new file and a file handle for the new file's parent directory.

[**0361**] The process **1800** moves to the state **1815**, and the server node **150** indicated in the parent directory's file handle receives the file allocation request. For the purposes of the description of this figure, this server node **150** will be known as the "parent" server.

[**0362**] The process **1800** moves to the state **1820**, and the "parent" server **150** uses workload statistics received from the other server nodes of the DFSS **100** to decide if the file will be "owned" by the "parent" server node **150** or by another server node.

[0363] If the "parent" server node **150** decides that it will be the owner of the new file, then the process **1800** moves to a state **1830**, where the "parent" server creates a new file, makes an appropriate new Filename Entry **410** in the Filename Table **310**, and allocates a new G-node **600** for the new file. At this point, the "parent" server node **150** has enough information to create the file handle **1300** for the new file.

[0364] Returning to the state **1820**, if the "parent" server node **150** decides that another server node should own the new file, the process **1800** moves to a state **1850**, where the "parent" server **150** sends a file allocation request to another server of the DFSS **100**. For the purposes of describing this figure, the other server will be known as the "second" server.

[0365] From the state **1850**, the process **1800** moves to a state **1855** where the "second" server creates a new file, makes the appropriate new Filename Entry **410** in the Filename Table **310**, and allocates the new G-node **600** for the new file. At this point, the "second" server has enough information to create the file handle **1300** for the new file.

[0366] From the state **1855**, the process **1800** moves on to a state **1860**, where the "second" server sends the file handle **1300** for the new file to the "parent" server node **150**.

[0367] At this point, when the "parent" server node **150** has the file handle **1300** for the new file, the process **1800** moves on to a state **1835**.

[0368] The state **1835** can also be reached from state **1830** in the case where the "parent" server **150** decided to be the owner of the file. As disclosed above, in state **1830** the "parent" server **150** also had the information to create a file handle **1300** for the new file, and the process **1800** also moves on to a state **1835**.

[0369] For either case, in state **1835**, the "parent" server node **150**, as owner of the new file's parent directory, allocates a Gnid **710** for the new file, adds it to the appropriate Gnid-string **700**, and, if one does not already exist, the "parent" server node **150** makes an appropriate new Filename Entry **410** in the Filename Table **310**.

[0370] From state **1835**, the process **1800** moves on to a state **1840**, where the "parent" server node **150** sends the file handle **1300** for the new file to the requesting client **110**.

[0371] The process **1800** moves on to a state **1845** where the process of file allocation is now complete. The requesting client **110** can access the new file using the newly received file handle **1300**, and since the file handle **1300** contains identification for the server that owns the new file, any access request can be automatically routed to the appropriate server node.

[0372] Redirectors

[0373] In various embodiments, the DFSS **100** can be configured to store and manage a very large number of files of widely varying sizes. In some embodiments, it can be advantageous to store all of the file metadata on disk, while copies of the metadata for only some of the most recently used files are additionally cached in volatile memory. In some embodiments, memory for metadata structures can be dynamically allocated as new metadata structures are brought from disk to volatile memory.

[0374] **FIG. 19** depicts one embodiment of a scheme to allow for efficient access to file metadata when not all metadata is kept in volatile memory. In the embodiment shown in **FIG. 19, a** G-node Redirector (GNR) array **1900** in volatile memory holds a G-node Redirector (GNR) **1910** per file. The G-node Redirector (GNR) is a small data structure that comprises information for locating the G-node **600** of a desired file, including information regarding whether the file's G-node **600** is currently in cache **1920**. In the embodiment shown in **FIG. 19, a** client **110** requesting access to a given file sends a file handle **1300** that includes an index for the desired G-node Redirector (GNR) **1910** in the G-node Redirector (GNR) array **1900**, which references the G-node **600** of the desired file. In one embodiment, when a desired G-node **600** is not currently cached, a least recently used G-node **600** in cache **1920** can be removed from cache **1920**, and a copy of the desired G-node **600** can be brought from the disk array to the cache **1920**.

[0375] Super G-nodes

[0376] In one embodiment, the file system **250** can be advantageously configured to store file metadata in a data structure called a Super G-node (SG) that comprises the file's G-node, other file information, and information that allows the file system **250** to locate the physical storage locations of the file's data blocks, as will be described in greater detail below.

[0377] **FIG. 20A** shows one embodiment of a Super G-node **2000** structure of fixed size that can provide location information for files of a wide variety of sizes. As shown in **FIG. 20A, a** Status field **2010** in the Super G-node **2000** can be used to indicate a type of Super G-node that corresponds to a category of associated file sizes, as will be described in greater detail with reference to **FIG. 20B**. A Linking Information field **2020** can be used to interconnect Super G-nodes **2000** into one or more linked lists or other structures. A G-node field **2030** comprises attribute and other information about a corresponding file that is similar to the information stored in the G-node **600** embodiment described with reference to **FIG. 6**. A File Location Data field **2040** in the Super G-node **2000** allows the file system **250** to locate a file's data, as will be described in greater detail below.

[0378] In the embodiment shown in **FIG. 20**A, the Super G-node **2000** comprises **16** Kbytes of memory. The Status **2010**, Linking Information **2020**, and G-node **2030** fields together comprise **128** Bytes of the Super G-node **2000**, and the remainder of the Super G-node can be used to store the File Location Data **2040**.

[0379] **FIG. 20B** depicts one embodiment of a scheme that uses Super G-nodes **2000** of a fixed size to hold information about files of widely differing sizes. In the embodiment shown in **FIG. 20**A, four types **2001**-**2004** of Super G-node **2000** are depicted.

[0380] A Super G-node **2000** of type Super G-node Data (SGD) **2001** can be used for a file that is small enough that its data **2005** can fit entirely within the File Location Data **2040** field of the SGD **2001**. For the embodiment described with reference to **FIG. 20A, a** small file refers to a file that is 16,256 Bytes, or smaller. When a file's Super G-node **2000** is of type SGD **2001**, locating the file's data simply means reading it from the File Location Data **2040** field of the SGD **2001**.

[0381] In the embodiment shown in **FIG. 20B, a** Super G-node **2000** of type Super G-node Gee (SGG) **2002** can be used for medium files, that is, files of sizes up to approximately 700 MegaBytes of data that are too large to fit into an SGD **2001**. In an SGG **2002**, the File Location Data **2040** field is used to hold a Gee String Packet (GSP) **2007** that comprises information very similar to that of the Gee-String **500** described with reference to **FIG. 5**. As with the Gee-String **500**, the Gee String Packet **2007** comprises Gees **2006** that point to the physical locations of the file's data **2005**.

[0382] A Super G-node **2000** of type Super G-node List (SGL) **2003** can be used for large files whose Gee-String **500** is too large to be described by a Gee String Packet **2007** that fits within the SGL's **2003** File Location Data **2040** field. Instead, the SGL's **2003** File Location Data **2040** field is used to hold a Gee String Packet Block (GSPB) **2008**, which is a list of pointers to a plurality of Gee String Packets **2007** that together describe the Gees **2006** that point to the locations of the file's data **2005**. In one embodiment, an SGL **2003** can reference files of sizes up to approximately **490** GigaBytes.

[0383] A Super G-node **2000** of type Super G-node List of Lists (SGLL) **2004** can be used for very large files. Here, the File Location Data **2040** field of the SGLL **2004** comprises a Gee String Packet List Block **2009** that comprises pointers to a plurality of Gee String Packet Blocks **2008** that point to a plurality of Gee String Packets **2007** that points to a plurality of Gees **2006** that point to a plurality of storage locations that hold the desired data **2005**.

[0384] In one embodiment, Gee String Packet List Blocks **2009**, Gee String Packet Blocks **2008**, and Gee String Packets **2007** are implemented in structures that are equivalent in size and organization to the Super G-node **2000** described with reference to **FIG. 20A**, except that the G-node field **2030** is not used.

[0385] Parity Groups

[0386] The foregoing description of a distributed file storage system addresses the need for a fault tolerant storage system with improved reliability and scalability characteristics. This system features a flexible disk array architecture that accommodates the integration of variably sized disk drives into the disk array and provides mechanisms to permit each drive's capacity to be more fully utilized than prior art systems. In one embodiment, variably sized data and parity blocks are distributed across the available space of the disk array. Furthermore, the system provides methods of redistributing data across the disk array to improve data storage and retrieval, as well as, provide for improved fault-tolerance. Another benefit of the data redistribution characteristics of the system is that it continues to provide fault-tolerant data access in situations where many drives of the disk array have failed. This feature is a notable improvement over conventional RAID systems that typically only provide fault-tolerance for single (or at most two) drive failures.

[0387] **FIG. 22A** shows a file storage system **100** having the server node **150** that operates within a computer network architecture to provide data and file storage. The computer network comprises one or more clients **110** that exchange information with the server node **150** through the communications medium or fabric **120** to store and retrieve desired data from the server node **150**. In one aspect, the clients **110** include one or more computing devices that exchange information with the server node **150** through the communications medium **120**.

[0388] The communications medium **120** can be any of a number of different networking architectures including, for example, Local Area Networks (LAN), Wide Area Networks (WAN), and wireless networks which may operate using Ethernet, Fibre Channel, Asynchronous Transfer Mode (ATM), and Token Ring, etc. Furthermore, any of a number of different protocols can be used within the communications medium **120** to provide networking connectivity and information exchange capabilities between the clients **110** and the server node **150**, including, for example, TCP/IP protocols, Bluetooth protocols, wireless local area networking protocols (WLAN), or other suitable communications protocols.

[0389] The server node **150** includes the server **130** that serves as a front end to the disk array **140**. The server **130** receives information and requests from the clients **110** and processes these requests to store and retrieve information from the disk array **140**. In one aspect, the server **130** maintains at least a portion of an instruction set or file system that determines how data and information are stored and retrieved from the disk array **140**.

[0390] Although the server node **150** is illustrated as a single entity in **FIG. 22A**, it will be appreciated that many server nodes **150** can be connected to the communications medium **120**. Thus, a plurality of server nodes **150** can be connected to the communications medium **120** and accessible to the clients **110** for the purposes of information storage and retrieval. Furthermore, the server nodes **150** can operate independently of one another or be configured to transparently present a single disk image to each client **110** thus creating a unified storage area that facilitates end user interaction with the server nodes **150**. In one aspect, the server nodes **150** incorporate functionality for maintaining the single disk image through the use of the file system present in each of the servers **130** which provides communication and organization to create the single disk image.

[0391] **FIG. 22B** illustrates another embodiment of a file storage system comprising a distributed file storage system architecture. In this embodiment, two or more server nodes **150, 151** are physically or logically interconnected to form the cluster **160**. File data stored on any server node is accessible to any other server in the cluster **160**. The cluster **160** may also provide metadata and transaction mirroring. Furthermore, stored files may be replicated across at least two server nodes **150, 151** within the distributed file storage system **100** to provide increased redundancy or data mirroring capabilities.

[0392] One advantage achieved by the aforementioned distributed configurations is that they may provide increased data protection and/or fault tolerance. For example, if the replicated server node **150** fails or becomes unavailable, the second replicated server node **151** can handle client requests without service interruption. Another advantage achieved by using this interconnected arrangement is that alternative server node access paths **165** can be created where identical data can be read simultaneously from the two or more interconnected server nodes **150, 151**. Thus, if one server node **150** in the cluster is busy and unavailable, another redundant server node **151** can service client requests to

increase data throughput and accessibility. As with the single server node configuration, a plurality of clusters **160** may be present and accessible to the clients **110**. Similarly, the clusters **160** can be configured to present a single disk image to the clients **110** to facilitate interaction by the end users of the distributed file storage system **100**.

[**0393**] As shown in **FIG. 22**B, each disk array **140**, **141** in the server nodes **150**, **151** can include a variable number of disks where each server node **150**, **151** has a different disk array configuration. Each disk within the disk array **140**, **141** can have a different storage capacity. These features of the distributed file storage system **100** contribute to improved flexibility and scalability in configuring the server nodes **150**, **151**.

[**0394**] The variable disk configuration of the distributed file storage system **100** overcomes a limitation present in many conventional storage systems which require that upgrades to the storage system be performed in a coordinated manner where all disks in each disk array **140**, **141** are replaced in unison. Additionally, many conventional storage systems, including RAID architectures, require strict conformity amongst the disk arrays within the system, as well as, conformity in disk capacity within individual disk arrays. The distributed file storage system **100** of the present invention is not limited by the restriction of uniform disk upgrades or conformity in disk capacity and can accommodate replacement or upgrades of one or more drives within each server node with drives of differing capacity. To maintain data integrity and knowledge of available storage space within the distributed file storage system **100**, one of the functions of the aforementioned file system present in the servers **130**, **131** is to accommodate differences in disk array capacity and disk number between the server nodes.

[**0395**] **FIG. 23** illustrates the use of a distributed file storage mechanism within the disk array **140** to improve space utilization and flexibility of data placement. A space mapping configuration **2300** is illustrated for the disk array **140** where each disk **2305** is subdivided into a plurality of logical blocks or clusters **2310**. For the purposes of this illustration the cluster size is shown to be fixed across all disks **2305** of the array **140**, although, as will be illustrated in greater detail in subsequent figures, the cluster size can be variable within each disk **2305** and across disks **2305** within the array **140**.

[**0396**] A first file **2320** having data to be stored on the disk array **140** is subdivided into one or more data blocks. The determination of the data block size, number, and distribution is calculated by the file system as data storage requests are received from the clients **110**. Each data block **2330** is mapped or assigned to a location within the disk array **140** that corresponds to the particular disk **2305** and logical block **2310** within the disk **2305**. Unlike conventional disk arrays, the block size used for data storage is variable from one block to the next within the file.

[**0397**] The server **130** organizes and distributes information to the disk array **140** by dividing a file into one or more data blocks **2330** that are distributed between one or more parity groups **2335**. Each parity group **2335** includes a discrete number of data blocks **2330** and further includes a parity block **2337** containing parity information calculated for the data blocks **2330** contained within the particular parity group **2335**. Unlike conventional systems, the size of the data blocks **2330** and parity blocks **2337** is not singularly fixed throughout the disk array **140**. The collection of data blocks **2330** and parity blocks **2337** can include a number of different sizes and configurations resulting in more flexible storage of data within the disk array **140**.

[**0398**] Using File #1 in **FIG. 23** as an example, the information contained in the file is distributed in 7 data blocks corresponding to $DATA_1$1-$DATA_1$7. Each data block, $DATA_1$1-$DATA_1$7 is distributed between 3 parity groups wherein the first parity group contains $DATA_1$1-$DATA_1$2 the second parity group contains $DATA_1$3-$DATA_1$4 and the third parity group contains $DATA_1$5-$DATA_1$7. Furthermore, 3 parity blocks $PARITY_1$1-2, $PARITY_1$3-4, and $PARITY_1$5-7 are formed, one for each parity group.

[**0399**] The parity groups **2335** are determined by the server **130** which assesses the incoming data to be stored in the disk array **140** and determines how the data is distributed into discrete data blocks **2330** and furthermore how the data blocks **2330** are distributed into parity groups **2335**. After determining the data block and parity group distribution, the server **140** calculates the parity information for the data blocks **2330** in each parity group **2335** and associates the parity block **2337** containing this information with the appropriate parity group **2335**.

[**0400**] The server **130** then determines how the information for each parity group **2335** is stored within the disk array **140**. Each data block **2330** and parity block **2337** is distributed within the disk array **140** in an arrangement where no blocks **2330**, **2337** originating from the same parity group **2335** are stored on the same disk of the disk array **140**. The non-overlapping storage of data blocks **2330** and parity blocks **2337** derived from the same parity group **2335** creates the fault-tolerant data storage arrangement where any block **2330**, **2337** within a parity group **2335** can be reconstructed using the information contained in the other remaining blocks of the parity group **2335**. This arrangement where blocks **2330**, **2337** associated with the same parity group **2335** are not be stored on the same disk **140** is important in case of a disk failure within the array **140** to insure that that lost data can be reconstructed. Otherwise, if two or more blocks associated with the same parity group **2335** are stored on the same drive, then in the event of a disk failure, data recovery can not be assured.

[**0401**] An example distribution of data blocks **2330** and parity blocks **2337** within the disk array **140** is shown in **FIG. 23**. The 7 data blocks and 3 parity blocks corresponding to the File #1 are distributed along disk numbers 0,1,8,3,7,2 and 2110 respectively. In a similar manner, a second file **2340** is divided into 4 data blocks (and 2 parity groups) that are distributed along disk numbers 0,2,4, and 5 respectively. The size, order, and placement of the data blocks is predetermined by the server **130** which assigns regions of each disk **2305**, corresponding to particular logical blocks, to store data blocks of designated sizes. The parity blocks **2337** of the parity groups **2335** associated with the first file **2320** are further stored on disks 9,6,11 with the parity blocks **2337** of the second file **2340** stored on disks 3, 9.

[**0402**] The data blocks **2330** and the parity blocks **2337** need not be sequentially stored but rather can be distributed throughout the disk array **140**. Using this arrangement, the distributed file storage system **100** permits the non-sequen-

tial assignment and storage of parity group information in a flexible manner that is not limited by a rigid order or placement schema. Flexible block placement in the aforementioned manner improves disk utilization within the disk array **140** and provides for accommodating variable disk capacities as will be shown in greater detail in subsequent figures.

[**0403**] **FIG. 24A** illustrates a process **2400** for the storage of data and parity information within the distributed file storage system **100**. The process **2400** commences with a data storage request **2410** issued by the client **110** to the server node **150**. During this time the client **110** sends or transmits data **2415** to the server node **150** which receives and prepares the data **2420** for subsequent processing and storage. In one embodiment, the server node **150** includes hardware and/or software functionality to perform operations such as error checking, data buffering, and re-transmission requests, as needed, to insure that the data **2415** is received by the server **130** in an uncorrupted manner. Furthermore, the server node **150** is able to process simultaneous requests from a plurality of clients **110** to improve performance and alleviate bandwidth limitations in storage and retrieval operations. In one aspect, the data **2415** is transmitted through the communications fabric **120** in the form of a plurality of data packets that are automatically processed by the server node **150** to generate the data **2415** that is to be desirably stored within the disk array **140**.

[**0404**] Upon receiving the data **2420**, the server **130** analyzes the characteristics of the data **2430** to determine how the data **2415** will be distributed into one or more data blocks **2330**. In one aspect, the data analysis **2430** includes identifying the content or type of data that has been sent, such as, for example, multimedia data, textual data, or other data types. Using one or more of the plurality of available disk blocks sizes, the server **130** identifies desirable block sizes and distribution mappings that are used to group the data **2415** and organize it into the data blocks **2330**.

[**0405**] The data **2415** is then parsed into blocks **2440** according to the data analysis **2430** and the resulting blocks are further arranged into one or more parity groups **2450**. The parity group arrangement determination **2450** distributes the data blocks **2330** between the parity groups **2335** and dictates the size of the parity blocks **2337** that will be associated with each parity group **2335**. For example, a parity group composed of 3 data blocks having sizes of 128K, 64K, and 256K respectively will have a different associated parity block size than and parity group composed of 2 data blocks having sizes of 128K and 256K. The server **130** can therefore vary the block size as well as the parity group size in a number of different ways to achieve improved storage and distribution characteristics within the disk array **140**.

[**0406**] In one aspect, the distributed file storage system **100** is an improvement over conventional systems by allowing both data and parity blocks to be assigned to physical disk blocks. Furthermore, the mapping of the data and parity blocks to the physical disk(s) may be performed either before or after the parity calculations thus improving storage flexibility.

[**0407**] Upon determining the parity group arrangement **2450**, the server **130** calculates the parity blocks **2460** for each parity group **2335**. As previously described, the parity block calculation **2450** creates a fault-tolerant information block which is associated with each group of data blocks **2330** within the parity group **2335**. The parity block is calculated **2460** by selecting all data blocks **2330** in a parity group **2335** and performing a logical operation on the data **2415** contained therein to compute error correction information. In one embodiment, the error-correction information is determined using the logical operation, exclusive OR to generate the parity information. Using this error-correcting information the parity block **2337** can be used to restore the information contained in a particular data block **2330** or parity group **2335** that may become corrupted. Furthermore, the parity information can be used to restore the contents of entire disks **2305** within the disk array using the error correction information in conjunction with other non-corrupted data.

[**0408**] When the parity groups **2335** have been formed, the server **130** then determines how the data blocks **2330** and parity block **2337** for each parity group **2335** will be distributed **2470** in the disk array. Although, the data **2415** can be striped sequentially across the disks **2305** of the disk array **140**, it is typically more efficient to map and distribute the blocks **2335**, **2337** throughout the disk array **140** in a non-sequential manner (See **FIG. 23**). Mapping the data blocks **2330** in this manner requires knowledge of how the data blocks **2330** are positioned and ordered within the disk array **140**. Detailed knowledge of the mapping for each data block **2330** is maintained by the server **130** using a file storage mapping structure. This structure will be discussed below in connection with **FIGS. 7 and 9**. Using the mapping schema determined by the server **130**, the blocks **2330**, **2337** of each parity group **2335** are stored **2480** in the disk array **140**.

[**0409**] As previously indicated, the distributed file storage system **100** employs a variable parity approach where the size of the parity block **2337** is not necessarily constant. The server **130** creates parity blocks **2337** by selecting one of more data blocks **2330** for which error correction information will be computed. The size of the parity block **2337** is dependent upon the number of data blocks **2330** whose error correction information is computed and is determined by the server **130**. In one aspect, the server **130** selects a parity block size that is convenient and efficient to store within the existing space of the disk array **140**. The server **130** also provides for distributed placement of the parity blocks **2337** in a manner similar to that of the data blocks **2330**. Thus, both data blocks **2330** and parity blocks **2337** are desirably mapped throughout the disk array **140** with the server **130** maintaining a record of the mapping.

[**0410**] The server **130** insures that both data blocks **2330** and parity blocks **2337** are appropriately positioned within the disk array **140** to insure some level of fault tolerance. Therefore, the server **130** desirably distributes selected data blocks and parity blocks containing error correction information for the selected data blocks on non-overlapping disks (e.g. all blocks of a parity group are on separate disks). This insures that if a disk failure does occur, that the corrupted information can be recovered using the remaining data/parity information for each parity group. Upon calculating the appropriate parity information and distribution mapping **2470**, the parity blocks **2337** are stored in the disk array **2480** in a manner designated by the server **130**.

[0411] **FIG. 24B** illustrates another embodiment of a process **2405** for the storage of data and parity information within the distributed file storage system **100**. As with the aforementioned data and parity information storage method **2400**, the process begins with the data storage request **2410** issued by the client **110** to the server node **150**. Subsequently, an analysis of the characteristics of the data **2430** is performed to determine how the data **2415** will be distributed into the one or more data blocks **2330**. The data **2415** is then parsed into blocks **2440** according to the data analysis **2430** and the resulting blocks are further arranged into one or more parity groups **2450**. The server **130** then determines how the data blocks **2330** and parity block **2337** for each parity group **2335** will be distributed **2470** in the disk array. At this point the client **110** sends or transmits data **2415** to the server node **150**, which receives and prepares the data **2420** for subsequent processing and storage. After receiving the data **2420**, the server **130** calculates the parity blocks **2460** for each parity group **2335**. Once the data blocks **2330** and parity blocks **2337** have been obtained they are stored in the disk array **2480** in a manner similar to that described with reference to **FIG. 24A** above.

[0412] In either method of data and parity information storage **2400**, **2405**, the transfer of information from the client **110** may comprise both a parametric component and a data component. The parametric component defines a number of parameters used in the storage of information to the disk array **2480** and may include for example: operation definitions, file handles, offsets, and data lengths. When using the aforementioned storage methods **2400**, **2405** the parameters and data need not necessarily be transferred at the same time. For example, the parameters may be transferred during the client storage request **2410** and the data may be transferred anytime thereafter in a subsequent stage of the method **2400**, **2405**. In one aspect, transfer of information using the parametric and data components desirably allows the distributed file storage system **100** to make decisions about how to process the incoming data prior to the actual data transfer to thereby improve the flexibility and functionality of the system.

[0413] **FIG. 25** illustrates another embodiment of the distributed file storage system **100** using a variable capacity disk array. The variable capacity disk array incorporates a plurality of disks **2305** with potentially non-identical sizes whose space can be addressed and used for storing data blocks **2330** and parity blocks **2337**. Unlike conventional RAID storage systems that are limited by the capacity of the smallest drive within the disk array, the variable capacity disk array can contain any number or combination of disks and is not limited to accessing an address space boundary **2490** denoted by the smallest drive in the array. Using similar methods as described previously in conjunction with **FIGS. 23 and 24**, the server **130** receives files **2320**, **2340** and determines a parity group distribution for each file such that a plurality of data blocks **2330** and parity blocks **2337** are created. The data blocks **2330** and parity blocks **2337** are then distributed throughout the disk array **140** in such a manner so as to avoid storing more than one block **2330**, **2337** from the same parity group **2335** on a single disk **2305**. The server **130** stores of these blocks **2330**, **2337** across all of the available disk space, and thus is able to access disk space that lies beyond the boundary **2490** defined by the smallest disk capacity (a typical storage boundary which limits conventional systems). As shown in **FIG. 25**, the distributed file storage system **100** stores both data blocks **2330** and parity blocks **2337** throughout the address space of each disk **2305** without boundary limitations imposed by other disks within the array **140**.

[0414] In addition to improved space utilization, a number of other important features arise from the aforementioned flexible distribution of the blocks **2330**, **2337**. In one aspect, using variable capacity disks **2305** within the array **140** contributes to improved scalability and upgradeability of the distributed file storage system **100**. For example, if the unused storage space within the array **140** fails below a desired level, one or more of the disks within the array **140** can be readily replaced by higher capacity disks. The distributed file storage system **100** implements an on-the-fly or "hot-swap" capability in which existing disks within the array **140** can be easily removed and replaced by other disks. Since each server in a cluster maintains a copy of the metadata for other servers in the cluster, servers can also be hot-swapped. Using this feature, a new higher capacity disk can be inserted into the array **140** in place of a lower capacity disk. The server **140** is designed to automatically incorporate the disk space of the newly inserted drive and can further restore data to the new drive that resided on the former smaller capacity drive. This feature of the distributed file storage system **100** provides for seamless integration of new disks into the array **140** and facilitates disk maintenance and upgrade requirements.

[0415] In addition to exchanging or swapping existing disks **2305** within the array **140**, the server **130** can accommodate the addition of new disks directly into the array **140**. For example, the disk array **140** containing the fixed number of disks **2305** can be upgraded to include one or more additional disks such that the total number of disk in the array is increased. The server **140** recognizes the additional disks and incorporates these disks into the addressable space of the distributed file storage system **100** to provide another way for upgrading each disk array **140**.

[0416] In the examples shown above, both the swapping of disks to increase storage space and the incorporation of additional disks into the array is facilitated by the flexible block placement and addressing of disk space within the array **140**. Unlike conventional systems that have a rigid architecture where the number of disks within each array is fixed and the addressable disk space is dictated by the smallest disk within the array, the distributed file storage system **100** accommodates many different disk array configurations. This flexibility is due, in part, to the manner in which the disk space is formatted, as well as, how the data is arranged and processed by the server **130**.

[0417] In one aspect, the flexibility of the distributed file storage system **100** is improved through the use of parity groups **2335**. In order to accommodate files with different characteristics, as well as, improve how information is distributed throughout the disk array **140**, parity groups **2335** are formed with variable block numbers. The block number of the parity group is defined by the number of blocks **2330**, **2337** within the group. For example, a parity group containing 4 data blocks is characterized as having a block number of 4. In a similar manner, a parity group containing a single data block is characterized as having a block number of 1. The block number of the parity group is

one factor that determines the size of the parity group and additionally determines the information that will be used to form the parity block.

[0418] **FIG. 26A** illustrates the formation of variable block number parity groups in the distributed file storage system **100**. In the illustrated embodiment, exemplary parity groups **2502**, **2504** are shown with different extents having 4 and 2 data blocks respectively. The server **130** determines the number of data blocks **2330** associated with each group **2502**,**2504** and furthermore determines the distribution of each type of parity group having specific block numbers that make up the total parity group distribution in the disk array **140**. This feature of the distributed file storage system **100** is discussed in connection with **FIGS. 29 and 34**.

[0419] Data organization and management by the server **130** is maintained using one or more data structures that contain information which identifies the size and ordering of the data blocks **2330** within each parity group **2502**, **2504**. In one embodiment, the ordering or sequence of the blocks **2330**, **2337** is maintained through a linked list organizational schema. The linked list contains one or more pointers that act as links **2505** between each block **2330**, **2337** within the parity group **2335**. The links **2505** therefore allow the server **130** to maintain knowledge of the order of the blocks **2330**, **2337** as they are distributed throughout the disk array **140**. As blocks are written to or read from the disk array **140**, the server **130** uses the links **2505** to identify the order of the blocks **2502**, **2504** used for each parity group **2335**.

[0420] As shown in **FIG. 26**B, the distributed file storage system **100** can also allocate parity groups **2335** on the basis of block size. In the illustrated embodiment, exemplary parity groups **2506**, **2508** are shown having the same block number of 4 with differing block sizes of 256K and 128K respectively. The feature of variable block size allocation within each parity group **2335** provides yet another way by which the server **130** can distribute data and information within the disk array **140** in a highly flexible and adaptable manner.

[0421] The implementation of parity groups having a plurality of different block numbers, as well as allowing for the use of different block sizes within each block, improves the ability of the server **130** to utilize available disk space within the array **140**. Furthermore, using combinations of different data block and parity group characteristics allows the server to select combinations that are best suited for particular data types.

[0422] For example, large data files such as multimedia video or sound are well suited for storage using large parity groups that contain large block sizes. On the other hand, smaller files such as short text files do not have the same space requirements as the larger file types and thus do not significantly benefit from storage in a similar block size. In fact, when small files are stored in large blocks, there is the potential for wasted space, as the smaller file does not use all of the space allocated to the block. Therefore, the distributed file storage system **100**, benefits from the ability to create data blocks **2330** and parity groups **2335** of variable sizes to accommodate different data types and permit their storage in a space-efficient manner.

[0423] As discussed in connection with FIGS. **14**, the distributed file storage system **1100** further improves the utilization of space within the disk array **140** by implementing a mechanism for reorganizing the allocation of data blocks as needed to accommodate data stored to the disk array **140**. Furthermore, a redistribution function (shown in **FIG. 36**) can alter the composition or distribution of blocks **2330**, **2337** or parity groups **2335** within the array **140** to make better use of available space and improve performance by reorganizing information previously written to the array **140**.

[0424] In order to maintain coherence in the data stored to the disk array **140**, knowledge of the size and ordering of each block within the parity group **2335** is maintained by the server **130**. Prior to writing of data to the disk array **140**, the server **130** creates a disk map that allocates all of the available space in the disk array **140** for storing particular blocks sizes and/or parity group arrangements. Space allocation information is maintained by the server **140** in a metadata structure known as a Gee Table. The Gee Table contains information used to identify the mapping and distribution of blocks within the disk array **140** and is updated as data is stored to the disks **2305**.

[0425] The Gee Table stores informational groups which interrelate and reference disk blocks or other discrete space allocation components of the disk array **140**. These informational groups, referred to as Gee-strings, contain disk space allocation information and uniquely define the location of files in the disk array **140**. Each Gee-string is subdivided into one or more Gee-groups which is further divided into one or more Gees containing the physical disk space allocation information. The Gee-strings and components thereof are interpreted by the server **130** to define the mapping of parity groups **2335** in the disk array **140** which store information and files as will be discussed in greater detail hereinbelow.

[0426] Based on the available space within the disk array **140**, the server **130** determines the type and number of parity groups **2335** that will be allocated in the array **140**. The initial parity group allocation prior to data storage forms the Gee Table and directs the storage of data based on available parity groups. The Gee Table therefore serves as a map of the disk space and is updated as data is stored within the blocks **2330**, **2337** of the array **140** to provide a way for determining the file allocation characteristics of the array **140**. The server **130** retrieves stored files from the disk array **140** using the Gee Table as an index that directs the server **130** to the blocks **2330** where the data is stored so that they may be retrieved in a rapid and efficient manner.

[0427] **FIG. 27** illustrates a portion of a Gee Table used to determine the mapping of parity groups **2335** in the disk array **140**. For additional details of this architecture the reader is directed to sections which relate specifically to the implementation of the file system.

[0428] In one embodiment, space allocation in the disk array **140** is achieved using a Gee Table **2530** containing an index field **2532**, a G-code field **2534**, and a data field **2536**. The index field **2532** is a value that is associated with a row of information or Gee **2538** within the Gee Table **2530** and is used as an index or a pointer into the array or list comprising the Gee Table **2530**. Additionally, the index field **2532** uniquely identifies each Gee **2538** within the Gee Table **2530** so that it can be referenced and accessed as needed.

[0429] The G-Code field **2534** indicates the type of data that is stored in the disk space associated with each Gee **2538** and is further used to identify space allocation characteristics of the Gees **2538**. During initialization of the disk array, the server **140** assigns all of the disk space within the array **140** to various parity groups **2335**. These parity groups **2335** are defined by the block size for data and parity blocks **2330**, **2337** and the number of data blocks within the group **2335**. Identifiers in the G-Code field **2534** correspond to flags including "FREE", "AVAIL", "SPARE", "G-NODE", "DATA", "PARITY", "LINK", "CACHE-DATA", or CACHE-PARITY".

[0430] The data field **2536** stores data and information interpreted by the server **130** in a specific manner depending upon the G-code field identifier **2534**. For example, this field can contain numerical values representing one or more physical disk addresses defining the location of particular blocks **2330**, **2337** of the parity groups **2335**. Additionally, the data field **2536** may contain other information that defines the structure, characteristics, or order of the parity blocks **2335**. As will be described in greater detail hereinbelow, the information contained in the G-table **2530** is accessed by the server **130** and used to store and retrieve information from the disk array **140**.

[0431] In one embodiment, the fields **2532**, **2534**,**2536** of the G-table **2530** map out how space will be utilized throughout the entire disk array **140** by associating each physical block address with the designated Gee **2538**. Parity groups **2335** are defined by sets of contiguous Gees **2538** that are headed by the first Gee **2538** containing information that defines the characteristics of the parity group **2335**. The G-Code field identifier "G-NODE" instructs the server **130** to interpret information in the data field **2536** of a particular Gee **2538** having the "G-NODE" identifier as defining the characteristics of a parity block **2335** that is defined by a G-group **2540**.

[0432] A characteristic defined in the data field **2536** of the Gee **2538** having a "G-NODE" identifier includes an extent value **2542**. The extent value **2542** represents the extent or size of the blocks **2330**, **2337** associated with each Gee **2538** in a particular G-group **2540**. The extent value **2542** further indicates the number of logical disk blocks associated with each file logical block **2330**, **2337**. For example, the Gee with an index of "45" contains the G-Code identifier "G-NODE" and has a value of "2" associated with the extent value. This extent value **2542** indicates to the server **130** that all subsequent data blocks and parity blocks defined in the parity group **2335** and represented by the G-group **2540** will have a size of 2 logical disk blocks. Thus, as indicated in **FIG. 27**, the Gees having indexes "46"-"49" are each associated with two logical addresses for drive blocks within the array **140**. In a similar manner, the Gee **2538** with an index of "76" contains the G-Code identifier "G-NODE" and has an extent value of "3". This value indicates to the server **130** that the subsequent Gees "77"-"79" of the parity group are each associated with 3 physical drive block addresses.

[0433] In the preceding discussion of **FIG. 27**, information is organized into a single G-table however it will be appreciated that there are a number of different ways for storing the information to improve system flexibility including the use of multiple tables or data structures. The exact manner in which this information is stored is desirably designed to insure that it may be efficiently accessed. For example, in one embodiment nodes of the Gee Table **2530** can be utilized as a common storage vehicle for multiple types of metadata, including file names, identifiers (GNIDS), Gees, etc.

[0434] As discussed in connection with **FIG. 29**, other G-code identifiers are used during the storage and retrieval of information from the disk array **140**. For example, another G-code identifier, "DATA", signifies that the data field **2536** of a particular Gee **2538** is associated with the physical address for one or more drive blocks that will store data. Likewise, the G-code identifier, "PARITY", signifies that the data field **2536** of a particular Gee is associated with the physical address for one or more drive blocks that store parity information. The parity information stored in the data blocks referenced by the "PARITY" Gee is calculated based upon the preceding "DATA" Gees as defined by the "G-NODE" Gee. Thus, as shown in the **FIG. 27**, the Gee **2538** having an index of "79" will store the physical address of disk blocks that contain parity information for data blocks specified by Gees having indexes "77"-"78".

[0435] **FIG. 28** illustrates a process **2448** used by the server **130** to prepare the disk array **140** for data storage. Preparation of the disk array **140** commences with the server **130** identifying the characteristics **2550** of each disk **2305** within the array **140** to determine the quantity of space available. In one embodiment, the server **130** identifies physical characteristics for the drives **2305** within the array **140**. These characteristics can include: total drive number, individual drive size, sectors per disk, as well as other drive characteristics useful in determining the available space of the disk array **140**. To facilitate the configuration of the array **140**, the server **130** can automatically detect and recognize the presence of each disk **2305** within the array **140** and can electronically probe each disk **2305** to determine the drive characteristics. Alternatively, the server **130** can be programmed with information describing the array composition and drive characteristics without automatically determining this information from the array **140**.

[0436] Upon acquiring the necessary information describing the array composition, the server **130** determines a parity group allotment **2555** to be used in conjunction with the available disk space. The parity group allotment **2555** describes a pool of available parity groups **2335** that are available for data storage within the array **140**. The parity group allotment further describes a plurality of different block and/or parity group configurations each of which is suited for storing particular data and file types (i.e. large files, small files, multimedia, text, etc). During data storage, the server **130** selects from the available pool of parity groups **2335** to store data in a space-efficient manner that reduces wasted space and improves data access efficiency.

[0437] In one embodiment, the parity group allotment is determined automatically by the server **130** based on preprogrammed parity group distribution percentages in conjunction with available disk space within the array **140**. Alternatively, the server **130** can be configured to use a specified parity group allotment **2555** that is provided to the server **130** directly. In another aspect, the parity groups can be allocated dynamically by the server based on file characteristics such as file size, access size, file type, etc.

[0438] Based on the allotment information and the disk space available in the array **140**, the server **130** performs a mapping operation **2560** to determine how the parity groups **2335** of the allotment will be mapped to physical block addresses of drives **2305** within the array **140**. The mapping operation **2560** comprises determining a desirable distribution of parity groups **2335** on the basis of their size and the available space and characteristics of the disk array **140**. As the distribution of parity groups **2335** is determined by the server **130**, the G-table **2530** is created and populated with Gees **2538** which associate each available parity group **2335** with the physical block addresses defining their location on one or more disks **2305** in the disk array **140**. Initially, the G-table **2530** describes parity groups **2335** that contain free or available space, however, as data is stored to the disk **2575**, the G-table is updated to reflect the contents of the physical disk blocks that are pointed to by the Gees **2538**.

[0439] During operation of the distributed file storage system **100**, the G-table **2530** is accessed by the server **130** to determine the logical addresses of files and information stored within the disk array **140**. Furthermore, server **130** continually updates the G-table **2530** as information is saved to the disk array **140** to maintain knowledge of the physical location of the information as defined by the logical block addresses. The dynamically updated characteristics of the G-Table **2530** data structure therefore define and maintain the mapping of data and information in the disk array **140**.

[0440] In addition to the aforementioned a priori method of parity group allocation other methods of disk preparation may also be utilized. For example, another method of disk preparation can use a set of free disk block maps to allow dynamic allocation of the parity groups. This method additionally provides mechanisms for dynamic extension of existing parity groups and includes logic to ensure that the disk does not become highly fragmented. In some instances, fragmentation of the disk is undesirable because it reduces the ability to use long parity groups when mapping and storing information to the disk.

[0441] **FIG. 29** illustrates one embodiment of a file storage schema **2600** that uses the aforementioned parity group arrangements **2335** and G-table **2530** to store information contained in an exemplary file **2605**. The file **2605** contains information coded by an electronic byte pattern that is received by the server **130** during client storage requests. In the storage schema **2600**, the file **2605** is divided into one or more file logical blocks **2610** for storage. Each file logical block **2610** is stored in a cluster of one or more disk logical blocks **2615** in the disk array **140**. As previously indicated, the distributed file storage system **100** retains many of the advantages of conventional storage systems, including the distribution of files across multiple disk drives and the use of parity blocks to enhance error checking and fault tolerance. However, unlike many conventional systems, the distributed file storage system **100** does not restrict file logical blocks to one uniform size. File logical blocks of data and parity logical blocks can be the size of any integer multiple of a disk logical block. This variability of file logical block size increases the flexibility of allocating disk space and thus improves the use of system resources.

[0442] Referring to **FIG. 29**, the file **2605** is divided into a plurality of file logical blocks **2610**, each of which contains a portion of the information represented in the file **2605**. The number, size, and distribution of the file logical blocks **2610** is determined by the server **130** by selecting available disk logical blocks **2615** designated in the G-table **2530**. The information contained in each file logical block **2610** is stored within the disk logical blocks **2615** and mapped using the G-table **2530**. In the distributed file storage system **100**, the size of each file logical block **2610** is described by the extent value **2542** which is an integer multiple in disk logical blocks **2615**. For example, the logical block designated "LB-1" comprises two disk logical blocks **2615** and has an extent value of 2. In a similar manner, the logical block designated "LB-7" comprises three disk logical blocks **2615** and has an extent value of 3.

[0443] The server **130** forms parity groups **2335** using one or more file logical blocks **2615** and the associated parity block **2337**. For each file **2605**, one or more parity groups **2335** are associated with one another and ordered through logical linkages **2617** (typically defined by pointers) used to determine the proper ordering of the parity groups **2335** to store and retrieve the information contained in the file **2605**. As shown in the illustrated embodiment, the file **2605** is defined by a parity string **2620** containing four parity groups **2610**. The four parity groups are further linked by three logical linkages **2617** to designate the ordering of the logical blocks "LB-1" through "LB-10" which make up the file **2605**.

[0444] The G-table **2530** stores the information defining the G-string **2620** using a plurality of indexed rows defining Gees **2538**. The Gees **2538** define the characteristics of the G-strings **2620** and further describe the logical location of the associated file **2605** in the disk array **140**. In the G-table **2530**, the G-string **2620** is made up of the one or more Gee-groups. Each G-group is a set of contiguous Gees **2538** that all relate to a single file. For example, in the illustrated embodiment, the Gee-string **2620** includes three Gee-groups **2627**, **2628**, and **2629**.

[0445] The first Gee in each G-group **2627-2629** is identified by the G-Code field identifier "G-NODE" and the data field **2536** of this Gee contains information that defines the characteristics of a subsequent Gee **2632** within the Gee-group **2627-2629**. The data field **2536** of the first Gee in each G-group **2627-2629** further contains information that determines the ordering of the Gee-groups **2627-2629** with respect to one another. Some of the information typically found in the data field **2536** of the first Gee in each G-group **2627-2629** includes: A G-NODE reference **2635** that relates the current G-group with a file associated with a G-node at a particular index ("67" in the illustration) in the G-table **2530**; the extent value **2542** that defines the size of each file logical block **2610** in terms of disk logical blocks **2615**; and a root identifier **2637** that indicates if the G-group is the first G-group in the G-string. Of a plurality of G-NODE Gees **2630**, **2640**, **2650**, only the first Gee **2630** contains an indication that it is a Root Gee, meaning that it is the first Gee of the Gee-string **2620**.

[0446] Following the G-NODE Gee in a Gee-group are Gees representing one or more distributed parity groups **2655-2658**. A distributed parity group is set of one or more contiguous DATA Gees followed by an associated PARITY Gee. A DATA Gee is a Gee with the G-code **2534** of "DATA" that lists disk logical block(s) where a file logical block is stored. For example, in **FIG. 29**, the Gees with indexes of 46-47, 50-52, 77-79 and 89-90 are all DATA Gees, and each is associated with one file logical block **2610**.

[0447] A PARITY Gee is a Gee with the G-code **2534** of "PARITY." Each PARITY Gee lists disk logical block location(s) for a special type of file logical block that contains redundant parity data used for error checking and error correcting one or more associated file logical blocks **2610**. A PARITY Gee is associated with the contiguous DATA Gees that immediately precede the PARITY Gee. The sets of contiguous DATA Gees and the PARITY Gees that follow them are known collectively as distributed parity groups **2655-2658**.

[0448] For example, in **FIG. 29**, the PARITY Gee at index 49 is associated with the DATA Gees at indexes 46-48, and together they form the distributed parity group **2655**. Similarly, the PARITY Gee at index 53 is associated with the DATA Gees at indexes 50-52, and together they form the distributed parity group **2656**. The PARITY Gee at index 79 is associated with the DATA Gees at indexes 77-78, which together form the distributed parity group **2657**, and the PARITY Gee at index 91 is associated with the DATA Gees at indexes 89-90, which together form the distributed parity group **2658**.

[0449] The size of a disk logical block cluster described by a DATA Gee or a PARITY Gee matches the extent listed in the previous G-NODE Gee. In the example of **FIG. 29**, the G-NODE Gee **2630** of the first Gee-group **2627** defines an extent size of 2, and each DATA and PARITY Gee of the two distributed parity groups **2655**, **2656** of the Gee-group **2627** lists two disk logical block locations. Similarly, G-NODE Gee **2640** of the second Gee-group **2628** defines an extent size of 3, and each DATA and PARITY Gee of the Gee-group **2628** lists three disk logical block locations. G-NODE Gee **2650** of the third Gee-group **2629** defines an extent size of 3, and each DATA and PARITY Gee of the Gee-group **2629** lists three disk logical block locations.

[0450] If a Gee-group is not the last Gee-group in its Gee-string, then a mechanism exists to link the last Gee in the Gee-group to the next Gee-group of the Gee-string using the logical linkages **2617**. LINK Gees **2660**, **2661** both have the G-code **2534** of "LINK" and a listing in their respective Data fields **2536** that provides the index of the next Gee-group of the Gee-string **2620**. For example, the Gee with an index of 54 is the last Gee of Gee-group **2627**, and its Data field **2536** includes the starting index "76" of the next Gee-group **2628** of the Gee-string **2620**. The Gee with an index of 80 is the last Gee of Gee-group **2628**, and its Data field **2536** includes the starting index "88" of the next Gee-group **2629** of the Gee-string **2620**. Since the Gee-group **2629** does not include a LINK Gee, it is understood that Gee-group **2629** is the last Gee-group of the Gee-string **2620**.

[0451] As previously indicated, the G-code **2534** of "FREE" (not shown in **FIG. 29**) indicates that the Gee has never yet been allocated and has not been associated with any disk logical location(s) for storing a file logical block. The G-code **2534** of "AVAIL" (not shown in **FIG. 29**) indicates that the Gee has been previously allocated to a cluster of disk logical block(s) for storing a file logical block, but that the Gee is now free to accept a new assignment. Two situations in which a Gee is assigned the G-code of "AVAIL" are: after the deletion of the associated file logical block; and after transfer of the file to another server in order to optimize load balance for the distributed file storage system **100**.

[0452] **FIG. 30** illustrates a fault recovery mechanism **700** used by the distributed file storage system **100** to maintain data consistency and integrity when a data fault occurs. Data faults are characterized by corruption or loss of data or information stored in one or more logical blocks **2330** of the array **140**. Each data fault can be further characterized as a catastrophic event, where an entire disk **2305** fails requiring all data on the failed disk to be reconstructed. Alternatively, the data fault can be characterized as a localized event, where the disk **2305** maintains operability but one or more physical disk sectors or logical blocks become corrupted or damaged. In either instance of the data fault, the distributed file storage system **100** uses a fault-tolerant restoration process to maintain data integrity.

[0453] **FIG. 30** illustrates one embodiment of a fault-tolerant restoration process used to maintain data integrity in the distributed file storage system **100**. As an example of how the process operates, a loss of integrity in a data block for a single parity group is shown. It will be appreciated that this loss of integrity and subsequent recovery methodology can be applied to both instances of complete drive failure or localized data corruption. Thus, the restoration of information contained in a plurality of logical blocks can be accomplished using this process (i.e. restoring all data stored on a failed disk). Additionally, in instances where parity blocks become corrupted or lost, the information from each parity block can be restored in a similar manner to the restoration process for data blocks using the remaining non-corrupted blocks of the parity group.

[0454] In the illustrated embodiment the parity group **2335** includes two data blocks "$DATA_1$1" and "$DATA_1$2" and an associated parity block "$PARITY_1$1-2" and are shown stored on "DISK 2", "DISK 8", and "DISK 11" respectively. Knowledge of the logical disk addresses for each of these blocks is maintained by the server **130** using the aforementioned G-table **2530**. As previously discussed, the G-table maintains mapping and structural information for each parity group defined by the plurality of Gees **2538**. The Gees further contain information including; the file descriptor associated with the blocks of the parity group **2335**, the size and extent of the blocks of the parity group **2335**, and the mapping to the logical disk space for each block of the parity group **2335**. During routine operation, the server accesses data in the disks of the array using the G-table **2530** to determine the appropriate logical disk blocks to access.

[0455] As shown in **FIG. 30, a** complete disk failure is exemplified where a loss of data integrity **3072** results in the logical blocks on "DISK 8" becoming inaccessible or corrupted. During the fault tolerant restoration process the server **130** determines that the data block "$DATA_1$2" is among the one or more blocks that must be recovered **3074**. Using conventional data/parity block recovery methods, the server **130** recovers the compromised data block "$DATA_1$2" using the remaining blocks "$DATA_1$1" and "$PARITY_1$1-2" of the associated parity group **2335**. The recovered data block "$DATA_1$2-REC" is then stored to the disk array **140** and contains the identical information that was originally contained in "$DATA_1$2". Using the existing G-table mapping as a reference, the server **130** identifies a new region of disk space that is available for storing the recovered data block and writes the information contained in "$DATA_1$2-REC" to this region. In one embodiment, space for a new parity group is allocated and the reconstructed parity group is stored in

the new space. In another embodiment, the "old" parity group having 1 parity block and N data blocks where one data block is bas, is entered onto the free list as a parity group having N-1 data blocks. The server **130** further updates the G-table **2530** to reflect the change in logical disk mapping (if any) of the recovered data block "$DATA_1$2-REC" to preserve file and data integrity in the disk array **140**.

[**0456**] One desirable feature of the distributed file storage system **100** is that the recovered data block need not be restored to the same logical disk address on the same disk where the data failure occurred. For example, the recovered data block "$DATA_1$2-REC" can be stored to "DISK 3" and the G-table updated to reflect this change in block position. An important benefit resulting from this flexibility in data recovery is that the disk array **140** can recover and redistribute data from a failed drive across other available space within the disk array **140**. Therefore, a portion of a disk or even an entire disk can be lost in the distributed file storage system **100** and the data contained therein can be recovered and moved to other locations in the disk array **140**. Upon restoring the data to other available disk space, the server **130** restores the integrity of the parity group **2335** resulting in the preservation of fault-tolerance through multiple losses in data integrity even within the same parity group without the need for immediate repair or replacement of the faulted drive to restore fault-tolerance.

[**0457**] As an example of the preservation of fault tolerance through more than one data fault, a second drive failure **3076** is shown to occur on "DISK 2" and affects the same parity group **2335**. This disk failure occurs subsequent to the previous disk failure in which "DISK 8" is illustrated as non-operational. The second disk failure further results in the loss of data integrity for the block "$DATA_1$1". Using the method of data recovery similar to that described above, the information contained in the data block "$DATA_1$1" can be recovered and redistributed **3078** to another logical address within the disk array **140**. The recovered data block "$DATA_1$1-REC" is illustrated as being saved to available disk space located on "DISK 5" and is stored in a disk region free of corruption of data fault. Thus, fault tolerance is preserved by continuous data restoration and storage in available non-corrupted disk space.

[**0458**] The fault tolerant data recovery process demonstrates an example of how the distributed file storage system **100** handles data errors or corruption in the disk array **140**. An important distinction between this system **100** and conventional storage systems is that the aforementioned data recovery process can automatically redistribute data or parity blocks in a dynamic and adaptable manner. Using block redistribution processes described above results in the distributed file storage system **100** having a greater degree of fault-tolerance compared to conventional storage systems. In one aspect, the increase in fault tolerance results from the system's ability to continue normal operation even when one or more drives experience a data loss or become inoperable.

[**0459**] In conventional storage systems, when a single disk failure occurs, the storage system's fault tolerant characteristics are compromised until the drive can be repaired or replaced. The lack of ability of conventional systems to redistribute data stored on the faulted drive to other regions of the array is one reason for their limited fault tolerance. In these conventional systems, the occurrence of a second drive failure (similar to that shown in **FIG. 30**) will likely result in the loss or corruption of data that was striped across both of the failed drives. The distributed file storage system **100** overcomes this limitation by redistributing the data that was previously stored on the faulted drive to a new disk area and updating the G-table which stores the mapping information associated with the data to reflect its new position. As a result, the distributed file storage system **100** is rendered less susceptible to sequential drive faults even if it occurs within the same parity group. Thus, the process of recovery and redistribution restores the fault-tolerant characteristics of the distributed file storage system **100** and beneficially accommodates further drive failures within the array **140**.

[**0460**] Another feature of the distributed file storage system **100** relates to the flexible placement of recovered data. In one aspect, a recovered data block may be stored anywhere in the DFSS through a modification of the parity group associated with the data. It will be appreciated that placement of recovered data in this manner is relatively simple and efficient promoting improved performance over conventional systems.

[**0461**] In one embodiment, this feature of tolerance to multiple disk failures results in an improved "hands-off" or "maintenance-free" data storage system where multiple-drive failures are tolerated. Furthermore, the distributed file storage system **100** can be configured with the anticipation that if data corruption or a drive failure does occur, the system **100** will have enough available space within the array **140** to restore and redistribute the information as necessary. This improved fault tolerance feature of the distributed file storage system **100** reduces maintenance requirements associated with replacing or repairing drives within the array. Additionally, the mean time between failure (MTBF) characteristics of the system **100** are improved as the system **100** has reduced susceptibility to sequential drive failure or data corruption.

[**0462**] In one embodiment the distributed file storage system is desirably configured to operate in a "hands-off" environment where the disk array incorporates additional space to be tolerant of periodic data corruption or drive failures without the need for maintenance for such occurrences. Configuration of the system **100** in this manner can be more convenient and economical for a number of reasons such as: reduced future maintenance costs, reduced concern for replacement drive availability, and reduced downtime required for maintenance.

[**0463**] In one aspect, the fact that parity groups may be integrated with the file metadata provides a way for prioritizing recovery of the data. For example, when some file or set of files is designated as highly important, or is frequently accessed, a background recovery process can be performed on those designated files first. In the case where the file is frequently accessed, this feature may improve system performance by avoiding the need for time-consuming on-demand regeneration when a client attempts to access the file. In the case where the file is highly important, this feature reduces the amount of time where a second drive failure might cause unrecoverable data loss.

[**0464**] **FIG. 31** illustrates one embodiment of a method **3172** for recovering corrupted or lost data resulting from one or more data faults. As discussed above and shown the previous figure, data corruption can occur as a result of a

complete drive failure or data corruption can be localized and affect only a limited subset of logical storage blocks within the array. The distributed storage system identifies the presence of data corruption in a number of ways. In one aspect, the server recognizes corrupted data during storage or retrieval operations in which the one or more of the disks of the array are accessed. These operations employ error checking routines that verify the integrity of the data being stored to or retrieved from the array. These error checking routines typically determine checksum values for the data while performing the read/write operation to insure that the data has been stored or retrieved in a non-corrupted manner. In cases where the read/write operation fails to generate a valid checksum value, the read/write operation may be repeated to determine if the error was spurious in nature (oftentimes due to cable noise or the like) or due to a hard error where the logical disk space where the data is stored has become corrupted.

[0465] Data corruption may further be detected by the server **130** when one or more disks **2305** within the array **140** become inaccessible. Inaccessibility of the disks **2305** can arise for a number of reasons, such as component failure within the drive or wiring malfunction between the drive and the server. In these instances where one or more disks within the array are no longer accessible, the server **130** identifies the data associated with the inaccessible drive(s) as being corrupted or lost and requiring restoration.

[0466] During the identification of the data fault **3175**, the number and location of the affected logical blocks within the disk array **140** is determined. For each logical block identified as corrupted or lost, the server **130** determines the parity group associated with the corrupted data **3177**. Identification of the associated parity group **2335** allows the server **130** to implement restoration procedures to reconstruct the corrupted data using the non-corrupted data and parity blocks **2330**, **2337** within the same parity group **2335**. Furthermore, the logical storage block or disk space associated with the corrupted data is identified **3179** in the G-table **2530** to prevent further attempts to use the corrupted disk space.

[0467] In one embodiment, the server **130** identifies the "bad" or corrupted logical blocks mapped within the G-table **2530** and removes the associated Gees from their respective parity groups thereby making the parity group shorter. Additionally, the server **130** can identify corrupted logical blocks mapped within the G-table **2530** and remap the associated parity groups to exclude the corrupted logical blocks.

[0468] Prior to restoring the information contained in the affected logical blocks, the server **130** determines the number and type of parity groups that are required to contain the data **3180** that will subsequently be restored. This determination **3180** is made by accessing the G-table **2530** and identifying a suitable available region within the disk array **140** based on parity group allocation that can be used to store the reconstructed data. When an available parity group is found, the server **130** updates the G-table **2530** to reflect the location where the reconstructed data will be stored. Additionally, the mapping structure of the array **140** is preserved by updating the links or references contained in Gees **2538** of the G-table **2530** to reflect the position and where the reconstructed data will be stored in relation to other parity groups of the parity string. Data is then restored **3181** to the logical disk address pointed to by the updated Gee using the remaining non-corrupted blocks of the parity group to provide the information needed for data restoration.

[0469] As previously discussed, one feature of the distributed file storage system **100** is the use of variable length and/or variable extent parity groups. Unlike conventional storage systems that use only a fixed block size and configuration when storing and striping data to a disk array, the system **100** of the present invention can store data in numerous different configurations defined by the parity group characteristics. In one embodiment, by using a plurality of different parity group configurations, the distributed file storage system **100** can improve the efficiency of data storage and reduce the inefficient use of disk space.

[0470] **FIGS. 32A, B** illustrate a simplified example of the use of variably sized parity groups to store files with different characteristics. As shown in **FIG. 32**A, File #1 comprises a 4096 byte string that is stored in the disk array **140**. As previously discussed, the server **130**, selects space from the plurality of parity groups **2335** having different structural characteristics to store the data contained in File #1. In the illustrated embodiment, 4 exemplary parity strings **3240-3243** are considered for storing File #1. Each of the parity strings **3240-3243** comprises one or more parity groups **2335** that have a designated extent based on a logical disk block size of 512 bytes. The parity groups **2335** of each parity string **3240-3243** are further associated using the G-table **2530** which link the information in the parity groups **2335** to encode the data contained in File #1.

[0471] The first parity string **3240** comprises a single 4-block parity group having 1024-byte data and parity blocks. The total size of the first parity string **3240** including all data and parity blocks is 5120 bytes and has an extent value of 2. The second parity string **3241** comprises two 3-block parity groups having 1024-byte data and parity blocks. The total size of the second parity string **3241** including the data and parity blocks is 8192 bytes and has an extent value of 2. The third parity string **3242** comprises four 2-block parity groups having 512-byte data and parity blocks. The total size of the third parity string **3242** including the data and parity blocks is **6144** bytes and has and extent value of 1. The fourth parity string **3243** comprises nine 1-block parity groups having 512-byte data and parity blocks. The total size of the fourth parity string **3243** including the data and parity blocks is 8192 bytes and has an extent of 1.

[0472] Each of the parity strings **3240-3243** represent the minimum number of parity groups **2335** of a particular type or composition that can be used to fully store the information contained in File #1. One reason for the difference in parity group composition results from the different numbers of total bytes required to store the data contained in File #1. The differences in total byte numbers further result from the number and size of the parity blocks **2337** associated with each parity group **2335**.

[0473] A utilization value **3245** is shown for each parity string **3240-3242** used to store File #1. The utilization value **3245** is one metric that can be used to measure the relative efficiency of storage of the data of File #1. The utilization value **3245** is determined by the total number of bytes in the parity string **3240-3242** that are used to store the data of File

#1 compared to the number of bytes that are not needed to store the data. For example, in the second parity string **3241**, one parity group **3247** is completely occupied with data associated with File #1 while another parity group **3246** is only partially utilized. In one aspect, the remainder of space left in this parity group **3246** is unavailable for further data storage due to the composition of the parity group **3246**. The utilization value is calculated by dividing the file-occupying or used byte number by the total byte number to determine a percentage representative of how efficiently the data is stored in the parity string **3240-3243**. Thus, the utilization values for the first, second, third, and fourth parity strings **3240-3243** are 100%, 66%, 100%, and 100% respectively.

[**0474**] In one embodiment, the server **130** determines how to store data based on the composition of the file and the availability of the different types of parity groups. As shown in **FIG. 32**A, of the different choices for storing File #1, the first parity string **3240** is most efficient as it has the lowest total bytes required for storage (5120 bytes total), as well as, a high utilization value (100%). Each of the other parity strings **3241-3243** are less desirable for storing the data in File #1 due to greater space requirements (larger number of total bytes) and in some cases reduced storage efficiency (lower utilization value).

[**0475**] **FIG. 32B** illustrates another simplified example of the use of variably sized parity groups to store files of differing sizes. In the illustrated embodiment the storage characteristics of a plurality of four parity strings **3250-3253** are compared for a small file comprising a single 1024 byte string. The parity strings comprise: The first parity string **3250** composed of the single parity group **2335** having 4 data blocks **2330** and 1 parity block **2337**, each **1024** bytes in length; The second parity string **3251** composed of the single parity group **2335** having 3 data blocks **2330** and 1 parity block **2337**, each **1024** bytes in length; The third parity string **3251** composed of the single parity group **2335** having 2 data blocks **2330** and 1 parity block **2337**, each 512 bytes in length; and The fourth parity string **3253** having two parity groups **2335** each composed of the single 512-byte data block **2330** and the parity block **2337**.

[**0476**] When storing the byte pattern contained in File #2 different storage characteristics are obtained for each parity string **3250-3253**. For example, the first parity string **3250** is only partially occupied by the data of File #2 resulting in the utilization value **3245** of 25%. Similarly, the second parity string **3251** is also partially occupied resulting in the utilization value **3245** of 33%. Conversely, the third and fourth parity strings **3252-3253** demonstrate complete utilization of the available space in the parity group (100% percent utilization). Based on the exemplary parity group characteristics given above, the most efficient storage of File #2 is achieved using the third parity string **3252** where a total of 1536 bytes are allocated to the parity string with complete (100%) utilization.

[**0477**] The aforementioned examples demonstrate how files with differing sizes can be stored in one or more parity group configurations. In each of the above examples, the unused blocks or partially filled blocks remaining in the parity group are "zero-filled" or "one-filled" to complete the formation of the parity group and encode the desired information from the file. Furthermore, by providing a plurality of parity group configurations, improved storage efficiency can be achieved for different file sizes where less space is left unutilized within the disk array **140**. It will be appreciated by one of skill in the art that many possible parity group configurations can be formed in a manner similar to those described in **FIGS. 32A, B**. Examples of characteristics which may influence the parity group configuration include: logical block size, extent, parity group size, parity group number, among other characteristics of the distributed file storage system **100**. Therefore, each of the possible variations in parity group characteristics and distribution should be considered but other embodiments of the present invention.

[**0478**] Typically, one or more selected parity groups of the available configurations of parity groups provide improved storage efficiency for particular file types. Therefore, in order to maintain storage efficiency across each different file configuration a plurality of parity group configuration are desirably maintained by the server. One feature of the distributed file storage system **100** is to identify desirable parity group configurations based on individual file characteristics that lead to improved efficiency in data storage.

[**0479**] **FIG. 33** illustrates one embodiment of a data storage process **3360** used by the distributed file storage system **100** to store data. This process **3360** desirably improves the efficiency of storing data to the disk array **140** by selecting parity group configurations that have improved utilization characteristics and reduce unused or lost space. In this process **3360** the server **130** receives files **3361** from the clients **110** that are to be stored in the disk array **140**. The server **130** then assesses the file's characteristics **3363** to determine suitable parity string configurations that can be used to encode the information contained in the file. During the file assessment **3363**, the server **130** can identify characteristics such as the size of the file, the nature of the data contained in the file, the relationship of the file to other files presently stored in the disk array, and other characteristics that are used to determine how the file will be stored in the disk array **140**. Using the G-table **2530** as a reference, the server **130** then identifies **3365** available (free) parity groups that can be used to store the file to the disk array **140**.

[**0480**] Typically, a plurality of parity group configurations are available and contain the requisite amount of space for storing the file. Using an analysis methodology similar to that described in **FIGS. 32A, B**, the server **130** assesses the utilization characteristics for each parity group configuration that can be used to store the file. Based on the available configurations and their relative storage efficiency, the server **130** selects a desirable parity group configuration **3367** to be used for file storage. In one embodiment, a desirable parity group configuration is identified on the basis of the high utilization value **3245** that is indicative of little or no wasted space (non-file encoding space) within the parity groups. Furthermore, a desirable parity group configuration stores the file in the parity string **2335** comprising the least number of total bytes in the parity string. Using these two parameters as a metric, the server **130** selects the desirable parity group configuration **3367** and stores the data contained in the file **3369**. During file storage **3369**, the G-table **2530** is updated to indicate how the file is mapped to the disk array **140** and characteristics of the G-string **2530** used to store the file are encoded in the appropriate Gees of the G-table **2530**. Furthermore, the one or more Gees corresponding to the logical disk blocks where the data from the file is stored are updated to reflect their now occupied status (i.e. removed from pool of available or free disk space).

[0481] In another embodiment the distributed file storage system **100** provides a flexible method for redistributing the parity groups **2335** of the disk array **140**. As discussed previously, prior to storage of information in the disk array **140** the distributed file storage system **100** creates the G-table **2530** containing a complete map of the logical blocks of each disk **2305** of the disk array **140**. Each logical block is allocated to a particular parity group type and may be subsequently accessed during data storage processes when the group type is requested for data storage. During initialization of the disk array **140**, the server **130** allocates all available disk space to parity groups **2335** of various lengths or sizes which are subsequently used to store data and information. As files are stored to the disk array **140**, the parity groups **2335** are accessed as determined by the server **130** and the availability of each parity group type changes.

[0482] Using the plurality of different sizes and configurations of parity groups **2335** allows the server **130** to select particular parity group configurations whose characteristics permit the storage of a wide variety of file types with increased efficiency. In instances where a file is larger than the largest available parity group, the server **130** can break down the file and distribute its contents across multiple parity groups. The G-table **2530** maps the breakdown of file information across the parity groups over which it is distributed and is used by the server **130** to determine the order of the parity groups should be accessed to reconstruct the file. Using this method, the server **140** can accommodate virtually any file size and efficiently store its information within the disk array **140**.

[0483] When a large quantity of structurally similar data is stored to the disk array **140**, a preferential parity group length can be associated with the data due to its size or other characteristics. The resulting storage in the preferential parity group length reduces the availability of this particular parity group and may exhaust the supply allocated by the server **130**. Additionally, other parity group lengths can become underutilized, as the data stored to the disk array **140** does not utilize these other parity group types in a balanced manner. In one embodiment the distributed file storage system **100** monitors the parity set distribution and occupation characteristics within the disk array **140** and can alter the initial parity set distribution to meet the needs of client data storage requests on an ongoing basis and to maintain a balanced distribution of available parity group types. The parity group monitoring process can further be performed as a background process or thread to maintain data throughput and reduce administrative overhead in the system **100**.

[0484] FIGS. **34**A-C illustrate a simplified parity set redistribution process useful in maintaining availability of parity groups **2335** within the disk array **140**. Redistribution is handled by the server **130**, which can update sets of Gees of the G-table **2530** to alter their association with a first parity group into an association with a second parity group. Furthermore, other characteristics of the data and parity blocks within a parity group can be modified, for example, to change the size or extent of each block. By updating the G-table **2530**, the server **140** provides a parity group balancing functionality to insure that each type or configuration of parity group is available within the disk array **140**.

[0485] **FIG. 34A** illustrates an exemplary parity group distribution for the disk array **140** prior to storage of data from clients **110**. The parity group distribution comprises four types of parity groups corresponding to a 4-block parity group **3480**, a 3-block parity group **3481**, a 2-block parity group **3482**, and a 1-block parity group **3483**. In configuring the distributed file storage system **100** there is an initial allocation **3491** of each type of parity group **3480-3483**. For example, in the illustrated embodiment, **10000** groups are allocated for each type of parity group **3480-3483**. Each parity group **3480-3483** further occupies a calculable percentage of a total disk space **3485** within the disk array **140** based on the size of the parity group. Although the parity group distribution is illustrated as containing four types of parity groups, it will be appreciated by one of skill in the art that numerous other sizes and configurations of parity groups are possible. (e.g. 8, 10, 16, etc.) In one embodiment, the number of blocks within the parity group **2335** can be any number less than or equal to the number of disks within the disk array **140**. Furthermore, the parity groups **2335** may be distributed across more than one disk array **140** thus allowing for even larger parity group block numbers that are not limited by the total number of disks within the single disk array **140**.

[0486] As disk usage occurs **3487**, parity groups **3480-3483** become occupied with data **3490** and, of the total initial allocation of parity groups **3491**, a lesser amount remain as free or available parity groups **3492**. **FIG. 34B** illustrates parity group data occupation statistics where of the original initially allocated parity groups **3491** for each parity type, a fraction remain as free or available **3492** for data storage. More specifically: The occupation statistics for the 4-block parity group comprise **2500** free vs. **7500** occupied parity groups, the occupation characteristics for the 3-block parity group comprise **7500** free vs. **2500** occupied parity groups, the occupation characteristics for the 2-block parity group comprise **3500** free vs. **6500** occupied parity groups, and the occupation characteristics for the 1-block parity group comprise **500** free vs. **9500** occupied parity groups.

[0487] During operation of the distributed file storage system **100**, free parity groups can become unevenly distributed such that there are a greater proportion of free parity groups in one parity group length and a lesser proportion of free parity groups in another parity group length. While this disparity in distribution does not necessarily impact the performance or effectiveness of storing data to the disk array **140**, the server **130** monitors the availability of each parity group **3480-3483** to insure that no single parity group type becomes completely depleted. Depletion of a parity group is undesirable as it reduces the choices available to the server **130** for storing data and can potentially affect the efficiency of data storage. As shown in **FIG. 34**B, the 3-block parity group **3481** possess a greater number of free parity groups **3492** compared to any of the other parity groups **3480**, **3482**, **3483** while the 1-block parity group **3483** possess the smaller number of free parity groups and may be subject to complete depletion should data storage continue with a similar parity group distribution characteristics.

[0488] To prevent parity group depletion, the server **130** can redistribute or convert **3494** at least a portion of one parity group into other parity group lengths. As shown in **FIG. 34**C, the server **130** converts a portion of the 3-block

parity group **3481** into the 1-block parity group **3483**. The resulting conversion redistributes the number of parity groups within the disk array **140** by reducing the number of parity groups of a first parity group type (3-block parity) and generates an additional quantity of parity groups of the second parity group type (1-block parity). Redistribution in this manner beneficially prevents the complete depletion of any parity group and thus preserves the efficiency of data storage by insuring that each parity group is available for data storage.

[**0489**] In one embodiment, parity group redistribution is performed by updating one or more Gees of the G-table **2530** to reflect new parity group associations. As previously discussed, each parity group **2335** is assigned using a data structure linking associated Gees. The redistribution process updates these data structures to redefine the parity group associations for the logical blocks of the disk array **140**. Thus, the server **130** can rapidly perform parity group distribution without affecting existing occupied parity groups or significantly degrading the performance of the distributed file storage system **100**.

[**0490**] **FIGS. 35A, B** illustrate two types of parity group redistribution processes **3500** that are used by the system **100** to maintain parity group availability in the disk array **140**. A first redistribution process known as parity group dissolution **3510** converts a larger parity group into one or more smaller parity groups. As shown in **FIG. 35A, a** 5-block parity group **3515** can be converted into two smaller parity groups consisting of a 1-block parity group **3520** and a 3-block parity group **3525**. The 5-block parity group **3515** can also be converted into two 2-block parity groups **3530** or alternatively three 1-block parity groups **3520**.

[**0491**] A second redistribution process **3500** known as parity group consolidation **3535** (shown in **FIG. 35B**) converts two or more smaller parity groups into one or more larger parity groups. For example, two 2-block parity groups **3530** can be combined to form the single 5-block parity group **3515**. Alternatively, the two 2-block parity groups **3530** can be combined to form a 3-block parity group **3525** and a 1-block parity group **3525**.

[**0492**] It will be appreciated that numerous combinations of parity group dissolution **3510** and consolidation **3535** exist. These redistribution processes **3500** are advantageously used to modify the existing parity group configurations to accommodate the demands of the system **100** as it is populated with information. Using these processes **3500** improves the performance and efficiency of storing data in the system **100**. Consistency and knowledge of the parity group distribution is maintained using the G-table **2530** which is updated as the modifications to the parity groups are made. These processes **3500** can further be performed using both occupied and unoccupied parity groups or a combination thereof to further improve the flexibility of the distributed storage system **100**.

[**0493**] **FIG. 36** illustrates a process **3600** used by the server **130** to monitor parity group availability and perform parity group redistribution as needed. This process **3600** is important in maintaining a desirable quantity of each type of parity group so that files can be stored with improved storage efficiency. In the illustrated embodiment, the process **3600** commences with a monitoring function that determines parity group availability **3602**. The monitoring function **3602** can be performed continuously or at periodic time intervals to insure available parity groups remain balanced within the disk array **140**. Using the G-table **2530** as a reference, the monitoring function **3602** rapidly assesses the current status of data occupation within the array **140**. More specifically, the monitoring function **3602** can determine the availability of each type of parity group and determine the number of free or available groups using the mapping information of the G-table **2530**.

[**0494**] As a particular type of parity group is depleted **3604**, indicated by a reduction in the number of free parity groups for the particular group type, the server **130** proceeds to assess the parity group statistics **3606** for each parity group defined within the G-table **2530**. The assessment of parity group statistics **3606** comprises determining both the free and available parity group statistics using the G-table **2530** as a reference. In determining how to increase the quantity of free parity groups for a depleted parity group type, the server **130** assesses which other parity groups contain available or free parity groups that have not be used to store data. This assessment is made based upon the parity group usage statistics which, for example, indicate free parity groups, occupied parity group, disk space occupation, frequency of access or utilization, among other statistics that can be collected while the distributed file storage system **100** is in operation.

[**0495**] In one embodiment, the server **130** continually collects and stores usage statistics so as to provide up-to-date and readily available statistical information that can be used to determine how redistribution of available parity groups should proceed. Additionally, these statistics can be acquired from the G-table **2530** where the server **130** calculates the usage statistics based upon the current contents of the G-table **2530**.

[**0496**] Upon acquiring the parity group statistics **3606**, the server **130** calculates a suitable re-distribution **3608** of the parity groups. The re-distribution **3608** desirably takes into account factors such as, for example, the number and type of parity groups **2335** within the disk array **140**, the availability of unoccupied parity groups within each parity group type, the frequency of usage or access of each parity group type, among other considerations that can be determined using the parity group statistics. During parity group redistribution **3608**, one or more different parity groups can be used as a source for supplementing the depleted parity group set. The overall effect of redistribution **3608** is to balance the free or available parity groups of each type so that no one single parity group is depleted.

[**0497**] Parity group redistribution in the aforementioned manner is facilitated by the use of the G-table **2530** mapping structure. Using the G-table **2530**, parity groups can be readily assigned and re-assigned without significant overhead by modifying the contents of appropriate Gees. This method of disk space allocation represents a significant improvement over conventional disk storage methods such as those used in RAID architectures. In conventional RAID architectures, the rigid nature of disk space allocation prevents optimizing data storage in the manner described herein. Furthermore, the parity group redistribution feature of the distributed file storage system **100** provides an effective method to monitor and maintain optimized disk storage characteristics within the array to insure efficient use of available disk space.

[0498] In addition to redistributing free or available space within the disk array **140**, the distributed file storage system **100** also features a method by which occupied parity groups can be modified and re-configured into other parity group types. One benefit realized by re-configuring occupied parity groups is that unnecessary space allocated to a particular parity group in which data is stored may be reclaimed for use and converted to available or free storage space. Furthermore, re-configuration of occupied parity groups can be used to de-fragment or consolidate the information stored in the disk array **140** enabling the information contained therein to be accessed more efficiently.

[0499] **FIG. 37** illustrates one embodiment of a parity group optimization/de-fragmentation routine used to re-configure data within the disk array **140**. Parity group occupation statistics are shown for different parity lengths including: a 1-block parity group having 2800 free parity groups and 7200 occupied parity groups, a 2-block parity group having 1800 free parity groups and 8200 occupied parity groups, a 3-block parity group having 800 free parity groups and 9200 occupied parity groups, and a 4-block parity group having 2300 free parity groups and 7700 occupied parity groups.

[0500] When the server **130** performs an optimization routine **3785**, one or more of the parity groups can be re-configured into another type of parity group. For example, as shown in the illustration, a portion of the 1-block parity groups corresponding to 3200 groups can be consolidated into 2000 groups of 4-block parity. In the consolidated parity groups, the original information contained in the 1-block parity group is retained in a more compact form in the 4-block parity groups. The resulting 4-block parity groups require less parity information to maintain data integrity compared to an equivalent quantity of information stored in a 1-block parity configuration. In the illustrated embodiment, the residual space left over from the optimization routine corresponds to approximately 1200 groups of 1-block parity and can be readily converted into any desirable type of parity group using G-table updating methods.

[0501] The aforementioned optimization routine can therefore beneficially re-allocate occupied logical disk blocks into different parity group configurations to reclaim disk space that might otherwise be lost or rendered inaccessible due to the manner in which the data is stored in the parity groups. As with other parity group manipulation methods provided by the distributed file storage system **100**, the process of optimizing parity groups is readily accomplished by rearrangement of the mapping assignments maintained by the G-table **2530** and provides a substantial improvement in performance compared to conventional storage systems. In conventional systems, data restriping is a time consuming and computationally expensive process that reduces data throughput and can render the storage device unavailable while the restriping takes place.

[0502] Like conventional storage systems, the distributed file storage system **100** provides complete functionality for performing routine data and disk optimization routines such as de-fragmentation of logical block assignments and optimization of data placement to improve access times to frequently accessed data. These processes are efficiently handled by the system **100**, which can use redundant data access to insure availability of data disk optimization routines take place.

[0503] The distributed file storage system **100** further provides adaptive load balancing characteristics that improve the use of resources including servers **130** and disk arrays **140**. By balancing the load between available resources, improved data throughput can be achieved where client requests are routed to less busy servers **130** and associated disk arrays **140**. Load-dependent routing in this manner reduces congestion due to frequent accessing of a single server or group of servers. Additional details of these features can be found in those discussions relating to adaptive load balancing and proactive control of the DFSS **100**.

[0504] In one embodiment, frequently accessed data or files are automatically replicated such that simultaneous requests for the same information can be serviced more efficiently. Frequently accessed data is identified by the servers **130** of the distributed file storage system **100**, which maintain statistics on resource usage throughout the network. Furthermore, the servers **130** can use the resource usage statistics in conjunction with predictive algorithms to "learn" content access patterns. Based on these access patterns frequently accessed content can be automatically moved to server nodes **150** that have high bandwidth capacities capable of serving high numbers of client requests. Additionally, less frequently accessed material can be moved to server nodes **150** that have higher storage capacities or greater available storage space where the data or files can be conveniently stored in areas without significant bandwidth limitations.

[0505] **FIG. 38** illustrates one embodiment of a load balancing method **3800** used in conjunction with the distributed file storage system **100** to provide improved read/write performance. In the load balancing method **3800**, file operations are performed **3851** and file access statistics are continuously collected **3852** by the servers **130**. These statistics include information describing file access frequencies, file size characteristics, file type characteristics, among other information. Resource utilization statistics are also collected **3854** and contain information that characterize how data is stored within the distributed file storage system **100**. The resource utilization statistics identify how each disk array **140** is used within the system **100** and may contain statistics that reflect the amount of free space within the array, the amount of used space within the array, the frequency of access of a particular disk within the disk array, the speed of servicing client requests, the amount of bandwidth consumed servicing client requests and other statistics that characterize the function of each disk array **140** within the distributed file storage system **100**. The resource utilization statistics can also be used to evaluate the statistics across multiple disk arrays to determine how each disk array compares to other disk arrays within the distributed file storage system **100**. This information is useful in identifying bandwidth limitations, bottlenecks, disk arrays overloads, and disk array under utilization.

[0506] Using either the resource utilization statistics **3854**, the file access statistics **3852**, or a combination thereof, the one or more servers **130** of the distributed file storage system **100** predict future file and resource utilization characteristics **3856**. In one embodiment, the future file and resource

utilization characteristics **3856** describe a predicted workload for each of the disk arrays within the distributed file storage system **100**. The predicted workload serves as a basis for determining how to best distribute the workload **3858** among available servers and disk arrays to improve access times and reduce bandwidth limitations. Furthermore, the predicted workload can be used to distribute files or content **3860** across the available disk arrays to balance future workloads.

[**0507**] An additional feature of the distributed file storage system **100** is the ability to perform "hot upgrades" to the disk array **140**. This process can involve "hot-swapping" operations where an existing disk within the array is replaced (typically to replace a faulted or non-operational drive). Additionally, the "hot upgrade" process can be performed to add a new disk to the existing array of disks without concomitant disk replacement. The addition of the new disk in this manner increases the storage capacity of the disk array **140** automatically and eliminates the need to restrict access to the disk array **140** during the upgrade process in order to reconfigure the system **100**. In one embodiment, the server **130** incorporates the additional space provided by the newly incorporated disk(s) by mapping the disk space into existing unused/available parity groups. For example, when a new drive is added to the disk array **140**, the server **130** can extend the length or extent of each available parity group by one. Subsequently, parity group redistribution processes can be invoked to optimize and distribute the newly acquired space in a more efficient manner as determined by the server **130**. In one embodiment, when there are more newly added logical disk blocks than can be accommodated by addition to the unused parity groups, at least some of the unused parity groups are split apart by the dissolution process to create enough unused parity groups to incorporate the newly added logical disk blocks.

[**0508**] Load Balancing

[**0509**] One approach to adaptive or active load balancing includes two mechanisms. A first mechanism predicts the future server workload, and a second mechanism reallocates resources in response to the predicted workload. Workload prediction can have several aspects. For example, one aspect includes past server workload, such as, for example, file access statistics and controller and network utilization statistics. The loading prediction mechanism can use these statistics (with an appropriate filter applied) to generate predictions for future loading. For example, a straightforward prediction can include recognizing that a file that has experienced heavy sequential read activity in the past few minutes will likely continue to experience heavy sequential read access for the next few minutes.

[**0510**] Predictions for future workload can be used to proactively manage resources to optimize loading. Mechanisms that can be used to reallocate server workload include the movement and replication of content (files or objects) between the available storage elements such that controller and storage utilization is balanced, and include the direction of client accesses to available controllers such that controller and network utilization is balanced. In one embodiment, some degree of cooperation from client machines can provide effective load balancing, but client cooperation is not strictly needed.

[**0511**] Embodiments of the invention include a distributed file server (or servers) comprising a number of hardware resources, including controllers, storage elements such as disks, network elements, and the like. Multiple client machines can be connected through a client network or communication fabric to one or more server clusters, each of which includes of one or more controllers and a disk storage pool.

[**0512**] File system software resident on each controller can collect statistics regarding file accesses and server resource utilization. This includes information of the access frequency, access bandwidth and access locality for the individual objects stored in the distributed file, the loading of each controller and disk storage element in terms of CPU utilization, data transfer bandwidth, and transactions per second, and the loading of each network element in terms of network latency and data transfer bandwidth.

[**0513**] The collected statistics can be subjected to various filter operations, which can result in a prediction of future file and resource utilization (i.e. workload). The prediction can also be modified by server configuration data which has been provided in advance, for example, by a system administrator, and explicit indications regarding future file and/or resource usage which may be provided directly from a client machine.

[**0514**] The predicted workload can then be used to move content (files, objects, or the like) between storage elements and to direct client accesses to controllers in such a manner that the overall workload is distributed as evenly as possible, resulting in best overall load balance across the distributed file storage system and the best system performance.

[**0515**] The predicted workload can be employed to perform client network load balancing, intra-cluster storage load balancing, inter-node storage load balancing, intra-node storage capacity balancing, inter-node storage capacity balancing, file replication load balancing, or the like.

[**0516**] Client network load balancing includes managing client requests to the extent possible such that the client load presented to the several controllers comprising a server cluster, and the load presented to the several client network ports within each is evenly balanced. Intra-cluster storage load balancing includes the movement of data between the disks connected to a controller cluster such that the disk bandwidth loading among each of the drives in an array, and the network bandwidth among network connecting disk arrays to controllers is balanced. For example, intra-cluster storage load balancing can be accomplished by moving relatively infrequently accessed files or objects. Intra-cluster storage load balancing advantageously achieves uniform bandwidth load for each storage sub-network, while also achieving uniform bandwidth loading for each individual disk drive.

[**0517**] Inter-node storage load balancing comprises the movement of data between drives connected to different controller clusters to equalize disk access load between controllers. This can often cost more than intra-node drive load balancing, as file data is actually copied between controllers over the client network. Intra-node storage capacity balancing comprises movement of data between the disks connected to a controller (or controller pair) to balance disk storage utilization among each of the drives.

[0518] Inter-node storage capacity balancing comprises movement of data between drives connected to different controllers to equalize overall disk storage utilization among the different controllers. This can often cost more than intra-node drive capacity balancing, as file data is actually be copied between controllers over the network. File replication load balancing comprises load balancing through file replication as an extension of inter-node drive load balancing. For example, high usage files are replicated so that multiple controller clusters include one or more that one local (read only) copy. This allows the workload associated with these heavily accessed files to be distributed across a larger set of disks and controllers.

[0519] Based on the foregoing, embodiments of the present invention include a distributed file storage system that proactively positions objects to balance resource loading across the same. As used herein, load balancing can include, among other things, capacity balancing, throughput balancing, or both. Capacity balancing seeks balance in storage, such as the number of objects, the number of Megabytes, or the like, stored on particular resources within the distributed file storage system. Throughput balancing seeks balance in the number of transactions processed, such as, the number of transactions per second, the number of Megabytes per second, or the like, handled by particular resources within the distributed file storage system. According to one embodiment, the distributed file storage system can position objects to balance capacity, throughput, or both, between objects on a resource, between resources, between the servers of a cluster of resources, between the servers of other clusters of resources, or the like.

[0520] The distributed file storage system can proactively position objects for initial load balancing, for example, to determine where to place a particular new object. While existing server loading is a factor used in the determination, other data can be used to help predict the access frequency of the new object, such as, for example, file extensions, DV access attributes, or the like. For example, a file extension indicating a streaming media file can be used to predict a likely sequential access to the same.

[0521] The distributed file storage system actively continues load balancing for the existing objects throughout the system using load balancing data. For capacity load balancing, large objects predicted to be infrequently accessed, can be moved to servers, which for example, have the lower total percent capacity utilizations. Movement of such files advantageously avoids disrupting throughput balancing by moving predominantly infrequently accessed files. For throughput balancing, objects predicted to be frequently accessed can be moved to servers, which for example, have the lower total percent transaction utilizations. In one embodiment, smaller objects predicted to be frequently accessed can be moved in favor of larger objects predicted to be frequently accessed, thereby advantageously avoiding the disruption of capacity balancing.

[0522] According to one embodiment, one or more filters may be applied during initial and/or active load balancing to ensure one or a small set of objects are not frequently transferred, or churned, throughout the resources of the system.

[0523] The distributed file storage system can comprise resources, such as a server or server, which can seek to balance the loading across the system by reviewing a collection of load balancing data from itself, one or more of the other servers in the system, or the like. The load balancing data can include object file statistics, server profiles, predicted file accesses, historical statistics, object patterns, or the like. A proactive object positioner associated with a particular server can use the load balancing data to generate an object positioning plan designed to move objects, replicate objects, or both, across other resources in the system. Then, using the object positioning plan, the resource or other resources within the distributed file storage system can execute the plan in an efficient manner.

[0524] According to one embodiment, the generation of the positioning plan can be very straightforward, such as, for example, based on object sizes and historical file access frequencies. Alternatively, the generation of the plan can be quite complex, based on a large variety of load balancing information applied to predictive filtering algorithms, the output of which is a generally more accurate estimate of future file accesses and resource usage, which results in more effective object positioning. Another embodiment can include adaptive algorithms which track the accuracy of their predictions, using the feedback to tune the algorithms to more accurately predict future object access frequencies, thereby generating effective object positioning plans.

[0525] According to one embodiment, each server pushes objects defined by that server's respective portion of the object positioning plan to the other servers in the distributed file storage system. By employing the servers to individually push objects based on the results of their object positioning plan, the distributed file storage system provides a server-, process-, and administrator-independent automated approach to object positioning, and thus load balancing, within the distributed file storage system.

[0526] To facilitate a complete understanding of exemplary load balancing aspects of the invention, this part of the detailed description describes the invention with reference to FIGS. **39-41**, wherein like elements are referenced with like numerals throughout.

[0527] **FIG. 39** depicts an exemplary embodiment of servers and disk arrays of a distributed file storage system (DFSS) **3900**, disclosed for the purpose of highlighting the distributed proactive object positioning aspects of an exemplary embodiment of the invention. A skilled artisan will recognize **FIG. 39** is not intended to limit the large number of potential configurations of servers and disk arrays encompassed by the foregoing distributed file storage system **100** disclosed with reference to **FIG. 1**. As shown in **FIG. 39**, the DFSS **3900** comprises five nodes formed into three clusters **3905**, **3910**, and **3915**. Cluster **3905** includes a first node comprising server F1 and a disk array **3920**, and a second node comprising server F2 and a disk array **3922**. Cluster **3910** includes one node comprising server F3 and a disk array **3924**. Additionally, cluster **3915** includes a first node comprising server F4 and a disk array **3926**, and a second node comprising server F5 and a disk array **3928**.

[0528] According to one embodiment, each of the servers F1, F2, F3, F4, and F5 comprises software, hardware, and communications similar to the servers **130-135** disclosed with reference to **FIGS. 1 and 2**. For example, server F1 communicates with each drive of the disk array **3920**. Additionally, server F1 forms part of cluster **3905**. According to one embodiment, at least some of the objects stored on a disk array within a cluster, are stored, and are thereby

accessible, on other disk arrays within the cluster. For example, server F1 can be configured to communicate with each drive of the disk array **3922**. Server F1 also communicates with one or more of the other servers of the DFSS **3900**. Moreover, the servers F1, F2, F3, F4, and F5 include software and hardware systems which employ some or all of the features of the distributed file storage system **100**, such as, for example, the disclosed use of metadata structures for object organization, metadata and data caching, and the like.

[**0529**] **FIG. 39** also shows exemplary self-explanatory attributes of each of the drives of the disk arrays **3920-3928**. For example, the drives of the disk array **3920** include two high speed drives having small storage capacity, e.g., "FAST, SMALL," one drive having high speed and average storage capacity, e.g., "FAST, AVERAGE," and one drive having average speed and large storage capacity, e.g., "AVERAGE, LARGE." Additionally, **FIG. 39** shows servers F3 and F4 providing access to a resource, such as, for example, a printer, scanner, display, memory, or the like. A skilled artisan will recognize from the disclosure herein that the speed of a drive includes its ordinary meaning as well as a measure of the data rate, or the like, of read or write operations.

[**0530**] According to one embodiment, the DFSS **3900** includes proactive object positioning. For example, each server F1-F5 of the DFSS **3900** proactively positions objects, such as files, directories, or the like, based on a desire to balance or optimize throughput, capacity, or both. According to one embodiment, the foregoing balancing and optimization can advantageously occur at multiple levels within the DFSS **3900**. For example, the DFSS **3900** can advantageously seek to optimize the placement and structure of objects within and between disks of the disk arrays, between the servers of a cluster and between servers of other clusters.

[**0531**] Load Balancing Within and Between the Drives of the Disk Arrays

[**0532**] Similar to the embodiments disclosed with reference to **FIGS. 1 and 5**, the DFSS **3900** provides the server F1 with the ability to adjust the file logical block size and the distribution of files across multiple drives using, for example, the Gee Table **320**. Thus, the server F1 can adjust or choose the layout of particular files within a disk, using, for example, larger file logical block sizes for larger files, or the like, thereby creating efficient storage of the same. Moreover, the server F1 can adjust or choose the layout of particular files across varying numbers of disks, thereby matching, for example, performance of drives within the disk array **3920** with attributes of particular files.

[**0533**] For example, **FIG. 39** shows the placement of two files within the DFSS **3900**, e.g., streamed file "SF" and large file "LF." According to the exemplary embodiment, file "SF" comprises a file which is to be streamed across computer networks, such as, for example, the Internet. As shown in **FIG. 39**, file SF is stored in the disk array **3920** using a distributed parity group of three blocks, e.g., two data blocks, "SF_1," and "SF_2," and one parity block "SF_3." Similar to the foregoing description of distributed file storage system **100**, the DFSS **3900** advantageously allows files to modify the number of drives in the distributed parity group for a variety of reasons, including to take advantage of attributes of a disk array. Thus, when it is determined that it is desirable to store file SF on only fast disk drives, the distributed parity group can be chosen such that file SF is stored on the fastest drives of disk array **3920** in equally shared portions. A skilled artisan will recognize from the disclosure herein that the servers advantageously balance the desire to employ the faster drives of a particular disk array, against the desire to reduce the overhead associated with using smaller parity groups. For example, according to some embodiments, use of only two disks of five disks means that half of the data stored is overhead parity data.

[**0534**] **FIG. 39** also shows that in the disk array **3922**, file SF', a copy of file SF, can be stored according to the attributes of the disk array **3922**, e.g., file SF' is stored using a distributed parity group of two because the disk array **3922** has only two fast drives. Moreover, **FIG. 39** shows file LF stored in the disk array **3924**. According to the exemplary embodiment, file LF is stored is using distributed parity groups of three blocks, thereby fully taking advantage of all three very fast drives.

[**0535**] Thus, the server F1 advantageously and proactively can adjust the placement and structure of objects, such as files, within and between drives of the disk array **3920**. A skilled artisan will recognize that such proactive placement is outside the ability of conventional data storage systems. For example, as disclosed with reference to FIGS. **14-16**, the DFSS **3900** advantageously includes a directory and file handle lookup process which allows the clients **110** to find files without first knowing which server is currently storing the file. Thus, when one of the servers of the DFSS **3900** repositions an object to balance load, capacity, or the like, the clients **110** can use the lookup process to find the repositioned object in its new location.

[**0536**] Load Balancing Between Servers of a Cluster

[**0537**] As disclosed in the foregoing, one embodiment of the DFSS **3900** seeks to balance the loading and capacity between servers of a cluster. As disclosed with reference to the embodiments of **FIGS. 1 and 13-14**, the clients **110** request data from a file through the use of the file handle **1300**, which according to one embodiment, includes the server identification **1320**. Thus, the DFSS **3900** can advantageously alter the server identification **1320** of the file handle **1300** for a particular file, thereby changing the read or write request from being processed by, for example, server F1 to, for example, server F2. A skilled artisan will recognize a wide number of reasons for making the foregoing alteration of the file handle **1300**, including the availability of F1, the load of F1 versus F2, or the like. In addition, the DFSS **3900** can alter the file handle **1300** based on comparisons of server load balancing data, to set up read-only copies of heavily accessed files, or the like, as discussed below.

[**0538**] Load Balancing Between Servers of Other Clusters

[**0539**] Load balancing between servers differs from load balancing between drives in, among other things, load balancing between servers involves balancing through the movement or creation of additional copies of objects, while load balancing between drives involves the movement of data blocks.

[**0540**] One embodiment of the DFSS **3900** comprises servers F1-F5 each having access to load balancing data from itself and each of the other servers. According to one

embodiment, each server uses the load balancing data to generate an object positioning plan, and then pushes objects defined by their respective portion of the plan, to other servers in the DFSS **3900**. The foregoing implementation provides a distributed and server-independent approach to object positioning within the DFSS **3900**. It will be understood by a skilled artisan from the disclosure herein that resources, or groups of resources, can gather load balancing data, such as, for example, each, some, or all clusters, each, some, or all servers, or the like.

[**0541**] According to one embodiment, the load balancing data of a particular server can include a wide variety of statistical and attribute data relating to the architecture and performance of the respective server and disk array. Additional statistical information can be maintained relating to the historical object access frequencies and patterns. This statistical information can be applied to a filtering function to predict future object frequencies and patterns.

[**0542**] The load balancing data can include relatively static information, such as, for example, the number of servers for a given cluster and the number of drives connected to each server. Moreover, for each server, the load balancing data can include an indication of the number and type of interfaces available to the server, performance statistics of the server, amount of available memory, an indication of the health of the server, or the like. For each drive, the load balancing data can include an indication of the layout of the drive, such as track information, cylinder information, or the like, capacity and performance information, performance statistics, an indication of the health of the drive, or the like. Additionally, the load balancing data can include an indication of the performance and the health of storage network configurations, client network configurations, or the like. The relatively static load balancing data can be considered the "profile" of the resources associated therewith.

[**0543**] Other relatively static information can include an indication of the quality of service being demanded by the clients **110** from a particular server, such as, for example, server F**1** and its associated disk array **3920** can be configured to provide data availability with little or no downtime, thereby allowing the server to support Internet hosting applications or the like. Additionally, the foregoing relatively static statistical or attribute information can change occasionally, such as, for example, when a drive is replaced or added, a server is reconfigured, the quality of service is changed, or the like.

[**0544**] According to yet another embodiment, the load balancing data can also include relatively dynamic information, such as, for example, throughput information like the number of read or write input/output operations per second (IOPS). For example, the dynamic information can include server throughput for each server, such as, for example, client transactions per second, client megabytes per second, disk transaction per second, disk megabytes per second, or the like. The foregoing server throughput information can include read, write, or both operations for each client interface of the particular server. The server throughput data also includes dynamic information such as the cache hit ration, errors, or the like, of each particular server. The dynamic information can also include disk throughput for each disk, such as, for example, an indication of the amount of metadata capacity that is being utilized, the amount of data capacity utilized, read, write, or both transactions per second, read, write, or both megabytes per second, errors or the like.

[**0545**] In addition to the foregoing data, the load balancing data includes object statistic information, such as, for example, the last access time and the access frequency for each object. According to one embodiment, the measurement of access frequency can be filtered using one or more filtering weights designed to emphasize, for example, more recent data over more historical data.

[**0546**] According to one embodiment, each server may include file statistical information in the load balancing data, comprising additional information for the more heavily accessed, and potentially smaller, objects. For example, the file statistical information can include an indication of access frequency for, for example, the last ten (10) minutes, one (1) hour, twenty-four (24) hours, or the like. Moreover, the file statistical information can include average read block size, average write block size, access locality, such as a indication of randomness or sequentialness for a given file, histogram data of accesses versus day and time, or the like. According to one embodiment, the indication of randomness can include randomness rating, such as, for example, a range from 0 and 1, where 0 corresponds to primarily randomly accessed file and one corresponds to a primarily sequentially accessed file, or vice versa.

[**0547**] Based on the above, the load balancing data for a given server can include virtually any information, performance or attribute statistic, or the like that provides insight into how objects, such as files and directories, should be created, reconfigure, moved, or the like, within the DFSS **3900**. For example, a skilled artisan can include additional information useful in the prediction of file access frequencies, such as, for example, the time of day, the file size, the file extension, or the like. Moreover, the additional information can include hints corresponding to dynamic volume access attributes, such as, for example, block size, read/write information, the foregoing quality of service guarantees or the randomness/sequentialness of file access.

[**0548**] According to one embodiment, the load balancing data can include a Least Recently Used (LRU) stack and/or a Most Recently Used (MRU) stack, advantageously providing insight into which objects can be used for balancing capacity, throughput, or both, within the DFSS **3900**. For example, according to one embodiment, the LRU stack tracks the objects that are rarely or infrequently accessed, thereby providing information to the servers about which objects can be mostly ignored for purposes of throughput balancing, and are likely candidates for capacity balancing. The MRU stack tracks the objects that are more frequently accessed, thereby providing information to the servers about which objects are highly relevant for throughput balancing. According to one embodiment, the servers F**1**-F**5** can employ the MRU stack to determine the objects, on which the servers should be tracking additional performance statistics used in more sophisticated load balancing or sharing solutions, as discussed in the foregoing.

[**0549**] A skilled artisan will recognize from the disclosure herein that the MRU and LRU stacks can be combined into a single stack or other structure tracking the frequency of access for some or all of the objects of the servers F**1**-F**5**. A

skilled artisan will also recognize from the disclosure herein that the time frame chosen for determining frequency of use for a given object affects the throughput and capacity balancing operations. For example, if the time frame is every twelve hours, the number of objects considered to be frequently accessed may be increased as compared to a time frame of every half-second. According to one embodiment, the DFSS **3900** uses an adaptive time frame of ten (10) minutes to twenty-four (24) hours.

[**0550**] Although the load balancing data is disclosed with reference to its preferred embodiment, the invention is not intended to be limited thereby. Rather, a skilled artisan will recognize from the disclosure herein a wide number of alternatives for the same. For example, the load balancing data can include detailed performance statistics similar to those disclosed above. On the other hand, the load balancing data can include only a few data points providing only a rough sketch of the throughput and capacity on a particular server. Moreover, the server may track access frequency using information contained in the G-Node of an object, such as, for example, the last access time, or "atime," field.

[**0551**] **FIG. 40** illustrates a block diagram of an exemplary server **4000**, such as the servers F1-F5 of **FIG. 39**, according to aspects of an exemplary embodiment of the invention. As shown in **FIG. 40**, the server **4000** include a server interface **4005**, a server software or file system **4010**, load balancing data **4020**, and an object positioning plan **4025**. The server interface **4005** passes data access requests from, for example, the clients **110**, to the file system **4010**. The server interface **4005** includes a server manager **4008**, which collects client access statistics, such as transactions per second per client, per port, and per server, and megabytes per second per client, per port, and per server. The server system **4010** includes several layers that participate in statistics collection. For example, the server system **4010** includes a request processing layer **4012**, a data/metadata management layer **4014**, and a storage management layer **4016**. The request processing layer **4012** collects the statistics related to accesses to specific files. The data/metadata management layer **4014** collects drive resource and capacity utilization information. The storage management layer **4016** collects statistics related to transactions per second and megabytes per second for each storage network interface and drive.

[**0552**] **FIG. 40** also shows that each server **4000**, such as the servers F1-F5 of **FIG. 39**, includes a proactive object positioner **4018**, according to aspects of an exemplary embodiment of the invention. According to one embodiment, the positioner **4018** comprises a set of rules, a software engine, or the like, employing logic algorithms to some or all of the load balancing data **4020** to generate the object positioning plan **4025**.

[**0553**] As disclosed in the foregoing, the servers F1, F2, F3, F4, and F5, each share their respective load balancing data with one another. Thus, the load balancing data **4020** comprises load balancing data from the particular server, in this example, server F3, and the load balancing data from each of the other servers, F1-F2 and F4-F5. According to one embodiment, a server transmits its load balancing data at predetermined time intervals. According to another embodiment, each server determines when a significant change or a time limit has expired since the last broadcast of its load balancing data, and then broadcasts the same.

[**0554**] As shown in **FIG. 40**, each server **4000** includes the proactive object positioner **4018**, which accepts as an input, the load balancing data of the some or all of the servers, and generates as an output, the object positioning plan **4025**. According to one embodiment, the proactive object positioner **4018** for a given server generates a plan for that server. The server then attempts to push objects found in the plan to the other servers in the DFSS **3900** to balance throughput, capacity, or both. According to another embodiment, the proactive object positioner **4018** for a given server generates the plan **4025**, which is relevant to all servers. In such a case, the server attempts to push only its objects from the plan **4025** to other servers. Thus, each server in the DFSS **3900** acts independently to accomplish the plan **4025** of the entire DFSS **3900**, thereby advantageously providing a distributed and balanced approach that has no single point of failure and needing, if any, only minimal supervision.

[**0555**] As discussed in the foregoing, the object positioner **4018** corresponding to each server in the DFSS **3900** can generate the positioning plan **4025** to position objects to balance capacity, throughput, or both.

[**0556**] Positioning to Balance Capacity, Such as the Number or Size of Objects

[**0557**] According to one embodiment, the proactive object positioner **4018** for each server can instruct its server to balance the number of objects stored on some or each disk array of the DFSS **3900**. For example, as disclosed with reference to **FIG. 5**, each server has a predefined amount of memory for caching the G-nodes of the objects stored on the disk array associated with that server. By balancing the number of objects related to a particular server, the DFSS **3900** advantageously avoids having more G-node data for a server than can be stored in that server's G-node memory cache.

[**0558**] According to one embodiment, the proactive object positioner **4018** for each server can instruct its server to balance the size of objects stored on some or each disk array of the DFSS **3900**. For example, if a particular server is associated with a disk array having a large number of small objects stored therein, the server can exceed that server's G-node memory cache. Therefore, each proactive object positioner **4018** can instruct its server to push objects such that the size of objects accessible by each server is balanced. For example, the servers can evenly distribute the number of small objects, the number of medium-sized objects, and the number of large objects between servers. By balancing the size of objects related to a particular server, the DFSS **3900** reduces the chances of having more G-node data for a server than can be stored in that server's G-node memory cache.

[**0559**] According to yet another embodiment, the proactive object positioner **4018** for each server can instruct its server to optimize the number of free and used data blocks when the servers in the DFSS **3900** have a large average object size. In such case, the number of G-nodes and the G-node memory cache will not likely be a performance issue, although number of used versus free data blocks will likely be an issue. While used versus free data blocks need not be entirely uniform across servers, maintaining a certain level of unused block capacity for each server provides flexibility in throughput balancing and new object creation, thereby enhancing the performance of the overall DFSS **3900**.

[0560] Positioning to Balance Throughput, Such as the Access Frequency of Objects

[0561] According to one embodiment, the proactive object positioner **4018** generates the positioning plan **4025** to position objects based on, for example, predicted access frequencies of the same. As discussed above, prediction may comprise historical data, and may comprise a number of other data and factors as well. The positioner **4018** can advantageously use objects predicted to be infrequently accessed for capacity balancing to avoid upsetting any throughput balancing already in place. For example, when the positioner **4018** determines to balance the capacity among resources of the DFSS **3900**, such as, for example, a drive, disk array, or server, the positioner **4018** can move objects that are of little significance to the throughput of the resource, such as, for example, those objects predicted to be least accessed. Thus, as the positioner **4018** balances the capacity through objects predicted to be, or found to be least recently accessed, the respective throughput of the resources will not be substantially affected. According to one embodiment, each server tracks the objects predicted to be infrequently used by maintaining in their load balancing data, an LRU stack of, for example, pointers to the G-Nodes of the objects predicted to be infrequently accessed.

[0562] Additionally, the positioner **4018** can generate the positioning plan **4025** to move objects predicted to be infrequently accessed from faster drives to slower drives. For example, if the large file LF from **FIG. 39** were predicted to be infrequently accessed, storage of file LF on the fastest drives of the DFSS **3900**, for example, the drives of the disk array **3924**, would be inefficient. Thus, the proactive object positioner **4018** determines that the large file LF predicted to be infrequently accessed can be advantageously stored on the slow, large drives of the disk array **3926** of server F**4**. A skilled artisan will recognize that movement of the file LF to servers F**4** is not expected to substantially affect the throughput of servers F**3** and F**4**, outside of the processes for moving the file LF.

[0563] Additionally, the proactive object positioner **4018** can use the MRU stack in a server's load balancing data to instruct an overburdened server to take actions to offload some of the access from itself to those servers with less throughput. For example, the positioner **4018** can generate instructions to move the objects predicted to be heavily accessed to other servers, thereby moving the entire throughput load associated therewith, to the other servers. Also, positioner **4018** can generate instructions to create copies of objects predicted to be heavily accessed on other servers, thereby sharing the throughput load with the other servers.

[0564] For example, according to one embodiment, the server F**1** includes the streamed file SF predicted to be heavily accessed, which in this example may include extremely popular multimedia data, such as, for example, a new video or music release, a major news story, or the like, where many clients are requesting access of the same. Moreover, according to this embodiment, the server F**1** is being over-utilized, while the server F**3** is being under-utilized. Thus, the object positioner **4018** recognizes that the movement of the file SF to the server F**3** may simply overload the server F**3**. According to one embodiment, the proactive object positioner **4018** can instruct the server F**1** to push, for example, read-only copies of the file SF to the server F**3**. Moreover, a skilled artisan will recognize from the disclosure herein that the server F**1** can then return to a requesting client, a file handle **1300** for the file SF designating server F**3**, and the client will then generate requests to server F**3**, instead of server F**1**. Accordingly, the over utilization of server F**1** is advantageously decreased while the under utilization of server F**3** is advantageously increased, thereby balancing the throughput across the DFSS **3900**.

[0565] According to yet another embodiment, the proactive object positioner **4018** can generate instructions to move objects to match the attributes of resources available to a particular server, thereby potentially decreasing the response time of the DFSS **3900**. For example, as illustrated in the foregoing embodiment, the object positioner **4018** can instruct the server F**1** to push the file SF predicted to be heavily accessed, to the server F**3** having very fast disk drives, even when the server F**1** is not being over-utilized. Moreover, as discussed above, the positioner **4018** can instruct the server F**3** to store the file in distributed parity groups matching the number of very fast drives.

[0566] According to one embodiment, one or more of the servers can include specific software and hardware solutions, such as dedicated digital signal processors, which can add additional horse power to the generation of the object positioning plan **4025**. For example, load balancing can be performed by an external client connected to the DFSS **3900**.

[0567] **FIG. 41** depicts the object positioning plan **4025** of server F**3** of **FIG. 39**, according to aspects of an exemplary embodiment of the invention. As shown in **FIG. 41**, the plan **4025** includes instructions to push an object, and instructions on how to handle subsequent client requests for access to that object. According to one embodiment, a server that pushes an object tells clients seeking access to the object that the object has been moved. The pushing server can maintain a cache of objects that it recently pushed, and when feasible, the pushing server will supply the requesting client with the location, or server, where the object was moved, thereby providing direct access to the object for the client.

[0568] As shown in **FIG. 41**, the plan **4025** calls for server F**3** to push the large file LF to server F**4** for storage thereon, thereby freeing the fastest drives in the DFSS **3900** to store more objects predicted to be more heavily accessed. Moreover, the plan **4025** includes an indication that server F**3** will return an indication of staleness for any clients still caching the file handle of file LF designating server F**3**. The plan **4025** also indicates that if server F**1** requests, server F**3** will accept and store a copy of the streamed file SF and return an indication of file creation to server F**1**, such as, for example, the file handle of server F**3**'s copy of file SF. Thus, the DFSS **3900** uses a pushing approach to ensure server independence in proactively placing objects.

[0569] Based on the foregoing disclosure related to FIGS. **39-41**, a skilled artisan will recognize the vast scalability of the DFSS **3900**. For example, adding or removing hardware components such as drives, resources, or even servers, simply causes updated, or sometimes additional, load balancing information to be broadcast to the other servers. Each server then can immediately generate new positioning plans to take full advantage of the new components or configuration of the DFSS **3900**. Each server then pushes their

respective objects throughout the DFSS **3900**, thereby efficiently balancing the throughput, capacity, or both, of the same.

[**0570**] Although the foregoing invention has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. For example, the DFSS **3900** may advantageously push new file handles to clients, such as, for example, file handles including information on the location of an object. According to another embodiment, the DFSS **3900** can advantageously allow servers who have pushed objects to other servers, to automatically suggest new file handles to requesting clients. However, this approach can have the drawback that the file handle stored by the old server can itself be outdated, for example, when the new server subsequently pushed the same object to yet another server. Thus, according to one embodiment, servers return indications of staleness for objects they not longer have stored on their respective disk arrays.

[**0571**] In addition, a skilled artisan will recognize from the disclosure herein that many of the balancing ideas can be implemented in conventional non-distributed file storage systems. For example, the method of moving infrequently accessed files to balance capacity so as not to upset balanced load can be incorporated into conventional data storage systems.

[**0572**] Data Flow Architecture

[**0573**] Each server **130-135** in the DFSS **100** includes storage controller hardware and storage controller software to manage an array of disk drives. For example, the servers **130-131** each manage data on the disk arrays **140** and **141**. A large number of disk drives can be used, and the DFSS **100** can be accessed by a large number of client machines **110**. This potentially places a large workload on the servers **130-135**. It is therefore desirable that the servers **130-135** operate in an efficient manner to reduce the occurrence of bottlenecks in the storage system.

[**0574**] Prior art approaches for storage servers tend to be software intensive. Specifically, a programmable CPU in the server becomes involved in the movement of data between the client and the disks in the disk array. This limits the performance of the storage system because the server CPU becomes a bottleneck. While prior approaches may have a certain degree of hardware acceleration, such as XOR parity operations associated with RAID, these minimal acceleration techniques do not adequately offload the server CPU.

[**0575**] **FIG. 42** shows an architecture for a server, such as the server **130**, that reduces loading on a CPU **4205** of the server **130**. As shown in **FIG. 42**, the clients **110** communicate (over the network fabric **120**, not shown) with one or more network interfaces **4214**. The network interfaces **4214** communicate with a first I/O bus **4201** shown as a network bus. The network bus communicates with the CPU **4205** and with a data engine **4210**. A first data cache **4218** and a second data cache **4220** are provided to the data engine **4210**. A metadata cache **4216** is provided to the CPU **4205**. The CPU **4205** and the data engine **4210** also communicate with a second I/O bus **4202** shown as a storage bus. One or more storage interfaces **4212** also communicate with the second bus **4202**.

[**0576**] The storage interfaces **4212** communicate with the disks **140, 141**. In one embodiment, the first I/O bus **4201** is a PCI bus. In one embodiment, the second I/O bus **4202** is a PCI bus. In one embodiment, the caches **4216, 4218**, and **4220** are non-volatile. In one embodiment, the network interfaces **4214** are Fibre Channel interfaces. In one embodiment, the storage interfaces **4212** are Fibre Channel interfaces. The data engine **4210** can be a general-purpose processor, a digital signal processor, a Field Programmable Gate Array (FPGA), other forms of soft or hard programmable logic, a custom ASIC, etc. The network interface controllers **4214, 4212** can support Fibre Channel, Ethernet, Infiniband, or other high performance networking protocols.

[**0577**] The architecture shown in **FIG. 42** allows data to be efficiently moved between the client machines **110** and disks **140-141** with little or no software intervention by the CPU **4205**. The architecture shown in **FIG. 42** separates the data path from the control message path. The CPU **4205** handles control, file system metadata, and housekeeping functions (conceptually, the CPU **4205** can be considered as a control engine). Actual file data passes through the data engine **4210**.

[**0578**] Control messages (e.g. file read/write commands from clients) are routed to the CPU **4205**. The CPU **4205** processes the commands, and queues data transfer operations to the data engine **4210**. The data transfer operations, once scheduled with the data engine **4210** can be completed without further involvement of the CPU **4205**. Data passing between the disks **140, 141** and the clients **110** (either as read or write operations) is buffered through the data cache **4218** and/or the data cache **4220**. In one embodiment, the data engine **4210** operates using a data flow architecture that packages instructions with data as the data flows through the data engine **4210** and its associated data caches.

[**0579**] The data engine **4210** provides a separate path for data flow by connecting the network interfaces **4214** and the storage interfaces **4212** with the data caches **4218, 4220**. The data engine **4210** provides file data transfers between the network interface **4214** and the caches **4218, 4220** and between the storage interface **4212** and the caches **4218, 4220**. As an example of the data path operation, consider a client file read operation. A client read request is received on one of the network interfaces **4214** and is routed to the CPU **4205**. The CPU **4205** validates the request, and determines from the request which data is desired. The request will typically specify a file to be read, and the particular section of data within the file. The CPU **4205** will use file metadata in the cache **4216** to determine if the data is already present in one of the data caches **4218, 4220**, or if the data must be retrieved from the disks **140, 141**. If the data is in the data cache **4218, 4220**, the CPU **4205** will queue a transfer with the network interfaces **4214** to transfer the data directly from the appropriate data cache **4218, 4220** to the requesting client **110**, with no further intervention by the CPU **4205**. If the data is not in the data caches **4218, 4220**, then the CPU **4205** will queue one or more transfers with the storage interfaces **4212** to move the data from the disks **140, 141** to the data caches **4218, 4220**, again without further intervention by the CPU **4205**. When the data is in the data caches **4218, 4220**, the CPU **4205** will queue a transfer on the network interfaces **4214** to move the data to the requesting client **110**, again without further intervention by the CPU **4205**.

[0580] One aspect of the operation of the data engine **4210** is that the CPU **4205** schedules data movement operations by writing an entry onto a queue in the network interfaces **4214** or into a queue in the storage interfaces **4212**. The data engine **4210** and the network and storage interfaces **4214**, **4212** are connected by busses **4201**, **4202**. The busses **4201**, **4202** each include an address bus and a data bus. In one embodiment, the network or storage interfaces **4214**, **4212** perform the actual data movement (or sequence of data movements) independently of the CPU **4205** by encoding an instruction code in the address bus that connects the data engine to the interface. The instruction code is set up by the host CPU **4205** when the transfer is queued, and can specify that data is to be written or read to one or both of the cache memories **4218**, **4220**. In addition, the instruction code can specify that an operation such as a parity XOR operation or a data conversion operation be performed on the data while it is in transit through the data engine **4210**. Because instructions are queued with the data transfers, the host CPU can queue hundreds or thousands of instructions in advance with each interface **4214**, **4212**, and all of these instructions can be can be completed asynchronously and autonomously. As described above, once a data movement operation has been queued, the data engine **4210** offloads the CPU **4205** from direct involvement in the actual movement of data from the clients **110** to the disks **140**, **141**, and vice-versa. The CPU **4205** schedules network transfers by queuing data transfer operations on the network interfaces **4214** and the storage interfaces **4212**. The interfaces **4214** and **4212** then communicate directly with the data engine **4210** to perform the data transfer operations. Some data transfer operations involve the movement of data. Other data transfer operations combine the movement of data with other operations that are to be performed on the data in transit (e.g., parity generation, data recovery, data conversion, etc.). The processing modules in the data engine **4210** can perform five principal operations, as well as a variety of support operations. The principal operations are:

[0581] 1) read from cache

[0582] 2) write to cache

[0583] 3) XOR write to cache

[0584] 4) write to one cache with XOR write to other cache

[0585] 5) write to both caches

[0586] A typical client file read operation would proceed as follows in the server **130**:

[0587] (1) The file read command is received from the client

[0588] (2) The CPU **4205** authenticates client access and access permissions. The CPU **4205** also does metadata lookups to locate the requested data in cache or on disk.

[0589] (3) If data is not in cache, a disk read transaction is queued by sending instructions to the storage interfaces **4212**.

[0590] (4) The storage interfaces **4212** mode data from disk to the data caches **4218**, **4220**.

[0591] (5) The CPU **4205** queue a data-send transaction to the network interfaces **4214**.

[0592] (6) The network interfaces **4214** send the data to the client, completing the client read operation.

[0593] **FIG. 43** is a block diagram of the internal structure of an ASIC **4310** that is one example of a hardware embodiment of the data engine **4210**. The ASIC **4310** provides the capability for autonomous movement of data between the network interfaces **4214** and data caches **4218**, **4220**, and between the storage interfaces, **4212** and the data caches **4218**, **4220**. The involvement of the CPU **4205** is often just queuing the desired transfer operations. The ASIC **4310** supports this autonomy by combining an asynchronous data flow architecture, a high-performance data path than can operate independently of the data paths of the CPU **4205**, and a data cache memory subsystem. The ASIC **4310** also implements the parity generation functions used to support a RAID-style data protection scheme.

[0594] The data ASIC **4310** is a special-purpose parallel processing system that is data-flow driven. That is, the instructions for the parallel processing elements are embedded in data packets that are fed to the ASIC **4310** and to the various functional blocks within the ASIC **4310**.

[0595] In one embodiment, the ASIC **4310** has four principal interfaces: a first data cache interface **4318**, a second data cache interface **4320**, a first bus interface **4301**, and a second bus interface **4302**. Other versions of the ASIC **4310** can have a different number of interfaces depending on performance goals.

[0596] Data from the first data cache interface **4318** is provided to a cache read buffer **4330**, to a feedback buffer **4338**, to a feedback buffer **4340** and to a cache read buffer **4348**. Data from the second data cache interface **4320** is provided to a cache read buffer **4331**, to a feedback buffer **4339**, to a feedback buffer **4341** and to a cache read buffer **4349**.

[0597] Data is provided from the bus interface **4301** through a write buffer **4336** to a parity engine **4334**. Data is provided from the parity engine **4334** through a cache write buffer **4332** to the cache interface **4318**. Data is provided from the feedback buffer **4338** to the parity engine **4334**.

[0598] Data is provided from the bus interface **4302** through a write buffer **4346** to a parity engine **4344**.

[0599] Data is provided from the parity engine **4344** through a cache write buffer **4342** to the cache interface **4318**. Data is provided from the feedback buffer **4340** to the parity engine **4344**.

[0600] Data is provided from the bus interface **4301** through a write buffer **4337** to a parity engine **4335**. Data is provided from the parity engine **4335** through a cache write buffer **4333** to the cache interface **4320**. Data is provided from the feedback buffer **4339** to the parity engine **4335**.

[0601] Data is provided from the bus interface **4302** through a write buffer **4347** to a parity engine **4345**. Data is provided from the parity engine **4345** through a cache write buffer **4343** to the cache interface **4320**. Data is provided from the feedback buffer **4341** to the parity engine **4345**.

[0602] Data is provided from the cache read buffers **4348**, **4349** to the bus interface **4202**. Data is provided from the cache read buffers **4330**, **4331** to the bus interface **4201**.

[0603] Data transfer paths are provided between the cache interface **4218** and the bus interface **4301** and **4302**. Similarly, data transfer paths are provided between the cache

interface **4220** and the bus interfaces **4301** and **4302**. A control logic **4380** includes, in each of these data path, a processing engine that controls data movement between the respective interfaces as well as operations that can be performed on the data as it moves between the interfaces. The control logic **4380** is data-flow driven as described above.

[**0604**] In one embodiment, the bus **4201** is a PCI bus, the bus **4202** is a PCI bus, and data-transfer commands for the data engine are contained in PCI addresses on the respective buses. **FIG. 44** is a map **4400** of data fields in a 64-bit data transfer instruction to the data engine for use with a 64-bit PCI bus. A cache address is coded in bits **0-31**. A parity index is coded in bits **35-50**. An opcode is coded in bits **56-58**. A block size is coded in bits **59-61**. A PCI device address is coded in bits **62-63**. Bits **32-34** and **51-55** are unused.

[**0605**] The block size is used to select the extent of a block addressed by the parity index. This is the number of consecutive 16 kilobyte blocks that make up the parity block addressed by the parity index. In one embodiment, the block size is three bits, interpreted as follows:

block size = 0	parity block = 16 k
block size = 1	parity block = 32 k
block size = 2	parity block = 64 k
block size = 3	parity block = 128 k
block size = 4	parity block = 256 k
block size = 5	parity block = 512 k
block size = 6	parity block = 1024 k
block size = 7	parity block = 2048 k

[**0606**] In one embodiment, the bus interface **4301** is a PCI interface and the bus interface **4302** is a PCI interface. Each of these PCI interfaces includes a read control to control reads from the caches **4218** and **4220**. The read control reads data from the respective output buffers **4330**, **4331**, **4348**, and **4349** as needed. On completion of a PCI transaction, the output buffer is cleared. Each PCI interface also includes a write control to control writes to the input buffers. The write control adds an address word to the start of a data stream and control bits to each word written to the input buffer. In the case where parity is generated and data is saved, the write control: determines which cache **4218**, **4220** gets the data; assigns parity to the other cache (that is, the cache that does not receive the data); and adds control bits to the data stream. Address words are typically identical for the various input buffers, but added control bits will be different for each input buffer. For parity generation, or regeneration of lost data, the data in transit is stored in one of the feedback buffers **4338**, **4339**, **4341**, or **4340**. The feedback buffer is cleared on completion of a data stream operation.

[**0607**] As described above, each data block written to an input buffer has address and control bits inserted into the data stream. The control bits are as follows:

[**0608**] bit **0**: identifies a word as an address/control word or a data word

[**0609**] bit **1**: set to tag last word in a data stream

[**0610**] bit **2**: enable/disable XOR (enable/disable parity operations)

[**0611**] bit **3**: for an address word, specifies type of addressing as either: index addressing (for parity and regeneration data) direct addressing (for normal data)

[**0612**] For operations that include an XOR operation, the XOR destination is a "parity block" in cache (e.g., in the cache **4218** or the cache **4220**). When a parity block is addressed the address is calculated from a combination of: the parity index field from the PCI address word; the lower bits of the PCI address bus (the number depending on the block size); and the block size field from the PCI address word. Once the ASIC **4310** calculates the parity block address for the first PCI data word, this address is incremented for each subsequent data word.

[**0613**] The parity block address can be generated from the PCI address word using one of two methods. The first method is to concatenate the parity index with the lower bits of the PCI address word. The second method is to sum the parity index with the lower bits of the PCI address word. In either method, data is typically aligned to a natural boundary (e.g., 16 k blocks to a 16 k boundary, 32 k blocks to a 32 k boundary, etc.).

[**0614**] The CPU **4205** queues network transaction requests to the network interfaces **4214** and storage transaction requests to the storage interfaces **4212**. In one embodiment, the network bus **4201** is a memory-mapped bus having an address word and one or more data words (such as, for example, a PCI bus) and queuing a storage transaction request involves sending an address word and one or more data words to a selected network interface **4214**. In one embodiment, the address word includes opcode bits and address bits as shown in **FIG. 44**. The data words provide information to the selected network interface **4214** regarding what to do with the data at the specified address (e.g., where to send the data and to notify the CPU **4205** when the data has been sent). In one embodiment, the selected network interface **4214** views the data engine **4210** (e.g., the ASIC **4310**) as simply a memory to use for retrieving and storing data using addresses in the address word included in the network transaction request. In such an embodiment, the network interface **4214** does not know that the data engine **4210** is interpreting various bits of the address word as opcode bits and that the data engine **4210** is performing operations (e.g., parity operations) on the data.

[**0615**] The storage interfaces **4212** operate with the data engine **4210** (e.g., the ASIC **4310**) in a similar manner. The storage interfaces **4212** view the data engine **4210** as a memory (e.g., a simple cache). The storage interfaces **4212** communicate with the disks **140**, **141** to retrieve data from the disks and write data to the disks. The data engine **4210** takes care of assembling parity groups, computing parity, recovering lost data, etc. "Hiding" the parity calculations in the data engine **4210** offloads the parity workload from the CPU **4205**, thereby giving the CPU **4205** more time for metadata operations. Moreover, using a portion of the memory-mapped bus address word allows the CPU **4205** to send commands to the data engine **4210**, again offloading data operations from the CPU **4205**. The commands are associated with the data (by virtue of being associated with the address of the data). The network interfaces **4214** and the storage interfaces **4212** (which, themselves are typically network-type interfaces such as Fibre Channel interfaces,

SCSI interfaces, InfiniBand interfaces, etc.) are unaware of the opcode information buried in the address words. This allows standard "off-the-shelf" interfaces to be used.

[0616] In one embodiment, the CPU **4205** keeps track of the data stored in the data caches **4218** and **4220**, thus allowing the server **130** to service many client requests for file data directly from the caches **4218** and **4220** to the network interfaces **4214**, without the overhead of disk operations.

[0617] Although the foregoing description of the invention has shown, described and pointed out novel features of the invention, it will be understood that various omissions, substitutions, and changes in the form of the detail of the apparatus as illustrated, as well as the uses thereof, may be made by those skilled in the art without departing from the spirit of the present invention. Consequently the scope of the invention should not be limited to the foregoing discussion but should be defined by the appended claims.

What is claimed is:

1. A computer storage system, comprising:

a plurality of disk drives for storing distributed parity groups, each distributed parity group comprising storage blocks, said storage blocks comprising one or more data blocks and a parity block associated with said one or more data blocks, each of said storage blocks stored on a separate disk drive such that no two storage blocks from a given parity group reside on the same disk drive;

file system metadata to describe a location of each of said storage blocks;

a resource-allocation module to recognize a new disk drive hot-swapped into said plurality of disk drives during file system operation and to use said new disk drive to store one or more storage blocks.

2. The computer storage system of claim 1, wherein a size of a first distributed parity group is larger than a size of a second distributed parity group within a first file.

3. The computer storage system of claim 1, further comprising metadata to specify which disk drive in said plurality of disk drives and said new disk drive contains each storage block.

4. The computer storage system of claim 1, wherein said new disk drive is provided to a Fibre Channel network.

5. The computer storage system of claim 1, wherein a file is organized as one or more of said distributed parity groups.

6. The computer storage system of claim 1, wherein said file system metadata comprises information to specify a logical block address for each storage block in a distributed parity group.

7. The computer storage file system of claim 1, wherein an extent of a first distributed parity group of a file is larger than an extent of a second distributed parity group of said file.

8. The computer storage file system of claim **23**, further comprising a load-balancing module to distribute one or more existing storage blocks to said new disk drive.

9. A method for hot-swapping a new storage device in a storage system, comprising:

recognizing said new storage device;

adding said new disk drive to a list of previously-available storage devices to produce a list of currently-available storage devices;

determining a size of a new parity group, said size describing a number of data blocks in said new parity group;

computing a parity block for said parity group; and

storing one of said data blocks or said parity block on said new storage device.

10. The method of claim 9, further comprising storing metadata to describe a disk and logical block location of each of said data blocks and said parity block.

11. The method of claim 9, further comprising combining a first parity group having a first size and a second parity group having a second size to produce a combined parity group having a third size, wherein said third size specifies a number of data blocks that is one less than the number of currently-available storage devices.

12. The method of claim 9, wherein said new storage device comprises a disk drive.

13. The method of claim 9, further comprising: recognizing that a selected storage device has gone offline, removing said selected storage device from said list of currently-available storage devices to produce a list of remaining storage devices; reconstructing data stored on said selected storage device; storing said reconstructed data on one or more of said remaining storage devices; and updating file system metadata to facilitate locating said reconstructed data.

* * * * *