

(19) **United States**

(12) **Patent Application Publication**  
**Knight et al.**

(10) **Pub. No.: US 2021/0006621 A1**

(43) **Pub. Date: Jan. 7, 2021**

(54) **IOT CONTEXTUALLY-AWARE DIGITAL TWIN WITH ENHANCED DISCOVERY**

(52) **U.S. Cl.**

CPC ..... *H04L 67/12* (2013.01); *H04L 67/1065* (2013.01); *H04L 67/16* (2013.01); *G05B 19/048* (2013.01)

(71) Applicant: **CohesionIB**, Chicago, IL (US)

(72) Inventors: **Robert Knight**, Northfield, IL (US);  
**Nikunj Patel**, Naperville, IL (US);  
**Rick Szcodronski**, San Jose, CA (US)

(73) Assignee: **CohesionIB**, Chicago, IL (US)

(21) Appl. No.: **17/026,995**

(22) Filed: **Sep. 21, 2020**

#### Related U.S. Application Data


(63) Continuation of application No. 16/456,525, filed on Jun. 28, 2019, now Pat. No. 10,798,175.

#### Publication Classification

(51) **Int. Cl.**  
*H04L 29/08* (2006.01)  
*G05B 19/048* (2006.01)

#### (57) ABSTRACT

IoT devices within a commercial real-estate or residential building environment may be connected through networks, such as a Building Automation and Control network (BACnet). Systems and methods according to this disclosure provide automatic discovery of IoT devices and relationships in commercial real-estate and residential buildings and integration of the BACnet devices into the digital twin of the building. In some implementations, an IoT gateway is configured to translate the communication received from the BACnet to an IoT cloud platform and configured to normalize the data across the different security platforms into a consistent format which enables integration and interoperability of the different building system platforms that may otherwise be operating in isolation from each other. Systems and methods according to the present disclosure provide edge based analytics and control of IoT BACnet devices based on defining conditions and rules, and provide integration of multiple building systems in the context of commercial real-estate and residential buildings.






FIG. 1




FIG. 2


300

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8

## IOT CONTEXTUALLY-AWARE DIGITAL TWIN WITH ENHANCED DISCOVERY

**[0001]** This application is a continuation of U.S. patent application Ser. No. 16/456,525 filed Jun. 28, 2019. The present application claims priority to and the benefit of the above-identified application and the above-identified application is incorporated by reference herein in their entirety.

### FIELD

**[0002]** Aspects described herein generally relate to building automation, IoT (Internet of Things) devices, and hardware and software related thereto. More specifically, one or more aspects describe herein provide intelligent commercial real-estate and residential building systems and automation.

### BACKGROUND

**[0003]** IoT devices within a commercial real-estate building environment may be connected through networks with different wired or wireless communication protocols, such as Ethernet or Building Automation and Control network (BACnet), which is a wired communications protocol that allows the building automation and control systems to communicate back up to a network. The IoT devices within a commercial real-estate building environment may be connected to the Internet via an IoT Gateway. The IoT Gateway bridges IoT BACnet devices with the Internet by performing a communication protocol translation between the BACnet and Internet.

### SUMMARY

**[0004]** The following presents a simplified summary of various aspects described herein. This summary is not an extensive overview, and is not intended to identify required or critical elements or to delineate the scope of the claims. The following summary merely presents some concepts in a simplified form as an introductory prelude to the more detailed description provided below.

**[0005]** According to one aspect, the disclosure relates to a computer-implemented method of generating a contextually-aware digital twin of a commercial real estate or residential building. The method includes receiving information about an asset comprising one or more devices residing in one or more physical spaces associated with the commercial real-estate or residential building. The method includes determining based on an identification of the one or more devices of the asset, one or more points corresponding to a sensor or an actuator of the one or more devices. The method includes identifying, based on the one or more points, at least one controller that serves the asset via the one or more points. The at least one controller comprises a physical or logical entity. The method includes determining, one or more networks, and one or more locations associated with the asset. The method includes storing each of the asset, the one or more points, the at least one controller, the one or more networks, and the one or more locations as separate nodes of a graph representation of the commercial real estate building.

**[0006]** In some implementations, the method includes determining, based on an identification of a device connected to a network, whether the device is stored in the graph representation of the commercial real estate or residential building. In some implementations, the method includes,

based on a determination that the device is not stored in the graph database of the commercial real estate building, identifying the device as a new device. In some implementations, the method includes determining one or more points corresponding to a sensor or an actuator of the new device. In some implementations, the method includes identifying, based on the one or more points of the new device, at least one controller, at least one location, and at least one network that is associated with the new device. In some implementations, the method includes storing the one or more points, the at least one controller, the at least one location, and the at least one network associated with the new device in the graph representation of the commercial real-estate building. In some implementations, the one or more devices of the asset are connected to a Building Automation Control (BAC) network. In some implementations, the one or more locations may include a physical or logical location associated with the one or more physical spaces of the commercial real estate building. The one or more locations comprise at least one of an identification of a floor, a longitude-latitude coordinate, a space, an elevation, a zone, a space zone, and an identification of an occupant of the one or more physical spaces. In some implementations, the graph representation of the building comprises a label property graph representation. In some implementations, the points comprise at least one of a setpoint value or a schedule. In some implementations, the identifying of the at least one controller associated with the new device is based on information generated by training a machine learning algorithm on one or more previously generated graph representations of the commercial real estate building.

**[0007]** According to certain aspects of the present disclosure, a system for generating a contextually-aware digital twin of a commercial real estate building is provided. The system includes one or more processors. The system includes a memory storing computer-readable instructions that, when executed by the one or more processors, cause the one or more processors to receive information about an asset comprising one or more devices residing in one or more physical spaces associated with the commercial real estate building. The instructions cause the one or more processors to determine based on an identification of the one or more devices of the asset, one or more points corresponding to a sensor or an actuator of the one or more devices. The instructions cause the one or more processors to identify, based on the one or more points, at least one controller that serves the asset via the one or more points. The at least one controller is a physical or logical entity. The instructions cause the one or more processors to determine, one or more networks, and one or more locations associated with the asset. The instructions cause the one or more processors to store each of the asset, the one or more points, the at least one controller, the one or more networks, and the one or more locations as separate nodes of a graph representation of the commercial real estate building.

**[0008]** In some implementations, the instructions cause the one or more processors to, determine, based on an identification of a device connected to a network, whether the device is stored in the graph representation of the commercial real estate building. In some implementations, the instructions cause the one or more processors to, based on a determination that the device is not stored in the graph database of the commercial real estate building, identify the device as a new device. In some implementations, the

instructions cause the one or more processors to determine one or more points corresponding to a sensor or an actuator of the new device. In some implementations, the instructions cause the one or more processors to identify, based on the one or more points of the new device, at least one controller, at least one location, and at least one network that is associated with the new device. In some implementations, the instructions cause the one or more processors to store the one or more points, the at least one controller, the at least one location, and the at least one network associated with the new device in the graph representation of the commercial real-estate building. In some implementations, the one or more devices of the asset are connected to a Building Automation Control (BAC) network. In some implementations, the one or more locations may include a physical or logical location associated with the one or more physical spaces of the commercial real estate building. The one or more locations comprise at least one of an identification of a floor, a longitude-latitude coordinate, a space, an elevation, a zone, a space zone, and an identification of an occupant of the one or more physical spaces. In some implementations, the graph representation of the building comprises a label property graph representation. In some implementations, the points comprise at least one of a setpoint value or a schedule. In some implementations, the identifying of the at least one controller associated with the new device is based on information generated by training a machine learning algorithm on one or more previously generated graph representations of the commercial real estate building.

**[0009]** According to certain aspects of the present disclosure, a non-transitory machine readable storage medium containing machine-readable instructions for causing a processor to execute a method of generating a contextually-aware digital twin of a commercial real estate building is provided. The instructions contained on the non-transitory machine readable storage medium cause the processor to perform a method that includes receiving information about an asset comprising one or more devices residing in one or more physical spaces associate with the commercial real estate building. The method includes determining based on an identification of the one or more devices of the asset, one or more points corresponding to a sensor or an actuator of the one or more devices. The method includes identifying, based on the one or more points, at least one controller that serves the asset via the one or more points. The at least one controller comprises a physical or logical entity. The method includes determining, one or more networks, and one or more locations associated with the asset. The method includes storing, each of the asset, the one or more points, the at least one controller, the one or more networks, and the one or more locations as separate nodes of a graph representation of the commercial real estate building.

**[0010]** These and additional aspects will be appreciated with the benefit of the disclosures discussed in further detail below.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0011]** A more complete understanding of aspects described herein and the advantages thereof may be acquired by referring to the following description in consideration of the accompanying drawings, in which like reference numbers indicate like features, and wherein:

**[0012]** FIG. 1 depicts an illustrative environment in which an IoT contextually-aware digital twin with enhanced discovery is provided in accordance with one or more illustrative aspects described herein.

**[0013]** FIG. 2 shows hardware elements of a computing device that may be used to implement any of the computing devices shown in FIG. 1.

**[0014]** FIG. 3 illustrates an example process for providing an IoT contextually-aware digital twin with enhanced discovery performed by the example system shown in FIG. 1.

**[0015]** FIG. 4 illustrates another example process for providing an IoT contextually-aware digital twin with enhanced discovery performed by the example system shown in FIG. 1.

**[0016]** FIG. 5 illustrates another example process for providing IoT edge analytics and control performed by the example system shown in FIG. 1.

**[0017]** FIG. 6 illustrates an example graph schema of various entities and relationships.

**[0018]** FIG. 7 illustrates an example graph schema of the location entities.

**[0019]** FIG. 8 illustrates an example representation of an actor system in an actor model.

#### DETAILED DESCRIPTION

**[0020]** In the following description of the various embodiments, reference is made to the accompanying drawings identified above and which form a part hereof, and in which is shown by way of illustration various embodiments in which aspects described herein may be practiced. It is to be understood that other embodiments may be utilized and structural and functional modifications may be made without departing from the scope described herein. Various aspects are capable of other embodiments and of being practiced or being carried out in various different ways.

**[0021]** It is to be understood that the phraseology and terminology used herein are for the purpose of description and should not be regarded as limiting. Rather, the phrases and terms used herein are to be given their broadest interpretation and meaning. The use of “including” and “comprising” and variations thereof is meant to encompass the items listed thereafter and equivalents thereof as well as additional items and equivalents thereof. The use of the terms “mounted,” “connected,” “coupled,” “positioned,” “engaged” and similar terms, is meant to include both direct and indirect mounting, connecting, coupling, positioning, and engaging.

**[0022]** One technique for creating digital twins of commercial real-estate buildings relies on modeling the relationships between different physical entities, such as the building, floors, suites, and spaces, as parent-child relationships which, however, do not accurately capture the many-to-many relationships between these entities. As an example, a variable air volume (VAV) box connected to a VAV controller may serve four different spaces within a building. In a parent-child relationship model, the VAV box is at the parent level, the VAV controller is a child of the VAV box, and the four spaces within the building are children of the VAV controller. As another example, there may be four VAV boxes serving a single open space. In this example, one parent-child representation may have the single open space at the parent level with the 4 VAV boxes as children. In another parent-child representation, each VAV box may be a parent node with the open space as its child node. Thus,

modeling the relationships between different physical entities in a commercial building as parent-child relationships can become complex and convoluted. However, the many-to-many relationships between physical entities in a commercial building can be modeled and stored as a graph database. Some techniques use a RDF version of a graph database which stores the relationships between entities in subject-predicate-object format, and thus, cannot go as deep as, for example, a label property version of a graph database. Additionally, one technique does not represent controllers and devices as separate entities in the graph database.

**[0023]** IoT devices within a commercial real-estate building environment may be connected through networks with different wired or wireless communication protocols, such as Ethernet or Building Automation and Control network (BACnet) which is a wired communications protocol that allows the building automation and control systems to communicate back up to a network. The IoT devices within a commercial real-estate building environment may be connected to the Internet via an IoT Gateway. The IoT Gateway bridges IoT BACnet devices with the Internet by performing a communication protocol translation between the BACnet and Internet. An IoT Gateway may monitor BACnet devices by periodically polling these devices. While a pubset model has been developed so that IoT devices connected through a BACnet may publish in an asynchronous fashion, the pubset model is limited by the bandwidth of the BACnet, which has a specific baud rate and thus, there is only so much data that can be pumped onto the wire.

**[0024]** Some techniques use centralized queues for receiving data from devices or sending data to devices, which are a single point of failure, have bottlenecks, and do not prioritize messages well. Additionally, a centralized scheduler does not account for the device response time, the number of devices that can be queried within a time interval, or the aggregation of queries over time intervals (i.e. queries over 5 second, 10 second, 15 second intervals stacking on top of each other). Further, a centralized rules engine (i.e. if temperature exceeds value 'y', then change to mode value 'z') requires too much complexity to account for dynamic rules per device.

**[0025]** Systems and methods according to this disclosure provide a contextually-aware digital twin of a commercial building based on a graph database representation of entities and relationships that are important in the context of commercial buildings and spaces. Every commercial building is unique. Even though two commercial buildings may look alike, the connectivity between a device and its controller may be different between the buildings. Thus, the same device may have a different relationship to its controller in each building. Further, a device and its controller may be physically separate entities. A device such as a thermostat may be placed at a specific location because that may be the best location for the thermostat to accurately determine the temperature within a space. However, the thermostat may be communicating with a controller that is in a different location from the thermostat. As another example, a variable air volume (VAV) box is an essential part of an air conditioning system in any large industrial or commercial building. The air conditioning system is, in turn, part of a HVAC system, which encompasses heating, ventilation, air conditioning, and associated control systems. The VAV box may connect to a VAV controller that controls the opening and shutting of the VAV box dials in order to control the flow of air that is

coming into a building. The VAV box may also include a heating element. If the air entering into the building is not at a high enough temperature, the VAV controller may turn on the heating element in the VAV box to raise the temperature of the air entering the building. In complex commercial buildings and structures, the VAV controller is not necessarily synonymous with the VAV box or device. Instead, the VAV box and the VAV controller may be physically separate entities. Additionally, the VAV box and the VAV controller may be manufactured by different entities. A customer may mix and match the parts from different manufacturers. Thus, modeling the VAV controller and VAV box as different entities in the digital twin of the building is also useful for inventory tracking. Therefore, decoupling the thermostat and its controller into separate entities in the graph database provides an accurate IoT model of the building resulting in accurate queries and analytics. Thus, implementations according to this disclosure decouple devices and controllers in terms of how the cloud platform interacts with them. Implementations may store document level data by using the label property graph version of the graph database which store all or some of the properties of the device and points, which may be the registers of a controller of a device. The digital twin of a building may reside in the cloud and may track every device that is supported by the platform. The digital twin may track points, assets, controllers and network and location, including service location and installed location. Digital twins of different buildings may be integrated. The graph database and actor model allows us to integrate with other digital twins like BIM, energy models, third-party APIs, third-party building software and applications, etc. Additionally, relationships between entities may be modeled based on an understanding of how the actual physical equipment gets connected. For example, a controller may be managed by another upstream controller, thus, the data model's representation of parent-child relationships can scale. Further, implementations according to this disclosure enable data from traditionally separate subsystems to be combined. Implementations enable search and filtering and navigation based on location, type, etc. (e.g. all assets serving a specific room—and query power meter, HVAC, lighting, etc.). An energy model is typically a static model that gets created upon initial design and uses approximations for how systems will perform with a defined set of inputs. In some implementations, an energy model may be calibrated for HVAC zones based on a representation of a building's digital twin. Implementations according to this disclosure may leverage machine learning in which the inputs may be varied to model how the building will perform in an infinite number of scenarios.

**[0026]** Systems and methods according to this disclosure provide automatic discovery of IoT devices and relationships in commercial real-estate buildings and integration of the devices into the digital twin of the building. Devices may be discovered on the network based on their IP addresses. For example, BACnet devices may be discovered via the "whois" command which returns the device identifiers of BACnet devices. For example, there may be multiple different manufacturers that make VAB boxes on the market and each manufacturer may manufacture several different models. This information may be recorded in a library of devices. When a new device is discovered on the network, it may be identified based on the information recorded in the device library. Additionally, the information in the library of

devices may include relationships that may arise from an asset that includes a known device. The relationships for a device may be determined based on training a machine learning algorithm on the digital twins of various commercial real-estate buildings. If a device is known, then the relationships that come from that device may be predicted, enabling automatic creation of all or some of the related entities and relationships, thereby automatically setting up the nodes and relationships of an asset in the digital twin.

**[0027]** Systems and methods according to this disclosure provide an IoT Gateway configured to translate the communication received from the BACnet to an IoT cloud platform. Systems and methods according to this disclosure provide an IoT Gateway configured to provide normalization of big data generated by interconnected IoT in commercial real-estate buildings. A controller may have multiple registers in which the controller stores data. Each register may be identified as a separate point. However, different manufacturers may store specific types of data in the same register. Therefore, in order to enable seamless data collection and analytics, the data generated by the IoT devices and controllers may be normalized across various manufacturers and models before transmitting to a cloud platform for further processing, storage, and integration with other systems and platforms. The normalization may be performed at the API level. For example, a typical commercial real-estate building may comprise IoT devices and controllers related to multiple different security platforms that each store data in a specific manner or format. The IoT Gateway may be configured to normalize the data across the different security platforms into a consistent format which enables integration and interoperability of the different building system platforms that may otherwise be operating in isolation from each other. Additionally, the IoT Gateway may be configured to evaluate and filter the data received from the IoT devices before transmitting the data to a cloud platform for further processing and analytics, thus reducing the impact on network processing and bandwidth. Further, the IoT Gateway may be configured to perform edge based analytics and edge based control of IoT devices, including IoT BACnet devices, within a commercial real-estate building environment. In some implementations, the IoT Gateway may be configured to control the IoT devices based on evaluating incoming real-time data with rules. The IoT Gateway may be configured to perform queries and analytics based on edge computing which does not rely on network connectivity or the cloud computing resources. This enables real-time response to events without significant increase in bandwidth or processing power.

**[0028]** Systems and methods according to the present disclosure provide edge based analytics and control of IoT devices based on defining conditions and rules. For example, a rule may trigger an action based on receiving real-time data related to a supply air temperature that has exceeded a min/max alarm threshold. A windowing function may ensure that a specific number of consecutive real-time data points are received or observed before the rule is triggered. Once it is confirmed that the incoming data points sufficiently meet the relevant conditions set by the rule, automatic control of the related devices may be triggered. Representations of building systems and devices may be created using an actor model. In an actor model, a plurality of actors may receive message from other actors, perform computations, manage their state, and send messages to other actors. Actors

may correspond to devices or groups of devices related to building systems, such as HVAC, lighting, etc. For example, a sensor may communicate a measurement, such as temperature, to an actor corresponding to the sensor. The measurement may be communicated to the actor as a message. Upon receiving the message, the actor updates the stored state based on the sensor measurement. The actor representing the sensor may also receive messages from other actors for access to the latest sensor measurement. The actor may also send messages to the physical sensor device to update the device configuration. An actor that triggers a rule may query connected devices and assets to find an optimum solution based on the current situation of the system. Once data related to various solutions is received, the best option may be determined based on pre-determined constraints and settings, such as energy usage, time required, etc. In some implementations, device analytics may be provided to model expected performance of a device based on a current state, and the device may be controlled based on computations in real-time using context aware data. By maintaining a stateful machine representation of the device, the exact behavior of a device may be modeled by training a data analytics machine learning algorithm on the real-time data of the input and output data points of the device. Implementations may provide precision command and control for an infinite number of stateful scenarios of the device instead of just a handful that are included in the device's onboard controller.

**[0029]** The actor model may be implemented by a distributed computing and non-blocking framework, such as Akka. The actor model and rules may be stored in a cloud platform. In addition to hosting an actor system in the cloud, implementations may also run the actor system at the edge which avoids reliance on cloud computing and enables better real-time response. The edge device analytics may be performed on an IoT gateway.

**[0030]** Systems and methods according to this disclosure provide integration of multiple building systems in the context of commercial real-estate buildings. Typically, there may be multiple different building software platforms supporting a commercial real-estate building that are isolated from each other. Implementations according to this disclosure provide integration of previously isolated software platforms and related building systems. Integration of various building systems enable discovery of new patterns and insights into the building systems. Integration of various building systems also enables the automation of interactions between devices across various building systems.

**[0031]** FIG. 1 depicts an illustrative environment **100** in which an IoT contextually-aware digital twin with enhanced discovery is provided in accordance with one or more illustrative aspects described herein. The environment **100** includes three buildings **102a-c** (generally referred to as buildings **102**). The buildings **102** may be commercial real-estate or industrial buildings or structures. FIG. 1 shows an example building **102a**. The example building **102a** includes eight devices **110a-h** (generally referred to as devices **110**). The devices **110** may include electrical or mechanical devices associated with building automation systems (BAS) for applications such as heating, ventilating, and air-conditioning (HVAC), lighting control, access control, and fire detection. The devices **110** may include IoT "smart" devices. The devices **110** may include sensors and actuators. The devices **110** may be connected to one or more

controllers. The example building **102a** includes four controllers **113a-d** (generally referred to as controllers **113**). The controllers **113** may receive information, such as sensor data, from the devices **110**. The controllers **113** may be configured to effectuate an action via the actuators in the devices **110** based on evaluating the received sensor data. Referring to the example building **102a**, the first and second devices **110a-b** are connected to the first controller **113a**. The third and fourth devices **110c-d** are connected to the second controller **113b**. Additionally, the second controller **113b** and a fifth device **110** are connected to a third controller **113c**. In the example building **102a**, the first through fifth devices **110a-e** may be referred to as “BACnet devices” because they are connected through a Building Automation and Control network (BACnet), which is a wired communications protocol that allows communication of building automation and control systems to transmit or receive data.

[0032] In addition to the devices **110a-e** that are connected to the BACnet **112**, the example building **102a** includes a sixth device **110f** and a seventh device **110g** that are connected to a fourth controller **113d**. The sixth and seventh devices **110f-g** may communicate via an Ethernet protocol and may be referred to as “Ethernet devices.” The example building **102a** includes an IoT Gateway **125** which serves as a connection point between the devices **110** and an external network, such as network **160**. The BACnet devices **110a-d** may connect to the IoT Gateway **125** via a BACnet Interface **112**. The Ethernet devices may connect to the IoT Gateway via an Ethernet Interface **120**. An eighth device **110h** interfaces directly with the IoT Gateway **125**. The devices **110** may leverage other networking protocols. The example building **102a** may include additional devices **110** that may communicate via communications protocols, such as CoAP, DTLS MQTT, ModBus, AMQP, HTTP, HTTPS, and FTP, among others. The example building **102a** may include additional devices **110** that may communicate via wireless protocols, such as IPv6, LPWAN, Zigbee, Bluetooth Low Energy, Z-Wave, RFID and NFC.

[0033] The IoT Gateway **125** may connect the devices **110** and the controllers **113** to the Intelligent Building Cloud Platform **165** over a network **160**. The IoT Gateway **125** may be configured to bridge the BACnet devices **110** with the Internet by performing a communication translation between the BACnet and Internet communication protocols. The IoT Gateway **125** may communicate with an Intelligent Building Edge Application Platform **142**. Additionally, the IoT Gateway **125** may be configured to evaluate and filter the data received from the IoT devices before transmitting the data to a cloud platform for further processing and analytics, thus reducing the impact on network processing and bandwidth. Further, the IoT Gateway **125** may be configured to perform edge based analytics and edge based control of IoT devices **110**, including the BACnet devices **110**, within the example building **102a**. In some implementations, the IoT Gateway **125** may be configured to control the IoT devices **110** based on evaluating incoming real-time data with rules. The IoT Gateway **125** may be configured to perform queries and analytics based on edge computing which does not rely on network connectivity or the cloud computing resources. This enables real-time response to events without significant increase in bandwidth or processing power.

[0034] The Intelligent Building Edge Application Platform **142** include an Intelligent Building Edge Application

Server **140** via a communication link **130**. The Intelligent Building Edge Application Server **140** may receive data via the IoT Gateway **125** and send the data over the network **160** to the Intelligent Building Cloud Platform **165** for further processing and storage. The Intelligent Building Edge Application Server **140** may push one or more applications to configure the IoT Gateway **125** to perform various functions. Intelligent Building Edge Application Server **140** may be configured to normalize the data generated by the devices **110** and controller **113** may be normalized across various manufacturers and models before transmitting to a cloud platform, such as the Intelligent Building Cloud Application Platform **165**, for further processing, storage, and integration with other systems and platforms. The normalization may be performed at the API level. The IoT Gateway **125** of different buildings may collect data specific for that building and send the collected data to the Intelligent Building Cloud Application Server which in turn process and analyze the data further for providing recommendations. For example, implementations may include training a machine learning algorithm on the data collected across various buildings to gain insights and patterns which may then in turn be analyzed for the purpose of providing recommendations on other buildings. Data from various buildings may be crowd sourced in such implementations. The Intelligent Building Edge Application Server **140** may be configured to create and manipulate a contextually-aware digital twin for each of the buildings **102** based on a graph database representation of entities and relationships that are important in the context of commercial buildings and spaces. The Intelligent Building Edge Application Server **140** may be configured to provide automatic discovery of devices located in the buildings **102**, generate the various relationships arising from the discovered devices and integrate the discovered devices and relationships into the digital twins of the buildings **102**.

[0035] The Intelligent Building Edge Application Server **140** may be configured to perform edge based analytics and control the devices **110**. The Intelligent Building Edge Application Server **140** may be configured to generate and maintain an actor model comprising representations of building systems and devices. Actors may correspond to devices or groups of devices related to building systems, such as HVAC, lighting, etc. The Intelligent Building Edge Application Server **140** may store the generated digital twins and actor models of the buildings **102** in the Intelligent Building Cloud Platform **165**. The Intelligent Building Edge Application Server **140** may also store the digital twins and the actor models of the buildings **102** at the edge as Building Edge Data **145**. The Intelligent Building Edge Application Server **140** may be configured provide integration of multiple software platforms related to the building systems of the buildings **102** and to enable discovery of new patterns and insights into the building systems. The integration may enable the automation of interactions between the devices **110** across various building systems of the building **102a** and across the buildings **102**.

[0036] An example Building Edge Data **145a** includes an Edge Digital Twin **150** and an Edge Actor Model **155**. The Intelligent Building Edge Application Server **140** may use the Building Edge Data **145** for performing edge analytics and processing. The Intelligent Building Cloud Platform **165** includes an Intelligent Building Cloud Application Server **170** that may be configured to perform cloud analytics and processing. The Intelligent Building Cloud Platform **165**

includes a Device Library **190** and Building Data **175**. The Building Data **175** may store various information about the buildings **102**. An example Building Data **175a** includes a Historical Data **185**, a Digital Twin **180**, and an Actor Model **182**. The Historical Data **185** may include data about one of the buildings **102** that is collected over a period of time. The Intelligent Building Cloud Application Server **170** may access the Historical Data **185**, the Digital Twin **180**, and the Actor Model **182** in order to perform analytics that provide additional insights into the devices and systems of the corresponding building **102a**. The Intelligent Building Cloud Application Server **170** may store information about devices and controllers in the Device Library **190**. The IoT Gateway **125** may include a Dell **500** box with a Linux operating system, and the Intelligent Building Edge Application Server **140** may include an IoTium orchestrator using an orchestration system, such as Kubernetes. The Intelligent Building Edge Application Server **140** may include software applications developed in JavaScript or TypeScript using a Backstack library, and an akkajs or scalajs framework. Additionally, PostgreSQL database system may be used for relational data, and a message broker such as Kafka, Akka Stream, RabbitMQ, EventHub, etc. The Intelligent Building Cloud Application Platform **165** may include Azure data storage and analytics.

[0037] FIG. 2 shows hardware elements of a computing device **200** that may be used to implement any of the computing devices shown in FIG. 1 (e.g., any of the devices shown in the example building **102a**, any of the devices shown in the Intelligent Building Cloud Application Platform **165**, any devices interfacing with the external network **160**) and any other computing devices discussed herein (e.g., the Intelligent Building Cloud Application Server **170** and the Intelligent Building Edge Application Server **140** in FIG. 1). The computing device **200** may comprise one or more processors **201**, which may execute instructions of a computer program to perform any of the functions described herein. The instructions may be stored in read-only memory (ROM) **202**, random access memory (RAM) **203**, removable media **204** (e.g., a USB drive, a compact disk (CD), a digital versatile disk (DVD)), and/or in any other type of computer-readable medium or memory. Instructions may also be stored in an attached (or internal) hard drive **205** or other types of storage media. The computing device **200** may comprise one or more output devices, such as a display device **206** (e.g., an external television and/or other external or internal display device) and a speaker **214**, and may comprise one or more output device controllers **207**, such as a video processor. One or more user input devices **208** may comprise a remote control, a keyboard, a mouse, a touch screen (which may be integrated with the display device **206**), microphone, etc. The computing device **200** may also comprise one or more network interfaces, such as a network input/output (I/O) interface **210** (e.g., a network card) to communicate with an external network **209**. The network I/O interface **210** may be a wired interface (e.g., electrical, RF (via coax), optical (via fiber)), a wireless interface, or a combination of the two. The network I/O interface **210** may comprise a modem configured to communicate via the external network **209**. The external network **209** may comprise the communication links **101** discussed above, the external network **109**, an in-home network, a network provider's wireless, coaxial, fiber, or hybrid fiber/coaxial distribution system (e.g., a DOCSIS network), or any other

desired network. The computing device **200** may comprise a location-detecting device, such as a global positioning system (GPS) microprocessor **211**, which may be configured to receive and process global positioning signals and determine, with possible assistance from an external server and antenna, a geographic position of the computing device **200**.

[0038] Although FIG. 2 shows an example hardware configuration, one or more of the elements of the computing device **200** may be implemented as software or a combination of hardware and software. Modifications may be made to add, remove, combine, divide, etc. components of the computing device **200**. Additionally, the elements shown in FIG. 2 may be implemented using basic computing devices and components that have been configured to perform operations such as are described herein. For example, a memory of the computing device **200** may store computer-executable instructions that, when executed by the processor **201** and/or one or more other processors of the computing device **200**, cause the computing device **200** to perform one, some, or all of the operations described herein. Such memory and processor(s) may also or alternatively be implemented through one or more Integrated Circuits (ICs). An IC may be, for example, a microprocessor that accesses programming instructions or other data stored in a ROM and/or hardwired into the IC. For example, an IC may comprise an Application Specific Integrated Circuit (ASIC) having gates and/or other logic dedicated to the calculations and other operations described herein. An IC may perform some operations based on execution of programming instructions read from ROM or RAM, with other operations hardwired into gates or other logic. Further, an IC may be configured to output image data to a display buffer.

[0039] FIG. 3 illustrates an example process **300** for providing an IoT contextually-aware digital twin with enhanced discovery performed by the example system shown in FIG. 1. While FIG. 3 is described with reference to FIG. 1, it should be noted that the method steps of FIG. 3 may be performed by other systems.

[0040] A "thing" in the context of IoT (Internet of Things) may be a device configured to transmit or receive data through a network. Thus, a "thing" may be a sensor device transmitting sensor data to a controller and receiving control data from the controller. An IoT contextually-aware digital twin of a commercial real-estate building may be generated based on an IoT data model schema that defines various entities associated with a "thing", such as a type, network, manufacturer, controller, point, asset, and location. A type entity may be a classification of a thing. A thing may be classified based on different categories, such as its class and subclass. A network entity may be a collection of "things" that are connected through wired or wireless protocols. The wired protocol may be a BACnet protocol. A manufacturer entity may be a maker or producer of a "thing". A point may be a sensor or actuator of a device or controller that contains a digital or analog property. A point may be a configuration value, such as a setpoint value or a schedule. An asset entity may be physical equipment or an object that is located within a place, as understood by a person having skill in the art after review of the entirety disclosed herein. An asset may comprise multiple physical devices and/or points. An asset may have attributes, such as a serial number, or a manufacturer. Assets may be categorized into types and subtypes. Asset types may correspond to building systems, such as HVAC air, HVAC water, plumbing, fire protection,

electrical, and fire alarm. Each asset type may include various subtypes. An asset type corresponding to the HVAC air system may include subtypes, such as the variable air volume (VAV) box/controller, fan powered box (FPB), fan coil unit (FCU), computer room air handler (CRAH), fan system, fan, air handling unit (AHU), heat recovery unit (HRU), and heat pump. An asset type corresponding to the HVAC water system may include subtypes, such as chilled water plant, pump, heat exchanger, unit heater, baseboard heater, duct heater, boiler, and expansion tank. An asset type corresponding to the plumbing system may include subtypes, such as pump, and grease trap. An asset type corresponding to the fire protection system may include subtypes, such as pump, and pre-action. An asset type corresponding to the electrical system may include subtypes, such as meter, switchboard, panel board, generator, transfer switch, uninterruptible power supply (UPS), lighting control panel, fire alarm control panel (FACP), and remote control panel. A controller entity may be a physical or logical entity that is associated with one or more points. A controller entity may serve one or more assets through the points of the one or more assets. A location entity may be a physical or logical identification of the whereabouts of a “thing,” such as longitude-latitude coordinates, elevation, address, floor name, logical, or physical zone. The location entities may be determined based on the physical location of an asset, as well as the areas of the building that the asset serves. For example, a VAV box residing at one location may serve many other areas of the building. Location entities may have their own digital twin that defines relationships between the physical and logical locations. The digital twin of the location entities may interface with the digital twin of the asset.

[0041] The IoT data model schema enables physical devices 110 to be decoupled from their corresponding physical controllers 113 and represented as separate entities in the digital twin of the building 102a. Even though the buildings 102 may look alike, the connectivity between a device, such as a sensor device, and its controller may be different across the buildings 102. Thus, the same device 110 may have a different relationship to its controller 113 in each of the buildings 102. Further, a device and its controller may be physically separate entities. A device, such as a thermostat residing at a physical location, may communicate with a controller that is placed in a different physical location from the thermostat. The IoT data model schema enables the thermostat and its controller to be represented as different entities in the digital twin of the building. According to the IoT data model schema, the sensors and actuators of the thermostat may be mapped to one or more points, and its physical controller may be mapped to a controller entity. As another example, in complex commercial buildings and structures, a VAV controller may not be synonymous with the VAV box or device that it controls. Instead, the VAV box and its VAV controller may be physically separate entities. Additionally, the VAV box and its VAV controller may have different manufacturers, so that a customer may mix and match the parts from different manufacturers. In this case, representing the VAV controller and VAV box as different entities in the digital twin is also useful for inventory tracking. Therefore, according to the IoT data model schema, the sensors and actuators of the VAV box may be mapped to points and the VAV controller may be mapped to a controller entity. In some cases, a device may include sensors, actua-

tors, and control logic within the same physical device. According to the IoT data model schema, the sensors, actuators, and control logic of the device may be mapped to points and a logical controller entity, and thus decoupled from each other and represented as separate entities in the digital twin of the building. Decoupling devices from their corresponding controllers and representing them as separate entities provides a more accurate digital twin of the building resulting in more accurate querying and analytics.

[0042] FIG. 6 illustrates an example graph schema 600 of the various entities and relationships. The graph schema 600 includes a plurality of nodes 605a-g (generally referred to as nodes 605). The asset, type, point, location, controller, network, and manufacturer entities are represented respectively as the nodes 605a-g of the graph schema 600. The graph schema 600 includes a plurality of edges 610a-i (generally referred to as edges 610). The edges 610 represent relationships between the nodes 605 and their corresponding entities. The edges may be directional and may include properties. The relationship between the asset entity of node 605a and the type entity of node 605b is represented as an edge 610a. The direction of the edge 610a is from the asset entity of node 605a to the type entity of node 605b. The property of the edge 610a indicates that the asset entity of node 605a is a “part of” the type entity of node 605b. The nodes 605 may include properties. The property 620a of the asset entity of node 605a includes an “id” in a GUID format and a “name” in a string format. The relationship between the asset entity of node 605a and the point entity of node 605c is represented as an edge 610b. The direction of the edge 610b is from the asset entity of node 605a to the point entity of node 605c. The property of the edge 610b indicates that the point entity of node 605c “belongs to” the asset entity of node 605a. The property of the point entity of node 605c includes an “id” in a GUID format and a “name” in a string format. The relationship between the asset entity of node 605a and the location entity of node 605d is represented as the edge 610c. The direction of the edge 610c is to the asset entity of node 605a from the location entity of node 605d. The property of the edge 610c indicates that the asset entity of node 605a is “served by” the location entity of node 605d. The property 620c of the point entity of node 605c includes an “id” in a GUID format and a “name” in a string format. The relationship between the type entity of node 605b and the point entity of node 605c is represented as the edge 610d. The direction of the edge 610d is from the point entity of node 605c to the type entity of node 605b. The property of the edge 610d indicates that the point entity of node 605c is “part of” the type entity of node 605b. The relationship between the location entity of node 605d and the point entity of node 605c is represented as the edge 610e. The direction of the edge 610e is from the point entity of node 605c to the location entity of node 605d. The property of the edge 610e indicates that the point entity of node 605c is “located in” the location entity of node 605d. The relationship between the controller entity of node 605e and the type entity of node 605b is represented as the edge 610f. The direction of the edge 610f is from the controller entity of node 605e to the type entity of node 605b. The property of the edge 610f indicates that the controller entity of node 605e is “part of” the type entity of node 605b. The relationship between the controller entity of node 605e and the network entity of node 605f is represented as the edge 610g. The direction of the edge 610g is from the controller entity



of node **605e** to the network entity of node **605f**. The property of the edge **610g** indicates that the controller entity of node **605e** “resides on” the network entity of node **605f**. The relationship between the controller entity of node **605e** and the manufacturer entity of node **605g** is represented as the edge **610i**. The direction of the edge **610i** is from the controller entity of node **605e** to the manufacturer entity of node **605g**. The property of the edge **610i** indicates that the controller entity of node **605e** is “made by” the manufacturer entity of node **605g**. The relationship between the location entity of node **605d** and the network entity of node **605f** is represented as the edge **610h**. The direction of the edge **610h** is to the location entity of node **605d** from the network entity of node **605f**. The property of the edge **610h** indicates that the network entity of node **605f** is located in, as understood by a person of skill in the art after review of the entirety disclosed herein, the location entity of node **605f**.

**[0043]** FIG. 7 illustrates an example graph schema **700** of the location entities. Each of the location entities, such as tower, building, floor, company, space zone, space, and zone, correspond to a logical or physical location associated with the building. The tower, building, floor, company, space zone, space, and zone are represented respectively as the nodes **705a-g** (generally referred to as nodes **705**) of the graph **700**. The nodes **705** may include properties **720a-g**, such as an “id” in a GUID format, a “name” in a string format, and a “description” in a string format. The graph representation **700** includes a plurality of edges **710a-g** that represent relationships between the location entities mapped to the nodes **705**. The relationship between the tower entity of node **705a** and the building entity of node **705b** is represented by the edge **710a**. The direction of the edge **710a** is from the tower entity of node **705a** to the building entity of node **705b**. The property of the edge **710a** indicates that the tower entity of node **705a** is a “located in” the building entity of node **705b**. The relationship between the tower entity of node **705a** and the floor entity of node **705c** is represented by the edge **710b**. The direction of the edge **710b** is to the tower entity of node **705a** from the floor entity of node **705c**. The property of the edge **710b** indicates that the floor entity of node **705c** is a “located in” the tower entity of node **705a**. The relationship between the building entity of node **705b** and the floor entity of node **705c** is represented by the edge **710c**. The direction of the edge **710c** is to the building entity of node **705b** from the floor entity of node **705c**. The property of the edge **710c** indicates that the floor entity of node **705c** is a “located in” the building entity of node **705b**. The relationship between the building entity of node **705b** and the company entity of node **705d** is represented by the edge **710d**. The direction of the edge **710d** is to the building entity of node **705b** from the company entity of node **705d**. The property of the edge **710d** indicates that the company entity of node **705d** is a “located in” the building entity of node **705b**. The relationship between the space zone entity of node **705e** and the company entity of node **705d** is represented by the edge **710e**. The direction of the edge **710e** is from the space zone entity of node **705e** to the company entity of node **705d**. The property of the edge **710e** indicates that the space zone entity of node **705d** is a “occupied by” the company entity of node **705d**.

**[0044]** Referring back to FIG. 1, the example building **102a** may include one or more building systems. Each building system may include one or more assets. As discussed above, an asset is an entity that is associated with a

“thing.” An asset may be physical equipment or an object that is located within a place. An asset may be associated with multiple physical devices **110** and/or points. An asset may also include attributes, such as a serial number, or a manufacturer. At stage **305**, the process **300** begins when the Intelligent Building Edge Application Server **140** receives information about an asset associated with a commercial real-estate building, such as the example building **102a** in FIG. 1. The asset may be associated with a building system of a commercial real-estate building. The information about the asset may include an identification of one or more devices **110** that are associated with the asset.

**[0045]** A plurality of relationships associated with the asset may be identified based on determining the points, controller entities, location entities, and network entities associated with the asset. The Device Library **190** in the Intelligent Building Cloud Platform **165** may include various information about the relationships between devices and controllers generated based on training a machine learning algorithm on the data of various building systems. The plurality of relationships associated with the asset may be determined based on the points, controller entities, location entities, and network entities associated with the asset. Therefore, at stage **310**, the process **300** may include determining one or more points associated with the asset. At stage **315**, the process **300** may include determining one or more controller entities associated with the asset. As discussed above, the controller entities may be logical controllers or physical controllers, such as the controllers **113**. At stage **320**, the process **300** may include determining a plurality of location entities for the asset. The location entities may be physical and logical locations associated with the asset. The location entities may be determined based on information about the actual locations of the devices and controllers associated with the asset, the areas of the building that the devices and controllers service (service areas), and other information from Building Information Modeling (BIM) data of the building. At stage **325**, the process **300** may include determining the network entities associated with the asset. At stage **330**, the process **300** may include determining the upstream and downstream utilities or data flow associated with the asset, thereby identifying the controllers and devices that are associated with the upstream and downstream data flow from the asset.

**[0046]** In some implementations, the Intelligent Building Edge Application Server **140** may be configured to provide an application and User Interface (UI) for adding an asset. The determined relationships associated with the asset may be validated in real-time based on asset templates. The asset templates may be based on training a machine learning algorithm on various building data and the digital twins of various buildings.

**[0047]** The process **300** may be repeated for each asset, resulting in a digital twin of the commercial real-estate building. The Intelligent Building Edge Application Server **140** may send the generated digital twin to the Intelligent Building Cloud Application Server **170** of the Intelligent Building Cloud Platform **165** over the network **160**. The Intelligent Building Cloud Application Server **170** may store the digital twin as the Digital Twin **180** in the Building Data **175**. The Intelligent Building Cloud Platform **165** may perform cloud analytics and processing based on integrating the data stored in the Digital Twin **180** of the different buildings **102**. The Intelligent Building Cloud Application

Server **170** may access the Historical Data **185**, the Digital Twin **180**, and the Actor Model **182** in order to perform analytics that provide additional insights into the devices and systems of the corresponding building **102a**. The Intelligent Building Edge Application Server **140** may also store the digital twins of the buildings **102** at the edge as Building Edge Data **145**. An example Building Edge Data **145a** includes an Edge Digital Twin **150** and an Edge Actor Model **155**. The Intelligent Building Edge Application Server **140** may use the Building Edge Data **145** for performing edge analytics and processing.

[0048] FIG. 4 illustrates another example process **400** for providing an IoT contextually-aware digital twin with enhanced discovery performed by the example system shown in FIG. 1. At stage **402**, the process **400** may include monitoring for a new device connected to a network. The network may be a BAC network. A command may be issued on the network to detect new devices. The command may be a “whois” command on a BAC network. The command may retrieve the device identifiers of devices connected to the network. At stage **403**, the process **400** detects a new device. The device identifiers may indicate a new device that is connect to the network. At stage **405**, the new device is identified and the device characteristics may be determined. At stage **401**, the process **400** includes determining one or more points of the new device. The one or more points of the new device may be determined based on information stored in the Device Library **190**. The Device Library **190** in the Intelligent Building Cloud Platform **165** may include various information about the relationships between devices and controllers generated based on training a machine learning algorithm on the data of various building systems. At stage **415**, the process **400** may include identifying at least one controller entity associated with the one or more points of the new device. At stage **420**, the process **400** includes determining the network and location entities associated with the new device. At stage **425**, the process **400** may include updating the graph representation of the digital twin of the commercial real-estate building with the points, networks, controller and locations associated with the new device. At stage **435**, the process **400** may return to stage **402** monitor for a new device.

[0049] In some implementations, a User Interface (UI) may be provided for on-boarding building systems and devices. The Intelligent Building Edge Application Server **140** may be configured to provide an application and User Interface (UI) for generating a contextually-aware digital twin of a building. In order to access the application and UI, a user may connect a machine to a network of the building. The network may interface with a BACnet. The machine may be a laptop or an IoTium edge device. The user may provide information about a building, select a building from a list of buildings, and add all or some of the assets associated with the selected building to a database. The user may then run a command, such as a “whois” command, on the BACnet to discover the devices on the network. In response, the device identifiers for each of the devices associated with each of the assets may be obtained. The user may obtain additional details about the devices corresponding to the device identifiers by running a “whois” command, on the BACnet. Based on the device identifiers, the points corresponding to the devices may be identified based on device information stored in, for example, the Device Library **190**. The points may be added to the assets and

saved to the database. The determined relationships associated with the asset may be validated in real-time based on asset templates. The asset templates may be based on training a machine learning algorithm on various building data and the digital twins of various buildings. The asset templates may be stored in a Document/NoSQL database that is integrated with the graph database representation of the building. In addition to the BACnet discovery discussed above, various information about the devices, such as the physical location, may also be retrieved from .dwg format files.

[0050] The graph representation of the building may track other static information about devices such as a manufacturer, serial number, model number, etc. Implementations may access the digital twin of a building to support user queries. For example, a user may, through an application on a user device, such as a smartphone, pull up data for the building or query information about the values of devices. Since the edge application is constantly updating the digital twin at the edge, it is possible to quickly and efficiently search for various information about the current state of the building systems.

[0051] FIG. 5 illustrates an example process **500** for providing IoT edge analytics and control performed by the example system shown in FIG. 1. While FIG. 5 is described with reference to FIG. 1, it should be noted that the method steps of FIG. 5 may be performed by other systems.

[0052] Representations of building systems and devices may be created using an actor model, such as the Edge Actor Model **155**. The actors may correspond to devices or groups of devices related to building systems, such as HVAC, lighting, etc. FIG. 8 illustrates an example actor system **800** in an actor model, such as the Edge Actor Model **155**. For example, a sensor may communicate a real time measurement, such as temperature, to an actor corresponding to the sensor. The measurement may be communicated to the actor corresponding to the sensor device as an Incoming Message **880**. The Incoming Message **880** is processed by a Processing module **840**. The Processing module **840** may update the device state stored in the State **830** based on the sensor measurement received in the Incoming Message **880**. The actor **800** may also receive messages from other actors for access to the latest sensor measurement stored in the State **830**. The actor **800** may also send messages to the sensor device to update the device configuration. The data generated by each device is collected in different amounts and at different time intervals. The time interval is dependent on an importance of the device point for real-time control and analytics. For example, a damper percentage may be designated as having a medium priority, and thus data relevant for measuring the damper percentage may be collected from the devices at a five minute interval. A zone temperature may be designated as having a high priority, and thus data relevant for measuring the zone temperature may be collected from the relevant device points at a 30 second interval. An alarm may be designated as having a highest priority, and thus data relevant for measuring triggering of the alarm may be collected in real-time based on a change of value. Since thousands of devices may be requesting data at different intervals, the priority amongst devices needs to be maintained in order to reduce overloading of the BACnet bandwidth. The actor model may be able to handle millions of messages per second. The actor model is set up to mimic the device built in environment. In other words, the actor model

maintains a stateful representation of the device. When the data indicates a defective value within a set up window, the corrective actions are triggered based on the rules in Rules **815**. This enables a quicker response in real time without a need for cloud connectivity and reduces network bandwidth usage, response time, and manual input.

**[0053]** An actor that triggers a rule may query connected devices and assets to find an optimum solution based on the current situation of the system. Once data related to various solutions is received, the best option may be determined based on pre-determined constraints and settings, such as energy usage, time required, etc. In some implementations, device analytics may be provided to model expected performance of a device based on a current state, and the device may be controlled based on computations in real-time using context aware data. By maintaining a stateful machine representation of the device, the exact behavior of a device may be modeled by training a data analytics machine learning algorithm on the real-time data of the input and output data points of the device. Implementations may provide precision command and control for an infinite number of stateful scenarios of the device instead of just a handful that are included in the device's onboard controller. The actor model may be implemented by a distributed computing and non-blocking framework, such as Akka. The actor model and rules may be stored as the Actor Model **182** in the Building Data **175** of the Intelligent Building Cloud Application Platform **165**. In addition to hosting the Actor Model **182** in the cloud, implementations may also run the actor system at the edge, which avoids reliance on cloud computing and enables better real-time response.

**[0054]** At stage **505**, the process **500** includes setting up the rules for each of the actors. The Intelligent Building Edge Application Server **140** and the IoT Gateway **125** may be configured to provide edge based analytics and control of the devices **110** and the controllers **113** based on rules. For example, a rule may be set to trigger an action based on receiving real-time data related to a supply air temperature that has exceeded a min/max alarm threshold. The rule may indicate that if the supply air temperature falls below a minimum threshold value or exceeded a maximum threshold value for more than five minutes, then actions must be taken to adjust air temperature to a preferred temperature set as a predetermined value. The rule may be stored in the Rules **815** of the actor **800** corresponding to the temperature sensor.

**[0055]** At stage **510**, the process **500** includes monitoring the incoming real-time data from the temperature sensor device as an Incoming Message **880**, and at stage **515**, the process **500** includes processing the Incoming Message **880** and evaluating whether the real-time data meets the rule stored in the Rules **815**. A windowing function may ensure that a specific number of consecutive real-time measurements are received from the temperature sensor in order for the rule in the Rules **815** to be triggered. Upon a determination that the supply air temperature has fallen below the minimum threshold value or exceeded the maximum threshold value for more than five minutes, the process **500** moves to stage **520**.

**[0056]** At stage **520**, the process **520** includes requesting other actors for information for adjusting the air temperature to the predetermined value. For example, other actors relevant for maintaining the air supply temperature may include devices related to a chiller system, an FPB, or other

devices configured to effectuate local changes that may impact the air supply temperature. The air temperature actor may send the request to other actors via an Outgoing Message **855**. The other actors may receive the Outgoing Message **855** and determine the actions their devices may take in order to achieve a solution, based on the current state of their devices. For example, the actor corresponding to the chiller may determine that operating the chiller for 5 min at 12 Kw is needed to adjust the air temperature to the preferred temperature. The actor corresponding to the FPB (Fan Powered Box) may determine that operating its devices for 2 min at 14 Kw is needed to adjust the air temperature to the preferred temperature. The actor corresponding for local changes may determine that operating its devices for 7 min at 9 Kw is needed to adjust the air temperature to the preferred temperature. Each actor sends this information as an Outgoing Message **855** to the air temperature actor which receives the information as Incoming Messages **880** and processes the messages. At stage **503** of the process **500**, the air temperature actor may select a solution based on evaluating the information received from the other actors based on other considerations related to, for example, time, energy, and feasibility. At stage **545**, the process **500** includes executing the solution by notifying the relevant assets. The air temperature actor may notify the relevant actor to take an action for executing the solution proposed by the actor. For example, the air temperature actor may send an Outgoing Message **855** to notify the chiller actor to operate the chiller for 5 minutes at 12 KW. The chiller actor receives the message from the air temperature actor as an Incoming Message **880**. The chiller actor turns on the cooling system in order to decrease the air temperature and notifies the air temperature actor. At stage **555** of the process **500**, the air temperature actor monitors the air temperature based on continuing to receive real-time temperature measurements. At stage **560**, the process **500** includes determining whether the air temperature meets the criteria set by the rule stored in the Rule **815**. Upon a determination that the air temperature has returned to the preferred temperature, at stage **565** of the process **500**, the air temperature actor notifies the chiller to return to its normal operation.

**[0057]** Performing edge based device analytics (i.e. space temperature rate of change) may be used for controlling a device, for example, an air damper, without relying upon cloud compute. Performing edge device analytics relies on accessing the digital twin at the edge to perform a computation rather than relying on the digital twin stored in the cloud. For example, a device may have a data point called space temperature, which may have a function that checks for the rate of change of that value. If the rate of change exceeds a threshold consecutively for a given time period, the air damper of the device closes. This enables the device to act quickly to an urgent fire related condition without relying upon network connectivity to the cloud platform in order to provide a command back to the device.

**[0058]** In some implementations, the data collected from the devices may be stored in a time series database. If a user is attempting to change the temperature, or check on a current status of a VAV box, it is inefficient and expensive to query the cloud stored data. Thus, implementations provide information about the VAV box or other devices within the most recent period, such as 24 hours. If, based on the most recent data, it is observed that the present behavior of the device is not as expected, the cloud platform may be

accessed for querying the cloud stored big data related to the device. This may happen based on both the end user triggering or requesting the query or automatically based on preset parameters and thresholds. In some implementations, artificial intelligence and machine learning may be used to analyze and identify anomalies at the same time as the data is being collected. In some implementations, a time bounding may be set of the last 30 sec or other predetermined time period of the data flowing in or being collected. Based on observed patterns in the data, an alert may be triggered which in turn triggers an action to be performed by various devices or systems. Using machine learning by training a machine learning algorithm on previously collected data enables implementations to predict anomalies in the device data as it is being collected. Implementations may access collected data and evaluate it to gain insights. The data that comes off of that could provide previously unknown insights that would not be possible to obtain using traditional methods. Additionally, implementations are able to maintain and manipulate the state machine for entire subsystems.

**[0059]** Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are described as example implementations of the following claims.

1. A method of generating a contextually-aware digital twin of a commercial real estate building comprising:

receiving, by a computing device, device data about an asset comprising one or more devices residing in one or more physical spaces associated with the commercial real estate building;

storing, by the computing device, the device data about the one or more devices in a device library;

discovering, based on a received identification of a discovered device connected to an associated network, whether the discovered device is stored in a graph representation of the commercial real estate building;

accessing the device data from the device library;

when the device data from the device library is known about the discovered device, identifying device information about the discovered device from the accessed device data; and

when the discovered device is not stored in the graph representation, modifying the graph representation to include the discovered device with the identified device information.

2. The method of claim 1, wherein the identifying comprises predicting a relationship between the discovered device and another entity of the graph representation of the commercial real estate building.

3. The method of claim 1, further comprising:

including manufacturer information in the stored device data at the device library.

4. The method of claim 3, further comprising:

including model information in the stored device data at the device library.

5. The method of claim 3, further comprising:

obtaining a manufacturer identification of the discovered device; and

accessing the device information based on the manufacturer identification.

6. The method of claim 4, further comprising:

obtaining a model identification of the discovered device; and

accessing the device information based on the model identification.

7. The method of claim 2, further comprising:

determining at least one controller associated with at least one or more points of the discovered device.

8. The method of claim 1, further comprising:

training a machine learning algorithm with the received device data on the contextually-aware digital twin.

9. The method of claim 1, further comprising:

determining one or more points based on the device information.

10. A system for generating a contextually-aware digital twin of a commercial real estate building comprising:

one or more processors; and

a memory storing computer-readable instructions that, when executed by the one or more processors, configure the one or more processors to:

receive device data about an asset comprising one or more devices residing in one or more physical spaces associated with the commercial real estate building;

store the device data about the one or more devices in a device library;

discover, based on a received identification of a discovered device connected to an associated network, whether the discovered device is stored in a graph representation of the commercial real estate building;

access the device data from the device library;

when the device data from the device library is known about the discovered device, identify device information about the discovered device from the accessed device data; and

when the discovered device is not stored in the graph representation, modify the graph representation to include the discovered device with the identified device information.

11. The system of claim 10, wherein the memory storing computer-readable instructions that, when executed by the one or more processors, configure the one or more processors to:

predict a relationship between the discovered device and another entity of the graph representation of the commercial real estate building.

12. The system of claim 10, wherein the memory storing computer-readable instructions that, when executed by the one or more processors, configure the one or more processors to:

include manufacturer and model information in the stored device data at the device library;

obtain a manufacturer and model identification of the discovered device; and

access the device information based on the manufacturer and model identification.

13. The system of claim 11, wherein the memory storing computer-readable instructions that, when executed by the one or more processors, configure the one or more processors to:

determine at least one controller associated with at least one or more points of the discovered device.

14. The system of claim 10, wherein the memory storing computer-readable instructions that, when executed by the one or more processors, configure the one or more processors to:

train a machine learning algorithm with the received device data on the contextually-aware digital twin.

**15.** The system of claim **10**, wherein the memory storing computer-readable instructions that, when executed by the one or more processors, configure the one or more processors to:

determine one or more points based on the device information.

**16.** A non-transitory machine readable storage medium comprising machine-readable instructions for causing a processor to execute a method of generating a contextually-aware digital twin of a commercial real estate building comprising:

receiving device data about an asset comprising one or more devices residing in one or more physical spaces associated with the commercial real estate building;

storing the device data about the one or more devices in a device library;

discovering, based on a received identification of a discovered device connected to an associated network, whether the discovered device is stored in a graph representation of the commercial real estate building;

accessing the device data from the device library;

when the device data from the device library is known about the discovered device, identifying device information about the discovered device from the accessed device data; and

when the discovered device is not stored in the graph representation, modifying the graph representation to include the discovered device with the identified device information.

**17.** The non-transitory machine readable storage medium of claim **16**, wherein the machine-readable instructions cause the processor to execute the method comprising: predicting a relationship between the discovered device and another entity of the graph representation of the commercial real estate building.

**18.** The non-transitory machine readable storage medium of claim **16**, wherein the machine-readable instructions cause the processor to execute the method comprising: including manufacturer and model information in the stored device data at the device library; obtaining a manufacturer and model identification of the discovered device; and accessing the device information based on the manufacturer and model identification.

**19.** The non-transitory machine readable storage medium of claim **17**, wherein the machine-readable instructions cause the processor to execute the method comprising: determining at least one controller associated with at least one or more points of the discovered device.

**20.** The non-transitory machine readable storage medium of claim **16**, wherein the machine-readable instructions cause the processor to execute the method comprising: training a machine learning algorithm with the received device data on the contextually-aware digital twin.

\* \* \* \* \*