



US008561345B2

(12) **United States Patent**
Armas

(10) **Patent No.:** **US 8,561,345 B2**
(45) **Date of Patent:** **Oct. 22, 2013**

(54) **APPARATUS FOR DISPLAYING A PLANT**

(76) Inventor: **James Vincent Armas**, Port Jefferson
Station, NY (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/861,715**

(22) Filed: **Aug. 23, 2010**

(65) **Prior Publication Data**

US 2011/0041398 A1 Feb. 24, 2011

Related U.S. Application Data

(60) Provisional application No. 61/236,392, filed on Aug.
24, 2009.

(51) **Int. Cl.**
A47G 7/02 (2006.01)

(52) **U.S. Cl.**
USPC **47/39; 47/67; 47/46**

(58) **Field of Classification Search**
USPC 47/65.5, 66.6, 67, 82, 83, 86, 39, 46, 47
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

554,661 A	2/1896	Doolittle
1,473,318 A	11/1923	Ranson
1,566,982 A	12/1925	Shee
1,628,823 A	5/1927	Jonnes
1,663,366 A	3/1928	Berry
1,809,018 A	8/1931	Bruning
1,913,587 A	6/1933	Edwards
2,235,966 A	3/1941	Ellingson
2,544,817 A	3/1951	White

2,764,384 A	9/1956	Kirsch
2,770,957 A	11/1956	Bronson
3,010,256 A *	11/1961	Ise 47/42
3,302,328 A *	2/1967	King 47/47
3,521,401 A *	7/1970	Shisler 47/43
3,559,939 A *	2/1971	Luna 248/210
D231,296 S	4/1974	Morris et al.
4,109,415 A	8/1978	Hall
4,480,403 A	11/1984	Williams
4,524,542 A	6/1985	Elliott
4,603,507 A	8/1986	Nelson
4,666,115 A	5/1987	Schiro
4,908,982 A	3/1990	Quatrini
5,220,744 A	6/1993	Kendall
5,292,014 A	3/1994	Lelong
5,327,678 A	7/1994	Schweiker
D350,081 S	8/1994	May
5,395,081 A	3/1995	Vollink
D357,596 S	4/1995	Kragt et al.
5,457,911 A	10/1995	Vollink
5,649,386 A	7/1997	Rynberk
5,966,865 A	10/1999	Jones
6,299,116 B1	10/2001	Levesque

(Continued)


Primary Examiner — Rob Swiatek

Assistant Examiner — Lisa Tsang

(57) **ABSTRACT**

An apparatus for displaying a plant is described. The apparatus includes a first substantially horizontal member that engages a first surface of a structure at a first vertical position. A second substantially horizontal member engages a second surface of the structure at a second vertical position that is lower than the first vertical position. The first surface is opposite to the second surface. A frame is coupled to the second substantially horizontal member and is shaped to support a pot containing the plant. The weight of the supported plant urges the first substantially horizontal member against the first surface of the structure and urges the second substantially horizontal member against the second surface of the structure, thereby securing the apparatus to the structure.

10 Claims, 9 Drawing Sheets




(56)

References Cited

U.S. PATENT DOCUMENTS

6,375,141	B1 *	4/2002	Kettlestrings	248/303	7,024,816	B1	4/2006	Marks et al.	
6,539,665	B1	4/2003	Liona		7,263,799	B2	9/2007	Zanten	
6,672,003	B2	1/2004	Park		7,275,728	B1 *	10/2007	Branson	248/302
6,708,832	B1	3/2004	Hannon		7,360,336	B2	4/2008	Zanten	
6,971,204	B1 *	12/2005	Gibney	47/39	7,677,513	B1 *	3/2010	Londo	248/217.1
					2003/0132355	A1	7/2003	Denton	
					2008/0110087	A1	5/2008	Serio	
					2009/0064573	A1	3/2009	Braun	

* cited by examiner

*FIG. 1*




FIG. 2A









FIG. 2B


*FIG. 3*


*FIG. 4*

*FIG. 5*

*FIG. 6*

*FIG. 7*

*FIG. 8*

*FIG. 9*

1

APPARATUS FOR DISPLAYING A PLANT**CROSS REFERENCE TO RELATED APPLICATION**

The present application is related to and claims the benefit of priority under 35 U.S.C. §119(e) from U.S. Provisional Application Ser. No. 61/236,392, filed Aug. 24, 2009, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

The invention relates generally to displaying plants and other objects on a variety of structures.

BACKGROUND

A typical plant hanger for use on a fence post or a deck railing generally includes an L-shaped bracket having a vertical member that is screwed into the post or railing. The plant may reside in a pot that includes chains or rope connected to a small hook that fits over a horizontal member of the bracket. Another type of bracket includes a large hook that fits over a horizontal structure, such as a deck railing. A hook on the opposite end of the bracket is adapted to engage the small hook of a hanging plant.

SUMMARY

In one aspect, the invention is embodied in an apparatus for displaying a plant. The apparatus includes a first substantially horizontal member for engagement with a first surface of a structure at a first vertical position. A second substantially horizontal member engages a second surface of the structure at a second vertical position that is lower than the first vertical position. The first surface is substantially opposite to the second surface. A frame is coupled to the second substantially horizontal member. The frame is shaped to support a pot containing the plant such that the weight of the supported plant urges the first substantially horizontal member against the first surface of the structure and the second substantially horizontal member against the second surface of the structure, thereby securing the apparatus to the structure.

In one embodiment, the first and second substantially horizontal members are formed from a first piece of material and the frame is formed from a second piece of material. The first piece of material can include a mechanical coupling that mates with a corresponding mechanical coupling of the second piece of material.

The apparatus can also include an inverted U-shaped member located between the first and second substantially horizontal members. The U-shaped member is shaped to engage a substantially horizontal structure.

In one embodiment, at least one of the first substantially horizontal member, the second substantially horizontal member, and the frame is formed from a metal material. The metal material can have a substantially circular cross-section. In one embodiment, the frame is adjustable to support a plurality of pots having different dimensions.

The structure can include a post. The weight of the supported plant urging the first substantially horizontal member against the first surface and the second substantially horizontal member against the second surface prevents the supported plant from moving down the post.

The shape of the pot can be chosen from the group comprising a cylinder, a cone, a square, and a rectangle. An extension member can be located between the second sub-

2

stantially horizontal member and the frame. The extension member can be adapted to separate the second substantially horizontal member from the frame.

In another aspect, the invention is embodied in an apparatus for displaying a plant. The apparatus includes a bracket having a first curved member for engagement with a first surface of a columnar-shaped structure at a first vertical position. The bracket includes a second curved member for engagement with a second surface of the columnar-shaped structure at a second vertical position that is lower than the first vertical position. A frame is coupled to the bracket. The frame is shaped to support a pot containing the plant such that the weight of the supported plant urges the first curved member against the first surface of the columnar-shaped structure and urges the second curved member against the second surface, thereby securing the apparatus to the columnar-shaped structure.

In one embodiment, the bracket includes a first piece of material and the frame includes a second piece of material. The first piece of material can include a mechanical coupling that mates with a corresponding mechanical coupling of the second piece of material.

The apparatus can also include an inverted U-shaped member located between the bracket and the frame. The inverted U-shaped member is shaped to engage a substantially horizontal structure.

In one embodiment, the bracket and/or the frame is formed from a metal material. The metal material can have a substantially circular cross-section. In one embodiment, the frame is adjustable to support a plurality of pots having different dimensions. The columnar-shaped structure can be a post.

The weight of the supported plant urging the first curved member against the first surface and the second curved member against the second surface prevents the supported plant from moving down the post. The shape of the pot can be chosen from the group including a cylinder, a cone, a square, and a rectangle.

In one embodiment, an extension member is located between the bracket and the frame. The extension member is adapted to separate the bracket from the frame.

BRIEF DESCRIPTION OF THE FIGURES

Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of various embodiments. In addition, the description and drawings do not necessarily require the order illustrated. It will be further appreciated that certain actions and/or steps may be described or depicted in a particular order of occurrence while those skilled in the art will understand that such specificity with respect to sequence is not actually required. Apparatus and method components have been represented where appropriate by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the various embodiments so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein. Thus, it will be appreciated that for simplicity and clarity of illustration, common and well-understood elements that are useful or necessary in a commercially feasible embodiment may not be depicted in order to facilitate a less obstructed view of these various embodiments.

The above and further advantages of this invention may be better understood by referring to the following description in

3

conjunction with the accompanying drawings, in which like numerals indicate like structural elements and features in various figures. Skilled artisans will appreciate that reference designators shown herein in parenthesis indicate components shown in a figure other than the one in discussion. For example, talking about a device (10) while discussing Figure A would refer to an element, 10, shown in figure other than Figure A.

FIG. 1 is a perspective view of an apparatus for displaying a plant according to the invention.

FIG. 2A and FIG. 2B illustrate top views of the apparatus of the present invention.

FIG. 3 is a perspective view of an apparatus for displaying a plant according to another embodiment of the invention.

FIG. 4 illustrates a perspective view of the apparatus of FIG. 1 attached to a post.

FIG. 5 illustrates a perspective view of an apparatus attached to a post according to one embodiment of the invention.

FIG. 6 illustrates a top view of an apparatus attached to a post according to another embodiment of the invention.

FIG. 7 illustrates a perspective view of the apparatus of FIG. 1 attached to a picket-type fence.

FIG. 8 illustrates a side view of an apparatus for displaying a plant according to one embodiment of the invention.

FIG. 9 illustrates a perspective view of the apparatus of FIG. 1 attached to a chain link fence.

DETAILED DESCRIPTION

The following detailed description is merely illustrative in nature and is not intended to limit the invention or the application and uses of the invention. Furthermore, there is no intention to be bound by any express or implied theory presented in the preceding technical field, background, brief summary or the following detailed description. For the purposes of conciseness, many conventional techniques and principles related to conventional plant hangers, need not, and are not, described in detail herein.

Techniques and technologies may be described herein in terms of functional components and various processing steps. It should be appreciated that such components may be realized by any number of hardware components configured to perform the specified functions.

The following description may refer to elements or features being “connected” or “coupled” together. As used herein, unless expressly stated otherwise, “connected” means that one element/feature is directly joined to (or directly communicates with) another element/feature. Likewise, unless expressly stated otherwise, “coupled” means that one element/feature is directly or indirectly joined to (or directly or indirectly communicates with) another element/feature. The term “exemplary” is used in the sense of “example, instance, or illustration” rather than “model,” or “deserving imitation.”

Technologies and concepts discussed herein relate to systems utilizing potted plants. In an exemplary embodiment, an apparatus for displaying a plant includes a first substantially horizontal member for engagement with a first surface of a structure at a first vertical position. A second substantially horizontal member engages a second surface of the structure at a second vertical position that is lower than the first vertical position. A frame is coupled to the second substantially horizontal member. The frame is shaped to support a pot containing the plant such that the weight of the supported plant urges the first substantially horizontal member against the first surface of the structure and the second substantially horizontal member against the second surface of the structure, thereby

4

securing the apparatus to the structure. Besides plants, the apparatus can also support other objects, such as pumpkins or decorations.

FIG. 1 is a perspective view of an apparatus 100 for displaying a plant according to the invention. The apparatus 100 includes a first substantially horizontal member 102. A second substantially horizontal member 104 is coupled to the first substantially horizontal member 102. In one embodiment, an inverted U-shaped member 106 couples the first substantially horizontal member 102 to the second substantially horizontal member 104. In another embodiment, an inverted V-shaped member or any other suitable shape can also be used. The inverted U-shaped member 106 can assist in securing the apparatus 100 to a structure (not shown).

The inverted U-shaped member 106 can include a dimension 107 that corresponds to the thickness of a horizontal structure (not shown) to which the apparatus 100 can be attached. For example, the horizontal structure can be a two-inch by four-inch piece of material or a horizontal two-inch pipe supporting a chain link fence.

The first substantially horizontal member 102 can optionally include a hook 108 that secures the apparatus 100 to a link in a chain link fence (not shown). In one embodiment, the distance between the inverted U-shaped member 106 and the hook 108 corresponds to the approximate thickness of a post or other structure to which the apparatus 100 is attached.

In one embodiment, the distance between the first substantially horizontal member 102 and the second substantially horizontal member 104 corresponds to the approximate thickness of a post or other structure to which the apparatus 100 is attached.

The apparatus can also include an extension member 110. The extension member 110 can be located between the second substantially horizontal member 104 and a frame 112. The extension member 110 can be adapted to separate the second substantially horizontal member 104 from the frame 112. The length of the extension member 110 can be varied depending on the size of the plant to be displayed and/or the desired distance between the plant and the structure to which the apparatus 100 is attached.

In one embodiment, the distance between the second substantially horizontal member 104 and the frame 112 can correspond to the thickness of a picket on a picket fence. In this embodiment, the apparatus 100 can be secured to the picket fence by inserting the picket in the recess 114 between the second substantially horizontal member 104 and the frame 112.

The frame 112 is adapted to support a pot (not shown). In one embodiment, the frame 112 is adjustable to support pots having different dimensions. For example, the frame 112 can be substantially circular and its diameter 116 can be varied. In other embodiments, the frame can be substantially square, rectangular, triangular, or oval-shaped. In practice, any suitable shape can be used.

The apparatus 100 can be fabricated from any suitable material. In one embodiment, the apparatus 100 is fabricated from a metal material. For example, the apparatus 100 can be fabricated from stainless steel. In another embodiment, the apparatus 100 can be fabricated from a plastic material. The material can be a round stock material or a flat stock material. By round stock material, we mean a material having a substantially circular cross-section.

In operation, a user of the apparatus 100 adjusts the diameter 116 of the frame 112 to fit the pot (not shown) containing the plant to be displayed. The user then attaches the apparatus 100 to the structure on which the plant is to be displayed. For example, the user may attach the apparatus 100 to a vertical

5

post by inserting the post between the first substantially horizontal member **102** and the second substantially horizontal member **104**.

The user then inserts the pot containing the plant into the frame **112**. The weight of the plant in the frame **112** urges the first substantially horizontal member **102** into a first surface of the post and urges the second substantially horizontal member **104** into a second surface of the post. The first surface of the post is opposite to the second surface of the post. In one embodiment, the second substantially horizontal member **104** can act as a cantilever for tilting the front of the frame **112** downward, thereby allowing the user to view a greater portion of the plant.

FIG. 2A and FIG. 2B illustrate top views **200**, **200'** of the apparatus **100** of the present invention. FIG. 2A illustrates the frame **112** having a first diameter **202**. The first diameter **202** is adapted to support a round pot (not shown) having a large diameter. For example, the first diameter **202** can be between about twelve and twenty inches. The recess **204** is formed from the first **102** and second substantially horizontal members **104** and the inverted U-shaped member **106**. In the embodiment shown, the recess **204** is shaped to accept a post having a square cross-section.

FIG. 2B illustrates the frame **112** having a second diameter **206**. The second diameter **206** is adapted to support a round pot (not shown) having a smaller diameter. For example, the second diameter **206** can be between about four and ten inches. The frame **112** can include one or more clamps **208**. The clamps **208** are used to prevent the diameter **206** of the frame **112** from unintentionally increasing. In one embodiment, the clamps **208** can be fabricated from washers, such as lock washers, or coils for example. Alternatively, the clamps **208** can be fabricated from sections of plastic or rubber tubing. Skilled artisans will appreciate that a variety of techniques can be used to secure the diameter **206** of the frame **112** without departing from the spirit and scope of the invention.

FIG. 3 is a perspective view of an apparatus **300** for displaying a plant according to another embodiment of the invention. The apparatus **300** includes a bracket **302** having a first curved section **304** for engagement with a first surface of a columnar-shaped structure (not shown) at a first vertical position. The bracket **302** includes a second curved section **306** for engagement with a second surface of the columnar-shaped structure at a second vertical position that is lower than the first vertical position.

A frame **308** is coupled to the bracket **302**. The frame **308** is shaped to support a pot **310** containing a plant (not shown) such that the weight of the supported plant urges the first curved section **304** against the first surface of the columnar-shaped structure and urges the second curved section **306** against the second surface, thereby securing the apparatus **300** to the columnar-shaped structure. The columnar-shaped structure can be a pole, such as a telephone pole, a column supporting a roof, or a trunk of a tree, for example.

The frame **308** is adapted to support the pot **310**. In one embodiment, the frame **308** is adjustable to support pots having different dimensions. For example, the frame **308** can be substantially circular and its diameter **312** can be varied. In other embodiments, the frame **308** can be substantially square, rectangular, triangular, or oval-shaped. In practice, any suitable shape can be used.

The apparatus **300** can also include an optional perch **314**. The perch **314** is positioned adjacent to, or alternatively, formed in the second curved section **306**. In one embodiment, the perch **314** provides additional support to the apparatus **300** when the pot **310** is inserted into the frame **308**. For

6

example, the weight of the pot **310** urges the perch **314** against the second surface of the columnar-shaped structure, thereby providing additional support.

In one embodiment, an extension member **316** is located between the bracket **302** and the frame **308**. The extension member **316** is adapted to separate the bracket **302** from the frame **308**. For example, the extension member **316** can be used to situate the pot **310** a short distance away from the columnar-shaped structure. The length of the extension member **316** can be varied depending on the size of the plant to be displayed and/or the desired distance between the plant and the columnar-shaped structure.

In one embodiment, the bracket **302** is fabricated from a first piece of material and the frame **308** is fabricated from a second piece of material. The first piece of material can include a mechanical coupling that mates with a corresponding mechanical coupling formed on the second piece of material.

In one embodiment, the bracket **302** and/or the frame **308** is formed from a metal material. For example, the metal material can be a flexible stainless steel. The metal material can have a substantially circular cross-section. As previously described, the frame **308** can be adjustable to support a plurality of pots having different dimensions. The frame **308** can also include one or more clamps **318**. The clamps **318** are used to prevent the diameter **312** of the frame **308** from unintentionally increasing. The bracket **302** and/or the frame **308** can be coated in vinyl or plastic to protect the columnar-shaped structure.

In operation, a user of the apparatus **300** adjusts the diameter **312** of the frame **308** to fit the pot **310** containing the plant to be displayed. The user then attaches the bracket **302** to the columnar-shaped structure on which the plant is to be displayed. For example, the user may attach the bracket **302** to a trunk of a tree by inserting the trunk between the first curved section **304** and the second curved section **306**.

The user then inserts the pot **310** containing the plant into the frame **308**. The weight of the plant in the frame **308** urges the first curved section **304** against a first surface of the tree trunk and urges the second curved section **306** against a second surface of the tree trunk. In one embodiment, the perch **314** can act as a cantilever for tilting the front of the frame **308** downward, thereby allowing the user to view a greater portion of the plant.

FIG. 4 illustrates a perspective view of the apparatus **100** of FIG. 1 attached to a post **402**. The apparatus **100** includes the frame **112** supporting a pot **404**. This embodiment includes the inverted U-shaped member **106**. Skilled artisans will appreciate that other suitable shapes can be used instead of an inverted U-shape. Upon installation, the inverted U-shaped member **106** contacts a surface **406** of the post **402** to provide additional support to the apparatus **100**. The extension member **110** separates the pot **404** from a surface **408** of the post **402**. The post **402** can be a wooden or a vinyl fence post having a substantially square cross-section. The post **402** can be a standard four inch by four inch, six by six inch, or eight inch by eight inch post. In other embodiments, the post can have a substantially rectangular cross-section (not shown).

FIG. 5 illustrates a perspective view of an apparatus **500** according to one embodiment of the invention. The apparatus **500** is attached to a post **504**. The apparatus **500** includes a frame **506** supporting a pot **508**. This embodiment does not include an inverted U-shaped member. Instead, a coupling member **510** couples a first horizontal member **512** to a second horizontal member **514**. Skilled artisans will appreciate

that other suitable techniques for coupling the first horizontal member **512** to the second horizontal member **514** can also be used.

FIG. **6** illustrates a top down view of an apparatus **600** attached to a post **604** according to another embodiment of the invention. The apparatus **600** includes a frame **606**, an extension member **608**, first **610** and second horizontal members **612**, an inverted U-shaped member **614**, and a hook **616**. The apparatus **600** is attached to the post **604** having a substantially square cross-section. In one embodiment, the apparatus **600** includes an optional relief **618**. The relief **618** is adapted to allow the apparatus **600** to fit on a post having a non-standard size. For example, a four inch by four inch wooden post has a thickness that is generally around three and one-half inches per side, whereas a four inch vinyl fence post has a thickness that is truly four inches per side.

FIG. **7** illustrates a perspective view of the apparatus **100** of FIG. **1** attached to a picket-type fence **702**. The apparatus **100** includes the frame **112** containing a pot **704**. The optional inverted U-shaped member **106** engages a horizontal structure **706** of the fence **702**. The weight of the pot **704** containing a plant urges the second horizontal member **104** against a picket **708** and a portion **710** of the inverted U-shaped member **106** against the horizontal structure **706** of the fence **702**. In one embodiment, a portion of the optional hook **108** is also urged against the horizontal structure **706** of the fence **702**. In one embodiment, the horizontal structure **706** is a one-inch by six-inch cross beam used to support each picket in a vertical position.

FIG. **8** illustrates an apparatus **800** for displaying a plant according to one embodiment of the invention. The apparatus **800** is embodied in a two-piece design. The two-piece design includes a bracket and a frame. First **802** and second substantially horizontal members **804** are fabricated from a first piece of material and form the bracket **806**. A frame **808** is fabricated from a second piece of material. In one embodiment, the bracket **806** includes a mechanical coupling **812**. The frame **808** also includes a mechanical coupling **814** that mates with the corresponding mechanical coupling **812** of the bracket **806**. Skilled artisans will appreciate that the bracket **806** and the frame **808** can be coupled using a variety of techniques.

Although the frame **808** is illustrated containing a pot **816**, various other accessories can be coupled to the mechanical coupling **812** of the bracket **806**. For example, an apparatus (not shown) including a plurality of frames for displaying multiple plants can be coupled to the bracket **806**.

FIG. **9** illustrates a perspective view of the apparatus **100** of FIG. **1** attached to a chain link fence **902**. The apparatus **100** includes the frame **112** containing a pot **904**. The optional inverted U-shaped member **106** engages a horizontal structure **906** of the fence **902**. The weight of the pot **904** urges the second horizontal member **104** against the chain **908** and a portion **910** of the inverted U-shaped member **106** against the horizontal structure **906**. In one embodiment, the optional hook **108** engages a chain link **912** of the fence **902** to further secure the apparatus **100** to the fence **902**. In one embodiment, the horizontal structure **906** is a metal pipe used to support the chain links. The metal pipe can be a standard two-inch diameter pipe.

In the foregoing specification, specific embodiments have been described. However, one of ordinary skill in the art appreciates that various modifications and changes can be made without departing from the scope of the invention as set forth in the claims below. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of present teachings. The benefits,

advantages, solutions to problems, and any element(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, or essential features or elements of any or all the claims. The invention is defined solely by the appended claims including any amendments made during the pendency of this application and all equivalents of those claims as issued.

Moreover in this document, relational terms such as first and second, top and bottom, and the like may be used solely to distinguish one entity or action from another entity or action without necessarily requiring or implying any actual such relationship or order between such entities or actions. The terms “comprises,” “comprising,” “has,” “having,” “includes,” “including,” “contains,” “containing” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises, has, includes, contains a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “comprises . . . a”, “has . . . a”, “includes . . . a”, “contains . . . a” does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises, has, includes, contains the element. The terms “a” and “an” are defined as one or more unless explicitly stated otherwise herein. The terms “substantially”, “essentially”, “approximately”, “about” or any other version thereof, are defined as being close to as understood by one of ordinary skill in the art, and in one non-limiting embodiment the term is defined to be within 10%, in another embodiment within 5%, in another embodiment within 1% and in another embodiment within 0.5%. A device or structure that is “configured” in a certain way is configured in at least that way, but may also be configured in ways that are not listed.

The Abstract of the Disclosure is provided to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in various embodiments for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter.

While at least one example embodiment has been presented in the foregoing detailed description, it should be appreciated that a vast number of variations exist. It should also be appreciated that the example embodiment or embodiments described herein are not intended to limit the scope, applicability, or configuration of the claimed subject matter in any way. Rather, the foregoing detailed description will provide those skilled in the art with a convenient road map for implementing the described embodiment or embodiments. It should be understood that various changes can be made in the function and arrangement of elements without departing from the scope defined by the claims, which includes known equivalents and foreseeable equivalents at the time of filing this patent application.

In addition, the section headings included herein are intended to facilitate a review but are not intended to limit the

scope of the present invention. Accordingly, the specification and drawings are to be regarded in an illustrative manner and are not intended to limit the scope of the appended claims.

In interpreting the appended claims, it should be understood that:

- a) the word “comprising” does not exclude the presence of other elements or acts than those listed in a given claim;
- b) the word “a” or “an” preceding an element does not exclude the presence of a plurality of such elements;
- c) any reference signs in the claims do not limit their scope;
- d) several “means” may be represented by the same item implemented structure or function;
- e) any of the disclosed devices or portions thereof may be combined together or separated into further portions unless specifically stated otherwise; and
- f) no specific sequence of acts or steps is intended to be required unless specifically indicated.

What is claimed is:

1. An apparatus for displaying a plant, comprising:

a first substantially horizontal member for engagement with a first surface of a structure at a first vertical position;

a second substantially horizontal member for engagement with a second surface of the structure at a second vertical position that is lower than the first vertical position, the first surface being substantially opposite to the second surface;

an inverted U-shaped member located between the first and second substantially horizontal members and being shaped to engage a substantially horizontal structure; and

a frame coupled to the second substantially horizontal member and being shaped to support a pot containing the plant such that the weight of the supported plant urges the first substantially horizontal member against the first surface of the structure and the second substantially horizontal member against the second surface of

the structure, thereby securing the apparatus to the structure, a diameter of the frame being adjustable to fully surround any one of a plurality of pots having different diameters.

2. The apparatus of claim 1, wherein the first and second substantially horizontal members comprise a first piece of material and the frame comprises a second piece of material.

3. The apparatus of claim 2, wherein the first piece of material includes a mechanical coupling that mates with a corresponding mechanical coupling of the second piece of material.

4. The apparatus of claim 1, wherein the substantially horizontal structure comprises one of a deck railing, a horizontal pipe, a picket fence, and a horizontal fence support.

5. The apparatus of claim 1, wherein at least one of the first substantially horizontal member, the second substantially horizontal member, and the frame is flamed from a metal material comprising a substantially circular cross-section.

6. The apparatus of claim 1, wherein the frame further comprises a clamp for locking the frame around the any one of the plurality of pots having the different diameters.

7. The apparatus of claim 1, wherein the structure comprises a post.

8. The apparatus of claim 7, wherein the weight of the supported plant urging the first substantially horizontal member against the first surface and the second substantially horizontal member against the second surface prevents the supported plant from moving down the post.

9. The apparatus of claim 1, wherein a shape of the pot is chosen from the group consisting of a cylinder, a cone, a square, and a rectangle.

10. The apparatus of claim 1, further comprising an extension member located between the second substantially horizontal member and the frame and being adapted to separate the second substantially horizontal member from the frame.

* * * * *