

(51) International Patent Classification:
H04N 7/08 (2006.01) *H04N 5/44* (2006.01)(21) International Application Number:
PCT/US2009/040067(22) International Filing Date:
9 April 2009 (09.04.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12/122,622 16 May 2008 (16.05.2008) US(71) Applicant (for all designated States except US): **SONY COMPUTER ENTERTAINMENT AMERICA INC.**
[US/US]; 919 E. Hillsdale Blvd., Second Floor, Foster City, CA 94404 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ZALEWSKI, Gary, M.** [US/US]; 919 E. Hillsdale Blvd., Second Floor, Foster City, CA 94404 (US).(74) Agent: **ISENBERG, Joshua, D.**; Jdi Patent, 809 Corporate Way, Fremont, CA 94539 (US).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: CHANNEL HOPPING SCHEME FOR UPDATE OF DATA FOR MULTIPLE SERVICES ACROSS MULTIPLE DIGITAL BROADCAST CHANNELS



(57) Abstract: Data broadcast over different channels may be updated in a digital broadcast receiving device. The device may include a receiver unit, a processor, memory instructions embodied in the memory for execution on the processor. The instructions may be configured to implement the method for updating data broadcast over different channels. A first digital broadcast signal may be received over a first channel. The receiving device may be tuned to a second channel at a predetermined time to receive a second digital broadcast signal. Selected data may be extracted from the second digital broadcast signal and stored or utilized with the receiving device. An update schedule may be generated for data transmitted with a digital broadcast signal. A broadcast time for an update packet may be determined from a packet header. A schedule packet may be generated containing the broadcast time and broadcast before the update packet.

CHANNEL HOPPING SCHEME FOR UPDATE OF DATA FOR MULTIPLE SERVICES
ACROSS MULTIPLE DIGITAL BROADCAST CHANNELS

PRIORITY CLAIM

This application claims the benefit of priority of commonly assigned U.S. Patent Application
5 12/122,622, filed May 16, 2008, the entire disclosures of which are incorporated herein by
reference.

FIELD OF THE INVENTION

Embodiments of this invention are related to digital broadcasting and more specifically to
updating data for services usable in conjunction with a digital broadcast signal.

10 BACKGROUND OF THE INVENTION

Introduced in the late 1990s, digital television (DTV) technology appealed to the television
broadcasting business and consumer electronics industries as offering new consumer services
and business opportunities that were impractical with previous analog television. Digital
television is more flexible and efficient than analog television. When properly used by
15 broadcasters, digital television allows higher-quality images and sound and more
programming choices than analog does. In DTV moving images and sound are sent and
received by means of discrete (digital) signals, in contrast to the analog signals used by
analog television. Digital television includes, but is not limited to Digital Terrestrial
Television (DTTV or DTT), which is an implementation of digital technology to provide a
20 greater number of channels and/or better quality of picture and sound using aerial broadcasts
to a conventional antenna (or aerial) as opposed to a satellite dish or cable connection.

The development of digital television has lead to many changes in television broadcasting
and related industries. Many countries have mandated a change from an analog television
signal format to a new digital format. One example of such a digital television broadcast
25 standard was developed by the Advanced Television Systems Committee. With a
conventional analog television broadcast, a video signal modulates a carrier wave signal that
is broadcast by a transmission tower. A television set contains a receiver that detects
broadcast signals. The receiver includes a tuner that selects a particular channel according to
its carrier frequency and a demodulator that extracts the video signal from the modulated
30 carrier signal. With a digital television signal, the video signal is generated in a digital format
or an analog video signal is converted to a digital format to produce a digital signal. The
carrier wave is modulated according to the digital signal format, e.g., using vestigial sideband

(VSB) modulation. This new format allows data for additional digital services to be broadcast along with a regular television signal. Examples of such services may include real time stock quotes, sports, weather and traffic updates and other services traditionally associated with delivery via two-way media, such as the internet, digital wireless services or
5 cellular telephone services.

The delivery of digital services by a primarily one-way medium through digital broadcast presents certain challenges and problems. Conventionally, a broadcast, digital or otherwise sends information on a schedule determined by the broadcaster. Digital services delivered by two-way media, by contrast, may be obtained more or less on demand. Updating information
10 delivered by digital broadcast over multiple broadcast channels presents certain problems heretofore unrecognized in the art.

It is within this context that embodiments of the present invention arise.

SUMMARY OF THE INVENTION

According to an embodiment of the present invention, a method for updating data broadcast over different channels may be implemented in a digital broadcast receiving device
15 configured to receive programming and data over a plurality of broadcast channels. A first digital broadcast signal may be received over a first digital broadcast channel. The receiving device may be tuned to a second digital broadcast channel at a predetermined time and a second digital broadcast signal may be received over the second digital broadcast channel.
20 The second digital broadcast signal includes data associated with one or more services resident on the receiving device. Selected data associated with one or more of the services may be extracted from the second digital broadcast signal and the data may be stored or utilized with the receiving device.

In some embodiments the first digital broadcast signal may include television programming
25 mixed with overlaid data. The overlaid data may be data associated with the first digital broadcast channel or another digital broadcast channel.

In some embodiments, receiving the first digital broadcast signal may include storing information derived from the first digital broadcast signal in a buffer. Images derived from the information stored in the buffer may be displayed while the second digital broadcast
30 signal is received.

In some embodiments the receiving device may include a tuner. The first digital broadcast signal may be received by tuning the tuner to the first broadcast channel and the tuner may be tuned to the second digital broadcast channel at the predetermined time.

5 In some embodiments, missing data that was not received as part of an update may be identified and retrieved.

In some embodiments, a geographic location of the receiving device may be determined. In such embodiments, tuning the receiver to the second digital broadcast channel at the predetermined time and receiving the second digital broadcast signal may include selecting the second digital broadcast channel based on the geographic location of the receiving device.
10 The selected data may be extracted from the second digital broadcast signal based on the geographic location.

In accordance certain embodiments, the second digital broadcast channel may be selected based on a schedule of update priority for the one or more services resident on the receiving device.

15 In some embodiments the predetermined time may be determined from data embedded in the first digital broadcast signal. For example, the data embedded in the first digital broadcast signal may indicate a time of a relevant data gap in the first digital broadcast signal.

In some embodiments the receiving device may include a first tuner and a second tuner. In such a case, the first tuner may be tuned to the first digital broadcast channel and the second
20 tuner may be selectively tuned to the second digital broadcast channel at the predetermined time. The second digital broadcast signal may be received with the first tuner and the first digital broadcast signal may be received with the first tuner.

According to another embodiment of the invention, a digital broadcast receiving device may include a receiver unit configured to receive programming and data over a plurality of
25 broadcast channels, a processor coupled to the receiver unit; a memory coupled to the processor; and a set of processor readable instructions embodied in the memory for execution on the processor. The instructions may be configured to implement a method for updating data broadcast over different channels including a) receiving a first digital broadcast signal over a first digital broadcast channel; b) receiving a second digital broadcast signal over the
30 second digital broadcast channel with the receiver at a predetermined time, wherein the second digital broadcast signal includes data associated with one or more services resident on

the receiving device; c) extracting data associated with one or more of the services; and d) storing the data in the memory or utilizing the data in program executed on the processor.

In some embodiments the receiver may include a single tuner. In other embodiments, the receiver may include first and second tuners.

- 5 In some embodiments, the device may further comprise a geographical positioning system coupled to the processor.

According to another embodiment, an update schedule may be generated for data transmitted with a digital broadcast signal. One or more input data streams may be received. The input data streams contain data for one or more digital broadcast data services. The data may be in
10 the form of a plurality of packets. Each packet may have a header and a payload. A time that an update packet containing data for one of the digital broadcast data services will be broadcast as part of a digital broadcast signal may be determined from the headers. A schedule packet may be generated containing the time that the update packet will be broadcast as part of the digital broadcast signal. The schedule packet may be broadcast
15 before broadcasting the update packet.

In some versions of this embodiment, the header may include information identifying a channel over which the packet associated with the header is to be broadcast.

In some versions of this embodiment, the header may include information identifying a type of data in the payload.

- 20 In some versions of this embodiment, the header may include information identifying a size of the packet.

In some versions of this embodiment, the header may include information identifying a given packet as being associated with other packets in the digital broadcast signal.

- 25 In some versions of this embodiment, the header may include information identifying a number of related downstream packets.

In some versions of this embodiment, the schedule packet may include update times for update packets that are to be transmitted over different digital broadcast channels.

In some versions of this embodiment, the schedule packet may include information relating to a broadcast time for one or more other schedule packets.

In some versions of this embodiment, the schedule packet may include information relating to a duty cycle with which schedule packets are broadcast.

BRIEF DESCRIPTION OF THE DRAWINGS

The teachings of the present invention can be readily understood by considering the

5 following detailed description in conjunction with the accompanying drawings, in which:

FIG. 1 is a schematic diagram illustrating a broadcast environment in which embodiments of the present invention may be employed.

FIG. 2 is a block diagram of an apparatus that implements scheduled updating of digital broadcast data according to an embodiment of the present invention.

10 FIG. 3 is a flow diagram illustrating a method of scheduled updating of digital broadcast data according to an embodiment of the present invention.

FIGS. 4A-4B schematically illustrate an example of scheduled updating of digital broadcast data with a single tuner according to an embodiment of the present invention.

15 FIG. 4C schematically illustrates an example of scheduled updating of digital broadcast data with a multiple tuners according to an embodiment of the present invention.

FIG. 5 is block diagram of an input data stream that may be used in conjunction with scheduled updating of digital broadcast data according to an embodiment of the present invention.

20 FIG. 6 is a flow diagram illustrating an example of generating an update schedule from multiple input data streams according to an embodiment of the present invention.

FIG. 7 illustrates a flow diagram illustrating an example of transmitting schedule packets at varying duty cycles according to an embodiment of the present invention.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

25 Although the following detailed description contains many specific details for the purposes of illustration, anyone of ordinary skill in the art will appreciate that many variations and alterations to the following details are within the scope of the invention. Accordingly, examples of embodiments of the invention described below are set forth without any loss of generality to, and without imposing limitations upon, the claimed invention.

Introduction

A digital television broadcast may be implemented in conjunction with multiple services that utilize data broadcast on the same frequency or channel as a conventional television broadcast. A broadcaster, such as a television station or television network, may bundle these services with its regular broadcast services. However, users of devices that receive the digital broadcast signal may wish to receive digital services provided by different broadcasters. For example a user may receive sports and weather updates from one broadcaster and stock updates from another broadcaster. If each broadcaster transmits over a different channel, the user must switch channels to receive updates for all three services. Consequently, in a digital broadcast environment, there is a previously unrecognized need for a way to automatically tune the user's device to different channels to receive updates for information associated with services on a user's device. Fulfilling such a need would allow a single device to update assets and objects that are broadcast on different channels.

FIG. 1 schematically illustrates a broadcast environment in which embodiments of the present invention may be employed. In such an environment broadcasters **102** receive or generate input data streams **101**. The input data streams **101** are converted to digital broadcast data streams **103**, which are converted to a digital broadcast signal **105** for reception by digital broadcast receivers **110**. By way of example, a digital broadcast signal **105** may be a modulated radiation signal transmitted from a broadcast tower **104**, e.g., in the form of an over-the-air broadcast, such as by radiofrequency electromagnetic wave signal. It is noted that the digital broadcast signal **105** transmitted by a given broadcast tower **104** may include multiple digital broadcast channels modulated at different carrier signal frequencies. Broadcast towers **104** associated with different broadcast units **102** may broadcast over different sets of frequencies. For example Broadcaster 1 may broadcast over a first set of carrier frequencies $f_1 \dots f_m$ and Broadcaster N may broadcast over a different set of carrier frequencies $f'_1 \dots f'_j$. There may be some overlap between the two sets of carrier frequencies.

Furthermore, the digital broadcast signal **105** may be transmitted in a form other than an over-the-air broadcast. Alternatively, embodiments of the invention may be used in conjunction with digital broadcasts transmitted over media such as cable (e.g., coaxial cable), optical fiber, or satellite transmission.

By way of example, the digital broadcast signal **105** may be configured in accordance with a digital broadcast standard. Examples of digital broadcast standards include, but are not limited to, the Digital Video Broadcasting (DVB) family of standards maintained in Europe and Australia, the Advanced Television Standards Committee (ATSC) family of standards

developed for use in the United States and Canada, the Integrated Services Digital Broadcasting (ISDB) family of standards developed for use in Japan, Digital Multimedia Broadcasting (DMB) standard used in South Korea.

The DVB family of standards includes the DVB-S and DVB-S2 standards for satellite television, the DVB-T and DVB-T2 standards for terrestrial television, DVB-C for cable television and DVB-H for mobile television and other DVB standards which have been or may be developed. The ATSC family of standards includes the ATSC standard for terrestrial television broadcasts and the ATSC M/H standard for broadcasts to mobile and handheld devices. The ISDB family of standards includes the ISDB-S, ISDB-T, and ISDB-C standards, which were developed for satellite, terrestrial and cable television respectively.

By way of example, and not by way of limitation, the digital broadcast signal **105** may be configured according to the ATSC or ATSC-M/H standards. The ATSC standard is described in detail, e.g., in “ATSC Digital Television Standard Part 1 – Digital Television System” (A/53, Part 1:2007), “ATSC Digital Television Standard Part 2 - RF/Transmission System Characteristics” (A/53, Part 2:2007), and “ATSC Digital Television Standard Part 3 – Service Multiplex and Transport Subsystem Characteristics” (A/53, Part 3, 2007), the disclosures of all three of which are incorporated herein by reference. The ATSC Data Broadcast Standard is described, e.g., in (ATSC Recommended Practice: Implementation Guidelines for the ATSC Data Broadcast Standard (Doc. A/90)”, which is incorporated herein by reference.

The input data stream **101** may include data streams from multiple sources. For example, within the broadcaster **102** data streams for different television program **107** may be made up of audio, video and ancillary data streams. These data streams may be multiplexed to form a program data stream associated with a given program **107**. Multiple program data streams may be multiplexed with each other into the broadcast data stream **103**. Furthermore, data service data streams **108** for broadcast data services $s_1 \dots s_k$ not specifically associated with a given program **107** may be overlaid (e.g., multiplexed) with the program data streams $P_1 \dots P_N$ into the broadcast data stream **103**.

The data streams **101** that make up digital broadcast data stream **103** may be subject to data transforms, such as source coding and compression. As used herein, “source coding and compression” refers to bit rate reduction methods, also known as data compression, appropriate for application to the video, audio, and ancillary digital data streams. The term

“ancillary data” includes control data, conditional access control data, and data associated with the program audio and video services, such as closed captioning. “Ancillary data” can also refer to independent program services. The broadcast unit **102** may include a coder configured to minimize the number of bits needed to represent the audio and video
5 information. If configured according to the ATSC standard, the broadcast unit **102** may employ the MPEG-2 video stream syntax for the coding of video and the Digital Audio Compression (AC-3) Standard for the coding of audio.

The broadcast unit **102** may also subject the digital broadcast data stream **103** to service and multiplex transport operations. As used herein, “service multiplex and transport” refers to the
10 means of dividing the digital data stream into “packets” of information, the means of uniquely identifying each packet or packet type, and the appropriate methods of multiplexing video data stream packets, audio data stream packets, and ancillary data stream packets into a single data stream. By way of example, and not by way of limitation, digital broadcast unit **102** may employ the MPEG-2 transport stream syntax for the packetization and multiplexing
15 of video, audio, and data signals for digital broadcasting systems. Such packetization and multiplexing is described e.g., ISO/IEC 13818- 1:2000 (E), International Standard, Information technology – Generic coding of moving pictures and associated audio information: systems”, which is incorporated herein by reference.

The digital broadcast data stream **103** may be converted to a digital broadcast signal **105**
20 through processes referred to as channel coding and modulation. The channel coder takes the data bit stream encoded in the digital broadcast data stream **103** and adds additional information that can be used by a receiving device **110** to reconstruct the data from the received signal which, due to transmission impairments, may not accurately represent the transmitted signal. A modulation subsystem (or physical layer) uses the digital data stream
25 information to modulate the transmitted signal. By way of example and not by way of limitation, the ATSC standard, the modulation subsystem offers two modes. Both modes are based on vestigial sideband modulation. One mode is a terrestrial broadcast mode known as 8-VSB. The other mode is a high data rate mode known as 16-VSB.

A digital broadcast receiving device **110** receives the digital broadcast signal **105** and extracts
30 the digital broadcast data stream **103** encoded within the digital broadcast signal **105**. By way of example, and not by way of limitation, the digital broadcast receiving device **110** may include a digital receiver **111**, a processor **114**, a memory **115**, a display **117** and a data storage device **118**. The digital broadcast receiving device **110** may be any type of device

capable of receiving and utilizing the digital broadcast signal **105**. By way of example, the digital broadcast receiving device **110** may be a digital television set, digital radio receiver, personal computer, laptop computer, a mobile or handheld device such as a cellular telephone, mobile internet device or mobile digital television receiver.

- 5 Furthermore, the term digital broadcast receiving device encompasses “digital media receivers”, GPS devices, game consoles, portable game devices, home, mobile or device security systems, and any combination thereof and including other devices for which the present invention may be coupled to provide command and control.

The digital receiver **111** may include one or more tuners **112** and a decoder **113**. The tuner(s)
10 **112** may be coupled to an antenna **119** that receives the digital broadcast signal **105**. The tuner **112** selects one or more particular frequencies from among the various signals that are picked up by the antenna **119**. The tuner **112** and decoder **113** may extract data and generate audio and video signals from the digital broadcast signal **105**. By way of example the tuner **112** and decoder **113** may provide the following functions: demodulation, transport stream
15 demultiplexing, decompression, error correction, analog-to-digital conversion, AV synchronization and media reformatting to fit the specific type of display **117** optimally.

As used herein, demodulation refers to the process of transforming the received digital broadcast signal **105** into a usable signal from which data may be extracted and/or from which quality images and sound may be produced.

- 20 Transport Stream Demultiplexing may be implemented, e.g., where multiple digital signals are combined and then transmitted from one antenna source to create over the air broadcasts. In such a case, the decoder **113** may decode the digital broadcast data stream **103** and convert it to a suitable form for display of a particular program of the audio and/or video components with the display **117** or for extraction of a broadcast service data stream **108** from the digital
25 broadcast data stream **103**. The decoder **113** may implement decompression if the digital broadcast data stream **103** contains data in compressed form. The tuner **112** may decompress such data, e.g., by unpacking compressed packets of digital data to their original size.

- The decoder **113** may also implement Error Correction to make sure that any data that is missing from the received digital broadcast signal **105** can be corrected. For instance,
30 sometimes interference or a poor-quality signal will cause the loss of data information that the tuner **112** receives. In such cases, the decoder **113** may perform a number of checks and

repair data so that a signal can be viewed on a TV set or data may be utilized by the processor **114**.

The decoder **113** may implement AV Synchronization to coordinate audio and video signals being displayed on the display **117** in proper time. AV synchronization ensures that the audio
5 does not lag behind the video that is being displayed on the display **117** or vice versa, so that both audio and video are in sync. Media reformatting allows the display **117** to properly display video images using the data extracted from the digital broadcast signal. Media reformatting is important since the formatting of images on TV sets may differ significantly according to the technology employed. For example, some televisions utilize an interlaced
10 picture, whereas others utilize a progressive-scan picture.

The display **117** may be any suitable video and/or audio display usable with the digital broadcast signal **105**. By way of example, and not by way of limitation, the display **117** may include a video monitor, such as a cathode ray tube (CRT), plasma display, liquid crystal display (LCD) or organic light-emitting diode (OLED) display. In addition, the display **117**
15 may include one or more devices for generating audio, e.g., one or more speakers.

The receiving device **110** may also implement a backchannel **120** that allows information to be sent from the device to a broadcast unit **102** or a data center affiliated with the broadcast unit. The back channel **120** may be implemented through a digital broadcast signal transmitted from the device **110**, e.g., via the antenna **119**. Alternatively, the backchannel
20 **120** may be implemented through some other mode of communication such as wireless telephony (e.g., cellular), wireless internet, cable, optical fiber and the like.

The receiving device **110** may also include a data storage device **118** for non-volatile storage of data. Examples of data storage devices include hard disk drives, flash memories, compact disk (CD) drives, digital video disk (DVD) drives, tape drives, and the like.

25 The processor **114** may execute software program instructions that facilitate the above-referenced functions. In addition, the processor **114** may execute program instructions $SW_1 \dots SW_p$ for various digital broadcast data services. Data for these data services may be updated as part of the digital broadcast data stream **103** that is carried by the digital broadcast signal **105**. The program instructions $SW_1 \dots SW_p$ may operate on corresponding data $D_1 \dots D_p$
30 for these broadcast data services that is stored, e.g., in the memory **115**. According to an embodiment of the present invention, the digital broadcast receiving device **110** may update the data $D_1 \dots D_p$ for digital broadcast data services that are broadcast over different channels

according to a schedule. Any combination of subscriptions or services may be updated according to the schedule.

Specifically, the processor **114** may execute instructions that implement a scheduler **SCH** that implements a method for updating data broadcast over different channels. A first digital broadcast signal **105** may be received over a first digital broadcast channel. The receiving device **110** may be tuned to a second broadcast channel at a predetermined time and a second digital broadcast signal **106** may be received over the second digital broadcast channel. The second broadcast signal **106** includes data **108** associated with one or more services resident on the receiving device **110**. Selected data associated with one or more of the data services may be extracted from the second digital broadcast signal **106** and the data may be stored in or used by the receiving device **110**. By way of example, the extracted data may be stored in the memory **115** or storage device **118** for later use by one or more of the software programs **SW₁...SW_p**. The extracted data may replace portions of the data **D₁...D_p** for the broadcast data services. Alternatively, the extracted data may be utilized by the receiving device without storing it. For example, extracted data may be utilized by one or more of the data service programs **SW₁...SW_p** and then discarded.

It is noted that for the sake of example, the two digital broadcast signals **105**, **106** are shown as being transmitted from different towers **104**. This is not to be construed as a limitation upon any embodiment of the invention. Alternatively, the two digital broadcast signals may originate from the same broadcast tower **104**.

In some embodiments, the scheduler **SCH** may be turned off in order to save power for the receiving device **110**. This may be useful, e.g., if the device **110** relies on battery power, as in a mobile device. In other embodiments, the data extracted from the digital broadcast signal **105** may be stored in a buffer in the memory **115**, while the receiver **111** tunes one of the tuners **112** to other channels to receive data updates until a certain amount of the buffer has been emptied. At that point the receiver **111** may tune back to the first channel to receive a fresh stream.

Information may be filtered from a geographic perspective based on device position information. To facilitate such functionality, the receiving device **110** may optionally include a position location system **116**, such as a GPS receiver. For example, in the case of a mobile or hand-held device, GPS data may be used to filter weather and traffic updates and only download those that are relevant to the area in which the device is presently located. In some

embodiments, the function of the position location system **116** may be implemented by one of the tuners **112** in conjunction with software running on the processor **114**. The position location signal may originate from one or more of the towers **104**.

By way of example, a digital broadcast receiving device **200** shown in FIG. 2 may be
5 configured to implement scheduled updating according to an embodiment of the present invention as shown in FIG. 1. By way of example, and without loss of generality, the receiving device **200** may be implemented as part of a digital television set, personal computer, video game console, personal digital assistant, mobile or handheld device such as a cellular phone or personal digital assistant, portable email device and the like, or other digital
10 device. The device **200** may include a central processing unit (CPU) **205** and a memory **206** coupled to the CPU **205**. The CPU **205** may be configured to run software applications and, optionally, an operating system. Some embodiments of the present invention may take advantage of certain types of processor architecture in which the CPU **205** includes a main processor **205A** and one or more auxiliary processors **205B**. Each auxiliary processor may
15 have its own associated local data storage. One example, among others of such a processor architecture is a Cell Processor. An example of a Cell Processor architecture is described in detail, e.g., in Cell Broadband Engine Architecture, copyright International Business Machines Corporation, Sony Computer Entertainment Incorporated, Toshiba Corporation August 8, 2005 a copy of which may be downloaded at <http://cell.scei.co.jp/>, the entire
20 contents of which are incorporated herein by reference.

The memory **206** may store applications and data for use by the CPU **205**. The memory **206** may be in the form of an integrated circuit, e.g., RAM, DRAM, ROM, and the like). A computer program **201** may be stored in the memory **206** in the form of instructions that can be executed on the processor **205**. The instructions of the program **201** may be configured to
25 implement, amongst other things, an update scheduler having certain features described below.

The update scheduler program **201** may facilitate updating of data for digital broadcast data services that are resident on the device **200**. By way of example, and not by way of limitation, the memory **206** may contain service data **203** and/or programs usable in
30 conjunction with such services. Examples of such services include, but are not limited to stock quotes **204**, weather **207**, traffic **208** and sports **209**. Examples of stock quote service data **204** include, but are not limited to, prices of stocks. Examples of weather service data

207 include, but are not limited to, the text of weather forecasts. Examples of traffic service data **208** include local traffic conditions, notices of road closures or hazards and the like. Examples of sports data **209** include, but are not limited to, scores, statistics and standings.

By way of example, the update scheduler program **201** may include instructions to update the
5 service data **203** in memory **206** with data broadcast over different channels. A first broadcast stream may be received over a first digital broadcast channel. The receiving device **200** may be tuned to a second broadcast channel at a predetermined time and a second broadcast stream may be received over the second digital broadcast channel. Selected data associated with one or more of the services may be extracted from the second digital
10 broadcast signal and the data may be stored or utilized with the receiving device.

The receiving device **200** may also include well-known support functions **210**, such as input/output (I/O) elements **211**, power supplies (P/S) **112**, a clock (CLK) **213** and cache **214**. The device **200** may further include a fast data storage device **215** such as a hard disk drive that provides non-volatile storage for applications and data. The fast storage device **215** may
15 be used for temporary or long-term storage of files **216** retrieved from a slower data storage device **220**. By way of example, the storage device **215** may be a fixed disk drive, removable disk drive, flash memory device, tape drive. The slower storage device **220** may be, e.g., a CD-ROM, DVD-ROM, Blu-ray, HD-DVD, UMD, or other optical storage devices. Files **216** from the slower storage device **220** may be temporarily stored in the storage device **215** in a
20 hardware cache for quick loading into the memory **206**.

The device **200** may include a digital broadcast receiver **240** which may be coupled to an antenna **241**. One or more digital broadcast tuners **242** may receive digital broadcast signals picked up by the antenna **241**. The receiver **240** may further include a decoder **244**, which may implement the functions described above.

25 One or more user input devices **222** may be used to communicate user inputs from one or more users to the system **200**. By way of example, one or more of the user input devices **222** may be coupled to the client device **200** via the I/O elements **211**. Examples of suitable input device **222** include keyboards, mice, joysticks, touch pads, touch screens, light pens, still or video cameras, and/or microphones. The client device **200** may include a network interface
30 **225** to facilitate communication via an electronic communications network **227**. The network interface **225** may be configured to implement wired or wireless communication over local

area networks and wide area networks such as the Internet. The system **200** may send and receive data and/or requests for files via one or more message packets **226** over the network **227**.

The system **200** may further comprise a graphics subsystem **230**, which may include a
5 graphics processing unit (GPU) **235** and graphics memory **239**. The graphics memory **239** may include a display memory (e.g., a frame buffer) used for storing pixel data for each pixel of an output image. The graphics memory **239** may be integrated in the same device as the GPU **235**, connected as a separate device with GPU **235**, and/or implemented within the memory **206**. Pixel data may be provided to the graphics memory **239** directly from the CPU
10 **205**. Alternatively, the graphics unit may receive video signal data extracted from a digital broadcast signal from the decoder **244**. Alternatively, the CPU **205** may provide the GPU **235** with data and/or instructions defining the desired output images, from which the GPU **235** may generate the pixel data of one or more output images. The data and/or instructions defining the desired output images may be stored in memory **206** and/or graphics memory
15 **239**. In an embodiment, the GPU **235** may be configured (e.g., by suitable programming or hardware configuration) with 3D rendering capabilities for generating pixel data for output images from instructions and data defining the geometry, lighting, shading, texturing, motion, and/or camera parameters for a scene. The GPU **235** may further include one or more programmable execution units capable of executing shader programs.

20 The graphics subsystem **230** may periodically output pixel data for an image from the graphics memory **239** to be displayed on a video display device **250**. The video display device **250** may be any device capable of displaying visual information in response to a signal from the device **200**, including CRT, LCD, plasma, and OLED displays that can display text, numerals, graphical symbols or images. The digital broadcast receiving device
25 **200** may provide the display device **250** with a display driving signal in analog or digital form, depending on the type of display device. In addition, the display **250** may include one or more audio speakers that produce audible or otherwise detectable sounds. To facilitate generation of such sounds, the client device **200** may further include an audio processor **255** adapted to generate analog or digital audio output from instructions and/or data provided by
30 the CPU **205**, memory **206**, and/or storage devices **215**, **220**.

The receiving device **200** may optionally include a position location device **270**. Such a device may be based on any suitable technology capable of providing information on the

geographic location of a device. Examples of existing technology include global positioning satellite (GPS) technology, inertial guidance technology, and the like. Information from such devices may be used in digital broadcast data applications such as navigation for mobile or hand-held devices.

- 5 The components of the device **200**, including the CPU **205**, memory **206**, support functions **210**, data storage devices **215**, **220** user input devices **222**, network interface **225**, graphics unit **230**, audio processor **255** and position location device **270** may be operably connected to each other via one or more data buses **260**. These components may be implemented in hardware, software or firmware or some combination of two or more of these.
- 10 By way of example, and not by way of limitation, the update scheduler program **201** may update the data for digital broadcast services that are broadcast over different channels in accordance with a method **300** depicted in the flow diagram of FIG. 3. As indicated at **302** a first broadcast stream is received over a first digital broadcast channel. The receiving device **200** is tuned to a second digital broadcast channel at a predetermined time as indicated at **304**.
- 15 The first broadcast stream may include digital television programming mixed with overlaid data. The overlaid data may be associated with the first digital broadcast channel or with another digital broadcast channel. There are a number of ways in which data may be overlaid with digital television programming. For example, data packets may be interleaved into a digital television broadcast stream. Such a scheme is sometimes referred to as time division
- 20 multiplexing (TDM). In this scheme two or more signals or bit streams are transferred apparently simultaneously as sub-channels in one communication channel. In reality the two bit streams are physically taking turns on the channel. In TDM, the time domain may be divided into several recurrent timeslots of fixed length, one for each sub-channel. A sample, byte or data block of each sub-channel may be transmitted during its corresponding timeslot,
- 25 e.g., sub-channel 1 during timeslot 1; sub-channel 2 during timeslot 2, etc.
- A second broadcast stream is then received over the second digital broadcast channel, as indicated at **306**. The second broadcast stream includes data associated with one or more services resident on the receiving device **200**. Data associated with one or more of these services may be extracted from the second broadcast stream as indicated at **308**. As used
- 30 herein the term “extracted” in this context refers to the process of demodulating the signal carrying the second broadcast stream and decoding it into data that can be read and manipulated by the processor. Extracting the data from the broadcast stream may also

include the process of separating data relevant to specific services from amongst the data decoded from the digital broadcast signal.

Once the relevant data has been extracted it may be stored in or utilizing by the receiving device **200** as indicated at **310**. By way of example, the relevant data may be stored in the memory for later use by the service programs. Alternatively, the service programs may make immediate use of the relevant data and then either store or discard the data. In some embodiments of the present invention, updates for certain broadcast data services **203** may have different priorities. In such cases, the update scheduler **201** may be configured to select the channel for such updates based on an update priority schedule **UPS** for the broadcast data services **203**. The update priority schedule **UPS** may be stored in the memory **206**.

There are a number of different ways in which the receiving device may scheduled updates may be implemented. There are a number of different ways in which the scheduler **201** may determine the predetermined time for switching channels in order to receive updates. In some embodiments, the update scheduler **201** may determine a predetermined time for switching from one channel to another from data embedded in the digital broadcast signal to which the receiver **240** is currently tuned. By way of example, and not by way of limitation, data may be embedded in the broadcast signal indicating the time of a relevant data gap in a stream of programming packets in the digital broadcast signal. The scheduler **201** may utilize such data to select the predetermined time for changing channels to coincide with the data gap.

For example, as shown in FIGs. 4A-4B, a single tuner **242** may update data received over multiple channels where data and digital television programming a time division multiplexed. As shown in FIG. 4A, first and second digital data streams are transmitted over first and second channels **CH1** and **CH2**. The data stream on the first channel **CH1** contains digital television programming data **PR1** that is time division multiplexed in the data stream with other data. The other data may be in the form of programming for a different sub-channel or data for a digital broadcast data service. The data stream on the second channel **CH2** includes data for a digital broadcast data service **D1** that is time division multiplexed with other data. The other data on the second channel **CH2** may be data for other digital broadcast services or digital television programming for one or more sub-channels of the second channel **CH2**.

Initially, the single tuner **242** is tuned to the first channel **CH1**, as shown in FIG. 4A. After the decoder **244** decodes the program data **PR1** from the first channel's data stream the decoded data may be used directly for display on the display device **250** or may be stored in the memory **206**, e.g., in a buffer for later display.

- 5 If the data stream on the first channel **CH1** is time divisional multiplexed there may be gaps in the data stream during which the device **200** may receive no relevant broadcast program or other data. For example, suppose the user of the device **200** is watching a certain program on a certain sub-channel of the first channel **CH1**. If the time division multiplexing is done on a schedule, there may be intervals of time during which data other programming is transmitted
- 10 over other sub-channels of the first channel **CH1**. The decoder **244** may ignore this data if the device **200** is not configured to receive them. During such intervals, the update scheduler **201** may direct the tuner **242** to switch to the second channel **CH2** to receive updates for digital broadcast data service **D1** as shown in FIG. 4B. The data may be decoded from the data stream by the decoder **244** and displayed on the display **250** or stored in a data buffer for
- 15 later use or display. The update scheduler may then direct the tuner **242** to switch back to the first channel **CH1** to receive programming data **PR1** during the next time slot for such data.

Gaps in buffered programming data **PR1** or digital service data **D1** stored in the memory **206** may be filled, e.g., through forward error correction. Forward error correction (FEC) refers to a system of error control for data transmission, whereby the sender adds redundant data to

20 its messages, also known as an error correction code. This allows the receiver to detect and correct errors (within some bound) without the need to ask the sender for additional data. The advantage of forward error correction is that a back-channel is not required, or that retransmission of data can often be avoided, at the cost of higher bandwidth requirements on average.

- 25 As an alternative to FEC, the update scheduler **201** may be configured to identify one or more missing data packets from the second broadcast stream that were not received as part of an update. Such packets may be identified, e.g., if each packet contains a sequential identifier and the scheduler **201** determines from these identifiers that one or more packets were not received. The scheduler **201** may then invoke a routine for retrieving the one or more
- 30 missing data packets, e.g., by downloading them through a back channel, such as the network **227**.

Embodiments of the present invention may also be implemented on receiver devices having a two or more tuners. For example, as shown in FIG. 4C, the receiving device **200** may include a first tuner **242A** and a second tuner **242B**. In such a case, the first tuner **242A** may be tuned to the first digital broadcast channel **CH1** and the second tuner **242B** may be selectively
5 tuned to another digital broadcast channel (e.g., **CH2** or **CH3**) at the predetermined time. A digital broadcast signal from the other channel may be received with the second tuner **242B** and the digital broadcast signal from the first channel **CH1** may be received with the first tuner **242A**.

According to certain embodiments, it may be useful to determine a geographic location of the
10 receiving device. Certain digital broadcast services, such as weather and traffic information are local in nature. By way of example and not by way of limitation, a user of a digital receiving device located in, say, a particular locale within the Los Angeles metropolitan area would likely be interested in traffic information for that locale. If such a user is traveling to a destination in a different locale, the user might also be interested in traffic conditions in the
15 vicinity of the destination and along the route to the destination. The digital broadcast signal may include traffic information for several different locales within the Los Angeles area. In such a case it may be useful to filter out the traffic information most relevant to the user of the receiving device. To facilitate such filtering, the position locating device **270** may provide geographic location information that may be used to filter location-specific relevant
20 information from the digital broadcast signal. Furthermore, in accordance with certain embodiments of the present invention, the scheduler **201** may select the digital broadcast channel to which to tune for particular data updates (e.g., traffic or weather data updates) based on the geographic location of the receiving device as determined by the position locating device **270**.

By way of example, and not by way of limitation, the digital broadcast signal may include traffic data update packets that include in their headers information identifying a region for which the information is relevant. The update scheduler **201** may extract the information from these headers and use such information to determine whether to store, use or discard the information in the packet. For example, a packet header for a packet containing traffic
25 information may identify the information as being relevant to Northridge. Information obtained by the position locating device **270** may indicate that the device is located in Northridge, heading to Northridge or traveling on a route through Northridge. Based on this information, the scheduler **201** may choose to store or utilize the information. Similarly, if
30

the packet header indicates that the information is for some irrelevant region, e.g., one where the device is not located, going to, or scheduled to travel through, the scheduler **201** may be configured to ignore the packet.

In some embodiments, the update scheduler **201** may determine a switching scheme or
5 schedule for updating data from different channels using schedule data received as part of a digital broadcast signal. By way of example, and not by way of limitation, FIG. 5 depicts a data stream **500** that may be used in conjunction with scheduled updating of digital broadcast data according to an embodiment of the present invention. The data stream **500** (e.g., an
input data stream **101** or digital broadcast data stream **103**) may include a plurality of data
10 packets **502, 504, 506**. Each packet may include a header **H1, H2, H3** and a payload **P1, P2, P3**. The headers **H1, H2, H3** for the packets **502, 504, 506** may include information regarding the data in the corresponding payloads **P1, P2, P3**. Such information may include, but is not limited to, a channel identifier, a data type, an optional packet, information identifying a number of related packets, and a packet identifier.

15 The packet headers **H1, H2, H3** may also indicate one or more of the following: a frequency of a broadcast burst, a total number of groups of bursts that make up a complete update for a service, a time start signal in which a broadcast or service or burst or complete update for a service will occur, a channel, or frequency of the transmission, a sub-channel associated with the packet, a URL associated with the broadcast, service or transmission, and any
20 combination thereof and including that which may be coupled to an application or operating system and prompting the application or operating system to take an action in response thereto.

The channel identifier may identify the particular channel (or channels) over which the packet is to be broadcast. The sub-channel identifier may identify the particular sub-channel
25 within a channel for a service with which the packet is associated. The data type may identify the particular data service or data type for the data in the payload. The packet size may specify a size of the data contained in the payload. The packet identifier and information identifying a number of related packets may be used to facilitate reconstruction of a block data sent over the course of multiple packets. For example, the packet identifier
30 may uniquely identify a packet as being part of a particular group of packets and the information identifying a number of related packets may indicate that this particular packet is the fifth packet in the group. In some versions, information identifying related packets may

include information identifying a number of related downstream packets (i.e., packets to be broadcast later).

FIG. 6 illustrates an example of how an update schedule may be generated from multiple input data streams. As seen in FIG. 6, an input data stream **601** for a digital broadcast signal may contain input streams for multiple digital broadcast channels **C1**, **C2**, **C3**. In this example, each channel **C1**, **C2**, **C3** is broadcast over a different carrier frequency. The digital broadcast signals for the channels **C1**, **C2**, **C3** may be broadcast more or less simultaneously by a transmitter **606** using frequency division multiplexing. Individual data streams for different programming and digital data services within the within each channel may be multiplexed using time division multiplexing. The data streams for each channel are made up of packets **603**, having a payload **P1...P9** and corresponding headers **H1...H9**. As discussed above, each header may identify the type of data in the packet. In particular the headers may identify whether a packet is associated with television programming or a data service. If a packet is associated with a data service, the header for that packet may identify the specific data service. The headers of all the packets in the input data stream **601** may be analyzed by an update schedule generator **602** to determine which packets contain updates for data services. Furthermore, the update schedule generator **602** may determine a time of broadcast for each of the packets **603**. For example, the update schedule generator may receive the packets in the order in which they are to be broadcast. From this broadcast order, the update schedule generator may determine the time at which a given packet is to be broadcast. In the example depicted in FIG. 6, the packets having payloads **P1**, **P4**, and **P7** are to be broadcast at time **T1**, the packets having payloads **P2**, **P5**, and **P8** are to be broadcast at time **T2**, and the packets having payloads **P3**, **P6**, and **P9** are to be broadcast at time **T3**.

The update schedule generator **602** may combine the information from the packet headers and the transmission times to generate an update one or more schedule packets **604**. These packets may contain information indicating the time of broadcast of update packets. By way of example, suppose that the packet payloads **P1**, **P6** and **P9** in the input data stream **601** contain update for digital broadcast data services. The update schedule generator **602** may determine this from information in the headers **H1**, **H6**, and **H9**. From the order of the packets in the in data stream **601** the update schedule generator **602** may determine that the packet containing payload **P1** is to be broadcast over channel **C1** at time **T1** and the packets containing payloads **P6** and **P9** are to be broadcast over channels **C2** and **C3** respectively at time **T3**. The update schedule generator **602** may combine this information into the update

schedule packet **604** along other information included in the packet headers, as described above. For the sake of example, the update schedule is shown in the form of a table. An “X” in the table indicates that an update is scheduled to be broadcast over a particular channel at a particular time. Blank spaces in the table indicate that no update is scheduled for a given channel at a given time. Spaces in the table marked with an “X” may include additional information relating to the update, e.g., obtained from the header of the corresponding update packet. This particular configuration is not meant as a limitation upon the invention. The update schedule packets **604** may be inserted into the digital broadcast signals for channels **C1**, **C2** and **C3** and transmitted by the transmitter **606** before the corresponding update packets containing payloads **P1**, **P6** and **P9** are broadcast. In this way a receiving device may receive an update schedule packet independent of whether it is tuned to any particular one of the channels **C1**, **C2** or **C3**. A given update schedule packet **604** may be broadcast multiple times over a given channel to increase the chance that a receiving device will receive it in time to implement channel switching to receive a relevant update packet.

In some situations, it may be desirable to repeatedly broadcast the update schedule packets **604** at a regular duty cycle to increase the likelihood that they will be received in a timely manner. In addition, the number of data packets broadcast between update schedule packets and the times at which the update schedule packets are broadcast may also vary. As seen in FIG. 7, the update schedule packets may include information identifying the duty cycle with which update schedule packets are broadcast. For example, update schedule packets **SP** may be broadcast along with data packets **P1...P11**. Initially, the update schedule packets **SP** may be broadcast at a duty cycle **d₁** of one update schedule packet followed by three data packets. The update schedule packets **SP** may identify that a subsequent schedule packets will be broadcast at a new duty cycle **d₂** of one update schedule packet followed by two data packets. The update scheduler **201** may take such update schedule packet duty cycle changes into account when determining when to hop between channels.

In some embodiments, the update schedule packet scheme described above may be utilized to synchronize services on different sub-channels within a given digital broadcast channel transmitted over a given frequency. For example, as depicted in FIG. 7, update schedule packets **SP** may include information relating to different sub-channels with a digital broadcast stream may be time multiplexed. Services on different sub-channels may be used by different applications within the receiving device **200**. The update schedule program **201**

may make use of sub-channel update information from the update schedule packets to efficiently allocate computational resources within the device **200**.

Embodiments of the present invention allow for efficient updating of data services received in conjunction with a digital broadcast signal. Data services may be updated while a device
5 is presenting digital television programming so that a user has timely access to relevant data.

While the above is a complete description of the preferred embodiment of the present invention, it is possible to use various alternatives, modifications and equivalents. Therefore, the scope of the present invention should be determined not with reference to the above description but should, instead, be determined with reference to the appended claims, along
10 with their full scope of equivalents. Any feature described herein, whether preferred or not, may be combined with any other feature described herein, whether preferred or not. In the claims that follow, the indefinite article “A”, or “An” refers to a quantity of one or more of the item following the article, except where expressly stated otherwise. The appended claims are not to be interpreted as including means-plus-function limitations, unless such a limitation
15 is explicitly recited in a given claim using the phrase “means for”.

WHAT IS CLAIMED IS:

- 1 1. In a digital broadcast receiving device configured to receive programming and data over a
2 plurality of digital broadcast channels, a method for updating data broadcast over
3 different channels, comprising:
4 a) receiving a first digital broadcast signal over a first digital broadcast channel;
5 b) tuning the receiving device to a second digital broadcast channel at a predetermined
6 time;
7 c) receiving a second broadcast signal over the second digital broadcast channel, wherein
8 the second digital broadcast signal includes data associated with one or more services
9 resident on the receiving device;
10 d) extracting selected data associated with one or more of the services from the second
11 digital broadcast signal; and
12 e) storing or utilizing the selected data with the receiving device.
- 1 2. The method of claim 1, wherein the first digital broadcast signal includes television
2 programming mixed with overlaid data.
- 1 3. The method of claim 2 wherein the overlaid data is data associated with the first digital
2 broadcast channel.
- 1 4. The method of claim 2 wherein the overlaid data is data associated with another digital
2 broadcast channel.
- 1 5. The method of claim 1, wherein a) includes storing information derived from the first
2 digital broadcast signal in a buffer.
- 1 6. The method of claim 5, further comprising displaying images derived from the
2 information stored in the buffer during b).
- 1 7. The method of claim 1, wherein the receiving device includes a tuner, wherein a) includes
2 tuning the tuner to the first digital broadcast channel and wherein b) includes tuning the
3 tuner to the second digital broadcast channel at the predetermined time.

- 1 8. The method of claim 1, further comprising, identifying data missing from the second
2 digital broadcast signal that was not received as part of an update and retrieving the
3 missing data.
- 1 9. The method of claim 1, further comprising determining a geographic location of the
2 receiving device.
- 1 10. The method of claim 9 wherein b) includes selecting the second digital broadcast channel
2 based on the geographic location of the receiving device.
- 1 11. The method of claim 9 wherein d) includes extracting selected data based on the
2 geographic location.
- 1 12. The method of claim 1, wherein b) includes selecting the second digital broadcast channel
2 based on a schedule of update priority for the one or more services resident on the
3 receiving device.
- 1 13. The method of claim 1 wherein b) includes determining the predetermined time from data
2 embedded in the digital first broadcast signal.
- 1 14. The method of claim 13 wherein the data embedded in the first broadcast stream indicates
2 a time of a relevant data gap in the first digital broadcast signal.
- 1 15. The method of claim 1 wherein the receiving device includes a first tuner and a second
2 tuner, wherein a) includes tuning the first tuner to the first digital broadcast channel and
3 wherein b) includes tuning the second tuner to the second digital broadcast channel at the
4 predetermined time and wherein c) includes receiving the second digital broadcast signal
5 with the second tuner while receiving the first digital broadcast signal with the first tuner.
- 1 16. A digital broadcast receiving device, comprising:
2 a receiver unit configured to receive programming and data over a plurality of digital
3 broadcast channels,
4 a processor coupled to the receiver unit;
5 a memory coupled to the processor;
6 a set of processor readable instructions embodied in the memory for execution on the
7 processor, the instructions being configured to implement a method for updating data

- 8 broadcast over different channels, comprising:
9 a) receiving a first digital broadcast signal over a first digital broadcast channel;
10 b) receiving a second digital broadcast signal over the second digital broadcast channel
11 with the receiver at a predetermined time, wherein the second digital broadcast signal
12 includes data associated with one or more services resident on the receiving device;
13 c) extracting data associated with one or more of the services; and
14 d) storing the data in the memory or utilizing the data in program executed on the
15 processor.
- 1 17. The device of claim 16 wherein the receiver includes a single tuner.
- 1 18. The device of claim 16 wherein the receiver includes first and second tuners.
- 1 19. The device of claim 16, further comprising a geographical positioning system coupled to
2 the processor.
- 1 20. A method for generating an update schedule for data transmitted with a digital broadcast
2 signal, comprising:
3 a) receiving one or more input data streams containing data for one or more digital
4 broadcast data services, wherein the data is in the form of a plurality of packets, each
5 packet having a header and a payload;
6 b) determining from the headers of the plurality of packets a time that an update packet
7 containing data for one of the digital broadcast data services will be broadcast as part of a
8 digital broadcast signal;
9 c) generating a schedule packet containing the time that the update packet will be
10 broadcast as part of the digital broadcast signal; and
11 d) broadcasting the schedule packet before broadcasting the update packet as part of the
12 digital broadcast signal.
- 1 21. The method of claim 20, wherein the header includes information identifying a channel
2 over which the packet associated with the header is to be broadcast.
- 1 22. The method of claim 20, wherein the header includes information identifying a type of
2 data in the payload.

1 23. The method of claim 20 wherein the header includes information identifying a size of the
2 packet.

1 24. The method of claim 20 wherein the header includes information identifying a given
2 packet as being associated with other packets in the digital broadcast signal.

1 25. The method of claim 20 wherein the header includes information identifying a number of
2 related downstream packets.

1 26. The method of claim 20 wherein the schedule packet includes update times for update
2 packets that are to be transmitted over different digital broadcast channels.

1 27. The method of claim 20 wherein the schedule packet includes information relating to a
2 broadcast time for one or more other schedule packets.

1 28. The method of claim 20 wherein the schedule packet includes information relating to a
2 duty cycle with which schedule packets are broadcast.

1/6




FIG. 1

2/6





FIG. 2

3/6

300**FIG. 3**

4/6




FIG. 4A




FIG. 4B




FIG. 4C

5/6




FIG. 5




FIG. 6

6/6




FIG. 7