

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁴: H04M 11/08, 15/00, H04N 7/10 H04H 9/00

(11) International Publication Number:

WO 87/04884

(43) International Publication Date:

13 August 1987 (13.08.87)

(21) International Application Number:

PCT/US87/00242

A1

(22) International Filing Date:

3 February 1987 (03.02.87)

(31) Priority Application Number:

826,082

(32) Priority Date:

4 February 1986 (04.02.86)

(33) Priority Country:

U

(71) Applicant: PACIFIC BELL [US/US]; 140 Montgomery Street, San Francisco, CA 94104 (US).

(72) Inventors: LEWIS, David, Robert; 55 Adair Lane, Portola Valley, CA 94025 (US). PERKINS, Albert, James; 616 Brenda Lee Drive, San Jose, CA 95123 (US). RAYA, Gasper, Louis; 2122 Mendocino Drive, West Pittsburg, CA 94565 (US). VARGO, Michael, Francis; 522 Chestnut Street #8, San Carlos, CA 94070 (US). HAGGMARK, James, Eric; 2160 Martin Road, Tracy, CA 95376 (US).


(74) Agents: WATT, Phillip, H. et al.; Fitch, Even, Tabin & Flannery, Room 900, 135 South LaSalle Street, Chicago, IL 60603 (US).

(81) Designated States: AT (European patent), AU, BE (European patent), CH (European patent), DE (European patent), FR (European patent), GB (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent).

Published

With international search report. With amended claims.

(54) Title: PAY-PER-VIEW CATV SYSTEM



(57) Abstract

A system (11) for interfacing a pay-per-view CATV system with the switched public network telephone system. In a conventional switched public network telephone system having at least one central office switch (10) and a plurality of subscriber loops (16) operatively coupled to the central office switch (10), each subscriber loop (16) is identified by an originating telephone number. The subscriber selects a specific one of the scheduled television programming events by calling a telephone number which uniquely identifies the selected event. The called and originating numbers are identified, digitized and combined to form a digital word. The digital word is then transmitted to the CATV supplier (30). This system makes program selection more convenient for the subscribers and facilitates billing of the subscribers by supplier (30) for individual selections.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	ML	Mali
ATU BB BE BG BJ BR CF CG	Australia	GA	Gabon	MR	Mauritania
BB	Barbados	GB	United Kingdom	MW	Malawi
BE	Belgium	HU	Hungary	NL	Netherlands
BG	Bulgaria	TT	Italy	NO	Norway
BJ	Benin	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic	SD	Sudan
ÇF	Central African Republic		of Korea	SE	Sweden
€G	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
√/CM	Cameroon	LK	Sri Lanka	TD	Chad
/ DE	Germany, Federal Republic of	LU	Luxembourg	TG	Togo
/ DK	Denmark	MC	Monaco	US	United States of America
ं स	Finland	MG	Madagascar		

30

35

PAY-PER-VIEW CATY SYSTEM

The present invention relates generally to television viewing and more particularly to novel apparatus and techniques for enabling a viewer to conveniently select a particular one of scheduled programming events and to be billed only for such events as may from time to time be selected.

BACKGROUND OF THE INVENTION

Videly available to the public on a subscription basis.

Usually, the subscriber has several levels of service available, with the cost of the subscription dependent upon the options available with each level of service. For example, the basic subscription service usually includes local VHF and UHF programming, which is normally also broadcast for antenna reception throughout the subscription area, and remote VHF and UHF programming from nearby cities, which would not be generally receivable with a local reception antenna at the subscriber premises.

Additional CATV services above the basic service, for example, include movie channels which release the latest movies, and sports channels which make available sporting events normally blacked out from commercial television. However, a subscriber may not customarily obtain a subscription to one or more of these optional services without also obtaining a subscription to the basic service.

The basic subscription service charges are computed from the cost to rebroadcast the local and remote programming and a rental fee for CATV company equipment located at the subscriber premises. Such equipment may include decoders or descramblers for example. The subscription service charges to the optional CATV services includes the right to receive all scheduled programming events provided by the

15

20

25

30

35

optional service. The subscription charge is based upon the cost to the CATV company to make the service available and the royalties payable to the copyright owners of the programmed events. However, many potential subscribers do not desire to view all scheduled events but merely from time to time desire to view only a selected event, such as a recently released movie or the re-release of an old movie classic. For these viewers the subscription charges of the optional service may be too large to justify the purchase of the subscription for a limited use.

In order to expand the market base of CATV subscribers, there have been several attempts to develop systems wherein a viewer may preselect and only receive an individual programming event. With this type of system the subscriber would not be forced to subscribe to a basic service which he may not desire should normal antenna reception provide adequate service, or be forced to pay the subscription charge for the entire optional service, i.e., paying royalties on all events which the potential subscriber does not wish to view. A CATV system in which the subscriber would only have to pay rental fees for the lease of CATV company equipment and service charges for the events viewed has the potential of expanding the subscriber base of CATV companies.

Two different types of systems have heretofore been developed wherein the subscriber may selectively view a scheduled programming event. In the first group of these systems, the subscriber accesses the CATV computer over phone lines and selects an event from a menu by entering the appropriate data from the telephone key-pad. The menu may either be a recorded voice prompt transmitted through the telephone or a video prompt simultaneously displayed on the subscribers television set. For example, see U.S.

10

20

25

Patent No. 4,381,522 for "Selective Viewing" and U.S. Patent No. 4,008,369 for a "Telephone Interface Subscription Cable Television System. The second group of systems utilizes an interrogation of a subscriber terminal at the subscriber premises. subscriber terminal stores information concerning those programs which the subscriber has viewed. The CATV computer interrogates the subscriber terminal overphone lines to retrieve the stored data for billing purposes. For example, see U.S. Patent No. 4,170,782 and "Pay TV: A Pay per Minute System Prototype", Television: Journal of the Royal Television Society, March 1984, pp. 79-83.

In the above cited '522 patent, there is provided a printed menu of available selectable 15 programs, each designated by a number. The menu is stored in the computer located at the CATV company and broadcast over a menu channel. A viewer at the subscriber premises selects a program by first dialing the CATV station telephone number. The telephone system then connects the viewer's telephone to the CATV computer. The CATV computer responds by transmitting to the viewer an audible tone to signal the viewer to dial the number corresponding to the desired program on the menu. The CATV computer stores the information on the program source location, the status of the selected program source, and the available channels and the schedules for each.

The significant disadvantage and limitation of the system described in the '522 patent is that the 30 CATV Company would require additional information on how to bill the subscriber. Such billing information may only be obtained by additional equipment that would have to be located at the subscriber premises or by requiring the subscriber to input an account number 35 along with the menu selection. Such billing

10

20

25

30

35

information equipment requires additional technical complexity not described in the '522 patent. Accordingly, the '522 patent is described as being most useful for providing video-tex information for the advertisement of products and services. However, where copyrighted material is required, such system does not allow for convenient means for billing the subscriber for service charges.

The above cited '369 patent describes a PABX telephone interface cable television system especially. useful in hotels and motels for distributing free and premium program channels via a coaxial cable television signal distribution network to one or more subscriber terminals and associated television sets. Again, the subscriber dials a predetermined access number so that 15 the subscriber can be connected with a control and monitoring station. After a telephone connection is made, the program requests must be subsequently entered through the telephone key-pad. The control and monitoring station includes means for sending output signals to a paper tape printer to provide a record of the channel use activity of each subscriber terminal in the system. Hence, no automatic billing is contemplated in this system, but must be subsequently added to the bill for hotel services.

The above mentioned publication discloses one such automatic billing system wherein a CATV company provided recording device makes a record of the subscriber's usage of the CATV programming events. recording device, located at the subscriber premises, is periodically interrogated by the CATV company over telephone lines to obtain subscriber usage information necessary to generate a bill to the subscriber. significant disadvantage and limitation of using a recording device at the subscriber premises is the possibility that the subscriber may tamper with or

10

25

30

bypass the recording device, ultimately resulting in a loss of revenues to the CATV company.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to overcome one or more of the disadvantages described hereinabove.

It is a primary object of the present invention to provide a cable television system wherein the subscriber may select only those events which may from time to time be desired.

A principle object of the present invention is to provide a cable television system wherein the subscriber is billed only for those events which are selected.

Another object of the present invention is to provide a cable television system which eliminates the need for the subscriber to enter program selection or account number information through the telephone interface.

Yet another object of the present invention is to eliminate the use of a recording device located at the subscriber premises to record subscriber usage of the cable television system.

According to the present invention, a pay-per-view CATV system is interfaced with the switched public network telephone system. A conventional switched public network telephone system has at least one central office switch and a plurality of subscriber loops operatively coupled to the central office switch. Each subscriber loop extends to a subscriber location and is terminated by at least one telephone identified by an originating telephone number. The subscriber selects a specific one of the scheduled television programming events by selecting a telephone number which uniquely identifies the selected event. To select an event, the subscriber dials the

20

25

telephone number for the selected event. This call is handled by the central office switch in a conventional manner. The called and originating numbers are identified, digitized and combined to form a digital word. The digital word is then transmitted to the CATV supplier. From the digital word, the CATV supplier can identify the subscriber and the subscriber selected event so that the subscriber receives the selected event and a bill for viewing such event.

Other objects, advantages and features of the present invention will become apparent from the following specification when read in conjunction with the drawings, and from the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

15: FIGURE 1 is a block diagram of a pay-per-view CATV system constructed according to the present invention; and

FIGURE 2 is a flow chart illustrating the sequence of steps according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to FIGURE 1, there is shown a CATV pay-per-view system constructed according to the principles of the present invention. The pay-per-view system of the present invention employs a service node 11 designed for interaction between the established switched public telephone network which includes a plurality of central offices 10, and the cable company system 30.

To avoid confusing the principles of the

present invention, only two central offices 10 are
illustrated in FIGURE 1. Each central office 10
includes a central office switch 12. A plurality of
telephones 14 are each operatively coupled to its
respective central office switch 12 over an associated
one of a plurality of subscriber loops 16. Each of the
subscriber loops 16 is an ordinary twisted pair which

15

20

25

30

35

extends from the central office switch 12 located in the respective central office 10 to the telephone 14 which is located at the subscriber premises. The routing of calls between telephones 14 served by a single central office 10 or between telephones 14 served by separate central offices 10 is well known and need not be described herein. For example, it is to be understood that trunk lines (not shown) connect the central offices 10 to each other within a telephone system.

According to the present invention, the service node 11 includes a modular switch 18 operatively connected to a plurality of the central offices 10. More specifically, the modular switch 18 is coupled to each central office switch 12 over a standard one-way outgoing trunk 20. For example, trunk 20 may be a traffic service position system (TSPS) trunk which normally connects a central office switch 12 to an operator's console. However, other standard trunk types may be used in the present invention, as long as such trunks have the capability of having called and calling directory numbers sent over them as hereinbelow described.

The modular switch 18 performs telephonic switching and signaling functions under the control of the communications controller 22 described hereinbelow, which is also part of the service node 11. The modular switch 18 provides trunk termination for each of the outgoing trunks 20 connected thereto and trunk supervision sensing from the originating central office 10 to the communications controller 22. Such trunk supervision sensing includes on-hook and off-hook sensing. The modular switch 18 also provides trunk supervision signaling toward the originating central office 10 both in response to commands from the communications controller 22 and automatically,

10

15

20

25

30

35

according to established conventions. One type which may be employed in the present invention as the modular switch 18 is the MSP model modular switching peripheral commercially available from Redcom Laboratories.

The communications controller 22 provides for overall system control. It acts as the controller of the modular switch 18 and oversees the processing of incoming calls arriving on the trunks 20. communications controller 22 assigns a unique state variable to each of the outgoing trunks 20 terminated by the modular switch 18 under its control. communication controller 22 steps the state of each trunk 20 through discrete states as events occur during the call handling process. The state of the trunk state variable is stepped through a closed cycle (idle to idle) once for each incoming call process. A second function of the communications controller is to serve as the originator of messages, containing the digital words described hereinabove, which are sent to the cable vendor premises, as described hereinbelow. this respect, the communications controller implements one or more layers of a data communications protocol. This protocol is chosen to ensure the error free transportation of these messages.

In a preferred embodiment of the present invention, the communications controller 22 is a supermicrocomputer running suitable applications specific programs. An example of one such super-microcomputer is the Tricept model microcomputer commercially available from Morrow Designs, Inc.

As mentioned hereinabove, the pay-per-view system of the present invention shares each central office switch 12 with normal message traffic. The central office 10 will process calls made under this invention no differently than it processes any other message traffic. A cyclic call handling process is

١

20

25

30

35

performed by shared equipment within each central office 10, such equipment operating without modification. The phases within the central office 12 cyclic call handling process include call origination, dialed directory number collection, translation, idle trunk search, trunk seizure, digit outpulsing, audio path completion, talk and call termination. summary, the central office switch 12 does not treat calls made under the present invention any differently than other message traffic. Following a call setup phase, the central office switch 12 creates a voice grade path through itself, which connects the caller to the outgoing trunk 20. The call to the pay-per-view telephone number is processed similar to a toll message 15 call usually handled by a conventional Class 4 switch.

Each central office switch 12 includes a plurality of multifrequency (MF) outpulsers, generally indicated at 24. In conventional message traffic, the MF outpulser sends digits and simple process state information to a destination central office 10 over the interoffice connecting trunks (not shown). These MF outpulsers 24 are used for the pay-per-view system of the present invention in a manner similar to that used for other interoffice calls. A central office (CO) switch controller 26 located in each central office 10 selects an idle MF outpulser from the pool of MF outpulsers 24 when one is needed. The CO switch controller 26 controls the establishment of an audio path from the selected MF outpulser to the outgoing trunk 20.

At the beginning of the call set up phase, the CO switch controller 26 detects when one of the telephones 14 goes "off-hook" by conventionally sensing a DC current in the associated subscriber loop 16. The called number is collected from the subscriber loop 16 by the CO switch controller 26 as it is dialed. If the

10

20

collected called number is one assigned to a cable vendor programming event, the central office switch controller 26 will, as a result of the execution of a conventional data-base look up function, identify an outgoing trunk 20 connecting the central office switch 12 to the modular switch 18, as the destination of such a call. Under the control of the CO switch controller 26, a conventional automatic number identification (ANI) unit 28 conventionally identifies the calling or originating number. After the CO switch controller 26 determines that the destination of a given call is an outgoing trunk 20, and after the calling number has been determined, the CO switch controller 26 will select an idle MF outpulser 24, seize the outgoing trunk, create a voice path through the CO switch 12 **15**: connecting the selected MF outpulser 24 to the outgoing trunk, and send the called and calling numbers to the selected MF outpulser. The selected MF outpulser then outpulses the called and calling numbers as multifrequency (MF) tones. The MF tones are sent to the modular switch 18 over the outgoing trunk 20 of the same central office 10 in which the MF outpulser resides.

Associated with each modular switch 18 is a multifrequency receiver pool 28, for receiving the MF 25 tones generated by the multifrequency outpulsers and transmitted over the outgoing trunks 20. Each MF receiver pool 28 includes a plurality of MF decoders which share the use of a single board computer (SBC). The term MF decoder is used to refer to the device 30 which converts MF tones into digital form. receiver pool 28 connects to the modular switch 18 and converts MF tones arriving over one of the trunks 20 from an originating central office 10 into a digital form. More particularly, the modular switch 18 35 connects to each MF receiver pool 28 via a standard

20

phone line or twisted pair. An audio path is created through the modular switch connecting the incoming trunk to a unique MF receiver. The SBC scans the digital output of several of the MF decoders looking for digits, and collects contiguous digits to form a character string or digital word containing a called or calling number. The SBC sends this string, together with its own identity, to the communications controller In a preferred embodiment of the present invention, each MF decoder may be a Model No. M-985 decoder commercially available from Teltone in conjunction with a single board computer commercially available from Micromint Company, to construct each MF receiver pool 28. Alternatively, the MF receiver pool 15 can be integrated into the modular switch without altering the system's function.

Connected to the communications controller 22 is the cable vendor equipment including cable company system computer 30 and fall-back modem selector 32. The lines connecting the service node communications controller 22 to the fall-back modem selector 32 are leased lines and will always be active. The data link between the service node and CATV vendor equipment connects on the service node at communications controller 22. The line is asynchronous and uses conventional format and protocol. Of course, modems are provided at each end of the leased lines 34 for providing data communications. The service node modem will be operated in its originating mode and cable company equipment will respond in answer mode. These modes are maintained for as long as normal operation progresses.

Also associated with the modular switch 18 is an audio response unit pool 36 (ARUP) in order to provide confirmation messages to the calling party. Each ARUP 36 contains several audio response units

10

20

25

30

35

(ARU). Each ARU has a message loaded by placing an ordinary phone call to the number assigned to a standard phone line (not shown) connected to the ARU, keying in a password and following a product-specific update procedure. In a preferred embodiment of the present invention, each ARU is a digital announcer commercially available from Cook Electric.

With further reference to FIGURE 2, there is shown a flow diagram of the operation of the pay-per-view system of the present invention. As described above, when the subscriber takes his telephone 14 off hook, a DC current is developed in the associated subscriber loop 16. The central office switch 12 detects this DC current and returns a dial 15 tone over the subscriber loop 16 to the subscriber telephone 14. When the subscriber hears the dial tone the subscriber dials the telephone number associated with the event the subscriber wishes. The central office switch detects the special services number and routes the call to the service node. Furthermore, as described hereinabove, the called and calling numbers are transmitted to the service node which then provides ring back tone to the caller. The audio response unit pool through the modular switch 18 will return an audio message to the subscriber through the established voice path described above. When the subscriber hears the confirmatory message, the subscriber simply returns his telephone 14 to on hook. The central office switch 12 detects the telephone 14 going on hook and terminates the call.

As this call is terminated, the communication controller 22, storing the called and calling numbers, will initiate a link to the CATV cable company as hereinabove described. An inquiry is first transmitted to the cable company equipment and if operating, and acknowledgment is received. Upon receipt of the

15

acknowledgment, the communications controller 22 will download the called and calling number digitals words which it has stored for receipt by the cable company. At the end of this transmission, the cable company will send an acknowledgment back to the communications controller 22 thereby terminating that connection.

There has been described above novel apparatus and techniques for a pay-per-view system wherein a subscriber may preselect a specific one of a plurality of television programming events and be billed only for that event. However, modifications, variations and other uses of the present invention may be made by those skilled in the art without departing from the inventive concepts herein. For example, the techniques of the present invention may be expanded to other special services such as the current 976 service. Accordingly, the present invention is to be limited solely by the scope of the following claims.

10

15

20

25

WHAT IS CLAIMED IS:

- In a switched public network telephone system having at least one central office switch, a plurality of subscriber loops, and a plurality of telephones, each of said subscriber loops operatively coupling an associated one of said telephones to said central office switch, said central office switch connecting one of said telephones identified by a calling number to another of said telephones identified by a called number in response to said telephone identified by said calling number originating a telephone call to said telephone identified by said called number, an apparatus for subscriber selection of a specific one of a plurality of scheduled television program events provided by a supplier of such events comprising: means for detecting selected called numbers electrically coupled through any of said subscriber loops, each of said selected called numbers identifying one of said television program events; means for identifying the calling number of the telephone coupled to each one of said subscriber loops from which one of said selected called numbers was detected; means for developing a digital word representing said detected called number and said calling number originating each said called number; and means for transmitting each said digital word to said supplier, said supplier identifying the subscriber and the subscriber selected event from said digital word.
- 2. An apparatus as set forth in Claim 1
 further comprising: means for transmitting said

 digital data to a central processor; means for storing digital data from each said subscriber loop in said central processor, said transmitter means transmitting said stored digital data to said supplier at regular intervals.

10

1.5

20

25

30

35

- In a switched public network telephone system having at least one central office switch, a plurality of subscriber loops, and a plurality of telephones, each of said subscriber loops operatively coupling an associated one of said telephones to said central office switch, said central office switch connecting one of said telephones identified by a calling number to another of said telephones identified by a called number in response to said telephone identified by said calling number originating a telephone call to said telephone identified by said called number, a method for subscriber selection of a specific one of a plurality of scheduled television program events provided by a supplier of such events comprising the steps of: detecting selected called numbers electrically coupled through any of said subscriber loops, each of said selected called numbers identifying one of said television program events; identifying the calling number of said telephone coupled to each one of said subscriber loops in which one of said selected called numbers was detected; developing a digital word representing said detected called number and said calling number originating each said called number; and transmitting each said digital word pair to said supplier, said supplier identifying the subscriber and the subscriber selected event from said digital word pair.
- 4. In a switched public network telephone system having a plurality of central office switches, a plurality of subscriber loops associated with each of said central office switches, and a plurality of telephones, each of said subscriber loops operatively coupling an associated one of said telephones to one of said central office switches, said central office switches connecting one of said telephones identified by a calling number to another of said telephones

10

15

20

25

identified by a called number in response to said telephone identified by said calling number originating a telephone call to said telephone identified by said called number, an apparatus for subscriber selection of a specific one of a plurality of scheduled television program events provided by a supplier of such events comprising: means for detecting at each of said central office switches selected called numbers electrically coupled through any of said subscriber loops coupled thereto, each of said selected called numbers identifying one of said television program events; means for identifying the calling number of the telephone coupled to each one of said subscriber loops from which one of said selected called numbers was detected; means for developing a digital word representing said detected called number and said calling number originating each said called number; and means for transmitting each said digital word to said supplier, said supplier identifying the subscriber and the subscriber selected event from said digital word.

- 5. An apparatus as set forth in Claim 4 further comprising means for storing each said digital word from said subscriber loops, said transmitting means transmitting said stored digital data to said supplier at regular intervals.
- 6. An apparatus as set forth in Claim 5 wherein said transmitting means includes a dedicated data link between said modular service node and said supplier.

AMENDED CLAIMS

[received by the International Bureau on 12 June 1987 (12.06.87); original claims 1—6 amended; new claims 7 and 8 added (8 pages)]

Please amend Claim 1 as follows:

1. (amended) In a switched public network telephone system having at least one central office switch, a plurality of subscriber loops, and a plurality of telephones, each of said subscriber loops operatively coupling an associated one of said telephones to said central office switch, said central office switch connecting one of said telephones identified by a calling number to another of said telephones identified by a called number in response to said telephone identified by said calling number originating a telephone call to said telephone identified by said called number, an apparatus for subscriber selection of a specific one of a plurality of scheduled television program events provided by a

supplier of such events <u>having premises remote from</u> said apparatus, said apparatus comprising:

means for detecting selected called numbers electrically coupled through any of said subscriber loops, each of said selected called numbers identifying one of said television program events;

means for identifying the calling number of the telephone coupled to each one of said subscriber loops from which one of said selected called numbers was detected;

means for coupling a confirmation message to the said subscriber loop identified by each said calling number in response to said detecting means detecting one of said selected called numbers:

means for developing a digital word
representing <u>each</u> said detected called number and <u>each</u>
said calling number originating each said <u>detected</u>
called number; and

means for transmitting [each] a said digital word to said [supplier] supplier's premises, said digital word representing the called number detected by said detecting means and the calling number identified by said identifying means [, said supplier identifying the subscriber and the subscriber selected event from said digital word], said transmitting means transmitting said digital word to said supplier subsequent to said coupling means coupling said confirmation message to said subscriber loop.

Please amend Claim 2 as follows:

2. (amended) An apparatus as set forth in Claim 1 further comprising:

a central processor coupled to said
transmitting means:

means for transmitting [said] digital data

representing each said digital word developed by said developing means to said central processor;

means coupled to said central processor for storing said digital data [from each said subscriber loop in said central processor], said [transmitter] transmitting means transmitting said stored digital data to said [supplier] supplier's premises at regular intervals.

Please amend Claim 3 as follows:

3. (amended) In a switched public network telephone system having at least one central office switch, a plurality of subscriber loops, and a plurality of telephones, each of said subscriber loops operatively coupling an associated one of said telephones to said central office switch, said central office switch connecting one of said telephones identified by a calling number to another of said telephones identified by a called number in response to said telephone identified by said calling number originating a telephone call to said telephone identified by said called number, a method for subscriber selection of a specific one of a plurality of scheduled television program events provided by a supplier of such events comprising the steps of:

detecting a telephone call to one of a plurality of predetermined [selected] called numbers electrically coupled through any of said subscriber loops, each of said [selected] predetermined called numbers identifying one of said television program events;

identifying the calling number of the said telephone which originated said detected telephone call: [coupled to each one of said subscriber loops in which one of said selected called numbers was

detected; 1

coupling a confirmation message to the said subscriber loop identified by said calling number in response to detecting one of said [selected] predetermined called numbers:

developing a digital word representing said detected called number and the said identified calling number originating [each] said telephone call to said detected called number; and

transmitting [each] said digital word [pair] to said supplier, subsequent to coupling said confirmation message to the said subscriber loop identified by said calling number. [, said supplier identifying the subscriber and the subscriber selected event from said digital word pair.]

Please amend Claim 4 as follows:

4. (amended) In a switched public network telephone system having a plurality of central office switches, a plurality of subscriber loops associated with each of said central office switches, and a plurality of telephones, each of said subscriber loops operatively coupling an associated one of said telephones to one of said central office switches, said central office switches connecting one of said telephones identified by a calling number to another of said telephones identified by a called number in response to said telephone identified by said calling number originating a telephone call to said telephone identified by said called number, an apparatus for subscriber selection of a specific one of a plurality of scheduled television program events provided by a supplier of such events, said apparatus being remotely located with respect to each said supplier's premises, said apparatus comprising:

means for detecting at each of said central office switches selected called numbers electrically coupled through any of said subscriber loops coupled thereto, each of said selected called numbers identifying one of said television program events;

means for identifying the calling number of the telephone coupled to each one of said subscriber loops from which one of said selected called numberswas detected;

means for coupling a confirmation message to the said subscriber loop identified by each said calling number in response to said detecting means detecting one of said selected called numbers:

means for developing a digital word representing <u>each</u> said detected called number and <u>each</u> said calling number originating each said called number; and

means for transmitting [each] a said digital word to said supplier said digital word representing the called number detected by said detecting means and the calling number identified by said identifying means, said transmitting means transmitting said digital word to said supplier subsequent to said coupling means coupling said confirmation message to said subscriber loop. [, said supplier identifying the subscriber and the subscriber selected event from said digital word.]

Please amend Claim 5 as follows:

5. (amended) An apparatus as set forth in Claim 4 further comprising means for storing each said digital word developed by said developing means, [from said subscriber loops] said transmitting means further comprising means for transmitting said stored digital words [data] to said supplier at regular intervals.

Please amend Claim 6 as follows:

6. (amended) An apparatus as set forth in Claim 5 wherein said transmitting means includes a dedicated data link between said [modular service node] transmitting means and said supplier.

Please add the following new Claim 7:

7. In a switched public network telephone system having at least one central office switch, and a plurality of telephones, each of said telephones being identified by a telephone number, said telephone system including means for operatively coupling a calling telephone to an answering telephone in response to the telephone number identifying said answering telephone being communicated to a central office switch by said calling telephone or an apparatus connected thereto, an apparatus for subscriber selection of one of a plurality of services or products offered by one or more vendors of said services or products, said apparatus being remotely located with respect to each said vendor's premises, said apparatus comprising:

means for detecting each said selected telephone number communicated by a calling telephone to a central office switch, each said selected telephone number identifying a predetermined vendor and a specified product or service offered by said vendor, said detecting means including signal generating means for generating a signal indicating the selected telephone number so detected;

means for identifying the telephone number identifying the calling telephone which communicated a said selected telephone number;

means for coupling a confirmation message to the said subscriber loop identified by each said calling number in response to said detecting means detecting one of said selected called numbers;

means for developing a digital word

representing each said telephone number detected by

said detecting means and each said telephone number

identified by said identifying means, said developing

means being responsive to said signal generating means

and said identifying means; and

means for transmitting said digital word tothe vendor specified by a said detected telephone
number, said digital word representing the called
number detected by said detecting means and the calling
number identified by said identifying means, said
transmitting means transmitting said digital word to
said vendor subsequent to said coupling means coupling
said confirmation message to said subscriber loop.

Please add the following new Claim 8:

8. (new) In a switched public network telephone system having a plurality of central offices, each said central office including a central office switch serving a plurality of telephones, each of said telephones being identified by a telephone number, said telephone system including means for operatively coupling a calling telephone to [a] an answering telephone in response to the telephone number identifying said answering telephone being communicated to a central office switch by said calling telephone or an apparatus connected thereto, an apparatus for subscriber selection of one of a plurality of services or products offered by one or more vendors of said services or products, said apparatus being remotely located with respect to each said vendor's premises, said apparatus comprising:

means for coupling said apparatus to at least two of said central offices;


means for detecting each said selected telephone number communicated by a calling telephone to a central office switch, each said selected telephone number identifying a predetermined vendor and a specified product or service offered by said vendor, said detecting means including signal generating means for generating a signal indicating the selected telephone number so detected;

means for identifying the telephone number identifying the calling telephone which communicated a said selected telephone number;


means for coupling a confirmation message to the said subscriber loop identified by each said calling number in response to said detecting means detecting one of said selected called numbers;

means for developing a digital word representing each said telephone number detected by said detecting means and each said telephone number identified by said identifying means, said developing means being responsive to said signal generating means and said identifying means; and

means for transmitting said digital word to the vendor specified by a said detected telephone number, said digital word representing the called number detected by said detecting means and the calling number identified by said identifying means, said transmitting means transmitting said digital word to said vendor subsequent to said coupling means coupling said confirmation message to said subscriber loop.







SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International Application NoPCT/US87/00242

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) 3							
According to International Patent Classification (IPC) or to both National Classification and IPC INT. CL.(4) HO4M 11/08; HO4M 15/00; HO4N 7/10; HO4H 9/00							
U.S.							
II. FIELDS SEARCHED							
Minimum Documentation Searched +							
Classification System Classification Symbols							
358/84,85,86; U.S. 379/93,94,102,105,127,142,246; 455/2,4,5							
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched 5 -							
III. DOCU	JMENTS CONSIDERED TO BE RELEVANT 14						
Category *	Citation of Document, 16 with indication, where appropriate, of the relevant passages 17	Relevant to Claim No. 13					
X	Zenith Electronics, "Advanced New Cable TV Technology Developed For Impulse-Pay-Per-	1,3,4					
	View", published 03 June 1985, by Zenith Electronics, Corp (Glenview, Illinois), see especially page 2, obtained from DIALOG Data-						
Y	base: 'File 621'.	2,5,6					
A	The Yankee Group, "Cable And The Telcos: From Confrontation To Detente," published June 1983 by the Yankee Group (Boston) see pages 162 to 167.	1-6					
A	US, A, 3,920,908 (Kraus) 18 November 1975.	1-6					
Т	US, A, 4,590,516 (Abraham) 20 May 1986.	1-6					
A	WO, A, 85/03830 (Russell) 29 August 1985.	1-6					
	•	: 					
* Special categories of cited documents: 15 "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "V. CERTIFICATION Date of the Actual Completion of the International Search 2 O 1 APRIL 1987 "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention cannot be considered novel or cannot be considered novel or cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family Date of Mailing of this International Search Report 2 1 3 APR 1987							
International Searching Authority 1 Signature of Authorized Officer 20 Letth 2. Leave TSA/IIS Keith F. George							