



(22) Date de dépôt/Filing Date: 1997/06/16

(41) Mise à la disp. pub./Open to Public Insp.: 1998/01/16

(45) Date de délivrance/Issue Date: 2006/04/11

(30) Priorité/Priority: 1996/07/16 (08/680,947) US

(51) Cl.Int./Int.Cl. *B65D 83/08* (2006.01),
B65D 5/72 (2006.01), *A61B 19/02* (2006.01),
A61B 17/04 (2006.01), *A61B 17/06* (2006.01),
B65D 5/32 (2006.01)


(72) Inventeurs/Inventors:
GEMMA, EDWARD A., JR., US;
VISELLI, DAVID, US;
RITCHIE, TERRY L., US

(73) Propriétaire/Owner:
UNITED STATES SURGICAL CORPORATION, US

(74) Agent: MCFADDEN, FINCHAM

(54) Titre : DISTRIBUTEUR UNIVERSEL POUR ENSEMBLES DE SUTURE

(54) Title: UNIVERSAL SUTURE DISPENSER BOX



(57) Abrégé/Abstract:

A dispenser box for suture packages includes an outer casing and drawer portion slidably disposed within the outer casing. The dispenser preferably includes at least two access portals for withdrawal of the suture packages. A first access portal allows the suture packages to be withdrawn in accordance with the U.S. preferred mode, wherein the dispenser box disposed so that the suture packages are stacked in a vertical array and withdrawn horizontally. A second access portal allows the suture packages to be withdrawn in accordance with the European preferred mode, wherein the suture packages are stacked in a horizontal array and are withdrawn vertically.

ABSTRACT

A dispenser box for suture packages includes an outer casing and drawer portion slidably disposed within the outer casing. The dispenser preferably includes at
5 least two access portals for withdrawal of the suture packages. A first access portal allows the suture packages to be withdrawn in accordance with the U.S. preferred mode, wherein the dispenser box disposed so that the suture packages are stacked in a vertical array
10 and withdrawn horizontally. A second access portal allows the suture packages to be withdrawn in accordance with the European preferred mode, wherein the suture packages are stacked in a horizontal array and are withdrawn vertically.

1793 Canada

UNIVERSAL SUTURE DISPENSER BOX**5 BACKGROUND****1. Technical Field**

The container disclosed herein relates to a dispensing box for surgical suture packages. More specifically, the suture dispensing box is configured to
10 be used in both the U.S. preferred mode wherein the box is vertically disposed, and in the European preferred mode, wherein the box or a portion thereof is disposed horizontally.

2. Background of the Art

15 Modern surgical procedures draw upon a wide variety of types and sizes of surgical sutures. These sutures are usually contained in individual retainers or foil laminate envelopes wherein the suture is wound, for example, in a figure eight type pattern, or coil. Indicia
20 indicating the size and type of the suture are typically printed on the enclosure envelopes to facilitate identification.

Dispensing boxes for such suture packages are known in the art. As shown In Fig. 1, the preferred
25 format for dispensing boxes in the United States is to have the longer side of the box 2 disposed vertically. Suture packages 50 are retrieved horizontally from the bottom of the vertical stack of suture packages by grasping a shorter side of the generally rectangular

suture package. As suture packages are withdrawn, the stack drops down to reposition other packages for retrieval.

The preferred European format, however, is with the longer side of the dispenser 2a and the stack of suture packages 50 disposed horizontally, as shown in Fig. 2. The dispenser 2a acts like a drawer, the suture packages being withdrawn vertically from the dispensing box 2a by grasping the longer side of the generally rectangular suture package. A typical operating room has suture box shelving or racks configured to accommodate either the U.S. or European boxes.

Because the U.S. and European dispensing boxes have different configurations, manufacturers currently provide separate boxes for each market. As such, two separate manufacturing, labeling and inventory systems must be maintained. What is needed is a dispensing box that can be used in both the U.S. preferred mode and the European preferred mode. Such a universal dispenser would eliminate the need for separate box constructions for different markets, providing both economy of manufacture and flexibility of use.

SUMMARY

A universal suture dispenser box is provided herein. The universal suture dispenser is a container for holding a plurality of suture packages in a stacked array. In a preferred embodiment, the container has first and

second adjacent sides, the suture packages being individually oriented perpendicular to the first side and parallel to the second side. The container has first and second access portals for withdrawal of the suture packages from the stacked array. The first access portal permits the suture packages to be withdrawn from the container in a line of direction perpendicular to the first side and parallel to the second side. The second access portal permits the sutures to be withdrawn from the container in a line of direction parallel to both the first and second sides. In a most preferred embodiment, the universal suture package dispenser includes an outer casing and a drawer portion slidably disposed within the outer casing. The drawer portion has a storage space for holding the stacked array of suture packages.

The outer casing preferably includes a first side, a second side foldably connected to the first side along an edge thereof, a third side foldably connected to the second side on an edge of the second side opposite to the edge at which the first side is foldably connected, a fourth side foldably connected to the third side along an edge of the third side opposite to that at which the second side is connected, and a fifth side foldably connected to the third side, the aforementioned sides forming at least a partial enclosure defining an interior space and having an open end. The drawer portion includes first, second, third, fourth, fifth, sixth, and seventh

4

panels, the first and third panels being foldably
connected to the second panel along adjacent edges
thereof, the fifth and fourth panels being foldably
connected to the sixth panel along adjacent edges of the
5 third panel, and the fifth and seventh panels being
foldably connected to the sixth panel along respective
adjacent edges of the sixth panel. The fifth and second
panels are foldably connected to opposite edges of the
third panel, and the sixth and third panels are foldably
10 connected to opposite edges of the fifth panel.

The universal suture package dispenser can be
positioned vertically for dispensing suture packages in
the U.S. preferred mode, or horizontally, wherein the
suture packages can be withdrawn in the European preferred
15 mode. Preferably, a spacer panel is included to conform
the dimensions, of the dispensing box to those of
conventional box shelving.

DETAILED DESCRIPTION OF THE DRAWINGS

20 Figs. 1 and 2 illustrate prior art box
containers for dispensing suture packages.

Fig. 3 is a perspective view of a preferred
universal dispenser box described herein positioned in a
vertical orientation.

25 Fig. 4 is a perspective view of the universal
dispenser box of Fig. 3 positioned in a horizontal
orientation.

5

Fig. 5 is a plan view of the blank used to make the outer case of the universal dispenser shown in Fig. 3.

Fig. 6 is a perspective view illustrating the folding and assembly of the blank of Fig. 5 to form the
5 outer case.

Fig. 7 is a plan view of a blank used to make the drawer portion of the dispensing box shown in Fig. 3.

Fig. 8 is a perspective view showing the folding and assembly of the blank of Fig. 7 to form the drawer.

10 Fig. 9 is an exploded perspective view illustrating the assembly of the drawer and outer casing and the loading of suture packages in the universal dispenser box shown in Fig. 3.

Fig. 10 illustrates the removal of the retainer
15 tab from the universal dispenser box of Fig. 3.

Fig. 11 illustrates dispensing of a suture package.

Fig. 12 is a perspective view illustrating of an alternative preferred embodiment including a spacer flap.

20 Fig. 13 is a perspective view illustrating the embodiment of Fig. 12 stacked with conventional suture dispenser boxes.

Fig. 14 is a perspective view of an alternative embodiment of the universal suture
25 package dispenser box having a spacer extension wherein the suture packages are stacked vertically.

6

Fig. 15 is a perspective view of the embodiment of Fig. 14 wherein the suture packages are stacked horizontally.

Fig. 16 is a plan view of the blank used to make the outer casing of the embodiment of Fig. 14.

Fig. 17 is a perspective view illustrating the folding and assembly of the blank of Fig. 16.

Fig. 18 is a cutaway view of the embodiment of Fig. 14.

Fig. 19 is a perspective view showing the embodiment of Fig. 14 stacked with conventional suture package dispenser boxes.

15 DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

With reference to Figs. 3-11, a preferred universal suture dispenser 10 is described herein.

Universal suture dispenser 10 includes an outer casing 100 having a folded blank defining an interior space, and a drawer portion 200 slidably disposed within the interior space of the outer casing. Individual suture packages are preferably stacked in a single array within the drawer portion. The suture packages are typically of a rectangular, planar configuration and are stacked such that the planes are parallel to each other. The stack can be positioned vertically, as in Fig. 3, or horizontally, as in Fig. 4. The suture dispenser can be fabricated from

paperboard, cardboard stock, plastic sheet material or other material suitable for the purposes described herein.

Referring now to Fig. 3, universal suture dispenser 10 is illustrated in a vertical position as favored in the United States. Fig. 4 illustrates the universal suture dispenser 10 positioned in the European preferred horizontal orientation.

Referring now to Fig. 5, the blank from which the outer casing 100 is made is shown unfolded. The blank has five main panels which correspond to sides of the outer casing. Each of the panels is a flat sheet of suitable material.

Panel 110 has a body portion 111 to which flap 112 is attached along fold line 118. Tab 113 is adapted for insertion into slot 155 (discussed below) and is attached to bendable portion 119 along fold line 114. Bendable portion 119 is at least partially defined by slots 116a and 116b, and is attached to body portion 111 along fold line 115. Slots 117a and 117b between tab 113 and bendable portion 119 facilitate the bending of tab 113 relative to the bendable portion 119 and help to prevent inadvertent withdrawal of tab 113 from slot 155 after they have been fully engaged.

Panel 120 has a first strip portion 121 extending between panels 110 and 130 and being foldably connected thereto along fold lines 122a and 122b, respectively. A second strip portion 124 extends between

panels 110 and 130 and is foldably connected thereto along fold lines 125a and 125b. Edges 111a of the panel 110, 131a of panel 130, 124a of strip 124, and 121a of strip 121 define a window 123. Window 123 enables the operating room personnel or other user to see identifying indicia printed on the outer side of panel 260 of the drawer portion 200 (Fig. 7) when the dispenser is assembled.

Bendable tabs 126 are attached to strip portion 124 along fold lines 129 and are at least partially defined by slits 128a and 128b. Finger slot 127 provides access to grasp the suture package with one's fingers (usually forefinger and thumb).

Panel 130 includes a body portion 131 attached to first and second strip portions 121 and 124 along fold lines 122b and 125b, respectively, and further is attached to panel 140 along fold line 132.

Panel 150 includes a body portion 151 attached to panel 130 along fold line 156 and also includes a window 157 for permitting the operating room personnel or other user to read identifying indicia on the outer surface of panel 220 of the drawer portion 200.

Panel 150 also preferably includes an arcuate cut out portion 152 to facilitate grasping of the suture package for withdrawal. Tab 153 is bendably attached to body portion 151 along fold line 154. Slot 155 is disposed along fold line 154 and is adapted to receive tab

113 of the first panel when the panels are folded together to form the outer casing.

Referring now to Fig. 6, this folding operation is illustrated. Panels 110, 120, 130, 140, and 150 are
5 folded inward along fold lines 122a, 125a, 122b, 125b, 132, and 156 to form a box-like structure. Tab 112 includes a gummed adhesive surface 112a adapted to abut an inner surface portion of panel 140 and to adhere thereto. Panel 150 is folded with tab 153 tucked inside panel 110
10 with tab 113 being inserted through slot 155 to lock the panels and secure the enclosure. The outer casing thus formed is prepared to receive the drawer portion 200.

Drawer portion 200 is adapted to provide a storage space in which the suture packages are stacked.
15 Referring to Fig. 7, as seen in unfolded plan view, the blank from which the draw portion is folded includes several foldably connected panels.

Panel 210 includes a body portion 211. Flap 215 is attached to body portion 211 along fold line 213.
20 Slits 212a and 212b facilitate folding of tab 215 and its retention in the tucked-in configuration by panels 240 and 270, as discussed below. Panel 210 is foldably attached to panel 220 along fold line 214.

Panel 220 includes body portion 221 connected
25 along one edge to panel 210 along fold line 214 and along an adjacent edge to panel 230 along fold line 225. Removable tab 223 is detachably connected to body portion

10

221 along arcuate score line 222. Tab 223 has portions 223a and 223b, which are foldably connected to each other along fold line 224. Portion 223a is at least partially defined by the arcuate score line 222 and fold line 224.

5 Portion 223b includes an arcuate cut away portion 225. Tab 223 is adapted to be detached from body portion 221 by ripping along the score line 222.

Panel 230 includes a body portion 231 which is attached to body portion 221 along fold line 225, and on 10 an opposite edge to body portion 251 of panel 250 along fold line 233, and on an adjacent edge to body portion 241 of panel 240 along fold line 232.

Body portion 241 includes an angled side 243 with a laterally offset portion 242 which engages slit 15 212b when the drawer portion 220 is foldably assembled. The inner surface of portion 242 provides an abutment which prevents tab 215 from inadvertently being withdrawn from a folded engagement configuration.

Panel 250 includes a body portion 251 foldably 20 connected to body portion 231 along fold line 233 and to tab 254 by adhesion, or other suitable means of fixation. Body portion 251 includes an arcuate cutaway portion 252 to provide access to the user's finger to grasp and pull the drawer 200. Panel 250 forms an end panel which 25 constitutes side 12 of the dispenser (See Figs. 3, 4).

Panel 260 includes a body portion 261 which is foldably connected to body portion 271 of panel 270 along

11

fold line 273. Body portion 261 includes a cutaway portion 263 to facilitate grasping of the suture package by the user's finger. Tab 254 of panel 250 is foldably connected to body portion 261 along fold line 262. Fold
5 line 262 is on the edge of panel 250 opposite to that of fold line 233. Body portion 261 included an elongated recess 265 along an edge.

Panel 270 includes body portion 271 attached to body portion 261 along fold line 273, which is adjacent to
10 fold line 262. Body portion 271 also includes an angled edge 274 with a laterally offset portion 272 which engages slit 212a when the drawer portion 220 is foldably assembled. The inner surface of portion 272 provides an abutment which prevents tab 215 from inadvertently being
15 withdrawn from a folded engagement configuration, and acts cooperatively with corresponding lateral offset portion 242 of panel 240.

Referring to Fig. 8, the folding assembly of the drawer portion 200 is illustrated. Panels 220, 230, 250,
20 and 260 are folded around along fold lines 225, 233, and 262 to form the sides of the drawer portion 200.

Panels 240 and 270 are then folded up and in along fold lines 232 and 273, respectively. Panel 210, which forms the floor of the drawer portion 200, is then
25 folded up with tab 215 being inserted in the space between body portion 251 and angled edges 243 and 274 of panels 240 and 270, respectively. Lateral offset portions 242

12

and 272 engage slots 212b and 212a, respectively, thereby retaining the tab 215.

As can be seen from Figs. 3, 4, 9 and 11, suture package dispenser 10 is a container for holding a plurality of suture packages 50 in a stacked array, the suture packages 50 being of generally planar, rectangular configuration, stacked parallel to each other. The suture package dispenser is characterized by a generally planar first side wall 11 and a generally planar second side wall 12, side walls 11 and 12 being adjacent and substantially perpendicular to each other, and a side wall 13 which constitutes a top panel when the suture dispenser is positioned horizontally on a support surface, as shown in Fig. 4. The first side wall 11 is defined by panel 120 of the outer casing (Fig. 5) in conjunction with panel 260 of the drawer portion (Figs. 7, 8). Side wall 12 is defined by panel 250 of the drawer portion (Figs. 7, 8). Side wall 13 is defined by panel 110 (Figs. 5, 6), and is substantially perpendicular to side walls 11 and 12. The planes of the individual suture packages are oriented perpendicular to the first and third side walls 11 and 13, and parallel to the second side wall 12.

Suture package dispenser 10 includes two access portals through which the suture packages can be individually withdrawn. A first portal 14 is located at the bottom of the first side wall 11 when the suture

13

package dispenser 10 is positioned vertically as shown in Fig. 3.

Referring to Figs. 3, 9, 10 and 11, removable tab 223 is initially folded over to at least partially close the first portal 14. To withdraw a suture package from the first portal 14 the user detaches tab 223 (Fig. 10), thereby allowing retrieval of a suture package 50.

As can be seen in Fig. 11, the suture packages 50 are individually withdrawn through the first portal 14 in a line of direction perpendicular to the first side wall 11 and parallel to both the second side wall 12 and the third side wall 13, as in the U.S. preferred mode of dispensing.

A second portal 15 is defined by side walls 12 and 13. When the drawer portion 200 is fully inserted into the outer casing 100, the second portal 15 is in a closed configuration. When the drawer portion 200 is at least partially withdrawn from the outer casing 100 the second portal 15 is open and a suture package 50 can be removed as in the European preferred mode. See e.g., Fig. 2 which illustrates the European preferred mode of dispensing.

As can be seen, the suture package is removed from the second portal in a line of direction perpendicular to third wall 13, but parallel to both the first side wall 11 and the second side wall 12, although, as mentioned above, the planes of the suture packages are

14

perpendicular to the first side wall 11 and parallel to the second side wall 12.

Referring to Figs. 12 and 13, another embodiment 10a of the universal suture dispenser is shown. In Fig. 5 13, conventional suture package dispenser boxes 2 are shown oriented vertically for use in the U.S. preferred mode of dispensing. A typical U.S. dispenser box has a depth A, about 5.4 inches. Because the width of the European style box is typically about 4.7 inches (i.e., 10 the length of panel 250 between fold lines 233 and 262, Fig. 7), universal suture package dispenser 10 has a depth B of about 4.7 inches as well. Therefore, when both conventional suture package dispensers 2 and universal suture package dispensers, such as described herein, are 15 shelved together on a U.S. rack 5 there is an uneven presentation because the universal suture dispenser 10 is about 0.7 inches shorter in this dimension. To make up the difference a spacer flap 180 can optionally be included as part of the outer casing 100. Spacer flap 180 20 preferably includes a main panel portion 181, a spacer panel 182, and insertion tabs 183. The spacer panel 182 is about 0.7 inches wide and makes up for the difference in depth between the universal suture dispenser 10 and conventional suture dispenser boxes 2, as shown in Fig. 25 13. The spacer panel also causes the dispenser box to properly fit within the U.S. style rack (i.e., the front panel of the box is flush with the front-most portion of

15

the shelving). Spacer panel 182 is preferably fixedly attached to panel 140 of the outer casing. The main panel portion 181 is foldably connected to spacer panel 182 along fold line 185. Tabs 183 extend from the main panel portion 181 and are insertable into slots 184 in the outer casing 100.

For purposes of shipping and for European style dispensing, the spacer flap 180 can be folded back along fold line 186 so that it is flush against panel 110 of the outer casing 100. The user then has the option to bend the spacer flap around to its operating position and insert tabs 183 into slots 184 as shown in Fig. 12, thereby preparing the universal suture package dispenser 10a for shelving with dispenser boxes 2, the U.S. preferred mode.

Referring now to Fig. 14, yet another embodiment 20 of the universal suture package dispenser is illustrated in a vertical position as favored in the United States. Fig. 15 illustrates embodiment 20 of the universal suture dispenser positioned in the European preferred horizontal orientation. When universal suture dispenser 20 is used in European style shelving or racks, the outer casing 300 is preferably discarded and drawer 200 is placed in the rack.

Universal dispenser box 20 is provided with a spacer to make up for the difference in dimension between the U.S. and European boxes. Unlike the embodiment shown in

16

Figs. 12 and 13, the spacer of dispenser box 20 provides a back panel adapted to be completely flush against the rear wall of the U.S. rack on which they are displayed or stored. The universal dispenser box 20 can employ the same drawer portion 200 as that of dispenser box 10. However, the outer casing 300 differs from outer casing 100 by providing a more rigid, permanent spacing member that is oriented inward from the outer periphery of the box rather than outward of the box. More specifically, the outer casing 100 of the embodiment shown in Figs. 12 and 13 is adapted to fit the drawer portion 200, with additional spacer 180 being provided to adapt the dispenser box 10 to the U.S. rack 5 (Fig. 19). Spacer 180 is exterior to the enclosed space formed by the outer casing 100. Outer casing 300, however, is dimensioned to fit the dispenser box 20 to the rack 5 (Fig. 19), with the spacer portions being provided to adapt the outer casing 300 to the drawer portion 200. The spacer panels are inside an enclosed space defined by the outer casing 300.

Referring now to Fig. 16, the blank from which the outer casing 300 is made is shown unfolded. The blank has five main panels which correspond to exterior sides of the outer casing, and spacer panels to adapt the interior dimensions of the enclosed space to fit the drawer portion 200. Each of the panels is a flat sheet of suitable material.

17

Panel 310 has a body portion 311 and tab 313. Tab 313 is adapted for insertion into slot 355 (discussed below) and is attached to bendable portion 319 along fold line 314. Bendable portion 319 is at least partially defined by slots 316a and 316b, and is attached to body portion 311 along fold line 315. Slots 317a and 317b between tab 313 and bendable portion 319 facilitate the bending of tab 313 relative to the bendable portion 319 and help to prevent inadvertent withdrawal of tab 313 from slot 355 after they have been fully engaged.

Panel 320 includes a first strip portion 321 extending between panels 310 and 330 and which is foldably connected thereto along fold lines 322a and 322b, respectively. A second strip portion 324 extends between panels 310 and 330 and is foldably connected thereto along fold lines 325a and 325b. Edges 311a of the panel 310, 331a of panel 330, 324a of strip 324, and 321a of strip 321 define a window 323. Window 323 enables the operating room personnel or other user to see identifying indicia printed on the outer side of panel 260 of the drawer portion 200 when the dispenser is assembled. Finger slot 327 provides access to grasp the suture package with one's fingers (usually forefinger and thumb).

Panel 330 includes a body portion 331 attached to first and second strip portions 321 and 324 along fold

lines 322b and 325b, respectively, and further is attached to panel 340 along fold line 332.

Panel 340 includes a body portion 341 to which flap 342 is attached along fold line 343.

5 Panel 350 includes a body portion 351 attached to panel 330 along fold line 356 and also includes a window 357 for permitting the operating room personnel or other user to read identifying indicia on the outer surface of panel 220 of the drawer portion 200.

10 Panel 350 also preferably includes an arcuate cut out portion 352 to facilitate grasping of the suture package for withdrawal. Tab 353 is bendably attached to body portion 351 along fold line 354. Slot 355 is disposed along fold line 354 and is adapted to receive
15 tab 313 of the first panel when the panels are folded together to form the outer casing.

Spacer panel 360 includes a body portion 361 and a spacer portion 362 which is attached to body portion 361 along fold line 363. Fold line 363 can include a slit
20 363a extending partially across the fold line. Spacer portion 362 is attached to one edge of body portion 341 along fold line 364.

Spacer panel 370 includes a body portion 371 and a spacer portion 372 which is attached to body portion 371
25 along fold line 373. Spacer portion 372 is attached to an edge of the body portion 341 along fold line 374.

19

Fold line 374 can include a slit 374a extending partially across the fold line.

Referring now to Fig. 17, the folding operation is illustrated. Panels 310, 320, 330, 340, and 350 are
5 folded inward along fold lines 322a, 325a, 322b, 325b, 332, and 356 to form a box-like structure. Tab 342 includes a gummed adhesive surface 342a adapted to abut an inner surface portion of panel 310 and to adhere thereto. Panel 350 is folded with tab 353 tucked inside
10 panel 310 with tab 313 being inserted through slot 355 to lock the panels and secure the enclosure. The spacer panels 360 and 370 are folded along fold lines 363, 364, 373, and 374 to construct an interior wall (formed by body portions 361 and 371) parallel to and spaced apart
15 from body portion 341 by a distance equal to the width of spacer portions 362 and 372. Body portion 361 can have a gummed surface portion 361a to adhere to body portion 371. The outer casing thus formed is prepared to receive the drawer portion 200.

20 Referring now to Figs. 18 and 19, it can be seen that the outer casing 300 is adapted to correspond in dimensions to U.S. prior art suture package dispensers 2 so that suture package dispenser box 20 can be shelved alone or side by side with the conventional boxes 2 on a
25 standardized U.S. display or storage rack 5 to present a uniform array of dispenser boxes flush with the front of the shelving. Both the prior art suture package

20

dispensers 2 and the outer casing 300 of the suture dispenser 20 are characterized by a depth dimension A. However, the drawer portion 200 is characterized by a dimension L which is less than A. It is this dimension, 5 L, that corresponds to the preferred European width for a suture dispensing box. Spacer panels 360 and 370 provide an interior wall formed by body portions 361 and 371, which is spaced apart from exterior panel 341 by a distance D equal to the width of spacer portions 362 and 10 372. Width D is chosen such that the dimensions of the drawer portion 200 are accommodated within the outer casing 300, as previously explained. Most preferably, with respect to Fig. 19, dimension A is about 5.4 inches, spacer width D is about 0.7 inches, height H is about 5.6 15 inches and box width W is about 2.5 inches. Therefore, the exterior dimensions of the U.S. preferred suture dispensing box is about 2.5 X 5.6 X 5.4 inches, while the European suture package dispenser drawer is about 2.5 X 5.6 X 4.7 inches ($\pm$ about 0.5 inches in each dimension).

20 In like manner as with suture package dispenser 10, and as can be seen from Figs. 14, 15, and 19, the suture package dispenser 20 includes a container for holding a plurality of suture packages 50 in a stacked array, the suture packages 50 being of generally planar 25 configuration, stacked parallel to each other. The suture package dispenser 20 is characterized by a generally planar first side wall 21 and a generally

21

planar second side wall 22, side walls 21 and 22 being adjacent and substantially perpendicular to each other, and a side wall 23 which constitutes a top panel when the suture dispenser is positioned horizontally on a support surface, as shown in Fig. 15. The first side wall 21 is defined by panel 320 of the outer casing (Fig. 16) in conjunction with panel 260 of the drawer portion (Figs. 7, 8). Second side wall 22 is defined by panel 250 of the drawer portion (Figs. 7, 8). Side wall 23 is defined by panel 310 (Figs. 16, 17), and is substantially perpendicular to side walls 21 and 22. The planes of the individual suture packages are oriented perpendicular to the first and third side walls 21 and 23, and parallel to the second side wall 22.

Suture package dispenser 20 includes two access portals through which the suture packages 50 can be individually withdrawn. A first portal 24 is located at the bottom of the first side wall 21 when the suture package dispenser 20 is positioned vertically (U.S. preferred mode) as shown in Fig. 14.

Removable tab 223 is initially folded over to at least partially close the first portal 24. To withdraw a suture package from the first portal 24 the user detaches tab 223, thereby allowing retrieval of a suture package 50. The suture packages 50 are withdrawn (by grasping a shorter side of the rectangular suture package) through the first portal 24 in a line of direction perpendicular

22

to the first side wall 21 and parallel to both the second side wall 22 and the third side wall 23, as in the U.S. preferred mode of dispensing.

The second portal 25 is defined by side walls 22 and 23. When the drawer portion 200 is fully inserted into the outer casing 300, the second portal 25 is in a closed configuration. When the drawer portion 200 is at least partially withdrawn from the outer casing 300 the second portal 25 is open and a suture package 50 can be removed (by grasping a longer side of the rectangular suture package) as in the European preferred mode. As discussed above, drawer 200 can be removed from casing 300 and placed alone in a dispensing rack.

As can be seen, the suture package is removed from the second portal 25 in a line of direction which is perpendicular to third wall 23, but parallel to both the first side wall 21 and the second side wall 22, although, as mentioned above, the planes of the suture packages are perpendicular to the first side wall 21 and parallel to the second side wall 22.

It can further be seen from Fig. 18 that the interior wall formed by body portions 361 and 371 of the spacer panels 360 and 370 is oriented in a plane which is parallel to first side wall 21.

It will be understood that various modifications may be made to the embodiments described herein. Therefore the above description should not be construed as

23

limiting, but merely as exemplifications of preferred embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A suture package dispenser comprising:

a container for holding a plurality of suture
5 packages in a stacked array, the suture packages being of
generally planar configuration and stacked such that the
planes of the packages are parallel to each other;

the container having first and second adjacent
sides, the first side generally defining a first plane
10 and the second side generally defining a second plane,
wherein the individual suture package planes are oriented
perpendicular to the first plane and parallel to the
second plane; and,

the container having first and second access
15 portals for withdrawal of the suture packages from the
stacked array, the first access portal permitting the
suture packages to be withdrawn from the container in a
line of direction perpendicular to the first plane and
parallel to the second plane, and the second access
20 portal permitting the sutures to be withdrawn from the
container in a direction parallel to both the first and
second planes.

2. The suture package dispenser of claim 1,
25 wherein the container includes an outer casing and a
drawer portion slidably disposed within the outer casing.

25

3. The suture package dispenser of claim 2 wherein the drawer portion has a storage space for holding the stacked array of suture packages.

5 4. The suture package dispenser of claim 3 wherein the first access portal is positioned on the first side of the container and is at least partially defined by corresponding openings in the drawer portion and the outer casing.

10

5. The suture package dispenser of claim 4 wherein the opening in the drawer portion is at least partially formed by removal of a tab which is removably attached to the drawer portion.

15

6. The suture package dispenser of claim 5, wherein the second side of the container is defined by an end panel of the drawer portion, the outer casing having a first side wall which is adjacent and substantially perpendicular to the first and second sides of the container, and the second portal is at least partially defined by the end of the drawer portion and the first side wall of the outer casing, the second portal being in an open configuration when the drawer portion is at least partially withdrawn from the outer casing and in a closed configuration when the drawer portion is fully disposed within the outer casing.

7. The suture package dispenser of claim 1 wherein the container is fabricated from a material selected from the group consisting of paperboard, and plastic sheet.

8. The suture package dispenser of claim 1 wherein the container includes a window for viewing the suture package at one end of the stacked array.

9. The suture package dispenser of claim 2 further including a spacer flap foldably connected at one edge to the outer casing, the spacer flap including at least one tab for insertion within a corresponding slot in the outer casing.

10. The suture package dispenser of claim 2 wherein the drawer portion has at least one side dimension which is less than a corresponding side dimension of the outer casing, and the outer casing includes at least one spacer panel spaced apart from an exterior wall of the outer casing by a distance substantially equal to the difference between the corresponding side dimensions of the outer casing and drawer portion, and which is oriented parallel to said first plane.

Fig. 1
(Prior Art)




Fig. 2
(Prior Art)






Fig. 3**Fig. 4**

McFadden, Fincham

3/14




Fig. 5






Fig. 6

**Fig. 7**

6/14

**Fig. 8**

7/14




Fig. 9

Fig. 10







Fig. 11



**Fig. 12****Fig. 13**

10/14






Fig. 14

11/14



12/14

**Fig. 16**

13/14



Fig. 17

Fig. 18**Fig. 19**