



(22) Date de dépôt/Filing Date: 1999/05/11

(41) Mise à la disp. pub./Open to Public Insp.: 1999/11/25

(45) Date de délivrance/Issue Date: 2010/03/09

(62) Demande originale/Original Application: 2 331 856

(30) Priorité/Priority: 1998/05/18 (US09/080,609)

(51) Cl.Int./Int.Cl. *B65D 71/08* (2006.01)

(72) Inventeurs/Inventors:

ANDERSEN, DALE C., US;
LASECKE, DONALD J., US


(73) Propriétaire/Owner:

DELKOR SYSTEMS, INC., US

(74) Agent: PIASETZKI & NENNIGER LLP

(54) Titre : EMBALLAGE TEMPORAIRE

(54) Title: TEMPORARY PACKAGE



(57) Abrégé/Abstract:

A temporary packaging method and a resultant package are provided for comprising temporarily bonding containers on a flat base member to stabilize the containers for further packaging, the method comprising the steps of providing a base member, providing

(57) **Abrégé(suite)/Abstract(continued):**

containers, temporarily bonding the containers to the base member with a hot melt adhesive, advancing the base member with containers through the packaging or handling system so that further processing of the containers may optionally be effected, encapsulating the base member and bonded containers with a plastic shrink film to complete the package, followed by release of the containers from the bond to base member within minutes after shrink wrapping, with the adhesive remaining bonded to the base member.

ABSTRACT OF THE DISCLOSURE

A temporary packaging method and a resultant package are provided for comprising temporarily bonding containers on a flat base member to stabilize the containers for further packaging, the method comprising the steps of providing a base member, providing containers, temporarily bonding the containers to the base member with a hot melt adhesive, advancing the base member with containers through the packaging or handling system so that further processing of the containers may optionally be effected, encapsulating the base member and bonded containers with a plastic shrink film to complete the package, followed by release of the containers from the bond to base member within minutes after shrink wrapping, with the adhesive remaining bonded to the base member.

TEMPORARY PACKAGE

Background Of the Invention

Field Of The Invention

5 This invention relates to a method for package assembly, and more particularly to a method for briefly stabilizing containers on a flat base member by temporarily bonding the containers to the base member with a hot melt adhesive that releases the container from its bond to the base member soon after the handling and packaging process is complete, and a package which consists of a rigid base member,
10 containers temporarily bonded with hot melt adhesive to the base member, and a plastic shrink film encapsulating the base member and containers.

Description Of The Related Art

 Prior art packaging methods and packages do not address the special need of
15 stabilizing containers on a flat base member during the brief period of package assembly by forming a temporary adhesive bond between the containers and the base member.

 Placement of a group or pack pattern of containers on a flat base member poses a stability problem as the base member with containers is transported through a packaging or handling process. This is particularly a problem for intermittent motion
20 packaging or handling systems, but is also a concern for continuous motion equipment. Even the machine vibration on a continuous motion machine can result in movement of containers on the flat base member, which can negatively effect the completed package, or the effectiveness of the packaging or handling system.

 To avoid this instability with containers on a flat base member, many
25 packaging or handling systems use a corrugated box or tray with four side walls. The box or tray forms a containment boundary so that movement of the containers during the handling or packaging process minimizes the stability problem.

 A need exists for a temporary packaging method and package so that containers are restricted from movement when placed on a flat base member during the
30 packaging or handling process, yet upon completion of the packaging or handling, the

containers are free of this movement restriction.

Summary Of The Invention

Accordingly, the present invention provides a temporary packaging method
5 and package which briefly bonds a group or pack pattern of containers to a flat base member
to stabilize the containers during the handling or packaging process, and these containers
release from this adhesive bond soon after the handling or packaging process is completed
by plastic shrink film encapsulation of the base member and containers. The method
comprises the steps of providing a base member, providing adhesive to the base member,
10 placement of containers to base member resulting in a temporary bond, advancing the base
member with bonded containers through the handling or packaging process, encapsulation
of base member and containers with plastic shrink film, and release of containers from bond
to base member within minutes after the encapsulation by shrink film, with adhesive
remaining bonded to base member.

15 The method of the present invention eliminates the instability of the
containers on a flat base member during the handling or packaging process, thereby
permitting a wide range of movement and handling to occur. The present invention permits
the group of containers which are bonded to the flat base member to be aggressively handled
by inclines, declines, side transfers, abrupt starting and stopping, equipment vibration,
20 stacking, etc.

The temporary bond effectively locks the containers in place during the
handling or packaging process. This temporary bond is defined herein as a bond that
releases by itself over time. It is required to hold the containers in place during the handling
or packaging process, and within minutes after the base member and containers are
25 encapsulated by film, the container releases from the base member with the adhesive residue
remaining on the base member.

This novel packaging method dramatically simplifies the packaging and
handling process for packaging containers on a flat base member. By temporarily
stabilizing the group or pack pattern on the base member during the packaging or handling
30 process, this invention offers an effective alternative to the traditional corrugated box or tray

with four side walls.

This invention utilizes less packaging materials than boxes or trays, is more cost efficient, and because there is no need to form boxes or trays, which generate both corrugated dust and spores, it is more sanitary. This invention also offers greater efficiency
 5 than current methods of packaging containers on flat base members because of the increased stability of containers on the base member during package assembly.

Brief Description Of The Drawings

Figure 1 is a perspective view of a grouping of containers of the present
 10 invention showing a base member with containers adhered thereto;

Figure 2 is a plan view of a base member with continuous strips of a temporary adhesive applied thereto;

Figure 3 is a plan view of a base member with intermittent strips of a temporary adhesive applied thereto;

15 Figure 4 is a diagram of the apparatus and method for assembling the package assembly of the present invention including encapsulating the containers with shrink film;

Figure 5 is a perspective view of a package comprising a base member with containers adhered thereto and a cover member encapsulated by a plastic film;

20 Figure 6 is a perspective view of a base member with containers adhered thereto and having a divider insert;

Figure 7 is a perspective view of a grouping of containers of the present invention temporarily bonded to a base member and traveling up an incline prior to encapsulation by shrink film, and

25 Figure 8 is a perspective view of a grouping of containers of the present invention showing a base member with containers encapsulated with shrink film.

Figure 9 is a perspective view of a grouping of containers of the present invention showing stacked layers of base members with bonded containers encapsulated with shrink film.

30 Figure 10 is a perspective view of a grouping of containers of the present invention on a circular base member encapsulated with shrink film.

Description Of The Preferred Embodiments

While this invention may be embodied in many different forms, there are shown in the drawings and described in detail herein specific preferred embodiments of the invention. The present disclosure is an exemplification of the principles of the invention
 5 and is not intended to limit the invention to the particular embodiments illustrated.

The present invention provides a temporary packaging method and package which briefly bonds a group or pack pattern of containers to a flat base member during the handling or packaging process and releases this bond once the handling or packaging process is completed. The method comprises the steps of providing a base member,
 10 providing adhesive to the base member, placement of containers on base member to form a temporary bond, optionally adding a top cover member or divider, advancing the base member with bonded containers through the handling or packaging process so that further processing of the containers may optionally be effected, encapsulation of the base member with bonded containers by a plastic shrink film, followed by release of containers from base
 15 member soon after encapsulation of the shrink film, with adhesive remaining bonded to base member.

The method of the present invention provides a means for briefly bonding containers to a base member so containers can be effectively controlled during the handling or packaging process. The optional top cover member adds extra strength and protection for
 20 certain container types such as those having foil or paper lids or a bottle with a sport cap, the optional divider insert adds extra protection for certain container types such as glass bottles or jars to avoid glass on glass contact.

Referring to Figure 1, an assembly of containers of the present invention is shown generally at 10 and comprises a flat base member 12, onto which containers 10 are
 25 adhered to temporary bonding adhesive strips 13.

Base member 12 may be made of any suitable material such as chip board, paper board or corrugated board depending on the dimensions of the package and intermediate steps which accompany the packaging method. Chip board, however, possesses the minimum desired degree of stiffness according to the present invention.

30 By means of appropriate adhesive dispensing equipment the nature of which will be readily apparent to those familiar with the art, strips of adhesive 20 are placed on the upper surface 21 of base member 12, as shown in Figure 2, adhesive strips 20 being

disposed parallel to ends 22 and 24 of base member 12. The adhesive is a hot melt adhesive which may be applied by applicators situated above a conveyor (not shown) along which base member 12 is traveling during the packaging process. Both the application temperature and depth of adhesive strip should be consistent with the strips of adhesive 20
5 on base member 12.

The timing between application of adhesive strips and placement of containers should be substantially consistent, generally 2 to 3 seconds between placement of adhesive strips on base member and placement of containers on base member.

In order to form a temporary bond, the hot melt adhesive should have an
10 open time of approximately 30 to 45 seconds. The open time is defined as the period between application of adhesive on base member and solidification of adhesive. During the open time the elasticity of the semi-solid hot melt adhesive permits aggressive movement of the base member without movement of the containers from their position on the base member. As the adhesive begins to solidify the bond weakens and within minutes
15 the container totally releases from the bond to base member, with all adhesive remaining on the base member.

An adhesive with this characteristic is commercially available from H.B. Fuller® as Product No. H.L. 7674. Depending upon the type of handling contemplated, however, the specific open time may vary. In general, an open time of between 20 seconds
20 to 1 minute is particularly well suited for the present invention.

The specific bonding strength between base member and container is controlled by varying the application temperature of the adhesive, and the depth of the adhesive strips (generally 1/16 to 1/8" i.e. 0.15875-0.3175 cm depth). A higher application temperature and deeper adhesive strips will increase the bonding, and a lower temperature
25 and thinner adhesive strips will decrease bonding. In general, the hot melt adhesive is preferably applied within a temperature range of 270 degrees F to 340 degrees F (132-171 degrees C).

Adhesive strips 20 hold containers 14 firmly in place on base member 12, as shown in Figure 1. The adhesive is such that it will adhere to containers 14 to the extent
30 that containers 14 are secured to base member 12 firmly enough to resist movement relative thereto and provide stability during normal handling.

Figure 3 shows an alternative embodiment of the invention, in which

adhesive strips 20a are intermittent, so that the adhesive strips extend only beneath the individual containers and not between them.

Soon after the adhesive is applied to base member 12 (generally 2 to 3 seconds), containers are placed in an adjacent side by side relationship on adhesive strips 20 on base member 12, as shown in Figure 1. Containers 14 may be positioned on base member 12 by equipment which feeds containers 14 in a direction perpendicularly to the direction in which base member is traveling, and then positions a pre-arranged set of containers 14 on base member 12 within a consistently short period of time (generally 2 to 3 seconds). Containers 14 preferably touch the adhesive strip at two contact points, or at four contact points, as shown in Figure 2 at 26, 28, 30 and 32, and in Fig. 3 at 26a, 28a, 30a and 32a in which strips of adhesive, after a container has been affixed thereto and removed, are shown for purposes of illustration.

The advantage of automatic loading of containers into a pack pattern and bonding same to a base member is that a stable unitized assembly is placed on the adhesive strips at the same time. The time interval between application of adhesive and placement of containers should remain substantially constant to replicate the bonding characteristics of container to base member. For this reason, automatic loading equipment is the most preferred method.

Figure 4 is a diagram of the apparatus for assembling the package assembly and temporary packaging method of the present invention. Containers enter this apparatus on a single lane conveyor (A) and are channeled through lane dividers (B) which separate the containers into the appropriate number of lanes. A pack pattern of containers is released to collation area (C). Simultaneously a base member is picked from the base member magazine (D) and placed on the conveyor bed (F). As the base member indexes forward on the conveyor bed the adhesive unit (E) and adhesive applicator (G) place strips of the temporary bonding hot melt adhesive on the base member.

The adhesive unit and applicator apply a consistent strip or strips of adhesive to the base member (generally 1/16" to 1/8" depth i.e. 0.15875- 0.3175 cm) at a consistent application temperature (generally 270 degrees F to 340 degrees F i.e. 132 - 171 degrees C).

Within a consistent time period after application of adhesive to base member (generally 2 to 3 seconds), the pack pattern of containers (C) are transferred by the apparatus for placement on the base member with temporary bonding adhesive.

Once containers have been loaded onto the base member, the package assembly is moved by a conveyor through a series of optional applications such as placement of cover member or divider insert (J), conveying on inclines, declines or angled turns (K), abrupt stopping and starting (L), and transfer into the apparatus for encapsulating the base member and containers with plastic shrink film (M), and ending with the final package with shrink wrap encapsulation (N). Within minutes after shrink wrapping, the containers will release from the bond to base member with adhesive remaining bonded to base member.

As shown in Figure 5, a flat cover member 40 may optionally be applied over the containers. The cover member provides added strength to package and offers top layer protection for certain container types such as containers with paper or foil lids, or bottles with sport caps. Once cover member is in position, the package assembly is encapsulated with shrink film 11 such as commercially available from Armin Plastics as Product No. 2304B. The tight film encapsulation thus provided keeps the top pad tightly pressed to the tops of the containers which increases package strength and protects the top layer of containers.

An alternative embodiment of a temporary package assembly according to the present invention is shown at Figure 6. A divider 50 has been added to avoid container to container contact within package assembly. This has application for such containers as glass jars, bottles, vials, etc., in which container to container contact can result in damage during distribution. The divider (usually corrugated or chipboard) is placed between containers after containers are bonded to base member and prior to shrink film encapsulation.

Referring to Figure 7, a schematic drawing of the temporary package assembly according to the present invention is shown. Use of the flat base member and temporary adhesive bonding of containers to base member locks product containers in place and prevents individual movement of the containers until after the package assembly has been shrink wrapped. Within minutes the adhesive releases the containers from the bond to base member with the adhesive remaining on the base member. This temporary package assembly uses less packaging material than either a box or tray with four side walls, is more cost efficient, and because there is no need to form boxes or trays, which generate both

corrugated dust and spores, it is more sanitary.

The present invention provides a method for temporarily bonding containers to a flat base member to restrict movement of containers on the base member during the handling or packaging process. This method of bonding the containers permits a wide range of movement and handling to occur without concern for container stability on the flat base member.

The present invention permits the group or pack pattern of containers to be aggressively handled by inclines 16 as shown in Figure 7, declines, side transfers, abrupt starting and stopping, equipment vibrations, stacking, etc., without individual movement of container, and within minutes after the group or pack pattern of containers and base member has been encapsulated with plastic shrink film, the adhesive bond releases the containers from the base member with the adhesive residue remaining on the base member. The completed package assembly of the present invention is shown in Figure 8.

Additional embodiments of the invention are shown in Figures 9 and 10. Figure 9 shows an embodiment in which multiple layers of base members with bonded containers are stacked. Figure 10 shows an embodiment in which a circular base member is used.

Other advantages of the method of the present invention are as follows. The temporary bond effectively eliminates individual movement of the container on a flat base member during package assembly or handling, thereby greatly enhancing stability of the package assembly, which results in greater packaging efficiency. This improved stability increases the range of containers which are candidates for packaging by means of a flat base member, and it reduces the need for the packaging or handling equipment to maintain control of container movement after the container has been placed on the flat base member, thereby reducing equipment costs.

Additionally, for containers that are placed into boxes or trays for conveying through a heat transfer process, the present invention offers greater heat transfer due to the flat base member. The present invention permits greater airflow than a box or tray, thereby improving heat transfer.

This completes the description of the preferred and alternate embodiments of the invention. Those skilled in the art may recognize other equivalents to the specific embodiment described herein which equivalents are intended to be encompassed by the

claims attached hereto.

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:**


1. A package comprising:
a substantially rigid planar base member;
a plurality of containers, the plurality of containers temporarily bonded to the base member by a self-releasing adhesive; and
plastic shrink film encapsulating the base member and containers.
2. The package of claim 1 further including a flat cover member over the top of the containers.
3. The package of claim 1 wherein there is a plurality of rows of containers and the base member has a plurality of strips of self-releasing adhesive, each adhesive strip extending beneath a respective row of containers.
4. The package of claim 3 wherein the adhesive strips are continuous.
5. The package of claim 3 wherein the adhesive strips are intermittent, such that each strip extends substantially beneath only one container.
6. The package of claim 1 wherein the base member is selected from the group consisting of a generally rectangular rigid base member having four rounded corners, a generally rectangular rigid base member and having four clipped corners and a circular rigid base member.
7. The package of claim 1 further comprising a divider placed between the containers.
8. The package of claim 1 further comprising a multiple layer arrangement of base members with bonded containers.

9. A package comprising:
 - a base member; and
 - a plurality of containers bonded to the base member with an adhesive which self-releases after a predetermined period of time without the application of force to the containers and the base.
10. The package of claim 9 further comprising a plastic shrink film encapsulating the base member and the containers.
11. The package of claim 9 further comprising a cover member placed over the containers and a plastic shrink film encapsulating the base member, the cover member and the containers.
12. The package of claim 9 wherein the adhesive is a hot-melt adhesive.
13. An encapsulated package comprising:
 - a base member;
 - a plurality of containers; and
 - a plastic shrink film encapsulating the base member and the containers, the containers having been bonded to the base member with a self-releasing adhesive, the self-releasing adhesive having released after a predetermined period of time without the application of force to the base member and the containers.
14. The package of claim 13 further comprising a cover member placed over the containers, the plastic shrink film encapsulating the base member, the cover member and the containers.
15. The package of claim 13 wherein the adhesive is a hot-melt adhesive.
16. A package comprising:

a base member;
 a plurality of containers; and
 a plastic shrink film encapsulating the base member and the containers,
 the containers having been bonded to the base member with a self-releasing
 adhesive, the self-releasing adhesive having self-released from the containers.

17. The package of claim 16 further comprising a cover member placed over the containers, the plastic shrink film encapsulating the base member, the cover member and the containers.
18. The package of claim 16 wherein the adhesive is a hot-melt adhesive.
19. A package comprising a continuous, substantially rigid planar base member having at least one row of containers, and a quantity of hot melt adhesive which forms a self-releasing temporary bond between the containers and the base member, and plastic shrink film encapsulating the base member and containers.
20. A package of claim 19 including a member selected from the group consisting of:
 - a flat cover member over the top of the containers;
 - a corrugated or shipboard divider placed between the containers;
 - a multiple layer arrangement of base members with bonded containers;
 - a ridge base member wherein it is generally rectangular and has four rounded corners;
 - a rigid base member wherein it is generally rectangular and has four clipped corners, and
 - any combination of the foregoing members of the group.

Fig. 1






Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10

