

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 June 2010 (17.06.2010)

(10) International Publication Number
WO 2010/066393 A1

(51) International Patent Classification:

A47B 88/04 (2006.01)

(21) International Application Number:

PCT/EP2009/008713

(22) International Filing Date:

7 December 2009 (07.12.2009)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

MI2008A002196 12 December 2008 (12.12.2008) IT

(71) Applicant (for all designated States except US): ARTURO SALICE S.p.A. [IT/IT]; Via Provinciale Novedratese, 10, I-22060 Novedrate (Como) (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SALICE, Luciano [IT/IT]; Via Ronco, 30, I-22060 Carimate (IT).

(74) Agent: RAPISARDI, Mariacristina; UFFICIO BREVETTI RAPISARDI S.r.l., Via Serbelloni, 12, I-20122 Milano (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(54) Title: DEVICE FOR OPENING AND CLOSING A MOBILE PART OF A FURNITURE UNIT



(57) Abstract: The device for opening and closing a movable part of a furniture unit comprises a body (108), associated with a fixed part of the furniture unit (116), for supporting a slider (3) reversibly sliding along a sliding axis (100) in contrast and due to the action of first elastic means (5), the slider being engageable with drawing means provided on a drawing element (105) slidable in the direction of the sliding axis with an integral or reversibly couplable connection to the movable part (103) of the furniture unit, the supporting body comprising first displacement means suitable for moving the drawing means so as to release said drawing means and the slider from their mutual engagement, an elastically yielding stop element against which the drawing element abuts directly or indirectly before engaging with the drawing means in the first displacement means.

WO 2010/066393 A1

DEVICE FOR OPENING AND CLOSING A MOVABLE PART OF A
FURNITURE UNIT

DESCRIPTION

The present invention refers to a device for opening and closing a movable part of a furniture unit. It is common knowledge that there have been devices on the market for some time now that achieve the virtually automatic opening and/or closing of movable parts of furniture units, such as a door or a drawer in a furniture unit.

For example, to open a drawer in a furniture unit, a device called a ratchet is currently used, which substantially comprises thrust means that are released by exerting a mild pressure on the drawer and, when released, under an elastic force they confer a thrust on the drawer that determines its controlled displacement, thereby enabling the user to grasp the drawer and open it completely, especially in the case of drawers without handles.

Conversely, to close the drawer, a self-closing device is used that is normally associated with the fixed drawer guide and consists of a body for supporting a slider that is movable inside a groove provided in said body, between two stable terminal positions.

The slider normally moves inside the groove in contrast and due to the action of a spring that is activated by drawing means integrally attached to the withdrawable drawer guide.

The opening of the drawer determines the activation of the self-closing device, which takes over, when the drawer is closed again, in the final stretch of its stroke - by means of a pin, for instance -

returning it to the completely closed position due to the effect of the spring.

Cooperating with the self-closing device, there is normally also a decelerator that absorbs the closing force of the drawer, attenuating the shock that would occur due to the effect of the drawer's closing spring.

In the light of the above considerations, it is easy to perceive the complexity inherent in the need to be able to combine an automated opening system with a self-closing system governing the movable part of a furniture unit, since the forces involved in the ratchet and in the self-closing device normally tend to contrast with one another, preventing either the opening or the closing action.

For these reasons, sometimes extremely complex systems have been conceived that also exploit parts driven by electric motors for the purpose, in order to be able to compensate for the forces involved and enable a virtually automatic (albeit only partial) opening and closing of the movable part of a furniture unit. Such solutions are sometimes scarcely effective, however, because in addition to making the device extremely complex, they easily tend to fail to assure a constant efficiency over time, they need regular maintenance and they entail high costs, making their application unsuitable for certain types of furniture. When the movable part consists of a drawer, the self-closing device can be arranged indifferently in various positions in relation to the furniture unit, e.g. in line with guides that enable its movement. In the case of doors swinging by means of hinges, on the other hand, the device should preferably be located on the

part of the furniture unit opposite to the one where the hinges are located, i.e. where it is possible, by means of a pressure exerted from the outside by the user, to obtain a displacement of the door sufficient to enable the device. The door is opened by completely separating its edge from the side of the furniture unit against which it abuts, with a consequently more complicated interaction between the drawing means and the slider of the self-closing system.

Moreover, there are various different types of hinge commercially available, some in particular in which an elastic device is integrated for providing the thrust in the door-closing direction, possibly assisted by a decelerator device, or fitted with an elastic device for inducing a thrust in the door-opening direction, possibly for associating with the previously-described ratchet devices.

The technical aim of the present invention is consequently to produce a device for opening and closing a movable part of a furniture unit that enables the technical drawbacks of the known art to be overcome. In the context of this technical aim, one object of the invention is to produce a device for opening and closing a movable part of a furniture unit that is reliable and of extremely straightforward functional design, guaranteeing its long-term efficiency without the need for any type of ordinary or extraordinary maintenance to achieve this end. Another object of the invention is to produce a device for opening and closing a movable part of a furniture unit that can be installed without difficulty even by unskilled personnel, consequently also enabling its replacement or

adjustment by the user if necessary, and that, among other things, has a limited cost, which can facilitate its diffusion on the market.

Another, not necessarily last object of the invention is to produce a device for opening and closing a movable part of a furniture unit that can be installed on any type of furniture unit, occupying a limited amount of space.

The above technical aim, and these and other objects according to the present invention are achieved by a device for opening and closing a movable part of a furniture unit according to claim 1 below.

The device according to the invention can generally be attached to movable parts of furniture units, including drawers, for instance, but it is particularly suitable for opening doors swinging around a vertical or horizontal axis. The closing of the movable parts of furniture units is instead preferably assisted by or entrusted to known closing devices integrated in the normal guides or hinges with which these parts are provided to enable their movement.

Other characteristics of the present invention are stated, moreover, in the dependent claims.

Further characteristics and advantages of the invention will emerge more clearly from the description of preferred, but not exclusive embodiments of the device for opening and closing a movable part of a furniture unit according to the invention, shown as a non-limiting example in the attached drawings, wherein:

- figure 1 shows a view from above of the device according to a first preferred embodiment of

the present invention with the drawing means in the initial position, with the door closed;

- figure 2 shows the device in figure 1 with the drawing pin disengaged from the rear cavity of the slider;
- figure 3 shows the device in figure 1 with the drawing pin abutting against the front edge of the slider, in the position in which the door is opened sufficiently to enable it to be grasped by the user;
- figure 4 shows the device in figure 1 in which, due to the user exerting a pulling action on the door from the outside, the drawing means are displaced transversely to the direction of their sliding axis until they release the door;
- figure 5 shows the device in figure 1 at the point where, during the retraction of the drawing element, the drawing pin abuts against the edge of the rear cavity of the slider;
- figure 6 shows the device in figure 1 that, with the door open, has the drawing element in the initial position once again;
- figure 7 shows a cross-sectional view of the device in figure 1 along line 7-7;
- figure 8 shows a view from above of the body for supporting the device shown in figure 1;
- figure 9 shows a view from above of the inside of the cover for the box-shaped body of the device in figure 1;
- figure 10 shows a view from above of the drawing element of the device in figure 1;
- figure 11 shows a side view of the second slider of the device in figure 1;
- figure 12 shows a view from above of the device

according to a second preferred embodiment of the present invention, with the drawing element in the initial position and the door closed; and

- figure 13 shows a view from above of the drawing element of the device in figure 12.

In the various embodiments, equivalent parts are identified by the same numerical references.

With reference to the above-mentioned figures, a device for opening and closing a movable part of a furniture unit according to the invention is shown, globally indicated by the reference number 1.

The movable part 103 of the furniture unit to which reference is made herein, in this specific preferred embodiment, is a door swinging in relation to the body of a furniture unit, but more in general it might equally be the front of a drawer or other such parts.

The device 1 comprises a body 208, associated with the fixed part of the furniture unit 116, for supporting a slider 3 reversibly sliding along a sliding axis 100 in contrast and due to the action of first elastic mean, and in particular of a spring 5. More precisely, the slider 3 is slidably engaged in a groove 204 in the supporting body 208 that extends in the direction of the sliding axis 100, and that is engageable with drawing means installed on a drawing element 205 sliding in the direction of the sliding axis 100 and integral or reversibly couplable with the movable part 103 of the furniture unit. In particular, the drawing element 205 is slidably supported inside a guide element 114 provided in a cover element 215 on the supporting body 208.

The drawing element 205 extends longitudinally in the direction of the sliding axis 100 and has a "C"-shaped cross-section.

The supporting body 208 comprises first displacement means suitable for moving the drawing means so as to release said drawing means and the slider 3 from their mutual engagement.

The drawing means are advantageously supported by the drawing element 205 so that they are movable transversely to the direction of the sliding axis 100.

In particular, the drawing means comprise a drawing pin 206 attached to a lever 43 that is hinged at 44 to the drawing element 205 so as to enable a swinging action.

With reference to the embodiment shown in figures 1-11, on the arm opposite to the drawing pin 206, the lever 43 carries an element 42 for mechanically hooking to the movable part 103, e.g. by means of an element 41 attached to the movable part 103 and provided with two flanges that hold a cross pin 40 hooked up by the hooking element 42.

Figures 12 and 13 show a second embodiment of the invention that essentially differs from the first only in terms of the structure of the drawing element 205, in that the system for hooking up the movable part 103 is of magnetic type.

In this case, the lever 43 is a simple lever with the drawing pin 206 fitted at its free end. The magnetic element 300 can be carried by the movable part 103, or by the front end of the drawing element 205.

From now on, reference is made once again to both the preferred embodiments of the invention.

The supporting body 208 includes a track 45 along which the free end of the drawing pin 206 is guided. The first displacement means, consisting of at least one first stretch 151 and one second stretch 152 of the track 45, extend in a sloping manner transversely to the direction of the sliding axis 100 and they are connected by a third stretch 153 and a fourth stretch 154 of said track that extend parallel to the direction of the sliding axis 100.

In particular, the track 45 comprises two adjacent parallel rails that extend along a closed path with a quadrangular shape.

The first embodiment of the present invention enables the mechanical control of the engagement and disengagement of the device 1 to and from a movable part 103 of a furniture unit using the track 45 provided for the drawing pin 206, and it is preferable to the second embodiment of the present invention because it avoids the need to use magnetic couplings, which are less reliable and noisier.

In its front end portion, the groove 204 comprises second means for displacing the slider 3 transversely to the sliding axis 100, and suitable for engaging in a releasable manner with means for guiding the slider 3.

The second displacement means comprise a front bend 155 in the groove 204, while the guide means comprise a front guide pin 156 and a rear guide pin 157, carried permanently by the slider 3 and slidably inside the groove 204.

The slider 3 also comprises a recessed surface 158, limited by a front edge 159 and a rear edge 160 for intercepting the drawing pin 206, with a rear cavity

161, where the drawing pin 206 is releasably engageable.

In the present embodiment of the invention, in which the device 1 is attached to a furniture unit fitted with hinges that exert a thrust in the direction for closing the movable part 103, there is also a second slider 101 carried by the supporting body 208 and reversibly movable in the direction of the sliding axis 100 in contrast and due to the action of second elastic means, and particularly of a second spring 102. The second slider 101 is engageable with second drawing means provided on the drawing element 205.

The second drawing means comprise a fin 207 that extends laterally from the drawing element 205 and engages slidingly in a guiding slot 108 provided in the second slider 101.

The device 1 also includes an elastically yielding stop element 209 against which the drawing element 205 abuts directly or indirectly before it engages with the drawing means in the first displacement means, and it may be fitted with thrust means that push the drawing element in the opening direction.

These thrust means preferably push the drawing element 205 only over one stretch of its displacement stroke.

The thrust means comprise an ejector contained in the supporting body 208 to the rear of the drawing element 205. The ejector includes a portion 20 for accommodating a stem 20b that is movable in the direction of the sliding axis 100 in contrast and due to the action of a spring (not shown) and it is designed to take effect on the rear base of the drawing element 205 to generate an initial opening

stroke of the movable part 103 with a greater force than is exerted thereon by any independent closing devices, such as those integrated in the hinges, for instance.

In any case, the ejector has a force of expulsion that is weaker than the elastic force of the first elastic means so that, when the slider 3 is free to slide, the latter are able to bring the drawing element 205, with which the slider 3 engages, into the position corresponding to the closed position of the movable part 103 (Fig. 6).

In the embodiments illustrated, the drawing element 205 consequently abuts indirectly against the stop element 209, i.e. with the interposition of the ejector that, in the closed position, has its stem 20b completely withdrawn inside the portion 20, thus forming a rigid unit.

The portion 20 of the ejector is pushed by the elastically yielding stop element 209 against a fixed stop element 50 on the supporting body 208 with a greater force than is exerted by the first elastic means, so that it can withdraw in the direction of the sliding axis 100 under the effect of an external action contrasting the elastically yielding stop element 209, that in the case in point is a spring interposed between the rear base of the portion 20 and the bottom wall of the fixed guide 162 along which the portion 20 is movable. The operation of the device according to the invention emerges clearly from the above description and illustrations, and with reference to the first preferred embodiment in particular, it is substantially as follows.

In the first phase, in which the movable part 103 is closed and abuts against the drawing element 205,

the drawing pin 206 engages in the rear cavity 161 of the slider 3, that is retained in a position at rest in which the drawing element 205 abuts against the stem 20b of the ejector, which in turn abuts against the elastically yielding stop element 209, which is not compressed, but only preloaded so as to retain the ejector in position against the fixed stop element 15. The stem 20b is in a withdrawn position, since the force of the ejector 20 is weaker than the force of the spring 5.

As shown in figure 2, following the displacement of the drawing element 205, a pressure exerted on the movable part 103 of the furniture unit from the outside induces a withdrawal of the accommodation portion 20 of the ejector in contrast with the stop element 209, that yields elastically. This displacement makes the drawing pin 206 slide transversely along the sloping wall 152 of the track 45, releasing the drawing pin 206 from its seat 161 where it engages with the slider 3, while simultaneously making the hooking element 42 engage with the pin 40 of the movable part 103 of the furniture unit. When the pressure exerted by the user from the outside is released, the spring 5 keeps the slider 3 in its position at the bottom of the groove 204, while the accommodation portion 20 of the ejector returns to its initial position abutting against the fixed stop element 50 and the stem 20b is extracted and thus pushes the drawing element 205 with the drawing pin 206 into the position shown in figure 3, in which the movable part 103 can be grasped and pulled to open it completely.

During this opening movement, the drawing pin 206 encounters and pushes against the front edge 159 of the slider 3, which is drawn along the groove 204 into the position shown in figure 4, in which the drawing pin 206 slides along the sloping front wall 151 of the track 45. In this position, the slider 3 engages with the guide pin 156 in the front bend 155 in the groove 204 and thus remains locked in its position with the spring 5 loaded, the hooking element 42 is disengaged from the pin 40 and the drawing element 205, together with the drawing pin 206, is pushed backwards due to the effect of its drawing fin 207 being engaged with the slider 101 recalled by the spring 102, that was loaded previously, during the extraction of the drawing element 205.

In the position shown in figure 5, the drawing pin 206 encounters and pushes against the rear edge 160 of the slider 3, which is thus released from its current position and returns, together with the drawing element 205, to the initial position shown in figure 6, but with the movable part 103 open. Since the hooking element 42 is raised in this position, the movable part 103 can be closed again normally, by means of the typical closing devices of known type with which it is fitted. Moreover, from its closed position the movable part 103 can also be opened accidentally by pulling it without the device being operated in an anomalous manner, and consequently without it being damaged. The device comprising a magnetic hooking system, shown in figures 12 and 13, is also suitable for movable parts of furniture units fitted with guides or hinges and already complete with independent thrust devices in the opening direction, but it is

distinguishable essentially in that the rotation of the lever 43 is exploited only to disengage the drawing pin 206 from the slider, while the drawing element 205 is released from the movable part 103 of the furniture unit when the magnetic connecting force is exceeded by the pulling force exerted by the user and the drawing element 205 is retained at the end of its stroke by the front stop on the slider 101.

It has been demonstrated in practice that the device according to the invention is particularly advantageous in enabling the simple and practical opening and closing of a door or drawer, making it easy for the user to grasp and ensuring a controlled closing action.

The invention thus conceived may undergo numerous modifications and variants, all coming within the scope of the inventive concept; moreover, all the component parts may be replaced with other, technically equivalent components.

In practice, any materials may be used, and in any sizes, according to need and the state of the art.

CLAIMS

1. Device for opening and closing a moveable part of a furniture, characterised in that it comprises - associated to a fixed part of the furniture - a body for supporting a slider reversibly sliding along a sliding axis in contrast and due to the action of first elastic means, said slider being engageable with drawing means present on a drawing element sliding in the direction of said sliding axis integral or in a manner reversibly couplable with said moveable part of the furniture, said support body comprising first movement means adapted to move said drawing means in such a manner to free said drawing means and said slider from their mutual engagement, further provided for being a yielding elastic stop element against which said drawing element directly or indirectly abuts against before being engaged with said drawing means in said first movement means.
2. Device for opening and closing a moveable part of a furniture according to claim 1, characterised in that it comprises thrust means adapted to directly or indirectly push said drawing element in the opposite direction and with a force lower with respect to the

pushing of said first elastic means.

3. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said thrust means push said drawing element only for a section of the movement thereof.
4. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said drawing means are supported by said drawing element in a moveable manner transversely to the direction of said sliding axis.
5. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said drawing means comprise a drawing pin fixed onto a lever pivoted in an oscillating manner on said drawing element.
6. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said first movement means comprise - in a track provided for in the body of said support and guided along which is the free end of said drawing pin - at least one first and one second section of said track transverse to the direction of said sliding axis and connected

to a third and a fourth section of said track developing parallel to the direction of said sliding axis.

7. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said track comprises two adjacent rails parallel to each other.
8. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said lever bears - on the opposite arm with respect said drawing pin - an element for mechanical engagement with said moveable part.
9. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that it comprises a magnetic element for engaging said drawing element with said moveable part.
10. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said support body has a groove which develops in the direction of said sliding axis and in that it comprises - in the zone of its front end - second means for moving said slider in a manner transverse to said sliding axis, such

means being adapted to be engaged in a releasable manner with guide means of said slider.

11. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said second movement means comprise a front curve of said groove, and said guide means comprise a front guide pin and a rear guide pin borne fixed by said slider and sliding in said groove.
12. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said slider comprises a lowered surface delimited by a front side and a rear side for intercepting said drawing pin, said lowered surface further having a front slot in which said sliding pin can be engaged in a releasable manner.
13. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that it comprises a second slider borne by said support body and reversibly sliding in the direction of said sliding axis in contrast and due to the action of second elastic means,

said second slider being engageable with second drawing means present on said drawing element.

14. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said thrust means comprise and ejector comprising a part for accommodating a slider moveable in the direction of said sliding axis, wherein said accommodation part is moved by said elastically yielding stop element against a fixed stop element of said support body in such a manner to be able to be retracted in the direction of said sliding axis in contrast to said elastically yielding stop element, and wherein said slider is adapted to operate against the rear base of said drawing element to generate an initial travel for opening said moveable part.

15. Device for opening and closing a moveable part of a furniture according to one or more of the preceding claims, characterised in that said elastically yielding stop element is a spring interposed between the rear base of said accommodation part and a bottom wall of a fixed guide along which said accommodation part is moveable.




Fig. 1




Fig. 2

Fig. 3














Fig. 4









INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2009/008713

A. CLASSIFICATION OF SUBJECT MATTER
INV. A47B88/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A47B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 199 35 120 A1 (BULTHAUP GMBH & CO) 15 February 2001 (2001-02-15)	1-4, 10
Y	column 1, line 3 - line 4	14-15
A	column 1, line 14 - column 2, line 10 column 2, line 51 - column 4, line 67; figures 1-13	12
X	-----	
Y	WO 2005/012678 A1 (SALICE ARTURO SPA) 10 February 2005 (2005-02-10) page 1, line 3 - line 6 page 3, line 21 - page 6, line 21; figures 1,2,4-6,9	1,4-5, 9-10,12 14-15

	-/-	

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

25 February 2010

04/03/2010

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Jacquemin, Martin

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2009/008713

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2007/222346 A1 (KLEINSASSER) 27 September 2007 (2007-09-27)	1-3, 10-11
A	paragraph [0005] - paragraph [0007] paragraph [0011] - paragraph [0013] paragraph [0016] paragraph [0026] paragraph [0029] - paragraph [0032]; figures 4a,5a,5b,5c,5d,5e,5f -----	5,12-13

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No
PCT/EP2009/008713

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
DE 19935120	A1	15-02-2001	NONE	
WO 2005012678	A1	10-02-2005	CN EP	1829847 A 1664466 A1 06-09-2006 07-06-2006
US 2007222346	A1	27-09-2007	AT WO CN EP JP	503066 A1 2006058351 A1 101068487 A 1816927 A1 2008521517 T 15-07-2007 08-06-2006 07-11-2007 15-08-2007 26-06-2008