

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 February 2009 (19.02.2009)

PCT

(10) International Publication Number
WO 2009/021810 A1

(51) International Patent Classification:
H04L 29/06 (2006.01)

(21) International Application Number:
PCT/EP2008/059599

(22) International Filing Date: 22 July 2008 (22.07.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
07114269.9 13 August 2007 (13.08.2007) EP

(71) Applicant (for all designated States except US): **NOKIA SIEMENS NETWORKS OY** [FI/FI]; Karaportti 3, FIN-02610 Espoo (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BELLING, Thomas** [DE/DE]; Gleiwitzerstr. 25, 85435 Erding (DE).

(74) Agents: **LESON, Thomas J.A.** et al.; Bavariaring 4 - 6, 80336 Munich (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(54) Title: SUPPORT OF MEDIA ORIENTED NEGOTIATION ACCELERATION PROCEDURES IN SPLIT ARCHITECTURE

FIG 3A





FIG 3



(57) Abstract: A gateway controlling device is configured to send a message to a controlled device requesting that a media oriented negotiation acceleration preference message is to be sent repeatedly. The gateway controlling device is further configured to provide the controlled device with media oriented negotiation acceleration preferences within that message which are to be advertised by the controlled device, and to request the controlled device to send a notification to the gateway controlling device about receipt of the first media oriented negotiation acceleration preference message. The gateway controlling device receives a notification from the controlled device about receipt of a media oriented negotiation acceleration preference message which firstly came in at the controlled device.

**Support of media oriented negotiation acceleration
procedures in split architecture**

The present invention relates to a controlling device and
5 a media gateway device both of which are configured to
support media oriented negotiation procedures in split
architecture. The present invention also relates to
corresponding methods and computer program products.

10 Media Oriented Negotiation Acceleration (MONA), as
specified in the specification ITU-T H.324 Amendment 1 of
the International Telecommunication Union (ITU), provides
— simplified procedures that allow for a faster call set-up
of a H.324 Multimedia call (e.g. using voice and video)
15 than standard H.324 procedures as specified in
specification ITU-T H.324, and also allow for a fallback
to standard H.324 procedures if either party does not
support the enhanced procedures. H.324 is a protocol
— suite which combines signalling according to
20 specification ITU-T H.245 and media in user plane
bearers.

Multimedia calls may also be performed using the session
initiation protocol SIP according to the specification
25 RFC 3261 of the International Engineering Task Force as
call control and Internet Protocol (IP)/user datagram
protocol (UDP)/real time protocol (RTP) based media
transport.

30 While Multimedia calls in the circuit switched (CS)
domain of the 3rd generation (according to the 3rd
generation partnership project 3GPP) use H.324, possibly
with the MONA enhancements, multimedia calls in the 3GPP
Internet Multimedia Subsystem (IMS) use SIP and
35 IP/UDP/RTP.

For multimedia calls between the 3GPP CS domain and the IMS, an interworking between H.324 and SIP is therefore required. Such an interworking is standardised in the
5 specification 3GPP TS 29.163.

A typical network configuration as outlined above is shown in Fig. 1.

10 The interworking is performed by entities with a so-called split architecture between call control signalling handling and media handling: The Media Gateway Control
— Function (MGCF) controls the attached Internet Multimedia Media gateway (IM-MGW) using the ITU-T H.248 protocol
15 over the so-called Mn interface.

Some of the present MONA procedures are summarized in the following.

—
20 MONA "preference message" signalling is used instead of H.324 Multiplexing level negotiation. Should standard H.324 Multiplexing level stuffing flags be received, a fallback to standard H.324 procedures is triggered. The sending of MONA preference messages is repeated by each
25 MONA capable H.324 terminal until a reception is acknowledged by the peer.

During this phase, two packet data unit (PDU) types may optionally be attached by MONA terminals to these
30 preference messages. Either, these could be Media Preconfigured Channel (MPC) packet data units. That is, MONA defines a small number of preconfigured H.223 channels for the most widespread audio and video codecs (AMR, AMR-WB, H.264 MPEG4 and H.263). Media packet data
35 units for these codecs may be attached to the MONA

"preference message" during the call setup. Or, these could be Signalling Preconfigured Channel (SPC) packet data units. These packet data units are H.245 generic request messages with special parameters defined by MONA.

5 These packet data units may also be attached to MONA preference messages.

According to MONA, each MONA capable terminal shall support at least one of these PDU types.

10

The MONA preference message exchange in combination with attached MPC or SPC packet data units may result in the establishment of the desired media channels without further H.245 signalling. Otherwise, H.245 will be used after the MONA preference message exchange is acknowledged to negotiate media channels, but MONA defines some accelerated H.245 procedures (ACP) to speed up these H.245 procedures.

20

H.248 procedures to support the interworking between standard H.324 procedures and SIP in split architecture have already been standardized in the specifications 3GPP TR 29.863, TS 29.163 and TS 29.332 and ITU-T H.248.12, but H.248 procedures to support the interworking between H.324 MONA and SIP in split architecture are still outstanding.

25

Therefore, it is an object of the present invention to overcome the above described shortcomings of the prior art.

30

Thus, an implementation of the present invention to the above described scenario can provide suitable procedures for the above described purpose.

35

In addition, the same procedures can also be applied for an interworking between the ITU-T H.324 protocol suite, which uses H.245 signalling in-band, and the ITU-T H.323 protocol suite, which uses H.245 signalling out-of-band.

5

According to a first aspect of the present invention, there is provided a gateway controlling device configured to send a message to a controlled device requesting that a media oriented negotiation acceleration preference message is to be sent repeatedly; provide the controlled device with media oriented negotiation acceleration preferences within that message which are to be advertised by the controlled device; request the controlled device to send a notification to the gateway controlling device about receipt of the first media oriented negotiation acceleration preference message; and receive a notification from the controlled device about receipt of a media oriented negotiation acceleration preference message which firstly came in at the controlled device.

Modifications of the first aspect according to the present invention may be follows.

25 The gateway controlling device may be further configured to have a media gateway control function implemented.

The gateway controlling device may be further configured to send a message to the controlled device requesting to be notified about the channel type of received media preconfigured channel packet data units.

The gateway controlling device may be further configured to send a message to the controlled device requesting to send media encoded according to one or several of media

35

predefined channel types defined by media oriented negotiation acceleration.

5 The gateway controlling device may be further configured to send a message to the controlled device requesting to be notified about the receipt of signalling preconfigured channel packet data units.

10 The gateway controlling device may be further configured to send a message to the controlled device providing a signalling preconfigured channel packet data unit and requesting that this packet data unit is forwarded
— repeatedly.

15 The gateway controlling device may be further configured to send a message to the controlled device requesting to be notified about the receipt of H.323 multiplex level stuffing flags.

—
20 According to a second aspect of the present invention, there is provided a media gateway device configured to receive a message from a gateway controlling device requesting that a media oriented negotiation acceleration preferences negotiation is started and including media
25 oriented negotiation acceleration preferences to be advertised; repeatedly send media oriented negotiation acceleration preference messages; and increment acknowledgment bits of sent media oriented negotiation acceleration preference messages when receiving incoming
30 media oriented negotiation acceleration preference messages.

Modifications of the second aspect according to the present invention may be follows.

The media gateway device may be further configured to have an internet multimedia subsystem media gateway functionality implemented.

- 5 The media gateway device may be further configured to notify the gateway controlling device when receiving the first incoming media oriented negotiation acceleration preference message; and forward the received information, wherein the gateway controlling device is not notified
10 about subsequent incoming media oriented negotiation acceleration preference message.

— The media gateway device may be further configured to receive a first media preconfigured channel packet data
15 unit of a given predefined channel type; and notify the gateway controlling device about the received channel type.

— The media gateway device may be further configured to
20 receive media streams that require interworking towards a corresponding H.324 session; and send these media streams in media preconfigured channel packet data units of a predefined channel type requested by the gateway controlling device by media oriented negotiation
25 acceleration preference messages, transcoding the media if required.

The media gateway device may be further configured to receive a first signalling preconfigured channel packet
30 data unit; and forward the signalling preconfigured channel packet data unit to the gateway controlling device.

The media gateway device may be further configured to
35 compare any subsequently received signalling

preconfigured channel packet data units with the previously received signalling preconfigured channel packet data unit; and forward the subsequently received signalling preconfigured channel packet data unit to the gateway controlling device only, if it differs from the previously received signalling preconfigured channel packet data unit.

The media gateway device may be further configured to receive a message from the gateway controlling device providing a signalling preconfigured channel packet data unit; and repeatedly forward this signalling preconfigured channel packet data unit.

The media gateway device may be further configured to notify the gateway controlling device about the receipt of more than a preconfigured number of valid consecutive multiplex level stuffing flags.

According to a third aspect of the present invention, there is provided a controlling method, comprising sending a message from a gateway controlling device to a controlled device requesting that a media oriented negotiation acceleration preference message is sent repeatedly; providing the controlled device by the gateway controlling device with media oriented negotiation acceleration preferences within that message which are to be advertised by the controlled device; requesting the controlled device to be notified about the receipt of the first media oriented negotiation acceleration preference message; and receiving a notification from the controlled device about the receipt of a media oriented negotiation acceleration preference message which firstly came in at the controlled device.

35

Modifications of the third aspect of the present invention may be as follows.

5 The controlling method may further comprise using a media gateway control function by the gateway controlling device.

10 The controlling method may further comprise sending a message by the gateway controlling device to the controlled device requesting to be notified about a channel type of received media preconfigured channel packet data units.

15 The controlling method may further comprise sending a message by the gateway controlling device to the controlled device requesting to send media encoded according to one or several of media predefined channel types defined by media oriented negotiation acceleration.

20 The controlling method may further comprise sending a message by the gateway controlling device to the controlled device requesting to be notified about the receipt of signalling preconfigured channel packet data units.

25 The controlling method may further comprise sending a message by the gateway controlling device to the controlled device providing a signalling preconfigured channel packet data unit and requesting that this packet data unit is forwarded repeatedly.

30 The controlling method may further comprise sending a message to the controlled device requesting to be notified about the receipt of H.323 multiplex level stuffing flags.

According to a fourth aspect of the present invention,
there is provided a media gateway method comprising
receiving a message from a gateway controlling device by
5 a media gateway device requesting that a media oriented
negotiation acceleration preferences negotiation is
started and including media oriented negotiation
acceleration preferences to be advertised; repeatedly
sending media oriented negotiation acceleration
10 preference messages by the media gateway device; and
incrementing acknowledgment bits of sent media oriented
negotiation acceleration preference messages by the media
— gateway device when receiving incoming media oriented
negotiation acceleration preference messages.

15 Modifications of the fourth aspect of the present
invention may be as follows.

— The media gateway method may further comprise using an
20 internet multimedia subsystem media gateway functionality
by the media gateway device.

The media gateway method may further comprise notifying
the gateway controlling device by the media gateway
25 device when receiving the first incoming media oriented
negotiation acceleration preference message; and
forwarding the received information by the media gateway
device, wherein the gateway controlling device is not
notified about subsequent incoming media oriented
30 negotiation acceleration preference message.

The media gateway method may further comprise receiving a
first media preconfigured channel packet data unit of a
given predefined channel type by the media gateway

device; and notify the gateway controlling device by the media gateway device about the received channel type.

5 The media gateway method may further comprise receiving media streams by the media gateway device that require interworking towards a corresponding H.324 session; and sending these media streams by the media gateway device in media preconfigured channel packet data units of a predefined channel type requested by the gateway
10 controlling device by media oriented negotiation acceleration preference messages, and transcoding the media by the media gateway device if required.

15 The media gateway method may further comprise receiving a first signalling preconfigured channel packet data unit by the media gateway device; and forwarding the signalling preconfigured channel packet data unit by the media gateway device to the controlling device.

20 The media gateway method may further comprise comparing by the media gateway device any subsequently received signalling preconfigured channel packet data units with the previously received signalling preconfigured channel packet data unit; and forwarding the subsequently
25 received signalling preconfigured channel packet data unit by the media gateway device to the gateway controlling device only, if it differs from the previously received signalling preconfigured channel packet data unit.

30

The media gateway method may further comprise receiving a message by the media gateway device from the gateway controlling device providing a signalling preconfigured channel packet data unit; and repeatedly forwarding this

signalling preconfigured channel packet data unit by the media gateway device.

5 The media gateway method may further comprise notifying the gateway controlling device about the receipt of more than a preconfigured number of valid consecutive multiplex level stuffing flags.

10 According to a fifth aspect of the present invention, there is provided a computer program product embodied on a computer-readable medium, the computer program product configured to provide instructions to carry out a method
— according to the third or fourth aspect of the present invention or any of their modifications.

15 Further aspects, features and advantages of the present invention will become more fully apparent from the following detailed description of the preferred embodiments
— which is to be taken in conjunction with the appended drawings, in which:

20

Fig. 1 shows a typical network configuration to which the present invention is applicable;

25 Fig. 2 shows an H.248 context model according to specification 3GPP TS 29.163 which underlies preferred embodiments of the present invention;

Fig. 3 shows signalling interactions at the Mn interface
30 for MONA preference messages involving a gateway controlling device (MGCF) and a media gateway device (IM MGW) and thus also illustrates respective configurations of these devices;

Fig. 4 shows signalling interactions at the Mn interface for MONA media preconfigured channels involving a gateway controlling device (MGCF) and a media gateway device (IM MGW) and thus also illustrates respective configurations of these devices;

Fig. 5 shows signalling interactions at the Mn interface for sending MONA signalling preconfigured channels involving a gateway controlling device (MGCF) and a media gateway device (IM MGW) and thus also illustrates respective configurations of these devices;

Fig. 6 shows signalling interactions at the Mn interface for receiving MONA signalling preconfigured channels involving a gateway controlling device (MGCF) and a media gateway device (IM MGW) and thus also illustrates respective configurations of these devices; and

Fig. 7 shows signalling interactions at the Mn interface for fallback from MONA procedures to standard H.324 setup involving a gateway controlling device (MGCF) and a media gateway device (IM MGW) and thus also illustrates respective configurations of these devices.

In the following, preferred embodiments of the present invention are described with reference to the accompanying drawings. It should, however, be understood that this description is for illustrative purposes only and that the present invention is by no means to be construed as being limited to the embodiments described and illustrated.

According to preferred embodiments of the present invention, one or more of the following is implemented.

A controlling entity (e.g. MGCF) sends a message to a controlled entity (e.g. IM-MGW) requesting that the MONA preferences negotiation is started, and provides the MONA preferences to be advertised by the controlled entity
5 within that message.

Upon reception of this message, the controlled entity starts sending MONA preference messages. The controlled entity repeats sending those messages and increments the
10 acknowledgment bits of sent MONA preference messages when receiving incoming MONA preference messages according to MONA procedures.

The controlled entity notifies the controlling entity
15 when receiving the first incoming MONA preference message and forwards the received information. The controlled entity does not notify the controlling entity about subsequent incoming MONA preference message.

20 To use MONA MPC related procedures, the controlling entity may also send a message to the controlled entity requesting to be notified about the channel type of received MPC packet data units. If the controlled entity then receives the first MPC PDU of a given predefined
25 channel type (see e.g. Fig. 3, signal 6), and the controlling entity has requested a notification about such an event, the controlled entity notifies the controlled entity about the received channel type.

30 To use MONA MPC related procedures, the controlling entity may also send a message to the controlled entity requesting to send media encoded according to one or several of the media predefined channel types defined by MONA.

Upon reception of this request, if the controlled entity receives any media streams that require interworking towards the corresponding H.324 session, the controlled entity sends these media in MPC packet data units of the requested predefined channel type attached to MONA preference messages, and transcodes the media if required.

To use MONA SPC related procedures, the controlling entity may also send a message to the controlled entity requesting to be notified about the reception of SPC packet data units. If the controlled entity then receives the first SPC PDU, and the controlling entity has requested a notification about such an event, the controlled entity forwards the SPC PDU to the controlled entity. The controlled entity compares any subsequent received SPC packet data units with the previous received SPC PDU and forwards the subsequently received SPC PDU to the controlled entity only if it differs from the previous received SPC PDU.

To use MONA SPC related procedures, the controlling entity may also send a message to the controlled entity providing an SPC PDU and requesting that this PDU is forwarded. Upon reception of this request, the controlled entity sends the SPC PDU. The controlled entity should repeat sending this SPC PDU without further request from the controlling entity.

Thus, according to a design of procedures at the Mn interface to support MONA as described in connection with the above embodiments, the following advantages can be achieved.

The H.245 handling can be performed in the MGCF to keep procedures aligned as far as possible with standard Mn procedures to support H.324 interworking.

5 The MGCF can also control MONA preference message exchange procedures in order to maintain the agreed architectural work split between MGCF and IM-MGW in analogy to the H.245 handling.

10 In a preferred implementation, the IM-MGW understands the MONA preference messages at least to a sufficient degree
— to de-encapsulate the possibly attached MPC and SPC packet data units.

15 Furthermore, the frequent retransmissions of MONA preference messages required by MONA procedures are performed by the IM-MGW autonomously to avoid unnecessary load at the Mn interface and the MGCF.

—
20 In the following, the preferred embodiments of the present invention are described in even more detail, wherein the H.248 context model according to specification 3GPP TS 29.163 as shown in Fig. 2 underlies signalling flows described below.

25 Fig. 3 shows the signalling flows for interactions at the Mn interface for MONA preference messages. It is to be noted that the MONA preference messages are repeated several times, wherein one repetition is illustrated for
30 each such message with the same number as the first message.

According to the preferred embodiments shown in Fig. 3, the MGCF requests terminations towards the CS network
35 (signals 1 and 2) and towards the IMS (signals 3 and 4).

For the terminations towards the IMS, the MGCF provides an estimate about the applicable codecs in the required information elements "Local IMS Resources" (for both "Reserve IMS Connection Point" procedure and "Reserve IMS
5 Connection Point and Configure Remote Resources" procedure) and possibly "Remote IMS Resources" (only for "Reserve IMS Connection Point and Configure Remote Resources" procedure).

10 The MGCF requests that the H.223 stream is (de-) multiplexed at the MUX termination T2 (signal 6).
Furthermore, the MGCF requests that MONA preferences
— negotiation is started, and provides that the MONA preferences are to be indicated by the IM-MGW. The MGCF
15 encodes the MONA preferences as described in clause 6 of specification ITU-T H.324 Amendment 1. The MGCF takes the H.324 related capabilities of the IM-MGW into account in the MONA preferences. These capabilities can be known by
— the MGCF by configuration. The MGCF also requests to be
20 notified about the reception of the remote MONA preferences and about the completion of the MONA preference exchange, and about the possible reception of a H.323 multiplex level message or a H.245 message on the H.323 control channel. The MGCF also provides a
25 multiplexing level which will be advertised by the IM-MGW for fallback to standard H.324 setup procedures. If the MGCF indicates the capability to receive SPC packet data units within the MONA preferences, it also requests to be notified about incoming SPC packet data units (which is
30 described further below). If the MGCF indicates the capability to receive any MPC packet data units within the MONA preferences, it also requests to be notified about incoming MPC packet data units, as detailed below.

The IM-MGW starts sending MONA preference messages after receipt of the corresponding request from the MGCF and CS bearer establishment (signal 8). The IM-MGW repeats sending those messages and increments the acknowledgment
5 bits of sent MONA preference messages when receiving incoming MONA preference messages according to MONA procedures (signals 8, 10, 14).

After sending at least ten MONA preference messages,
10 while the IM-MGW continues to send and receive MONA preference messages, it attaches MPC or SPC packet data units if requested to do so by the MGCF, as described
— further below. If the IM-MGW receives preference messages with an attachment, it inspects the first octet of that
15 attachment that will contain a MUX code according to table K.15 of specification ITU-T H.324 Amendment 1 that identifies the attached PDU as either a MPC PDU of one of the predefined channels or a SPC PDU. The IM-MGW handles
— the attached MPC or SPC packet data units as described
20 below.

After sending at least ten MONA preference messages, the IM-MGW inserts stuffing flags indicating the multiplexing level received from the MGCF between MONA preference
25 messages as described in clause K.7.1.1 of specification ITU-T H.324 Amendment 1.

The IM-MGW notifies the MGCF, when receiving the first incoming MONA preference message (signals 11 and 12), and
30 forwards the received information. Subsequent incoming MONA preference message will be identical apart from possible increments in the acknowledgement bits. The IM-MGW does not notify the MGCF about these messages. Upon reception of the notification of a MONA preference
35 message, the MGCF compares the received MONA preferences

message with the preferences message it sent, and reacts as described in clause 7.1 of specification ITU-T H.324 Amendment 1.

- 5 When receiving an incoming MONA preference message with acknowledgment bits 10, the IM-MGW stops sending MONA preference messages and notifies the MGCF about the completion of the MONA preference exchange procedure (signals 16 and 17).

10

Upon reception of this notification, the MGCF checks if all desired media channels have been established.

— Otherwise the MGCF uses accelerated H.245 procedures as defined by MONA to set up media channels. Corresponding
15 H.245 messages are transported transparently between the IM-MGW and the MGCF using the "Signal H.245 message" and "Notify H.245 message" procedures defined in specification 3GPP TS 29.163.

- 20 After receiving the notification about the completion of the MONA preference exchange procedure, and a completion of the possible subsequent accelerated H.245 setup procedures, the MGCF configures the multiplexing termination T2 by indicating to the IM-MGW the contents
25 of the incoming and outgoing multiplex tables (signal 19), and modifies the selected codecs at the IMS side (signal 21).

- Herein below, reference is made to Fig. 4, which shows
30 the signalling interactions at the Mn interface for MONA media preconfigured channels as referred to above as a modification to the preferred embodiments of the present invention.

It is to be noted that MONA preference messages are repeated several times, However, only one repetition is shown for each such message with the same signal number as the first message.

5

Specifically, Fig. 4 illustrates that if the MGCF indicates the ability to receive any predefined MPC channel types in the MONA preferences messages, the MGCF requests the IM-MGW to report the channel type of received MPC packet data units (signal 1).

10

If the MGCF intends to use media preconfigured channels for sending media during the MONA setup, the MGCF requests the IM-MGW to send media encoded according to one or several of the media predefined channel types defined by MONA (signal 3), while the MONA preference exchange described in described above is ongoing. The MGCF selects channel types for codecs which are supported by both the IMS side and the IM-MGW, and/or for codecs which could be transcoded by the IM-MGW from the codecs supported by the IMS side. The MGCF may also configure the MGW to receive these channels at the same time.

15

20

Upon reception of this request, the IM-MGW forwards any media received from the IMS side in MPC packet data units of the corresponding predefined channel type attached to MONA preference messages, and transcodes the media if required (signal 5).

25

If the IM-MGW receives the first MONA preference message with attached MPC PDU of a given predefined channel type (signal 6), and the MGCF has requested a notification about such an event, the IM-MGW notifies the MGCF about the received channel type (signal 7). The IM-MGW does not

30

notify the MGCF about subsequent receptions of MPC packet data units of the same channel type.

Upon reception of such a notification, if the IM-MGW
5 supports the indicated channel type and has not yet been configured to receive media of that channel type, and if the MGCF has previously indicated the capability to receive media preconfigured channels of that channel type within MONA preference messages, the MGCF configures the
10 IM-MGW to receive media of that channel type and forwards them to the IMS side (signal 9).

— Herein below, reference is made to Fig. 5, which shows the signalling interactions at the Mn interface for
15 sending MONA signalling preconfigured channels as referred to above as a further modification to the preferred embodiments of the present invention.

— It is to be noted that the MONA preference messages are
20 repeated several times. However, only one repetition is shown for each such message with the same signal number as the first message.

Specifically, Fig. 5 illustrates that H.245 packet data
25 units for SPC are transported between the IM-MGW and MGCF over the Mn interface using H.248 events (from the IM-MGW towards the MGCF) and H.248 signals (from the MGCF towards the IM-MGW). The events/signals contain the H.245 message in binary format as parameters.

30

The related procedures are distinct from the procedures in clause E.4.2.3 of specification 3GPP TS 29.163, since the packet data units are received or sent by the IM-MGW using the SPC, i.e. as attachment to MONA preference
35 messages.

If the MGCF supports signalling preconfigured channels, it complies to the SPC procedures in Clause K.8 of specification ITU-T H.324 Amendment 1. However, the MGCF
5 does not repeat sending the same signalling preconfigured channels, as this repetition will be handled by the IM-MGW.

Within the sent SPC packet data units, the MGCF includes
10 the codecs which are supported by both the IMS side and the IM-MGW, and the codecs which could be transcoded by the IM-MGW from the codecs supported by the IMS side.

—
In signal 1, the MGCF requests the IM-MGW to send an
15 H.245 message to the CS side. To request the IM-MGW to send a H.245 message to the CS side, the MGCF sends an H.248 signal to the IM-MGW with the complete H.245 message content.

—
20 Upon reception of this signal, the IM-MGW sends the encapsulated H.245 message within the H.248 signal as attachment to a MONA preference message as described in Clause K.9.4 of specification ITU-T H.324 Amendment 1 (signal 3). It repeats sending this H.245 message as
25 attachment to subsequent MONA preference messages.

Herein below, reference is made to Fig. 6, which shows the signalling interactions at the Mn interface for receiving MONA signalling preconfigured channels as
30 referred to above as a further modification to the preferred embodiments of the present invention.

It is to be noted that MONA preference messages are repeated several times. However, only one repetition is

shown for each such message with the same signal number as the first message.

Specifically, Fig. 6 illustrates with signal 1, that the
5 MGCF requests the IM-MGW to detect a received H.245 message from the CS side in SPC packet data units attached to MONA preference messages and forwards them to the MGCF. To request the IM-MGW to detect and forward these H.245 message, the MGCF sends a suitable H.248
10 event to the IM-MGW. The event may be indicated through an H.248 ADD command.

— In signal 3, the IM-MGW receives an H.245 message from the CS side attached as SPC PDU to a MONA preference
15 message. Upon reception of such an H.245 message from the CS side, the IM-MGW checks if it has already forwarded the same H.245 message to the MGCF, and otherwise forwards the H.245 message to the MGCF within an H.248
— Notify command (signal 4). The IM-MGW does not forward
20 the same H.245 message which is received again in subsequent MONA preference messages.

If the IM-MGW does not support forwarding SPC packet data units or has not been requested by the MGCF to forward
25 these packet data units, it discards received SPC packet data units.

Herein below, reference is made to Fig. 7, which shows the signalling interactions at the Mn interface for fall
30 back from MONA procedures to standard H.324 setup as referred to above as a further modification to the preferred embodiments of the present invention.

It is to be noted that MONA preference messages are repeated several times. However, only one repetition is shown for each such message with the same signal number as the first message.

5

Specifically, Fig. 7 illustrates that when the MGCF requests that the MONA preferences negotiation is started, the MGCF also requests to be notified about the possible reception of H.323 multiplex level stuffing
10 flags or a H.245 message on the H.323 control channel. The MGCF also provides a multiplexing level which will be advertised by the IM-MGW for fallback to standard H.324
— setup procedures (signal 6).

15 If the IM-MGW receives more than 20 valid consecutive multiplexer level stuffing flags (signal 9), it notifies the MGCF (signal 10) and stops sending MONA preference messages. The IM-MGW engages in normal H.324 multiplexing
— level negotiations.

20

The MGCF then stops MONA procedures and falls back to standard H.245 call set-up procedures, as depicted in Figure E.4.2.4.1 in specification 3GPP TS 29.163 starting with step 9.

25

If the IM-MGW receives a normal H.245 message (not shown), it also forwards this message to the MGCF. If the MGCF receives such a H.245 message during the MONA call setup, and this H.245 message is a normal Terminal
30 Capability Set message, the MGCF also stops MONA procedures and falls back to standard H.245 call set-up procedures, as depicted in Figure E.4.2.4.1 in specification 3GPP TS 29.163 starting with step 9.

An implementation of embodiments of the present invention may be achieved by providing a computer program product embodied as a computer readable medium which stores instructions according to the above described
5 embodiments.

Thus, what is described above is a gateway controlling device is configured to send a message to a controlled device requesting that a media oriented negotiation
10 acceleration preference message is to be sent repeatedly. The gateway controlling device is further configured to provide the controlled device with media oriented
— negotiation acceleration preferences within that message which are to be advertised by the controlled device, and
15 to request the controlled device to send a notification to the gateway controlling device about receipt of the first media oriented negotiation acceleration preference message. The gateway controlling device receives a
— notification from the controlled device about receipt of
20 a media oriented negotiation acceleration preference message which firstly came in at the controlled device.

What has been described above is what is presently considered to be preferred embodiments of the present
25 invention. However, as is apparent to the skilled reader, these are provided for illustrative purposes only and are in no way intended to that the present invention is restricted thereto. Rather, it is the intention that all variations and modifications be included which fall
30 within the spirit and scope of the appended claims.

Claims:

1. An apparatus, comprising:

means configured to send a message to a controlled device requesting that a media oriented negotiation acceleration preference message is to be sent repeatedly;

means configured to provide the controlled device with media oriented negotiation acceleration preferences within that message which are to be advertised by the controlled device;

means configured to request the controlled device to send a notification to the apparatus about receipt of the first media oriented negotiation acceleration preference message; and

means configured to receive a notification from the controlled device about receipt of a media oriented negotiation acceleration preference message which firstly came in at the controlled device.

2. The apparatus according to claim 1, further comprising means configured to have a media gateway control function implemented.

3. The apparatus according to any one of the preceding claims, further comprising

means configured to send a message to the controlled device requesting to be notified about the channel type of received media preconfigured channel packet data units.

4. The apparatus according to any one of the preceding claims, further comprising

means configured to send a message to the controlled device requesting to send media encoded according to one or several of media predefined channel types defined by media oriented negotiation acceleration.

5. The apparatus according to claim 1 or claim 2, further comprising

means configured to send a message to the controlled device requesting to be notified about the receipt of signalling preconfigured channel packet data units.

6. The apparatus according to any one of claims 1, 2 and 5, further comprising

means configured to send a message to the controlled device providing a signalling preconfigured channel packet data unit and requesting that this packet data unit is forwarded repeatedly.

7. The apparatus according to any one of the preceding claims, further comprising

means configured to send a message to the controlled device requesting to be notified about the receipt of H.323 multiplex level stuffing flags.

8. An apparatus, comprising:

means configured to receive a message from a gateway controlling device requesting that a media oriented negotiation acceleration preferences negotiation is started and including media oriented negotiation acceleration preferences to be advertised;

means configured to repeatedly send media oriented negotiation acceleration preference messages; and

means configured to increment acknowledgment bits of sent media oriented negotiation acceleration preference messages when receiving incoming media oriented negotiation acceleration preference messages.

9. The apparatus according to claim 8, further comprising means configured to have an internet multimedia subsystem media gateway functionality implemented.

10. The apparatus according to claim 8 or claim 9, further comprising

means configured to notify the gateway controlling device when receiving the first incoming media oriented negotiation acceleration preference message; and

means configured to forward the received information, wherein

the gateway controlling device is not notified about subsequent incoming media oriented negotiation acceleration preference message.

11. The apparatus according to any one of claims 8 to 10, further comprising

means configured to receive a first media preconfigured channel packet data unit of a given predefined channel type; and

means configured to notify the gateway controlling device about the received channel type.

12. The apparatus according to any one of claims 8 to 11, further comprising

means configured to receive media streams that require interworking towards a corresponding H.324 session; and

means configured to send these media streams in media preconfigured channel packet data units of a predefined channel type requested by the gateway controlling device by media oriented negotiation acceleration preference messages, transcoding the media if required.

13. The apparatus according to any one of claims 8 to 10, further comprising

means configured to receive a first signalling preconfigured channel packet data unit; and

means configured to forward the signalling preconfigured channel packet data unit to the gateway controlling device.

14. The apparatus according to any one of claims 8 to 10 and 13, further comprising

means configured to compare any subsequently received signalling preconfigured channel packet data units with the previously received signalling preconfigured channel packet data unit; and

means configured to forward the subsequently received signalling preconfigured channel packet data unit to the gateway controlling device only, if it differs from the previously received signalling preconfigured channel packet data unit.

15. The apparatus according to any one of claims 8 to 10, 13 and 14, further comprising

means configured to receive a message from the gateway controlling device providing a signalling preconfigured channel packet data unit; and

means configured to repeatedly forward this signalling preconfigured channel packet data unit.

16. The apparatus according to any one of claims 8 to 10, further comprising

means configured to notify the gateway controlling device about the receipt of more than a preconfigured number of valid consecutive multiplex level stuffing flags.

17. A method, comprising

sending a message from a gateway controlling device to a controlled device requesting that a media oriented

negotiation acceleration preference message is sent repeatedly;

providing the controlled device by the gateway controlling device with media oriented negotiation acceleration preferences within that message which are to be advertised by the controlled device;

requesting the controlled device to be notified about the receipt of the first media oriented negotiation acceleration preference message; and

receiving a notification from the controlled device about the receipt of a media oriented negotiation acceleration preference message which firstly came in at the controlled device.

18. The method according to claim 17, further comprising using a media gateway control function by the gateway controlling device.

19. The method according to claim 17 or 18, further comprising

sending a message by the gateway controlling device to the controlled device requesting to be notified about a channel type of received media preconfigured channel packet data units.

20. The method according to any one of claims 17 to 19, further comprising

sending a message by the gateway controlling device to the controlled device requesting to send media encoded according to one or several of media predefined channel types defined by media oriented negotiation acceleration.

21. The method according to claim 17 or 18, further comprising

sending a message by the gateway controlling device to the controlled device requesting to be notified about the receipt of signalling preconfigured channel packet data units.

22. The method according to any one of claims 17, 18, and 21, further comprising

sending a message by the gateway controlling device to the controlled device providing a signalling preconfigured channel packet data unit and requesting that this packet data unit is forwarded repeatedly.

23. The method according to claim 17 or 18, further comprising

sending a message to the controlled device requesting to be notified about the receipt of H.323 multiplex level stuffing flags.

24. A method comprising

receiving a message from a gateway controlling device by a media gateway device requesting that a media oriented negotiation acceleration preferences negotiation is started and including media oriented negotiation acceleration preferences to be advertised;

repeatedly sending media oriented negotiation acceleration preference messages by the media gateway device; and

incrementing acknowledgment bits of sent media oriented negotiation acceleration preference messages by the media gateway device when receiving incoming media oriented negotiation acceleration preference messages.

25. The method according to claim 24, further comprising

using an internet multimedia subsystem media gateway functionality by the media gateway device.

26. The method according to claim 24 or claim 25, further comprising

notifying the gateway controlling device by the media gateway device when receiving the first incoming media oriented negotiation acceleration preference message; and

forwarding the received information by the media gateway device, wherein

the gateway controlling device is not notified about subsequent incoming media oriented negotiation acceleration preference message.

27. The method according to any one of claims 24 to 26, further comprising

receiving a first media preconfigured channel packet data unit of a given predefined channel type by the media gateway device; and

notifying the gateway controlling device by the media gateway device about the received channel type.

28. The method according to any one of claims 24 to 27, further comprising

receiving media streams by the media gateway device that require interworking towards a corresponding H.324 session; and

sending these media streams by the media gateway device in media preconfigured channel packet data units of a predefined channel type requested by the gateway controlling device by media oriented negotiation acceleration preference messages, and transcoding the media by the media gateway device if required.

29. The method according to any one of claims 24 to 26, further comprising

receiving a first signalling preconfigured channel packet data unit by the media gateway device; and

forwarding the signalling preconfigured channel packet data unit by the media gateway device to the controlling device.

30. The method according to any one of claims 24 to 26 and 29, further comprising

comparing by the media gateway device any subsequently received signalling preconfigured channel packet data units with the previously received signalling preconfigured channel packet data unit; and

forwarding the subsequently received signalling preconfigured channel packet data unit by the media gateway device to the gateway controlling device only, if it differs from the previously received signalling preconfigured channel packet data unit.

31. The method according to any one of claims 24 to 26, 29 and 30, further comprising

receiving a message by the media gateway device from the gateway controlling device providing a signalling preconfigured channel packet data unit; and

repeatedly forwarding this signalling preconfigured channel packet data unit by the media gateway device.


32. The method according to any one of claims 24 to 26, further comprising

notifying the gateway controlling device about the receipt of more than a preconfigured number of valid consecutive multiplex level stuffing flags.

33. A computer program product embodied on a computer-readable medium, the computer program product configured to provide instructions to carry out a method according to any

one of claims 17 to 32 when the program is run on a computer.

FIG 2



CS-Domain

IMS

Termination:

T1 CS-Domain (CS-Bearer (BS30) for H.245 control, Speech, Video)

T2 Multiplexing (H.245 control, Speech, Video)

T3 Video (own RTP-stream)+Speech (own RTP-stream)

Stream:

Stream1 (between T1 and T2) data (H.245 control, speech, Video)

Stream2 (terminated an T2) H.245 Control Information

Stream3 (between T2 and T3) Video

Stream4 (between T2 and T3) Speech

FIG 3A




FIG 3B





FIG 3C






FIG 5






FIG 6





INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2008/059599

A. CLASSIFICATION OF SUBJECT MATTER
INV. H04L29/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, INSPEC, COMPENDEX

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	NOKIA SIEMENS NETWORKS: "MONA Mn Procedures" C3-070764, [Online] 7 August 2007 (2007-08-07), pages 1-10, XP002467696 3GPP TSG-CT WG3 Meeting #45 Vienna, Austria Retrieved from the Internet: URL: http://www.3gpp.org/ftp/tsg_ct/WG3_int/erworking_ex-CN3/TSGC3_45_Vienna/Docs/C3-070764.zip [retrieved on 2008-02-05] the whole document ----- -/--	1-33

☒ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

19 December 2008

Date of mailing of the international search report

05/01/2009

Name and mailing address of the ISA/
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Mannekens, Jan

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2008/059599

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	ITU-T: "ITU-T Recommendation H.324 (2005) - Amendment 1: New Annex K "Media oriented negotiation acceleration procedure" and associated changes to Annex J" H.324 AMENDMENT 1, [Online] August 2006 (2006-08), pages 1-34, XP002467697 Retrieved from the Internet: URL: <a href="http://mirror.itu.int/dms/pay/itu-t/re
c/h/T-REC-H.324-200608-I Amd1 PDF-E.pdf">http://mirror.itu.int/dms/pay/itu-t/re c/h/T-REC-H.324-200608-I Amd1 PDF-E.pdf [retrieved on 2008-02-05] the whole document -----	1-33
A	ITU-T: "Terminal for low bit-rate multimedia communication; H.324 (2005) Amendment 1 (08/06)" ITU-T STANDARD IN FORCE (I), INTERNATIONAL TELECOMMUNICATION UNION, GENEVA,, CH, 22 August 2006 (2006-08-22), XP017404830 the whole document -----	1-33