

**(12) STANDARD PATENT**  
**(19) AUSTRALIAN PATENT OFFICE**

(11) Application No. **AU 2015308928 B2**

(54) Title  
**Compression garment inflation**

(51) International Patent Classification(s)  
**A61H 9/00** (2006.01)

(21) Application No: **2015308928**

(22) Date of Filing: **2015.08.27**

(87) WIPO No: **WO16/033264**

(30) Priority Data

(31) Number  
**62/042,317**

(32) Date  
**2014.08.27**

(33) Country  
**US**

(43) Publication Date: **2016.03.03**

(44) Accepted Journal Date: **2019.03.14**

(71) Applicant(s)  
**Covidien LP**

(72) Inventor(s)  
**Denson, Jesse;Wudkya, Scott**

(74) Agent / Attorney  
**Griffith Hack, GPO Box 1285, Melbourne, VIC, 3001, AU**

(56) Related Art  
**US 2014/0094725 A1**




- (51) International Patent Classification:  
A61H 9/00 (2006.01)
- (21) International Application Number:  
PCT/US2015/047070
- (22) International Filing Date:  
27 August 2015 (27.08.2015)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
62/042,317 27 August 2014 (27.08.2014) US
- (71) Applicant: COVIDIEN LP [US/US]; 15 Hampshire St.,  
Mansfield, Massachusetts 02048 (US).
- (72) Inventors: DENSON, Jesse; 47 Carriage Drive, Lincoln,  
Rhode Island 02865 (US). WUDKYA, Scott; 57 Kelleher  
Street, Marlborough, Massachusetts 01752 (US).
- (74) Agent: MELLO, John Paul; Covidien LP, 15 Hampshire  
St., Mansfield, Massachusetts 02048 (US).

- (81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,  
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,  
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,  
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,  
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,  
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,  
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,  
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,  
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,  
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,  
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,  
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,  
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: COMPRESSION GARMENT INFLATION



(57) Abstract: A compression device controller for use with a compression garment includes a pressurized fluid source (e.g., a pump), a manifold in fluid communication with the pressurized fluid source, a pressure sensor in communication with the manifold, at least two bladder ports, and at least two two-way valves. The pressure sensor is arranged to measure a signal representative of pressure in the manifold. Each bladder port is connectable in fluid communication to a respective inflatable bladder of the compression garment. Each two-way valve is in fluid communication with the manifold and with a respective bladder port. Each two-way valve is actuatable to control fluid communication between the manifold and the respective bladder port.

WO 2016/033264 A1

**Published:**

— with international search report (Art. 21(3))

## COMPRESSION GARMENT INFLATION

## BACKGROUND

**[0001]** Vascular compression systems include a compression garment fluidly connected to a fluid source, for cyclically inflating the compression garment when it is worn on a limb of a patient. The cyclical inflation of the compression garment enhances blood circulation and decreases the likelihood of deep vein thrombosis (DVT). A controller controls operation of the fluid source to deliver fluid to bladders of the compression garment to produce bladder pressure gradient along the compression garment, which moves blood in a desired direction. The manner in which the compression garment is applied to the wearer's limb, the size and shape of the wearer's limb, and the wearer's activity during use of the compression garment can affect the gradient of the bladder pressure that is actually applied to the limb, potentially creating a disparity between a target gradient bladder pressure and the actual gradient bladder pressure applied to the limb.

## SUMMARY

**[0002]** The present disclosure is directed to systems and methods that provide robust application of a target therapeutic pressure gradient by a compression garment to a limb of a patient under a variety of conditions associated with, among other things, the manner in which the compression garment is applied to the wearer's limb, the size and shape of the wearer's limb, and the wearer's activity during use of the compression garment.

**[0003]** Accordingly, the present invention provides a compression device controller for use with a compression garment including inflatable bladders, the compression device controller comprising:

- a pressurized fluid source;
- a manifold in fluid communication with the pressurized fluid source, without a check valve between the pressurized fluid source and the manifold;
- a pressure sensor in communication with the manifold, the pressure sensor arranged to measure pressure in the manifold;

at least two bladder ports, each bladder port connectable in fluid communication to a respective inflatable bladder of the compression garment; and

at least two two-way valves, each two-way being valve in fluid communication with the manifold and with a respective bladder port, and each two-way valve actuatable to control the fluid communication between the manifold and the respective bladder port; and

one or more processors and a non-transitory, computer-readable storage medium having computer executable instructions for causing the one or more processors to:

direct fluid from the pressurized fluid source to the at least two two-way valves;

actuate the at least two two-way valves in sequence such that only one inflatable bladder at a time is in fluid communication with the manifold when each respective bladder port is in fluid communication with the respective inflatable bladder of the compression garment;

receive, from the pressure sensor, a respective pressure signal indicative of the pressure in the manifold while each respective bladder port is in fluid communication with the manifold and while pressurized fluid is being directed to the at least two two-way valves, each respective bladder port being placed in the fluid communication with the manifold one at a time;

compare each received pressure signal to another pressure; and

based at least in part on the comparison of the received pressure signals, adjust one or more of the pressurized fluid source and the at least two two-way valves.

**[0004]** In one embodiment, a compression device controller for use with a compression garment includes a pressurized fluid source (e.g., a pump), a manifold in fluid communication with the pressurized fluid source, a pressure sensor in communication with the manifold, at least two bladder ports, and at least two two-way valves. The pressure sensor is arranged to measure a signal representative of pressure in the manifold. Each bladder port is connectable in fluid communication to a respective inflatable bladder of the compression garment. Each two-way valve is in fluid communication with the manifold and with a respective bladder port. Each two-way valve is actuatable to control fluid communication between the manifold and the respective bladder port.

**[0005]** In some embodiments, the compression device controller includes a vent port and a vent valve. The vent valve is in fluid communication with the manifold and with the vent

port. The vent port is in fluid communication with atmosphere. The vent valve is actuatable to control fluid communication between the manifold and the vent port.

**[0006]** In certain embodiments, each of the two-way valves is a normally open valve.

**[0007]** In some embodiments, the compression device controller includes one or more processors and a non-transitory, computer-readable storage medium having computer executable instructions. The computer executable instructions include instructions for causing the one or more processors to direct fluid from the pressurized fluid source to the at least two two-way valves, actuate the at least two valves in sequence such that only one bladder at a time is in fluid communication with the manifold when each bladder port is in fluid communication with a respective bladder of the compression garment, receive a respective pressure signal from the pressure sensor indicative of pressure in the manifold while each respective bladder port is in fluid communication with the manifold, compare each received pressure signal to another pressure (e.g., another one of the received pressure signals and/or to a predetermined value), and, based at least in part on the comparison of the received pressure signals, adjust one or more of the pressurized fluid source and the at least two two-way valves.

**[0008]** In certain embodiments, the instructions to compare pressure signals include instructions to determine a pressure gradient.

**[0009]** In some embodiments, the instructions for causing the one or more processors to adjust at least one of the pressurized fluid source and the at least two two-way valves includes instructions to control at least one of the pressurized fluid source and the at least two two-way valves to match the determined pressure gradient to a predetermined pressure gradient.

**[0010]** In certain embodiments, the computer executable instructions further include instructions for causing the one or more processors to direct fluid from the pressurized fluid source to the at least two two-way valves and actuate the at least two valves to inflate the inflatable bladders one at a time and one after another when the inflatable bladders are in fluid communication the respective bladder ports.

**[0011]** In some embodiments, the instructions for causing the one or more processors to compare the received pressure signals includes determining, based at least in part on the received pressure signals, respective linear slopes of the pressure in each respective inflatable bladder in fluid communication with the respective bladder port.

**[0012]** In certain embodiments, the instructions to compare the received pressure signals include instructions to determine, based on the linear slope and time remaining to an end of inflation of an inflatable bladder in fluid communication with a respective bladder port, that the inflation pressure at the end of the inflation of the respective inflatable bladder will exceed an inflation pressure of a previously inflated inflatable bladder in fluid communication with another bladder port.

**[0013]** In some embodiments, there are three two-way valves.

**[0014]** In another aspect, a compression system includes a compression device controller including any of the features above, and a compression garment including two or more inflatable bladders (e.g., three inflatable bladders).

**[0015]** In another aspect, a computer implemented method of controlling inflation of a compression garment includes directing fluid from a pressurized fluid source to a manifold in fluid communication with at least two two-way valves, each two-way valve is in fluid communication with a respective inflatable bladder of a compression garment, actuating the at least two two-way valves in sequence such that only one bladder at a time is in fluid communication with the manifold, receiving a respective pressure signal from a pressure sensor in communication with the manifold indicative of pressure in the manifold while each respective bladder port is in fluid communication with the manifold, comparing the received pressure signals to at least one of (i) one another and (ii) a predetermined value, and, based at least in part on the comparison of the received pressure signals to one another and/or to a predetermined value, adjusting at least one of the directed flow of fluid from the pressurized fluid source and the actuation of the at least two two-way valves.

**[0016]** In certain embodiments, comparing the received pressure signals includes determining a pressure gradient.

**[0017]** In some embodiments, adjusting the directed flow of fluid includes controlling one or more of the pressurized fluid pump and the at least two two-way valves to match the determined pressure gradient to a predetermined pressure gradient.

**[0018]** In another aspect, a system includes means for controlling a fluid flow source and valves to inflate inflatable bladders of the compression garment, means for controlling the valves in sequence between at least first and second configurations, means for receiving pressure signals from a pressure sensor while the valves are in the first configuration and in the second

configuration, and means for comparing the pressure signal from the first configuration with the pressure signal from the second configuration. In the first configuration one of the valves is open in fluid communication with a respective one of the inflatable bladders and the pressure sensor while the at least one other valve and any other valves are closed. In the second configuration the at least one other valve is open in fluid communication with the pressure sensor and another respective one of the inflatable bladders while the one valve and the any other valves are closed.

**[0019]** In certain aspects, the means for comparing pressure signals from the first and second configurations includes means for determining a pressure gradient.

**[0020]** Embodiments can include one or more of the following advantages.

**[0021]** In some embodiments, end-of-cycle pressure in each bladder is measured separately and independently from the other bladder(s). As compared to pneumatic circuits that do not permit measurement of end-of-cycle pressure in each bladder, such measurement of end-of-cycle pressure in each bladder facilitates active control of pressure gradient among multiple bladders of a compression garment. Such active control of pressure gradient among multiple bladders of a compression garment can, for example, facilitate detection of undesirable pressure gradients and/or maintenance of a desired gradient (e.g., a gradient corresponding to a target therapeutic pressure gradient).

**[0022]** In some embodiments, an entire fluid output from a fluid source is directed to filling a single one of a plurality of bladders of a compression garment. As compared to configurations that do not allow for isolation of a single bladder during filling, such direction of fluid to a single bladder can increase the efficient use of fluid from the fluid source, which can, for example, reduce the overall size of the fluid source required to achieve a therapeutic compression pressure gradient.

**[0023]** In some embodiments, the compression system includes a pneumatic circuit that can pneumatically isolate each bladder of a plurality of inflatable bladders such that a single pressure sensor can sense the pressure in each bladder of the plurality of inflatable bladders. As compared to other pneumatic configurations that require the use of multiple pressure sensors to sense the pressure in each bladder, the use of a single pressure sensor can facilitate a reduction in parts, which has an associated cost savings and, additionally or alternatively, facilitates more

robust measurement. For example, the use of a single pressure sensor can eliminate or reduce the need to account for differences in calibration between multiple pressure sensors.

**[0024]** In some embodiments, the compression system achieves specific pressure profiles and pressure gradients independent of garment size, garment wrap configuration, and/or activity of the wearer of the garment. For example, the compression system can adjust to achieve a prescribed therapeutic pressure profile and pressure gradient even as the position of the wearer changes and/or as the garment wrap configuration changes over time.

**[0025]** In some embodiments, no check valve is required to inhibit back flow to a pump.

**[0026]** Other aspects, features, and advantages will be apparent from the description and drawings, and from the claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0027]** FIG. 1 is a perspective view of a compression system including a compression garment and a controller.

**[0028]** FIG. 2 is a schematic representation of the compression system of FIG. 1, including a schematic representation of a pneumatic circuit.

**[0029]** FIG. 3 is a graphical illustration of a pressure profile produced by the compression system of FIG. 1 during a compression cycle, with the shown pressure profile for each bladder acquired using a test configuration in which separate pressure sensors are associated with each respective bladder.

**[0030]** FIG. 4 is the graphical illustration of a pressure profile of FIG. 3 overlaid with a pressure reading produced by a single pressure sensor of the compression system of FIG. 1.

**[0031]** FIG. 5 is an enlarged portion of a section of the graphical illustration of FIG. 4.

**[0032]** Corresponding reference characters indicate corresponding parts throughout the drawings.

#### DETAILED DESCRIPTION

**[0033]** As used herein, the terms "proximal" and "distal" represent relative locations of components, parts and the like of a compression garment when the garment is worn. For example, a "proximal" component is disposed most adjacent to the wearer's torso, a "distal"

component is disposed most distant from the wearer's torso, and an "intermediate" component is disposed generally anywhere between the proximal and distal components.

**[0034]** Referring to Figs. 1 and 2, a compression system 1 includes a compression garment 10 for applying sequential compression therapy to a limb of a wearer and a controller 5 having one or more processors 7 and computer executable instructions embodied on a non-transitory, computer readable storage medium 33, the computer executable instructions including instructions for causing the one or more processors to control operation of the compression garment 10. The compression garment 10 includes a distal inflatable bladder 13a, an intermediate inflatable bladder 13b, and a proximal inflatable bladder 13c. The compression garment 10 is securable (e.g., using hook and loop fasteners) around the wearer's limb and can be adjustable to fit around limbs of different circumferences.

**[0035]** As described in further detail below, the controller 5 controls operation of the compression garment 10 to perform a compression cycle, in which the inflatable bladders 13a, 13b, 13c are inflated to apply pressure to the wearer's limb to establish a pressure gradient applied to the wearer's limb by the inflatable bladders 13a, 13b, 13c of the compression garment 10 during one or more compression cycles. For the purpose of describing exemplary operation of the compression system 1, each compression cycle includes inflation phases for all three bladders 13a, 13b, 13c and a decay phase for bladders 13a and 13b. A vent cycle follows the compression cycle, in which the pressure in each of the bladders 13a, 13b, 13c is released. Together the compression cycle and vent cycle form one complete therapeutic cycle of the compression system 1. As also explained below, the compression system 1 can measure the pressure gradient applied by the bladders 13a, 13b, 13c and can make adjustments based on this measured pressure gradient. As compared to compression systems that do not measure a pressure gradient and/or do not adjust a pressure gradient, the measurement and adjustment of the pressure gradient during operation of the compression system 1 can, for example, increase the likelihood that an appropriate pressure gradient is applied to a limb of a wearer. Additionally or alternatively, the measurement and adjustment of the pressure gradient during operation of the compression system 1 can decrease the likelihood of undesirable reverse pressure gradient that can result from variations associated with the position of the wearer's limb, the wearer's activity, and/or fit of the compression garment during therapeutic compression cycles.

**[0036]** The compression garment 10 is a thigh-length sleeve positionable around the leg of the wearer, with the distal bladder 13a positionable around the wearer's ankle, the intermediate bladder 13b positionable around the wearer's calf, and the proximal bladder 13c positionable around the wearer's thigh. The inflatable bladders 13a, 13b, 13c expand and contract under the influence of fluid (e.g., air or other fluids) delivered from a pressurized fluid source 21 (e.g., a pump) in electrical communication with the controller 5. The pressurized fluid source 21 can deliver pressurized fluid (e.g., air) to the inflatable bladders 13a, 13b, 13c through, for example, tubing 23.

**[0037]** Referring to Fig. 2, each inflatable bladder 13a, 13b, 13c is in fluid communication with a respective valve 25a, 25b, 25c. A pressure sensor 27 is in fluid communication with a manifold 29 to measure pressure in the manifold 29. Each valve 25a, 25b, 25c is in electrical communication with the controller 5, which controls fluid communication between the manifold 29 and the respective inflatable bladders 13a, 13b, 13c through control of the position of the respective valves 25a, 25b, 25c (e.g., through activation and/or deactivation of the respective valves 25a, 25b, 25c). The pressure sensor 27 is in electrical communication with the controller 5 to deliver signals indicative of the measured pressure of the manifold 29 which, depending on the positions of the respective valves 25a, 25b, 25c, can be indicative of the pressure in one or more of the inflatable bladders 13a, 13b, 13c in fluid communication with the manifold 29. The controller 5 can control the position of each valve 25a, 25b, 25c and, thus, inflation of each respective inflatable bladder 13a, 13b, 13c, based at least in part on the signal received from the pressure sensor 27.

**[0038]** If only one inflatable bladder 13a, 13b or 13c is in fluid communication with the manifold 29, the pressure measured by the pressure sensor 27 in the manifold 29 is representative of the pressure of the respective inflatable bladder 13a, 13b, 13c in fluid communication with the manifold 29. For example, the pressure sensor 27 measures pressure in the inflatable bladder 13a when the valve 25a is open and the valves 25b, 25c are closed. Similarly, pressure in the inflatable bladder 13b is measured by the pressure sensor 27 when the valve 25b is open and the valves 25a and 25c are closed. Likewise, the pressure in the inflatable bladder 13c is measured by the pressure sensor 27 when the valve 25c is open and the valves 25a and 25b are closed. The arrangement of the valves 25a, 25b, 25c to hold pressure in the individual inflatable bladders

13a, 13b, 13c facilitates operation of the entire compression system 1 without a check valve between the fluid pressure source 21 and the manifold 29.

**[0039]** A vent valve 25d is in fluid communication with ambient atmosphere and with the manifold 29, through a vent port 26d, to vent the compression system 1. Each inflatable bladder 13a, 13b, 13c can be vented using the same vent valve 25d.

**[0040]** Each of the valves 25a, 25b, 25c is a 2-way/2-position, normally open, solenoid valve and includes a respective inlet port 24a, 24b, 24c and a respective bladder port 26a, 26b, 26c. Each of the valves 25a, 25b, 25c is actuatable to place the respective inlet port 24a, 24b, 24c in fluid communication with the respective bladder port 26a, 26b, 26c in a first, open position. Each of the valves 25a, 25b, 25c is further actuatable to shut off fluid communication between the respective inlet port 24a, 24b, 24c and the respective bladder port 26a, 26b, 26c in a second, closed position. The inlet port 24a, 24b, 24c of each respective valve 25a, 25b, 25c is in fluid communication with the pressurized fluid source 21 and the manifold 29. The bladder port 26a, 26b, 26c of each respective valve 25a, 25b, 25c is in fluid communication with a respective inflatable bladder 13a, 13b, 13c. Any one of the inflatable bladders 13a, 13b, 13c can be placed in fluid communication with the pressurized fluid source 21 and the manifold 29 by the respective valve 25a, 25b, 25c.

**[0041]** The inflatable bladders 13a, 13b, 13c of the compression garment 10 can be individually inflated by opening the respective valve 25a, 25b, 25c and closing the other valves 25a, 25b, 25c so that only the respective one inflatable bladder 13a, 13b, 13c associated with the opened valve 25a, 25b, 25c is in fluid communication with the pressurized fluid source 21 and the manifold 29. It should be appreciated that the individual inflation of the inflatable bladders 13a, 13b, 13c facilitates the use of the pressure sensor 27 to measure a pressure in each of the inflatable bladders 13a, 13b, 13c individually without also reading a cumulative back pressure from other inflatable bladders due to multiple inflatable bladders being in fluid communication with the manifold 29.

**[0042]** Vent valve 25d is also a 2-way/2-position, normally open, solenoid valve including an inlet port 24d and a vent port 26d. The vent valve 25d is actuatable to place the inlet port 24d in fluid communication with the vent port 26d in a first position. The vent valve 25d is further actuatable to a second position to shut off fluid communication between the inlet port 24d and the vent port 26d of the vent valve 25d. The inlet port 24d of vent valve 25d is in fluid

communication with the pressurized fluid source 21 and the manifold 29. The vent port 26d of vent valve 25d is in fluid communication with ambient atmosphere.

**[0043]** The computer executable instructions embodied on the non-transitory, computer readable storage medium 33 include instructions to cause the one or more processors 7 to pressurize (e.g., inflate) the inflatable bladders 13a, 13b, 13c to provide cyclical therapeutic compression pressure to a wearer's limb. For example, the computer executable instructions embodied on the non-transitory, computer readable storage medium 33 can include instructions to cause the one or more processors 7 to control the pressurized fluid source 21 and/or the valves 25a, 25b, 25c, 25d to pressurize the inflatable bladders 13a, 13b, 13c to different therapeutic compression pressures for a predetermined amount of time to move blood from limb regions underlying the inflatable bladders 13a, 13b, 13c when the compression garment 10 is worn.

**[0044]** The inflation of the inflatable bladders 13a, 13b, 13c to the respective therapeutic compression pressure of each inflatable bladder 13a, 13b, 13c is referred to herein as an inflation phase. The length of time each inflatable bladder 13a, 13b is held at the respective therapeutic compression pressure is referred to herein as a decay phase of the respective inflatable bladder 13a, 13b. In a vent phase, the computer executable instructions include instructions to cause the one or more processors 7 to control the pressurized fluid source 21 and/or the valves 25a, 25b, 25c, 25d to reduce the pressure in the inflatable bladders 13a, 13b, 13c to a lower pressure (e.g., to atmospheric pressure). As described in further detail below, a therapeutic compression cycle of the compression garment 10 includes an inflation phase of each inflatable bladder 13a, 13b, 13c, a decay phase of the inflatable bladders 13a, 13b, and a vent phase of each inflatable bladder 13a, 13b, 13c.

**[0045]** As used herein, "end-of-cycle pressure" refers to the pressure in an inflatable bladder prior to the vent phase of the respective inflatable bladder 13a, 13b, 13c. Thus, for the inflatable bladders 13a, 13b, the end-of-cycle pressure corresponds to the pressure in the respective inflatable bladder 13a, 13b at the end of the decay phase of the respective inflatable bladder 13a, 13b. For the inflatable bladder 13c, the end-of-cycle pressure corresponds to the pressure in the inflatable bladder 13c at the end of the inflation phase of the inflatable bladder 13c.

**[0046]** Referring now to FIG. 3, a pressure profile for the compression system 1 is shown for a single therapeutic compression cycle of the compression garment 10. A pressure plot P1

shows measured pressure of the distal inflatable bladder 13a throughout the single therapeutic compression cycle, a pressure plot P2 shows a measured pressure of the intermediate inflatable bladder 13b throughout the therapeutic compression cycle, and a pressure plot P3 shows a measured pressure of the proximal inflatable bladder 13c throughout the therapeutic compression cycle. The pressure data for pressure plots P1, P2, and P3 were acquired using a test configuration in which separate pressure sensors were associated with each respective inflatable bladder 13a, 13b, 13c. Each pressure plot P1, P2, P3 includes an initial inflatable bladder fill period which defines the inflation phase of the therapeutic compression cycle for the inflatable bladder 13a, 13b, 13c. Once a target pressure is achieved, inflation is stopped and the pressure in the inflatable bladders 13a, 13b is held at or near the target pressure for a period of time defining the decay phase. After the decay phase associated with the inflatable bladders 13a, 13b and immediately after the inflation phase of the inflatable bladder 13c, fluid in each inflatable bladder 13a, 13b, 13c is evacuated from the respective inflatable bladder 13a, 13b, 13c for a period of time defining the vent phase.

[0047] At the beginning of the compression cycle, the valves 25b, 25c, and 25d are each energized to closed positions such that only the inflatable bladder 13a is in fluid communication with the pressurized fluid source 21. To inflate the distal inflatable bladder 13a, pressurized fluid from the pressurized fluid source 21 is delivered through the valve 25a, which remains open, and to the inflatable bladder 13a via the tubing 23. Once a target pressure for the distal inflatable bladder 13a is achieved, and/or after a period of time measured by a timer 31, after which the target pressure is expected to be achieved, the valve 25a is energized to close, holding the pressurized fluid in the distal inflatable bladder 13a. Next, the intermediate inflatable bladder 13b is inflated by de-energizing the valve 25b, allowing pressurized fluid from the pressurized fluid source 21 to flow into the intermediate inflatable bladder 13b. Once a target pressure for the intermediate inflatable bladder 13b is achieved, and/or after a period of time measured by the timer 31, after which the target pressure is expected to be achieved, the valve 25b is closed, holding the pressurized fluid in the intermediate inflatable bladder 13b. The proximal inflatable bladder 13c is then inflated by de-energizing valve 25c, allowing pressurized fluid from the pressurized fluid source 21 to flow into the proximal inflatable bladder 13c. Once a target pressure for the proximal inflatable bladder 13c is achieved, and/or after a period of time measured by the timer 31 after which the target pressure is expected to be achieved, the valves

25a, 25b, and 25d are additionally de-energized, resulting in opening all of the valves 25a, 25b, 25c, and 25d. The vent valve 25d is opened to allow for the fluid in each of the inflatable bladders 13a, 13b, 13c to vent to atmosphere.

**[0048]** As compared to pneumatic circuit configurations in which multiple inflatable bladders are inflated at the same time, the compression system 1 can individually inflate the inflatable bladders 13a, 13b, 13c such that only one inflatable bladder is being filled with pressurized fluid at a time, which can facilitate the use of a smaller pump to achieve the same therapeutic compression cycle. It should be appreciated, however, that the inflatable bladders 13a, 13b, 13c can be additionally or alternatively inflated such that the inflation phases of one or more of the inflatable bladders 13a, 13b, 13c overlap.

**[0049]** Referring to FIGS. 4 and 5, a signal received from the pressure sensor 27 during the therapeutic compression cycle shown in FIG. 3 is represented as a pressure plot P0 and is overlaid on the pressure plots P1, P2, P3 of FIG. 3. The computer executable instructions embodied on the non-transitory, computer readable storage medium 33 include instructions to cause the one or more processors 7 to receive a signal indicative of the pressure measured by the pressure sensor 27 in the manifold 29 throughout the therapeutic compression cycle.

**[0050]** As the distal inflatable bladder 13a is inflated, the pressure sensor 27 measures the pressure in the manifold 29, which correlates to the pressure in the distal inflatable bladder 13a. This correlation is represented, for example, by the similarity between the pressure plot P0 and the pressure plot P1 at the end of the inflation phase of the distal inflatable bladder 13a.

**[0051]** As the intermediate inflatable bladder 13b is inflated, the pressure sensor 27 measures the pressure in the manifold 29, which correlates to the pressure in the intermediate inflatable bladder 13b. This correlation is represented, for example, by the similarity between the pressure plot P0 and the pressure plot P2 at the end of the inflation phase of the intermediate inflatable bladder 13b.

**[0052]** As the proximal bladder 13c is inflated, the pressure sensor 27 measures the pressure in the manifold 29, which correlates to the pressure in the proximal inflatable bladder 13c. This correlation is represented, for example, by the similarity between the pressure plot P0 and the pressure plot P3 at the end of the inflation phase of the proximal inflatable bladder 13c.

**[0053]** Referring to FIGS. 4 and 5, the signals received by the one or more processors 7 from the pressure sensor 27 can provide an indication of the pressure in each inflatable bladder

13a, 13b, 13c at the end of the compression cycle. For example, the valves 25a, 25b, 25c can be sequentially toggled open and closed after the proximal inflatable bladder 13c is inflated to its target pressure to measure an end-of-cycle pressure in each of the inflatable bladders 13a, 13b, 13c. In this example, because the valve 25c is open from having inflated the proximal inflatable bladder 13c, the end-of-cycle pressure for the proximal inflatable bladder 13c is measured first. As will be understood from the pressure profile in FIGS. 4 and 5, the end of inflation pressure and the end of cycle pressure for the proximal inflatable bladder 13c are the same because the proximal inflatable bladder 13c does not undergo a decay phase. The valve 25c can be open and closed (e.g., by toggling the valve 25c off and then on) at the end of the inflation phase of the proximal inflatable bladder 13c. The valve 25a can be toggled open and the valve 25c can be closed to measure an end of cycle pressure for the distal inflatable bladder 13a. The valve 25b can be toggled open and valve 25a closed to measure an end-of-cycle pressure for the intermediate inflatable bladder 13b. While one sequence of toggling the valves 25a, 25b, 25c has been described, it should be appreciated that the computer executable instructions can include additionally or alternatively instructions to cause the one or more processors 7 to toggle the valves 25a, 25b, 25c in a different sequence.

**[0054]** In some embodiments, each valve 25a, 25b, 25c is toggled open for an amount of time necessary for the pneumatic circuit to reach an equilibrium condition to measure the end-of-cycle pressure in the respective inflatable bladder 13a, 13b, 13c. For example, each of the valves 25a, 25b, 25c can be toggled open for less than about 150 ms (e.g., about 75 ms). It should be appreciated that, in general, such short toggling times can facilitate measurement of pressure in each inflatable bladder 13a, 13b, 13c with an insignificant impact on the therapeutic compression cycle. The signals received from the pressure sensor 27 and indicative of the pressure in each inflatable bladder 13a, 13b, 13c are stored in the non-transitory, computer readable storage medium 33.

**[0055]** The computer executable instructions stored on the non-transitory, computer readable storage medium 33 include instructions to cause the one or more processors 7 to determine the pressure gradient of the compression system 1 at the end of the therapeutic compression cycle. The computer executable instructions include instructions for causing the one or more processors 7 to compare the received pressure signals for each of the inflatable bladders 13a, 13b, 13c to one another to determine whether the pressure gradient at the end of

the therapeutic compression cycle matches a desired or predetermined pressure gradient for the compression system 1. For example, in one predetermined pressure gradient of the inflatable bladders 13a, 13b, 13c relative to one another, the inflatable bladder 13a for the ankle should be at the highest pressure, the inflatable bladder 13b for the calf should be the next highest pressure, and the inflatable bladder 13c for the thigh should be the lowest pressure at the end of the therapeutic compression cycle.

**[0056]** In some embodiments, the computer executable instructions include instructions to cause the one or more processors 7, based at least in part on a predetermined deviation (e.g., a percent deviation) of the received pressure signals from a target pressure gradient, to adjust the pressurized fluid source 21 (e.g., the speed of a pump) and/or the timing of one or more of the valves 25a, 25b, 25c in a subsequent compression cycle to match more nearly the target pressure gradient.

**[0057]** Additionally or alternatively, the end-of-inflation-phase pressure and the end-of-decay-phase pressure of the inflatable bladder 13a can be used as a linear representation of the decay phase of the inflatable bladder 13a. In a subsequent compression cycle, the values of this representative line of pressure as a function of time can be compared to the end-of-inflation-phase pressure of one or more of the subsequently inflated inflatable bladders 13b, 13c to estimate whether the pressure of the subsequently inflated inflatable bladder 13b and/or 13c likely rose above the pressure of the previously inflated inflatable bladder 13a at any point during the subsequent compression cycle. It should be appreciated that an analogous linear representation of the decay phase of the inflatable bladder 13b can be compared to the end-of-inflation-phase pressure of the subsequently inflated inflatable bladder 13c to estimate whether the pressure of the subsequently inflated inflatable bladder 13c likely rose above the pressure of the previously inflated inflatable bladder 13b at any point during the subsequent compression.

**[0058]** If the end of inflation pressure of one of the inflatable bladders 13b, 13c is higher than any pressure taken from the representation of the pressure decay for another of the inflatable bladders 13a, 13b during a previous compression cycle, the computer executable instructions include instructions for causing the one or more processors 7 to adjust the inflation of one of the inflatable bladders 13a, 13b, 13c to restore the desired or predetermined pressure gradient. For example, adjusting the inflation of one of the inflatable bladders 13a, 13b, 13c can include

increasing the inflation time and/or rate of one of the inflatable bladders 13a, 13b, and/or decreasing the inflation time and/or rate of one of the inflatable bladders 13b, 13c.

**[0059]** Additionally or alternatively, the computer executable instructions can include instructions for causing the one or more processors 7 to halt the compression cycle if the end of inflation pressure of one of the inflatable bladders 13b, 13c is higher than any corresponding pressure along representative pressure decay line for the respective inflatable bladder 13a, 13b during a previous compression cycle.

**[0060]** The rate of inflation of at least one of the inflatable bladders 13a, 13b, 13c during the inflation phase can be measured using at least two pressure measurements taken during the inflation of each inflatable bladder 13a, 13b, 13c. Using the two pressure measurements to determine a slope of the inflation of the inflatable bladder 13a, 13b, 13c, a linear representation of the inflation of the respective inflatable bladder 13a, 13b, 13c can be generated. The linear representation can be used along with the known time to end of the inflation to predict the end of inflation pressure for the inflatable bladder 13a, 13b, 13c.

**[0061]** If the predicted end of inflation pressure of one of the inflatable bladders 13b, 13c is higher than the end-of-cycle pressure of a previously inflated inflatable bladder 13a, 13b (and/or higher than a set point by more than a predetermined amount), the computer executable instruction include instructions for causing the one or more processors 7 to adjust the inflation of one of the inflatable bladders 13a, 13b, 13c during the current inflation phase. This adjustment can increase the likelihood that the desired or predetermined pressure gradient is achieved during the present compression cycle. Adjusting the inflation of one or more of the inflatable bladders 13a, 13b, 13c can include increasing the inflation time and/or inflation rate of one of the inflatable bladders 13a, 13b and/or decreasing the inflation time and/or the inflation rate of one of the inflatable bladders 13b, 13c. In some embodiments, the computer executable instructions include instructions for causing the one or more processors 7 to halt the therapeutic compression cycle if the end-of-cycle pressure of one of the inflatable bladders 13b, 13c is higher than the end-of-cycle pressure of one or more of the a previously inflated inflatable bladders 13a, 13b.

**[0062]** If the end of inflation pressure of one of the inflatable bladders 13b, 13c is higher than the end of inflation pressure of a previously inflated inflatable bladder 13a, 13b, the computer executable instruction include instructions for causing the one or more processors 7 to adjust the inflation of one of the inflatable bladders 13a, 13b, 13c to restore the desired or

predetermined pressure gradient of the bladders 13a, 13b, 13c. Adjusting the inflation of one of the inflatable bladders 13a, 13b, 13c can include increasing the inflation time (duration) and/or the inflation rate (volume/time) of one of the inflatable bladders 13a, 13b, and/or decreasing the inflation time and/or inflation rate of one of the inflatable bladders 13b, 13c. In some embodiments, the computer executable instructions include instructions for causing the one or more processors 7 to halt the compression cycle if the end of inflation pressure of one of the inflatable bladders 13b, 13c is higher than the end of inflation pressure of a previously inflated inflatable bladder 13a, 13b.

**[0063]** In some embodiments, the computer executable instructions include instructions to cause the one or more processors 7 to be responsive to a potential leak condition in the inflatable bladders 13a, 13b, 13c if the adjustment to obtain or restore the desired or predetermined pressure gradient requires one of the inflatable bladders 13a, 13b, 13c to be inflated to a pressure exceeding a threshold pressure. In certain embodiments, the computer executable instructions can include instructions to cause the one or more processors 7 to alert a user or clinician (e.g., through an audible and/or visual alarm) of a potential leak in one of the inflatable bladders 13a, 13b, 13c.

**[0064]** As shown in FIG. 4, the pressure measurement produced by the pressure sensor 27 is slightly higher than the actual pressure within the inflatable bladder 13a, 13b, 13c. For the purposes of using the signals received from the pressure sensor 27 to maintain a desired gradient in the inflatable bladders 13a, 13b, 13c, the difference in pressures is negligible with respect to maintaining a target pressure gradient of the inflatable bladders 13a, 13b, 13c within a range of pressures associated with therapeutic compression pressures (e.g., for prophylaxis of deep vein thrombosis). Additionally or alternatively, by briefly deactivating the fluid source 21, the pressure signal received from the pressure sensor 27 normalizes to the actual pressure in the respective bladder 13a, 13b, 13c in fluid communication with the manifold 29.

**[0065]** In some embodiments, the pressure gradient during the compression cycle of the therapeutic compression cycle decreases from the distal inflatable bladder 13a to the proximal inflatable bladder 13c. For example, the distal inflatable bladder 13a can be inflated to about 45 mmHg, the intermediate inflatable bladder 13b can be inflated to about 40 mmHg, and the proximal inflatable bladder 13c can be inflated to about 30 mmHg during the compression cycle. It should be appreciated that the operation of the controller 5 to adjust the compression gradient

of the inflatable bladders 13a, 13b, 13c can facilitate maintaining this compression gradient through variations associated with the position of the wearer's limb and/or fit of the compression garment 10. For example, the operation of the controller 5 to adjust the compression gradient of the inflatable bladders 13a, 13b, 13c can reduce the likelihood of the occurrence of a reverse gradient condition (e.g., a condition in which the pressure in the inflatable bladders 13a, 13b, 13c increases from the distal inflatable bladder 13a to the proximal inflatable bladder 13c), which works against the desired therapeutic effect of the compression garment 10.

**[0066]** For ease of description, methods of controlling inflation of a compression garment is described herein with respect to the compression system 1 shown in Figs. 1 and 2. It should be appreciated, however, that the methods of controlling inflation of a compression garment can be implemented using any of various different hardware and software configurations without departing from the scope of the present disclosure.

**[0067]** While certain embodiments have been described, other embodiments are additionally or alternatively possible.

**[0068]** While compression systems have been described as being used with thigh length compression sleeves, it should be understood that compression systems can additionally or alternatively be used with other types of compression garments. For example, the compression systems can be used with knee-length compression sleeves and/or with sleeves having a different number of bladders configured to be disposed over different areas of the wearer's body.

**[0069]** Embodiments can be implemented in digital electronic circuitry, or in computer hardware, firmware, software, or in combinations thereof. The controller of the compression system can be implemented in a computer program product tangibly embodied or stored in a machine-readable storage device for execution by a programmable processor; and method actions can be performed by a programmable processor executing a program of instructions to perform functions of the controller of the compression system by operating on input data and generating output. The controller of the compression system can be implemented in one or more computer programs that are executable on a programmable system including at least one programmable processor coupled to receive data and instructions from, and to transmit data and instructions to, a data storage system, at least one input device, and at least one output device. Each computer program can be implemented in a high-level procedural or object oriented

programming language, or in assembly or machine language if desired; and in any case, the language can be a compiled or interpreted language.

**[0070]** Suitable processors include, by way of example, both general and special purpose microprocessors. Generally, a processor will receive instructions and data from a read-only memory and/or a random access memory. Generally, a computer will include one or more mass storage devices for storing data files; such devices include magnetic disks, such as internal hard disks and removable disks; magneto-optical disks; and optical disks. Storage devices suitable for tangibly embodying computer program instructions and data include all forms of non-volatile memory, including by way of example semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD\_ROM disks. Any of the foregoing can be supplemented by, or incorporated in, ASICs (application-specific integrated circuits) or FPGAs (field programmable logic arrays).

**[0071]** A number of embodiments have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the disclosure. For example, while a controller with a single pressure sensor has been described, additional pressure sensors (e.g., one for each inflatable bladder) can also be used without departing from the scope of the present disclosure. Accordingly, other embodiments are within the scope of the following claims.

**[0072]** In the claims which follow and in the preceding description of the invention, except where the context requires otherwise due to express language or necessary implication, the word “comprise” or variations such as “comprises” or “comprising” is used in an inclusive sense, i.e. to specify the presence of the stated features but not to preclude the presence or addition of further features in various embodiments of the invention.

**[0073]** It is to be understood that, if any prior art publication is referred to herein, such reference does not constitute an admission that the publication forms a part of the common general knowledge in the art, in Australia or any other country.

WHAT IS CLAIMED IS:

1. A compression device controller for use with a compression garment including inflatable bladders, the compression device controller comprising:

a pressurized fluid source;

a manifold in fluid communication with the pressurized fluid source, without a check valve between the pressurized fluid source and the manifold;

a pressure sensor in communication with the manifold, the pressure sensor arranged to measure pressure in the manifold;

at least two bladder ports, each bladder port connectable in fluid communication to a respective inflatable bladder of the compression garment; and

at least two two-way valves, each two-way valve in fluid communication with the manifold and with a respective bladder port, and each two-way valve actuatable to control the fluid communication between the manifold and the respective bladder port; and

one or more processors and a non-transitory, computer-readable storage medium having computer executable instructions for causing the one or more processors to:

direct fluid from the pressurized fluid source to the at least two two-way valves;

actuate the at least two two-way valves in sequence such that only one inflatable bladder at a time is in fluid communication with the manifold when each respective bladder port is in fluid communication with the respective inflatable bladder of the compression garment;

receive, from the pressure sensor, a respective pressure signal indicative of the pressure in the manifold while each respective bladder port is in fluid communication with the manifold and while pressurized fluid is being directed to the at least two two-way valves, each respective bladder port being placed in the fluid communication with the manifold one at a time;

compare each received pressure signal to another pressure; and  
based at least in part on the comparison of the received pressure signals, adjust one or more of the pressurized fluid source and the at least two two-way valves.

2. The compression device controller of claim 1, further comprising a vent port and a vent valve, the vent valve being in fluid communication with the manifold and with the vent port, the vent port being in fluid communication with atmosphere, and the vent valve actuatable to control the fluid communication between the manifold and the vent port.

3. The compression device controller of claim 1 or 2, wherein each of the two-way valves is a normally open valve.

4. The compression device controller of claim 1, wherein the computer executable instructions for causing the one or more processors to compare each received pressure signal to said another pressure include instructions to compare each received pressure signal to one another.

5. The compression device controller of claim 1, wherein the computer executable instructions for causing the one or more processors to compare each received pressure signal to said another pressure include instructions to compare each received pressure signal to a predetermined value.

6. The compression device controller of claim 1, wherein the computer executable instructions further comprise instructions to determine a pressure gradient between the respective inflatable bladders based on the received respective pressure signal indicative of the pressure in the manifold while each respective bladder port is in the fluid communication with the manifold.

7. The compression device controller of claim 1, wherein the computer executable instructions for causing the one or more processors to adjust one or more of the pressurized fluid source and the at least two two-way valves includes instructions to control at least one of the pressurized fluid source and the at least two two-way valves to match the determined pressure gradient to a predetermined pressure gradient.

8. The compression device controller of claim 1, wherein the computer executable instructions further include instructions for causing the one or more processors to direct the fluid

from the pressurized fluid source to the at least two two-way valves and actuate the at least two two-way valves to inflate the inflatable bladders one at a time and one after another when the inflatable bladders are in the fluid communication with the respective bladder ports.

9. The compression device controller of claim 1, wherein the computer executable instructions for causing the one or more processors to compare each received pressure signal to said another pressure includes instructions for causing the one or more processors to determine, based at least in part on each received pressure signal, respective linear slopes of a pressure in each respective inflatable bladder in the fluid communication with the respective bladder port, the respective linear slopes being determined from a plurality of received pressure signals for each respective inflatable bladder.

10. The compression device controller of claim 9, wherein the computer executable instructions for causing the one or more processors to compare each received pressure signal to said another pressure include instructions to determine, based on the linear slope and time remaining to an end of inflation of the respective inflatable bladder in the fluid communication with the respective bladder port, that an inflation pressure at the end of the inflation of the respective inflatable bladder will exceed an inflation pressure of a previously inflated inflatable bladder in fluid communication with its respective bladder port.

11. The compression device controller of claim 1, further comprising at least three bladder ports and at least three two-way valves, wherein the at least three two-way valves are respectively dedicated to the at least three bladder ports.




FIG. 1

FIG. 2




FIG. 3




FIG. 4




FIG. 5

