




(22) Date de dépôt/Filing Date: 2010/06/30
 (41) Mise à la disp. pub./Open to Public Insp.: 2010/12/30
 (45) Date de délivrance/Issue Date: 2013/04/30
 (30) Priorité/Priority: 2009/06/30 (US12/495,134)

(51) Cl.Int./Int.Cl. *F04B 49/025* (2006.01),
F04B 49/04 (2006.01), *F04D 13/08* (2006.01),
F04D 15/00 (2006.01), *F17C 13/02* (2006.01),
G05D 9/12 (2006.01), *H01H 36/02* (2006.01),
H01H 35/18 (2006.01)
 (72) Inventeurs/Inventors:
 LIN, CHIH, US;
 WATKINS, WILLIAM J., US
 (73) Propriétaire/Owner:
 CRANE PUMPS & SYSTEMS, INC., US
 (74) Agent: DEETH WILLIAMS WALL LLP

(54) Titre : ENSEMBLE A CONTACT FLOTTANT POUR POMPE
 (54) Title: SWITCH AND FLOAT ASSEMBLY FOR A PUMP



(57) Abrégé/Abstract:

An assembly controls the liquid level in a vessel in which a submersible pump is disposed. The assembly has a switch housing and a float housing, arranged proximate to each other. A switch in the switch housing selectively energizes a motor associated with the

(57) **Abrégé(suite)/Abstract(continued):**

pump. When a float disposed in the float housing moves in response to a change in the liquid level of the vessel, the movement is coupled to the switch by a pair of magnets arranged in attractive relationship to each other. One of the magnets is in the switch housing and the other is in the float housing. The magnets interact by providing force fields that acts through a wall that separates the switch housing and the float housing. A lever on which the switch housing magnet is positioned tilts the magnets away from alignment as they approach each other, reducing the increase in attractive force therebetween.

ABSTRACT

An assembly controls the liquid level in a vessel in which a submersible pump is disposed. The assembly has a switch housing and a float housing, arranged proximate to each other. A switch in the switch housing selectively energizes a motor associated with the pump. When a float disposed in the float housing moves in response to a change in the liquid level of the vessel, the movement is coupled to the switch by a pair of magnets arranged in attractive relationship to each other. One of the magnets is in the switch housing and the other is in the float housing. The magnets interact by providing force fields that acts through a wall that separates the switch housing and the float housing. A lever on which the switch housing magnet is positioned tilts the magnets away from alignment as they approach each other, reducing the increase in attractive force therebetween.

SWITCH AND FLOAT ASSEMBLY FOR A PUMP

Technical Field

The disclosed embodiments relate to an assembly for integrating a power supply
5 and switch for a pump, especially a submersible pump, with a float device that reacts to
a liquid level, especially in a basin in which the submersible pump is situated.

Background of the Art

A submersible pump is typically deployed as a sump pump in a basin located in
10 a residence. In such an application, two important elements of the pump are the switch
that controls the supply of electrical power to the motor and the liquid level sensing
device, which is in communication with the switch, and which serves to cause the switch
to activate or deactivate the motor of the pump, depending upon the liquid level that it
senses in the basin.

15 Another feature of this type of submersible pump is the power supply cord, which
provides electrical power from a location remote from the basin to the pump motor,
which is enclosed in a moisture-resistant housing on or adjacent to the pump.

A number of patents are directed at isolating the motor and the switch from the
moisture inherently present in the basin, while allowing a reliable communication
20 between the level sensing device and the switch.

One such patent is US 6,461,114, invented by one of the present inventors. In
the device described there, the switch assembly is positioned inside the motor housing.
An opening in the motor housing is required to allow a lever associated with the level
sensing device to contact the switch, and a further opening is required to pass the
25 power cord into the motor housing.

In another patent, US 5,562,422, to Ganzon, the switch is housed in a switch
chamber that is separate from the motor housing and the liquid level sensing device
uses an attractive magnetic interaction between a lower actuator in an actuator
chamber and an upper actuator that is in the switch housing, the actuator chamber and
30 the switch housing being isolated from each other.

One aspect of the level sensing arrangements and switches that has remained consistent over time is the shorter life expectancy of these devices, relative to the pump and motor.

It is therefore an unmet advantage of the prior art to provide a modular switch and float arrangement that may be quickly and easily changed out in the event of failure.

Summary

This and other unmet advantages are provided by an assembly for controlling the level of a liquid in a vessel in which a submersible pump is disposed. The pump is powered by a motor that is housed in a motor housing and is energized by an external power source. The level control assembly comprises a switch housing and a float housing, arranged in close proximity to each other. A float is disposed in the float housing and moves within the float housing responsive to the liquid level in the vessel. A switch disposed in the switch housing selectively connects the motor to, and disconnects the motor from, the external power source. The operation of the switch is coupled to the level of the float. A first portion of this coupling is movably disposed in the switch housing and a second portion of the coupling is disposed in the float housing. The portions interact by providing a force field that attracts the respective portions through a wall that separates the switch housing from the float housing. A relative angular relationship between the portions changes as the portions move toward and away from each other.

In some embodiments, the assembly also comprises a cord assembly that passes power from the external power source to the interior of the switch housing in an environmentally-sealed manner. Further, in some embodiments, the cord assembly has a power cord, adapted at a first end for connection to the external power source and communicating power therefrom in two lead wires and one ground wire, a plug, arranged at a second end of the power cord, for sealing engagement with an opening of the switch housing, the plug having two receptacles for engaging the switch internal to

the switch housing, and quick connect tabs, for communicating electrical power passing through the switch to the motor.

In some embodiments, the switch is a snap-action switch.

5 In some embodiments, the cord assembly has an elastomeric saddle, provided on a face of the plug extending into the switch housing, for sealing the connection of the plug in the switch housing.

10 In some embodiments, part of the means that couples the switch to the float is a first magnet. The second magnet is in the float housing and attached to the float. A force field of the first magnet has an axis that is aligned with a vertical longitudinal axis of the float. The coupling means is also a second magnet. This second magnet is in the switch housing, and is arranged relative to the first magnet so that the force fields of the magnets attract rather than repel. The second magnet is associated with, and moves on, a lever that is configured to bear against and activate the switch as the magnets approach each other and to deactivate the switch as the magnets move apart.

15 In many of the embodiments, the means for changing the relative angular relationship of the force fields is provided by a path of limited arcuate rotation defined by the lever and the pivot point about which it moves. As a result, the second magnet has a force field that is tilted away from the force field axis of the first magnet as the respective magnets approach each other. In some of these embodiments, the means for changing the relative angular relationship further comprises a protrusion, positioned
20 in the path of the second magnet, to tilt the second magnet as the second magnet moves toward the first magnet, misaligning the respective force fields.

In many of the embodiments, liquid access to an interior of the float housing is provided by a plurality of access holes in a lower surface of the float housing.

25 In many of the embodiments, the assembly further comprises a means for biasing the switch against force imposed by the lever thereupon through the attractive force of the magnets.

Brief Description of the Drawings

A better understanding of the disclosed embodiments will be obtained from a reading of the following detailed description and the accompanying drawings wherein identical reference characters refer to identical parts and in which:

5 **FIGURE 1** is a perspective view of a first embodiment of the switch and float assembly;

FIGURE 2 is a side sectional view of the Fig.1 assembly;

FIGURE 3 is an isolated perspective view of a cord assembly of the Fig. 1 assembly;

10 **FIGURE 4** is an isolated perspective view of the Fig. 3 cord assembly, with a switch installed therein;

FIGURE 5 is an enlarged view of the switch housing of the Fig. 1 assembly, showing details of the movement of the lever;

15 **FIGURE 6** is a first side sectional view of a second embodiment of the switch and float assembly, with the float in a lowered position; and'

FIGURE 7 is a second side sectional view of the Fig. 6 embodiment, with the float in its raised position.

Detailed Description of a Preferred Embodiment

20 **FIGURES 1** and **2** show, in perspective and side sectional views, a first embodiment of an assembly **10** for controlling the level of a liquid in a vessel, such as a sump basin or a sewer basin, in which a submersible pump **300**, as is generally known in the prior art is disposed. The pump **300** has an electrical motor **310** housed in a motor housing **320**. Such a pump **300** will be energized by an external power source
 25 (not shown), but this aspect is well known and the power will typically be 120 or 240 volt alternating current. As will be known, the pump **300** maybe a centrifugal impeller pump when the service involves a sump basin, but will more commonly be a grinder pump when the service involves a sewage basin. The level control assembly **10** has several pieces, including a switch housing **30**, a float housing **50**, and a cord assembly **70** that

passes the power from the external power source to the interior of the switch housing in an environmentally-sealed manner.

The float housing **50** is arranged in close proximity to the switch housing **30**, and a float **52** is disposed in the float housing for linear movement in a vertical direction that is responsive to the liquid level in the vessel. Unlike some of the float assemblies that have been used in the prior art, it is desirable to enclose the float **52** in the float housing **50**. When the float **52** or, for that matter, a switch associated with the float, is exposed in the sump basin to the rippling of the liquid in the basin, multiple strikes of the switch contacts can occur. This tends to shorten the service life of the switch. This rippling can be caused, for example, by the flow of liquid from a footer pipe into the basin. In general, then, a particularly useful float housing **50** is effectively closed along its sides, with liquid access to the interior of the float housing provided by a plurality of access holes **54** in a lower surface of the float housing. To accommodate air inside the float housing **50**, it may also be useful to provide access holes at the upper end of the float housing.

The float **52** should be sized to slide easily upward and downward in the float housing **50**. The float **52** has a density that can be carefully determined to provide the correct reaction to an increased liquid level, which may include, in some instances, filling at least some of the float with water, or another dense material. Having an appropriate weight to the float **52** is important in the proper operation of the switching system, as there needs to be sufficient weight present to counteract the attractive force of the magnets used to couple the action of a switch in the switch housing **30** with the float.

The switch housing **30** is intended to provide a sealable internal environment that is distinct from either the motor housing **320**, a pump housing (if the pump housing is separate from the motor housing, although they can be the same) and the float housing **50**. Unlike the float housing **50**, which will be subjected to humidity, the switch housing **30** should be as dry as possible. Unlike the motor housing **320**, where oil mist from the motor will be commonplace, the switch housing **30** should be free of oil mist.

A switch **32** is disposed in the switch housing **30**. The switch **32** is positioned in an electrical circuit provided between the motor **310** and the external power source operative to selectively connect the motor to, and disconnect the motor from, the external power source, as required to maintain the liquid level. In the illustrated embodiment, the switch **32** is a snap-action switch. To the extent that there is a preference, the switch **32** is preferably a commercially-available snap action switch that is provided with a pivoted lever **34** that can be urged against a switch button **36** that is biased against the action of the lever. Certainly, the lever **34** may be provided if it is not an integral part of the switch **32**.

Attention is now directed to **FIGURES 3** and **4**, where details of the cord assembly **70** and the switch **32** are disclosed. Along a length of the assembly **70**, a power cord **72** communicates electrical power through two lead wires and one ground wire that run the length of the power cord. These leads and ground will usually be connected to a plug at a first end of the cord assembly **70**, the first end being adapted for connection to the external power source. Since the power source will usually be a 120 or 240 volt alternating current source, the first end will normally be a conventional electrical plug **74** for connection to such a source. At the second or opposite end of the power cord, a plug **76** will also be provided. This second plug **76** is intended to be sealingly engaged in an opening **38** of the switch housing **30**. A side of the plug **76** that is internal to the switch housing **30** when the power cord assembly **70** is received therein, that is, a side that is opposite the power cord **72**, is preferably provided with receptacles **77** to receive the plugs on the switch **32** that is selected for use. This allows quick and easy replacement of the switch **32** when necessary. The same side of the plug **76** is also preferably provided with quick connect tabs **78**, for communicating electrical power passing through the switch **32** to the motor **310**, while keeping the switch housing **30** and the motor housing **320** isolated from each other. It is also preferred to provide an elastomeric shield or saddle **80** on the face of this side of the plug **76**, for sealing the connection of the plug in the switch housing **30**. While Fig. 3 shows the cord assembly **70** without the switch **32** connected, Fig. 4 shows the

assembly with the switch in place. The plug **76** retains the body of the switch **32** during the actuation of the switch, allowing movement only of the lever **34**. Figure 4 also shows the lever **34** and the second magnet **42**, more details of which are provided below.

5 Referring to **FIGURE 2** and **FIGURE 5**, the coupling of the switch **32**, located in the switch housing **30**, with the float **52**, located in the float housing **50** is now described. The switch housing **30** and float housing **50** are to be maintained in isolation from each other, and the coupling is achieved through the interacting attractive magnetic force fields of a pair of magnets. The first magnet **54** is positioned in the float
 10 housing **50** and is attached to the top of the float **52**. It is preferred to position this magnet **54** so that the force field associated with it has an axis that is aligned with a vertical longitudinal axis of the float **52**. As the float **52** moves upwardly and downwardly within the float housing **50**, the strength of the magnetic field from this magnet **54** increases and decreases in the switch housing **30**, as a wall separating the
 15 switch housing and the float housing is selected from a material that readily allows the magnetic field to pass therethrough. In the illustrated embodiment, a portion **40** of the switch housing **30** extends into an upper portion of the float housing **50**, resulting in that portion being placed into the longitudinal axis of the float housing.

A second magnet **42** is positioned in the switch housing **30** and, particularly, is
 20 positioned in the portion **40**. The second magnet **42** is seated at an end of the lever **34** of the switch **32**. The polarities of the magnets **42**, **54** are set so that the magnets attract each other, rather than repel each other.

In this first embodiment **10**, the second magnet **42** moves in a path defined by a limited arc of rotation about a pivot point **39** where the lever **34** is attached to the switch
 25 **32**. Because of this rotational limit, the force field of the second magnet **42** has an axis that tilts with regard to the vertical, arriving at the vertical as the switch **32** is activated by the force of the lever **34** acting on the switch button **36**.

In Fig. 5, the lever **34** is shown at the limits of its range of motion. Depicted as lever **34a** at the top of the range, second magnet **42a** has its force field axis tilted

slightly to the vertical. As the attractive force of a rising first magnet **54** draws the second magnet downward, the lever **34b** and the second magnet **42b** are shown at the bottom of the range of motion.

As also seen in Fig. 5, when the second magnet **42** arrives at a point in its arc
5 where its force field approaches being co-axial with that of the first magnet **54**, a part of a means for changing the relative angular relationship of the force fields comes into play. In this embodiment, this means is represented by a tang **44** that protrudes into the path of the second magnet **42**. Contact with the second magnet **42** by the tang **44** tilts the second magnet in a seat in which it is positioned. Accordingly, this tilting
10 misaligns the force fields. The tilting results in a reduction in the rate of increase in the attractive force between the magnets that would result if the force fields remained aligned as the separation decreases. In turn, this decreases the difference in magnetic force between the point where the switch **32** is activated and where it is deactivated, allowing the size of the float **52** and its weight to be minimized. The known prior art
15 devices require a heavier float to break the attractive force between magnets with continually aligned force fields. As the lever **34** rises away from the lowered position when the float magnet **54** moves away, the second magnet **42** resumes its position in the seat as the tang **44** no longer tilts the second magnet.

Once the magnets move far enough apart that the switch **32** is turned off, the
20 arcuate tilt of the first magnet's force field decreases the attractive force even more rapidly than the inverse square of the distance rule that applies during axial alignment. Accordingly, the assembly provides a very clean action, with attenuated sensitivity as the magnets **42**, **54** are in near axial alignment.

Fortuitously, switch button **36** of the typical commercially-available snap action
25 switch **32** is already provided with a means that biases the switch button against the downward force imposed by the lever **34** through the attractive force of the magnets.

A further embodiment **110** of the assembly is presented in **FIGURES 6** and **7**. Because a large proportion of the structures are unchanged in Figs. 6 and 7, many structures that are substantially identical to those in the prior figures are identified with
30 the same reference numbers and are only discussed in relation to the changed

structures, which are identified with new reference numbers. In this embodiment, the first magnet **54** has substantially the same vertical motion as described with regard to the prior figures. However, and because of a variety of differences, including but not limited to the position of the switch **32** relative to the float housing **50**, the lever **134** limits the movement of the second magnet **142** to an arc of rotation about a pivot point **139** where the lever **134** is attached to the switch **32**. In this case, however, the top of the range, as seen in side sectional view in Fig. 6, has the second magnet **142** with its magnetic force field essentially aligned with that of the first magnet **54**. In this position, the float **52** is lowered and the pump is not activated, because the switch **32** is “off”, with switch button **36** in its raised position. As float **52** begins to rise from accumulating water in the basin, first magnet **54** rises with the float, increasing the attractive magnetic force in the switch housing. However, as the second magnet **142** moves toward first magnet **54** and the lever **134** bears on switch button **36**, the force field of the second magnet **142** is tilted away from the alignment and the tilting continues as long as the second magnet moves downward. At its lower limit, as shown in Fig. 7, the lever **134** contacts a top portion of the wall separating the float housing from the switch housing. In this position, the attraction of the magnets **142**, **54** to each other is decreased because of the tilt that has occurred, allowing the magnets to move easily separate upon a reduction of the liquid level in the vessel from the activation of the pump.

20

CLAIMS

What is claimed is:

1. An assembly for controlling the level of a liquid in a vessel in which a submersible pump is disposed, the pump powered by a motor housed in a motor housing thereof, the motor energized by an external power source, the level control assembly comprising:

a switch housing;

a float housing, arranged in close proximity to the switch housing;

a float, disposed in the float housing and operative to move therewithin responsive to the liquid level in the vessel;

a switch, disposed in the switch housing and operative to selectively connect the motor to, and disconnect the motor from, the external power source;

means for coupling the operation of the switch to the level of the float through interacting attractive magnetic force fields, the means comprising:

a first magnet, in the float housing and attached to the float, the magnetic force field thereof having an axis that is aligned with a vertical longitudinal axis of the float;

a second magnet, in the switch housing, the first and second magnets arranged such that the respective force fields are attractive, the second magnet arranged to activate the switch as the respective magnets approach each other and to deactivate the switch as the magnets move apart; and

means for changing a relative angular relationship of the force field between the respective magnets as the magnets move toward and away from each other, comprising a lever having a path of limited arcuate rotation, so the force field axis of the second magnet is tilted away from the force field axis of the first magnet as the respective magnets approach each other and the lever bears against, and activates, the switch as the magnets approach each other.

2. The assembly of claim 1, further comprising:
a cord assembly that passes power from the external power source to the interior of the switch housing in an environmentally-sealed manner.
3. The assembly of claim 2, wherein:
the cord assembly further comprises:
a power cord, adapted at a first end for connection to the external power source and communicating power therefrom in two lead wires and one ground wire;
a plug, arranged at a second end of the power cord, for sealing engagement with an opening of the switch housing, the plug having two receptacles for engaging the switch, inside the switch housing; and
quick connect tabs, for communicating electrical power passing through the switch to the motor.
4. The assembly of claim 3, wherein:
the switch is a snap-action switch.
5. The assembly of claim 3, further comprising:
an elastomeric saddle, provided on a face of the plug extending into the switch housing, for sealing the connection of the plug in the switch housing.
6. The assembly of claim 1, wherein:
the means for changing the relative angular relationship further comprises a protrusion, positioned in the path of limited arcuate rotation of the second magnet, to further tilt the second magnet as the second magnet moves toward the first magnet, misaligning the respective force fields.

7. The assembly of claim 1, further comprising:

means for biasing the switch against force imposed by the lever thereupon through the attractive force of the magnets.

8. An assembly for controlling the level of a liquid in a vessel in which a submersible pump is disposed, the pump powered by a motor housed in a motor housing thereof, the motor energized by an external power source, the level control assembly comprising:

a switch housing;

a float housing, arranged in close proximity to the switch housing;

a float, disposed in the float housing and operative to move therewithin responsive to the liquid level in the vessel;

a snap action switch, disposed in the switch housing and operative to selectively connect the motor to, and disconnect the motor from, the external power source;

a power cord, adapted at a first end for connection to the external power source and communicating power therefrom in two lead wires and one ground wire;

a plug, arranged at a second end of the power cord, for sealing engagement with an opening of the switch housing, the plug having two receptacles for engaging the snap action switch, inside the switch housing;

quick connect tabs, for communicating electrical power passing through the switch to the motor;

an elastomeric saddle, provided on a face of the plug extending into the switch housing, for sealing the connection of the plug in the switch housing;

a first magnet, in the float housing and attached to the float, a force field of the magnet having an axis that is aligned with a vertical longitudinal axis of the float;

a second magnet, in the switch housing and operatively co-acting with a lever of the switch, the first and second magnets arranged such that the force field therebetween is attractive; and

a lever on which the second magnet moves, defining a path of limited arcuate rotation, so a force field axis of the second magnet is tilted away from alignment with the

force field axis of the first magnet as the magnets approach each other, the approach of the magnets towards each other serving to activate the snap-action switch.

9. An assembly for controlling the level of a liquid in a vessel in which a submersible pump is disposed, the pump powered by a motor housed in a motor housing thereof, the motor energized by an external power source, the level control assembly comprising:

switch housing;

a float housing, arranged in close proximity to the switch housing;

a float, disposed in the float housing and operative to move therewithin responsive to the liquid level in the vessel;

a switch, disposed in the switch housing and operative to selectively connect the motor to, and disconnect the motor from, the external power source;

a lever, arranged in the switch housing to activate the switch when the lever moves from a first position to a second position;

a first magnet, in the float housing and attached to the float, the magnetic force field thereof having an axis that is aligned with a vertical longitudinal axis of the float; and

a second magnet, positioned on the lever, such that a magnetic force field of the second magnet is generally aligned in an attracting manner with the magnetic force field of the first magnet when the lever is in the first position and the respective magnetic force fields move away from alignment as the first and second magnets approach each other, moving the lever to the second position.

10. The assembly of claim 8, further comprising:

means for biasing the switch against force imposed by the lever thereupon through the attractive force of the magnets.

11. The assembly of claim 9, further comprising:

means for biasing the switch against force imposed by the lever thereupon through the attractive force of the magnets.

12. The assembly of claim 8, further comprising:

a protrusion, positioned in the path of limited arcuate rotation of the second magnet, to further tilt the second magnet as the second magnet moves toward the first magnet, misaligning the respective force fields.

13. The assembly of claim 9, further comprising:

a protrusion, positioned in the path of limited arcuate rotation of the second magnet, to further tilt the second magnet as the second magnet moves toward the first magnet, misaligning the respective force fields.

14. The assembly of claim 9, further comprising:

a cord assembly that passes power from the external power source to the interior of the switch housing in an environmentally-sealed manner.

15. The assembly of claim 14, wherein:

the cord assembly further comprises:

a power cord, adapted at a first end for connection to the external power source and communicating power therefrom in two lead wires and one ground wire;

a plug, arranged at a second end of the power cord, for sealing engagement with an opening of the switch housing, the plug having two receptacles for engaging the switch, inside the switch housing; and

quick connect tabs, for communicating electrical power passing through the switch to the motor.

16. The assembly of claim 15, wherein:

the switch is a snap-action switch.

17. The assembly of claim 15, further comprising:
an elastomeric saddle, provided on a face of the plug extending into the switch housing, for sealing the connection of the plug in the switch housing.

1/3







FIG-2

2/3



3/3




FIG-7




FIG-6

