

(12) **United States Patent**  
**Kretsch et al.**

(10) **Patent No.:** **US 11,082,101 B2**  
(45) **Date of Patent:** **Aug. 3, 2021**

(54) **CHANNELIZING AND BEAMFORMING A WIDEBAND WAVEFORM**

6,898,235 B1 \* 5/2005 Carlin ..... H04B 1/001 342/147

6,937,674 B2 8/2005 Santhoff et al.

7,430,257 B1 9/2008 Shattil  
(Continued)

(71) Applicant: **Viasat, Inc.**, Carlsbad, CA (US)

(72) Inventors: **Michael T. Kretsch**, San Diego, CA (US); **David C. Jacobs**, Solana Beach, CA (US); **David J. Trusheim**, Poway, CA (US); **Robert T. Short**, Vista, CA (US)

**FOREIGN PATENT DOCUMENTS**

CA 2537395 A1 8/2006  
CN 106685476 B 2/2019

**OTHER PUBLICATIONS**

Sklivanitis et al., "All-Spectrum Cognitive Channelization around Narrowband and Wideband Primary Stations", IEEE, 2015, 8 pgs.  
(Continued)

*Primary Examiner* — Hirdepal Singh  
(74) *Attorney, Agent, or Firm* — Murphy, Bilak & Homiller, PLLC

(73) Assignee: **ViaSat, Inc.**, Carlsbad, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/598,261**

(22) Filed: **Oct. 10, 2019**

(65) **Prior Publication Data**

US 2021/0111774 A1 Apr. 15, 2021

(51) **Int. Cl.**  
**H04B 7/06** (2006.01)  
**H04B 1/713** (2011.01)

(52) **U.S. Cl.**  
CPC ..... **H04B 7/0617** (2013.01); **H04B 1/713** (2013.01)

(58) **Field of Classification Search**  
CPC ..... H04B 7/0617; H04B 1/713  
USPC ..... 375/267  
See application file for complete search history.

(56) **References Cited**


**U.S. PATENT DOCUMENTS**

4,112,430 A 9/1978 Ladstatter  
5,838,732 A 11/1998 Carney  
6,560,463 B1 5/2003 Santhoff

(57) **ABSTRACT**

Methods, systems, and devices for channelizing and beamforming a wideband waveform are described. Generally, the described techniques provide for transmitting and receiving wideband waveforms that are beamformed on a per-channel basis during generation of the wideband waveforms. A transmitter may separate a first wideband signal into segments, with each segment bandwidth corresponding to a channel of the system bandwidth, and may map the segments to channels. The segments may be replicated to generate multiple copies of each segment. The transmitter may beamform and combine the copies of the segments to generate multiple wideband waveforms, and transmit each wideband waveform using a different antenna. A receiver may receive multiple wideband waveforms using multiple antennas and may separate each wideband waveform into segments, then beamform and de-map the segments. The techniques may be used to transmit and receive beamformed wideband waveforms over tactical data links.

**30 Claims, 12 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

7,965,761	B2	6/2011	Shattil	
8,107,887	B2	1/2012	Rao et al.	
8,155,649	B2	4/2012	McHenry et al.	
9,094,109	B2	7/2015	Revol	
9,209,891	B1*	12/2015	Mandell .....	H04B 7/1851
9,385,798	B1	7/2016	Marr et al.	
9,722,660	B1	8/2017	McCloskey et al.	
2005/0190777	A1	9/2005	Hess et al.	
2006/0013327	A1	1/2006	Sugar et al.	
2007/0135052	A1*	6/2007	Park .....	H04L 5/023 455/63.1
2009/0067513	A1	3/2009	Kim et al.	
2012/0113831	A1	5/2012	Pelletier	
2012/0170672	A1	7/2012	Sondur	
2016/0137311	A1	5/2016	Peveerill et al.	
2016/0182266	A1*	6/2016	Gaal .....	H04L 27/2042 375/219
2017/0318497	A1	11/2017	Tranquilli, Jr.	
2018/0287682	A1*	10/2018	Kwak .....	H04B 7/0695
2019/0097678	A1*	3/2019	Park .....	H04L 1/0041
2019/0190595	A1*	6/2019	Ching .....	H04B 7/2628
2019/0207731	A1*	7/2019	Park .....	H04W 16/28
2019/0312766	A1*	10/2019	Sengupta .....	H04L 27/2602
2019/0334587	A1*	10/2019	Rahman .....	H04B 7/0417
2019/0379437	A1*	12/2019	Park .....	H04L 27/2636
2020/0022168	A1*	1/2020	Xu .....	H04L 5/0053
2020/0052947	A1*	2/2020	Sahin .....	H04W 72/0453

OTHER PUBLICATIONS

Harris et al., "Digital Receivers and Transmitters Using Polyphase Filter Banks for Wireless Communications" IEEE, Published Apr. 8, 2003, 40 pgs.

Harris et al., Orthogonal Waveforms and Filter Banks for Future Communication Systems, Chapter 6—"Filter banks for Software Defined Radio", <https://www.sciencedirect.com/science/article/pii/B9780128103845000062>; Published by Academic Press 2017, pp. 105-127.

International Search Report and Written Opinion issued in International Application No. PCT/US2020/054644, dated Dec. 16, 2020 in 20 pages.

U.S. Appl. No. 16/598,201, entitled "Channelizing a Wideband Waveform for Transmission on a Spectral Band Comprising Unavailable Channel Segments" (filed Oct. 10, 2019) (assigned to Viasat, Inc.).

International Search Report and Written Opinion issued in International Application No. PCT/US2020/054639 dated Jan. 29, 2021 in 11 pages.

Northrop Grumman, "Understanding voice and data link networking understanding voice and data link networking. Northrop Grumman's guide to secure tactical data links," Dec. 1, 2014, XP055559331, Retrieved from the Internet: [http://www.northropgrumman.com/capabilities/datalinkprocessingandmanagement/documents/understanding\\_voice+data\\_link\\_networking.pdf](http://www.northropgrumman.com/capabilities/datalinkprocessingandmanagement/documents/understanding_voice+data_link_networking.pdf).

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6





FIG. 7



800

FIG. 8




FIG. 9




FIG. 10

1000




FIG. 11




FIG. 12

## CHANNELIZING AND BEAMFORMING A WIDEBAND WAVEFORM

### BACKGROUND

The following relates generally to wideband communications, and more specifically to channelizing and beamforming a wideband waveform.

Wired and wireless communications systems are widely deployed to provide various types of communication content such as voice, video, packet data, messaging, broadcast, and so on. Some communications systems may be used in the context of secure communications, such as tactical communications. In addition, some communication systems may experience frequency-dependent interference. Such communications systems may be subject to various constraints and challenges.

### SUMMARY

The described techniques relate to improved methods, systems, devices, and apparatuses that support channelizing and beamforming a wideband waveform. Generally, the described techniques provide for transmitting and receiving beamformed wideband waveforms. The described techniques may include techniques for transmitting a beamformed wideband waveform via a spectral band comprising unavailable channel segments. The techniques may include generating a set of segments of a first wideband waveform, mapping the set of segments to a set of channels, where each of the set of channels has a respective channel bandwidth, generating a set of copies of each segment of the set of mapped segments, where each copy of a respective segment is associated with a corresponding antenna of a set of antennas for a transmission, applying respective sets of beamforming coefficients to the set of copies for the mapped set of segments to obtain a set of component segments for each of the mapped set of segments, where the respective sets of beamforming coefficients for the mapped set of segments are based on channels of the set of channels for the mapping, combining the component segments associated with each of the set of antennas into respective component wideband waveforms, and transmitting each of the respective component wideband waveforms via a separate antenna of the set of antennas for the transmission.

The described techniques may include techniques for receiving, over a beamformed receive beam, a wideband waveform via a spectral band comprising unavailable channel segments. The techniques may include receiving a set of component wideband waveforms via a set of antennas, where each component wideband waveform is received via a separate antenna of the set of antennas, separating each component wideband waveform of the set of component wideband waveforms into a corresponding set of component segments, each segment associated with a corresponding channel of a set of channels, applying respective sets of beamforming coefficients to the component segments, and combining the beamformed component segments.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an example of a wireless communication system that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

FIG. 2 illustrates an example of a transmitter that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

FIG. 3 illustrates an example of a transmitter that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

FIG. 4 illustrates an example of a spectrum plot that supports channelizing a wideband waveform for transmission on a spectral band comprising unavailable channel segments in accordance with aspects of the present disclosure.

FIGS. 5A and 5B illustrate an example of a polyphase analysis bank and an example of a polyphase synthesis bank that support channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

FIG. 6 illustrates an example of a receiver that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

FIG. 7 illustrates an example of a portion of a transmitter that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

FIG. 8 illustrates an example of a channel beamforming synthesizer that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

FIG. 9 illustrates an example of a portion of a receiver that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

FIG. 10 illustrates an example of a device that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

FIGS. 11 and 12 show flowcharts illustrating methods that support channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure.

### DETAILED DESCRIPTION

Wireless communications systems used for secure communications, such as for tactical communications between military entities, may be subject to various constraints and challenges. For example, such communications may be expected to provide a high level of robustness to external tampering, a high level of reliability, etc. The Link 16 communication protocol is an example of a tactical data link that may provide various advantages for tactical communications, such as providing a relatively high level of security for transmissions. Link 16 was originally developed for tactical airborne air-to-air communications and supports voice communications and limited data communications. The spectrum used by Link 16 has been highly regulated, and the protocol was designed to support sparse waveforms that use relatively little spectrum. Tactical data links such as Link 16 may operate as primary user (e.g., prioritized over other users), a secondary user (e.g., a lower priority user than at least one other user), or as a tertiary user (e.g., as a user that obtains permission to use spectrum for transmission).

In recent years the use of Link 16 has expanded and the risks of jamming and other undesirable interference have increased. Because tactical data links such as Link 16 operate on older physical layers and under relatively tight regulation, however, increasing the capacity (e.g., throughput), spectrum efficiency, and security—particularly while maintaining backward compatibility—may be challenging.

Traditional data links may use single-channel transmission. In this case, if a particular transmission channel is

jammed or otherwise unavailable for transmission, the transmitter may select a different channel if available. However, in single-channel transmissions, the transmission energy may be concentrated within the channel and may be more easily detectible or jammable. A transmitter may provide better anti-jamming performance, better throughput, and/or better spectrum efficiency by generating a wideband waveform representing the data to be transmitted and mapping the wideband waveform to multiple channels. In this case, the information may be spread across multiple channels to reduce detectability of the signal, improve transmission quality and throughput, and mitigate the effect of channel jamming.

In some cases, a waveform may be beamformed and transmitted using multiple antennas to increase signal quality. However, beamforming is typically a narrow band process. As the transmit frequency moves away from a beamformer's design frequency, the beam shape degrades. This may be a minor problem for narrowband systems such as WiFi or cellular telephony, but may be a more serious problem in a wideband system such as tactical systems or other systems described herein. That is, beamforming a wideband waveform may be more challenging than beamforming a narrowband waveform.

As described herein, a transmitter may be configured to beamform a wideband waveform on a per-channel basis before transmission. For example, in some cases, a transmitter may segment a first wideband waveform into multiple segments, where each segment may correspond to a channel of a system bandwidth. The transmitter may generate multiple copies of each segment to create multiple sets of segments, where each set of segments may correspond to an antenna for transmission. The transmitter may beamform the sets of segments on a per-channel basis, then combine the beamformed sets of segments into multiple (second) wideband waveforms for transmission. The transmitter may transmit each of the second wideband waveforms using a separate antenna.

Aspects of the disclosure are initially described in the context of a wireless communications system. Aspects of the disclosure are further illustrated by and described with reference to apparatus diagrams, system diagrams, and flowcharts that relate to channelizing and beamforming a wideband waveform.

FIG. 1 illustrates an example of a communication system **100** that may employ channelizing and beamforming a wideband waveform, according to various aspects of the disclosure. Communication system **100** includes devices **105** that may be capable of wireless communication using a tactical data link **110**. Devices **105** may be a handheld device carried by a user, or may be located in a vehicle such as aircraft, tank, ship, or other type of vehicle. Tactical data link **110** may support secure communications between devices **105** and may include frequency hopping capabilities. Frequency hopping may refer to rapidly switching a carrier among different frequency channels using a sequence (e.g., a pseudorandom sequence) known to both transmitter and receiver. For example, tactical data link **110** may support frequency hopping at 13 microsecond intervals or at other relatively short intervals.

Tactical data link **110** may enable devices **105** to communicate on a system bandwidth that includes multiple channels having predetermined bandwidths (e.g., each channel having the same bandwidth). In some cases, not all of the channels may be available for transmission. For example, in some cases tactical data link **110** may transmit on a data link network platform having a spectral band (e.g., a system

bandwidth) comprising  $N$  bandwidth segments (e.g., channels) only  $M$  of which may be available at any given time. In some cases, a tactical data link **110** may have a spectral band of 240 MHz (e.g., a band that ranges from 967.5 to 1207.5 MHz), where  $N$  is 80 channels each comprising 3 MHz and  $M$  is 51 or less.

In some cases, tactical data link **110** may be a time division multiple access (TDMA) platform in which each user is assigned one or more time slices in which to transmit. A transmitting user may transmit a message as a sequence of encoded pulses, which are frequency-hopped in a unique hopping pattern among the channels within a time slice. In some cases, each pulse may have a bandwidth equal to a channel bandwidth, and may be mapped to one of the channels according to the hopping pattern. In some cases, the hopping pattern is known to the receiving user. Use of hopping patterns may allow multiple users to transmit in the same time slice. In some cases, each user transmitting in the same time slice but using a different hopping pattern may be referred to as transmitting on a different "net." In some cases, transmissions may include parallel pulses on each available channel. However, if one or more channels on which the pulses are mapped is jammed or has substantial interference, the link performance may degrade substantially.

A transmitter used in a system for transmitting wideband waveforms over a tactical data link may receive a stream of bits for transmission (e.g., from a processor in the system), and may generate a wideband waveform based on the stream of bits. In some cases, the system may be configured to transmit wideband waveforms using a system bandwidth that may include or may be partitioned into multiple channels, where each channel may have a predetermined (e.g., the same) channel bandwidth.

According to various aspects of the disclosure, a transmitter may enhance performance over a segmented spectral band by generating a wideband waveform representing the data to be transmitted and mapping the wideband waveform to multiple channels. The transmitter may make multiple copies of the channelized wideband waveform, and may beamform each copy on a per-channel basis. Channelizing and beamforming the wideband waveform may provide better anti jamming performance, better throughput, and/or better spectrum efficiency. For example, the information may be spread across multiple channels to reduce detectability of the signal, improve transmission quality and throughput, and mitigate the effect of channel jamming.

FIG. 1 illustrates a system bandwidth **130** including 15 channels with three devices **105** transmitting over three different nets **115** of tactical data link **110** during a time slice **120**. For example, a first device **105-a** may transmit over net A **115-a**, a second device **105-b** may transmit over net B **115-b**, and a third device **105-c** may transmit over net C **115-c**. Each of the devices may concurrently receive or listen to one or more nets **115**. For example, device **105-a** may transmit over net **115-a** while receiving net B **115-b** and net C **115-c**. Alternatively, some devices **105** may only transmit or receive during a given time slice **120**. First device **105-a** may transmit using three channels **135** during each pulse period **125** in time slice **120**, where the channels **135** used by first device **105-a** for each pulse period **125** of time slice **120** may be determined by the hopping pattern associated with net A **115-a**. For each time slice **120**, device **105-a** may determine an available subset of the system bandwidth **130**. For example, device **105-a** may determine a number of channels that are configured for net A **115-a** for time slice **120**. Additionally or alternatively, device **105-a** may deter-

mine a subset of channels **135** available for the time slice **120**, which may be based on a configuration for the system bandwidth (e.g., for one or more time slices **120**). In addition, one or more channels **135** may be unavailable due to interference (e.g., jamming). For example, device **115-a** may be configured to use three channels **135** per pulse period **125** of time slice **120**, and may determine that 13 of the 15 channels of the system bandwidth are available for time slice **120**. In addition, device **105-a** may determine that one or more channels **135** have an interference level that meets or exceeds a threshold. In one example, device **105-a** may determine that channels **7** and **8** have excessive interference during time slice **120**. Device **105-a** may be mapped to different subsets (e.g., provisional subsets) of three channels **135** per pulse period **125**. For each pulse period **125** where net **A 115-a** is mapped to one or more of channels **7** and **8**, device **105-a** may allocate transmission power to the other channels associated with the pulse period **125**. For example, for pulse periods **8**, **6**, and **4** of time slice **120**, device **105-a** may allocate its transmission power between the other two channels **135** (e.g., allocating zero power to channels **7** and **8**), while in the other pulse periods device **105-a** may allocate its transmission power between three channels **135**. In some cases, devices **105** may make a determination of available channels on a pulse period **125** basis. For example, device **105-a** may receive or identify an indication of a provisional subset of channels for a given pulse period **125**, and may make a determination of the available channels of the provisional subset of channels (e.g., based on interference).

Although illustrated as having 15 total channels, tactical data link **110** may have any number of channels, and an arbitrary number up to and including all of the total number of channels may be available for each time slice **120**. Each net **115** may also be associated with varying numbers of channels for each pulse period, up to and including the number of available channels. Although nets **A**, **B**, and **C** are illustrated in FIG. **1** as having non-overlapping hopping patterns, hopping patterns for nets **115** may overlap during one or more pulse periods **125** of a time slice **120**, in some cases. Although FIG. **1** depicts three pulses (e.g., on three channels **135**) on each net **115** per pulse period **125**, in some cases, tactical data link **110** may support a different number of pulses on each net **115**, such as one pulse per net **115** per pulse period **125**.

FIG. **2** illustrates an example of a transmitter **200** that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. In some examples, transmitter **200** may be included in a wireless communication system, such as wireless communication system **100**.

Transmitter **200** may be configured to wirelessly transmit wideband waveforms over a tactical data link using one or more antennas **275** and a transmitter backend **272**. In some cases, a wideband waveform may be a waveform that spans a relatively wide band of frequencies, and may be a spread spectrum waveform. Transmitter **200** may be configured to transmit wideband waveforms using a system bandwidth, which may be a band of frequencies over which transmitter **200** may transmit signals. In some cases, a system bandwidth may be partitioned into channels, with each channel having a respective bandwidth (e.g., the same channel bandwidth). In some cases, one or more channels of the system bandwidth may be unavailable for transmissions if, for example, the channels are excluded from a subset of configured available channels or are jammed by interfering signals (e.g., other transmissions or intentional jamming). In

some cases, transmitter **200** may identify a channel set **215** (e.g., a set of channels selected for transmission) and may transmit wideband waveforms using the channel set **215**, as described in more detail herein. In some examples, the channel set **215** may correspond to all of the available channels, while in some cases channel set **215** may be a subset of the available channels (e.g., a configured number of channels). In some cases channel set **215** may be determined by excluding channels from the available channels or configured channels that have a level of signal power (e.g., interference) that satisfies (e.g., meets or exceeds) a threshold.

In operation, transmitter **200** may receive a stream of bits **205**, such as data bits for transmission. In some cases, the stream of bits **205** may be received for transmission in a time period (e.g., a pulse period). In some cases, transmitter **200** may receive the stream of bits **205** from a processor or other device that is coupled with transmitter **200**. Transmitter **200** may include a modulator **210** for modulating the stream of bits **205** to generate a first wideband waveform **220**. In some cases, modulator **210** may receive an indication of channel set **215**, and may modulate the stream of bits **205** based on the number of channels in channel set **215**. For example, a device that includes transmitter **200** may identify a total number of channels of a system bandwidth and a set of available channels for a time slice or pulse period (e.g., configured for the time slice or pulse period, or having a signal power level that does not satisfy a threshold). The device may determine channel set **215** from the set of available channels (e.g., a subset or all of the set of available channels).

In some cases, channel set **215** may exclude channels that have signal power satisfying the threshold (e.g., due to excessive use or intentional jamming). In some cases, the channel set **215** may be non-contiguous; that is, at least two channels in the channel set **215** may be separated by one or more channels that are excluded from the channel set **215**.

In some cases, the modulator **210** may modulate the stream of bits **205** to generate a first wideband waveform **220** having a bandwidth that is equal to an aggregate bandwidth of the channels in the channel set **215**. For example, where the bandwidth of the channels is the same, the bandwidth of first wideband waveform **220** may be determined by the number of channels in channel set **215** multiplied by the channel bandwidth. In one example, transmitter **200** may be configured to transmit via  $M$  segments, each segment having a bandwidth of  $B$  MHz. Thus, the bandwidth of the first wideband waveform may be equal to  $M \cdot B$  MHz. Where the bandwidths of the channels are not the same, the bandwidth of first wideband waveform **220** may be determined by summing the bandwidths of the channels in channel set **215**.

In some cases, modulator **210** may be a variable modulator that may select a modulation scheme (e.g., from a set of modulation schemes) for modulating the stream of bits **205** based on various factors. For example, modulator **210** may select a modulation scheme based on the channel set **215** and/or on a desired coding rate, block error rate (BLER), or throughput. In some cases, the modulation scheme may specify, for example, a modulation type (e.g. BPSK, QPSK, 16 QAM, etc.), a type of code (e.g., convolutional code, LDPC code), and a code rate (e.g., a rate 1/3 code, a rate 5/8 code).

Transmitter **200** includes analyzer **230**. Analyzer **230** includes segmenter **235** for separating the first wideband waveform **220** into multiple segments **225**. Segments **225** may have respective bandwidths corresponding to channel

bandwidths of the channel set **215** (e.g., the same bandwidth). In some cases, segmenter **235** may separate the first wideband waveform **220** into segments **225** by applying multiple filters (such as bandpass filters (BPFs)) to the first wideband waveform **220**. In some cases, segmenter **235** may include a series of filters to separate first wideband waveform **220** into segments **225**, and may be implemented using a polyphase filter. Each segment **225** may have an effective symbol timing that is less (e.g., substantially less) than the symbol timing (e.g., pulse period). That is, each segment **225** may carry information associated with multiple symbols in each symbol period or pulse period.

In some cases, analyzer **230** includes downconverter **240** to downconvert the segments **225** to baseband segments **245**. For example, segments **225** may each be associated with different frequency ranges and downconverter **240** may downconvert each segment to a baseband frequency range.

Transmitter **200** includes mapper **250** for mapping the segments (e.g., baseband segments **245**) to the corresponding frequency ranges of channel set **215**. In some cases, the remaining channels (e.g., channels of the system bandwidth that are not in channel set **215**) may be set to null values. For example, mapper **250** may output a null segment or null signal for channels of the system bandwidth that are not in channel set **215**. A null segment may be a signal having no signal energy within the baseband frequency range.

Mapper **250** may map segments **225** to channel set **215** in an order of the segments **225**. Alternatively, mapper **250** may scramble an order of the segments **225** among channel set **215** such that the segments **225** are mapped to channel set **215** out of order relative to the order of the segments, as depicted in FIG. 2. For example, adjacent segments may not be mapped to adjacent channels of channel set **215**. Where a scrambled order is used, mapping of non-adjacent segments to adjacent channels of channel set **215** may cause aliasing of signal energy from adjacent segments at the receiver. Thus, groups of segments may be mapped to contiguous blocks of channels of channel set **215**. That is, groups of contiguous blocks of channel set **215** may be identified, and sub-groups of contiguous segments **225** may be mapped to each of the groups of contiguous blocks. Mapper **250** may output mapped segments **251** to synthesizer **255**.

In some examples, mapper **250** may perform additional processing. For example, mapper **250** may perform multipath equalization of segments **225** or mapped segments **251** before outputting mapped segments **251**.

Transmitter **200** includes synthesizer **255** for generating a second wideband waveform **270**. Synthesizer **255** includes upconverter **260** for upconverting the mapped segments to higher frequencies. Synthesizer **255** includes combiner **265** for combining the upconverted segments and holes in the spectrum (corresponding to the null values) into a second wideband waveform **270** having a bandwidth corresponding to the channel set **215** (e.g., extending from a first channel of channel set **215** having a lowest frequency to a second channel of channel set **215** having a highest frequency). Second wideband waveform **270** may have a bandwidth that is wider than first wideband waveform **220**. Second wideband waveform may include null frequency ranges (e.g., corresponding to frequency channels of the system bandwidth that are not in channel set **215**).

In some cases, by generating the second wideband waveform **270** as described herein, the energy of each bit of the stream of bits **205** may be spread over the channels in second wideband waveform **270** and may therefore be less susceptible to data loss due to jamming of a single channel.

In some cases, transmitter **200** may include a transmitter backend **272** that includes hardware or software to implement additional processing on second wideband waveform **270** before transmission using one or more antennas **275**. For example, the second wideband waveform **270** may be upconverted to passband before transmission.

In some cases, the transmitted signal (e.g., the transmitted second wideband waveform) will carry the information in the first wideband waveform that is output by the modulator, but there may be substantial energy only in the channels of channel set **215**. In this case, the transmitted signal may not interfere with signals transmitted (e.g., by other transmitters) in the other channels of the system bandwidth.

In one example, a system bandwidth of 45 MHz may be configured with 3 MHz channels (e.g., 15 channels). Transmitter **200** may identify a channel set **215** for a first time period (e.g., a first pulse period) that includes channels **1-5, 8-10, 13, and 15** (e.g., including 10 of the 15 channels). Modulator **210** may generate a first wideband waveform **220** having a bandwidth of 30 MHz and analyzer **230** may segment and downconvert each segment to generate **10** baseband segments **245**, each representing a portion (e.g., 3 MHz) of the 30 MHz bandwidth, and each having a baseband frequency range of 0-3 MHz. Mapper **250** may map the baseband segments **245** to the channel set **215**, and may map null waveforms to channels of the system bandwidth not in channel set **215**. Mapper **250** may map the baseband segments **245** to channel set **215** in order, or mapper **250** may map the baseband segments **245** to channel set **215** in a scrambled order. For example, mapper **250** may map baseband segment **1** to channel **13**, baseband segments **2-4** to channels **8-10**, baseband segments **5-9** to channels **1-5**, and baseband segment **10** to channel **15**. Synthesizer **255** may upconvert the mapped segments **251** to corresponding frequencies of channel set **215** and combine the upconverted segments to obtain a second wideband waveform **270**. In this example, second wideband waveform **270** may have a bandwidth of 45 MHz, with substantially no signal energy in channels **6, 7, 11, 12, and 14**. In instances where channel set **215** does not include channel **1** or channel **15**, second wideband waveform **270** may have a bandwidth of less than the system bandwidth of 45 MHz (e.g., where one or more segments are not mapped to the upper or lower channels of the system bandwidth).

Transmitter **200** may identify a new channel set **215** for a second time period (e.g., a second pulse period), and may perform the segmenting, downconverting, mapping, upconverting, and combining to generate a second wideband waveform **270** for the second time period. For example, transmitter **200** may identify a new channel set **215** every pulse period, or every fourth, eighth, or twelfth pulse period, or every time slice, or at some other time period. New channel set **215** may be different than the channel set **215** for the first pulse period and may or may not have any channels in common with the previous channel set **215**. For example, new channel set **215** may have the same or a different number of channels. It should be understood that this example is provided for the sake of clarity, and other system bandwidths and channel bandwidths are contemplated without deviating from the scope of the application. For example, the system bandwidth may be 240 MHz, and the system may have 80 channels where each channel has a 3 MHz channel bandwidth. Channel set **215** may have up to 51 channels in each pulse period and thus first wideband waveform **220** may have a bandwidth of up to 153 MHz while second wideband waveform **270** may have a bandwidth of up to 240 MHz (e.g., the system bandwidth).

In some cases, transmitter **200** may beamform the second wideband waveform **270**. For example, transmitter **200** may include multiple antennas **275** upon which multiple component versions of the second wideband waveform **275** may be transmitted, resulting in a beamformed transmission. The set of segments and nulls processed by the synthesizer **255** can be replicated into as many copies as there are antennas **275**. Beamforming processing can be applied to each replicated set of the segments and nulls so each set forms one of the component versions of the second wideband waveform **270** transmitted on one of the antennas **275**. In one example, the segments and nulls can be replicated and the beamforming processing applied to the segments and nulls output by the mapper **250**, such as depicted in the example of FIG. 7. In some cases, the segments and nulls can be replicated and the beamforming processing applied to the segments and nulls within the synthesizer **660** (e.g., as output by the upconverter **665**) as depicted in FIG. 6.

FIG. 3 illustrates an example of a portion of a transmitter **300** that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. In some examples, transmitter **300** may implement aspects of wireless communication system **100** or transmitter **200**.

Transmitter **300** includes analyzer **230-a**, mapper **250-a**, and synthesizer **255-a**, which may be examples of analyzer **230**, mapper **250**, and synthesizer **255** of FIG. 2, respectively. A first wideband waveform **220-a** may be input to analyzer **230-a**. Analyzer **230-a** includes multiple bandpass filters **332**, downconverters (DCs) **334**, and decimators **336**. Band-pass filters **332** may each be associated with a frequency range of the first wideband waveform **220-a**. For example, the first wideband waveform **220-a** may have a bandwidth corresponding to an aggregate bandwidth of a number of segments in a channel set **215-a** configured for transmission within a pulse period. In one example, transmitter **300** may be configured to transmit via  $M$  segments, each segment having a bandwidth of  $B$  MHz. In this case, analyzer **230-a** may have  $M$  (or more) bandpass filters **332**, each configured to pass a range of frequencies corresponding to the bandwidth of one segment. That is, bandpass filters **332** may be configured to pass frequencies in ranges of  $\{0 \text{ to } B\}$ ,  $\{B \text{ to } 2B\}$ , . . .  $\{(M-1)B \text{ to } M*B\}$ . Bandpass filters **332** may output filtered segment waveforms **333**.

Downconverters **234** may downconvert filtered segment waveforms **333** to a baseband frequency range. For example, downconverters **234** may downconvert each filtered segment waveform **333** to have a frequency range of  $\{0 \text{ to } B\}$ . Decimators **336** may decimate (e.g., downsample) the downconverted filtered segment waveforms **333** from a first sample rate associated with the first wideband waveform **220-a** to a second, lower sample rate (e.g., which may not cause aliasing because of the smaller bandwidth of each segment). In some cases, bandpass filters **332** and downconverters **334** may be implemented in a downconverting filter **330**. Downconverting filter **330** may implement bandpass filters **332** using a polyphase filter an inverse discrete Fourier transform (IDFT). In some cases, both the inputs and the outputs of the IDFT are in the time domain. It should be understood that the IDFT may be implemented using an inverse fast Fourier transform (IFFT) algorithm, and the terms IDFT and IFFT may be used interchangeably.

Mapper **250-a** may map the downconverted filtered segment waveforms **333** to segments of a channel set (e.g., channel set **215-a**). Mapper **250-a** may map downconverted filtered segment waveforms **333** to the segments in order of the downconverted filtered segment waveforms **333**. Alter-

natively, mapper **250-a** may map the downconverted filtered segment waveforms **333** to the segments of the channel set using a scrambled mapping (e.g., not in order). Mapper **250-a** outputs mapped segment waveforms **351**, each mapped segment waveform **351** being a baseband waveform sampled according to a baseband sampling frequency. Mapper **250-a** may output  $M$  mapped segment waveforms **351**, where  $M$  corresponds to a number of segments in channel set **215-a** (e.g., null segments may not correspond to a mapped segment waveform **351**).

Synthesizer **255-a** includes interpolators **352**, image rejection (IR) filters **354**, upconverters **356**, and combiner **358**. Interpolators **352** effectively upsample the mapped segment waveforms **351** by interpolating from the second sample rate to a third, higher sample rate (e.g., a sample rate associated with a system bandwidth). For example, interpolators **352** may upsample the mapped segment waveforms **351** to a sample rate that is based on an aggregate bandwidth of a total number of channels of the system bandwidth (e.g., a sample rate that satisfies the Nyquist criteria for the system bandwidth).

Image rejection filters **354** may perform filtering to suppress image spectra that may result from interpolation.

Upconverters **356** upconvert each mapped segment waveform **351** to a frequency of the channel set **215-a**. For example, a first upconverter **356** may upconvert a first mapped segment waveform **351** to a frequency of a first channel of the channel set **215-a**, a second upconverter **356** may upconvert a second mapped segment waveform **351** to a frequency of a second channel of the channel set **215-a**, and so on, such that each of the mapped segment waveforms **351** are upconverted to respective channels of the channel set **215-a**. Combiner **358** combines the upconverted mapped segment waveforms **351** to obtain second wideband waveform **270-a**, which may include signal energy in channels of a system bandwidth corresponding to channel set **215-a**, and null waveforms (e.g., substantially no signal energy) in channels of the system bandwidth not within channel set **215-a**. Upconverters **356** and combiner **358** may be implemented as upconverting filter **350**. In some cases upconverting filter **350** may implement upconverters **356** and combiner **358** using a polyphase filter and an inverse DFT.

FIG. 4 illustrates a spectrum plot **400** of a channelized wideband waveform for transmission on a spectral band comprising unavailable channel segments in accordance with aspects of the present disclosure. Spectrum plot **400** shows, for example, a system bandwidth **130-a** that includes  $N$  channels **135-a**. Each channel **135-a** may have a channel bandwidth **410**. Although FIG. 4 illustrates channels **135-a** having the same channel bandwidth **410**, channels **135-a** may have different bandwidths, in some cases. In some examples, implementations using a polyphase synthesis bank or a polyphase analysis bank may be applied in environments where each channel **135** has the same channel bandwidth **135-a**, or are powers of two or multiples of a power of two relative to each other.

Spectrum plot **400** illustrates spectrum of a second wideband waveform **270-b**, which may be generated, for example, by the transmitters **200** or **300** of FIG. 2 or 3. Second wideband waveform **270-b** may include signal power within channels **135-a** of a channel set, while channels that are not included in the channel set may not have substantial signal power (e.g., may have null waveforms). For example, FIG. 4 illustrates that second wideband waveform **270-b** has signal power in channels **2**, **4**, **5**, and  $N$  (with some channels not shown for the sake of clarity), while channels **1**, **3**, and **6** have null signals (e.g., substantially no

signal power). The bandwidth of the signal power of second wideband waveform **270-b** for each channel **135-a** may be understood as the range of the spectral density of the channel **135-a** that includes signal power over a threshold (e.g., 3 dB, 6 dB). In some cases, the signal power waveform for each segment may have a guardband (e.g., a segment of 3 MHz may have guardbands of 100 KHz, or a 3 dB bandwidth of 2.8 MHz).

FIGS. **5A** and **5B** illustrate examples of polyphase analysis bank **500** and a polyphase synthesis bank **505** that support channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. In some examples, polyphase analysis bank **500** and polyphase synthesis bank **505** may implement aspects of wireless communication system **100**.

Polyphase analysis bank **500** includes multiple polyphase filters. For example polyphase analysis bank **500** is illustrated with P subfilters **515** and IDFT **525**. Each subfilter **515** may have the same or different orders. An input signal **520** (e.g., first wideband waveform **220**) may be input to subfilters **515** (e.g., different sample interlaces may be input to subfilters **515** by commutator **512**) and the output of the subfilters **515** may be input to inverse DFT **525**. Each subfilter **515** may receive an interlaced subset of samples of the input signal **520**. For example, subfilters **515-a**, **515-b**, and **515-c** may each receive different subsets of samples of the input signal **520**. In some cases, commutator **512**, subfilters **515**, and IDFT **525** may implement a downconversion polyphase filter that outputs downconverted filtered waveform segments **535**. For example, commutator **512** may downsample the input signal **520**, subfilters **512** may perform filtering, and IDFT **525** may perform downconversion. Polyphase analysis bank **500** may be an example of a downconverting filter **330**.

Polyphase synthesis bank **505** may also include multiple polyphase filters. For example polyphase synthesis bank **505** is illustrated with IDFT **545** and Q subfilters **515**. Each subfilter **515** (e.g., subfilters **515-d**, **515-e**, **515-f** and others) may have the same or different orders. Inverse DFT **545** may receive Q input signals (e.g., mapped segments **251**) and output Q signals to subfilters **515**. IDFT **545** and subfilters **515** may perform filtering and upconversion to generate an upconverted waveform combining the signal energy within the Q signals (e.g., corresponding to Q segments). For example, the output of subfilters **515** may be combined by commutator **550** (e.g., by interlacing samples from the Q subfilters) to obtain the upconverted waveform (e.g., second wideband waveform **270**). That is, IDFT **545** may perform upconversion, subfilters **515** may perform image reject filtering, and commutator **550** may perform upsampling. Polyphase synthesis bank **505** may be an example of an upconverting filter **350**.

FIG. **6** illustrates an example of a receiver **600** that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. In some examples, receiver **600** may be included in a wireless communication system, such as wireless communication system **100**.

Receiver **600** may be configured to wirelessly receive wideband waveforms over a tactical data link using one or more antennas **605**. Receiver **600** may be configured to receive a first wideband waveform **610** via a system bandwidth, which may be a band of frequencies over which receiver **600** may receive signals. In some cases, a system bandwidth may be partitioned into channels, with each channel having a respective bandwidth (e.g., the same channel bandwidth).

In some cases, one or more channels of the system bandwidth of the first wideband waveform **610** may be unused for a received signal (e.g., via a “net” of a tactical data link). Unused channels of the system bandwidth may not include data to be received and/or may have a received level of signal power (e.g., signal energy) that is below a threshold. That is, in some cases, there may be substantial energy of the received signal only in a subset of channels of the channels of the system bandwidth. In some cases, the subset of channels may be non-contiguous; that is, at least two channels in the subset of channels may be separated by one or more channels that are excluded from the subset of channels. In some cases, receiver **600** identifies that a level of signal power for at least one of the channels of the system bandwidth satisfies a threshold (e.g., is below a minimum), and excludes such channel(s) from the subset of channels **615**. Receiver **600** may identify or receive an indication of the subset of channels of the system bandwidth associated with a signal for reception (e.g., channel set **615**).

In some cases, receiver **600** may include a receiver frontend **607** that includes hardware or software to process a signal received using antenna(s) **605** to generate first wideband waveform **610**. For example, receiver frontend **607** may filter the received signal, mix the signal (e.g., downconvert), perform analog-to-digital conversion, and/or perform other processing.

Receiver **600** includes analyzer **620**. Analyzer **620** includes segmenter **625** for separating the first wideband waveform **610** into multiple segments **635**. Segments **635** may have respective bandwidths corresponding to channel bandwidths of the channels of the system bandwidth (e.g., the same bandwidth). In some cases, segmenter **625** may separate the first wideband waveform **610** into segments **635** by applying multiple filters (such as BPFs) to the first wideband waveform **610**. In some cases, segmenter **625** may include a series of filters to separate first wideband waveform **610** into segments **635**, and may be implemented using a downconverting filter. For example, analyzer **620** may be structurally similar to analyzer **230-a**, downconverting filter **330**, or polyphase analysis bank **500**. In one example, analyzer **620** may be structurally similar to analyzer **230-a** with M (or more) bandpass filters **332**, where M is the number of channels in channel set **615**. Alternatively, analyzer **620** may include N (or more) bandpass filters **332**, where N is the total number of channels of the system bandwidth.

In some cases, analyzer **620** includes downconverter **630** to downconvert the segments **635** to baseband segments **645**. For example, segments **635** may each be associated with different frequency ranges and downconverter **640** may downconvert each segment **635** to a baseband frequency range.

Receiver **600** includes mapper **650** for de-mapping the segments (e.g., baseband segments **645**) corresponding to the channel set **615** to the corresponding frequency ranges of synthesizer channels **690**. In some cases, the remaining channels (e.g., channels of the system bandwidth that are not included in channel set **615**) may be ignored. For example, the system bandwidth may include N channels while channel set **615** may include M channels. Mapper **650** may map M channels of the N channels that are in channel set **615** to a first set of M synthesizer channels **690** while NM channels of synthesizer channels **690** may not be mapped (e.g., may have a null signal mapped). In some cases, de-mapping the segments may include de-scrambling an order of the segments according to a scrambling sequence. The scrambling sequence may include an indication of a scrambled order of

the segments. In some cases, the scrambling sequence includes multiple sub-groups of the waveform segments, and the sub-groups are de-mapped from respective contiguous blocks of the subset of the plurality of channels.

In some examples, mapper 650 may perform additional processing. For example, mapper 650 may perform multipath equalization of baseband segments 645 before de-mapping the baseband segments 645.

Receiver 600 includes synthesizer 660 for generating a second wideband waveform 675. Second wideband waveform 675 may have a bandwidth that is narrower than first wideband waveform 610. Synthesizer 660 includes upconverter 665 for upconverting the de-mapped segments 655 to higher frequencies. Synthesizer 660 includes combiner 670 for combining the upconverted de-mapped segments to obtain a second wideband waveform 675 having a bandwidth corresponding to the total (e.g., aggregate) bandwidth of channel set 615. In some examples, synthesizer 660 may be structurally similar to synthesizer 255-a, upconverting filter 350, or polyphase synthesis bank 505. In one example, synthesizer 660 may be structurally similar to synthesizer 255-a with M (or more) interpolators 352, image rejection filters 354, and upconverters 356, where M is the number of channels in the channel set 615.

In some cases, receiver 600 may include hardware or software to implement additional processing on second wideband waveform 675 to generate a stream of bits 680 representing second wideband waveform 675. For example, receiver 600 may include a demodulator 685 to demodulate second wideband waveform 675 to obtain the stream of bits 680. In some cases, a receiver 600 may identify a modulation scheme (e.g., from a set of modulation schemes) for demodulating the second wideband waveform 675 to obtain stream of bits 680 based on information associated with the signal (e.g., from the transmitter). Receiver 600 may demodulate the second wideband waveform 675 according to the selected modulation scheme.

Receiver 600 may provide the stream of bits 680 to a processor or other device that is coupled with receiver 600.

In one example, a system bandwidth of 45 MHz may be configured with 3 MHz channels (e.g., 15 channels). Receiver 600 may identify a channel set 615 for a first time period (e.g., a first pulse period) that includes channels 1-5, 8-10, 13, and 15 (e.g., including 10 of the 15 channels). Receiver 600 may receive a first wideband waveform 610 (e.g., via antenna(s) 605 and receiver frontend 607). The first wideband waveform 610 may have a bandwidth corresponding to the system bandwidth (e.g., 45 MHz) with substantially no signal energy (e.g., associated with the signal to be received) in channels 6, 7, 11, 12, and 14. Analyzer 620 may segment and downconvert each segment to generate 15 baseband segments 645, each representing a portion (e.g., 3 MHz) of the 45 MHz bandwidth, and each having a baseband frequency range of 0-3 MHz. Mapper 650 may map the baseband segments 645 corresponding to channel set 615 to (e.g., a first 10) synthesizer channels 690, and may map null waveforms to other synthesizer channels 690 (e.g., synthesizer channels 690 other than the first 10). Mapper 650 may map the baseband segments 645 from analyzer 620 in order, or mapper 650 may map the baseband segments 645 in a scrambled order. For example, mapper 650 may map baseband segments 1-5 to synthesizer channels 5-9, baseband segments 8-10 to synthesizer channels 2-4, baseband segment 13 to synthesizer channel 1, and baseband segment 15 to synthesizer channel 10. Synthesizer 660 may upconvert the mapped segments to frequencies corresponding to a width of channels of the system bandwidth and combine the

upconverted segments to obtain a second wideband waveform 675. In this example, second wideband waveform 675 may have a bandwidth of 30 MHz.

Receiver 600 may identify a new channel set 615 for a second time period (e.g., a second pulse period), and may perform the segmenting, downconverting, mapping, upconverting, and combining to generate a second wideband waveform 675 for the second time period. New channel set 615 may be different than the channel set 615 for the first pulse period and may or may not have any channels in common with the previous channel set 615. For example, new channel set 615 may have the same or a different number of channels. It should be understood that this example is provided for the sake of clarity, and other system bandwidths and channel bandwidths are contemplated without deviating from the scope of the application. For example, the system bandwidth may be 240 MHz, and the system may have 80 channels where each channel has a 3 MHz channel bandwidth. Channel set 615 may have up to 51 channels in each pulse period and thus first wideband waveform 610 may have a bandwidth of up to 240 MHz while second wideband waveform 675 may have a bandwidth of up to 153 MHz (e.g., the system bandwidth).

In some cases, receiver 600 may include multiple antennas 605, each of which may receive a transmission from a transmitter, such as transmitter 200 described with reference to FIG. 2. The output of each antenna 605 may be processed using beamforming techniques to recover a set of segments and nulls that corresponds to one of the component versions of the waveform transmitted by the transmitter 200. Segments and nulls can then be combined such that a single set of segments and nulls corresponding to the received transmission is provided as an input to the mapper 650. In one example, the beamforming techniques and combining can be applied to the outputs of the analyzer 620, as described with reference to the example of FIG. 9. As another example, the beamforming techniques and combining can be applied to the sets of segments and nulls within the analyzer 620 (e.g., as output by the segmenter 625).

FIG. 7 illustrates an example of a portion of a transmitter 700 that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. In some examples, transmitter 700 may implement aspects of wireless communication system 100 or transmitter 200. As described herein, transmitter 700 may be configured to beamform channels of a wideband waveform during synthesis of the wideband waveform rather than beamforming the wideband waveform after it is generated. In some examples, transmitter 700 may be coupled with the outputs of mapper 250 described with reference to FIG. 2. In some cases, modulator 220, analyzer 230, mapper 250, and transmitter 700 may collectively implement a beamforming transmitter.

In some cases, transmitter 700 may receive an indication of a number K of antennas 740 that may be used for transmissions. Replicator 710 may be configured to receive mapped segments 705 (and, optionally, null segments) from a mapper, such as from mapper 250 of FIG. 2, and to generate K copies 715 of each mapped segment 705 (e.g., corresponding to the K antennas 740) to generate K sets of copies 715.

Transmitter 700 includes beamformer 720, which may include multiple component beamformers 722 (e.g., K beamformers 722-a, 722-b, 722-c, . . . 722-k) for beamforming each of the copies 715 of each mapped segment 705. In some cases, each component beamformer 722 generates multiple component segments 725 by applying beamform-

ing coefficients **723** to one of the copies **715** of each mapped segment **705**. Each beamforming coefficient may, for example, include amplitude and/or phase components applied to the copy **715** of the mapped segment **705**. Thus, where a mapper outputs M mapped segments **705**, beamformer **720** applies K respective sets of M beamforming coefficients **723** (e.g.,  $K \times M$  beamforming coefficients) to mapped segments **705** to generate  $K \cdot M$  component segments **725**. Alternatively, beamformer **720** may apply K respective sets of N beamforming coefficients **723** (e.g.,  $K \times N$  beamforming coefficients) to mapped segments **705** to generate  $K \cdot N$  component segments **725** (e.g., beamformer **720** may perform beamforming for mapped and null segments). In some cases, the respective sets of beamforming coefficients **723** are based on channel frequencies of the mapped segments **705**. In some cases, transmitter **700** may receive an indicator of the beamforming coefficients **723** and/or an indicator of the set of beamforming coefficients **723**, and may determine the respective sets of beamforming coefficients to be applied to the copies from the indicator of the set of beamforming coefficients and the channels for the mapping.

Transmitter **700** includes combiner **730**, which may include multiple component combiners **732** (e.g., K component combiners **732-a**, **732-b**, **732-c**, . . . **732-k**). Each component combiner **732** may combine the component segments **725** generated by a respective component beamformer **722** to generate a component wideband waveform **735**. In some cases, transmitter **700** may transmit each of the multiple component wideband waveforms **735** using a separate antenna **740**, which may result in a beamformed wideband waveform having signal energy in M channels of N total channels of a system bandwidth.

In some cases, transmitter **700** may include multiple transmitter backends **737** that includes hardware or software to implement additional processing on component wideband waveforms **735** before transmission using one or more antennas **740**. For example, the component wideband waveforms **735** may be upconverted to passband before transmission.

FIG. **8** illustrates channel beamforming synthesizer **800** that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. In some examples, channel beamforming synthesizer **800** may implement aspects of wireless communication system **100**, transmitter **200**, and/or transmitter **700**. Channel beamforming synthesizer **800** may be configured to beamform a slice (e.g., a channel) of a wideband waveform during synthesis of the wideband waveform rather than beamforming the wideband waveform after it is generated, as described herein.

Channel beamforming synthesizer **800** includes a channel beamformer **820**, which may include a set of channel component beamformers **822** (e.g., K channel component beamformers **822-a**, **822-b**, . . . **822-k**) and a channel synthesizer **830**, which may include a set of channel component synthesizers **832** (e.g., K channel component synthesizers **832-a**, **832-b**, . . . **832-k**). In some cases, there may be one such channel beamforming synthesizer **800** for each channel of a system bandwidth (e.g., each of N channels). Alternatively, a transmitter may have M channel beamforming synthesizers **800**, where M may be a number (e.g., maximum number) of channels for which a channelized beamformed signal may use for each transmission (e.g., each pulse period). Each channel component beamformer **822** may be configured to receive a mapped segment **805** and apply a beamforming coefficient **815**. Thus, channel beam-

former **820** may apply K coefficients to the mapped segment **805** to obtain K component segments **825** (e.g., component segments **825-a**, **825-b**, . . . **825-k**).

Channel beamforming synthesizer **800** depicts a relatively simple form of a beamformer in which an incoming signal **805** is multiplied by a single complex coefficient. In other examples, a channel beamforming synthesizer may be implemented using an FIR filter structure, in which time taps and coefficient multiplies may provide an appropriate phase-shifting operation over a wider band of frequencies than the simple multiplication depicted in FIG. **8**.

Channel synthesizer **830** may receive the component segments **825** and output component channel waveforms **835** (e.g., K component channel waveforms **835-a**, **835-b**, . . . , **835-k**). For example, each channel component synthesizer **832** may perform interpolation, image rejection, and upconversion to generate component channel waveforms **835** that are upconverted to the channel bandwidth associated with the mapped segment. In some examples, component channel waveforms **835** from different channel beamforming synthesizers **800** may be combined into a wideband waveform and transmitted via an antenna. In some cases, channel component synthesizers **832** and a component combiner (not shown) may be implemented as a polyphase filter and inverse DFT.

FIG. **9** illustrates an example of a portion of a receiver **900** that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. In some examples, receiver **900** may implement aspects of wireless communication system **100** or receiver **600**. In some examples, outputs of receiver **900** may serve as the inputs to synthesizer **660** described with reference to FIG. **6**. In some cases, receiver **900**, synthesizer **660**, and demodulator **685** may collectively implement a beamforming receiver.

Receiver **900** may receive, using K antennas **905**, K component wideband waveforms **910**. Receiver **900** includes segmenter **915**, which may include multiple component segmenters **917** (e.g., K segmenters **917-a**, **917-b**, **917-c**, . . . **917-k**) for separating each of the component wideband waveforms **910** into a corresponding set of component segments **920**. Each component segment **920** may be associated with a corresponding channel of the system bandwidth. Each segmenter **917** may be an example of a segmenter **625** as described with reference to FIG. **6**.

In some cases, receiver **900** may include a receiver frontend **907** that includes hardware or software to process signals received using antenna(s) **905** to generate component wideband waveforms **910**. For example, receiver frontend **907** may filter the received signals, mix the signals, perform analog-to-digital conversion, and/or perform other processing.

Receiver **900** may include downconverter **925**, which may include multiple component downconverters **927** (e.g., K downconverters **927-a**, **927-b**, **927-c**, . . . **927-k**) to downconvert respective component segments **920** to component baseband segments **930**. For example, component segments **920** may each be associated with different frequency ranges and downconverter **927** may downconvert each component segment **920** to a baseband frequency range. Each downconverter **927** may be an example of a downconverter **630** as described with reference to FIG. **6**.

In some cases, segmenter **915** and downconverter **925** may be collectively referred to as an analyzer, which may be an example of an analyzer **620** as described with reference to FIG. **6**.

Receiver **900** includes beam combiner **935**, which may include multiple component beam combiners **937** (e.g., **K** component beam combiners **937-a**, **937-b**, **937-c**, . . . **937-k**). Beam combiner **935** may apply beamforming coefficients **936** to component baseband segments **930** generated by downconverters **927** and combine component segments associated with the same corresponding channel to generate beamformed component segments **940**. In some cases, **K** component baseband segments corresponding to each of **M** channels are combined by beam combiners **937** to produce the **M** segments of the wideband waveform originated by the transmitter. In some cases, beam combiner **935** may implement an inverse of the beamforming performed by beamformer **720** described with reference to FIG. 7.

In some cases, beam combiner **935** may implement an inverse of the beamforming performed by beamformer **720** described with reference to FIG. 7.

In some cases, beamformed component segments **940** may be provided to a de-mapper **945** that is configured to de-map the beamformed component segments **940** from the corresponding channels. In some cases, de-mapper **945** may be the same as mapper **650** described with reference to FIG. 6, and may perform an inverse of the mapping performed by mapper **650**.

FIG. 10 shows a diagram of a system **1000** including a device **1005** that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. The device **1005** may include components for bi-directional communications of wideband waveforms including components for transmitting and receiving communications, including a processor **1010**, an I/O controller **1015**, a transceiver **1020**, an antenna **1025**, and memory **1030**. These components may be in electronic communication via one or more buses (e.g., bus **1040**).

The processor **1010** may include an intelligent hardware device, (e.g., a general-purpose processor, a DSP, a CPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, the processor **1010** may be configured to operate a memory array using a memory controller. In other cases, a memory controller may be integrated into the processor **1010**. The processor **1010** may be configured to execute computer-readable instructions stored in a memory (e.g., memory **1030**) to cause the device **1005** to perform various functions (e.g., functions or tasks supporting channelizing and beamforming a wideband waveform).

The I/O controller **1015** may manage input and output signals for the device **1005**. The I/O controller **1015** may also manage peripherals not integrated into the device **1005**. In some cases, the I/O controller **1015** may represent a physical connection or port to an external peripheral. In some cases, the I/O controller **1015** may utilize an operating system such as iOS®, ANDROID®, MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system. In other cases, the I/O controller **1015** may represent or interact with a modem, a keyboard, a mouse, a touchscreen, or a similar device. In some cases, the I/O controller **1015** may be implemented as part of a processor. In some cases, a user may interact with the device **1005** via the I/O controller **1015** or via hardware components controlled by the I/O controller **1015**.

The transceiver **1020** may communicate bi-directionally, via one or more antennas, wired, or wireless links as described above. For example, the transceiver **1020** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The trans-

ceiver **1020** may also include a modem to modulate signals and provide the modulated signals to the antennas for transmission, and to demodulate signals received from the antennas.

In some cases, the wireless device may include a single antenna **1025**. However, in some cases the device **1005** may have more than one antenna **1025**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions.

The memory **1030** may include RAM and ROM. The memory **1030** may store computer-readable, computer-executable code **1035** including instructions that, when executed, cause the processor to perform various functions described herein. In some cases, the memory **1030** may contain, among other things, a BIOS which may control basic hardware or software operation such as the interaction with peripheral components or devices.

The code **1035** may include instructions to implement aspects of the present disclosure, including instructions to support methods for transmitting and/or receiving channelized and beamformed wideband waveforms as described herein. For example, the code **1035** may include instructions for performing (e.g., by the processor **1010** and/or the transceiver **1020**) the functions of the modulator **210**, the analyzer **230** or **620**, the mapper **250** or **650**, the synthesizer **255** or **660**, and/or the demodulator **685**. The code **1035** may be stored in a non-transitory computer-readable medium such as system memory or other type of memory. In some cases, the code **1035** may not be directly executable by the processor **1010** but may cause a computer (e.g., when compiled and executed) to perform functions described herein.

The device **1005** may include channelizing manager **1045**. Channelizing manager **1045** may generate multiple segments of a first wideband waveform and map the segments to corresponding channels, each of which may have a respective channel bandwidth. Channelizing manager **1045** may generate multiple copies of each segment, where each copy of a respective segment is associated with a corresponding antenna of multiple antennas for a transmission.

The device **1005** may include beamforming manager **1050**. Beamforming manager **1050** may apply respective sets of beamforming coefficients to the copies for the mapped segments to obtain multiple component segments for each of the mapped segments, where the respective sets of beamforming coefficients for the mapped segments are based on channels of the multiple channels for the mapping. Beamforming manager **1050** may combine the component segments associated with each of the antennas into respective component wideband waveforms.

FIG. 11 shows a flowchart illustrating a method **1100** that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. The operations of method **1100** may be implemented by a transmitter or its components as described herein. For example, the operations of method **1100** may be performed by a transmitter as described with reference to FIGS. 2 and 7. In some examples, a transmitter may execute a set of instructions to control the functional elements of the transmitter to perform the described functions. Additionally or alternatively, a transmitter may perform aspects of the described functions using special-purpose hardware, programmable logic, or other means.

At **1105**, the transmitter may generate a set of segments of a first wideband waveform. The operations of **1105** may be performed according to the methods described herein. In

some examples, aspects of the operations of **1105** may be performed by a segmenter as described with reference to FIGS. **2** and **7**.

At **1110**, the transmitter may map the set of segments to a set of channels, where each of the set of channels has a respective channel bandwidth. The operations of **1110** may be performed according to the methods described herein. In some examples, aspects of the operations of **1110** may be performed by a mapper as described with reference to FIGS. **2** and **7**.

At **1115**, the transmitter may generate a set of copies of each segment of the set of mapped segments, where each copy of a respective segment is associated with a corresponding antenna of a set of antennas for a transmission. The operations of **1115** may be performed according to the methods described herein. In some examples, aspects of the operations of **1115** may be performed by a replicator as described with reference to FIG. **7**.

At **1120**, the transmitter may apply respective sets of beamforming coefficients to the set of copies for the mapped set of segments to obtain a set of component segments for each of the mapped set of segments, where the respective sets of beamforming coefficients for the mapped set of segments are based on channels of the set of channels for the mapping. The operations of **1120** may be performed according to the methods described herein. In some examples, aspects of the operations of **1120** may be performed by a beamformer as described with reference to FIG. **7**.

At **1125**, the transmitter may combine the component segments associated with each of the set of antennas into respective component wideband waveforms. The operations of **1125** may be performed according to the methods described herein. In some examples, aspects of the operations of **1125** may be performed by a combiner as described with reference to FIGS. **2** and **7**.

At **1130**, the transmitter may transmit each of the respective component wideband waveforms via a separate antenna of the set of antennas for the transmission. The operations of **1130** may be performed according to the methods described herein. In some examples, aspects of the operations of **1130** may be performed by a transceiver and antennas as described with reference to FIG. **10**.

FIG. **12** shows a flowchart illustrating a method **1200** that supports channelizing and beamforming a wideband waveform in accordance with aspects of the present disclosure. The operations of method **1200** may be implemented by a receiver or its components as described herein. For example, the operations of method **1200** may be performed by a receiver as described with reference to FIGS. **6** and **9**. In some examples, a receiver may execute a set of instructions to control the functional elements of the receiver to perform the described functions. Additionally or alternatively, a receiver may perform aspects of the described functions using special-purpose hardware.

At **1205**, the receiver may receive a set of component wideband waveforms via a set of antennas, where each component wideband waveform is received via a separate antenna of the set of antennas. The operations of **1205** may be performed according to the methods described herein. In some examples, aspects of the operations of **1205** may be performed by a transceiver and antennas as described with reference to FIG. **10**.

At **1210**, the receiver may separate each component wideband waveform of the set of component wideband waveforms into a corresponding set of component segments, each segment associated with a corresponding channel of a set of channels. The operations of **1210** may be performed

according to the methods described herein. In some examples, aspects of the operations of **1210** may be performed by a segmenter as described with reference to FIGS. **6** and **9**.

At **1215**, the receiver may apply respective sets of beamforming coefficients to the component segments. The operations of **1215** may be performed according to the methods described herein. In some examples, aspects of the operations of **1215** may be performed by a beam combiner as described with reference to FIG. **9**.

At **1220**, the receiver may combine the beamformed component segments. The operations of **1220** may be performed according to the methods described herein. In some examples, aspects of the operations of **1220** may be performed by a beam combiner as described with reference to FIG. **9**.

It should be noted that the methods described herein describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Further, aspects from two or more of the methods may be combined.

What is claimed is:

**1.** A method, comprising:

generating a plurality of segments of a first wideband waveform;

mapping the plurality of segments to a plurality of channels, wherein each of the plurality of channels has a respective channel bandwidth;

generating a plurality of copies of each segment of the plurality of mapped segments, wherein each copy of a respective segment is associated with a corresponding antenna of a plurality of antennas for a transmission;

applying respective sets of beamforming coefficients to the plurality of copies for the mapped plurality of segments to obtain a plurality of component segments for each of the mapped plurality of segments, wherein the respective sets of beamforming coefficients for the mapped plurality of segments are based at least in part on channels of the plurality of channels for the mapping;

combining the component segments associated with each of the plurality of antennas into respective component wideband waveforms; and

transmitting each of the respective component wideband waveforms via a separate antenna of the plurality of antennas for the transmission.

**2.** The method of claim **1**, further comprising:

downconverting the plurality of segments to a baseband frequency range before mapping the plurality of segments to the plurality of channels.

**3.** The method of claim **1**, further comprising:

receiving an indicator of a set of beamforming coefficients; and

determining the respective sets of beamforming coefficients from the indicator of the set of beamforming coefficients and the channels of the plurality of channels for the mapping.

**4.** The method of claim **1**, wherein the plurality of channels comprises a subset of a total set of channels of a system bandwidth that are available for the transmitting.

**5.** The method of claim **4**, wherein the subset of the total set of channels is a non-contiguous subset of the total set of channels.

**6.** The method of claim **1**, wherein transmitting each of the respective component wideband waveforms comprises: transmitting each of the respective component wideband waveforms using a tactical data link.

21

7. A method, comprising:  
 receiving a plurality of component wideband waveforms via a plurality of antennas, wherein each component wideband waveform is received via a separate antenna of the plurality of antennas;  
 separating each component wideband waveform of the plurality of component wideband waveforms into a corresponding plurality of component segments, each segment associated with a corresponding channel of a plurality of channels;  
 applying respective sets of beamforming coefficients to the component segments; and  
 combining component segments associated with the same corresponding channel to generate beamformed component segments.

8. The method of claim 7, further comprising:  
 downconverting the component segments before applying the respective sets of beamforming coefficients to the component segments.

9. The method of claim 7, further comprising:  
 de-mapping the beamformed component segments from the corresponding channels of the plurality of channels.

10. The method of claim 9, further comprising:  
 receiving an indicator of a set of beamforming coefficients; and  
 determining the respective sets of beamforming coefficients from the indicator of the set of beamforming coefficients and the corresponding channels of the plurality of channels for the de-mapping.

11. A method, comprising:  
 receiving a plurality of component wideband waveforms via a plurality of antennas, wherein each component wideband waveform is received via a separate antenna of the plurality of antennas;  
 separating each component wideband waveform of the plurality of component wideband waveforms into a corresponding plurality of component segments, each segment associated with a corresponding channel of a plurality of channels;  
 applying respective sets of beamforming coefficients to the component segments; and combining the beamformed component segments,  
 wherein the corresponding channels comprise a subset of a total set of channels of a system bandwidth that are available for the transmitting.

12. The method of claim 11, wherein the subset of the total set of channels is a non-contiguous subset of the total set of channels.

13. A method, comprising:  
 receiving a plurality of component wideband waveforms via a plurality of antennas, wherein each component wideband waveform is received via a separate antenna of the plurality of antennas;  
 separating each component wideband waveform of the plurality of component wideband waveforms into a corresponding plurality of component segments, each segment associated with a corresponding channel of a plurality of channels;  
 applying respective sets of beamforming coefficients to the component segments; and combining the beamformed component segments,  
 wherein receiving each of the respective component wideband waveforms comprises:  
 receiving the respective component wideband waveforms using a tactical data link.

22

14. The method of claim 13, wherein the respective component wideband waveforms are transmitted by a single transmitter associated with a network of the tactical data link.

15. The method of claim 14, further comprising:  
 receiving, from a second single transmitter from a second network of the tactical data link, a second plurality of component wideband waveforms via the plurality of antennas, wherein each component wideband waveform of the second plurality of component wideband waveforms is received via a separate antenna of the plurality of antennas;  
 separating each component wideband waveform of the second plurality of component wideband waveforms into a corresponding second plurality of component segments, each segment of the second plurality of component segments associated with a corresponding channel of a second plurality of channels;  
 applying respective second sets of beamforming coefficients to the component segments of the second plurality of component segments; and  
 combining the beamformed component segments of the second plurality of component segments.

16. An apparatus, comprising:  
 a modulator configured to generate a first wideband waveform;  
 an analyzer coupled with the modulator and configured to receive the first wideband waveform and generate a plurality of segments of a first wideband waveform, each segment having a same bandwidth;  
 a mapper configured to map the plurality of segments to a plurality of channels;  
 a replicator configured to generate a plurality of copies of each segment of the plurality of mapped segments, wherein each copy of a respective segment is associated with a corresponding antenna of a plurality of antennas for a transmission;  
 a plurality of beamformers configured to apply respective sets of beamforming coefficients to the sets of copies for the mapped plurality of segments to obtain a plurality of component segments for each of the mapped plurality of segments, wherein the respective sets of beamforming coefficients for the mapped plurality of segments are based at least in part on channels of the plurality of channels for the mapping;  
 a plurality of combiners, each combiner coupled with a beamformer of the plurality of beamformers and configured to combine the component segments associated with a respective antenna of the plurality of antennas into respective component wideband waveforms; and  
 a transmitter backend coupled with the combiner and configured to transmit the transmission by transmitting each of the respective component wideband waveforms via a separate antenna of the plurality of antennas.

17. The apparatus of claim 16, wherein each beamformer is configured to downconvert the plurality of segments to a baseband frequency range.

18. The apparatus of claim 16, further comprising:  
 a beamforming coefficient processor coupled with the plurality of beamformers and configured to receive an indicator of a set of beamforming coefficients and determine the respective sets of beamforming coefficients from the indicator of the set of beamforming coefficients and the channels of the plurality of channels for the mapping.

23

19. The apparatus of claim 16, wherein the plurality of channels comprises a subset of a total set of channels of a system bandwidth that are available for the transmitting.

20. The apparatus of claim 19, wherein the subset of the total set of channels is a non-contiguous subset of the total set of channels.

21. The apparatus of claim 16, wherein the transmitter backend is configured to transmit each of the respective component wideband waveforms by transmitting each of the respective component wideband waveforms using a tactical data link.

22. An apparatus, comprising:

a receiver frontend configured to receive a plurality of component wideband waveforms via a plurality of antennas, wherein each component wideband waveform is received via a separate antenna of the plurality of antennas;

a plurality of analyzers coupled with the receiver frontend, each analyzer configured to separate a respective component wideband waveform of the plurality of component wideband waveforms into a corresponding plurality of component segments, each component segment associated with a corresponding channel of a plurality of channels; and

a plurality of beam combiners coupled with the plurality of analyzers, each beam combiner configured to apply a respective set of beamforming coefficients to respective component segments and combine component segments associated with the same corresponding channel to generate beamformed component segments.

23. The apparatus of claim 22, wherein each analyzer comprises a downconverting filter to downconvert respective component segments.

24. The apparatus of claim 22, further comprising:

a de-mapper coupled with the plurality of beam combiners and configured to de-map the beamformed component segments from the corresponding channels of the plurality of channels.

25. The apparatus of claim 24, wherein the beam combiner is configured to receive an indicator of a set of beamforming coefficients and determine the respective sets

24

of beamforming coefficients from the indicator of the set of beamforming coefficients and the corresponding channels of the plurality of channels for the de-mapping.

26. The apparatus of claim 22, wherein the corresponding channels comprise a subset of a total set of channels of a system bandwidth that are available for the transmitting.

27. The apparatus of claim 26, wherein the subset of the total set of channels is a non-contiguous subset of the total set of channels.

28. The apparatus of claim 22, wherein the receiver frontend is configured to receive each of the respective component wideband waveforms using a tactical data link.

29. The apparatus of claim 28, wherein the respective component wideband waveforms are transmitted by a single transmitter associated with a network of the tactical data link.

30. The apparatus of claim 29, wherein:

the receiver frontend is configured to receive, from a second single transmitter from a second network of the tactical data link, a second plurality of component wideband waveforms via the plurality of antennas, wherein each component wideband waveform of the second plurality of component wideband waveforms is received via a separate antenna of the plurality of antennas;

each analyzer is configured to separate each component wideband waveform of the second plurality of component wideband waveforms into a corresponding second plurality of component segments, each segment of the second plurality of component segments associated with a corresponding channel of a second plurality of channels; and

each beam combiner is configured to apply a respective second set of beamforming coefficients to the component segments of the second plurality of component segments and combine the beamformed component segments of the second plurality of component segments.

\* \* \* \* \*