

(12) **United States Patent**  
**Yang**

(10) **Patent No.:** **US 10,950,609 B2**  
(45) **Date of Patent:** **Mar. 16, 2021**

(54) **GATE-ALL-AROUND (GAA) AND FIN FIELD-EFFECT TRANSISTOR (FINFET) HYBRID STATIC RANDOM-ACCESS MEMORY (SRAM)**

(71) Applicant: **QUALCOMM Incorporated**, San Diego, CA (US)

(72) Inventor: **Haining Yang**, San Diego, CA (US)

(73) Assignee: **QUALCOMM Incorporated**, San Diego, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/511,153**

(22) Filed: **Jul. 15, 2019**

(65) **Prior Publication Data**

US 2021/0020643 A1 Jan. 21, 2021

(51) **Int. Cl.**

- H01L 27/11** (2006.01)
- H01L 27/092** (2006.01)
- H01L 29/78** (2006.01)
- H01L 29/423** (2006.01)
- H01L 29/786** (2006.01)
- H01L 29/06** (2006.01)

(52) **U.S. Cl.**

- CPC ..... **H01L 27/1108** (2013.01); **H01L 27/0922** (2013.01); **H01L 27/0924** (2013.01); **H01L 29/0673** (2013.01); **H01L 29/42392** (2013.01); **H01L 29/7851** (2013.01); **H01L 29/78696** (2013.01)

(58) **Field of Classification Search**

None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 8,580,624 B2 \* 11/2013 Bangsaruntip ..... B82Y 10/00 257/351
- 9,219,064 B2 \* 12/2015 Kim ..... H01L 27/092
- 10,332,881 B1 \* 6/2019 Badaroglu ..... H01L 21/823437
- 2009/0289304 A1 \* 11/2009 Pouydebasque .... H01L 27/1211 257/351

(Continued)

OTHER PUBLICATIONS

Kaushal, G., Jeong, H., Maheshwaram, S., Manhas, S.K., Dasgupta, S. And Jung, S.O., "Low power SRAM design for 14nmn GAA Si-nanowire technology", Microelectronics Journal, vol. 46, Issue 12, Part A, (2015), pp. 1239-1247. (Year: 2015).\*

(Continued)


Primary Examiner — J. E. Schoenholtz

(74) Attorney, Agent, or Firm — Patterson & Sheridan, LLP

(57) **ABSTRACT**

Certain aspects of the present disclosure generally relate to a static random-access memory (SRAM) implemented using both a gate-all-around (GAA)-type transistor and a fin field-effect transistor (FinFET). For example, certain aspects are directed to an SRAM memory cell having a flip-flop (FF) having a pull-up (PU) transistor and a pull-down (PD) transistor, and a pass-gate (PG) transistor coupled between a bit line of the SRAM memory cell and the FF, a gate of the PG transistor being coupled to a word line (WL) of the SRAM memory cell. In certain aspects, at least one of the PU transistor, the PD transistor, or the PG transistor comprises a GAA transistor, and at least another one of the PU transistor, the PD transistor, or the PG transistor comprises a FinFET.

**16 Claims, 7 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2014/0153323 A1\* 6/2014 Liaw ..... G11C 11/412  
365/156  
2016/0043092 A1\* 2/2016 Mojumder ..... H01L 29/1054  
257/369  
2017/0221905 A1\* 8/2017 Chen ..... H01L 27/11582  
2018/0233570 A1\* 8/2018 Hellings ..... H01L 29/165  
2019/0081049 A1\* 3/2019 Zang ..... H01L 29/42392  
2020/0106441 A1\* 4/2020 Liaw ..... H01L 27/0924  
2020/0135740 A1\* 4/2020 Liaw ..... H01L 29/1033

OTHER PUBLICATIONS

Shin, C., "Advanced MOSFET Design and Implication for SRAM Scaling", Diss, University of California, Electrical Engineering and Computer Sciences, Spring 2011. (Year: 2011).\*

Dani, L., Singh, G., Kaur, M., "FinFET based 6T SRAM Cell for Nanoscaled Technologies", Internal Journal of Computer Applications (0975-8887), vol. 127, No. 13, pp. 5-10, Oct. 2015. (Year: 2015).\*

Yang, C.K., "SRAM Cell, Noise Margin, and Noise", University of California at Los Angeles, EE215B.\*

Zheng, P., Liao, Y.B., Damrongsplasit, N., Chiang, M.H., Liu, T.S. King, "Variation Aware Comparative Study of 10 nm GAA verses FinFET 6-t SRAM Performance and Yield", IEEE Transactions on Electron Devices, vol. 61, No. 12, pp. 3949-3954 Dec. 2014 (Year: 2014).\*

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B

**GATE-ALL-AROUND (GAA) AND FIN  
FIELD-EFFECT TRANSISTOR (FINFET)  
HYBRID STATIC RANDOM-ACCESS  
MEMORY (SRAM)**

TECHNICAL FIELD

Certain aspects of the present disclosure generally relate to electronic components and, more particularly, to a static random-access memory (SRAM).

BACKGROUND

Transistors are essential components in modern electronic devices. Large numbers of transistors are employed in integrated circuits (ICs) in many modern electronic devices. For example, components such as central processing units (CPUs) and memory systems each employ a large quantity of transistors for logic circuits and memory devices.

As electronic devices become more complex in functionality, so does the need to include a greater number of transistors in such devices. However, as electronic devices are provided in increasingly smaller packages, such as in mobile devices, for example, a greater number of transistors may be provided in a smaller IC chip. This increase in the number of transistors is achieved in part through continued efforts to miniaturize transistors in ICs.

SUMMARY

Certain aspects of the present disclosure generally relate to a static random-access memory (SRAM) implemented using both a gate-all-around (GAA)-type transistor and a fin field-effect transistor (FinFET).

Certain aspects are directed to an SRAM memory cell. The SRAM memory cell generally includes a flip-flop (FF) having a pull-up (PU) transistor and a pull-down (PD) transistor, and a pass-gate (PG) transistor coupled between a bit line (BL) of the SRAM memory cell and the FF, a gate of the PG transistor being coupled to a word line (WL) of the SRAM memory cell. In certain aspects, at least one of the PU transistor, PD transistor, or PG transistor comprises a GAA transistor, and at least another one of the PU transistor, the PD transistor, or the PG transistor comprises a FinFET.

Certain aspects are directed to an SRAM. The SRAM generally includes a plurality of memory cells, each of the plurality of memory cells comprising a FF having a PU transistor and a PD transistor, and a PG transistor coupled between a BL of the SRAM and the FF, a gate of the PG transistor being coupled to one of a plurality of WLS of the SRAM. In certain aspects, at least one of the PU transistor, the PD transistor, or the PG transistor comprises a GAA transistor, and at least another one of the PU transistor, the PD transistor, or the PG transistor comprises a FinFET.

BRIEF DESCRIPTION OF THE DRAWINGS

So that the manner in which the above-recited features of the present disclosure can be understood in detail, a more particular description, briefly summarized above, may be by reference to aspects, some of which are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrate only certain typical aspects of this disclosure and are therefore not to be considered limiting of its scope, for the description may admit to other equally effective aspects.

FIG. 1 illustrates example components and interconnections in a system-on-chip (SoC) suitable for implementing various aspects of the present disclosure.

FIG. 2 illustrates a memory cell of a static random access memory (SRAM), in accordance with certain aspects of the present disclosure.

FIGS. 3A, 3B, 3C, and 3D are cross-sectional views of an example gate-all-around (GAA) transistor and illustrate example operations for fabricating the GAA transistor.

FIGS. 4A and 4B are top and cross-sectional views, respectively, of an example SRAM having pass-gate (PG) and pull-down (PD) transistors implemented as GAA transistors and a pull-up (PU) transistor implemented as a fin field-effect transistor (FinFET), in accordance with certain aspects of the present disclosure.

FIGS. 5A and 5B are top and cross-sectional views, respectively, of an example SRAM having a PD transistor implemented as a GAA transistor and PU and PG transistors implemented as FinFETs, in accordance with certain aspects of the present disclosure.

FIGS. 6A and 6B are a top and cross-sectional views, respectively, of an example SRAM having PD and PU transistors implemented as GAA transistors and a PG transistor implemented as a FinFET, in accordance with certain aspects of the present disclosure.

FIGS. 7A and 7B are top and cross-sectional views, respectively, of an example SRAM having PG and PU transistors implemented as GAA transistors and a PD transistor implemented as a FinFET, in accordance with certain aspects of the present disclosure.

DETAILED DESCRIPTION

The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any aspect described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects.

As used herein, the term “connected with” in the various tenses of the verb “connect” may mean that element A is directly connected to element B or that other elements may be connected between elements A and B (i.e., that element A is indirectly connected with element B). In the case of electrical components, the term “connected with” may also be used herein to mean that a wire, trace, or other electrically conductive material is used to electrically connect elements A and B (and any components electrically connected therebetween).

The detailed description set forth below in connection with the appended drawings is intended as a description of various configurations and is not intended to represent the only configurations in which the concepts described herein may be practiced. The detailed description includes specific details for the purpose of providing a thorough understanding of various concepts. However, it will be apparent to those skilled in the art that these concepts may be practiced without these specific details. In some instances, well-known structures and components are shown in block diagram form in order to avoid obscuring such concepts.

The various aspects will be described in detail with reference to the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts. References made to particular examples and implementations are for illustrative purposes, and are not intended to limit the scope of the disclosure or the claims.

The terms “computing device” and “mobile device” are used interchangeably herein to refer to any one or all of

servers, personal computers, smartphones, cellular telephones, tablet computers, laptop computers, netbooks, ultra-books, palm-top computers, personal data assistants (PDAs), wireless electronic mail receivers, multimedia Internet-enabled cellular telephones, Global Positioning System (GPS) receivers, wireless gaming controllers, and similar personal electronic devices which include a programmable processor. While the various aspects are particularly useful in mobile devices (e.g., smartphones, laptop computers, etc.), which have limited resources (e.g., processing power, battery, size, etc.), the aspects are generally useful in any computing device that may benefit from improved processor performance and reduced energy consumption.

The term “multicore processor” is used herein to refer to a single integrated circuit (IC) chip or chip package that contains two or more independent processing units or cores (e.g., CPU cores, etc.) configured to read and execute program instructions. The term “multiprocessor” is used herein to refer to a system or device that includes two or more processing units configured to read and execute program instructions.

The term “system on chip” (SoC) is used herein to refer to a single integrated circuit (IC) chip that contains multiple resources and/or processors integrated on a single substrate. A single SoC may contain circuitry for digital, analog, mixed-signal, and radio-frequency functions. A single SoC may also include any number of general purpose and/or specialized processors (digital signal processors (DSPs), modem processors, video processors, etc.), memory blocks (e.g., ROM, RAM, flash, etc.), and resources (e.g., timers, voltage regulators, oscillators, etc.), any or all of which may be included in one or more cores.

FIG. 1 illustrates example components and interconnections in a system-on-chip (SoC) **100** suitable for implementing various aspects of the present disclosure. The SoC **100** may include a number of heterogeneous processors, such as a processor **102** (e.g., central processing unit (CPU)), a modem processor **104**, a graphics processor **106**, and an application processor **108**. Each processor **102**, **104**, **106**, **108**, may include one or more cores, and each processor/core may perform operations independent of the other processors/cores. The processors **102**, **104**, **106**, **108** may be organized in close proximity to one another (e.g., on a single substrate, die, integrated chip, etc.) so that the processors may operate at a much higher frequency/clock rate than would be possible if the signals were to travel off-chip. The proximity of the cores may also allow for the sharing of on-chip memory and resources (e.g., voltage rails), as well as for more coordinated cooperation between cores.

The SoC **100** may include system components and resources **110** for managing sensor data, analog-to-digital conversions, and/or wireless data transmissions, and for performing other specialized operations (e.g., decoding high-definition video, video processing, etc.). System components and resources **110** may also include components such as voltage regulators, oscillators, phase-locked loops (PLLs), peripheral bridges, data controllers, system controllers, access ports, timers, and/or other similar components used to support the processors and software clients running on the computing device. The system components and resources **110** may also include circuitry for interfacing with peripheral devices, such as cameras, electronic displays, wireless communication devices, external memory chips, etc.

The SoC **100** may further include a Universal Serial Bus (USB) controller **112**, one or more memory controllers **114**, and a centralized resource manager (CRM) **116**. The SoC

**100** may also include an input/output module (not illustrated) for communicating with resources external to the SoC, each of which may be shared by two or more of the internal SoC components.

The processors **102**, **104**, **106**, **108** may be interconnected to the USB controller **112**, the memory controller **114**, system components and resources **110**, CRM **116**, and/or other system components via an interconnection/bus module **122**, which may include an array of reconfigurable logic gates and/or implement a bus architecture (e.g., CoreConnect, AMBA, etc.). Communications may also be provided by advanced interconnects, such as high performance networks on chip (NoCs).

The interconnection/bus module **122** may include or provide a bus mastering system configured to grant SoC components (e.g., processors, peripherals, etc.) exclusive control of the bus (e.g., to transfer data in burst mode, block transfer mode, etc.) for a set duration, number of operations, number of bytes, etc. In some cases, the interconnection/bus module **122** may implement an arbitration scheme to prevent multiple master components from attempting to drive the bus simultaneously.

The memory controller **114** may be a specialized hardware module configured to manage the flow of data to and from a memory **124** via a memory interface/bus **126**. In certain aspects of the present disclosure, the memory **124** may be a static random-access memory (SRAM). The SRAM may be implemented using both a gate-all-around (GAA)-type transistor and a fin field-effect transistor (FinFET), as described in more detail herein.

The memory controller **114** may comprise one or more processors configured to perform read and write operations with the memory **124**. Examples of processors include microprocessors, microcontrollers, digital signal processors (DSPs), field programmable gate arrays (FPGAs), programmable logic devices (PLDs), state machines, gated logic, discrete hardware circuits, and other suitable hardware configured to perform the various functionality described throughout this disclosure. In certain aspects, the memory **124** may be part of the SoC **100**.

Example Static Random Access Memory (SRAM)

FIG. 2 illustrates a memory cell **200** of a static random access memory (SRAM) (e.g., memory **124**), in accordance with certain aspects of the present disclosure. As illustrated, the memory cell **200** may be coupled to a word line (WL) **202** of the SRAM. The WL **202** is coupled to a control input of a pass gate (PG) transistor **206** for selectively coupling a bit line (BL) **210** of the SRAM to node N1 (also referred to as an output node) of a flip-flop (FF) **214**, and is coupled to a control input of a PG transistor **208** for selectively coupling the complementary bit line (BLB) **212** to node N2 (also referred to as a complementary output node) of the FF **214**. The PG transistor **206** and/or the PG transistor **208** may each be implemented using a metal-oxide-semiconductor (MOS) transistor of various types, such as a GAA-type transistor or a FinFET, as described in more detail herein.

As illustrated, the FF **214** is coupled between a voltage rail (V<sub>dd</sub>) and a reference potential node (e.g., electric ground or V<sub>ss</sub>). The FF **214** includes a pull-up (PU) transistor **220** (e.g., a p-type metal-oxide-semiconductor (PMOS) transistor) having a drain coupled to a drain of a pull-down (PD) transistor **222** (e.g., n-type metal-oxide-semiconductor (NMOS) transistor), forming part of node N1. The FF **214** also includes a PU transistor **226** having a drain coupled to a drain of a PD transistor **224**, forming part of node N2. The gates of the PU transistor **220** and the PD transistor **222** are coupled to the node N2, and the gates of

the PU transistor **226** and the PD transistor **224** are coupled to the node **N1**, as illustrated. The nodes **N1** and **N2** represent the output and complementary output nodes of the FF **214**, respectively.

During a read operation, the BL of the SRAM may be pre-charged to  $V_{dd}$ , and then the WL of the SRAM is selected. On the side of the memory cell storing a logical low, the BL may be discharged via a PG transistor and a PD transistor, so that a differential voltage develops between the BL and the BLB of the memory cell. The differential voltage should be large enough for a sense amplifier to detect the state of the cell. The differential voltage should not be too large, however; otherwise, the cross-coupled transistors (inverters) of the FF **214** could flip states, causing a read disturbance failure. A read disturbance failure may be caused by a weak PU transistor (e.g., PU transistors **220**, **226**) having insufficient drive current strength. A read failure may also occur if a PD transistor (e.g., PD transistors **222**, **224**) of the SRAM is weak (e.g., has low drive current strength).

During a write operation, the bit lines are driven to complementary voltage levels via a write driver, and then the word line is selected. On the side of the memory cell for which the bit line voltage is logic low, the storage node (e.g., **N1**) of the flip-flop is discharged through the PG transistor. The cross-coupled inverters raise the voltage on the opposite storage node and latch the cell. The discharging strength of the PG transistor should overcome the restoring strength of the PU transistor. Therefore, a write failure may occur if the PG transistor is weak.

The SRAM memory cell characteristics are impacted by the PU/PD transistor drive current strength ratio. As used herein, drive current strength generally refers to a transistor's capability to drive current (e.g., drain-to-source current ( $I_{ds}$ ) or source-to-drain current ( $I_{sd}$ )) to a specific node. SRAM functionality depends on the transistor drive current strength ratios, which may be referred to as alpha and beta ratios. The alpha ratio generally refers to the ratio of the drive current strength of the PD transistor over the drive current strength of the PG transistor. The beta ratio generally refers to the ratio of the drive current strength of the PU transistor over the drive current strength of the PG transistor.

To avoid the memory failures described herein, the drive current strength of the PD transistor should be higher than the drive current strength of the PG transistor, and the drive current strength of the PG transistor should be higher than the drive current strength of the PU transistor. To overcome fin field-effect transistor (FinFET) SRAM memory cell shortcomings, read/write assistance circuitry may be implemented, which increase SRAM area, especially when many small SRAM compiler instances are used in a design. Aspects of the present disclosure provide techniques for reducing memory failures while maintaining a relatively small SRAM footprint as compared to conventional implementations.

Complementary metal-oxide-semiconductor (CMOS) technology has scaled from planar transistor to FinFET, and may migrate to nano-sheet gate-all-around (GAA) devices. GAA devices may overcome FinFET device scaling restrictions with improved short channel effect, channel length reduction, and gate pitch reduction. GAA technology allows for an increase of drive current strength for the transistor with a larger effective device width. GAA drive current strength may be adjusted by changing the nano-sheet width (e.g., the width of channel slabs of the GAA device), as described in more detail herein.

Certain aspects of the present disclosure are directed to an SRAM memory cell implemented using both FinFET and

GAA transistors, allowing the SRAM to be realized with improved performance and/or higher density as compared to conventional implementations. For example, the SRAM memory cell may include a PD transistor implemented as a GAA transistor and a PU transistor implemented as a FinFET. As another example, the SRAM memory cell may include a PD transistor implemented as a GAA transistor with PG and PU transistors implemented as FinFETs. The GAA transistor provides flexibility to design an SRAM memory cell with improved drive current strength ratios, as described herein. On the other hand, FinFET technology allows for a low number of transistors to be implemented using a small area with little to no sacrifice of the drive current strength of the transistors. In other words, a FinFET device with a single fin may provide higher drive current strength as compared to GAA transistors given the same footprint.

FIGS. **3A**, **3B**, **3C**, and **3D** are cross-sectional views of an example GAA transistor and illustrate example operations for fabricating the GAA transistor. As illustrated in FIG. **3A**, first semiconductor layers **302**, **304**, **306** (e.g., silicon germanium (SiGe)) and second semiconductor layers **308**, **310**, **312** (e.g., silicon layers, also referred to herein as "channel slabs") may be formed using an epitaxial growth process, followed by a patterning of the silicon to form active regions. As illustrated in FIG. **3B**, the first semiconductor layers **302**, **304**, **306** may be removed in the GAA channel region. As illustrated in FIG. **3C**, high-k dielectric regions **320**, **322**, **324**, work function metal regions **330**, **332**, **334**, and metal gate region **340** may be formed all around the channel slabs of the GAA transistor. As illustrated in FIG. **3D**, a gate contact **350** may be formed for electrical connection to the metal gate region **340**.

FIGS. **4A** and **4B** are top and cross-sectional views, respectively, of an example SRAM having PG and PD transistors implemented as GAA transistors and a PU transistor implemented as a FinFET, in accordance with certain aspects of the present disclosure. For instance, the PD transistor **222** and PG transistor **206** may be implemented as GAA transistors, and the PU transistor **220** is implemented as a FinFET. The PD transistor **222** of FIG. **4B** is a cross-section taken through line B-B' in FIG. **4A**, the PG transistor **206** of FIG. **4B** is a cross-section taken through line A-A' in FIG. **4A**, and the PU transistor **220** of FIG. **4B** is a cross-section taken through line C-C' in FIG. **4A**. The PU transistor **220** is implemented as a FinFET due to the relatively small footprint of FinFETs as compared to GAA transistors given the same drive current strength.

The PD transistor **222** implemented as a GAA transistor may have wider channel slabs **402**, **404**, **406** as compared to the slabs **408**, **410**, **412** of the PG transistor **206**, such that the drive current strength of the PD transistor **222** is greater than the drive current strength of the PG transistor **206**. Moreover, the PU transistor **220** may be implemented as a FinFET having lower drive current strength than the PG transistor **206** and having a smaller footprint as compared to the PG transistor **206**.

FIGS. **5A** and **5B** are top and cross-sectional views, respectively, of an example SRAM having a PD transistor implemented as a GAA transistor and PU and PG transistors implemented as FinFETs, in accordance with certain aspects of the present disclosure. For instance, the PD transistor **222** may be implemented as a GAA transistor, while the PU transistor **220** and the PG transistor **206** may be implemented as FinFETs. The PG transistor **206** of FIG. **5B** is a cross-section taken through line A-A' in FIG. **5A**, the PD transistor **222** of FIG. **5B** is a cross-section taken through

line B-B' in FIG. 5A, and the PU transistor 220 of FIG. 5B is a cross-section taken through line C-C' in FIG. 5A. The PU transistor 220 and the PG transistor 206 are implemented as FinFETs due to the relatively small footprint of FinFETs as compared to GAA transistors given the same drive current strength. Thus, the PD transistor 222 may have a stronger drive current strength as compared to the PG transistor 206. In certain aspects, the PG transistor 206 may be implemented with a lower drive current strength as compared to the PU transistor.

FIGS. 6A and 6B are top and cross-sectional views, respectively, of an example SRAM having PD and PU transistors implemented as GAA transistors and a PG transistor implemented as a FinFET, in accordance with certain aspects of the present disclosure. For instance, the PD transistor 222 and the PU transistor 220 are implemented as GAA transistors, while the PG transistor 206 is implemented as a FinFET. The PG transistor 206 of FIG. 6B is a cross-section taken through line A-A' in FIG. 6A, the PD transistor 222 of FIG. 6B is a cross-section taken through line B-B' in FIG. 6A, and the PU transistor 220 of FIG. 6B is a cross-section taken through line C-C' in FIG. 6A. As illustrated, the PD transistor 222 is implemented with relatively wide slabs 702, 704, 706 (e.g., as compared to the PU transistor 220) such that the PD transistor 222 has a higher drive current strength as compared to PG transistor 206 implemented as a FinFET. The PU transistor 220 is implemented as a GAA transistor with relatively short slabs 710, 712, 714 (e.g., as compared to the PD transistor 222) such that the PU transistor 220 has a lower drive current strength as compared to the PG transistor 206 implemented as a FinFET.

FIGS. 7A and 7B are top and cross-sectional views, respectively, of an example SRAM having PG and PU transistors implemented as GAA transistors and a PD transistor implemented as a FinFET, in accordance with certain aspects of the present disclosure. For instance, the PG transistor 206 and the PU transistor 220 are implemented as GAA transistors, while the PD transistor 222 is implemented as a FinFET. The PG transistor 206 of FIG. 7B is a cross-section taken through line A-A' in FIG. 7A, the PD transistor 222 of FIG. 7B is a cross-section taken through line B-B' in FIG. 7A, and the PU transistor 220 of FIG. 7B is a cross-section taken through line C-C' in FIG. 7A. As illustrated, the PG transistor 206 and the PU transistor 220 are implemented as GAA transistors with short slab widths such that the drive current strength of the PG transistor 206 and the PU transistor 220 are less than the drive current strength of the PD transistor 222 implemented as a FinFET.

Within the present disclosure, the word “exemplary” is used to mean “serving as an example, instance, or illustration.” Any implementation or aspect described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects of the disclosure. Likewise, the term “aspects” does not require that all aspects of the disclosure include the discussed feature, advantage, or mode of operation. The term “coupled” is used herein to refer to the direct or indirect coupling between two objects. For example, if object A physically touches object B and object B touches object C, then objects A and C may still be considered coupled to one another—even if objects A and C do not directly physically touch each other. For instance, a first object may be coupled to a second object even though the first object is never directly physically in contact with the second object. The terms “circuit” and “circuitry” are used broadly and intended to include both hardware implementations of electrical devices and conductors that, when

connected and configured, enable the performance of the functions described in the present disclosure, without limitation as to the type of electronic circuits.

The apparatus and methods described in the detailed description are illustrated in the accompanying drawings by various blocks, modules, components, circuits, steps, processes, algorithms, etc. (collectively referred to as “elements”). These elements may be implemented using hardware, for example.

One or more of the components, steps, features, and/or functions illustrated herein may be rearranged and/or combined into a single component, step, feature, or function or embodied in several components, steps, or functions. Additional elements, components, steps, and/or functions may also be added without departing from features disclosed herein. The apparatus, devices, and/or components illustrated herein may be configured to perform one or more of the methods, features, or steps described herein.

It is to be understood that the specific order or hierarchy of steps in the methods disclosed is an illustration of exemplary processes. Based upon design preferences, it is understood that the specific order or hierarchy of steps in the methods may be rearranged. The accompanying method claims present elements of the various steps in a sample order, and are not meant to be limited to the specific order or hierarchy presented unless specifically recited therein.

The previous description is provided to enable any person skilled in the art to practice the various aspects described herein. Various modifications to these aspects will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other aspects. Thus, the claims are not intended to be limited to the aspects shown herein, but are to be accorded the full scope consistent with the language of the claims, wherein reference to an element in the singular is not intended to mean “one and only one” unless specifically so stated, but rather “one or more.” Unless specifically stated otherwise, the term “some” refers to one or more. A phrase referring to “at least one of” a list of items refers to any combination of those items, including single members. As an example, “at least one of: a, b, or c” is intended to cover at least: a, b, c, a-b, a-c, b-c, and a-b-c, as well as any combination with multiples of the same element (e.g., a-a, a-a-a, a-a-b, a-a-c, a-b-b, a-c-c, b-b, b-b-b, b-b-c, c-c, and c-c-c or any other ordering of a, b, and c). All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. No claim element is to be construed under the provisions of 35 U.S.C. § 112(f) unless the element is expressly recited using the phrase “means for” or, in the case of a method claim, the element is recited using the phrase “step for.”

What is claimed is:

1. A static random-access memory (SRAM) memory cell, comprising:
  - a flip-flop (FF) having a pull-up (PU) transistor and a pull-down (PD) transistor; and
  - a pass-gate (PG) transistor coupled between a bit line (BL) of the SRAM memory cell and the FF, a gate of the PG transistor being coupled to a word line (WL) of the SRAM memory cell, wherein:
    - the PD transistor comprises a gate-all-around (GAA) transistor;

- the PG transistor comprises a first fin field-effect transistor (FinFET); and  
the PU transistor comprises a second FinFET.
- 2. The SRAM memory cell of claim 1, wherein a drive current strength of the PD transistor is greater than a drive current strength of the PG transistor. 5
- 3. The SRAM memory cell of claim 1, wherein:  
the PG transistor comprises an n-type metal-oxide-semiconductor (NMOS) transistor;  
the PD transistor comprises another NMOS transistor; and 10  
the PU transistor comprises a p-type metal-oxide-semiconductor (PMOS) transistor having a source coupled to the NMOS transistor and to a source of the other NMOS transistor.
- 4. The SRAM memory cell of claim 1, wherein a drive current strength of the PG transistor is less than a drive current strength of the PU transistor. 15
- 5. A static random-access memory (SRAM) memory cell comprising:  
a flip-flop (FF) having a pull-up (PU) transistor and a pull-down (PD) transistor; and 20  
a pass-gate (PG) transistor coupled between a bit line (BL) of the SRAM memory cell and the FF, a gate of the PG transistor being coupled to a word line (WL) of the SRAM memory cell, wherein:  
the PG transistor comprises a fin field-effect transistor (FinFET); 25  
the PD transistor comprises a first gate-all-around (GAA) transistor; and  
the PU transistor comprises a second GAA transistor. 30
- 6. The SRAM memory cell of claim 5, wherein a width of a channel slab of the PD transistor is greater than a width of a channel slab of the PU transistor.
- 7. The SRAM memory cell of claim 5, wherein a drive current strength of the PD transistor is greater than a drive current strength of the PG transistor. 35
- 8. The SRAM memory cell of claim 1, wherein the GAA transistor comprises a channel and a gate region surrounding the channel.
- 9. The SRAM memory cell of claim 1, wherein each of the first FinFET and the second FinFET comprises a fin and a gate region adjacent to at least two sides of the fin. 40

- 10. A static random-access memory (SRAM), comprising:  
a plurality of memory cells, each of the plurality of memory cells comprising:  
a flip-flop (FF) having a pull-up (PU) transistor and a pull-down (PD) transistor; and  
a pass-gate (PG) transistor coupled between a bit line (BL) of the SRAM and the FF, a gate of the PG transistor being coupled to one of a plurality of word lines (WLs) of the SRAM, wherein:  
the PG transistor comprises a first gate-all-around (GAA) transistor;  
the PU transistor comprises a second GAA transistor; and  
the PD transistor comprises a fin field-effect transistor (FinFET).
- 11. The SRAM of claim 10, wherein a drive current strength of the PG transistor is less than a drive current strength of the PD transistor.
- 12. The SRAM of claim 10, wherein:  
the PG transistor comprises an n-type metal-oxide-semiconductor (NMOS) transistor;  
the PD transistor comprises another NMOS transistor; and  
the PU transistor comprises a p-type metal-oxide-semiconductor (PMOS) transistor having a source coupled to the NMOS transistor and to a source of the other NMOS transistor.
- 13. The SRAM of claim 10, wherein a drive current strength of the PU transistor is less than a drive current strength of the PD transistor.
- 14. The SRAM memory cell of claim 5, wherein a drive current strength of the PU transistor is less than the drive current strength of the PG transistor.
- 15. The SRAM of claim 10, wherein a width of a channel slab of the PG transistor is smaller than a width of a channel slab of the PD transistor.
- 16. The SRAM of claim 10, wherein a width of a channel slab of the PU transistor is smaller than a width of a channel slab of the PD transistor.

\* \* \* \* \*