

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2009221630 B2**

(54) Title
Mask system

(51) International Patent Classification(s)
A61M 16/06 (2006.01)

(21) Application No: **2009221630**

(22) Date of Filing: **2009.02.27**

(87) WIPO No: **WO09/108995**

(30) Priority Data

(31) Number	(32) Date	(33) Country
61/064,406	2008.03.04	US
61/136,617	2008.09.19	US
61/071,893	2008.05.23	US

(43) Publication Date: **2009.09.11**

(44) Accepted Journal Date: **2014.07.17**

(71) Applicant(s)
ResMed Limited

(72) Inventor(s)
Valcic, Zoran;Lockwood, David James;D'Souza, Errol Savio alex;Sari, Mahsita;Wehbeh, Jamie Graeme;Eves, Matthew;Ng, Eva

(74) Agent / Attorney
Halfords IP, Level 7 1 Market Street, Sydney, NSW, 2000

(56) Related Art
US 2007/0215161
WO 2007/048174

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 September 2009 (11.09.2009)

(10) International Publication Number
WO 2009/108995 A1

(51) International Patent Classification:
A61M 16/06 (2006.01)

(21) International Application Number:

PCT/AU2009/000241

(22) International Filing Date:

27 February 2009 (27.02.2009)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/064,406	4 March 2008 (04.03.2008)	US
61/071,893	23 May 2008 (23.05.2008)	US
61/136,617	19 September 2008 (19.09.2008)	US

(71) Applicant (for all designated States except US):
RESMED LTD [AU/AU]; 1 Elizabeth Macarthur Drive,
Bella Vista, New South Wales 2153 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NG, Eva** [AU/AU]; ResMed Ltd, 1 Elizabeth Macarthur Drive, Bella Vista, New South Wales 2153 (AU). **LOCKWOOD, David, James** [AU/AU]; ResMed Ltd, 1 Elizabeth Macarthur Drive, Bella Vista, New South Wales 2153 (AU). **WEHBEH, Jamie, Graeme** [GB/AU]; ResMed Ltd, 1 Elizabeth Macarthur Drive, Bella Vista, New South Wales 2153 (AU). **VALCIC, Zoran** [AU/AU]; ResMed Ltd, 1 Elizabeth Macarthur Drive, Bella Vista, New South Wales 2153 (AU). **D'SOUZA, Errol, Savio Alex** [AU/AU]; ResMed Ltd, 1 Elizabeth Macarthur Drive, Bella Vista, New South Wales 2153 (AU). **EVES, Matthew** [AU/AU]; ResMed Ltd, 1 Elizabeth Macarthur

Drive, Bella Vista, New South Wales 2153 (AU). **SARI, Mahsita** [ID/AU]; ResMed Ltd, 1 Elizabeth Macarthur Drive, Bella Vista, New South Wales 2153 (AU).

(74) Agents: **DAVIDSON, Geoffrey, Robert** et al.; Halford & Co, 1 Market Street, Sydney, New South Wales 2000 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) Title: MASK SYSTEM




Fig. 30

(57) Abstract: A shroud (1020) for a mask system includes a retaining portion structured to retain a frame (1040), a pair of upper headgear connectors (1024) each including an elongated arm (1026) and a slot (1027) at the free end of the arm adapted to receive a headgear strap, and a pair of lower headgear connectors (1025) each adapted to attach to a headgear strap. The retaining portion, the upper headgear connectors, and the lower headgear connectors are integrally formed as a one piece structure.

WO 2009/108995 A1

WO 2009/108995 A1



Published:

— *with international search report (Art. 21(3))*

MASK SYSTEM

CROSS-REFERENCE TO APPLICATION

[0001] This application claims the benefit of U.S. Provisional Application Nos. 61/064,406, filed March 4, 2008, 61/071,893, filed May 23, 2008, and 61/136,617, filed September 19, 2008, each of which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

[0002] The present invention relates to a mask system used for treatment, e.g., of Sleep Disordered Breathing (SDB) with Continuous Positive Airway Pressure (CPAP) or Non-Invasive Positive Pressure Ventilation (NIPPV).

BACKGROUND OF THE INVENTION

[0003] Patient interfaces, such as a full-face or nasal mask systems, for use with blowers and flow generators in the treatment of sleep disordered breathing (SDB), typically include a soft face-contacting portion, such as a cushion, and a rigid or semi-rigid shell or frame. In use, the interface is held in a sealing position by headgear so as to enable a supply of air at positive pressure (e.g., 2-30 cm H₂O) to be delivered to the patient's airways.

[0004] One factor in the efficacy of therapy and compliance of patients with therapy is the comfort and fit of the patient interface.

[0005] The present invention provides alternative arrangements of mask systems to enhance the efficacy of therapy and compliance of patients with therapy.

SUMMARY OF THE INVENTION

[0006] One aspect of the invention relates to a mask system provided without a forehead support adapted to engage the patient's forehead.

[0007] Another aspect of the invention relates to a mask system including a frame and a shroud removably connected to the frame and adapted to attach headgear.

[0008] Another aspect of the invention relates to a mask system including a frame defining a breathing chamber, a cushion provided to the frame and adapted to form a seal with the patient's face, and a shroud provided to the frame. The shroud and the frame are co-molded with one another. The frame is constructed of a first, relatively soft, elastomeric material and the shroud is constructed of a second material that is more rigid than the frame. At least a portion of the frame includes a concertina section having a plurality of folds. Each of the folds has a side wall with the side walls of the folds becoming progressively longer away from the patient's face.

[0009] Another aspect of the invention relates to a cushion module including a frame defining a breathing chamber and a cushion adapted to form a seal with the patient's face. The frame and the cushion are co-molded with one another. The cushion is constructed of a first, relatively soft, elastomeric material and the frame is constructed of a second material that is more rigid than the cushion. At least a portion of the frame includes a concertina section.

[0010] Another aspect of the invention relates to a method for constructing a cushion module. The method includes molding a first part of the cushion module with a first, relatively soft, elastomeric material, co-molding a second part of the cushion module to the first part with a second material that is more rigid than the first material, and molding at least a portion of the second part to include a concertina section.

[0011] Another aspect of the invention relates to a shroud for a mask system including a retaining portion structured to retain a frame, a pair of upper headgear connectors each including an elongated arm and a slot at the free end of the arm adapted to receive a headgear strap, and a pair of lower headgear connectors each adapted to attach to a headgear strap, wherein the retaining portion, the upper headgear connectors, and the lower headgear connectors are integrally formed as a one piece structure.

[0012] Another aspect of the invention relates to a mask system including a frame defining a breathing chamber, a cushion provided to the frame and adapted to form a seal with the patient's face, a shroud provided to the frame and adapted to attach headgear, and an elbow provided to the frame and adapted to be connected to an air delivery tube that delivers breathable gas to the patient. The shroud includes a retaining mechanism structured to establish a positive connection between the shroud and the frame.

[0013] Another aspect of the invention relates to a mask system including a frame defining a breathing chamber and a cushion provided to the frame. The cushion is adapted to engage at least a portion of the patient's face. The cushion includes a base wall connected to an undercushion layer and a membrane, wherein the membrane extends around the perimeter of the cushion and contacts the patient's face. The undercushion layer is positioned underneath the membrane and supports the membrane. The under cushion layer provides differential support to the membrane at predetermined regions of the face.

[0014] Another aspect of the invention relates to a mask assembly for use in medical applications having a top and bottom ends defined by its position relative to a patient's face, wherein the mask assembly is connected to a plurality of flexible straps, which are adapted to engage the patient's head. The flexible straps engage at least two elongated rigid arms integrally molded to a portion of the mask assembly, and wherein the elongated arms are molded to the mask assembly proximal to the top end of the mask assembly.

[0015] Another aspect of the invention relates to a mask assembly for use in medical applications including a main body connected to a cushion adapted to cover nose and/or mouth and wherein the mask assembly is attached by a force substantially perpendicular towards the face and wherein the force is approximately constant along the length of the mask and is balanced by a portion of the cushion engaging the patient's cheeks.

[0016] Another aspect of the invention relates to a cushion for use with a medical mask including an outer membrane layer adapted to sealably engage a face and an undercushion layer adapted to support the membrane layer. The membrane or undercushion layer includes a surface positioned between the two layers adapted to allow the layers to slide against the respective surface.

[0017] Another aspect of the invention relates to a mask system including a frame defining a breathing chamber, a cushion provided to the frame and adapted to form a seal with the patient's face, and a releasable shroud adapted to engage a portion of the outer surface of the frame, wherein the shroud is connected to straps to position the mask system.

[0018] Another aspect of the invention relates to a mask assembly for use in medical applications including an upper end and a lower end wherein the upper end is adapted to cover the nose and the lower end is adapted to cover the mouth of a patient. The mask assembly includes no forehead support and includes two stiffened members attached to the

upper end on opposed sides of the mask assembly, and wherein the stiffened members include a general curved shape and adapted to avoid covering the patient's field of vision.

[0019] Another aspect of the invention relates to a cushion for attaching to a medical mask, wherein the cushion is flexible and includes a membrane attached to the circumference of the cushion adapted to seal against the face of a patient, and at least one undercushion adapted to support the membrane and positioned underneath the membrane to prevent collapse of the membrane, in use. The membrane is softer than the undercushion. The undercushion in the regions of nasal bridge or chin is between 0mm and 30mm in height as measured between the base and the tip of the undercushion.

[0020] Another aspect of the invention relates to a mask assembly for use in medical applications including an upper end and a lower end wherein the upper end is adapted to cover the nose and the lower end is adapted to cover the mouth of a patient. The mask assembly includes no forehead support and includes two stiffened members attached to the upper end on opposed sides of the mask assembly, and wherein the stiffened members include a general curved shape and adapted to avoid covering the patient's field of vision.

[0021] In an alternative embodiment, the mask system may include a headgear connector or rigidizer structured to attach to the frame with a snap-fit, mechanical interlock, friction fit, and/or grommet arrangement (e.g., constructed of rubber).

[0022] In an alternative embodiment, the mask system may include headgear having an arrangement of straps constructed of silicone and/or Breath-O-Prene™ material.

[0023] Other aspects, features, and advantages of this invention will become apparent from the following detailed description when taken in conjunction with the accompanying drawings, which are a part of this disclosure and which illustrate, by way of example, principles of this invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The accompanying drawings facilitate an understanding of the various embodiments of this invention. In such drawings:

[0025] Fig. 1 is a front perspective view of a mask system according to an embodiment of the present invention;

- [0026] Fig. 1B is a perspective view showing the mask system of Fig. 1 with headgear positioned on a patient's head;
- [0027] Fig. 1C is a cross-sectional view through the mask system of Fig. 1;
- [0028] Fig. 1D is another cross-sectional view through the mask system of Fig. 1;
- [0029] Fig. 1E is a side view of the mask system of Fig. 1;
- [0030] Fig. 2 is a front perspective view showing the frame and cushion of the mask system of Fig. 1;
- [0031] Fig. 3 is an exploded perspective view of the mask system of Fig. 1 showing the frame, cushion, shroud, and elbow;
- [0032] Fig. 4 is another exploded perspective view of the mask system of Fig. 1 showing the frame, cushion, and shroud;
- [0033] Fig. 5 is an exploded perspective view of the mask system of Fig. 1 showing the shroud and assembled frame/cushion;
- [0034] Fig. 6 is a front perspective view showing the shroud of the mask system of Fig. 1;
- [0035] Fig. 7 is a front perspective view showing the cushion of the mask system of Fig. 1;
- [0036] Fig. 8 is a cross-sectional view showing a portion of the cushion of Fig. 7;
- [0037] Fig. 8B is a cross-sectional view through nasal bridge and chin regions of the cushion of Fig. 7;
- [0038] Fig. 9 is a plan view of headgear laid out flat according to an embodiment of the present invention;
- [0039] Fig. 10 is a front perspective view of a mask system according to another embodiment of the present invention;
- [0040] Fig. 11 is a front perspective view showing the frame of the mask system of Fig. 10;
- [0041] Fig. 12 is a front view showing the frame of the mask system of Fig. 10;
- [0042] Fig. 13 is a side view showing the frame of the mask system of Fig. 10;
- [0043] Fig. 14 is a front perspective view showing the shroud of the mask system of Fig. 10;
- [0044] Fig. 15 is a front view showing the shroud of the mask system of Fig. 10;

- [0045] Fig. 16 is a side view showing the shroud of the mask system of Fig. 10;
- [0046] Fig. 17 is a rear perspective view showing the shroud of the mask system of Fig. 10;
- [0047] Figs. 18-1 to 18-2 are cross-sectional views showing in sequential relation attachment of the shroud to the frame of the mask system of Fig. 10;
- [0048] Figs. 19-1 to 19-4 are cross-sectional views showing in sequential relation attachment of the shroud to the frame of the mask system of Fig. 10;
- [0049] Fig. 20 is a perspective view showing an alternative arrangement for attaching the shroud to the frame;
- [0050] Fig. 21 is a rear perspective view showing the shroud of the mask system of Fig. 10;
- [0051] Fig. 22 is a cross-sectional view showing attachment of the shroud to the frame of the mask system of Fig. 10;
- [0052] Fig. 23 is a cross-sectional view showing attachment of the shroud, frame, and elbow of the mask system of Fig. 10;
- [0053] Fig. 24 is a cross-sectional view showing an alternative arrangement for attaching the shroud to the frame;
- [0054] Fig. 25 is a front perspective view of a mask system according to another embodiment of the present invention;
- [0055] Fig. 26 is a rear perspective view of the mask system of Fig. 25;
- [0056] Fig. 27 is a front perspective view of a mask system according to another embodiment of the present invention;
- [0057] Fig. 28 is an exploded view of the mask system shown in Fig. 27;
- [0058] Fig. 29 is an enlarged front perspective view of the mask system shown in Fig. 17;
- [0059] Fig. 30 is a side view of the mask system shown in Fig. 27;
- [0060] Figs. 31-1 is a rear view of a cushion according to an embodiment of the present invention;
- [0061] Fig. 31-2 is a front view of the cushion shown in Fig. 31-1 with a partial cut-away;
- [0062] Fig. 31-3 is a cross-section view through line 31-3-31-3 in Fig. 31-1;

- [0063] Fig. 31-4 is a cross-section view through line 31-4-31-4 in Fig. 31-1;
- [0064] Fig. 31-5 is a cross-section view through line 31-5-31-5 in Fig. 31-1;
- [0065] Figs. 32-1 to 32-3 illustrate top, front, and side views respectively of a concertina section according to an embodiment of the present invention;
- [0066] Fig. 33 is a side view of a mask system according to a variation of the present invention;
- [0067] Fig. 34 illustrates a cushion including a concertina section according to an embodiment of the present invention;
- [0068] Figs. 35-1 to 35-3 are front, side, and rear views of a mask system according to another embodiment of the present invention;
- [0069] Fig. 36 is a perspective view of a shroud for a mask system according to an embodiment of the present invention;
- [0070] Figs. 37-1 to 37-3 are perspective, front, and side views of a mask system according to another embodiment of the present invention;
- [0071] Figs. 38-1 to 38-5 are perspective, front, top, side, and bottom views of a shroud of the mask system shown in Figs. 37-1 to 37-3;
- [0072] Figs. 39-1 to 39-6 are perspective, front, side, bottom, and top views of a mask system according to another embodiment of the present invention;
- [0073] Figs. 40-1 and 40-2 are perspective and side views of a mask system according to another embodiment of the present invention;
- [0074] Fig. 40-3 is a perspective view of the frame of the mask system shown in Figs. 40-1 and 40-2;
- [0075] Figs. 40-4 and 40-5 illustrate a retaining member of the frame shown in Fig. 40-3;
- [0076] Figs. 40-6 and 40-7 illustrate a clip-on upper headgear connector of the mask system shown in Figs. 40-1 and 40-2;
- [0077] Figs. 41-1 and 41-2 are rear and front perspective views of a mask system according to another embodiment of the present invention;
- [0078] Figs. 41-3 and 41-4 are exploded views of the mask system shown in Figs. 41-1 and 41-2;

- [0079] Figs. 41-5 to 41-12 are various views of a clip-on upper headgear connector of the mask system shown in Figs. 41-1 and 41-2;
- [0080] Fig. 42-1 is a rear perspective view of a mask system according to another embodiment of the present invention;
- [0081] Fig. 42-2 is an exploded view of the mask system shown in Fig. 42-1;
- [0082] Figs. 42-3 to 42-7 are various views of a clip-on upper headgear connector of the mask system shown in Fig. 42-1;
- [0083] Figs. 43-1 to 43-4 are perspective, side, front, and rear views of a mask system according to another embodiment of the present invention;
- [0084] Fig. 44 illustrates a mask system according to another embodiment of the present invention; and
- [0085] Fig. 45 illustrates a mask system according to another embodiment of the present invention.

DETAILED DESCRIPTION OF ILLUSTRATED EMBODIMENTS

[0086] The following description is provided in relation to several embodiments or examples which may share common characteristics and features. It is to be understood that one or more features of any one embodiment or example may be combinable with one or more features of the other embodiments or examples. In addition, any single feature or combination of features in any of the embodiments or examples may constitute additional embodiments or examples.

[0087] In this specification, the word “comprising” is to be understood in its “open” sense, that is, in the sense of “including”, and thus not limited to its “closed” sense, that is the sense of “consisting only of”. A corresponding meaning is to be attributed to the corresponding words “comprise”, “comprised” and “comprises” where they appear.

[0088] The term “air” will be taken to include breathable gases, for example air with supplemental oxygen.

[0089] The term “shroud” will be taken to include components that partially or fully cover a second component within the illustrated embodiments. In an embodiment, the shroud may include the component that partially covers or is mounted on the frame components of the illustrated embodiments.

[0090] The term “positive connection” will be taken to include connections between components of the illustrated embodiments wherein connectors mounted on respective components are adapted to engage each other respectively.

1. Mask System

[0091] Embodiments of the invention are directed towards a mask system provided without a forehead support adapted to engage the patient's forehead. Such arrangement provides the mask system with a less obtrusive arrangement which does not significantly affect the patient's field of view. Although the system is designed such that a forehead support is not required, such a forehead support can be added if desired.

[0092] As described in greater detail below, the mask system includes a frame, a cushion provided to the frame and adapted to form a seal with the patient's face, a shroud provided to the frame and adapted to attach headgear, and an elbow provided to the frame and adapted to be connected to an air delivery tube that delivers breathable gas to the patient. Headgear may be removably attached to the shroud to maintain the mask system in a desired adjusted position on the patient's face. The mask system is intended for use in positive pressure therapy for users with Obstructive Sleep Apnea (OSA) or another respiratory disorder.

[0093] While each embodiment below is described as including a full-face or oronasal interface type, each embodiment may be adapted for use with other suitable interface types. That is, the interface type is merely exemplary, and each embodiment may be adapted to include other interface types, e.g., nasal interface, nasal mask, nasal prongs, etc.

2. Stabilizing Mechanisms

[0094] The stabilizing mechanisms (e.g., frame, shroud, headgear with associated headgear vectors) of a mask system according to embodiments of the invention are structured to accommodate the elimination of a forehead support from a full-face type interface. For example, a forehead support typically eliminates rotation of the mask system in the sagittal and coronal planes, so the mask system and headgear according to embodiments of the invention are structured to take on these functions since there is no forehead support.

[0095] The headgear is connected to the top and bottom of the frame either directly or via the shroud, which shroud provides headgear connection points for headgear positioned and arranged to stably maintain the mask system in position on the patient's face.

2.1 Frame

[0096] As shown in Figs. 1, 1B-1E, and 2-5, the frame 1040 of the mask system 1010 is structured to maintain the cushion 1060, shroud 1020, and elbow 1070 in an operative position with respect to the patient's face. The frame 1040 is constructed (e.g., injection molded) from a more rigid material (e.g., polyurethane) than the cushion 1060 (made of, e.g., silicone), however other materials may function likely as well (e.g., polycarbonate). In an embodiment, the frame has a general wall thickness of about 1-2 mm, e.g., 1.5 mm.

[0097] The frame 1040 defines a breathing chamber or cavity adapted to receive the patient's nose and mouth and provide air communication to the patient. One or the lower portion of the frame 1040 includes an opening 1046 adapted to receive or otherwise communicate with the elbow 1070 (e.g., swivel elbow) and another or upper portion of the frame 1040 includes a vent arrangement 1076 for gas washout. In addition, the upper portion of the frame 1040 includes an interfacing structure 1048 adapted to interface or otherwise removably connect to the shroud 1020.

[0098] Figs. 27-30 shows a mask system 10 including a frame 40 with a cushion 44 that provides a sealing portion or sealing ring adapted to form a seal with the patient's nose and/or mouth. Also, the frame 40 includes an opening 46 that is adapted to communicate with the elbow 70.

2.2 Shroud

[0099] As shown in Figs. 1 and 3-6, the shroud 1020 is connected to the frame 1040 and is structured to attach headgear to the mask system. In an embodiment, the shroud 1020 is constructed (e.g., injection molded) of a resilient material including but not limited to plastic or nylon (e.g., Nylon 12). However, the shroud may be constructed of other suitable materials, e.g., polycarbonate, polypropylene, thermoplastic elastomer (TPE), Pocan®, etc. In an embodiment, the shroud has a general wall thickness of about 1-2 mm, e.g., 1.3 mm.

[00100] The top end of the shroud 1020 is adapted to be positioned proximal to the nasal bridge region or nose of the patient and the bottom end is adapted to be positioned proximal to the mouth or chin of the patient. The top end includes an opening or vent receiving hole 1021 to accommodate the vent arrangement 1076 that protrudes from the frame 1040, and the bottom end includes an opening or elbow hole 1032 to accommodate the elbow 1070 and elbow opening into the frame 1040 (e.g., shroud provides no contact with elbow when assembled).

[00101] Upper headgear connectors 1024 extend from each side of the top end, and lower headgear connectors 1025 extend from each side of the lower end. The headgear connectors 1024, 1025 may be integrally molded or otherwise attached to the shroud.

2.2.1 Upper Headgear Connectors

[00102] Each upper headgear connector 1024 includes an elongated arm 1026 and a slot or receiving hole 1027 at the free end of the arm 1026 adapted to receive a respective headgear strap. In use, the arms 1026 extend around the face of the patient in a generally concave angle below the eyes of the patient so as to avoid the patient's field of view, i.e., direct headgear away from the patient's eyes. For example, as shown in Fig. 1E, each arm 1026 may extend at an angle α between about 10-25° (e.g., 17°) with respect to horizontal. That is, each arm 1026 is suitably formed, shaped, or contoured to follow the contours of the patient's face and avoid line of sight in use. In an embodiment, the shape of the arms may be generally arcuate and adapted to extend in a direction across the cheek of the patient, while avoiding the eyes or limiting the field of vision. In an embodiment, the arms may be integrally molded to the shroud of the mask system. One possible advantage of molding the arms onto the shroud is that it greatly increases manufacturability and also the shroud may be easily replaced in the case of accidental breakage of the arms rather than replacing the complete mask system. Additionally, molding of the arms onto the shroud may greatly increase the strength of the connection and reduce or limit the actual likelihood of breakage of the arms.

[00103] In an embodiment, the arms 1026 are at least semi-rigid (e.g., relatively rigid) so as to prevent up and down movement or bending of the arms relative to the face of the patient. Thus, the arms 1026 may act as rigidizers to effectively act as a level arrangement

and generate a mechanical advantage wherein the pressure or force applied to top end of the mask system is readjusted to a fulcrum point being about the center of balance between the top and bottom ends of the mask system. In an embodiment, the arms are attached to the highest possible point relative to the mask system to additionally stabilize the configuration. In an embodiment, the fulcrum point or moment of pivoting is positioned between the upper and lower connection points of the straps, and wherein the design, angle, length and/or configuration of the arms 1026 may effectively adjust the fulcrum point. In the illustrated embodiment, the fulcrum point is shown to be between the vent arrangement and elbow of the mask system. Additionally, when positioned on the face, the mask system may have a fulcrum point around or about the region between the bottom of the patient's nose and lip area. This feature effectively stabilizes the mask system on the patient's face without the traditional need for a forehead support.

[00104] The net result of the arms 1026 mounted in a position extending from the top end of the mask system around the face of the patient is that the mask system is more stable and reduces the net torsional forces experiences about the x- axis 1001 (see Fig. 1) for the mask system in use. Please note that the arms 1026 may be rigidly connected to the mask system in other suitable positions to generate a similar result.

[00105] In an embodiment, the arms 1026 may be used to stabilize the mask system by contacting the patient's face at the cheeks. A cheek pad may be provided to the inner surface of the arm to support the arm on the patient's cheek in use. Also, the arms 1026 may be enveloped in a soft fabric sleeve to act as additional padding against the cheeks of the patient. The soft fabric sleeve may be in the configuration of an elastic tube covering a portion of the arms 1026.

2.2.2 Lower Headgear Connectors

[00106] Each lower headgear connector 1025 includes an abbreviated arm and a clip receptacle 1031 at the free end of the arm adapted to be removably interlocked with a headgear clip associated with a respective headgear strap. The clips allow for easier positioning or donning/removal of the mask system. In an embodiment, the abbreviated arms and clips are also relatively rigid so as to prevent lateral movement of the arms along the y-axis 1002, relative to the mask system in use.

[00107] Figs. 27-30 illustrate an exemplary headgear clip 33 adapted to be removably interlocked with a clip receptacle 31. As best shown in Fig. 28, each clip 33 includes two spring arms 35 adapted to interlock with the respective clip receptacle 31 with a snap-fit and a slot 37 adapted to receive a respective headgear strap in use.

2.2.3 Alternative Headgear Connectors

[00108] As shown in Figs. 27-30, the arm 26 may be removably coupled to the shroud, e.g., arm 26 includes clip structure adapted to removably interlock with a clip receptacle provided to the shroud. This arrangement allows different styles of upper and lower headgear connectors to be used with the shroud, e.g., arms for both upper and lower headgear connectors, clips for both upper and lower headgear connectors, different length arms for upper and lower headgear connectors, etc.

[00109] However, the shroud may provide other suitable arrangements for attaching headgear straps of headgear. Also, the shroud may include one or more additional components, e.g., forehead support.

2.2.4 Headgear Connector Positioning

[00110] In the embodiment of Figs. 1-6, the upper and lower headgear connectors 1024, 1025 provide headgear connection points that are as far from each other as possible (i.e., top and bottom of frame) to allow for greater adjustability (e.g., allows adjustment at the top and bottom of the mask system) and stability (e.g., anchor points spread out around the mask system so more secure on the patient's face). Also, the upper headgear connectors are positioned as close to the top of the mask system as possible without obstructing the patient's eyes in use.

2.2.5 Separate Shroud

[00111] In the embodiment of Figs. 1-6, the shroud 1020 is formed separately (e.g., molded) and attached to the frame 1040. Such arrangement facilitates molding of the shroud, allows different materials to be used for the frame and shroud (e.g., frame can be semi-rigid or rigid for stability and shroud with headgear rigidizers can be flexible for adjustment, allows the shroud to hide elbow retention features around elbow/frame opening for retaining

elbow to frame (e.g., provides visual shroud for aesthetics), allows frame to be free of lower clip receptacles, allows shroud to be used with different size frames, and allows the shroud to be designed or stylized to minimize obtrusiveness of the mask system. The separate shroud may also allow the headgear, frame, cushion, and/or elbow to be replaced or washed independently.

2.2.6 Sleeves

[00112] In an embodiment, soft fabric sleeves may be mounted on the upper and/or lower headgear connectors. For example, the sleeves may be elastic and adapted to slide over the arms of the headgear connectors to form a tight fit. In an embodiment, the sleeves form elastic tubes. The sleeves may be padded to increase the comfort of the mask system in use. The sleeves may be particularly useful where the arms of the headgear connectors contact the patient's skin, e.g., to protect the patient's skin from irritation.

2.2.7 Arm Extends Over the Patient's Ear

[00113] Figs. 35-1 to 35-3 and 36 illustrate a shroud 220 for mask system 210 according to another embodiment of the present invention. The shroud 220 includes an annular retaining portion 222 structured to retain the frame 240 and upper and lower headgear connectors 224, 225 on each side of the retaining portion 222. In the illustrated embodiment, the shroud 220 is integrally formed in one piece (e.g., see Fig. 36).

[00114] In the illustrated embodiment, each upper headgear connector 224 includes an elongated arm 226 and a slot 227 at the free end of the arm 226 adapted to receive a respective rear strap 298 in use. As illustrated, the arm 226 is suitably contoured to extend along the cheeks and over the patient's ear just anterior of the patient's temple and retain the respective rear strap 298 in spaced relation over the patient's ear, e.g., to avoid the strap rubbing or irritating the patient's ear in use.

[00115] Also, each arm 226 is structured to extend along and engage an upper strap 292 of the headgear in use. As illustrated, each arm 226 is secured to the upper strap 292 to add rigidity to the strap and stabilize the mask system on the patient's face in use. In addition, the strap 292 provides padding to the arm 226 on the patient's face in use. In an embodiment, the upper strap 292 may be fixed to the arm 226 by gluing or stitching for example.

Alternatively, the arms 226 may be encapsulated by or inserted into respective straps 292 so that the arms 226 are substantially not visible.

[00116] Each lower headgear connector 225 includes an abbreviated arm 228 with a slot 229 at the free end of the arm 229 adapted to receive a respective lower strap 294 in use. As illustrated, the arm 228 is suitably oriented to retain the respective lower strap 294 in spaced relation under the patient's ear, e.g., to avoid the strap rubbing or irritating the patient's ear in use.

[00117] In an embodiment, each arm may be attached to the upper end of the mask system and curves below the patient's field of vision or eyes and curves upwards at an angle between about 10 to 20 degrees away from the horizontal axis.

[00118] In an alternative embodiment, as shown in Fig. 36, each lower headgear connector 225 may include a clip receptacle 231 adapted to be removably interlocked with a headgear clip (not shown) associated with a respective lower strap 294. In an embodiment, the headgear clip receptacle and clip may be similar to that on ResMed's Mirage Liberty™ mask. Exemplary clip arrangements are disclosed in U.S. Patent Publication Nos. 2007/0144525 and 2006/0283461, each of which is incorporated herein by reference in its entirety.

2.2.8 Shroud Without Upper Headgear Connector

[00119] Figs. 37-1 to 37-3 illustrate a mask system 310 according to another embodiment of the present invention. As illustrated, the mask system 310 includes a shroud 320, a frame 340, a cushion 344, and an elbow 370.

[00120] As best shown in Figs. 38-1 to 38-5, the shroud 320 includes an opening 322 structured to receive the elbow 370 and a headgear connector 325 on each side thereof. In the illustrated embodiment, each headgear connector 325 includes a clip receptacle 331 adapted to be removably interlocked with a headgear clip (not shown) associated with a respective lower headgear strap.

[00121] The frame 340 is removably attached to the shroud 320, e.g., fingers and tabs 345 extending from opening 322 adapted to engage collar of frame 340.

[00122] The frame 340 includes an upper headgear connector 324 on each upper side thereof. Each headgear connector 324 includes a clip retainer 333 adapted to be removably

interlocked with a headgear clip (not shown) associated with a respective upper headgear strap.

[00123] Figs. 39-1 to 39-6 illustrate an alternative version of the mask system 310, which is indicated with similar reference numerals. As illustrated, the frame 340 is provided without upper headgear connectors, and the each clip receptacle 331 includes an alternative configuration (e.g., holes for snap-fit tabs on the clip). Also, the shroud 320 in Figs. 39-1 to 39-6 includes support bars 329 structured to wrap around respective auxiliary ports 343, while the shroud 320 in Figs. 37-1 to 38-5 includes support bars 329 that extend in front of respective auxiliary ports 343.

2.3 Headgear

[00124] Headgear may be removably attached to the headgear connectors 1024, 1025 of the shroud 1020 to maintain the mask system 1010 in a desired position on the patient's face, e.g., see Fig. 1B.

[00125] As shown in Fig. 9, the headgear 1090 includes a pair of upper and lower straps 1092, 1094 with the upper straps 1092 removably attached to respective upper headgear connectors 1024 and the lower straps 1094 removably attached to respective lower headgear connectors 1025. The free end of each strap may include a Velcro® tab structured to engage the remainder of the strap to secure the strap in place. Such Velcro® attachment also allows adjustment of the length of the straps. However, the upper and lower headgear straps may be secured to the shroud in any other suitable manners, e.g., adjustable ladder-lock arrangement, etc.

[00126] The upper straps 1092 split at the crown of the patient's head to top straps 1096 (e.g., connected to one another by a buckle) adapted to pass over the top of the patient's head in use and rear straps 1098 adapted to pass behind the patient's head in use. In an embodiment, the headgear 1090 is structured to be self-supporting.

[00127] In Fig. 9, the top straps 1096 are adapted to be connected to one another by a buckle. In an alternative embodiment, as shown in Fig. 27-30, headgear 90 may include upper and lower straps 92, 94, top strap 96, and rear strap 98, with the top straps 96 integral with one another.

[00128] The upper straps 1092 are designed to adjust the position of the mask in a similar way that an adjustable forehead support would alter the position of the mask system, i.e., move the top of the mask system closer or further away from the patient's nasal bridge.

[00129] Without the forehead support, the headgear is connected at the top and bottom of the mask frame 1040 via the shroud 1020, and in order to avoid the eyes and ears, the arm 1026 of the upper headgear connector extends at an angle. In doing so, the headgear vectors V1 and V2 (see Figs. 1 and 1B) are aligned such that the mask system may have a tendency to ride up the patient's face (i.e., upper headgear connectors position upper headgear vectors upwardly from horizontal and lower headgear connectors position lower headgear vectors generally horizontal). By splitting the upper headgear strap 1092 at the crown of the patient's head (i.e., top and rear straps 1096, 1098), the upper headgear vectors are realigned to prevent the mask system from sliding up the patient's face.

2.3.1 Headgear Adjustment

[00130] Figs. 35-1 to 35-3 illustrate headgear 290 attached to the headgear connectors 224, 225 of the shroud 220 to maintain the mask system in a desired position on the patient's face.

[00131] In the illustrated embodiment, the headgear 290 includes a pair of upper or top straps 292, a pair of lower or bottom straps 294, and a pair of rear straps 298. In use, the upper straps 292 are secured to respective upper connectors or arms 226, the lower straps 294 are removably attached to respective lower connectors via slots 229/clip arrangement 231, and the rear straps 298 are removably attached to respective upper connectors via slots 227. The upper straps 292 may include upper strap portions adapted to pass over the top of the patient's head and couple to one another, e.g., via a headgear buckle or adjustable ladder-lock arrangement 299. In the illustrated embodiment, the lower straps 294 and rear straps 298 are formed in one piece.

[00132] This headgear arrangement allows adjustment to occur at three positions, i.e., upper straps 292 at the headgear buckle 299, lower straps 294 at the slot 229/clip 231 connection, and rear straps 298 at the slot 227 connection.

[00133] As illustrated, the free end of each strap may include a hook and loop tab 295 (e.g., Velcro®) structured to engage the remainder of the strap to removably secure the strap

in place. Such hook and loop attachment also facilitates adjustment of the length of the straps.

[00134] In the illustrated embodiment, the lower straps 294 and rear straps 298 are adapted to join and pass behind the patient's head in use (e.g., see Fig. 35-3). As illustrated, the lower straps 294 join at an angle α (e.g., similar to the bottom strap in ResMed's Mirage Liberty mask) to prevent the strap from irritating the patient's neck and/or prevent movement of the strap due to movement of the patient's neck in use.

[00135] In an embodiment, the headgear may be similar to that for ResMed's Mirage Liberty mask, however the top straps have been modified and there is an added rigidizer system. The top straps may be similar to ResMed's Swift style headgear, with the rigidizers extending along the sides.

2.3.2 Alternative Headgear Material

[00136] Figs. 43-1 to 43-4 illustrate a mask system 610 including a mask 615 and headgear 690 according to another embodiment of the present invention. In the illustrated embodiment, the headgear 690 includes an arrangement of straps wherein some of the straps are constructed of silicone and some of the straps are constructed of Breath-O-Prene™ material. However, the headgear may be constructed such that the straps are completely constructed of silicone or completely constructed of Breath-O-Prene™.

[00137] As illustrated, the lower strap portion 692 of the headgear is constructed of Breath-O-Prene™ and extends along the cheeks and around the back of the patient's head. The upper strap portion 694 of the headgear is constructed of silicone and includes side straps 694(1) that extend along the upper cheek and over the patient's ear, a top strap 694(2) that extends over the top of the patient's head, rear straps 694(3) that extend behind the patient's head and connects to the lower strap portion 692 (see Fig. 43-4), and connecting portions 694(4) that extend from respective side straps 694(1) in front of the patient's ear and connect to the lower strap portion 692.

[00138] The headgear straps may be connected to the mask in any suitable manner. For example, in the illustrated embodiment, the lower strap portion 692 is connected to the mask by a headgear clip arrangement and the upper strap portion 694 is connected to the mask using an elongated buckle 695 with buckle portions on each end thereof.

[00139] In an embodiment, the headgear straps are arranged such that the force vectors applied by the headgear to the mask are substantially perpendicular to the mask and substantially parallel to one another (e.g., as shown by the arrows in Fig. 43-2). This arrangement enhances the mask seal as the headgear forces the mask directly into the patient's face.

3. Seal

[00140] The seal (i.e., cushion) of the mask system is structured to accommodate the elimination of a forehead support from a full-face type interface.

3.1 Cushion

[00141] As shown in Figs. 1-5 and 7-8, the cushion 1060 is structured to interface with the frame 1040 and form a seal with the patient's nose and mouth in use. In the illustrated embodiment, the cushion is a full-face cushion adapted to engage the patient's face generally along nasal bridge, cheek, and lower lip/chin regions of the patient's face. However, other cushion interfaces are possible, e.g., nasal.

[00142] The cushion 1060 is structured be more compliant or flexible (e.g., particularly in the nasal bridge region) to accommodate more movement due to loss of some stability without a forehead support.

[00143] The cushion 1060 is constructed of a soft and flexible biocompatible material, e.g., such as silicone. In the illustrated embodiment, the cushion 1060 includes a dual wall configuration wherein the cushion comprises an undercushion or support wall 1062 underneath a membrane 1064 as shown in Fig. 8.

[00144] The membrane 1064 is generally softer and less stiff than the undercushion 1062 and provides a seal against the patient's face in use. The membrane may be relatively thin to allow for wider fit range and better conformance to the patient's face in view of less mask stability with a forehead support. The undercushion is structured to generally support the membrane and prevents collapse of the membrane when the mask system is attached and tightened using the headgear.

[00145] The membrane 1064 is generally concave and curves inwards towards the breathing chamber. The undercushion 1062 may also curve inwardly but is generally shorter, thicker, and more rigid than the membrane.

[00146] In an embodiment, the undercushion 1062 at the regions of the nasal bridge and/or chin of the patient is shorter in height or completely absent and the height from the tip to base of the undercushion 1062 may be between about 0 mm and 30 mm. The membrane is generally longer than the undercushion 1062 at any given cross-section and may be between about 1 mm and 40 mm. For example, Fig. 8B illustrates a cross-section through nasal bridge and chin regions of the cushion to illustrate the membrane 1064 without an undercushion in these regions.

[00147] In an embodiment, the undercushion 1062 may only be provided in selected regions of the mask system, e.g., where the mask system is to be pushed away from the patient's face. Certain pre-determined regions of the patient's face may be preferably avoided for applying pressure by the tightening of the headgear. In the illustrated embodiment, the nasal bridge and chin regions of the patient do not include an undercushion 1062. In these regions, the undercushion is only provided along lateral sides of the cushion (e.g., see Fig. 7) which press against the cheeks of a patient so as to more evenly distribute the force vectors applied by the mask system in use. In an embodiment, the undercushion may be relatively stiff along the cheek regions because these points of contact are acting as anchor points, i.e., holds mask system in position to provide effective seal.

[00148] This configuration of avoiding the nasal bridge and chin of the patient may increase the comfort of the mask system for patients by reducing the pressure or force applied to sensitive areas or to protruding regions of the patient's face that experience relatively higher contact pressures. Additionally, this arrangement avoids the cushion pinching the nasal bridge of the patient when the mask system is adjusted. Additionally, the cushion of this embodiment may be noticeably softer in the regions of the nasal bridge and chin because of the absence of the undercushion.

[00149] In an embodiment, the undercushion may include a variable height, stiffness, and/or thickness to generate a variable softness in the aforementioned predetermined regions of the face that require lighter support.

[00150] In the illustrated embodiment, the cushion may be structured to seal lower down on the patient's nasal bridge and the eye sockets so that the cushion is less obtrusive.

[00151] In an embodiment, the cushion may be generally frosted except at patient contacting surfaces where it is polished. In an embodiment, the frosting of the cushion may reduce restriction between the face and membrane and/or the membrane and undercushion. The frosting allows the surface of the membrane and undercushion to slide against each other's respective surface without the same restriction of unfrosted silicone. This feature may also prevent or limit sticking of the membrane to the undercushion components and also may generally improve the overall comfort and sealing properties of the cushion. Additionally, the frosting of the cushion may be easier to manufacture and may lead to a reduction of costs of manufacturing. The cushion may be constructed of frosted silicone or other suitable materials.

3.2 Cushion Lower On Nasal Bridge

[00152] Figs. 31-1 to 31-5 illustrate various views of a cushion 44 (e.g., constructed of silicone) according to an embodiment of the present invention. As illustrated, the cushion 44 includes a base wall 44(1) provided to the frame, an undercushion layer (UCL) 44(2) extending away from the base wall 44(1), and a membrane 44(3) provided to substantially cover the UCL 44(2) and provide a sealing structure. In the illustrated embodiment, the cushion 44 is structured to sit lower on the nasal bridge to reduce mask obtrusiveness and improve "line of sight" in use.

[00153] Also, as best shown in Figs. 31-3 and 31-5, the UCL 44(2) design in the nasal bridge region is structured to provide improved stability across the nasal bridge in use. As shown in Fig. 31-1 and 31-3, the UCL is not provided in the lower lip/chin region. However, other arrangements of the UCL are possible, e.g., UCL around entire perimeter.

[00154] In an embodiment of the cushion shown in Figs. 31-1 to 31-5, D1 may be about 15-20 mm, e.g., 18.2 mm, D2 may be about 53-59 mm, e.g., 55.8 mm, D3 may be about 88-93 mm, e.g., 90 mm, D4 may be about 78-83 mm, e.g., 81.1, D5 may be about 58-63 mm, e.g., 60 mm, D6 may be about 95-100 mm, e.g., 98.1 mm, D7 may be about 57-62 mm, e.g., 59.7 mm, D8 may be about 77-82 mm, e.g., 79 mm, D9 may be about 88-93 mm, e.g., 90.7 mm, D10 may be about 30-35 mm, e.g., 33.1 mm, D11 may be about 14-19 mm, e.g., 16.4

mm, D12 may be about 8-13 mm, e.g., 9.6 mm, D13 may be about 0.3-0.5 mm, e.g., 0.35 mm, D14 may be about 0.4-0.6 mm, e.g., 0.5 mm, and D15 may be about 0.3-0.5 mm, e.g., 0.4 mm. Although specific dimensions and ranges are indicated, it is to be understood that these dimensions and ranges are merely exemplary and other dimensions and ranges are possible depending on application. For example, the exemplary dimensions may vary by 10-20% or more or less depending on application.

3.3 Cushion Higher On Nasal Bridge

[00155] Figs. 35-1 and 35-2 illustrate a full-face cushion 244 adapted to engage the patient's face generally along nasal bridge, cheek, and lower lip/chin regions of the patient's face. In this embodiment, the cushion 244 is structured such that it is positioned higher on the bridge of the nose for sealing and comfort (e.g., with respect to the cushion 44 described above). The cushion 244 may also be better for anthropometrics, i.e., the cushion will fit more people.

[00156] In an embodiment, the cushion 244 may include a concertina section as described below (e.g., in the nasal bridge region) to enhance the flexibility of the cushion in use.

3.4 Concertina Section

[00157] As best shown in Figs. 30 and 33, a concertina section 50 may be provided in a nasal bridge region of the cushion and/or frame. As illustrated, the concertina section 50 includes a bellows structure with one or more folds 52 that provide a higher degree of flexibility or increased movement. That is, the concertina section 50 provides a higher level of adaptability or flexibility to the nasal bridge region of the cushion/frame which is a more sensitive region of the patient's face in use. Moreover, the concertina section 50 provides increased movement without compromising seal.

[00158] Figs. 32-1 to 32-3 illustrate various views of a concertina section 50 (isolated from the remainder of the cushion/frame) with one or more folds 52 according to an embodiment of the present invention. As best shown in Fig. 32-3, the folds may have different lengths, depths, and/or contours with respect to one another to optimize the concertina effect, e.g., provide sufficient degree of movement without compromising seal.

For example, as shown in Fig. 32-3, each fold 52 includes a first side wall 52(1) and a second side wall 52(2) that interconnects adjacent side walls 52(1).

[00159] In the illustrated embodiment, the first side walls 52(1) and/or the second side walls 52(2) may become progressively longer away from the patient's face. For example, the first side wall 52(1) and/or the second side wall 52(2) adjacent patient's face, or the combination of side walls 52(1) and 52(2), may have a length that is longer than and in some cases significantly longer than the adjacent side wall 52(1) and/or 52(2) (e.g., one side wall at least 25% greater than and up to 5x as long as the other side wall, e.g., 1x, 2x, 3x, or 4x).

[00160] The folds may be constructed and arranged to provide a predetermined order of movement or folding, e.g., folds structured to fold in a sequential or progressive manner wherein one fold collapses before an adjacent fold collapses. For example, upon application of force, the folds closest to the patient's face may fold or collapse before the folds furthest from the patient's face. Also, the folds may be constructed and arranged to provide various degrees of fold or collapse, e.g., folds may fold or collapse more than others.

[00161] In an embodiment of the concertina section shown in Figs. 32-1 to 32-3, D1 may be about 50-60 mm, e.g., 55.7 mm, D2 may be about 5-15 mm, e.g., 9.7 mm, and D3 may be about 0.3-0.5 mm, e.g., 0.4 mm. Although specific dimensions and ranges are indicated, it is to be understood that these dimensions and ranges are merely exemplary and other dimensions and ranges are possible depending on application. For example, the exemplary dimensions may vary by 10-20% or more or less depending on application.

[00162] It should be appreciated that a concertina section 50 may be provided in other regions of the cushion and/or frame, e.g., depending on patient comfort. For example, the concertina section 50 may be provided around the entire perimeter of the cushion and/or frame or may be provided in selected regions of the cushion and/or frame.

[00163] Also, the flexibility of the concertina section 50 may be varied and may be varied in different regions of the cushion and/or frame, e.g., depending on patient comfort. For example, the cushion and/or frame may include a concertina section in the nasal bridge region with a relatively high degree of flexibility and a concertina section in the lower lip/chin region with a relatively low degree of flexibility. The flexibility of the concertina section 50 may be varied by varying the number of folds 52 (e.g., 1-5 folds), the wall lengths, the wall thickness of the folds 52, the depth of the folds 52, etc.

[00164] As noted above, the cushion and frame may be co-molded of two parts with different materials/rigidities or may be integrally formed of the same material. In both embodiments, the concertina section may be provided in the frame and/or the cushion.

[00165] In Figs. 27-30, the cushion 44 and frame 40 are co-molded of two parts with the concertina section 50 provided in the frame 40. The frame 40 and cushion 44 include different rigidities in order to optimize the function of each part. For example, one part (i.e., cushion 44) may be constructed of a relatively soft, supple material to optimize the sealing effect and the other part (i.e., frame 40) may be constructed of a more rigid material to provide adequate support for the cushion while at the same time allowing a sufficient degree of movement to optimize the concertina effect. While the frame is more rigid than the cushion, the frame may be constructed of a flexible material to allow the concertina effect.

[00166] In Fig. 33, the frame 40 and cushion 44 are integrally formed in one piece with the concertina section 50 provided in the frame 40. The material properties and/or dimensions may be selectively modified to optimize sealing and concertina effects.

[00167] For both embodiments of Figs. 27-30 and 33, it should be appreciated that the concertina section may be alternatively provided in the cushion 44 or in both the frame 40 and cushion 44. For example, Fig. 34 illustrates a concertina section 50 integrally formed with the cushion 44 in the nasal bridge region.

4. Elbow

[00168] As shown in Fig. 3, the elbow 1070 (e.g., constructed of a relatively hard material such as polycarbonate or polypropylene) includes a first end portion 1074(1) and a second end portion 1074(2). The first end portion 1074(1) provides an interfacing structure structured to interface or otherwise attach to the frame 1040. The second end portion 1074(2) is adapted to be connected to an air delivery tube.

4.1 Elbow Connection to Frame

[00169] The frame 1040 is structured to maintain the elbow 1070 in an operative position with respect to the patient's face. That is, the frame acts as a carrier and bearing surface for the elbow. The frame and elbow may connect with a friction fit, snap-fit,

mechanical interlock, or other suitable attachment mechanism. However, other suitable arrangements for attaching the elbow to the frame are possible.

[00170] In the illustrated embodiment, the elbow 1070 includes a series of tangs 1075 adapted to releasably engage within the opening 1046 of the frame 1040, e.g., with a snap-fit. The tangs 1075 hold the elbow in place (e.g., preferably a relatively airtight connection) and permit rotation or swiveling of the elbow with respect to the frame.

[00171] That is, the elbow is rotatably attached to the frame so that the elbow may be rotated relative to the frame in use, e.g., 360° rotation. This arrangement allows the elbow to assume different orientations in use, e.g., depending on patient preference. For example, the elbow may assume a first orientation so that the elbow extends generally downwardly from the mask to direct the air delivery tube under the patient's head in use. Alternatively, the elbow may be rotated and assume a second orientation so that the elbow extends upwardly from the mask to direct the air delivery tube over the patient's head in use. In an embodiment, the frame and elbow may be constructed of dissimilar materials to prevent or at least reduce squeak between the components in use.

[00172] The second end portion of the elbow may be provided to a swivel joint adapted to be connected to the air delivery tube. For example, Figs. 27-30 illustrate a swivel joint 80 provided to the second end portion 74(2) of elbow 70. In the illustrated embodiment, the swivel joint 80 is provided to a short tube 82 (e.g., extendable and retractable tube) that interconnects the elbow with the air delivery tube. In an embodiment, the swivel joint 80 may be integrally formed in one piece with the short tube 82.

4.2 AAV

[00173] The elbow 1070 includes a slot 1081 to receive an anti-asphyxia valve (AAV), a port 1079 that is selectively closed by a flap portion of the AAV (depending on the presence of pressurized gas), and structure for attaching the AAV, e.g., with a snap-fit.

[00174] Figs. 27-30 illustrate an exemplary AAV 85 including a flap portion 86 to selectively close port 79 in elbow 70. In this embodiment, a clip portion 88 is provided to the flap portion 86 for attaching the AAV 85 to the elbow 70. In the illustrated embodiment, the flap portion 86 and the clip portion 88 are co-molded with one another to form a one-piece,

integrated component. However, the flap portion 86 and clip portion 88 may be secured to one another in other suitable manners, e.g., mechanical interlock.

[00175] In an embodiment, the flap portion 86 may be constructed of a relatively soft elastomeric material (e.g., silicone) and the clip portion 88 may be constructed of a more rigid material (e.g., rigid plastic) for interfacing with the elbow 70.

[00176] The clip portion 88 of the AAV 85 includes structure for removably interlocking with the elbow 70, e.g., with a snap-fit. For example, the clip portion 88 may include tabs structured to interlock with respective recesses/protrusions provided to the elbow.

[00177] Figs. 35-1 and 35-2 illustrate an elbow 270 including a port 279 that is selectively closed by a flap portion 286 of the AAV 285 (depending on the presence of pressurized gas). Also, Figs. 37-1 to 37-3 illustrate elbow 370 including a port 379 and a slot 381 to retain the AAV.

[00178] Alternative embodiments of the AAV are disclosed in PCT Application No. PCT/AU2006/000031, which is incorporated herein by reference in its entirety.

4.3 Large Diameter End Portion

[00179] As shown in Figs. 27-30, the first end portion 74(1) of the elbow 70 may provide a relatively large diameter which allows the potential for cleaner/smoother lines thereby contributing to the overall mask aesthetic and reduced obtrusiveness. In addition, the relatively large diameter elbow offers the potential for the patient's nose to protrude into the elbow cavity thereby permitting the mask to be brought closer to the patient's face (i.e., reduced obtrusiveness), less moment since center of gravity of mask is closer to the patient's face, and/or improved line of sight.

5. Modular Design

[00180] The mask system provides a modular design that allows different styles and/or sizes of the frame (also referred to as a frame module), shroud (also referred to as a shroud module), cushion (also referred to as a cushion module), and/or elbow (also referred to as an elbow module) to be interchanged or mixed and matched with one another to provide a more

customized mask system for the patient. In addition, such design allows selected modules to be easily replaced, e.g., treatment requirements change, worn out or damaged, etc.

[00181] In an embodiment, the mask system may be provided with a number of different cushions, e.g., each having cushions of different styles and/or sizes (e.g., depending on patient preference and/or fit). For example, the non-face contacting side of each cushion may include a common or universal configuration for interfacing with the frame, and the face-contacting side of the cushion may include different styles and/or sizes. This provides a modular arrangement that allows the frame to be selectively (e.g., and removably) coupled to one of multiple cushion. For example, the different cushions may include different size cushions (e.g., small, medium, and large) and may include a different cushion structures.

[00182] In an embodiment, the mask system may be provided with different shrouds, e.g., each shroud having a different style and/or size (e.g., shroud with different arrangement/style of headgear connectors, shroud with forehead support, different headgear vectors, etc).

[00183] In an embodiment, the mask system may be provided with different frames, e.g., each frame having a different style and/or size (e.g., frame with different vent arrangement, small, medium, and large size frame, etc).

[00184] In an embodiment, the mask system may be provided with a number of different elbows, e.g., each having a vent arrangement, AAV (in the case of an oro-nasal mask), and/or elbow of different styles and/or sizes. In the illustrated embodiment of Figs. 27-30, the vent arrangement 76 and AAV 85 are structured to be removably attachable to the elbow 70. This provides a modular arrangement that allows the elbow to be selectively and removably coupled to one of multiple vent arrangements and/or AAVs. This also allows the vent arrangement and AAV to be easily replaced, e.g., if damaged.

5.1 Shroud to Frame Connection

[00185] The shroud is mounted on the outer surface of the frame, e.g., preferably with a tight, conforming fit on the frame.

5.1.1 Upper Retaining Mechanism

[00186] In the illustrated embodiment of Figs. 1-5, the shroud 1020 is connected to the frame 1040 by an upper retaining mechanism or interfacing structure 1048 located on the top end of the frame and shroud.

[00187] As shown in Figs. 2 to 5, the upper retaining mechanism 1048 is in the form of two taper locks structured to secure the shroud 1020 on the frame 1040 and prevent unintentional disassembly particularly due to headgear forces. In this embodiment, opposing sides of the frame include a female slot 1055 adapted to receive a respective tang protrusion (which tapers along its length) on the underside of the shroud 1020. The tapered protrusion engages within a respective female slot, e.g., with a friction fit.

[00188] Figs. 10 to 19-4 show another embodiment of a mask system 1110 which more clearly illustrates an embodiment of the taper lock. Figs. 10 to 17 show various views of the frame 1140, shroud 1120, and elbow 1170 of the mask system 1110.

[00189] As best shown in Figs. 11 to 13, opposing sides of the top end of the frame 1140 include a platform 1154 which provides a first female slot 1155(1). In addition, the space between the platform 1154 and the outer surface of the frame 1140 defines a second female slot 1155(2). As best shown in Fig. 17, opposing sides of the top end of the shroud 1120 include a tang protrusion 1156 on the underside of the shroud 1120. The tang protrusion 1156 includes a first tang 1156(1) and a second tang 1156(2) that extends generally transverse to the first tang 1156(1). As shown in Figs. 18-1 and 18-2, each tang may taper along its length, i.e., thinner towards its free end.

[00190] Figs. 18-1 and 18-2 and 19-1 to 19-4 sequentially illustrate attachment of the shroud 1120 to the frame 1140. As illustrated, the tangs 1156(1), 1156(2) of each tang protrusion 1156 are structured to engage with respective slots 1155(1), 1155(2), e.g., with a friction fit. As best shown in Figs. 19-1 to 19-4, each slot 1155(2) includes lead-ins or guides 1157 that curve along their length (i.e., extend in vertical and horizontal direction) so as to guide the tang 1156(2) into the slot 1155(2) and aid assembly. Figs. 18-2 and 19-4 show the tangs 1156(1), 1156(2) when fully inserted with respective slots 1155(1), 1155(2).

[00191] In an alternative embodiment, as shown in Fig. 20, the upper retaining mechanism may include a clip-type arrangement. As illustrated, opposing sides of the top end of the frame 1240 provide a shoulder 1255(1) and a tapered protrusion 1255(2). Opposing sides of the top end of the shroud 1220 include a first tang 1256(1) and a second

tang 1256(2) on the underside of the shroud 1220. In use, each first tang 1256(1) is engaged with the respective shoulder 1255(1) and the second tang 1256(2) is engaged or clipped onto the tapered protrusion 1255(2), e.g., with a snap-fit.

5.1.2 Lower Retaining Mechanism

[00192] In an embodiment, the shroud may also be connected to the frame by a lower retaining mechanism located on the bottom end of the frame and shroud. For example, a retaining mechanism may be provided to the opening of the shroud which is structured to interlock or otherwise engage with the opening of the frame.

[00193] For example, as shown in Figs. 14, 15, 17, and 21, the opening 1132 of the shroud 1120 may include structure adapted to engage the collar 1149 surrounding the frame opening 1146 with a snap-fit. As illustrated, the shroud 1120 includes snap fingers 1145(1) (e.g., three snap fingers) and sandwich tabs 1145(2) (e.g., three sandwich tabs) that extend from the opening 1132. The snap fingers and sandwich tabs are alternatively spaced about the opening.

[00194] In use, the snap fingers 1145(1) resiliently deflect (e.g., 0.5 mm deflection) and engage respective part-annular protrusions 1149(1) provided to the collar 1149 (e.g., see Figs. 22 and 23) to provide an initial retention of the shroud 1120 to the frame 1140 (e.g., with allowable stresses), e.g., to facilitate assembly and disassembly. In addition, as the snap fingers 1145(1) engage respective protrusions 1149(1), the sandwich tabs 1145(2) are received in respective recesses 1149(2) provided to the end of the collar 1149 (e.g., see Figs. 22 and 23). When the elbow 1170 is engaged with the frame 1140 (e.g., see Fig. 23), an annular protrusion 1171 on the elbow 1170 is positioned on an opposing side of the sandwich tabs 1145(2) so that the sandwich tabs 1145(2) are sandwiched between the collar 1149 and the elbow 1170. Thus, the sandwich tabs utilize elbow retention forces to retain the shroud on the frame during use. The elbow 1170 has a distal shoulder 1173 adapted to extend under the edge of the frame 1140 to retain the elbow to the frame. The snap fingers 1145(1) allow the shroud to connect to the frame independent of the elbow.

[00195] In an alternative embodiment, as shown in Fig. 24, the shroud's lower section may be structured to clip to a single point below the collar. As illustrated, the lower end of the shroud 1320 includes a snap finger 1345 that is engaged or clipped onto a protrusion

1349(1) spaced below the collar 1349 of the frame 1340, e.g., with a snap-fit. In this embodiment, the protrusion 1349 extends from the cover enclosing auxiliary ports. This arrangement may facilitate molding of the collar on the frame, e.g., uniform thickness of the collar prevents molding distortions. In addition, removal of the protrusions 1149(1)/recesses 1449(2) from the collar may reduce the risk of leak.

5.1.3 Finger Grip

[00196] In an embodiment, the outer surface of the frame 1040 may include finger grips or recessed portions 1097, which are positioned to be exposed under the shroud 1020. The finger grips are adapted to allow the patient an improved ability to grip the frame and/or shroud which is particularly useful when disengaging the shroud from the frame.

5.1.4 Alternative Interfacing Structure

[00197] In an alternative embodiment, as shown in Fig. 27-30, the shroud 20 includes an open construction that provides an annular or part annular retaining portion 22 structured to retain the frame 40 and the elbow 70. As illustrated, the annular retaining portion 22 includes an interfacing structure 23 along an inner edge that is adapted to interface with or otherwise removably connect to an interfacing structure 48 along the outer perimeter of the frame 40 (e.g., see Fig. 28). In the illustrated embodiment, the interfacing structure 23 is in the form of opposed flanges 23(1) that are adapted to interlock with respective locking structures 48(1) provided on opposing sides of the frame 40. However, other suitable arrangements for attaching the frame 40 to the shroud 20 are possible, e.g., friction fit, snap-fit, mechanical interlock, or other suitable attachment mechanism.

[00198] For example, the frame 40 may be coupled to the shroud 20 in a manner that allows the frame 40 to be locked in different angular positions with respect to the shroud 20, e.g., pivotally mounted.

5.1.5 Alternative Upper Headgear Connector

[00199] Figs. 40-1 to 40-7 illustrate a frame and a clip-on upper headgear connector or rigidizer according to another embodiment of the present invention.

[00200] The frame 442 includes an opening 449 adapted to engage a frame shroud and/or elbow. Around and under the opening 449 is the u-shaped slot 402 for gas washout and auxiliary ports 443 on each side thereof.

[00201] In this embodiment, each upper side of the frame 442 includes a retaining member 433 and an upper intermediate portion of the frame 442 includes retaining grooves 435, which are structured and arranged to retain an upper headgear connector or rigidizer 424.

[00202] As best shown in Figs. 40-6 and 40-7, the upper headgear connector 424 includes a pair of elongated arms or rigidizers 426 coupled by a pair of wire members 428. Each rigidizer 426 includes a slot 427 at its free end adapted to receive a respective headgear strap in use.

[00203] In use, the upper headgear connector 424 is adapted to clip onto the frame 442 (e.g., see Figs. 40-1 and 40-2). Specifically, intermediate portions of the wire members 428 are received in respective grooves 435 of the frame 442, and end portions of the wire members 428 extend through respective retaining members 433 with the rigidizers 426 providing a shoulder to interlock with respective retaining members 433. Figs. 40-4 and 40-5 show an upper portion of a retaining member 433 to illustrate the groove 433(1) adapted to receive a respective wire. As illustrated, the end of the groove 433(1) includes tapered side walls 433(2) and drops off towards a rear side 433(3) to position the rigidizers 426 into interlocking engagement with the retaining member 433.

[00204] Figs. 41-1 to 41-12 illustrate an upper portion of a frame and a clip-on upper headgear connector or rigidizer according to another embodiment of the present invention.

[00205] As illustrated, the upper portion of the frame 542 includes a retaining member 533 on each side thereof and a retaining groove 535 along an intermediate portion thereof, which are structured and arranged to retain an upper headgear connector or rigidizer 524.

[00206] As best shown in Figs. 41-5 and 41-12, the upper headgear connector 524 includes a pair of elongated arms or rigidizers 526 coupled by a connecting portion 528. Each rigidizer 526 includes a slot 527 at its free end adapted to receive a respective headgear strap in use. In addition, the upper headgear connector 524 includes a clip structure 525 on each side of the connecting portion 528.

[00207] In use, the upper headgear connector 524 is adapted to clip onto the frame 542 (e.g., see Figs. 41-1 and 41-2). Specifically, the connecting portion 528 is received in the

groove 535 of the frame 542, and the clip structures 525 releasably interlock with respective retaining members 533. As best shown in Figs. 41-3 and 41-4, each retaining member 533 provides a cross-bar, and each clip structure 525 provides a v-shaped configuration that is adapted to resiliently deflect through the cross-bar and provide a shoulder to releasably interlock with the cross-bar.

[00208] Figs. 42-1 to 42-7 illustrate an alternative embodiment for engaging the upper headgear connector with the frame. As illustrated, each retaining member 533 provides an open-ended cross-bar, and each clip structure 525 provides an elongated arm. In this embodiment, the cross-bar is structured to resiliently deflect to allow the clip structure 525 to extend through the cross-bar and releasably engage the cross-bar, e.g., with a friction fit. In addition, the upper headgear connector 524 of Figs. 42-1 to 42-7 includes a c-shaped clip structure 529 adapted to interlock with a tab 549 provided to the frame 542 (see Figs. 42-1 and 42-2).

5.1.6 Grommet Attachment

[00209] Figs. 44 and 45 illustrate an alternative mask arrangement in which the shroud is attached to the frame via a grommet.

[00210] For example, as shown in Fig. 44, the frame 740 includes a grommet 745 (e.g., constructed of a rubber) and the shroud 720 includes an opening 725 adapted to receive the grommet 745 to secure the shroud 720 to the frame 740. As illustrated, the shroud 720 includes elongated upper and lower arms 724, 726 each with a slot 727 at its free end adapted to receive a respective headgear strap in use.

[00211] Fig. 45 illustrates an alternative shroud 820 which includes a single arm with a slot 827 at each end adapted to receive a respective headgear strap in use. In addition, the shroud 820 provides an elongated inner slot 825 adapted to receive the grommet 745 of the frame 740. The elongated slot 825 allows the grommet 745 to be fixed in one of multiple positions along the length of the slot 825, in contrast to the shroud 720 which provides a single fixed position. In an embodiment, the shroud 820 may be slidable with respect to the grommet 745 to allow an infinite number of positions with respect to the frame 740.

[00212] In each embodiment, the grommet 745 (e.g., constructed of a rubber) fixes the shroud in position but the inherent flexibility of the grommet provides a flexible connection

to decouple the shroud from the frame and allow a range of movement between the two components, e.g., like a ball joint or gimbal. Such arrangement helps with fitting and sealing of the mask to the patient's face. That is, the flexible connection allows the mask to selectively adjust and/or self-fit with the patient's face.

5.2 Cushion to Frame Connection

[00213] In Figs. 1-8, the non-face contacting side of the cushion 1060 is connected to frame 1040 in a tongue and groove relationship. The tongue 1066 (see Figs. 1C, 1D, and 8) of the cushion 1060 is inserted within a groove 1041 (see Figs. 1C and 1D) provided along the perimeter of the frame 1040. The tongue and groove relationship may also include a locking lip or sealing lip 1068 (see Figs. 1C, 1D, and 8) on the cushion that is adapted to interlock with an undercut bead 1042 (see Figs. 1C and 1D) within the frame groove to fixably retain the cushion to the frame.

[00214] In the illustrated embodiment, the cushion 1060 also includes one or more positioning features located around its circumference to assist with proper alignment of the cushion with the frame 1040. As shown in Fig. 7, the cushion 1060 includes notches and/or protrusions (e.g., two notches 1067 and one protrusion 1069) adapted to engage with complementary features in the frame, e.g., interlocking relationship.

5.2.1 Co-Molding Frame and Cushion

[00215] In an embodiment, as shown in Figs. 27-30, the frame 40 and cushion 44 may be co-molded with one another to form a one-piece, integrated component. For example, the frame 40 may be molded of a first material adapted to interface with the shroud 20 and the cushion 44 may be co-molded onto the frame 40 of a second material adapted to interface with patient's face.

[00216] In such embodiment, the cushion 44 may be constructed of a relatively soft elastomeric material (e.g., silicone) for sealing and the frame 40 may be constructed of a more rigid material than the cushion 44 (e.g., polycarbonate, polypropylene) for interfacing with the frame.

[00217] Co-molding the frame 40 to the cushion 44 provides a chemical bond without necessarily forming a mechanical interlock. As a result, the connection includes no cracks, a

gas tight seal, and clean interface. Moreover, such co-molded connection relaxes tolerances as the mold materials are sufficiently flexible to fill in any gaps at the interface between the frame 40 and the cushion 44. Also, the co-molded frame/cushion provides a reduced part count (reduced cost) and facilitates assembly/disassembly to the shroud 20.

[00218] In an alternative embodiment, as shown in Fig. 33, the frame 40 and cushion 44 may be integrally formed in one piece, e.g., of a silicone material. That is, the frame 40 may have the same shape and structure as described above, but be integrally molded of the same material, e.g., silicone.

[00219] In an embodiment, the integrally formed frame 40/cushion 44 may be co-molded to the shroud 20, e.g., constructed of polycarbonate or polypropylene. For example, the shroud 20 may be constructed of a relatively rigid material (e.g., polycarbonate or polypropylene) and the frame 40/cushion 44 may be co-molded onto the shroud 20 of a relatively soft elastomeric material (e.g., silicone).

5.3 Vent Arrangement

[00220] In Figs. 1, 1B, 1C, 1D, and 2-5, the vent arrangement 1076 is provided to the frame and includes a plurality of holes 1077 (e.g., 5-100 holes, e.g., 20-50 holes, or about 35 holes) oriented at an angle (e.g., 45°) on the outer surface of the frame so as ensure the exhausted air is directed away from the patient and preferably their bed partner when the patient is sleeping. As shown in Figs. 1C and 1D, each hole 1077 may include a contour or taper along its length. However, it should be appreciated that the vent arrangement may include other suitable arrangements, e.g., different number of holes, hole arrangement, positioning on frame, vent provides part pf interlocking structure with shroud, etc.

[00221] Fig. 35-1 illustrates a vent arrangement 276 provided to the frame 240 for gas washout. In the illustrated embodiment, the vent arrangement 276 is in the form of a vent insert (e.g., elastomeric vent insert) that is adapted to be removably supported within an outlet opening in the frame 240. The vent insert may be similar those described in U.S. Patent Nos. 6,561,190, 6,561,191, and 7,207,335, each of which is incorporated herein by reference in its entirety. However, it should be appreciated that the vent arrangement may have other suitable forms (e.g., vent holes in frame 40 (Fig. 28), etc.).

[00222] Figs. 37-3, 39-2, and 39-4 illustrate a frame 340 that includes a u-shaped slot 302 that receives a u-shaped plug-type vent 305 for gas washout. As illustrated, the plug-type vent 305 wraps around and under the opening in the frame 340 for the elbow 370. The plug-type vent 305 includes a plurality of tracks or grooves 307 on each side thereof. In use, the grooved plug-type vent 305 forms a seal with the slot 302 so that exhausted air can exit between the slot walls and the grooves 307 on the plug-type vent 305. In an embodiment, the port caps 347 may be integrated or incorporated into the plug-type vent 305 (e.g., integrally formed in one piece). Further details of such a plug-type vent arrangement are provided in U.S. Patent Application No. 12/230,120, filed August 22, 2008, which is incorporated herein by reference in its entirety. Figs. 39-2 to 39-6 show the frame 340 with the grooved plug-type vent 305 removed so as to more clearly illustrate the u-shaped slot 302 and auxiliary ports 343 on each side thereof.

[00223] Also, it should be appreciated that the vent arrangement may be provided to the elbow. For example, as shown in Figs. 27-30, the vent arrangement 76 is in the form of a vent insert that is adapted to be removably supported within an outlet opening in the elbow 70. In an embodiment, the vent arrangement 76 includes a base adapted to be supported within the outlet opening, one or more grill components or media (e.g., filter, membrane, or other porous material) provided to the base and structured to diffuse vent flow, and a cover to maintain the grill components/media within the base. Only the cover 77 of the vent arrangement 76 is visible in Figs. 27-30.

[00224] Exemplary embodiments of such a vent arrangement are disclosed in U.S. Patent Application No. 12/230,120, filed August 22, 2008, which is incorporated herein by reference in its entirety.

[00225] However, it should be appreciated that the vent arrangement may include other suitable arrangements, e.g., vent insert with one or more vent holes.

[00226] Also, the elbow may provide an alternative venting arrangement to the vent insert. For example, as indicated in dashed lines in Fig. 30, the first end portion 74(1) of the elbow 70 (e.g., along the interfacing structure 75) may include one or more vent holes 276 for gas washout. The one or more holes 276 may be provided to a soft part (e.g., silicone seal as described below) and/or a hard part (e.g., polycarbonate, polypropylene) of the elbow. The holes 276 may extend around the entire perimeter of the first end portion 74(1) or may extend

along one or more portions of the first end portion 74(1). It is noted that providing vent holes along the entire perimeter of the elbow may help to disperse the vent flow in use. However, other suitable hole arrangements, hole numbers, and/or hole shapes along the first end portion 74(1) and/or other portions of the elbow are possible.

5.4 Ports

[00227] In Figs. 1-5, the base of the frame 1040 includes two ports 1043 positioned so that in use, oxygen or other breathable gas can be delivered close to the patient's nares or pressure monitoring equipment can be attached. The ports 1043 may also be used to attach additional medical equipment such as pressure or flow sensors. The ports may be selectively closable or sealable by a ports cap.

[00228] In an alternative embodiment, as shown in Figs. 25 and 26, the frame 1040 may include a side port 1043.1, e.g., in addition to or as an alternative to the ports 1043.

[00229] Figs. 35-1 and 35-2 show a frame 240 that includes an auxiliary port or spigot 243 on an upper portion of the frame, e.g., for supplemental oxygen, measurement device, etc.

[00230] In Figs. 37-1 to 37-3 and 39-1 to 39-6, the frame 340 includes an auxiliary port or spigot 343 on each side thereof, e.g., for supplemental oxygen, measurement device, etc. Port caps 347 are provided to seal respective ports 343.

6. Interface Seal

[00231] In an embodiment, a seal may be provided at the interface between the elbow and the shroud, at the interface between the frame and the shroud, and/or at the interface between the elbow and the frame. For example, a seal (e.g., elastomeric, ring-shaped seal) may be formed separately from the modules and attached at the interface (e.g., sandwiched between modules, adhesive, etc.). Alternatively, a seal may be co-molded with one or more of the modules. In an embodiment, a silicone lip seal may be provided to the frame to seal against the elbow, thereby reducing leak.

[00232] In another embodiment, as shown in Fig. 27-30, the interfacing structure 75 of the elbow 70 may be constructed of a relatively soft, sealing material (e.g., silicone, which may be co-molded to the harder material of the elbow) that is structured to provide a seal at

the interface between the elbow 70 and the shroud 20. Also, the relatively soft interfacing structure 75 (e.g., silicone) provides a "soft" attachment to the relatively hard shroud 20 (e.g., polycarbonate, polypropylene) which may allow an interference type fit. As noted above, one or more vent holes may be provided to the softer interfacing structure and/or the harder elbow.

[00233] While the invention has been described in connection with what are presently considered to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the invention. Also, the various embodiments described above may be implemented in conjunction with other embodiments, e.g., aspects of one embodiment may be combined with aspects of another embodiment to realize yet other embodiments. Further, each independent feature or component of any given assembly may constitute an additional embodiment. Furthermore, each individual component of any given assembly, one or more portions of an individual component of any given assembly, and various combinations of components from one or more embodiments may include one or more ornamental design features. In addition, while the invention has particular application to patients who suffer from OSA, it is to be appreciated that patients who suffer from other illnesses (e.g., congestive heart failure, diabetes, morbid obesity, stroke, bariatric surgery, etc.) can derive benefit from the above teachings. Moreover, the above teachings have applicability with patients and non-patients alike in non-medical applications.

WHAT IS CLAIMED IS:

1. A mask system for use with a flow generator in the treatment of sleep disordered breathing to enable a supply of air at positive pressure to be delivered to a patient's airways, the mask system comprising:

a shroud module;

a cushion module provided to the shroud module, the cushion module defining a breathing chamber;

a vent arrangement with more than one hole for gas washout from the breathing chamber;

an elbow provided to the shroud module and adapted to be connected to an air delivery tube to deliver said air at positive pressure to the patient; and

headgear removably attachable to the shroud module,

wherein:

the shroud module is structured to retain the elbow, the shroud module being structured to act as a bearing surface for the elbow, the shroud module being structured to hold and secure the cushion module in an operative position with respect to the patient's face, the shroud module including headgear connectors to connect with the headgear, each of the headgear connectors being adapted to receive a respective headgear strap of the headgear,

the cushion module includes a frame of relatively harder material and a cushion of relatively softer material provided to the frame such that the frame and the cushion form a one-piece integrated component, the frame being adapted to interface with the shroud module, the frame defines the breathing chamber, the frame including an opening allowing said air at positive pressure to be delivered from the elbow to the breathing chamber, the cushion being adapted to seal with the patient's face along nasal bridge, cheek, and chin regions of the patient's face, and

the elbow includes an anti-asphyxia valve and a port that is selectively closed by a flap portion of the anti-asphyxia valve depending on the presence of pressurized gas, the elbow including a first end portion and a second end portion, the first end portion being attached to the shroud module, the second end portion being provided to a swivel joint adapted to be

connected to the air delivery tube, the elbow being attached to the shroud module so that the elbow is permitted to be rotated relative to the shroud module, so as to allow the air delivery tube to assume different orientations relative to the mask system in use.

2. The mask system according to claim 1, wherein the shroud module includes a portion to provide forehead support.
3. The mask system according to any one of claims 1-2, wherein the headgear connectors include four headgear connectors.
4. The mask system according to any one of claims 1-3, further comprising a concertina section that is provided in a nasal bridge region of the cushion, the concertina section including one or more folds that provide a degree of flexibility or movement relative to the frame without compromising seal.
5. The mask system according to claim 4, wherein the concertina section is provided only to the nasal bridge portion.
6. The mask system according to any one of claims 1-5, wherein the shroud module is modularly structured to be selectively and removably coupled to each of a small, medium and large size cushion module.
7. The mask system according to any one of claims 1-6, wherein a portion of the frame remains uncovered by the shroud module when the shroud module and the frame are engaged.
8. The mask system according to any one of claims 1-7, wherein the elbow is rotatable into a first orientation extending generally downward from the cushion module so as to direct the air delivery tube under the patient's head in use, and the elbow is rotatable into a second orientation extending generally upward from the cushion module so as to direct the air delivery tube over the patient's head in use.

9. The mask system according to any one of claims 1-8, wherein the elbow is rotatably attached to the shroud module so that the elbow is 360 degrees rotatable in use.
10. The mask system according to any one of claims 1-9, wherein the cushion module is sized and dimensioned to allow the patient's nose to protrude at least into the breathing cavity of the frame.
11. The mask system according to any one of claims 1-10, wherein the shroud module and the frame are structured and configured to prevent rotation relative to one another when the shroud module and the frame are attached.
12. The mask system according to any one of claims 1-11, wherein the shroud module includes a retaining portion having a pair of first interfacing structures and the frame of the cushion module includes a pair of second interfacing structures structured to interlock with the pair of first interfacing structures.
13. The mask system according to claim 12, wherein the first pair of interfacing structures are provided to an inner side of the shroud module, on opposed sides of an aperture in the shroud module.
14. The mask system according to any one of claims 1-13, wherein the shroud module is structured to act as a bearing surface for the elbow.
15. The mask system according to any one of claims 1-14, wherein the frame and the cushion are co-molded with one another to form an integrated co-molded component, the relatively harder material of the frame comprising a first molded material adapted to interface with the shroud module, and the relatively softer material of the cushion comprises a second molded material adapted to interface with patient's face.
16. The mask system according to claim 15, wherein the integrated co-molded component comprises a chemical bond between the first and second molded materials.

17. The mask system according to any one of claims 1-16, further comprising a mechanical interlock to mechanically interlock the elbow and the shroud module to form a combined elbow and shroud module, and a snap-fit attachment mechanism that releasably snap-fits the combined elbow and shroud module with the frame of the cushion module.
18. The mask system according to any one of claims 1-16, wherein the cushion module and the shroud module are attached via a snap fit attachment mechanism.
19. The mask system according to any one of claims 1-18, wherein the shroud module includes an annular or part annular retaining portion structured to hold and secure the cushion module.
20. The mask system according to claim 19, wherein the retaining portion is part annular.
21. The mask system according to any one of claims 19 or 20, wherein the retaining portion includes opposed flanges adapted to interlock with respective locking structures.







Fig. 1B








Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

10/81




Fig. 7

11/81




Fig. 8




Fig. 8B




Fig. 9




Fig. 10

14/81




Fig. 11




Fig. 12




Fig. 13

17/81




Fig. 14




Fig. 15




Fig. 16

19/81




Fig. 17




Fig. 18-1




Fig. 18-2




Fig. 19-1




Fig. 19-2




Fig. 19-3




Fig. 19-4




Fig. 20

27/81




Fig. 21




Fig. 22

28/81




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30




Fig. 31-1

37/81




Fig. 31-2

38/81




Fig. 31-3




Fig. 31-5




Fig. 31-4

40/81




Fig. 32-1

41/81




Fig. 32-2




Fig. 32-3




Fig. 34

45/81




Fig. 35-1




Fig. 35-2

47/81




Fig. 35-3




Fig. 36




Fig. 37-1




Fig. 37-2




Fig. 37-3

52/81




Fig. 38-1




Fig. 38-2

53/81




Fig. 38-3




Fig. 38-4




Fig. 38-5

54/81




Fig. 39-1

55/81




Fig. 39-2

56/81




Fig. 39-3

57/81




Fig. 39-4

58/81




Fig. 39-5

59/81




Fig. 39-6




Fig. 40-1

61/81




Fig. 40-2




Fig. 40-3




Fig. 40-4




Fig. 40-5

65/81




Fig. 40-6

66/81




Fig. 40-7

67/81




Fig. 41-1




Fig. 41-2




Fig. 41-3




Fig. 41-4

69/81




Fig. 41-5




Fig. 41-6




Fig. 41-7

70/81




Fig. 41-8




Fig. 41-9




Fig. 41-10

71/81




Fig. 41-11




Fig. 41-12

72/81




Fig. 42-1




Fig. 42-2

73/81




Fig. 42-3




Fig. 42-4




Fig. 42-5

75/81




Fig. 42-6

76/81




Fig. 42-7

77/81




Fig. 43-1




Fig. 43-2

79/81




Fig. 43-3




Fig. 43-4

81/81




Fig. 44




Fig. 45