



US00RE50333E

(19) **United States**
(12) **Reissued Patent**
Minnette et al.

(10) **Patent Number:** **US RE50,333 E**
(45) **Date of Reissued Patent:** **Mar. 11, 2025**

(54) **PACKAGE**

(71) Applicant: **Berry Global, Inc.**, Evansville, IN (US)

(72) Inventors: **Jeffrey C. Minnette**, Evansville, IN (US); **Eric W. Kost**, Evansville, IN (US)

(73) Assignee: **Berry Global, Inc.**, Evansville, IN (US)

(21) Appl. No.: **17/575,098**

(22) Filed: **Jan. 13, 2022**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **10,532,872**
Issued: **Jan. 14, 2020**
Appl. No.: **14/952,103**
Filed: **Nov. 25, 2015**

U.S. Applications:

(60) Provisional application No. 62/089,074, filed on Dec. 8, 2014.

(51) **Int. Cl.**

B65D 77/20 (2006.01)
B65D 3/06 (2006.01)
B65D 3/30 (2006.01)
B65D 43/02 (2006.01)

(52) **U.S. Cl.**

CPC **B65D 77/2032** (2013.01); **B65D 3/06** (2013.01); **B65D 3/30** (2013.01); **B65D 43/02** (2013.01); **B65D 2577/2083** (2013.01)

(58) **Field of Classification Search**

CPC **B65D 77/2032**; **B65D 3/06**; **B65D 3/30**; **B65D 2577/2083**

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

1,824,907 A	8/1929	Lermer	
2,196,206 A	3/1936	Foss	
2,277,066 A	2/1938	Bogner	
2,123,723 A *	7/1938	Furrer	B65D 57/00 229/162.1
2,422,239 A	6/1947	Holt	
3,051,580 A	12/1958	Brennan	
2,941,710 A *	6/1960	Smith	B65D 7/28 229/199
2,982,440 A	5/1961	Harrison	
3,410,939 A	3/1965	Driza et al.	
3,428,238 A	2/1969	Sherlby et al.	
3,434,652 A	3/1969	Shore	
3,447,714 A	6/1969	Elliot	
3,452,896 A	7/1969	Elliot	
3,452,921 A	7/1969	Donovan	
3,463,350 A	8/1969	Unger	
3,471,075 A	10/1969	Wolf	
3,685,685 A	8/1972	Phillips	
3,753,512 A	8/1973	Curry	
3,787,547 A	1/1974	Marco	

(Continued)

OTHER PUBLICATIONS

International Search Report dated Jun. 6, 2013, relating to International Application No. PCT/US2013/033153.

(Continued)


Primary Examiner — Terrence R Till

(57)

ABSTRACT

A package includes a lid and a container. The lid is adapted to mate with a brim of the container to close a top opening arranged to open into an interior product-storage region formed in the container.

11 Claims, 21 Drawing Sheets



US RE50,333 E

(56)

References Cited

U.S. PATENT DOCUMENTS

3,870,188	A	3/1975	Buffett	6,279,505	B1	8/2001	Plester et al.
3,923,190	A	12/1975	Roth	6,296,137	B1	10/2001	Bjørnsen
3,952,677	A	4/1976	Hartman et al.	6,305,546	B1	10/2001	Saunders et al.
3,956,550	A	5/1976	Sutch	6,320,172	B1	11/2001	Watkins
3,977,153	A	8/1976	Schrenk	6,325,213	B1	12/2001	Landis
4,040,461	A *	8/1977	Carson	6,363,695	B1	4/2002	Mykkänen
			B65D 7/18	6,375,023	B1	4/2002	Lecinski et al.
			206/515	6,390,323	B1	5/2002	Alticosalian
4,120,932	A	10/1978	Roth	6,399,170	B1	6/2002	Hock et al.
4,154,345	A	5/1979	Davis et al.	6,413,466	B1	7/2002	Boyd et al.
4,210,674	A	7/1980	Mitchell	6,460,714	B1	10/2002	Silvers et al.
4,215,797	A	8/1980	Chen	6,460,720	B1	10/2002	Massey et al.
4,270,475	A	6/1981	Fletcher	6,513,703	B2	2/2003	Becker
4,284,671	A	8/1981	Cancio et al.	6,521,158	B2	2/2003	Ichikawa et al.
4,292,355	A	9/1981	Bonis	6,544,613	B1 *	4/2003	Varadarajan
4,398,648	A	8/1983	Cerny et al.				B65D 77/2032
4,446,969	A	5/1984	Tyler	6,554,154	B1	4/2003	220/359.3
4,526,290	A	7/1985	Cerny	6,588,654	B2	7/2003	Chauhan et al.
4,542,029	A	9/1985	Caner et al.	6,627,278	B1	9/2003	Nakashima
4,641,005	A	2/1987	Seiferth	6,648,164	B1	11/2003	Sandstrom et al.
4,685,273	A	8/1987	Caner et al.	6,651,874	B1	11/2003	DeCola et al.
4,753,351	A	6/1988	Guillin	6,672,473	B2	1/2004	Pedersen
4,794,008	A	12/1988	Schmidt et al.	6,673,403	B1	1/2004	Torniainen et al.
4,809,876	A	3/1989	Tomaswick et al.	6,682,764	B1	1/2004	Shiiki et al.
4,859,822	A	8/1989	Ragusa et al.	6,685,049	B1	2/2004	Morris et al.
4,880,129	A	11/1989	McHenry et al.	6,685,049	B1	2/2004	Paladino
4,883,190	A	11/1989	Thomas	6,699,543	B1	3/2004	Agarwal
4,900,163	A	2/1990	Mack	6,712,232	B2	3/2004	Tanaka et al.
4,913,307	A	4/1990	Takata et al.	6,718,664	B2	4/2004	Williams
4,925,684	A	5/1990	Simon	6,722,518	B1	4/2004	Bartz
4,927,677	A	5/1990	Kasai	6,729,494	B2	5/2004	Portman et al.
4,948,006	A	8/1990	Okabe	6,729,495	B2	5/2004	Gardiner
4,959,446	A	9/1990	Davis et al.	6,763,962	B1	7/2004	Wang
4,964,205	A	10/1990	Coffman	6,763,968	B1	7/2004	Boyd et al.
4,982,872	A *	1/1991	Avery	6,808,753	B2	10/2004	Rule et al.
			B65D 25/14	6,811,826	B2	11/2004	Rule et al.
			220/62.13	6,868,980	B2	3/2005	Schultz et al.
4,988,841	A	1/1991	Pesheck et al.	6,870,145	B2	3/2005	Watkins
5,035,344	A	7/1991	Christopher	6,874,650	B2	4/2005	Welsh et al.
5,039,001	A	8/1991	Kinigakis et al.	6,881,286	B2	4/2005	Drummond et al.
5,045,369	A	9/1991	Kobayashi et al.	6,905,769	B2	6/2005	Komada
5,048,977	A	9/1991	Robbins, III	6,910,599	B2	6/2005	Tucker et al.
5,096,306	A	3/1992	Perrson et al.	6,919,135	B2	7/2005	Kasahara
5,098,751	A	3/1992	Tamura et al.	6,949,275	B2	9/2005	Johansson
5,165,568	A	11/1992	Wischusen, III	6,960,316	B2	11/2005	Brown et al.
5,176,284	A	1/1993	Sorensen	7,000,801	B2	2/2006	Rodriguez
5,176,314	A	1/1993	Akazawa et al.	7,004,345	B2	2/2006	Turner et al.
5,217,737	A	6/1993	Gygax et al.	7,017,773	B2	3/2006	Gruber et al.
5,236,102	A	8/1993	Quittmann et al.	7,022,955	B2	4/2006	Watkins
5,257,709	A	11/1993	Okabe et al.	7,090,880	B1	8/2006	Droste et al.
5,277,310	A *	1/1994	Mertz	7,097,063	B2	8/2006	Tucker et al.
			B65D 5/5028	7,097,066	B2	8/2006	Tucker et al.
			206/320	7,108,441	B2 *	9/2006	Altonen
							B65D 83/206
							220/9.1
5,360,649	A	11/1994	Sato et al.	7,112,356	B2	9/2006	Nomula et al.
5,428,943	A	7/1995	Balcombe	7,118,800	B2	10/2006	Shirane et al.
5,429,833	A	7/1995	Wyslotsky	7,122,234	B2	10/2006	Olofsson et al.
5,445,292	A	8/1995	Slomski et al.	7,128,233	B2	10/2006	Hogan
5,482,179	A	1/1996	Bruhn	7,131,289	B2	11/2006	Harl et al.
5,705,239	A	1/1998	Andersen et al.	7,137,524	B2	11/2006	Nomula
5,772,332	A	6/1998	Geller	7,137,525	B2	11/2006	Gibney
5,782,376	A	7/1998	Brauner et al.	7,178,687	B1	2/2007	Manderfield et al.
5,843,501	A	12/1998	Rubin et al.	7,195,803	B2	3/2007	Andersson et al.
5,928,741	A	7/1999	Andersen et al.	7,198,168	B2	4/2007	Mizuma
5,971,259	A	10/1999	Bacon	7,204,056	B2	4/2007	Sieverding
6,022,913	A	2/2000	Tanaka et al.	7,216,769	B2	5/2007	Palder
6,032,819	A	3/2000	Hanna	7,246,714	B2	7/2007	Garg et al.
6,065,628	A	5/2000	Page	7,261,219	B2	8/2007	Tucker et al.
6,077,578	A	6/2000	Valyi	7,284,673	B2	10/2007	Habeger et al.
6,082,571	A *	7/2000	Avery	7,306,852	B2	12/2007	Komada
			B65D 25/54	7,337,916	B2	3/2008	Clougherty
			220/9.1	7,370,788	B1	5/2008	Otani et al.
6,138,854	A	10/2000	Kaneko et al.	7,371,455	B2	5/2008	Shirane et al.
6,158,608	A	12/2000	Schlattl	7,437,990	B2	10/2008	Duch
6,170,696	B1	1/2001	Tucker et al.	7,458,480	B2	12/2008	Nguyen
6,189,744	B1	2/2001	Prince	7,458,500	B2	12/2008	Whitaker et al.
6,231,237	B1	5/2001	Geller	7,475,787	B2	1/2009	Gruver et al.
			B65D 75/008	7,476,428	B2	1/2009	Bürki et al.
			383/122	7,543,705	B2	6/2009	Yourist
6,257,401	B1	7/2001	Mangla et al.	7,543,713	B2	6/2009	Trude et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,549,540 B2 6/2009 Lee et al.
 7,552,841 B2 6/2009 Hollis et al.
 7,556,168 B2 7/2009 Turner et al.
 7,563,495 B2 7/2009 Anelli
 7,568,590 B1 8/2009 Gross et al.
 7,571,827 B2 8/2009 Haley et al.
 7,584,866 B2 9/2009 Selina et al.
 7,631,777 B1 12/2009 Bukowski
 7,644,823 B2 1/2010 Gelardi et al.
 7,644,833 B2 1/2010 Turner et al.
 7,651,651 B2 1/2010 Riffer
 7,665,601 B2 2/2010 Portier
 7,665,623 B2 2/2010 Emmerzaal
 7,681,732 B2 3/2010 Moehlenbrock et al.
 7,694,843 B2 4/2010 Hollis et al.
 7,699,216 B2 4/2010 Smith et al.
 7,726,483 B2 6/2010 Ramanujam et al.
 7,735,674 B2 6/2010 Cai
 7,748,553 B2 7/2010 Akiyama et al.
 7,757,885 B2 7/2010 Goeking et al.
 7,757,887 B2 7/2010 Gardiner
 7,766,168 B2 8/2010 Thrapp et al.
 7,766,178 B2 8/2010 Robinson et al.
 7,766,181 B2 8/2010 Fogle et al.
 7,789,262 B2 9/2010 Niederer et al.
 7,794,149 B2 9/2010 Wilkes
 7,799,400 B2 9/2010 Zihlmann
 7,823,737 B2 11/2010 Noll et al.
 7,824,749 B2 11/2010 Dawes
 7,861,881 B2 1/2011 Ali et al.
 7,862,318 B2 1/2011 Middleton et al.
 7,866,536 B2 1/2011 Calendrille
 7,874,453 B2 1/2011 Church
 7,874,476 B2 1/2011 D'Amato
 7,878,350 B2 2/2011 Ramoundos
 7,882,975 B2 2/2011 Kelly
 7,886,937 B2 2/2011 Py
 7,913,874 B2 3/2011 Gruskin et al.
 7,919,161 B2 4/2011 Ebner et al.
 7,922,021 B2 4/2011 Golden
 7,954,640 B2 6/2011 West et al.
 7,959,038 B2 6/2011 de Oliveira et al.
 7,963,419 B2 6/2011 Burney et al.
 7,980,403 B2 7/2011 Martinez
 7,980,404 B2 7/2011 Trude et al.
 7,984,807 B2 7/2011 Elliott
 8,002,170 B2 8/2011 Dixon-Garrett et al.
 8,038,023 B2 10/2011 Moore et al.
 8,113,368 B2 2/2012 Oguchi et al.
 8,733,572 B2 5/2014 Carmona
 2003/0000862 A1 1/2003 Matushek
 2003/0209556 A1 11/2003 Gruber
 2004/0060458 A1 4/2004 Janka
 2004/0185152 A1 9/2004 Garwood
 2004/0185154 A1 9/2004 Garwood
 2004/0185155 A1 9/2004 Garwood

2004/0185156 A1 9/2004 Garwood
 2004/0232026 A1 11/2004 Goeking et al.
 2005/0017013 A1 1/2005 Peisach
 2005/0031814 A1 2/2005 Dawes
 2005/0074531 A1 4/2005 Patterson
 2005/0077297 A1 4/2005 Marshburn et al. B65D 77/2032
 220/359.2
 2005/0084695 A1 4/2005 Shirane et al.
 2005/0158494 A1 7/2005 Koyama et al.
 2005/0175741 A1 8/2005 Reinders
 2005/0211713 A1 9/2005 Goeking et al.
 2005/0281494 A1 12/2005 Allen et al.
 2005/0284171 A1 12/2005 Harl et al.
 2006/0011635 A1* 1/2006 Shibata B65D 3/06
 220/485
 2006/0029757 A1 2/2006 Komada
 2006/0051463 A1 3/2006 Lopez
 2006/0131306 A1 6/2006 Shinogi
 2006/0175387 A1* 8/2006 Yukumoto B65D 77/2032
 229/123.1
 2006/0191940 A1 8/2006 Heyn
 2006/0201946 A1 9/2006 Witt
 2006/0204695 A1 9/2006 Shirane et al.
 2006/0269767 A1 11/2006 Sankey et al.
 2007/0267374 A1 11/2007 Middleton et al.
 2008/0078766 A1 4/2008 Oberholzer
 2008/0264939 A1 10/2008 Bray
 2009/0081336 A1 3/2009 Tuskiewicz et al.
 2009/0110784 A1 4/2009 Yasumuro et al.
 2009/0302040 A1 12/2009 Fox et al.
 2010/0108693 A1 5/2010 Zhang et al.
 2010/0176134 A1 7/2010 Cramer
 2010/0237069 A1 9/2010 Helou et al.
 2010/0237083 A1 9/2010 Trude et al.
 2011/0049155 A1 3/2011 Levine
 2011/0052106 A1 3/2011 Holmes et al.
 2011/0253713 A1 10/2011 Ichikawa et al.
 2012/0199599 A1 8/2012 Minnette et al.
 2012/0298663 A1 11/2012 Seidel et al.
 2013/0024852 A1 1/2013 Firman et al.
 2013/0099414 A1 4/2013 Minnette
 2013/0104505 A1 5/2013 Minnette
 2013/0292394 A1 11/2013 Minnette et al.
 2014/0367296 A1* 12/2014 Berger B65D 77/0453
 206/494

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Jan. 20, 2016, relating to International Application No. PCT/US2015/062659.
 International Preliminary Report on Patentability and Written Opinion for PCT App. No. PCT/2015/062659 dated May 30, 2017, BP-469 PCT II, 8 pages.
 International Search Report and Written Opinion, Application No. PCT/US2015/062659, dated Feb. 12, 2016.

* cited by examiner




FIG. 1




FIG. 1A




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

SEE FIG. 12




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 17




FIG. 18





FIG. 19






FIG. 21




FIG. 22




FIG. 23

1

PACKAGE

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

PRIORITY CLAIM

This application claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Application Ser. No. 62/089,074, filed Dec. 8, 2014, each of which is expressly incorporated by reference herein.

BACKGROUND

The present disclosure relates to a package, and in particular to a package made from plastics materials. More particularly, the present disclosure relates to a package that includes a container and a lid for the container.

SUMMARY

According to the present disclosure, a package includes a container and a lid. In illustrative embodiments, the container includes an interior casing comprising side and bottom film panels and a frame comprising a base section coupled to the bottom film panel to form a floor of the container, a brim arranged to lie above the base section, and several upright columns arranged to interconnect the base section and the brim and coupled to the side film panel to form a side wall of the container.

In illustrative embodiments, the frame is overmolded onto the side and bottom film panels that form the interior casing. The frame surrounds and rigidifies the interior casing. The interior casing is formed to provide an interior product-storage region of the container.

In illustrative embodiments, the interior casing is arranged to lie in an interior space bounded by the base section and four upright corner columns. A central portion of the bottom film panel is coupled to upwardly facing surfaces of the base section included in the container. A central portion of the side film panel is coupled to inwardly facing surfaces of the upright corner columns included in the container.

In illustrative embodiments, an upper end of the side film panel is flared outwardly so that an outer surface of that upper end faces downwardly to mate with the brim of the container and an inner surface of that upper end faces upwardly to mate with a lid that is configured to be mounted on the brim to close a top aperture opening into an interior product-storage region bounded by the interior casing.

In illustrative embodiments, an upwardly extending outer end of the bottom film panel is mated with a lower portion of the upright corner columns of the frame. A downwardly extending lower portion of the side film panel is arranged to lie in spaced-apart relation to the lower portion of the upright corner columns of the frame to trap the upwardly extending outer end of the bottom film panel therebetween so as to overlap with the upwardly extending outer end of the bottom film panel.

In illustrative embodiments, the lid of the package includes a pivotable U-shaped closure support appended to the brim to pivot about a horizontal pivot axis. The lid also

2

includes a closure (e.g., film panel) coupled to upwardly facing surfaces of the brim and the pivotable U-shaped closure. The lid includes frangible connectors that are arranged to interconnect an outer edge of the brim and an inner edge of the U-shaped closure support. The first time a consumer opens the package, a pivot-inducing lifting force is applied to an underside of the U-shaped closure support to break the frangible connectors and separate a portion of the closure from a portion of the brim.

Additional features of the present disclosure will become apparent to those skilled in the art upon consideration of illustrative embodiments exemplifying the best mode of carrying out the disclosure as presently perceived.

BRIEF DESCRIPTIONS OF THE DRAWINGS

The detailed description particularly refers to the accompanying figures in which:

FIG. 1 is a perspective view of a first embodiment of a package in accordance with the present disclosure showing that the package comprises a lid and a container and showing that the container includes a frame and an interior casing coupled to an interior surface of the frame to establish a floor and a side wall of the container;

FIG. 1A is an exploded perspective assembly view of the package of FIG. 1 showing that the frame of the container is monolithic and comprises a rectangular base section, a rectangular brim, and four upright corner columns, and showing that the interior casing of the container comprises a bottom film panel adapted to be coupled to the base section of the frame to establish the floor of the container and an endless side film panel adapted to be coupled to the four upright corner columns to establish the side wall of the container;

FIG. 2 is a sectional view taken along line 2-2 of FIG. 1;

FIG. 3 is a side elevation view similar to FIG. 2 with portions broken away showing illustrative dimensions of the container of FIGS. 1 and 2;

FIG. 4 is a right-side elevation view of the package of FIGS. 1-3 with a portion broken away showing additional illustrative dimensions of the container;

FIG. 5 is an enlarged view taken from a first circled region of FIG. 2;

FIG. 6 is an enlarged view taken from the circled region of FIG. 5 showing a portion of the frame and a portion of the side wall included in the interior casing and suggesting that an upwardly facing inner surface of an upper end of the side film panel included in the side wall is arranged to mate with a membrane sheet included in a lid so as to define an interior product-storage region bounded by the interior casing and the membrane sheet of the lid;

FIG. 7 is an enlarged view taken from a first circled region of FIG. 3 showing illustrative dimension of portions of the frame and the interior casing;

FIG. 8 is an enlarged view taken from a second circled region of FIG. 2 showing a lower portion of the frame of the container, a lower portion of the side film panel, and a portion of the bottom film panel;

FIG. 9 is an enlarged view taken from the circled region of FIG. 9 showing that an upwardly extending outer end of the bottom film panel is arranged to overlap a lower portion of the side film panel and lie in a space provided between the lower portion of the side film panel and the frame;

FIG. 10 is an enlarged view taken from a second circled region of FIG. 3 showing illustrative dimensions of portions of the frame and the interior casing;

FIG. 11 is a sectional view taken along line 11-11 of FIGS. 1 and 2 showing that the base section of the frame includes a generally rectangular border strip and a strip rigidifier located at each of the four interior corners of the generally rectangular border strip and coupled to the border strip to lie in an interior region bounded by the border strip;

FIG. 12 is an enlarged view taken from a circled region of FIG. 12;

FIG. 13 is a view similar to FIG. 12 showing various illustrative dimensions of portions of the container;

FIG. 14 is a plan view of a blank used to form the side film panel included in the interior casing of the container;

FIG. 15 is a plan view of a blank used to form the bottom film panel included in the interior casing of the container;

FIGS. 16-23 are a series of photographs of a package in accordance with a second embodiment of the present disclosure;

FIG. 16 is a photograph showing that the container includes an interior casing and a frame and showing that the frame includes, from bottom to top, a rectangular base section, four upright corner columns located at each corner of the container, a brim, and a lid comprising a pivotable U-shaped closure support appended to the brim to pivot about a horizontal pivot axis (when opened as suggested in FIGS. 22 and 23) and a closure coupled to the closure support and to the brim to close a top opening into a product-storage region formed in the container;

FIG. 17 is a photograph of the package of FIG. 16 taken from another perspective showing that a front portion of the U-shaped closure support includes two spaced-apart grip tabs configured to be grasped by a consumer to aid in separating the lid from the container brim to open the package;

FIG. 18 is a photograph of the package of FIGS. 16 and 17 taken from above the container looking downwardly toward the floor of the container;

FIG. 19 is a photograph of the container of FIGS. 16-18 taken from the bottom of the container looking upwardly toward the brim of the container;

FIG. 20 is a photograph of the package of FIGS. 16-19 taken from another perspective;

FIG. 21 is a photograph of a portion of the package of FIGS. 16-20 showing the U-shaped closure support coupled to the brim by two frangible connectors;

FIG. 22 is a photograph showing the closure support being separated from the brim to open the package; and

FIG. 23 is a photograph taken from another perspective showing the U-shaped closure support being separated from the brim after breakage of several of the frangible connectors included in the lid and used initially to anchor a front portion of the U-shaped closure support to an adjacent portion of the brim of the container.

DETAILED DESCRIPTION OF THE DRAWINGS

A package 10 in accordance with a first embodiment of the present disclosure includes a container 12 and a lid 14 as suggested in FIGS. 1-4. An interior casing 16 made of bottom and side film panels 16B, 16S is mounted on inner surfaces of an exterior frame 18 to form container 12 as suggested in FIG. 1A. Bottom and side film panels 16B, 16S overlap when assembled as suggested in FIGS. 8 and 9. Lid 14 is adapted to be coupled to a brim 180 of frame 18 as suggested diagrammatically in FIG. 1 and to an upper portion of side film panel 16S as suggested in FIGS. 5 and 6 to close a container 12.

A package 210 in accordance with a second embodiment of the present disclosure is shown in FIGS. 16-23. Lid 214 of package 210 includes a (1) U-shaped closure support 202 mounted on the brim 280 of frame 210 for pivotable movement about a horizontal pivot axis 202A between a closed position shown in FIGS. 16-18 and an opened position shown in FIGS. 22 and 23 and (2) a closure 204 made of film coupled to U-shaped closure support 202 to move therewith and adapted to mate with brim 280 when the U-shaped closure support 202 is in the closed position as suggested in FIG. 16.

Frame 18 of container 12 includes brim 180, four generally vertical corner columns 181-184, and a base section 185 as shown, for example, in FIG. 1A. Although brim 180 and base section 185 have rectangular shapes as suggested in FIG. 1A, any suitable shape may be used in accordance with the present disclosure. Each corner column 181-184 is arranged to interconnect a corner of brim 180 and a companion corner of base section 185. Brim 180 includes an upwardly facing surface 180U adapted to mate with lid 14 when lid 14 is mounted on container 12 as suggested diagrammatically in FIG. 1. Inner surfaces of brim 180, corner columns 181-184, and base section 185 are arranged to mate with outer surfaces of bottom and side film panels 16B, 16S when interior casing 16 is mounted on frame 18 at a factory to form container 12. Frame 18 is a monolithic component made of a plastic material and is overmolded onto interior casing 16 in any suitable manner in illustrative embodiments.

Brim 180 of container frame 18 includes an upwardly facing endless top strip 180T as shown in FIGS. 1 and 1A. Brim 180 also includes four downwardly extending side members 180S1, 180S2, 180S3, and 180S4 appended to the underside of top strip 180T. Each side member of brim 180 is arranged to interconnect two adjacent corner columns of frame 18 as suggested in FIG. 1. For example, side member 180S1 interconnects corner columns 181 and 182 and side member 180S2 interconnects corner columns 182 and 183.

Base section 185 of container frame 18 includes an endless border strip 185B as shown in FIGS. 1A and 11. Base section 185 also includes four upwardly extending side members 185S1, 185S2, 185S3, and 185S4 appended to the top side of border strip 185B. Each side member of base section 185 is arranged to interconnect two adjacent corner columns of frame 18 as suggested in FIG. 1A. For example, side member 185S3 interconnects corner columns 183 and 184 and side member 185S4 interconnects corner columns 184 and 181. As suggested in FIG. 11, border strip 185B has a generally rectangular shape and a strip rigidifier 185R1, 185R2, 185R3, or 185R4 is located at each of the four interior corners of the generally rectangular border strip 185B and coupled to border strip 185B to lie in an interior region bounded by border strip 185B.

First corner column 181 of container frame 18 has an upper end coupled to a first corner of brim 180 and a lower end coupled to a first corner of base section 185 as suggested in FIG. 1A. In an illustrative embodiment, first corner column 181 includes a first post 181P1 arranged to interconnect side member 185S4 of base section 185 and side member 180S4 of brim 180, a third post 181P3 arranged to interconnect side member 185S1 of base section 185 and side member 180S1 of brim 180, and a second post 181P2 arranged to interconnect border strip 185B of base section 185 and top strip 180T of brim 180. Second post 181P2 is arranged to lie between and interconnect first and third posts 181P1, 181P3. The thickness of the first and third posts 181P1, 181P3 is less than the thickness of the second post

5

181P2 to provide means for minimizing wrinkling of side film panel **16S** of interior casing **16** during overmolding of frame **18** onto interior casing **16**. Such a variation in post thickness also applies to the other corner columns **182-184** in accordance with the present disclosure.

Second corner column **182** of container frame **18** has an upper end coupled to a second corner of brim **180** and a lower end coupled to a second corner of base section **185** as suggested in FIG. 1A. In an illustrative embodiment, second corner column **182** includes a first post **182P1** arranged to interconnect side member **185S2** of base section **185** and side member **180S2** of brim **180**, a third post **182P3** arranged to interconnect side member **185S1** of base section and side member **180S1** of brim **180**, and a second post **182P2** arranged to interconnect border strip **185B** of base section **185** and top strip **180T** of brim **180**. Second post **182P2** is arranged to lie between and interconnect first and third posts **182P1**, **182P3**.

Third corner column **183** of container frame **18** has an upper end coupled to a third corner of brim **180** and a lower end coupled to a third corner of base section **185** as suggested in FIG. 1A. In an illustrative embodiment, third corner column **183** includes a first post **183P1** arranged to interconnect side member **185S2** of base section **185** and side member **180S2** of brim **180**, a third post **183P3** arranged to interconnect side member **185S3** of base section **185** and side member **180S3** of brim **180**, and a second post **183P2** arranged to interconnect border strip **185B** of base section **185** and top strip **180T** of brim **180**. Second post **183P2** is arranged to lie between and interconnect first and third posts **183P1**, **183P3**.

Fourth corner column **184** of container frame **18** has an upper end coupled to a fourth corner of brim **180** and a lower end coupled to a fourth corner of base section **185** as suggested in FIG. 1A. In an illustrative embodiment, fourth corner column **184** includes a first post **184P1** arranged to interconnect side member **185S4** of base section **185** and side member **180S4** of brim **180**, a third post **184P3** arranged to interconnect side member **185S3** of base section **185** and side member **180S3** of brim **180**, and a second post **184P2** arranged to interconnect border strip **185B** of base section **185** and top strip **180T** of brim **180**. Second post **184P2** is arranged to lie between and interconnect first and third posts **184P1**, **184P3**.

Bottom film panel **16B** of interior casing **16** is coupled to base section **185** of frame **18** and lower portions of corner columns **181-184** to establish a floor of container **12** as suggested in FIGS. 1A, 8, and 9. In illustrative embodiments, bottom film panel **16B** is coupled to inner surfaces of border strip **185B**, strip rigidifiers **185R1-4**, and side members **185S1-4**. Bottom film panel **16B** includes a central portion **16B5** and an upright rim **16R** comprising a series of four upwardly extending rim portions **16B1-16B4** as shown, for example, in FIG. 1A. In illustrative embodiments, rim portions **16B1-16B4** cooperate to form an endless rim **16R**. Bottom film panel **16B** is made of any suitable single or multilayer plastic material in illustrative embodiments of the present disclosure.

Side film panel **16S** of interior casing **16** is coupled to brim **180** of frame **18** and to upper portions of corner columns **181-184** and upwardly extending rim portions **16B1-16B4** of bottom film panel **16B** to establish a side wall of container **12** as suggested in FIGS. 1A, 5, and 6. In illustrative embodiments side film panel **16S** is coupled to an outer surface of top strip **180T** of brim **180** and inner surfaces of corner columns **181-184**. Lower portions of side film panel **16S** are also arranged to mate with and overlap

6

upwardly extending rim portions of **16B1-16B4** of bottom film panel **16B** and to lie in spaced-apart relations to interior surfaces of side members **185S1-S4** of base section **185** to trap the upwardly extending rim portions **16B1-16B4** of bottom film panel **16B** there between. Side film panel **16S** is made of any suitable single or multilayer plastics material in illustrative embodiments of the present disclosure.

Side film panel **16S** includes a series of four panel sections **16S1-16S4** as suggested in FIG. 1A. Each panel section **16S1-4** includes an outer surface **160** arranged to face toward the four corner columns **191-194** and an inner surface **161** arranged to face away from the corner columns **181-184** as suggested in FIG. 1. Each panel section **16S1-4** includes an upper end **16S1U-4U** that is flared outwardly as suggested in FIG. 1A and the outwardly flared upper end **16S4U** of fourth panel section **16S4** is shown in more detail in FIGS. 5 and 6 and is representative of the shape and configuration of outwardly flared upper ends **16S1U-3U**.

In illustrative embodiments, interior casing **16** is arranged to lie in an interior space bounded by base section **185** and four upright corner columns **181-184** as suggested in FIGS. 1 and 1A. A central portion **16B5** of bottom film panel **16B** is coupled to upwardly facing surfaces of base section **185** included in container **12**. A central portion of side film panel **16S** is coupled to inwardly facing surfaces of upright corner columns **181-184** included in container **12**. Together, four panel sections **16S1-16S4** cooperate to provide the central portion of the side wall panel **16S**.

In illustrative embodiments, an upper end **16S1U-16S4U** of side film panel **16S** is flared outwardly so that an outer surface of that upper end faces downwardly to mate with brim **180** of container **12** and an inner surface of that upper end faces upwardly to mate with a lid **14** that is configured to be mounted on brim **180** to close a top aperture opening into an interior product-storage region bounded by interior casing **16**.

In illustrative embodiments, an upwardly extending outer rim **16R** of bottom film panel **16B** is mated with a lower portion of the upright corner columns **181-184** of frame **18**. A downwardly extending lower portion of side film panel **16S** is arranged to lie in spaced-apart relation to the lower portion of upright corner columns **181-184** of frame **18** to trap the upwardly extending outer rim **16R** of bottom film panel **16B** therebetween so as to overlap with the upwardly extending outer end of the side film panel **16S**.

In illustrative embodiments, container **12** comprises a box-like interior casing **16** made of a thin film reinforced by a rigid injection-molded frame **18** made of a plastics material. Containers **12** are nestable to minimize pre-filled shipping volumes and are rectangular and stackable to maximize post-filled shelf densities.

Interior casing **16** comprises a side film panel **16S** and a bottom film panel **16B** that overlaps a lower portion of side film panel **16S** at the edges to maintain barrier integrity. Frame **18** is overmolded onto interior casing **16** to add strength and rigidity to container **12** as well as to bond and affix the joints and edges of side and bottom film panels **16S**, **16B**. In illustrative embodiments, the vertical seam of the endless side film panel **16S** is located behind on of the four corner columns **181-184** to hide and protect the seam and to hold the edges in intimate contact to maximize barrier integrity.

In one example, side film panel **16S** is a separate component from bottom film panel **16** as suggested in FIG. 1A. In another example, the side film panel and the bottom film panel may be a monolithic component.

In another example where the interior casing is a monolithic component, bottom wall panel may be quadrilateral in shape and the side wall panel may comprise four separate panel portions spaced apart from one another and coupled to a different side of the bottom wall panel. As a result, the interior casing may have a generally plus-sign shape. During container manufacturing, each panel portion is arranged to overlap a portion of the neighboring panel at an associated upright column. Any suitable number of sides and shapes and panel portions may be used.

Lid 14 comprises a membrane sheet 14M defined by a multilayer film structure that is heat sealed to brim 180 of container 12. Membrane sheet 14M has barrier properties selected to match barrier properties of side and bottom film panels 16S, 16B and includes a peel layer to make it easily removable by a consumer. An overmolded sheet-support frame made of plastic material can be used to surround and support membrane sheet 14M in illustrative embodiments. Peelable and resealable films can also be used to form a membrane sheet to provide a multi-use lid. An alternative illustrative hinged lid 214 having an integrated bail-brim system is disclosed in the embodiment shown in FIGS. 16-23.

In another example, a lid in accordance with the present disclosure may omit a membrane sheet or film component and be formed from a barrier material. In one example, the lid may be injection molded. The lid may be coupled by a snap-fit coupling to the brim of the container and may engage and couple to the upwardly facing surface of the brim and the upper end of the side film panel. The lid may couple to the upwardly facing surface of the brim and the upper end of the side film panel by a heat seal, a pressure sensitive adhesive, or any other suitable alternative or combination thereof.

In illustrative embodiments, a pre-printed sheet of film material is cut in any suitable manner to produce side and bottom film panels 16S, 16B. Side and bottom film panels 16S, 16B are placed on a mold core. Bottom film panel 16B overhangs to create an overlapping engagement with a lower portion of side film panel 16S. Frame 18 is overmolded onto interior casing 16 in a closed mold including the mold core.

Film portions and the frame are affixed and bonded to one another during overmolding. In one illustrative example, the frame is formed by injection molding hot liquid plastics material which interacts with the film portions to cause melting and intermixing at the areas of affixing and bonding.

Once formed, container 12 is filled with a product while container 12 is held in a sealing nest that supports brim 180 of frame 18. Lid 14 is then placed on top of the filled container and oriented properly. Lid 14 is then heat-sealed to another lid 14 to brim 180 and to the upwardly facing flared portion of side film panel 16S.

In illustrative embodiments, frame 18 is made of a polypropylene material. Any suitable film material may be used to form interior casing 16. In illustrative embodiments, the film thickness is about three mil or about four mil and between about 2 mil and about 5 mil.

A package 210 in accordance with a second embodiment of the present disclosure is shown in FIGS. 16-23. Package 210 includes a container 212 and a lid 214. Container 212 is the same as container 12 except that it has a brim 280 that has a shape different than brim 180 of container 12.

Lid 214 includes a U-shaped closure support 202 that is mounted on brim 280 of frame 218 for pivotable movement about a horizontal pivot axis 202A between a closed position shown in FIGS. 16-18 and an opened position shown in FIGS. 22 and 23. A closure 204 made of film is coupled to

U-shaped closure support 202 to move therewith relative to frame 218 and is adapted to mate with brim 280 when U-shaped closure support 202 is in the closed position suggested in FIG. 16.

As suggested in FIG. 18, several frangible connectors 206 are included in lid 214 and formed to retain U-shaped closure support 202 of lid 214 in the closed position alongside brim 280 of container 212 until the lid 214 is opened for the first time by a consumer. A front portion of U-shaped closure support 202 includes two spaced-apart grip tabs 207, 208 configured to be grasped by a consumer to aid in separating lid 214 from container brim 280 to open package 210.

Closure 204 is a membrane sheet that is heat-sealed to U-shaped closure support 202 and to brim 280. To open package 210, a consumer opens lid 214 by lifting up on tabs 207, 208 provided a front corners of U-shaped closure support 202. This separation breaks the frangible connectors 206 and fractures the membrane sheet providing closure 204 over the inner brim area. U-shaped closure support 202 and closure 204 cooperate to form a flip-top lid 214 pivotable about hinge axis 202A.

The invention claimed is:

[1. A package comprising

a container including an interior casing including a side film panel and a bottom film panel coupled together and a frame including a base section coupled to the bottom film panel to form a floor of the container, a brim arranged to lie in spaced-apart relation above the base section, and upright columns arranged to extend between and interconnect the brim and the base section and coupled to the side film panel to form a side wall of the container and

a lid coupled to the container to mate with the brim and close selectively a top aperture formed in the container and arranged to open into the interior product-storage region,

wherein an upper end of the side film panel is flared outwardly so that an outer surface of that upper end faces downwardly to mate with the brim of the container and an inner surface of the upper end faces upwardly to mate with the lid,

wherein the lid includes a closure support coupled to the brim to move relative to the brim and a membrane sheet coupled to an upwardly facing surface of the closure support and to an upwardly facing surface of the brim to cause the membrane sheet to trap the upper end of the side film panel between a portion of the upwardly facing surface of the brim and the membrane sheet so as to overlap with the upper end of the side film panel.]

[2. The package of claim 1, wherein an upwardly extending outer end of the bottom film panel is mated with a lower portion of the upright columns of the frame and a downwardly extending lower portion of the side film panel is arranged to lie in spaced-apart relation to the lower portion of the upright columns of the frame to trap the upwardly extending outer end of the bottom film panel therebetween so as to overlap with the upwardly extending outer end of the bottom film panel.]

[3. The package of claim 2, wherein the side film panel includes a first end arranged to extend between and interconnect the brim and the base section of the frame, a second end spaced apart from the first end and arranged to extend between and interconnect the brim and the base section of the frame, and the first end is arranged to overlies the second end to locate the first end between the second end and the interior product-storage region.]

[4. The package of claim 3, the first end is coupled to one of the upright columns, the second end is coupled to the first end to trap the first end between the second end and the upright column and overlap with the first end of the side film panel.]

[5. The package of claim 1, wherein a downwardly extending lower portion of the side film panel is mated with a lower portion of the upright columns of the frame and an upwardly extending outer end of the bottom film panel is arranged to lie in spaced-apart relation to the lower portion of the upright columns of the frame to trap the downwardly extending lower portion of the side film panel therebetween so as to overlap with the downwardly extending lower portion of the side film panel.]

[6. The package of claim 1, wherein closure support is coupled to the brim to pivot relative to the brim.]

[7. The package of claim 1, wherein an upwardly extending outer end of the bottom film panel is mated with a lower portion of the upright columns of the frame and a downwardly extending lower portion of the side film panel is arranged to lie in spaced-apart relation to the lower portion of the upright columns of the frame to trap an upwardly extending outer end of the bottom film panel therebetween so as to overlap with the upwardly extending outer end of the bottom film panel.]

[8. The package of claim 1, wherein the side film panel includes a first end arranged to extend between and interconnect the brim and the base section of the frame, a second end spaced apart from the first end and arranged to extend between and interconnect the brim and the base section of the frame, and the first end is coupled to one of the upright columns, the second end is coupled to the first end to trap the first end between the second end and the upright column and overlap with the first end of the side film panel.]

[9. The package of claim 1, wherein interior casing defines the interior product-storage region.]

[10. The package of claim 9, wherein the frame is overmolded onto the side and bottom film panels that form the interior casing.]

[11. The package of claim 9, wherein the frame surrounds and rigidifies the interior casing.]

[12. The package of claim 9, wherein the interior casing is arranged to lie in an interior space bounded by the base section and the upright columns.]

[13. The package of claim 1, wherein a central portion of the side film panel is coupled to inwardly facing surfaces of the upright columns included in the container.]

[14. The package of claim 1, wherein an upwardly extending outer end of the bottom film panel is mated with a lower portion of the upright columns of the frame.]

[15. The package of claim 1, wherein the lid includes a pivotable U-shaped closure support coupled to the brim to pivot about a horizontal pivot axis and a closure coupled to an upwardly facing surface of the pivotable U-shaped closure support.]

[16. The package of claim 15, wherein the closure is coupled to an upwardly facing surface of the brim.]

17. A package comprising

a container including [an interior] a casing including a side film panel and a bottom film panel [coupled together] *separate from the side film panel* and a frame including a base section coupled to the bottom film panel to form a floor of the container, a brim arranged to lie in spaced-apart relation above the base section, and upright columns arranged to extend between and

interconnect the brim and the base section and coupled to the side film panel to form a side wall of the container and

a lid coupled to the container to mate with the brim and close selectively a top aperture formed in the container and arranged to open into [the] *an interior product-storage region of the container*,

wherein the lid includes a [pivotable U-shaped] closure support *and is* coupled to the brim to pivot about a horizontal pivot axis [and a closure coupled to an upwardly facing surface of the pivotable U-shaped closure support,

wherein the closure is coupled to an upwardly facing surface of the brim] *from a closed position to an opened position*,

wherein the lid further includes frangible connectors arranged to extend between and interconnect [an outer edge of] the brim and [an inner edge of] the [U-shaped] closure support, *and*

wherein the lid is configured to be peeled away from the brim to open the top aperture of the container.

18. The package of claim [17] 27, wherein the frangible connectors break in response to application of a pivot-inducing lifting force to an underside of the [U-shaped closure support] *lid* to cause [a portion of the closure] *the lid* to separate from *at least* a portion of the brim.

19. The package of claim 18, wherein the [closure is] *lid* includes a film panel.

20. A container comprising

an interior casing including a side film panel and a bottom film panel coupled together and

a frame including a base section coupled to the bottom film panel to form a floor of the container, a brim arranged to lie above the base section, and a plurality of upright columns arranged to extend between and interconnect the brim and the base section and coupled to the side film panel to form a side wall of the container,

wherein the frame further includes a closure support coupled to the brim to move relative to brim and frangible connectors arranged to extend between and interconnect an outer edge of the brim and an inner edge of the closure support.

21. The container of claim 20, wherein the frame is overmolded onto the side and bottom film panels to rigidify the interior casing and cause the interior casing to define an interior product-storage region formed in the container and the interior casing is arranged to lie in an interior space bounded by the base section and upright columns.

22. The container of claim 20, wherein an upwardly extending outer end of the bottom film panel is mated with a lower portion of the upright columns of the frame.

23. The container of claim 22, wherein a downwardly extending lower portion of the side film panel is arranged to lie in spaced-apart relation to the lower portion of the upright columns of the frame to trap the upwardly extending outer end of the bottom film panel therebetween so as to overlap with the upwardly extending outer end of the bottom film panel.

24. The container of claim 23, wherein an upper end of the side film panel is flared outwardly so that an outer surface of that upper end faces downwardly to mate with the brim of the container and an inner surface of the upper end faces upwardly away from the brim.

25. The container of claim 24, wherein an upwardly extending outer end of the bottom film panel is mated with a lower portion of the upright columns of the frame and a

downwardly extending lower portion of the side film panel is arranged to lie in spaced-apart relation to the lower portion of the upright columns of the frame to trap the upwardly extending outer end of the bottom film panel therebetween so as to overlap with the upwardly extending outer end of the 5 bottom film panel.

26. The container of claim 20, wherein frangible connectors break in response to application of a lifting force to an underside of the closure support to cause a portion of the closure support to separate from a portion of the brim. 10

27. *The package of claim 17, wherein the frangible connectors are coupled to an outer edge of the brim.*

* * * * *