(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number
WO 2004/022674 A1

(51) International Patent Classification[7]: C10G 3/00, C10L 1/08

(21) International Application Number:
PCT/FI2003/000648

(22) International Filing Date:
4 September 2003 (04.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20021596 6 September 2002 (06.09.2002) FI

(71) Applicant *(for all designated States except US)*: **FORTUM OYJ** [FI/FI]; Keilaniementie 1, FIN-02150 Espoo (FI).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: **JAKKULA, Juha** [FI/FI]; Kivenhakkaajantie 9 A, FIN-04200 Kerava (FI). **AALTO, Pekka** [FI/FI]; Eemelintie 2, FIN-06400 Porvoo (FI). **NIEMI, Vesa** [FI/FI]; Ohratie 2, FIN-06400 Porvoo (FI). **KIISKI, Ulla** [FI/FI]; Trappaksentie 22, FIN-06650 Hamari (FI). **NIKKONEN, Jouko** [FI/FI]; Konemestarintie 9, FIN-06650 Hamari (FI). **MIKKONEN, Seppo** [FI/FI]; Rypsikuja 1 C, FIN-06400 Porvoo (FI). **PIIRAINEN, Outi** [FI/FI]; Ahvenkoskenpolku 3 A, FIN-00950 HElsinki (FI).

(74) Agent: **FORSSÉN & SALOMAA OY**; Eerikinkatu 2, FIN-00100 Helsinki (FI).

(81) Designated States *(national)*: AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) **Title:** DIESEL FUEL COMPOSITION, COMPRISING COMPONENTS BASED ON BIOLOGICAL RAW MATERIAL, OBTAINED BY HYDROGENATING AND DECOMPOSITION FATTY ACIDS

(57) **Abstract:** The invention is directed to a fuel composition for diesel engines. The fuel composition comprises 0.1-99 % by weight of a component or a mixture of components produced from biological raw material originating from plants and/or animals and/or fish. The fuel composition comprises 0-20 % of components containing oxygen. Both components are mixed with diesel components based on crude oil and/or fractions from Fischer-Tropsch process.

WO 2004/022674 A1

Diesel fuel composition, comprising components based on biological raw material, obtained by hydrogenating and decomposing fatty acids.

Technical field

The present invention relates to a fuel composition for diesel engines, comprising components based on vegetable oil and/or animal fat and/or fish oil, diesel components based on crude oil and/or fractions from Fischer-Tropsch process, and optionally components containing oxygen.

Prior art

Currently used fuels for diesel engines mainly contain components from crude oil. The aim of the climate agreement of Kyoto is to eliminate detrimental influences due to human activities on the atmosphere, and thus on the climate. The EU has agreed on reducing emissions of carbon dioxide, methane and other greenhouse gases by eight per cent until 2010, starting from the levels of 1990. One of the objects of the EU agricultural policy is to find uses for agricultural overproduction, and to increase the self-sufficiency for fuels. Accordingly, an EU directive is being prepared, demanding that at least two per cent of the petrol and diesel fuel consumed in 2005 should be of biological origin. It is anticipated that one of the requirements of this directive is to increase the proportion of biocomponents to about six per cent until 2010. The directive will be validated in all EU countries in the near future.

At the moment, the most common component of biological origin in fuels is rapeseed oil methyl ester, referred to as RME. RME is either used as such or as a mixture with fuels. Drawbacks of RME are its poor miscibility with diesel fuels, and, in comparison to a conventional diesel fuel (EN 590), particularly under low temperature conditions, its poor storage stability and poor performance at low tem-

peratures. Moreover, it causes engine fouling and increases emissions of nitrogen oxides (NO_x). A by-product of the production process of RME is glycerol, which may become a problem when high amounts of the product are produced. Esters of other vegetable oils may be produced in similar manner, and methyl esters of fatty acids are generally known as FAMEs (fatty acid methyl ester). These FAMEs may be used in similar applications as the rapeseed oil methyl ester, but they also have a negative effect on the quality of the diesel fuel, particularly with respect to the performance thereof at low temperatures, and in addition, the use thereof in fuels increases the emissions of nitrogen oxides. In some cases FAME and RME cause higher particle emissions and smoke development of the cold driven engine.

Vegetable oils and animal fats may be processed to decompose the ester and/or fatty acid structure and to saturate the double bonds of the hydrocarbon chains, thus obtaining about 80 to 85 % of n-paraffin product relative to the mass of the starting material. This product may be directly mixed with a diesel fuel, but a problem with the fuel so produced is its poor performance at low temperatures. In addition, n-paraffins having a carbon number of fatty acids are waxy with a high solidification point, typically above +10 °C, thus limiting the use of these compounds in diesel fuels at least at low temperatures.

WO 2001049812 discloses a method for producing a diesel fuel with a molar ratio of iso-paraffins to n-paraffins of at least 21:1. In the method, a feed stock containing at least 50 % of C_{10}-paraffins is contacted with a catalyst in the isomerization reaction zone.

WO 2001012581 discloses a method for producing methyl esters useful as biological diesel fuel, wherein mixtures of fatty acids and triglycerides are esterified in one phase. In this method, a solution is formed from fatty acids, triglycerides, alcohol, acid catalyst and co-solvents at a temperature below the boiling point of the solution. A co-solvent is used in amounts to provide a single phase, then the solution is maintained for a period of time sufficient for the acid catalyzed esteri-

fication of the fatty acids to take place. Thereafter, the acid catalyst is neutralized, a base catalyst is added to transesterify the triglycerides, and finally, the esters are separated from the solution. Thus a biofuel containing esters is obtained, having a glycerol content of less than 0,4 % by weight.

US 6,174,501 presents a method for producing oxidized diesel fuel of biological origin. This oxidized biological diesel fuel comprises a mixture of transesterified triglycerides.

FI 100248 describes a two-step process for producing middle distillate from vegetable oil by hydrogenating fatty acids of the vegetable oil, or triglycerides, to give n-paraffins, and then by isomerizing the n-paraffins to give branched-chain paraffins.

Any gases, liquid droplets and solid particles present in the atmosphere in amounts being hazardous to human health and/or having a detrimental effect on animals, plants and different materials, are considered as air pollutants. Air pollution mainly originates from three main emission sources, i.e. the industry, energy production, and traffic.

The harmfulness of particle emissions is caused by the substances and compounds they carry, such as heavy metals and other carcinogenic and mutagenic compounds. Particles present in exhaust gases are small and thus hazardous to health.

Greenhouse gases allow for the penetration of the radiation from the sun to reach the earth, preventing, however, the thermal radiation from escaping from the earth back to space. They thus contribute to the warming of the earth. One of the most significant greenhouse gases is carbon dioxide released, for instance, during the combustion of fossil fuels.

Nitrogen oxides are acidifying compounds. This acidification may, for instance, lead to plant damages and species changes in surface waters. Nitrogen oxides may also react with oxygen to give ozone. This phenomenon contributes particularly to air quality in cities.

As the above teachings indicate, there is a need for a high quality fuel composition for diesel engines containing components of biological origin and also meeting the quality requirements for diesel fuels under low temperature operation conditions. Moreover, the fuel should be more environmentally friendly than prior art solutions.

General description of the invention

The object of the invention is to provide a more environmentally friendly fuel composition for diesel engines containing components of biological origin, and also meeting the quality requirements for diesel fuels under low temperature conditions.

The fuel composition for diesel engines of the invention, containing components of biological origin, comprises at least one component produced from a biological starting material obtained from plants, animals or fish, diesel components based on crude oil and/or fractions from Fischer-Tropsch process, and optionally components containing oxygen.

The characteristic features of the fuel composition for diesel engines containing components of biological origin are presented in the appended claims.

Detailed description of the invention

It was surprisingly found that the diesel fuel composition of the invention, containing components of biological origin, also meets the quality requirements for diesel fuels under low temperature conditions. The composition of the diesel fuel of the invention comprises the following:

a) 0.1 to 99 % by volume, preferably 0.1 to 80 % by volume of a component or a mixture of components produced from biological raw material originating from plants and/or animals and/or fish;
b) 0 to 20 % by volume of components containing oxygen selected from the group consisting of aliphatic alcohols such as methanol and ethanol, ethers, fatty acid esters such as methyl and ethyl esters, water, and mixtures containing the same;


both components a) and b) being mixed as an emulsion or dissolved in diesel components based on crude oil and/or fractions from Fischer-Tropsch process.

Component a) produced from biological raw material originating from plants and/or animals and/or fish, referred to as the biological component in the present specification, is obtained by hydrogenating and decomposing fatty acids and/or fatty acid esters to give a hydrocarbon having a carbon number of 6-24, typically n-paraffin as the product having a carbon number of 12-24, and optionally by isomerizing the hydrocarbon, typically n-paraffin, thus obtained to give iso-paraffin. The hydrocarbon is preferably isomerized.

The biological raw material originating from plants and/or animals and/or fish is selected from the group consisting of vegetable oils, animal fats, fish oils and mixtures thereof containing fatty acids and/or fatty acid esters. Examples of suitable materials are wood-based and other plant-based fats and oils such as rapeseed oil, colza oil, canola oil, tall oil, sunflower oil, soybean oil, hempseed oil, olive

oil, linseed oil, mustard oil, palm oil, peanut oil, castor oil, coconut oil, as well as fats contained in plants bred by means of gene manipulation, animal-based fats such as lard, tallow, train oil, and fats contained in milk, as well as recycled fats of the food industry and mixtures of the above.

The basic component of a typical vegetable or animal fat is triglyceride i.e. a triester of glycerol and three fatty acid molecules having the structure presented in the following formula I:



(I)

where R_1, R_2, and R_3 are hydrocarbon chains, and R_1, R_2, and R_3 may be saturated or unsaturated $C_6 - C_{24}$ alkyl groups. The fatty acid composition may vary considerably in biological raw materials of different origin.

n-paraffin, iso-paraffin or mixtures thereof produced from the biological raw material may be used as a diesel fuel component in accordance with the properties desired for the diesel fuel. Fractions from Fischer-Tropsch-process typically contain high levels of n-paraffin and, optionally, they may be isomerized either simultaneously during the processing of the component of biological origin or separately therefrom, or they may be used as such.

The biological component may be produced, for instance, with a process comprising at least two steps and optionally utilizing the counter-current operation principle. In the first hydrodeoxygenation step of the process, optionally running counter-current, the structure of the biological raw material is broken, compounds

containing oxygen, nitrogen, phosphor and sulphur as well as light hydrocarbons as gas are removed, and thereafter, olefinic bonds are hydrogenated. In the second isomerization step of the process, optionally running counter-current, isomerization is carried out to give branched hydrocarbon chains, thus improving the low temperature properties of the paraffin.

Biological raw material originating from plants, animals or fish and containing fatty acids and/or fatty acid esters, selected from vegetable oils, animal fats, fish oils and mixtures thereof, is used as the feed stock.

High quality hydrocarbon component of biological origin, particularly useful as a component of a diesel fuel, as an isoparaffinic solvent and as a lamp oil, is obtained as the product having a high cetane number that may even be higher than 70. Also, with a turbidity point lower than -30 °C a cetane number higher than 60 can still be achieved. The process can be adjusted according to the desired cetane number and turbidity point.

Advantages of the diesel fuel composition of the present invention include superior performance at low temperatures and an excellent cetane number compared to solutions of prior art using FAME-based components like RME. Problems associated with the performance at low temperatures may be avoided by isomerizing waxy n-paraffins having a carbon number comparable with that of fatty acids to give isoparaffins. The properties of the products thus obtained are excellent, especially with respect to diesel applications, the n-paraffins typically have cetane numbers higher than 70, and isoparaffins higher than 60, and thus they have an improving effect on the cetane number of the diesel pool, which clearly makes them more valuable as diesel components. Moreover, the turbidity point of the isomerized product may be adjusted to the desired level, for example below -30 °C, whereas the corresponding value is about 0 °C for RME and more than +15 °C for n-paraffins. Table 1 below compares the properties of an isomerized biological component, RME, and a commercial diesel fuel.

Table 1

Product	Density (kg/m^3)	Cetane number	Turbidity point (°C)
Isomerized biological component	< 800	≥ 60	≤ -30
RME	~880	~ 50	~ 0
Diesel fuel EN 590	820-845	≥ 51	0 to -15

Fouling of engines is considerably diminished and the noise level is clearly lower when using the diesel fuel composition of the invention in comparison with similar prior art fuels of biological origin containing FAME components, and further, the density of the composition is lower. The composition does not require any modifications of the automobile technology or logistics. Higher energy content per unit volume may be mentioned as a further advantage compared to RME.

The properties of the diesel fuel composition of biological origin according to the invention correspond to those of a high quality diesel fuel based on crude oil, it is free of aromates and, in contrast to FAME, it leaves no impurity residues.

Nitrogen oxide emissions due to the fuel composition of the invention are lower that those from a similar FAME-based product, and further, the particle emissions are clearly lower, and the carbon portion of the particles is smaller. These significant improvements in the emissions of the fuel composition of biological origin are environmentally very important.

The invention will now be illustrated by means of the following examples without intending to limit the scope thereof.

EXAMPLES

Example 1

The following Table 2 compares the emission characteristics of a conventional diesel fuel used in Europe in summer, EN 590 (DI), to those of a composition containing 60 % by volume of hydrogenated and isomerized tall oil (TOFA), and 40 % by volume of the European summer diesel fuel EN 590.

Table 2

Characteristic	Unit	60 % b.v. TOFA + 40 % b.v. DI	DI
Turbidity point	°C	-15	-8
Cetane number	-	61.2	55.9
Aromates	% b.w.	8.7	19.2
Total aromates (IP391)	% b.v.	9.1	20.0
Polyaromates (IP391)	% b.v.	0.8	1.6
n-paraffins	% b.w.	14.7	24.5
i-paraffins	% b.w.	34.2	26.1
Naphtenes	% b.w.	42.4	30.2

b.w. = by weight

b.v. = by volume

Example 2

Table 3 below compares the emission characteristics of a high quality reformed crude oil based diesel fuel available on the Finnish market (DITC, produced by Fortum Oyj), to those of compositions containing 30 % by volume of hydrogenated and isomerized tall oil (TOFA), and 70 % by volume of DITC, or containing 30 % by volume of tall oil methyl ester (MME), and 70 % by volume of DITC.

Table 3

Characteristic	**Unit**	**DITC**	**30 % b.v. TOFA + 70 % b.v. DITC**	**30 % b.v. MME + 70 % b.v. DITC**
Cetane number	-	51	57	48
NO_x emissions (compared to DITC)	%		-1 to -4	+3
Particles	%		-3	+22
- carbon	%		-10 to -30	0 to -10
- PAH	%		± 0	± 0
Combustion noise	-		decreases	± 0

b.v. = by volume

Claims

1. Fuel composition for diesel engines, **characterized** in that the fuel composition comprises:

a) 0.1-99 % by volume of a component or a mixture of components produced from biological raw material originating from plants and/or animals and/or fish by hydrogenating and decomposing fatty acids and/or fatty acid esters to give a hydrocarbon, which is optionally isomerized;

b) 0-20 % by volume of components containing oxygen;

both components a) and b) being mixed as an emulsion or dissolved in diesel components based on crude oil and/or fractions from Fischer-Tropsch process.

2. Fuel composition of claim 1, **characterized** in that the fuel composition comprises 0.1-80 % by volume of a component or a mixture of components produced from biological raw material originating from plants and/or animals and/or fish.

3. Fuel composition of claim 1 or 2, **characterized** in that the product obtained from the biological raw material is isomerized.

4. Fuel composition of any of the above claims 1-3, **characterized** in that the biological raw material is selected from the group consisting of vegetable oils, animal fats, fish oils and mixtures thereof.

5. Fuel composition of any of the above claims 1-4, **characterized** in that the biological raw material is a wood-based or other plant-based fat or oil, a fat contained in plants bred by means of gene manipulation, an animal-based fat, a fat contained in milk, a recycled fat of the food industry or a mixture of the above.

6. Fuel composition of claim 5, **characterized** in that the biological raw material is rapeseed oil, colza oil, canola oil, tall oil, sunflower oil, soybean oil, hempseed

oil, olive oil, linseed oil, mustard oil, palm oil, peanut oil, castor oil, coconut oil, lard, tallow, or train oil.

7. Fuel composition of any of the above claims 1-6, **characterized** in that the components containing oxygen are selected from the group consisting of aliphatic alcohols, ethers, fatty acid esters, water, and mixtures containing the same.

8. Fuel composition of any of the above claims 1-7, **characterized** in that the component produced from biological raw material originating from plants, animals or fish is obtained by hydrogenating and decomposing fatty acids and/or fatty acid esters to give n-paraffin as the product having a carbon number of 12-24, and by isomerizing the n-paraffin thus obtained to give iso-paraffin.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/FI 03/00648

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: C10G 3/00, C10L 1/08
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: C10G, C10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ, CHEM.ABS.DATA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DATABASE WPI Week 200357 Derwent Publication Ltd., London, GB; Class D23, AN 1997-488372 & SE520633 C2 (NESTE OY), 05 August 2003 (2003-08-05) abstract --	1-8
X	US 4992605 A (CRAIG ET AL), 12 February 1991 (12.02.91), see table 9 --	1-8
X	US 5705722 A (MONNIER ET AL), 6 January 1998 (06.01.98) -- --------	1-8

☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
8 December 2003	17 -12- 2003
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86	Authorized officer ANNA SJÖLUND/BS Telephone No. +46 8 782 25 00

Form PCT/ISA/210 (second sheet) (July 1998)

INTERNATIONAL SEARCH REPORT

Information on patent family members

06/09/03

International application No.
PCT/FI 03/00648

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4992605 A	12/02/91	CA 1313200 A,C	26/01/93
US 5705722 A	06/01/98	CA 2149685 A	31/12/95