




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F28D 19/04	A1	(11) International Publication Number: WO 00/25079 (43) International Publication Date: 4 May 2000 (04.05.00)
(21) International Application Number: PCT/US99/06269 (22) International Filing Date: 23 March 1999 (23.03.99) (30) Priority Data: 09/179,045 26 October 1998 (26.10.98) US (71) Applicant: ABB AIR PREHEATER, INC. [US/US]; Andover Road, Wellsville, NY 14895 (US). (72) Inventors: MILLIGAN, Brenda, Lee; 71 Trapping Brook Road, Wellsville, NY 14895 (US). UPDYKE, Clair, Francis; P.O. Box 815, Andover, NY 14806 (US). (74) Agents: FOURNIER, Arthur, E., Jr. et al.; ABB Worldwide Boiler Business Area, Patent Services, 2000 Day Hill Road, Windsor, CT 06095 (US).		(81) Designated States: AU, BR, CA, CN, CZ, HU, ID, IL, IN, JP, KR, MX, PL, SG, ZA, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(54) Title: BYPASS SEALS FOR ROTARY REGENERATIVE HEAT EXCHANGERS



(57) Abstract

A heating element basket assembly (10) for a rotary regenerative air preheater has a picture-frame structure with the open areas on each side being covered by a flat plate (26) attached to the inside of the frame. A sealing plate member (28) is attached to the outside of each of the flat plates (26) within framework. The sealing plate member (28) has a portion bend and protruding outwardly from the periphery of the basket (10) to form a flexible seal (30) for engagement with the diaphragms (36) and stay plates (32) of the rotor.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Bypass Seals for Rotary Regenerative Heat Exchangers

Background of the Invention

5 The present invention relates to means for reducing or eliminating the internal bypassing of gas streams around the heating elements in rotary regenerative heat exchangers and particularly relates to the internal bypassing of air and flue gas streams around the heating elements in an air preheater.

10 In a rotary regenerative air preheater, the rotor is divided up by diaphragm plates into pie-shaped sectors, which are in turn subdivided into rotor compartments by stay plates. Each rotor compartment is designed to accommodate one or more assemblies of heating elements comprising basket-like containers with heat transfer surfaces therein. Because of fabrication tolerances and/or the distortion of the rotor structure associated with extended operation under varying thermal conditions, it is usually necessary to design the heating elements to allow a clearance around each basket so as to avoid interference at installation.

20 When fabrication tolerances, rotor distortion and/or design clearances result in excessive gaps ("bypass gaps") between the sides and ends of the baskets and the corresponding walls of the rotor compartment or an adjacent basket, a portion of the air and gas streams will flow through the gaps thereby bypassing the heat transfer surfaces and thereby resulting in a loss in heat transfer efficiency.

25

Summary of the Invention

30 The present invention provides a unique means to reduce or eliminate the bypass of air and flue gas around the heat transfer baskets in the compartments of rotary regenerative heat exchangers. The invention relates to picture frame style baskets with frame members along all the edges of the basket and involves the attachment of liner

plates on the insides of the frame members on the sides and ends much as is done with so-called hybrid baskets (picture frame baskets with plates closing off the sides and ends). Attached to the outside of the liner plates are sealing plates which have a portion deflected outwardly to form flexible sealing strips which seal against the compartment walls.

Brief Description of the Drawings

Figure 1 is a perspective view of a typical prior art rotary regenerative air preheater basket of the picture frame type.

Figure 2 is a similar perspective view of a picture frame type basket modified to incorporate the present invention.

Figure 3 is a vertical cross-section view of the inner end of the basket of Figure 2 taken along line 3 - 3.

Figure 4 is a top view of a portion of the basket of Figure 2.

Figure 5 is a vertical cross-section view of one of the sides of the basket of Figure 2 taken along line 5 - 5.

Figure 6 is a vertical cross-section view similar to Figure 5 but illustrating a modification.

Description of the Preferred Embodiments

The present invention relates to the heating elements for rotary regenerative air preheaters in which the heating elements are loaded into compartments in the rotor. As well known in the art, the compartments are formed by radially extending diaphragms forming pie-shaped sectors and by a series of tangentially extending stay plates dividing each sector into multiple compartments. As also known in the art, the heating elements must be slightly undersized in order to facilitate loading into and unloading out of the compartments. this means that there are clearances or gaps between the sides of the heating elements and the diaphragm plates and between the inboard and outboard ends of the

heating elements and the stay plates. As previously indicated, these gaps result in the bypass of air and flue gas around the heat transfer surface in the heating elements.

Figure 1 of the drawing shows a typical frame work 10 for a heating element basket of the picture frame type. The frame work 10 includes the two vertical inboard end corner pieces 12 and the two vertical outboard end corner pieces 14. The top band 16 and the bottom band 18 each extend around three sides and join the four corner pieces. The outboard top band 20 and bottom band 22 join the two corner pieces 14. The basket 10 contains the heat transfer surface in the form of a large number of closely spaced plates 24. Only two such plates are shown in this Figure 1. The heating element is assembled by joining the two corner pieces 12 and the top and bottom bands 16 and 18. The heat transfer surface plates 24 are then loaded from the outer end. The cover comprising the two outer corner pieces 14 assembled with the top and bottom bands 20 and 22 is then attached. Not shown in this Figure 1 or in the other figures for reasons of clarity are the conventional support bars for the heat transfer surface plates which extend radially from the inner end to the outer end across both the top and bottom of the element. When these heating elements are loaded into the compartments of the air preheater rotor, there are gaps between the periphery of the heating elements and the walls of the compartments as explained earlier and as will be shown later.

Figure 2 is a perspective view of the same type of basket as illustrated in Figure 1 but which incorporates the present invention. Located on all four sides of the basket are flat liner plates 26. These flat liner plates 26 are attached to the insides of the frame, such as by spot welding, such that they completely cover the picture frame opening in each side. This is much the same as what is sometimes referred to

as a hybrid basket structure with the sides closed off as in a full wrap basket structure.

Mounted to the outside of the flat liner plates 26 within the picture frame opening is a sealing plate 28 which has a portion deflected or bent outwardly to form a flexible sealing strip 30. Figure 3 shows a cross-section of the inner end of the basket taken along line 3 - 3 to further illustrate the structure. As shown at 31, the sealing plate 28 is spot welded to the flat liner plate 26. This Figure 3 also shows a stay plate 32 of the rotor structure and illustrates how the flexible sealing strip 30 seals against the stay plate and closes off the gap 34 between the basket and the stay plate. As a further detailed illustration, Figure 4 shows a top view of a portion of the basket of Figure 2. To illustrate the details of the outer corners, Figure 5 is a cross-section taken along line 5 - 5 of Figure 2. As can be seen, the cover comprising the outer corners 14 and bands 20 and 22 are now installed on the inside of the flat liner plate 26. Also illustrated is a portion of a radially extending diaphragm plate 36 engaging the sealing strip 30.

Figure 6 shows an alternate arrangement for mounting the sealing plates 28 on the sides of the basket. In this embodiment, the sealing plate extends down further below the picture frame opening such that the bottom end is sandwiched between the flat plate 26 and the bottom band 18. This provides added assurances that the sealing plates will remain in position.

Claims:

1. A heating element basket assembly for a rotary regenerative air preheater comprising:

- 5
- a. a basket framework including two inner corner members and two outer corner members and top and bottom bands each extending around said assembly and joining said corner members together and defining a basket periphery and thereby forming open center portions on each face of said assembly;
- 10
- b. a flat plate attached to the inside of said top and bottom bands and said corner members on each face of said assembly thereby covering said open center portions; and
- 15
- c. a sealing plate member attached to the outside of each of said flat plate members, said sealing plate members each having a flexible sealing strip extending parallel to the top and bottom bands and protruding outwardly from said basket periphery through said open center portion.
- 20

25 2. A heating element basket assembly as recited in claim 1 wherein said sealing plate members are welded to said flat plates.

30 3. A heating element basket assembly as recited in claim 1 wherein said sealing plate members extend down between said bottom band and said flat plate.




Fig. 1

PRIOR ART




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/06269

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F28D19/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F28D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 272 507 A (BEAUCHAMP JOHN MARTYN) 18 May 1994 (1994-05-18)	1
Y	page 4, paragraph 3 - page 6; figures 4-8 ---	2,3
Y	US 3 818 978 A (FINNEMORE H) 25 June 1974 (1974-06-25) column 2, line 60 - column 3, line 10; figures ---	2,3
A	US 3 915 220 A (GIBSON DAVID J) 28 October 1975 (1975-10-28) column 2, line 12 - line 21; figure 2 ---	1-3
A	US 4 984 621 A (MILLER NORMAN P ET AL) 15 January 1991 (1991-01-15) figures 3,4 -----	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

6 July 1999

Date of mailing of the international search report

13/07/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Mootz, F

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 99/06269

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2272507	A	18-05-1994	NONE	
US 3818978	A	25-06-1974	DE 2356274 A FR 2206487 A OA 4506 A	22-05-1974 07-06-1974 30-03-1980
US 3915220	A	28-10-1975	BR 7500011 A	06-07-1976
US 4984621	A	15-01-1991	CA 2043186 A,C CN 1058267 A,B DE 69106364 D DE 69106364 T EP 0538270 A ES 2069296 T JP 7104112 B KR 9514045 B MX 173820 B WO 9201900 A	17-01-1992 29-01-1992 09-02-1995 29-06-1995 28-04-1993 01-05-1995 13-11-1995 20-11-1995 29-03-1994 06-02-1992