

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 893 579 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:

27.03.2002 Bulletin 2002/13

(51) Int Cl.7: **F01M 11/04**

(21) Application number: **98110801.2**

(22) Date of filing: **12.06.1998**

(54) **Connecting system for the lubrication oil aspiration conduit of an internal combustion engine**

Verbindungsanordnung für die Ölansaugleitung einer Brennkraftmaschine

Dispositif de fixation de la conduite d'aspiration d'huile d'un moteur à combustion interne

(84) Designated Contracting States:
DE ES FR GB SE

(30) Priority: **24.07.1997 IT TO970159 U**

(43) Date of publication of application:
27.01.1999 Bulletin 1999/04

(73) Proprietor: **FIAT AUTO S.p.A.**
10135 Torino (IT)

(72) Inventor: **Sobrero, Remo**
10144 Torino (IT)

(74) Representative: **Di Francesco, Gianni et al**
Ing. Barzanò & Zanardo Milano S.p.A.
Corso Vittorio Emanuele II, 61
10128 Torino (IT)

(56) References cited:
FR-A- 2 639 089 **US-A- 2 372 286**
US-A- 4 479 463 **US-A- 5 601 060**

EP 0 893 579 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] This invention relates to a connecting system for an aspiration conduit of lubrication oil from the sump of an internal combustion engine.

[0002] In engines of the known type, the pump for oil circulation is connected to the conduit that includes an aspiration conduit end section on one end, located in the lower section of the sump containing engine oil, almost in contact with the bottom.

[0003] In this type of configuration, the aspiration conduit is located in such a way that it has to be maintained at a precise distance from the bottom. A point inside the sump is also required to connect the end section, before the sump itself is mounted on the engine. Where vibrations are present loosening of this type of connection can occur, particularly if it is not carried out appropriately.

[0004] It is an object of the present invention to provide an oil aspiration conduit fixing assembly and, in particular, of the aspiration conduit end section, to overcome disadvantages mentioned

[0005] According to this invention, this can be achieved by a fixing assembly for an aspiration conduit that presents the characteristics mentioned in the first claim.

[0006] Other characteristics and advantages will appear clear in the following description, given by way of example and referred to the accompanying drawings in which -

Figure 1 is a partially sectional side elevation view of the oil sump, equipped with a conduit, according to the invention, and

Figure 2 is an enlarged view of a section of figure 1.

Reference being made to the figures, in which 2 is used to indicate the oil sump of an internal combustion engine, connected to the block of said engine (not illustrated) by way of connecting seats 4. Said sump 2 includes, on the side section, an internal protrusion 6, on which conduit 8 is obtained, for oil circulation, into the aspiration opening of the oil pump located on the upper section of the block. The sealtightness of said connection is guaranteed by seal 9. The other end of the first section of conduit 8 opens on the inside of the sump, below the upper border, leaning on the bottom section of the engine block. To this is connected, by way of flange 10, fixed in place with bolts 12, the second section 14 of said aspiration conduit adequately shaped according to the shape of the sump, ending in aspiration conduit end section 16.

[0007] On the end turned towards the bottom of the sump, said end section includes a threaded nut 17, maintained fixed on the sump by way of plates 18 (four, in the case illustrated). Conduit 14 is shaped so that nut 17 can be positioned corresponding to slot 19 for the emptying of the oil (outlet) contained in the sump, in or-

der that bolt 20 covering the outlet point be screwed on the latter, with the shank of the bolt through slot 1 g. In this way, only one bolt can be used to fix both conduit 14 and end section 16, in the position and at the distance required -1 and the closing point of oil outlet 19. Usually the nut will be provided with sealing gasket.

[0008] Blocking of the aspiration conduit of engine oil obtained in this way not only presents the advantages already mentioned, it also facilitates engine assembly, in that it reduces and simplifies necessary operations. Also, the distance between the aspiration conduit end section and the bottom of the sump is determined only by the thickness of nut 17. This also allows for a more appropriate location of the conduit, also reducing the total weight of the system.

[0009] It is, of course, possible to vary the different components, as will appear clear to a field technician, whilst respecting the object of the invention provided here.

Claims

1. Fixing assembly for the lubrication oil aspiration conduit of the sump of an internal combustion engine, said conduit presenting an end section equipped with a connection flange, for connection to a conduit obtained in the wall of said sump, the other end being equipped with an aspiration conduit end section (16) located close to the bottom of said sump (2), **characterised by** the fact that said end section presents a threaded nut (17) located corresponding to the outlet slot (19) of the oil of said sump (2), so that the threaded shank of the bolt acting as a cover (20) of said outlet slot (19) can be screwed to said nut (17).
2. System according to claim 1, **characterised by** the fact that the outlet slot (19) has a diameter larger than that of the shank of the bolt also used as a cover (20).
3. System according to claim 1, **characterised by** the fact that nut (17) is connected to the end section of the conduit by way of plates (18).

Patentansprüche

1. Anbringungsanordnung für die Schmierölsaugleitung der Ölwanne eines Verbrennungsmotors, wobei diese Leitung einen Endabschnitt bietet, der mit einem Verbindungsflansch zur Verbindung mit einer in der Wand dieser Ölwanne erhaltenen Leitung ausgestattet ist, während das andere Ende mit einem dicht am Boden der Ölwanne (2) gelegenen Ansaugleitungsendabschnitt (16) ausgestattet ist, **dadurch gekennzeichnet, daß** der Endabschnitt

eine in Übereinstimmung mit einem Auslaßschlitz (19) für das Öl der Ölwanne (2) angeordnete Gewindemutter (17) zeigt, so daß der Gewindeschafte des als eine Abdeckung (20) dieses Auslaßschlitzes (19) wirkenden Bolzens mit dieser Mutter (17) verschraubt werden kann. 5

2. System nach Anspruch 1, **dadurch gekennzeichnet, daß** der Auslaßschlitz (19) einen Durchmesser aufweist, der größer als jener des Schafts des auch als eine Abdeckung (20) verwendeten Bolzens ist. 10
3. System nach Anspruch 1, **dadurch gekennzeichnet, daß** die Mutter (17) durch Platten (18) mit dem Endabschnitt der Leitung verbunden ist. 15

Revendications

1. Ensemble de fixation pour la conduite d'aspiration de l'huile lubrifiante du carter à huile d'un moteur à combustion interne, ladite conduite présentant une section d'extrémité munie d'un flasque de raccordement, pour effectuer le raccordement à une conduite ménagée dans la paroi dudit carter à huile, l'autre extrémité étant munie d'une section d'extrémité de conduite d'aspiration (16) située près du fond dudit carter à huile (2), **caractérisé en ce que** ladite section d'extrémité présente un écrou fileté (17) situé de manière correspondante à la fente de sortie d'huile (19) dudit carter à huile (2), de sorte que la tige filetée du boulon agissant comme un bouchon (20) d'obturation de ladite fente de sortie (19) peut être vissée sur ledit écrou (17). 20
25
30
2. Système selon la revendication 1, **caractérisé en ce que** la fente de sortie (19) a un diamètre plus grand que celui de la tige du boulon également utilisé comme bouchon (20). 35
40
3. Système selon la revendication 1, **caractérisé en ce que** l'écrou (17) est raccordé à la section d'extrémité de la conduite au moyen de plaquettes (18). 45

45

50

55

