



(12) **United States Patent**  
**Bowe**

(10) **Patent No.:** **US 10,405,924 B2**  
(45) **Date of Patent:** **Sep. 10, 2019**

(54) **SYSTEM AND METHOD OF ABLATIVE CUTTING AND VACUUM ASPIRATION THROUGH PRIMARY ORIFICE AND AUXILIARY SIDE PORT**

(58) **Field of Classification Search**  
CPC ..... A61B 17/3207; A61B 17/320758; A61B 18/245; A61B 2018/2211  
See application file for complete search history.

(71) Applicant: **The Spectranetics Corporation,**  
Colorado Springs, CO (US)

(56) **References Cited**

(72) Inventor: **Wade Bowe,** Colorado Springs, CO (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **THE SPECTRANETICS CORPORATION,** Colorado Springs, CO (US)

1,663,761 A 3/1928 Johnson  
3,400,708 A 9/1968 Scheidt  
(Continued)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 389 days.

JP H05506382 A 9/1993  
JP 2004516073 A 6/2004  
(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/725,766**

OTHER PUBLICATIONS

(22) Filed: **May 29, 2015**

U.S. Appl. No. 14/994,921 Entitled Device and Method of Ablative Cutting With Helical Tip, filed Jan. 13, 2016.

(65) **Prior Publication Data**

US 2015/0342682 A1 Dec. 3, 2015

(Continued)

**Related U.S. Application Data**

*Primary Examiner* — Julie A Szpira

(60) Provisional application No. 62/005,684, filed on May 30, 2014.


(57) **ABSTRACT**

(51) **Int. Cl.**  
**A61B 17/3207** (2006.01)  
**A61B 18/24** (2006.01)  
(Continued)

A system for ablation and removal of occlusions from blood vessels is provided. Laser cutting systems and mechanical cutting systems are provided in catheter devices, the cutting systems operable to ablate, cut, dislodge, and otherwise remove occlusions within a blood vessel that may limit or prevent proper circulation. Aspiration systems are further provided, the aspiration systems operable to remove ablated, cut, or dislodged material through a primary orifice at the distal end of the catheter and/or through an auxiliary orifice, which may be on the side of the catheter.

(52) **U.S. Cl.**  
CPC .... **A61B 18/245** (2013.01); **A61B 17/320758** (2013.01); **A61M 1/008** (2013.01); **A61B 17/3207** (2013.01); **A61B 2017/22079** (2013.01); **A61B 2017/320775** (2013.01); **A61B 2018/00345** (2013.01);  
(Continued)

**20 Claims, 10 Drawing Sheets**



- (51) **Int. Cl.**  
*A61M 1/00* (2006.01)  
*A61B 18/00* (2006.01)  
*A61B 18/22* (2006.01)  
*A61B 17/22* (2006.01)
- (52) **U.S. Cl.**  
 CPC ..... *A61B 2018/00577* (2013.01); *A61B 2018/2211* (2013.01); *A61B 2218/007* (2013.01)
- (56) **References Cited**  
 U.S. PATENT DOCUMENTS
- |           |   |           |                      |           |    |         |                    |
|-----------|---|-----------|----------------------|-----------|----|---------|--------------------|
| 3,472,234 | A | 10/1969   | Tachick              | 5,620,451 | A  | 4/1997  | Rosborough         |
| 3,498,286 | A | 3/1970    | Innis et al.         | 5,632,749 | A  | 5/1997  | Goode et al.       |
| 3,614,953 | A | 10/1971   | Moss                 | 5,651,781 | A  | 7/1997  | Grace              |
| 4,051,596 | A | 10/1977   | Hofmann              | 5,651,783 | A  | 7/1997  | Reynard            |
| 4,203,444 | A | 5/1980    | Bonnell et al.       | 5,697,936 | A  | 12/1997 | Sbipko et al.      |
| 4,227,770 | A | 10/1980   | Gunn                 | 5,713,860 | A  | 2/1998  | Kaplan et al.      |
| 4,246,902 | A | 1/1981    | Martinez             | 5,718,237 | A  | 2/1998  | Haaga              |
| 4,274,414 | A | 6/1981    | Johnson et al.       | 5,725,523 | A  | 3/1998  | Mueller            |
| 4,388,800 | A | 6/1983    | Trezeguet et al.     | 5,766,164 | A  | 6/1998  | Mueller et al.     |
| 4,471,777 | A | 9/1984    | McCorkle, Jr.        | 5,782,823 | A  | 7/1998  | Mueller            |
| 4,517,977 | A | 5/1985    | Frost                | 5,807,399 | A  | 9/1998  | Laske et al.       |
| 4,573,965 | A | 3/1986    | Russo                | 5,814,044 | A  | 9/1998  | Hooven             |
| 4,576,146 | A | 3/1986    | Kawazoe et al.       | 5,823,971 | A  | 10/1998 | Robinson et al.    |
| 4,582,056 | A | 4/1986    | McCorkle et al.      | 5,824,026 | A  | 10/1998 | Diaz               |
| 4,587,972 | A | 5/1986    | Morantte et al.      | 5,830,209 | A  | 11/1998 | Savage et al.      |
| 4,598,710 | A | 7/1986    | Kleinberg et al.     | 5,863,294 | A  | 1/1999  | Alden              |
| 4,646,738 | A | 3/1987    | Trott                | 5,873,865 | A  | 2/1999  | Horzewski et al.   |
| 4,662,869 | A | 5/1987    | Wright               | 5,873,886 | A  | 2/1999  | Larsen et al.      |
| 4,674,502 | A | 6/1987    | Imonti               | 5,879,365 | A  | 3/1999  | Whitfield et al.   |
| 4,729,763 | A | 3/1988    | Henrie               | 5,893,862 | A  | 4/1999  | Pratt et al.       |
| 4,754,755 | A | 7/1988    | Husted               | 5,899,915 | A  | 5/1999  | Saadat             |
| 4,767,403 | A | 8/1988    | Hodge                | 5,910,150 | A  | 6/1999  | Saadat             |
| 4,784,132 | A | * 11/1988 | Fox ..... A61B 18/20 | 5,916,210 | A  | 6/1999  | Winston            |
|           |   |           | 606/15               | 5,931,848 | A  | 8/1999  | Saadat             |
| 4,848,339 | A | 7/1989    | Rink et al.          | 5,941,893 | A  | 8/1999  | Saadat             |
| 4,943,289 | A | 7/1990    | Goode et al.         | 5,951,581 | A  | 9/1999  | Saadat et al.      |
| 4,950,232 | A | 8/1990    | Ruzicka et al.       | 5,972,012 | A  | 10/1999 | Ream et al.        |
| 4,950,277 | A | 8/1990    | Farr                 | 5,980,515 | A  | 11/1999 | Tu                 |
| 4,955,882 | A | 9/1990    | Hakky                | 5,980,545 | A  | 11/1999 | Pacala et al.      |
| 4,988,347 | A | 1/1991    | Goode et al.         | 6,007,512 | A  | 12/1999 | Hooven             |
| 5,011,482 | A | 4/1991    | Goode et al.         | 6,010,476 | A  | 1/2000  | Saadat             |
| 5,013,310 | A | 5/1991    | Goode et al.         | 6,019,756 | A  | 2/2000  | Mueller et al.     |
| 5,031,634 | A | 7/1991    | Simon                | 6,022,336 | A  | 2/2000  | Zadno-Azizi et al. |
| 5,041,084 | A | 8/1991    | DeVries et al.       | 6,024,751 | A  | 2/2000  | Lovato et al.      |
| 5,061,266 | A | 10/1991   | Hakky                | 6,027,497 | A  | 2/2000  | Daniel et al.      |
| 5,152,744 | A | 10/1992   | Krause et al.        | 6,033,402 | A  | 3/2000  | Tu et al.          |
| 5,201,316 | A | 4/1993    | Pomeranz et al.      | 6,036,685 | A  | 3/2000  | Mueller            |
| 5,207,683 | A | 5/1993    | Goode et al.         | 6,051,008 | A  | 4/2000  | Saadat et al.      |
| 5,243,679 | A | 9/1993    | Sharrow et al.       | 6,053,900 | A  | 4/2000  | Brown et al.       |
| 5,250,045 | A | 10/1993   | Bohley               | 6,066,131 | A  | 5/2000  | Mueller et al.     |
| 5,261,877 | A | 11/1993   | Fine et al.          | 6,080,175 | A  | 6/2000  | Hogendijk          |
| 5,263,928 | A | 11/1993   | Trauthen et al.      | 6,083,237 | A  | 7/2000  | Huitema et al.     |
| 5,275,609 | A | 1/1994    | Pingleton et al.     | 6,096,028 | A  | 8/2000  | Bahmanyar et al.   |
| 5,290,275 | A | 3/1994    | Kittrell et al.      | 6,099,537 | A  | 8/2000  | Sugai et al.       |
| 5,290,280 | A | 3/1994    | Daikuzono            | 6,102,926 | A  | 8/2000  | Tartaglia et al.   |
| 5,290,303 | A | 3/1994    | Pingleton et al.     | 6,117,149 | A  | 9/2000  | Sorensen et al.    |
| 5,328,488 | A | 7/1994    | Daikuzono            | 6,120,520 | A  | 9/2000  | Saadat et al.      |
| 5,383,199 | A | 1/1995    | Laudenslager et al.  | 6,126,654 | A  | 10/2000 | Giba et al.        |
| 5,395,328 | A | 3/1995    | Ockuly et al.        | 6,136,005 | A  | 10/2000 | Goode et al.       |
| 5,415,653 | A | 5/1995    | Wardle et al.        | 6,139,543 | A  | 10/2000 | Esch et al.        |
| 5,423,330 | A | 6/1995    | Lee                  | 6,152,909 | A  | 11/2000 | Bagaoisan et al.   |
| 5,423,740 | A | 6/1995    | Sullivan et al.      | 6,152,918 | A  | 11/2000 | Padilla et al.     |
| 5,423,806 | A | 6/1995    | Dale et al.          | 6,156,049 | A  | 12/2000 | Lovato et al.      |
| 5,451,221 | A | 9/1995    | Cho et al.           | 6,159,203 | A  | 12/2000 | Sinofsky           |
| 5,456,680 | A | 10/1995   | Taylor et al.        | 6,159,225 | A  | 12/2000 | Makower            |
| 5,463,712 | A | 10/1995   | Cawood               | 6,162,214 | A  | 12/2000 | Mueller et al.     |
| 5,484,433 | A | 1/1996    | Taylor et al.        | 6,165,188 | A  | 12/2000 | Saadat et al.      |
| 5,507,751 | A | 4/1996    | Goode et al.         | 6,167,315 | A  | 12/2000 | Coe et al.         |
| 5,531,741 | A | 7/1996    | Barbacci             | 6,174,307 | B1 | 1/2001  | Daniel et al.      |
| 5,536,242 | A | 7/1996    | Willard et al.       | 6,190,352 | B1 | 2/2001  | Haarala et al.     |
| 5,562,694 | A | 10/1996   | Sauer et al.         | 6,190,353 | B1 | 2/2001  | Makower et al.     |
| 5,569,284 | A | 10/1996   | Young et al.         | 6,203,537 | B1 | 3/2001  | Adrian             |
| 5,575,797 | A | 11/1996   | Neubauer et al.      | 6,210,400 | B1 | 4/2001  | Hebert et al.      |
|           |   |           |                      | 6,210,402 | B1 | 4/2001  | Olsen et al.       |
|           |   |           |                      | 6,228,076 | B1 | 5/2001  | Winston et al.     |
|           |   |           |                      | 6,233,474 | B1 | 5/2001  | Lemelson           |
|           |   |           |                      | 6,235,044 | B1 | 5/2001  | Root et al.        |
|           |   |           |                      | 6,241,692 | B1 | 6/2001  | Tu et al.          |
|           |   |           |                      | 6,245,011 | B1 | 6/2001  | Dudda et al.       |
|           |   |           |                      | 6,251,121 | B1 | 6/2001  | Saadat             |
|           |   |           |                      | 6,258,083 | B1 | 7/2001  | Daniel et al.      |
|           |   |           |                      | 6,290,668 | B1 | 9/2001  | Gregory et al.     |
|           |   |           |                      | 6,315,774 | B1 | 11/2001 | Daniel et al.      |
|           |   |           |                      | 6,324,434 | B2 | 11/2001 | Coe et al.         |
|           |   |           |                      | 6,368,318 | B1 | 4/2002  | Visuri et al.      |
|           |   |           |                      | 6,395,002 | B1 | 5/2002  | Ellman et al.      |
|           |   |           |                      | 6,398,773 | B1 | 6/2002  | Bagaoisan et al.   |
|           |   |           |                      | 6,402,771 | B1 | 6/2002  | Palmer et al.      |
|           |   |           |                      | 6,402,781 | B1 | 6/2002  | Langberg et al.    |

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,419,674 B1	7/2002	Bowser et al.	7,033,344 B2	4/2006	Imran
6,419,684 B1	7/2002	Heisler et al.	7,033,357 B2	4/2006	Baxter et al.
6,423,051 B1	7/2002	Kaplan et al.	7,060,061 B2	6/2006	Altshuler et al.
6,428,539 B1	8/2002	Baxter et al.	7,063,693 B2	6/2006	Guenst
6,428,556 B1	8/2002	Chin	7,077,856 B2	7/2006	Whitman
6,432,119 B1	8/2002	Saadat	7,092,765 B2	8/2006	Geske et al.
6,436,054 B1	8/2002	Viola et al.	7,097,120 B2	8/2006	Marino
6,436,114 B1	8/2002	Novak et al.	7,097,129 B2	8/2006	Matthies
6,440,124 B1 *	8/2002	Esch .....	7,104,983 B2	9/2006	Grasso et al.
		A61B 18/245	7,114,642 B2	10/2006	Whitman
		606/15	7,117,039 B2	10/2006	Manning et al.
6,440,125 B1	8/2002	Rentrop	7,149,587 B2	12/2006	Wardle et al.
6,447,525 B2	9/2002	Follmer et al.	7,151,965 B2	12/2006	Osyypka
6,454,741 B1	9/2002	Muni et al.	7,189,207 B2	3/2007	Viola
6,454,758 B1	9/2002	Thompson et al.	7,191,015 B2	3/2007	Lamson et al.
6,461,349 B1	10/2002	Elbrecht et al.	7,192,430 B2	3/2007	Truckai et al.
6,478,777 B1	11/2002	Honeck et al.	7,204,824 B2	4/2007	Moulis
6,488,636 B2	12/2002	Bryan et al.	7,214,180 B2	5/2007	Chin
6,500,182 B2	12/2002	Foster	7,226,459 B2	6/2007	Cesarini et al.
6,512,959 B1	1/2003	Gomperz et al.	7,238,179 B2	7/2007	Brucker et al.
6,527,752 B1	3/2003	Bosley et al.	7,238,180 B2	7/2007	Mester et al.
6,537,314 B2	3/2003	Langberg et al.	7,252,641 B2	8/2007	Thompson et al.
6,540,865 B1	4/2003	Miekka et al.	7,264,587 B2	9/2007	Chin
6,547,779 B2	4/2003	Levine et al.	7,273,478 B2	9/2007	Appling et al.
6,554,779 B2	4/2003	Viola et al.	7,276,052 B2	10/2007	Kobayashi et al.
6,558,382 B2	5/2003	Jahns et al.	7,288,096 B2	10/2007	Chin
6,565,588 B1	5/2003	Clement et al.	7,296,577 B2	11/2007	Lashinski et al.
6,569,082 B1	5/2003	Chin	7,306,588 B2	12/2007	Loeb et al.
6,575,997 B1	6/2003	Palmer et al.	7,326,226 B2	2/2008	Root et al.
6,592,607 B1	7/2003	Palmer et al.	7,328,071 B1	2/2008	Stehr et al.
6,595,982 B2	7/2003	Sekino et al.	7,344,546 B2	3/2008	Wulfman et al.
6,599,296 B1	7/2003	Gillick et al.	7,357,794 B2	4/2008	Makower et al.
6,602,241 B2	8/2003	Makower et al.	7,359,756 B2	4/2008	Goode
6,607,547 B1	8/2003	Chin	7,369,901 B1	5/2008	Morgan et al.
6,610,046 B1	8/2003	Usami et al.	7,392,095 B2	6/2008	Flynn et al.
6,610,066 B2	8/2003	Dinger et al.	7,396,354 B2	7/2008	Rychnovsky et al.
6,613,013 B2	9/2003	Haarala et al.	7,398,781 B1	7/2008	Chin
6,620,153 B2	9/2003	Mueller et al.	7,435,247 B2	10/2008	Woloszko et al.
6,620,160 B2	9/2003	Lewis et al.	7,449,010 B1	11/2008	Hayase et al.
6,620,180 B1	9/2003	Bays et al.	7,462,167 B2	12/2008	Kratz et al.
6,641,590 B1	11/2003	Palmer et al.	7,485,127 B2	2/2009	Nistal
6,652,480 B1	11/2003	Imran et al.	7,494,484 B2	2/2009	Beck et al.
6,652,548 B2	11/2003	Evans et al.	7,507,252 B2	3/2009	Lashinski et al.
6,660,021 B1	12/2003	Palmer et al.	7,509,169 B2	3/2009	Eigler et al.
6,663,626 B2	12/2003	Truckai et al.	7,510,576 B2	3/2009	Langberg et al.
6,669,685 B1	12/2003	Rizoiu et al.	7,513,877 B2	4/2009	Viola
6,673,090 B2	1/2004	Root et al.	7,513,892 B1	4/2009	Haarala et al.
6,687,548 B2	2/2004	Goode	7,526,342 B2	4/2009	Chin et al.
6,702,813 B1	3/2004	Baxter et al.	7,537,602 B2	5/2009	Whitman
6,706,018 B2	3/2004	Westlund et al.	7,540,865 B2	6/2009	Griffin et al.
6,706,052 B1	3/2004	Chin	7,544,197 B2	6/2009	Kelsch et al.
6,706,065 B2	3/2004	Langberg et al.	7,559,941 B2	7/2009	Zannis et al.
6,709,456 B2	3/2004	Langberg et al.	D600,792 S	9/2009	Eubanks et al.
6,712,773 B1	3/2004	Viola	7,591,790 B2	9/2009	Pflueger
6,712,826 B2	3/2004	Lui	7,597,698 B2	10/2009	Chin
6,772,014 B2	8/2004	Coe et al.	7,606,615 B2	10/2009	Makower et al.
6,802,838 B2	10/2004	Loeb et al.	7,611,474 B2	11/2009	Hibner et al.
6,805,692 B2	10/2004	Muni et al.	7,625,337 B2	12/2009	Campbell et al.
6,810,882 B2	11/2004	Langberg et al.	7,637,904 B2	12/2009	Wingler et al.
6,818,001 B2	11/2004	Wulfman et al.	7,645,286 B2	1/2010	Catanese et al.
6,860,860 B2	3/2005	Viola	7,648,466 B2	1/2010	Stephens et al.
6,871,085 B2	3/2005	Sommer	7,651,503 B1	1/2010	Coe et al.
6,879,761 B2	4/2005	Rogers	7,651,504 B2	1/2010	Goode et al.
6,884,240 B1	4/2005	Dykes	D610,259 S	2/2010	Way et al.
6,887,238 B2	5/2005	Jahns et al.	D611,146 S	3/2010	Way et al.
6,893,450 B2	5/2005	Foster	7,674,272 B2	3/2010	Torrance et al.
6,913,612 B2	7/2005	Palmer et al.	7,695,485 B2	4/2010	Whitman et al.
6,962,585 B2	11/2005	Poleo et al.	7,695,512 B2	4/2010	Lashinski et al.
6,979,290 B2	12/2005	Mourlas et al.	7,697,996 B2	4/2010	Manning et al.
6,979,319 B2	12/2005	Manning et al.	7,713,231 B2	5/2010	Wulfman et al.
6,989,028 B2	1/2006	Lashinski et al.	7,713,235 B2	5/2010	Torrance et al.
6,999,809 B2	2/2006	Currier et al.	7,713,281 B2	5/2010	Leefflang et al.
7,004,956 B2	2/2006	Palmer et al.	7,722,549 B2	5/2010	Nakao
7,011,682 B2	3/2006	Lashinski et al.	7,740,626 B2	6/2010	Takayama et al.
7,022,133 B2	4/2006	Yee et al.	7,743,960 B2	6/2010	Whitman et al.
7,033,335 B2	4/2006	Haarala et al.	D619,252 S	7/2010	Way et al.
			D619,253 S	7/2010	Way et al.
			7,758,594 B2	7/2010	Lamson et al.
			7,758,613 B2	7/2010	Whitman

(56)

## References Cited

## U.S. PATENT DOCUMENTS

D621,939 S	8/2010	Way et al.	RE43,300 E	4/2012	Saadat et al.
7,766,923 B2	8/2010	Catanese et al.	8,157,815 B2	4/2012	Catanese et al.
7,780,682 B2	8/2010	Catanese et al.	8,162,878 B2	4/2012	Bonnette et al.
7,780,694 B2	8/2010	Palmer et al.	8,186,559 B1	5/2012	Whitman
7,794,411 B2	9/2010	Ritchart et al.	8,187,204 B2	5/2012	Miller et al.
7,798,813 B1	9/2010	Harrel	8,192,430 B2	6/2012	Goode et al.
7,803,151 B2	9/2010	Whitman	8,202,229 B2	6/2012	Miller et al.
7,806,835 B2	10/2010	Hibner et al.	8,206,409 B2	6/2012	Privitera et al.
7,811,281 B1	10/2010	Rentrop	8,211,118 B2	7/2012	Catanese et al.
7,815,655 B2	10/2010	Catanese et al.	8,216,254 B2	7/2012	McLean et al.
7,842,009 B2	11/2010	Torrance et al.	8,235,916 B2	8/2012	Whiting et al.
7,845,538 B2	12/2010	Whitman	8,236,016 B2	8/2012	To et al.
7,858,038 B2	12/2010	Andreyko et al.	8,239,039 B2	8/2012	Zaremba et al.
7,875,018 B2	1/2011	Tockman et al.	8,241,272 B2	8/2012	Arnold et al.
7,875,049 B2	1/2011	Eversull et al.	8,251,916 B2	8/2012	Speeg et al.
7,890,186 B2	2/2011	Wardle et al.	8,252,015 B2	8/2012	Leeftang et al.
7,890,192 B1	2/2011	Kelsch et al.	8,257,312 B2	9/2012	Duffy
7,896,879 B2	3/2011	Solsberg et al.	8,260,390 B2	9/2012	Tang
7,896,891 B2	3/2011	Catanese et al.	8,272,554 B2	9/2012	Whitman et al.
7,905,889 B2	3/2011	Catanese et al.	8,273,078 B2	9/2012	Muenker
7,909,836 B2	3/2011	McLean et al.	8,295,947 B2	10/2012	Lamson et al.
7,914,464 B2	3/2011	Burdorff et al.	8,303,511 B2	11/2012	Eigler et al.
7,914,542 B2	3/2011	Lamson et al.	8,323,240 B2	12/2012	Wulfman et al.
D635,671 S	4/2011	Way et al.	8,323,326 B2	12/2012	Dorn et al.
7,918,230 B2	4/2011	Whitman et al.	8,326,437 B2	12/2012	Cully et al.
7,918,803 B2	4/2011	Ritchart et al.	8,333,740 B2	12/2012	Shippert
7,922,654 B2	4/2011	Boutillette et al.	8,333,776 B2	12/2012	Cheng et al.
7,930,040 B1	4/2011	Kelsch et al.	8,337,516 B2	12/2012	Escudero et al.
7,935,146 B2	5/2011	Langberg et al.	8,343,167 B2	1/2013	Henson
7,938,786 B2	5/2011	Ritchie et al.	8,343,187 B2	1/2013	Lamson et al.
7,942,830 B2	5/2011	Solsberg et al.	8,353,899 B1	1/2013	Wells et al.
7,951,071 B2	5/2011	Whitman et al.	8,361,094 B2	1/2013	To et al.
7,951,158 B2	5/2011	Catanese et al.	8,361,097 B2	1/2013	Patel et al.
7,959,608 B2	6/2011	Nash et al.	8,364,280 B2	1/2013	Marnfeldt et al.
7,963,040 B2	6/2011	Shan et al.	8,372,098 B2	2/2013	Tran
7,963,433 B2	6/2011	Whitman et al.	8,394,110 B2	3/2013	Catanese et al.
7,971,800 B2	7/2011	Combs et al.	8,394,113 B2	3/2013	Wei et al.
7,974,710 B2	7/2011	Seifert	8,425,535 B2	4/2013	McLean et al.
7,981,049 B2	7/2011	Ritchie et al.	8,696,695 B2	4/2014	Patel et al.
7,981,050 B2	7/2011	Ritchart et al.	8,961,551 B2	2/2015	Taylor
7,981,128 B2	7/2011	To et al.	8,979,828 B2	3/2015	Fix
7,988,726 B2	8/2011	Langberg et al.	9,005,115 B2	4/2015	Vayser
7,991,258 B2	8/2011	Temelkuran et al.	9,283,040 B2	3/2016	Hendrick et al.
7,992,758 B2	8/2011	Whitman et al.	9,603,618 B2	3/2017	Grace et al.
7,993,350 B2	8/2011	Ventura et al.	9,883,885 B2	2/2018	Hendrick et al.
7,993,351 B2	8/2011	Worley et al.	2001/0005789 A1	6/2001	Root et al.
7,993,359 B1	8/2011	Atwell et al.	2001/0016717 A1	8/2001	Haarala et al.
8,007,469 B2	8/2011	Duffy	2001/0025174 A1	9/2001	Daniel et al.
8,007,488 B2	8/2011	Ravenscroft	2001/0031981 A1	10/2001	Evans et al.
8,007,503 B2	8/2011	Catanese et al.	2001/0039427 A1	11/2001	Dinger et al.
8,007,506 B2	8/2011	To et al.	2001/0041899 A1	11/2001	Foster
8,016,748 B2	9/2011	Mourlas et al.	2001/0044568 A1	11/2001	Langberg et al.
8,016,844 B2	9/2011	Privitera et al.	2002/0002372 A1	1/2002	Jahns et al.
8,016,855 B2	9/2011	Whitman et al.	2002/0007190 A1	1/2002	Wulfman et al.
8,016,858 B2	9/2011	Whitman	2002/0007204 A1	1/2002	Goode
8,021,373 B2	9/2011	Whitman et al.	2002/0010475 A1	1/2002	Lui
8,025,199 B2	9/2011	Whitman et al.	2002/0010487 A1	1/2002	Evans et al.
8,043,309 B2	10/2011	Catanese et al.	2002/0016628 A1	2/2002	Langberg et al.
RE42,959 E	11/2011	Saadat et al.	2002/0045811 A1	4/2002	Kittrell et al.
8,052,616 B2	11/2011	Andrisek et al.	2002/0058956 A1*	5/2002	Honeycutt et al.
8,052,659 B2	11/2011	Ravenscroft et al.	2002/0065543 A1	5/2002	Gomperz et al.
8,056,786 B2	11/2011	Whitman et al.	2002/0068954 A1	6/2002	Foster
8,056,791 B2	11/2011	Whitman	2002/0087151 A1	7/2002	Mody et al.
8,070,762 B2	12/2011	Escudero et al.	2002/0103477 A1	8/2002	Grasso et al.
8,090,430 B2	1/2012	Makower et al.	2002/0103532 A1	8/2002	Langberg et al.
8,097,012 B2	1/2012	Kagarise	2002/0103533 A1	8/2002	Langberg et al.
8,100,920 B2	1/2012	Gambale et al.	2002/0123785 A1	9/2002	Zhang et al.
8,118,208 B2	2/2012	Whitman	2002/0151961 A1	10/2002	Lashinski et al.
8,126,570 B2	2/2012	Manning et al.	2002/0183735 A1	12/2002	Edwards et al.
8,128,577 B2	3/2012	Viola	2002/0188278 A1	12/2002	Tockman et al.
8,128,636 B2	3/2012	Lui et al.	2003/0009146 A1	1/2003	Muni et al.
8,133,214 B2	3/2012	Hayase et al.	2003/0036788 A1	2/2003	Coe et al.
8,137,377 B2	3/2012	Palmer et al.	2003/0050630 A1	3/2003	Mody et al.
8,142,442 B2	3/2012	Palmer et al.	2003/0055444 A1	3/2003	Evans et al.
8,142,446 B2	3/2012	Shan	2003/0055445 A1	3/2003	Evans et al.
			2003/0060762 A1	3/2003	Zvuloni et al.
			2003/0069575 A1	4/2003	Chin et al.

A61B 17/32075  
606/159

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2003/0073985	A1	4/2003	Mueller et al.	2005/0251116	A1	11/2005	Steinke et al.
2003/0078562	A1	4/2003	Makower et al.	2005/0259942	A1	11/2005	Temelkuran et al.
2003/0105451	A1	6/2003	Westlund et al.	2005/0267557	A1	12/2005	Flynn et al.
2003/0125619	A1	7/2003	Manning et al.	2005/0273090	A1	12/2005	Nieman et al.
2003/0167056	A1	9/2003	Jahns et al.	2005/0283143	A1	12/2005	Rizoiu
2003/0187460	A1	10/2003	Chin et al.	2005/0288596	A1	12/2005	Eigler et al.
2003/0187461	A1	10/2003	Chin	2005/0288604	A1	12/2005	Eigler et al.
2003/0199921	A1	10/2003	Palmer et al.	2005/0288654	A1	12/2005	Nieman et al.
2003/0204202	A1	10/2003	Palmer et al.	2005/0288722	A1	12/2005	Eigler et al.
2003/0208209	A1	11/2003	Gambale et al.	2006/0041250	A1	2/2006	Poleo
2003/0229323	A1	12/2003	Haarala et al.	2006/0052660	A1	3/2006	Chin
2003/0229353	A1	12/2003	Cragg	2006/0084839	A1	4/2006	Mourlas et al.
2004/0006358	A1	1/2004	Wulfman et al.	2006/0100663	A1	5/2006	Palmer et al.
2004/0010248	A1	1/2004	Appling et al.	2006/0116746	A1	6/2006	Chin
2004/0015193	A1	1/2004	Lamson et al.	2006/0116757	A1	6/2006	Lashinski et al.
2004/0019359	A1	1/2004	Worley et al.	2006/0149171	A1	7/2006	Vogel et al.
2004/0039242	A1	2/2004	Tolkoff et al.	2006/0167417	A1	7/2006	Kratz et al.
2004/0049208	A1	3/2004	Hill et al.	2006/0173440	A1	8/2006	Lamson et al.
2004/0054368	A1	3/2004	Truckai et al.	2006/0217755	A1	9/2006	Eversull et al.
2004/0054377	A1	3/2004	Foster et al.	2006/0229490	A1	10/2006	Chin
2004/0054388	A1	3/2004	Osypka	2006/0235431	A1	10/2006	Goode et al.
2004/0059348	A1	3/2004	Geske et al.	2006/0247751	A1	11/2006	Seifert
2004/0064024	A1	4/2004	Sommer	2006/0253179	A1	11/2006	Goode et al.
2004/0068256	A1	4/2004	Rizoiu et al.	2006/0264905	A1	11/2006	Eskridge et al.
2004/0068288	A1	4/2004	Palmer et al.	2006/0265042	A1	11/2006	Catanese et al.
2004/0093016	A1	5/2004	Root et al.	2006/0276871	A1	12/2006	Lamson et al.
2004/0097788	A1	5/2004	Mourlas et al.	2006/0287574	A1	12/2006	Chin
2004/0102804	A1	5/2004	Chin	2007/0005084	A1	1/2007	Clague et al.
2004/0102841	A1	5/2004	Langberg et al.	2007/0015964	A1	1/2007	Eversull et al.
2004/0111101	A1	6/2004	Chin	2007/0016130	A1	1/2007	Leefflang et al.
2004/0116939	A1	6/2004	Goode	2007/0021812	A1	1/2007	Manning et al.
2004/0116992	A1	6/2004	Wardle et al.	2007/0049929	A1	3/2007	Catanese et al.
2004/0133220	A1	7/2004	Lashinski et al.	2007/0050003	A1	3/2007	Zaremba et al.
2004/0138562	A1	7/2004	Makower et al.	2007/0078500	A1	4/2007	Ryan et al.
2004/0138744	A1	7/2004	Lashinski et al.	2007/0083217	A1	4/2007	Eversull et al.
2004/0143284	A1	7/2004	Chin	2007/0100211	A1	5/2007	Selover et al.
2004/0147911	A1	7/2004	Sinofsky	2007/0100410	A1	5/2007	Lamson et al.
2004/0147912	A1	7/2004	Sinofsky	2007/0106328	A1	5/2007	Wardle et al.
2004/0147913	A1	7/2004	Sinofsky	2007/0129710	A1	6/2007	Rudko et al.
2004/0153096	A1	8/2004	Goode et al.	2007/0142846	A1	6/2007	Catanese et al.
2004/0153098	A1	8/2004	Chin et al.	2007/0142880	A1	6/2007	Barnard et al.
2004/0153146	A1	8/2004	Lashinski et al.	2007/0197861	A1	8/2007	Reiley et al.
2004/0172116	A1	9/2004	Seifert et al.	2007/0198020	A1	8/2007	Reiley et al.
2004/0176840	A1	9/2004	Langberg et al.	2007/0232981	A1*	10/2007	Ravenscroft
2004/0181249	A1	9/2004	Torrance et al.				..... A61M 25/003
2004/0216748	A1	11/2004	Chin	2007/0276412	A1	11/2007	Catanese et al.
2004/0220519	A1	11/2004	Wulfman et al.	2007/0282404	A1	12/2007	Cottrell et al.
2004/0230212	A1	11/2004	Wulfman	2007/0293853	A1	12/2007	Truckai et al.
2004/0230213	A1	11/2004	Wulfman et al.	2008/0004643	A1	1/2008	To et al.
2004/0235611	A1	11/2004	Nistal	2008/0004644	A1	1/2008	To et al.
2004/0236312	A1	11/2004	Nistal et al.	2008/0004645	A1	1/2008	To et al.
2004/0236397	A1	11/2004	Coe et al.	2008/0004646	A1	1/2008	To et al.
2004/0243123	A1	12/2004	Grasso et al.	2008/0004647	A1	1/2008	To et al.
2004/0243162	A1	12/2004	Wulfman et al.	2008/0009749	A1	1/2008	Delianides et al.
2004/0254534	A1	12/2004	Bjorkman et al.	2008/0015625	A1	1/2008	Ventura et al.
2004/0260322	A1	12/2004	Rudko et al.	2008/0021484	A1	1/2008	Catanese et al.
2004/0267276	A1	12/2004	Camino et al.	2008/0021485	A1	1/2008	Catanese et al.
2004/0267304	A1	12/2004	Zannis et al.	2008/0033232	A1	2/2008	Catanese et al.
2005/0004644	A1	1/2005	Kelsch et al.	2008/0033456	A1	2/2008	Catanese et al.
2005/0025798	A1	2/2005	Moulis	2008/0033458	A1	2/2008	McLean et al.
2005/0027337	A1	2/2005	Rudko et al.	2008/0033488	A1	2/2008	Catanese et al.
2005/0038419	A9	2/2005	Arnold et al.	2008/0039833	A1	2/2008	Catanese et al.
2005/0060030	A1	3/2005	Lashinski et al.	2008/0039872	A1	2/2008	Catanese et al.
2005/0065561	A1	3/2005	Manning et al.	2008/0039874	A1	2/2008	Catanese et al.
2005/0090748	A1	4/2005	Makower et al.	2008/0039875	A1	2/2008	Catanese et al.
2005/0096740	A1	5/2005	Langberg et al.	2008/0039876	A1	2/2008	Catanese et al.
2005/0106710	A1	5/2005	Friedman et al.	2008/0039889	A1	2/2008	Lamson et al.
2005/0107667	A1	5/2005	Danitz et al.	2008/0039893	A1	2/2008	McLean et al.
2005/0131399	A1	6/2005	Loeb et al.	2008/0039894	A1	2/2008	Catanese et al.
2005/0149104	A1	7/2005	Leefflang et al.	2008/0045986	A1	2/2008	To et al.
2005/0149105	A1	7/2005	Leefflang et al.	2008/0051756	A1	2/2008	Makower et al.
2005/0197623	A1	9/2005	Leefflang et al.	2008/0058759	A1	3/2008	Makower et al.
2005/0222607	A1	10/2005	Palmer et al.	2008/0071341	A1	3/2008	Goode et al.
2005/0228402	A1	10/2005	Hofmann	2008/0071342	A1	3/2008	Goode et al.
2005/0228452	A1	10/2005	Mourlas et al.	2008/0097426	A1	4/2008	Root et al.
				2008/0103412	A1	5/2008	Chin
				2008/0103439	A1	5/2008	Torrance et al.
				2008/0103446	A1	5/2008	Torrance et al.
				2008/0103516	A1	5/2008	Wulfman et al.

604/6.16

(56)	<b>References Cited</b>				
	U.S. PATENT DOCUMENTS				
2008/0125748	A1	5/2008	Patel	2011/0105947	A1 5/2011 Fritscher-Ravens et al.
2008/0147061	A1	6/2008	Goode et al.	2011/0106004	A1 5/2011 Eubanks et al.
2008/0154293	A1	6/2008	Taylor	2011/0106099	A1 5/2011 Duffy et al.
2008/0154296	A1	6/2008	Taylor et al.	2011/0112548	A1 5/2011 Fifer et al.
2008/0161795	A1	7/2008	Wang et al.	2011/0112562	A1 5/2011 Torrance
2008/0183163	A1	7/2008	Lampropoulos et al.	2011/0112563	A1 5/2011 To et al.
2008/0208105	A1	8/2008	Zelickson et al.	2011/0112564	A1 5/2011 Wolf
2008/0221560	A1	9/2008	Arai et al.	2011/0118660	A1 5/2011 Torrance et al.
2008/0228208	A1	9/2008	Wulfman et al.	2011/0144423	A1 6/2011 Tong et al.
2008/0249516	A1	10/2008	Muenker	2011/0144425	A1 6/2011 Catanese et al.
2008/0262516	A1	10/2008	Gambale et al.	2011/0151463	A1 6/2011 Wulfman
2008/0275497	A1	11/2008	Palmer et al.	2011/0152607	A1 6/2011 Catanese et al.
2008/0275498	A1	11/2008	Palmer et al.	2011/0152906	A1 6/2011 Escudero et al.
2008/0281308	A1	11/2008	Neuberger et al.	2011/0152907	A1 6/2011 Escudero et al.
2008/0287888	A1	11/2008	Ravenscroft	2011/0160747	A1 6/2011 McLean et al.
2008/0306333	A1	12/2008	Chin	2011/0160748	A1 6/2011 Catanese et al.
2009/0012510	A1	1/2009	Bertolero et al.	2011/0166564	A1 7/2011 Merrick et al.
2009/0018523	A1	1/2009	Lamson et al.	2011/0178543	A1 7/2011 Chin et al.
2009/0018553	A1	1/2009	McLean et al.	2011/0190758	A1 8/2011 Lamson et al.
2009/0034927	A1	2/2009	Temelkuran et al.	2011/0196298	A1 8/2011 Anderson et al.
2009/0036871	A1	2/2009	Hayase et al.	2011/0196355	A1 8/2011 Mitchell et al.
2009/0054918	A1	2/2009	Henson	2011/0196365	A1 8/2011 Kim et al.
2009/0060977	A1	3/2009	Lamson et al.	2011/0208207	A1 8/2011 Bowe et al.
2009/0069761	A1	3/2009	Vogel	2011/0213398	A1 9/2011 Chin et al.
2009/0071012	A1	3/2009	Shan et al.	2011/0218528	A1 9/2011 Ogata et al.
2009/0076522	A1	3/2009	Shan	2011/0238078	A1 9/2011 Goode et al.
2009/0131907	A1	5/2009	Chin et al.	2011/0238102	A1 9/2011 Gutfinger et al.
2009/0157045	A1	6/2009	Haarala et al.	2011/0245751	A1 10/2011 Hofmann
2009/0163899	A1	6/2009	Burton et al.	2011/0257592	A1 10/2011 Ventura et al.
2009/0192439	A1	7/2009	Lamson et al.	2011/0270169	A1 11/2011 Gardeski et al.
2009/0204128	A1	8/2009	Lamson et al.	2011/0270170	A1 11/2011 Gardeski et al.
2009/0221994	A1	9/2009	Neuberger et al.	2011/0270289	A1 11/2011 To et al.
2009/0222025	A1	9/2009	Catanese et al.	2011/0295331	A1 12/2011 Wells et al.
2009/0227992	A1	9/2009	Nir et al.	2011/0300010	A1 12/2011 Jarnagin et al.
2009/0227999	A1	9/2009	Willis et al.	2011/0301417	A1 12/2011 Mourlas et al.
2009/0234378	A1	9/2009	Escudero et al.	2011/0301626	A1 12/2011 To et al.
2009/0270862	A1	10/2009	Arcenio	2012/0022512	A1 1/2012 Vaynberg
2010/0004606	A1	1/2010	Hansen et al.	2012/0029278	A1 2/2012 Sato et al.
2010/0016836	A1	1/2010	Makower et al.	2012/0035590	A1 2/2012 Whiting et al.
2010/0030154	A1	2/2010	Duffy	2012/0041307	A1 2/2012 Patel et al.
2010/0030161	A1	2/2010	Duffy	2012/0041422	A1 2/2012 Whiting et al.
2010/0030262	A1	2/2010	McLean et al.	2012/0053564	A1 3/2012 Ravenscroft
2010/0030263	A1	2/2010	Cheng et al.	2012/0065659	A1 3/2012 To
2010/0049225	A1	2/2010	To et al.	2012/0083810	A1 4/2012 Escudero et al.
2010/0063488	A1	3/2010	Fischer et al.	2012/0083826	A1 4/2012 Chao et al.
2010/0125253	A1	5/2010	Olson et al.	2012/0095447	A1 4/2012 Fojtik
2010/0137873	A1	6/2010	Grady et al.	2012/0095479	A1 4/2012 Bowe et al.
2010/0160952	A1	6/2010	Leefflang et al.	2012/0097174	A1 4/2012 Spotnitz et al.
2010/0191165	A1	7/2010	Appling et al.	2012/0116382	A1 5/2012 Ku et al.
2010/0191178	A1	7/2010	Ross et al.	2012/0123411	A1 5/2012 Ibrahim et al.
2010/0198194	A1	8/2010	Manning et al.	2012/0136341	A1 5/2012 Appling et al.
2010/0198229	A1	8/2010	Olomutzki et al.	2012/0165827	A1 6/2012 Khairkhan et al.
2010/0217081	A1	8/2010	Deppmeier et al.	2012/0165861	A1 6/2012 Palmer et al.
2010/0217277	A1	8/2010	Truong	2012/0191015	A1 7/2012 Zannis et al.
2010/0222737	A1	9/2010	Arnold et al.	2012/0209173	A1 8/2012 Hayase et al.
2010/0222787	A1	9/2010	Goode et al.	2012/0215305	A1 8/2012 Le et al.
2010/0240951	A1	9/2010	Catanese et al.	2012/0220879	A1 8/2012 Fandrey et al.
2010/0256616	A1	10/2010	Katoh et al.	2012/0239008	A1 9/2012 Fojtik
2010/0280496	A1	11/2010	Shippert	2012/0245600	A1 9/2012 McLean et al.
2010/0324472	A1	12/2010	Wulfman	2012/0253186	A1* 10/2012 Simpson ..... A61B 17/32075 600/426
2010/0331793	A1	12/2010	Tulleken	2012/0253229	A1 10/2012 Cage
2011/0004238	A1	1/2011	Palmer et al.	2012/0265183	A1 10/2012 Tulleken et al.
2011/0009942	A1	1/2011	Gregorich et al.	2012/0323252	A1 12/2012 Booker
2011/0009957	A1	1/2011	Langberg et al.	2012/0323253	A1 12/2012 Garai et al.
2011/0022057	A1	1/2011	Eigler et al.	2012/0330292	A1 12/2012 Shaddock et al.
2011/0028959	A1	2/2011	Chasan	2013/0006228	A1 1/2013 Johnson et al.
2011/0034790	A1	2/2011	Mourlas et al.	2013/0035676	A1 2/2013 Mitchell et al.
2011/0040238	A1	2/2011	Wulfman et al.	2013/0090563	A1* 4/2013 Weber ..... A61B 5/01 600/478
2011/0040312	A1	2/2011	Lamson et al.	2013/0096582	A1 4/2013 Cheng et al.
2011/0040315	A1	2/2011	To et al.	2013/0103047	A1 4/2013 Steingisser et al.
2011/0040326	A1	2/2011	Wei et al.	2013/0274614	A1 10/2013 Shimada et al.
2011/0046648	A1	2/2011	Johnston et al.	2014/0276682	A1 9/2014 Hendrick et al.
2011/0054493	A1	3/2011	McLean et al.	2014/0276683	A1 9/2014 Hendrick et al.
2011/0060349	A1	3/2011	Cheng et al.	2014/0276694	A1 9/2014 Hendrick et al.
2011/0071440	A1	3/2011	Torrance et al.	2014/0276920	A1 9/2014 Hendrick et al.
				2015/0065945	A1 3/2015 Zarins et al.
				2015/0272615	A1 10/2015 Newhauser et al.

(56)

**References Cited****U.S. PATENT DOCUMENTS**

2016/0001038	A1	1/2016	Romo et al.
2016/0015467	A1	1/2016	Vayser et al.
2016/0120605	A1	5/2016	Hendrick et al.
2016/0256705	A1	9/2016	Webler et al.

**FOREIGN PATENT DOCUMENTS**

WO	1991017711	A1	11/1991
WO	1995033513	A1	12/1995
WO	1999007295	A1	2/1999
WO	1999049937	A1	10/1999
WO	1999058066	A1	11/1999
WO	2001076680	A1	10/2001
WO	2002049690	A9	5/2003
WO	2003007797	A9	5/2004
WO	2004049956	A2	6/2004
WO	2004080345	A2	9/2004
WO	2004080507	A2	9/2004
WO	2006007410	A2	1/2006
WO	2008005888	A2	1/2008
WO	2008005891	A2	1/2008
WO	2008042987	A2	4/2008
WO	2009005779	A1	1/2009
WO	2009054968	A1	4/2009
WO	2009065082	A1	5/2009
WO	2009126309	A2	10/2009
WO	2011003113	A1	1/2011
WO	2011084863	A2	7/2011
WO	2011133941	A2	10/2011
WO	2011162595	A1	12/2011
WO	2012009697	A4	4/2012
WO	2012098335	A1	7/2012
WO	2012114333	A1	8/2012
WO	2012177117	A1	12/2012
WO	2013036588	A1	3/2013
WO	2014151814	A1	9/2014

**OTHER PUBLICATIONS**

"Horizon Scanning Technology Prioritising Summary: Laser lead extraction systems," Australia and New Zealand Horizon Scanning Network, Aug. 2010, 15 pages.

Extended European Search Report issued in EP147801195., dated Sep. 27, 2016.

U.S. Appl. No. 15/281,981 entitled Laser Ablation Catheter, filed Sep. 30, 2016.

Decision to Grant for European Patent Application No. 07255018.9, dated Aug. 8, 2013, 2 pages.

U.S. Appl. No. 61/793,597 entitled Surgical Instrument for Removing an Implanted Object filed Mar. 15, 2013.

EP extended Search Report dated Oct. 21, 2009; Application No. 07255019.7, 8 pages.

Extended European Search Report for European Application No. 07255018.9, dated Nov. 12, 2010.

Final Action for U.S. Appl. No. 11/615,005, dated Nov. 9, 2009, 10 pages.

Final Action for U.S. Appl. No. 11/615,005, dated Nov. 21, 2013, 20 pages.

Final Action for U.S. Appl. No. 11/615,006 dated Oct. 26, 2009, 9 pages.

Intent to Grant for European Patent Application No. 07255018.9, dated Nov. 29, 2012, 7 pages.

International Search Report and Written Opinion for International Patent Application No. PCT/US2013/059434, dated Dec. 13, 2013, 14 pages.

International Search Report and Written Opinion issued in PCT/US2014/019258, dated Aug. 8, 2014, 21 pages.

International Search Report and Written Opinion issued in PCT/US2014/021167 dated Jun. 26, 2014, 19 pages.

International Search Report and Written Opinion issued in PCT/US2014/026496 dated Jul. 30, 2014, 16 pages.

International Search Report and Written Opinion issued in PCT/US2015/016899, dated May 1, 2015, 14 pages.

Notice of Allowance for European Patent Application No. 07255018.9, dated Jul. 26, 2012, 47 pages.

Notice of Allowance for Japan Patent Application No. 2007-333273, dated Jan. 16, 2014, 3 pages.

Official Action for European Patent Application No. 07255018.9, dated Jul. 19, 2011, 3 pages.

Official Action for U.S. Appl. No. 11/615,005, dated Apr. 16, 2009, 13 pages.

Official Action for U.S. Appl. No. 11/615,005, dated Feb. 11, 2011, 12 pages.

Official Action for U.S. Appl. No. 11/615,005, dated Jul. 21, 2010, 10 pages.

Official Action for U.S. Appl. No. 11/615,005, dated Mar. 14, 2013, 16 pages.

Official Action for U.S. Appl. No. 13/800,728, dated Jan. 16, 2014, 14 pages.

Official Action for U.S. Appl. No. 11/615,006 dated Apr. 24, 2009, 7 pages.

Official Action for U.S. Appl. No. 11/615,006 dated Feb. 17, 2010, 8 pages.

Official Action for U.S. Appl. No. 11/615,006 dated Jul. 20, 2010, 9 pages.

Official Action for U.S. Appl. No. 11/615,006 dated Mar. 14, 2013, 16 pages.

Official Action for U.S. Appl. No. 11/615,006 dated Nov. 22, 2013, 16 pages.

Official Action with English translation for Japan Patent Application No. 2007-333173, dated Apr. 30, 2013, 5 pages.

Official Action with English translation for Japan Patent Application No. 2007-333173, dated Aug. 13, 2012, 7 pages.

Official Action with English translation for Japan Patent Application No. 2007-333273, dated Jul. 30, 2012, 7 pages.

Official Action with English translation for Japan Patent Application No. 2007-333273, dated Jun. 6, 2013, 10 pages.

PCT Application No. PCT/US2015/016899 entitled Medical Device for Removing an Implanted Object filed Feb. 20, 2015.

PCT Application No. PCT/US2015/018305 entitled Multiple Configuration Surgical Cutting Device filed Mar. 2, 2015.

U.S. Appl. No. 13/800,651 entitled System and Method of Ablative Cutting and Pulsed Vacuum Aspiration, filed Mar. 13, 2013.

U.S. Appl. No. 13/800,675 entitled Laser Catheter With Helical Internal Lumen, filed Mar. 13, 2013.

U.S. Appl. No. 13/800,700 entitled Device and Method of Ablative Cutting With Helical Tip, filed Mar. 13, 2013.

U.S. Appl. No. 13/800,728 entitled Laser Ablation Catheter, filed Mar. 13, 2013.

U.S. Appl. No. 13/828,231 entitled Tissue Slitting Methods and Systems, filed Mar. 14, 2013.

U.S. Appl. No. 13/828,310 entitled Tissue Slitting Methods and Systems, filed Mar. 14, 2013.

U.S. Appl. No. 13/828,383 entitled Tissue Slitting Methods and Systems, filed Mar. 14, 2013.

U.S. Appl. No. 13/828,441 entitled Tissue Slitting Methods and Systems, filed Mar. 14, 2013.

U.S. Appl. No. 13/828,536 entitled Expandable Lead Jacket, filed Mar. 14, 2013.

U.S. Appl. No. 13/828,638 entitled Lead Removal Sleeve, filed Mar. 14, 2013.

U.S. Appl. No. 13/834,405 entitled Retractable Blade for Lead Removal Device, filed Mar. 15, 2013.

U.S. Appl. No. 14/577,976 entitled Surgical Instrument Including an Inwardly Deflecting Cutting Tip for Removing an Implanted Object filed Dec. 19, 2014.

U.S. Appl. No. 14/589,688 entitled Retractable Separating Systems and Methods filed Jan. 5, 2015.

U.S. Appl. No. 14/627,851 entitled Medical Device for Removing an Implanted Object filed Feb. 20, 2015.

U.S. Appl. No. 14/627,950 entitled Medical Device for Removing an Implanted Object filed Feb. 20, 2015.

U.S. Appl. No. 14/635,742 entitled Multiple Configuration Surgical Cutting Device filed Mar. 2, 2015.

(56)

**References Cited**

OTHER PUBLICATIONS

U.S. Appl. No. 61/987,993 entitled Dual Mode Mechanical Catheter Cutting System filed May 2, 2014.

U.S. Appl. No. 62/005,315 entitled Surgical Instrument for Removing an Implanted Object filed May 30, 2014.

U.S. Appl. No. 62/058,790 entitled Medical Device for Removing an Implanted Object filed Oct. 2, 2014.

U.S. Appl. No. 62/094,808 entitled Multiple Configuration Surgical Cutting Device filed Dec. 19, 2014.

U.S. Appl. No. 62/113,865 entitled Medical Device for Removing an Implanted Object filed Feb. 9, 2015.

\* cited by examiner






FIG. 2




FIG. 1




FIG. 3







FIG.4






FIG.8




FIG. 9A




FIG. 9B




FIG.10A




FIG.10B




FIG. 11A




FIG. 11B






FIG. 12A




FIG. 12B

# SYSTEM AND METHOD OF ABLATIVE CUTTING AND VACUUM ASPIRATION THROUGH PRIMARY ORIFICE AND AUXILIARY SIDE PORT

## CROSS REFERENCE TO RELATED APPLICATION

The present application claims the benefit of and priority to, under 35 U.S.C. § 119(e), U.S. Provisional Application Ser. No. 62/005,684, filed May 30, 2014, entitled "System and Method of Ablative Cutting and Vacuum Aspiration through Primary Orifice and Auxiliary Side Port," the disclosure of which is hereby incorporated by reference in its entirety for all that it teaches and for all purposes. The present application is also related to commonly owned U.S. patent application Ser. No. 13/800,651 entitled "System And Method Of Ablative Cutting And Pulsed Vacuum Aspiration," U.S. patent application Ser. No. 13/800,675 entitled "Laser Catheter with Helical Internal Lumen," U.S. patent application Ser. No. 13/800,700 entitled "Device and Method of Ablative Cutting with Helical Tip," and/or U.S. patent application Ser. No. 13/800,728 entitled "Laser Ablation Catheter" all of which were filed on Mar. 13, 2013, the disclosures of which are hereby incorporated by reference in their entireties for all that they teach and for all purposes.

## FIELD OF THE DISCLOSURE

The present disclosure relates generally to medical devices, and, in particular, to a system of improved irrigation and aspiration catheters used in the containment and removal of material resulting from therapeutic treatment of occlusions within blood vessels.

## BACKGROUND

Human blood vessels often become occluded or blocked by plaque, thrombi, other deposits, or emboli which reduce the blood carrying capacity of the vessel. Should the blockage occur at a critical place in the circulatory system, serious and permanent injury, and even death, can occur. To prevent this, some form of medical intervention is usually performed when significant occlusion is detected.

Balloon angioplasty and other transluminal medical treatments are well-known and have been proven efficacious in the treatment of stenotic lesions in blood vessels. The application of such medical procedures to certain blood vessels, however, has been limited, due to the risks associated with creation of emboli during the procedure. For example, angioplasty is not the currently preferred treatment for lesions in the carotid artery because of the possibility of dislodging plaque from the lesion, which can enter the various arterial vessels of the brain and cause permanent brain damage. Instead, surgical procedures such as carotid endarterectomy are currently used, wherein the artery is split open and the blockage removed, but these procedures present substantial risks of their own.

Other types of intervention for blocked vessels include atherectomy, deployment of stents, introduction of specific medication by infusion, and bypass surgery. Each of these methods is not without the risk of embolism caused by the dislodgement of the blocking material which then moves downstream. In addition, the size of the vessel may limit access to it.

There is also a need to efficiently remove occlusions from a patient without excess undesired removal of native blood

and tissue within the system. Constant flow suction or vacuum pressure is effective at removing freed or dislodged occlusions, but typically remove unnecessary amounts of blood in the process. Thus, there is a need for a system to effectively contain and remove such emboli without undesired consequences, such as excess removal of blood and tissue from the vessel.

Vessels as small as 3 mm in diameter are quite commonly found in the coronary arteries, and even certain saphenous vein graft bypass vessels can also be as small as 3 mm or 4 mm; although some can range as high as 7 mm. Certain of the carotid arteries also can be as small as 4 mm in diameter; although, again, others are larger. Nevertheless, a successful emboli removal system must be effective within extremely small working areas.

Another obstacle is the wide variety in emboli dimensions. Although definitive studies are not available, it is believed that emboli may have approximate diameters ranging anywhere from tens of micrometers to a few hundred micrometers. More specifically, emboli which are considered dangerous to the patient may have diameters as large as 200 to 300 micrometers or even larger. Thus, an effective emboli removal system must be able to accommodate relatively large embolic particles and, at the same time, fit within relatively small vessels.

Another difficulty that must be overcome is the limited amount of time available to perform the emboli removal procedure. That is, in order to contain the emboli produced as a result of intravascular therapy, the vessel must be occluded, meaning that no blood perfuses through the vessel to the end organs. Although certain perfusion systems may exist or may be developed which would occlude emboli while permitting the substantial flow of blood, at present, the emboli may be contained only with a complete occlusion as to both blood flow and emboli escapement. Thus, again depending upon the end organ, the complete procedure, including time for the therapeutic treatment as well as exchanges of angioplasty balloons, stents, and the like, must be completed within a short time. Thus, it may be difficult to include time for emboli removal as well. This is particularly true in the larger size vessels discussed above wherein a larger volume results in additional time required for emboli evacuation.

Additionally, there has been a long felt unmet need to provide a catheter that is adept at removing harder material, such as calcium (e.g. harder than thrombus and plaque). Cutting and removal of such harder materials generally requires additional procedure time and increased risks.

Moreover, it is important that an emboli containment and removal system be easy to use by physicians, and compatible with present therapeutic devices and methods.

## SUMMARY

These and other needs are addressed by the various aspects, embodiments, and configurations of the present disclosure.

In various embodiments, a laser cutting and aspiration atherectomy system is provided, the system comprising a catheter comprising a ring or distribution of fibers that provide a cutting function and an inner lumen through which aspirated material is removed from a patient. It is contemplated that material be removed from the lumen by, for example, a pulsed aspiration system and an in-line filter for material collection as described herein. Embodiments of laser cutting and aspiration atherectomy systems of the present disclosure provide for a wide array of benefits,

including providing the ability to create visibly smoother lumens faster than conventional laser ablation methods and systems. Embodiments of the present disclosure ablate less native tissue, separate the lesion from the vasculature in pieces or plugs, and aspirate material through the catheter. With a deflection component, this design can be used to both create a pilot channel and subsequent larger channels, faster than conventional bulk ablation. Devices of the present disclosure create a pilot channel and larger lumens in a faster manner than convention bulk ablation methods and devices.

Embodiments of the present disclosure contemplate various mechanical cutting features provided in combination with a catheter, either in addition to or in lieu of laser ablation means. Such mechanical cutting features include, but are not limited to, various bladed or shearing devices provided at or proximal to a distal end of the catheter. Such mechanical cutting features are contemplated as being substantially fixed to a distal end of a catheter, such as the periphery of an annular distal end, or selectively retractable/extendable from the distal end such that the cutting features are only provided in a position of use when desired. An example of a device that include a mechanical sheath for extending a cutting blade from the distal end of the sheath are described and illustrated in U.S. Pat. No. 5,651,781 to Grace, which is hereby incorporated herein by reference in its entirety for all that it teaches and for all purposes.

In one embodiment, a laser cutting and aspiration atherectomy catheter is provided, the catheter comprising an outer jacket with a tapered outer band, an inner lumen or channel for passage of material, and at least one ring or circular array of cutting fibers. A narrowed orifice or inner band is provided at the distal tip of the catheter. In a preferred embodiment, the catheter comprises a flexible tip with deflection items such as pull wires or shaping wires. Such deflection items are provided in addition to or in lieu of a distal outer jacket. The outer jacket provides a rigid member for communication of various user-applied forces including, but not limited to, torque, compression, and tension forces. The inner lumen provides a reinforced, lubricious lumen for material aspiration. The lumen, in certain embodiments, comprises a coil reinforced polytetrafluoroethylene/polyimide composite. Cutting fibers provide or transmit laser energy for cutting plaque and other occlusive material. In preferred embodiments, the fibers comprise 100  $\mu$ m fibers provided in concentric arrangements (with respect to one another and/or the catheter).

In various embodiments, one or more catheters of the present disclosure are provided to remove cores or plug-shaped features from an occluded vessel. Devices and methods of the present disclosure contemplate cutting and removing of discrete portions of an occlusions, such as substantially cylindrical portions generally corresponding to the shape/diameter of a catheter distal end and inner lumen. Accordingly, and in contrast with prior art systems and devices, the present disclosure comprises the ability to remove discrete plugs or sections of an occlusion and minimize particulate that may be translocated to different locations within a system and cause additional complications. Annular cutting features, such as ablative lasers and/or mechanical cutting features, inner lumen removal systems, and structural features of catheters that enable application of axial of compression force to the catheter, for example, provide means for extracting discrete plugs or clogs of material from an occlusion and restoration of blood flow through an occlusion.

In additional embodiments, one or more catheters of the present disclosure are provided to remove the tissue from the

remainder of the vessel after the core(s) or plug-shaped features of the occlusion are removed and the remainder of the occlusion and/or vessel is now exposed. After the bulk of the occlusion within the vessel is removed, it may be desirable to aspirate from the vessel any additional or remaining portion of the occlusion, such as now-exposed plaque, thrombi, or other deposits. It may be desirable to use the same lumen within the catheter used to aspirate the core of plug-shaped feature or it may be desirable to use an additional aspiration lumen in the catheter to remove the additional or remaining portion of the occlusion. Additionally, it may be desirable to use the same orifice at the end of the catheter from which the lumen extends to aspirate the core of plug-shaped feature or it may be desirable to use an auxiliary orifice (or opening) that is located at the distal end of the catheter or the side of the catheter body. The auxiliary orifice may be connected to either the same lumen used to aspirate the core of plug-shaped feature or it may be desirable to use a supplemental aspiration lumen to remove the additional or remaining portion of the occlusion.

Including an additional aspiration orifice within the catheter, particularly, in the side of the catheter, negates the potential need for utilizing an additional medical device to aspirate any additional, remaining or now-exposed plaque, thrombi, or other deposits after the majority of the occlusion is removed. Utilizing an additional medical device for such further aspiration not only adds additional cost to perform the surgical procedure, but using an additional medical device increases the overall time of the procedure and potentially increases the overall surgically related risks, such as infection, to the patient. The additional aspiration orifice in the same catheter used to remove the core(s) or plug-shaped features of the occlusion, therefore, efficiently increases the size of the initially formed lumen within the vessel by aspirating more unwanted plaque, thrombi or other deposits.

A method for removing one or more occlusions from a vessel is provided. In one embodiment, the method for removing an occlusion from a vessel comprises the steps of (a) providing an aspiration catheter comprising a proximal end, a distal end, an inner lumen extending from the distal end toward the proximal end, an outer cylindrical surface extending from the distal end toward the proximal end, wherein the distal end has a substantially annular construction defining an orifice for the inner lumen; at least one cutting element provided coincident or distal with the inner lumen; and a second orifice disposed within the outer cylindrical surface and extending to the inner lumen. (b) providing a vacuum pump in fluid communication with the inner lumen and operable to transmit material through the inner lumen. (c) inserting the distal end of the aspiration catheter into a blood vessel navigating the distal end to a site of stenosis, (d) selectively activating appropriate cutting element parameters, (e) activating the vacuum pump to extract a stenotic material through the orifice and conveying the stenotic material through the inner lumen of the catheter, and (f) conveying stenotic material through the second orifice through the inner lumen of the catheter.

The second orifice may extend to the inner lumen and the stenotic material may be conveyed through the second orifice and through the inner lumen of the catheter. Alternatively, if the aspiration catheter comprises a second lumen extending toward the proximal end, with the second orifice coupled to the second lumen, then the stenotic material may be conveyed through the second orifice and through the second lumen. The inner lumen and the second lumen may be coupled to the same vacuum pump or the inner lumen

5

may be coupled to separate vacuum pumps. For example, inner lumen may be fluidly coupled to one vacuum pump and the second lumen may be fluidly coupled to the second vacuum pump.

In a further embodiment, there is provided a catheter aspiration system comprising a catheter having a tubular wall, the tubular wall comprising a distal end and an orifice for an inner lumen extending proximally from the distal end, an opening in the tubular wall; a plurality of optical fibers located within the tubular wall and exposed at the distal end of the catheter; and a vacuum pump in fluid communication with the inner lumen.

The catheter aspiration system may be configured such that the opening in the tubular wall extends to the inner lumen. The catheter of the catheter aspiration system may further comprise a second lumen extending toward the proximal end, wherein the opening is coupled to the second lumen. The inner lumen and the second lumen may be coupled to the same vacuum pump or the inner lumen may be coupled to separate vacuum pumps. For example, inner lumen may be fluidly coupled to one vacuum pump and the second lumen may be fluidly coupled to the second vacuum pump.

In a further embodiment, the catheter is provided comprising an outer jacket, the outer jacket providing protection for internally-disposed fibers and aiding in maintaining the integrity of the inner lumen(s). The outer jacket further provides enhancements in control of the device, including flexibility of the catheter, track-ability along a path, and enhanced ability to accommodate and/or transmit torque and compression. Preferably, a tricoil arrangement is provided. In alternative embodiments, braided Pebax®, braided polyimide, and Pebax® jackets are provided.

As used herein, a "tricoil" arrangement comprises a shaft comprising coiled wire in a plurality of layers. In certain embodiments, construction of a tricoil includes wrapping at least one round or flat wire in one direction, either clockwise or counter-clockwise around a core mandrel. The wires are wrapped side by side and secured when an appropriate length is achieved. A second layer of at least one round or flat wires is wound in the opposite direction on top of the first layer and secured. The final layer of at least one round or flat wire is wound in the opposite direction of the second layer (or the same direction as the first layer) and secured. The assembly is then welded together at the ends of the shaft to create the component. Wire dimensions and count can be varied in construction for various attributes.

Tricoils contemplated by the present disclosure include, but are not limited to 1-4-4 and 1-6-6 filar count by layer, with flat wires from 0.0014"×0.010" to 0.002"×0.016". Benefits of tricoils include extreme torquability (approaching 1:1 ratio of torque input to torque output, even in bends), kink resistance, inner lumen protection, and durability, to name a few.

Alternative catheter shaft constructions include, but are not limited to Pebax, Braided Pebax, Braided Polyimide, Bicoils, and various combinations thereof.

Inner lumens of catheters of the present disclosure provide a conduit or pathway for aspirating cut or ablated material out of the body. In various embodiments, a vacuum-sealed, lubricious inner surface is provided that does not substantially deform or kink, so as to facilitate consistent removal of material without clogging the device. In certain embodiments, the lumen comprises a coil-reinforced, polytetrafluoroethylene/polyimide composite that provides sufficient hoop strength while allowing for a lubricious inner surface. In additional embodiments, a braid-reinforced

6

PTFE/polyimide composite is provided for the inner lumen. In yet additional embodiments, the inner lumen may have ridges formed in a rifle-like manner to further control the removal of the material.

In certain embodiments, a catheter is provided comprising an internal rifled feature. A catheter jacket is contemplated as comprising an internal feature of a spiral and/or spinning helix or screw configuration. The jacket, which may be a polymer extrusion, comprises a helical rib or rifle such that rotation of the catheter about a longitudinal axis aspirates and/or macerates material. Extension and/or rotation of the catheter induces rotation of the helix structure, thereby freeing material and enabling removal. Freed material may be conveyed from a vessel via a central lumen of the catheter, for example.

The design of the inner lumen is essential to the removal of material without clogging. Requirements for the inner lumen include ovaling/kink resistance, vacuum compression resistance, and inner surface lubricity. Inner lumens that we have tried have been mostly composed of some type of Polyimide construction. We have used pure Polyimide lumens, PTFE/Polyimide Composite lumens, Pure PTFE inner liner with a PTFE/Polyimide composite outer layer. Reinforcement to the inner lumens has consisted of stainless steel wire braids and coils embedded into the walls of the lumen. These reinforcements prevent kinking, ovaling, and vacuum compression. Inner lumen design could consist of any combinations of components listed in the shaft design section.

Fibers of the present disclosure are provided to deliver laser energy, including that produced by a Spectranetics® CVX-300 and related interface circuit, for example. It is contemplated that fibers of the present disclosure be protected from damage and oriented correctly at the distal tip of the catheter for laser ablation. In various embodiments, approximately fifty to one hundred fibers are provided in concentric annular rings. In a preferred embodiment, seventy four 100 μm fibers are provided in concentric circles. This particular embodiment provides for sufficient energy to ablate tissue, while leaving enough room for a sufficiently large inner lumen space. It will be recognized, however, that the present disclosure is not limited to a particular number or arrangement of fibers. Indeed, various alternative arrangements and quantities of cutting fibers are contemplated as within the scope and spirit of the present disclosure. In alternative embodiments, any combination of fiber size can be utilized, including but not limited to 61/100/130 μm fibers, either in substantially circular or ovoid cross-section.

In various embodiments, a narrowed orifice/inner band is provided that creates a limiting orifice at the distal tip of the catheter. The narrowed orifice helps ensure that if material can pass through it, it will fit down the remainder of the inner lumen. Additionally, the narrowed orifice provides a rigid inner member for fiber support and prevents inner lumen degradation and damage. In one embodiment, a short, thin wall stainless steel hypotube is provided for the narrowed orifice. The shortness of the orifice decreases the chances of clogging at the tip, while the thin wall design reduces the amount of dead space for laser ablation.

In various embodiments, an outer band is provided at the distal end of the catheter, the outer band providing a rigid structure for fiber support and protection as well as ease of manipulation of fiber placement within the distal end. The present disclosure contemplates one or more bands or rows of fibers. One, two, or three or more substantially concentric rows of fibers may be provided for ablating material.

In one embodiment, a Pt/Ir band of approximately 2.0 mm diameter is provided that tapers to approximately 2.3 mm in diameter. Although various embodiments contemplate Pt/Ir bands, any biocompatible material including, but not limited to, stainless steel, plastic, etc. may be used to confine fibers. Outer band embodiments of the present disclosure provide for grouping of at least the distal ends of the fibers proximate an inner band, thus focusing the laser energy and allowing for more of the laser energy to create smaller plugs of material. It is further noted that such embodiments provide for a manufacturing “stop” when the flared inner lumen fits into the preferably tapered portion of the band. Although various embodiments contemplate a tapered outer band, non-tapered bands are also contemplated by the present disclosure.

Catheters of the present disclosure comprise one or more polished surfaces that dictate the interaction of the tip with a surface encountered by the tip. Various embodiments comprise flat polished faces that engage tissue concentrically. Preferably, a flat polish is provided that allows not only the fiber faces to engage tissue at the same time, but also allows the inner lumen to form a vacuum seal on tissue that fills the distal face.

Deflection means are provided in various embodiments of the present disclosure for user-selective manipulation of a distal end of a catheter. In various embodiments, deflection means comprise features involved in offsetting or deflecting the catheter tip, such that a larger lumen may be created in an occlusion, as compared with non-deflective or offset manipulation of the catheter. It is contemplated that deflection means of the present disclosure provide for between approximately 2-5 mm offsets from an initial or aligned positioned, and preferably for between approximately 3-4 mm offsets, particularly for “above the knee” procedures.

In certain embodiments, one or more pullwires are provided as deflection means. Pullwires of the present disclosure comprise wires that run down the length of the catheter and are attached to the distal tip for manipulation thereof. When a tension force is applied to at least one deflection means of such embodiments, the wire(s) causes deflection of the flexible distal end of the catheter. In one embodiment, a wire component is provided in the catheter that is permanently fixed to the distal portion of the catheter. User manipulation of the wire, for example at a user-proximal portion of the catheter, is effective to shape the wire and catheter to a particular desired shape for larger lumen creation. In an additional embodiment, a balloon feature is provided comprising a non-compliant balloon fastened to the distal tip that, when inflated, causes deflection preferentially to one side of a corridor. Additionally, ramped features, such as those shown and described in U.S. Pat. No. 5,484,433 to Taylor et al., which is hereby incorporated by reference in its entirety may be included within catheters of the present disclosure.

Embodiments of the present disclosure also contemplate a flexible tip provided in combination with deflection means such as a shaping spine or pullwire. A flexible portion at the distal tip allows for bends and angled to be induced at the intended site, while the rest of the catheter can remain straight and rigid. In certain embodiments, laser cut hypotubes are provided having a thick enough wall for flexing without buckling and kerf widths (laser cut widths) large enough to allow for the bend angle required. Such tips are attached to the end of the catheter by laser welding (with a tricoil) or a fuse joint (plastics) and can be cut to preferentially bend a certain direction. Additionally, Pebax segments may be provided, such segments being fused to the end of

a tricoil and able to deflect using a pullwire and/or shaping wire. Employing polymer tubing, a wire coil, or a combination thereof for the distal body, a guide wire may be used in peripheral or coronary angioplasty applications.

Various embodiments of the present disclosure also contemplate a spiraled ring ablation device with a mechanical cutting tip at the distal end of the catheter. A laser fiber ring is provided for cutting tissue while a blade or mechanical cutting edge assists in cutting and removal of harder calcium deposits, for example. The distal end may also be rotatable at various speeds to create various motions with the mechanical cutting edge. The edges of a spiral band may further be provided with mechanical cutting features. Thus, in various embodiments, a catheter is provided with a combination of laser and mechanical cutting or ablation features. Cutting efficiencies, particular with respect to calcium deposits, are thus improved.

Concurrent extension and rotation of at least a distal end of a catheter of the present disclosure is provided as a means for cutting and ablating an obstruction. In one embodiment, a method of removing material from a blood vessel is contemplated, the method comprising the step of concurrently extending a catheter along a length of a vessel and rotating at least the distal end of the catheter. Such methods provide various advantages, including the ability to core out or extract a substantially cylindrical mass of material and providing a fluid flow corridor through an obstruction, thus enabling fluid/blood flow through the corridor even when complete removal or ablation of the obstruction is not performed.

Various embodiments of the present disclosure contemplate a pulsed vacuum aspiration system to evacuate material removed during an atherectomy procedure and remove material as it is ablated and moved down the shaft of a vacuum device in a pulsed manner.

Although pulsed aspiration systems are contemplated with various features shown and described herein, the features, systems and methods described herein are not limited to use with pulsed aspiration systems and methods. Indeed, various removal means, devices and methods are contemplated for use with various features of the present disclosure. Such means, devices and methods include, but are not limited to, spinning helixes, rotating screws, Archimedes screws, continuous vacuum aspiration, and various combinations thereof. Additionally, aspiration systems other than a pulsed aspiration systems may be used. For example, an additional embodiment may include the use of a peristaltic pump for material aspiration in conjunction with laser cutting and coring. Use of the peristaltic pump may negate the use of a solenoid valve or pulse width modulator, due to the nature of peristaltic pump material movement. The peristaltic pump embodiment differs mainly from the vacuum pump embodiment in that it relies on a liquid filled system to aspirate or move material, while the vacuum pump system utilizes both air and liquid filled system, leading to potential variability within the system due to the compressibility nature of air. With reference to FIG. 4, if a peristaltic pump is used, then the vacuum pump 18 would be replaced with a peristaltic pump and the solenoid valve 22 and pulse width modulator 20 would be deleted.

Other disclosures include using mechanical or laser means to macerate/destroy material as it enters the inner lumen.

In various embodiments, one or more vacuum pumps are provided to generate the vacuum required to aspirate material down a central lumen of a catheter. Vacuum levels in the range of 10 to 30 in-Hg, and preferably approximately 20

in-Hg, are provided. Vacuum pumps of the present disclosure preferably comprise a disposable collection container.

Another aspect of the present disclosure comprises a clogging detection means which detects clogging in an aspiration tube or an aspiration catheter during an aspiration operation.

In certain embodiments, an aspirator includes clogging detection means for measuring a change in a flow rate of an aspirate at one more points in a system. Alternatively, clogging detection means comprise means for measuring a change in a weight of an aspirate sampling bottle and/or a change in an amount of aspiration dropping in an aspirate sampling bottle. In various embodiments, clogging alert means for informing a user that clogging in the aspiration tube or the aspiration catheter has occurred are provided.

Clogging alert means of the present disclosure include, but are not limited to warning sounds and/or visual indicators that immediately notify a user of a potential clog such that remedial action can be taken immediately.

In one embodiment, an aspirator is provided with clogging detection means, the clogging detection means comprising a load cell for measuring the weight of an aspirate collection feature, such as a sampling jar. When clogging in the aspiration catheter or the aspiration tube occurs, a rate of increase in the weight of the collection features decreases. Therefore, clogging in the aspiration catheter or the aspiration tube can be detected by measuring a change in weight of the aspirate collection feature with the load cell. Where clogging is detected, a warning indicia is provided to inform an operator that the clogging has potentially occurred.

In alternative embodiments, detection of clogging is performed by measuring a change in a flow rate of an aspirate at one or more points in the system, such as blood flow in the aspiration catheter and/or the aspiration tube. For example, flow rate in a part of an aspiration tube immediately before an aspirate collection device is continuously measured by a flowmeter, an ultrasonic wave flowmeter, or the like during an aspiration operation. When a flow rate falls to a set value or less, it can be judged that clogging has occurred.

In still further embodiments, clogging or blockage is detected based on monitoring pressure values at one or more points in a system. Since an aspiration pressure increases when the aspiration catheter or the aspiration tube is blocked, when the aspiration pressure rises to a set value or more, it can be judged that clogging has occurred. It is also possible to set a threshold value for an output to the pressure indicator and emit a warning when the output increases to the threshold value or more.

When clogging in the aspiration catheter or the aspiration tube has occurred, it is preferable that an operator is informed to that effect immediately, and prompt measures for restart of aspiration are taken. Examples of the clogging alert means emitting a warning indicia include, but are not limited to a buzzer, a bell, various electronic sounds, and artificial voices. The clogging alert means is not specifically limited. If the alert means using a warning sound is adopted, an operator can concentrate on manipulation sufficiently and safety of an operation or a patient is remarkably improved because it is unnecessary for the operator to look at the medical aspirator in order to monitor clogging during the manipulation. Clogging alert means are further contemplated as comprising visual indicia, including various lamps, LEDs, or the like.

Embodiments of the present disclosure contemplate a vacuum system with clog detection features. Such embodiments comprise means to detect a difference in vacuum

pressure, such as when a clog or obstruction is provided in a vacuum line and means to alert a user or operator of the device. Alert means of the present disclosure include, but are not limited to, auditory and visual feedback features to identify to the user that a clog in the vacuum system is present or likely present.

In one embodiment, alert means comprise a mechanical switch or feature that is activated upon a pressure value in a vacuum system exceeding a predetermined value. For example, a weighted or pressurized element is provided in a manner wherein the element is substantially hidden from a user's view when the vacuum is operating under normal unobstructed conditions. However, upon the pressure value exceeding a predetermined value, such as that corresponding to a significant blockage in the vacuum system, the element is displaced to a position whereby it is visible to a user. Such an embodiment provides a "red flag" warning indicia to a user that the vacuum is not operating normally and an obstruction may be present.

In a further embodiment, alert means comprise audio and/or visual indicia prompted by a waveform output of vacuum pressure at a particular point in the system. For example, a vacuum system is provided with one or more electromechanical pressure sensing features, such features outputting a waveform corresponding to pressure values at one or more points over time. Where at least one of such pressure values exceeds (thus indicating an upstream blockage) or drops below (thus indicating a downstream blockage) a predetermined value, the detected value prompts an associated audio and/or visual alarm to indicate to a user the presence of one or more blockages.

A method of operating a vacuum assisted aspiration system is provided, the method comprising the steps of: prepping and priming a catheter for surgery, inserting the catheter into a patient via a sheath, navigating the catheter to a site of stenosis (e.g. via guidewire), selecting appropriate mechanical and/or laser cutting parameters, activating appropriate mechanical and/or laser cutting features, activating a pulsed aspiration system via a foot pedal or similar user-actuation means, manipulating the catheter to core out stenotic material, applying laser energy and/or mechanical means to core material, and transmitting material into a distal tip of the catheter and subsequently conveying the material through the length of the catheter. A user may subsequently repeat various aforementioned steps until a stenosis is adequately removed or remedied. In embodiments comprising clog detection means, wherein a lesion material becomes clogged within the system, vacuum pressure will increase at a point in the system. Wherein such a condition occurs, alert means indicate to a user the presence of a clog. The user may then take correction, such as removing the device from the patient, purging the catheter, and subsequently re-employing the device for subsequent operations.

In one embodiment, a custom vacuum pump is provided. Alternatively, known and/or commercially available pumps, such as personal patient pumps are provided. It will be recognized that the present disclosure is not limited to any specific pump size, power, displacement etc. Preferably, however, one or more pumps of small, lightweight design that can still create and maintain the required vacuum levels are provided.

Various vacuum systems of the present disclosure comprise one or more solenoid valves to open and close a line between the vacuum pump and the aspiration lumen of the

catheter. Such valves are compatible with blood, are liquid sealed, and have a fast response time for opening and closing at high frequencies.

In various embodiments, a custom valve is provided that is small, fast responding and can be fully integrated with the pump and other circuitry. The valve(s) may be disposable with the rest of the system or reusable (e.g. with the proper filters).

One or more filters are provided to collect material being aspirated down the inner lumen of the catheter. Filters of the present disclosure are provided with, for example, Luer valve fittings for ease of use, removal, cleaning, and reattachment. One filter of the present disclosure comprises Luer valve sides of two syringes with a plastic grate inside. The pore size of the grate is large enough to let liquid move through unimpeded, but small enough to prevent material from going through the valve into the disposable collection jar.

Pulsed vacuum systems of the present disclosure comprise a pulse width modulator to provide various signals to a valve, causing the valve to react faster/slower and remain open/closed for longer amounts of time.

Pulsing characteristics can be programmed into the vacuum pump/valve, and/or controlled by a user-operable feature such as a manual device or foot-pedal. In certain embodiments, a delay is built into an interface circuit of the present disclosure, the delay provided to allow the vacuum pump to run for a set amount of time after cutting operations have ceased, thereby allowing the inner lumen and other aspiration corridors to clear of material, thus reducing risk of back-flow and providing the benefit of generally clearing or purging the system. The delay may be programmed to allow the vacuum to run various durations. It will be recognized, however, that a preferred duration is one that accounts for length of lumen/corridor and flow rate and thus provides sufficient clearing of the system.

Preferably, a preset/adjustable custom circuit is provided, the custom circuit designed for pulsed aspiration in combination with additional features. The circuit comprises a user interface for adjustment, or is alternatively completely preset. In one embodiment, an interface circuit is provided that interfaces with a laser excimer system foot pedal, such as that associated with the Spectranetics® CVX-300, allowing for activation of the pulsed aspiration system only when lasing is actively occurring, thus further reducing the amount of undesired or unnecessary fluid transferred from a patient. A delay is built into the circuit to allow the vacuum pump/valve to run for a set amount of time after lasing so that the inner lumen can clear material. Such a delay may be pre-programmed based on various system characteristics including, but not limited to, the length of the inner lumen.

The present disclosure can provide a number of advantages depending on the particular configuration. Advantages of embodiments of the present disclosure include, but are not limited to, the evacuation of particulate and occlusions from an atherectomy site as such particulate is generated, thus reducing the risk of mere translocation of the particulate to other areas of the circulatory system. Various embodiments of the present disclosure contemplate user-selected pulsation of a vacuum or removal system such that the system may be pulsed only as particulate generation is occurring, decreasing the volume of blood or fluid extracted from a patient.

Additionally, pulsation features of the present disclosure are capable of providing short duration peak vacuum pressures that enhance the device's ability to evacuate larger or higher friction particles. Pulsed action methods and devices create a stepped motion from the extraction site down a

catheter shaft, for example. Pulse width and duty cycle of the vacuum pulse can be varied to optimize the particle aspiration process for highest efficiency and minimum blood and fluid removal.

In various embodiments, the device of the present disclosure may not only be used for dissecting, coring and aspirating plug-type portions of lesion material, but the device or embodiments of the device of the present disclosure may be used to perform bulk ablation. Bulk ablation generally encompasses the use of catheter having a full face of laser emitters at its distal end, and all of the lesion material contacted by the energy transmitted by the laser emitters is ablated, in comparison to ablating the lesion with a circular or helical arrangement of lasers and coring the tissue. Depending upon the size and type of lesion, the bulk ablation technique may potentially increase the efficiency of the system and removal of debris. Such a technique may be used by a user/physician based on the specific removal needs and may comprise, for example, inserting an additional laser catheter through a central lumen to provide a substantially flat laser ablation distal end of the catheter.

Various embodiments of the present disclosure contemplate mechanical material removal means, such as helixes and screws. In one embodiment, a method and system is provided comprising a stainless steel hypotube further comprising a helical structure, the helical structure is capable of rotation at, for example, at approximately 15,000 to approximately 100,000 RPM. Such helical structure(s) are capable of macerating and translating material along their length, and thus removing occlusions from a vessel. Helical structures of the present disclosure may be provided in combination with various vacuum systems, laser and mechanical ablation systems, and other features described herein to assist in removal of material.

In various embodiments, a system is provided with user-selected presets for pulsed vacuum aspiration modes. For example, in one embodiment, a plurality of settings are provided in connection with a pulse width modular such that a user/physician may select between general vacuum aspiration settings including "low," "medium," and "high" based on the user's first-hand knowledge of the amount of particulate being evacuated or desired to be evacuated.

In various embodiments, one or more filters are applied, such as catch filters that allow a physician to visualize and/or analyze material being removed from an aspiration site.

These and other advantages will be apparent from the disclosure of the aspects, embodiments, and configurations contained herein.

As used herein, "at least one", "one or more", and "and/or" are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions "at least one of A, B and C", "at least one of A, B, or C", "one or more of A, B, and C", "one or more of A, B, or C" and "A, B, and/or C" means A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B and C together. When each one of A, B, and C in the above expressions refers to an element, such as X, Y, and Z, or class of elements, such as  $X_1$ - $X_m$ ,  $Y_1$ - $Y_m$ , and  $Z_1$ - $Z_m$ , the phrase is intended to refer to a single element selected from X, Y, and Z, a combination of elements selected from the same class (e.g.,  $X_1$  and  $X_2$ ) as well as a combination of elements selected from two or more classes (e.g.,  $Y_1$  and  $Z_m$ ).

It is to be noted that the term "a" or "an" entity refers to one or more of that entity. As such, the terms "a" (or "an"), "one or more" and "at least one" can be used interchangeably.



ably herein. It is also to be noted that the terms “comprising”, “including”, and “having” can be used interchangeably.

The term “automatic” and variations thereof, as used herein, refers to any process or operation done without material human input when the process or operation is performed. However, a process or operation can be automatic, even though performance of the process or operation uses material or immaterial human input, if the input is received before performance of the process or operation. Human input is deemed to be material if such input influences how the process or operation will be performed. Human input that consents to the performance of the process or operation is not deemed to be “material”.

A “catheter” is a tube that can be inserted into a body cavity, duct, lumen, or vessel, such as the vasculature system. In most uses, a catheter is a relatively thin, flexible tube (“soft” catheter), though in some uses, it may be a larger, solid-less flexible—but possibly still flexible—catheter (“hard” catheter).

The term “computer-readable medium” as used herein refers to any storage and/or transmission medium that participate in providing instructions to a processor for execution. Such a medium is commonly tangible and non-transient and can take many forms, including but not limited to, non-volatile media, volatile media, and transmission media and includes without limitation random access memory (“RAM”), read only memory (“ROM”), and the like. Non-volatile media includes, for example, NVRAM, or magnetic or optical disks. Volatile media includes dynamic memory, such as main memory. Common forms of computer-readable media include, for example, a floppy disk (including without limitation a Bernoulli cartridge, ZIP drive, and JAZ drive), a flexible disk, hard disk, magnetic tape or cassettes, or any other magnetic medium, magneto-optical medium, a digital video disk (such as CD-ROM), any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a PROM, and EPROM, a FLASH-EPROM, a solid state medium like a memory card, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read. A digital file attachment to e-mail or other self-contained information archive or set of archives is considered a distribution medium equivalent to a tangible storage medium. When the computer-readable media is configured as a database, it is to be understood that the database may be any type of database, such as relational, hierarchical, object-oriented, and/or the like. Accordingly, the disclosure is considered to include a tangible storage medium or distribution medium and prior art-recognized equivalents and successor media, in which the software implementations of the present disclosure are stored. Computer-readable storage medium commonly excludes transient storage media, particularly electrical, magnetic, electromagnetic, optical, magneto-optical signals.

A “coupler” or “fiber optic coupler” refers to the optical fiber device with one or more input fibers and one or several output fibers. Fiber couplers are commonly special optical fiber devices with one or more input fibers for distributing optical signals into two or more output fibers. Optical energy is passively split into multiple output signals (fibers), each containing light with properties identical to the original except for reduced amplitude. Fiber couplers have input and output configurations defined as  $M \times N$ .  $M$  is the number of input ports (one or more).  $N$  is the number of output ports and is always equal to or greater than  $M$ . Fibers can be thermally tapered and fused so that their cores come into

intimate contact. This can also be done with polarization-maintaining fibers, leading to polarization-maintaining couplers (PM couplers) or splitters. Some couplers use side-polished fibers, providing access to the fiber core. Couplers can also be made from bulk optics, for example in the form of microlenses and beam splitters, which can be coupled to fibers (“fiber pig-tailed”).

The terms “determine”, “calculate” and “compute,” and variations thereof, as used herein, are used interchangeably and include any type of methodology, process, mathematical operation or technique.

A “laser emitter” refers to an end portion of a fiber or an optical component that emits laser light from a distal end of the catheter towards a desired target, which is typically tissue.

An optical fiber (or laser active fibre) is a flexible, transparent fiber made of an optically transmissive material, such as glass (silica) or plastic, that functions as a waveguide, or “light pipe”, to transmit light between the two ends of the fiber.

The term “means” as used herein shall be given its broadest possible interpretation in accordance with 35 U.S.C., Section 112(f). Accordingly, a claim incorporating the term “means” shall cover all structures, materials, or acts set forth herein, and all of the equivalents thereof. Further, the structures, materials or acts and the equivalents thereof shall include all those described in the summary of the invention, brief description of the drawings, detailed description, abstract, and claims themselves.

It should be understood that every maximum numerical limitation given throughout this disclosure is deemed to include each and every lower numerical limitation as an alternative, as if such lower numerical limitations were expressly written herein. Every minimum numerical limitation given throughout this disclosure is deemed to include each and every higher numerical limitation as an alternative, as if such higher numerical limitations were expressly written herein. Every numerical range given throughout this disclosure is deemed to include each and every narrower numerical range that falls within such broader numerical range, as if such narrower numerical ranges were all expressly written herein.

The preceding is a simplified summary of the disclosure to provide an understanding of some aspects of the disclosure. This summary is neither an extensive nor exhaustive overview of the disclosure and its various aspects, embodiments, and configurations. It is intended neither to identify key or critical elements of the disclosure nor to delineate the scope of the disclosure but to present selected concepts of the disclosure in a simplified form as an introduction to the more detailed description presented below. As will be appreciated, other aspects, embodiments, and configurations of the disclosure are possible utilizing, alone or in combination, one or more of the features set forth above or described in detail below.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are incorporated into and form a part of the specification to illustrate several examples of the present disclosure. These drawings, together with the description, explain the principles of the disclosure. The drawings simply illustrate preferred and alternative examples of how the disclosure can be made and used and are not to be construed as limiting the disclosure to only the illustrated and described examples. Further features and advantages will become apparent from the following, more

15

detailed, description of the various aspects, embodiments, and configurations of the disclosure, as illustrated by the drawings referenced below.

FIG. 1 is a top perspective view of a distal end of a catheter according to one embodiment of the present disclosure;

FIG. 2 is an elevation view of a distal end of a catheter according to one embodiment of the present disclosure;

FIG. 3 is cross-sectional view of a distal end of a catheter according to one embodiment of the present disclosure;

FIG. 4 is a schematic of a pulsed vacuum system according to one embodiment of the present disclosure;

FIG. 5 is a perspective view of a distal end of a catheter according to one embodiment of the present disclosure;

FIG. 6 is an elevation view of a distal end of a catheter according to one embodiment of the present disclosure;

FIG. 7 is an elevation view of a distal end of a catheter according to one embodiment of the present disclosure;

FIG. 8 is a perspective view of a distal end of a catheter according to another embodiment of the present disclosure;

FIG. 9A, is a perspective view of a distal end of a catheter having a cutting blade at its distal tip in a retracted position according to one embodiment of the present disclosure;

FIG. 9B, is a perspective view of a distal end of a catheter having a cutting blade at its distal tip in an extended position according to one embodiment of the present disclosure;

FIG. 10A, is a perspective view of a distal end of a catheter having a cutting blade at its distal tip in a retracted position according to another embodiment of the present disclosure;

FIG. 10B, is a perspective view of a distal end of a catheter having a cutting blade at its distal tip in an extended position according to another embodiment of the present disclosure;

FIG. 11A is a cross-sectional elevation view of a catheter according to one embodiment;

FIG. 11B is a phantom perspective view of a catheter according to one embodiment;

FIG. 12A is a top perspective view of a distal end of a catheter according to an alternative embodiment of the present disclosure; and

FIG. 12B is cross-sectional view of a distal end of a catheter according to an alternative embodiment of the present disclosure.

#### DETAILED DESCRIPTION

Although a large portion of this disclosure includes a discussion of laser catheters (or catheters having a combination of laser emitters and mechanical cutting tips at the distal end its distal end,) used in conjunction with an aspiration system, catheters having mechanical cutting tips may also be used. Laser catheters typically transmit laser energy through optical fibers housed in a relatively flexible tubular catheter inserted into a body lumen, such as a blood vessel, ureter, fallopian tube, cerebral artery and the like to remove obstructions in the lumen. Catheters used for laser angioplasty and other procedures may have a central passageway or tube which receives a guide wire inserted into the body lumen (e.g., vascular system) prior to catheter introduction. The guide wire facilitates the advancement and placement of the catheter to the selected portion(s) of the body lumen for laser ablation of tissue.

Examples of laser catheters or laser sheaths are sold by the Spectranetics Corporation under the tradenames ELCA™ and Turbo Elite™ (each of which is used for coronary intervention or catheterization such as recanalizing occluded

16

arteries, changing lesion morphology, and facilitating stent placement) and SLSIT™ and GlideLight™ (which is used for surgically implanted lead removal). The working (distal) end of a laser catheter typically has a plurality of laser emitters that emit energy and ablate the targeted tissue. The opposite (proximal) end of a laser catheter typically has a fiber optic coupler, which connects to a laser system or generator. One such example of a laser system is the CVX-300 Excimer Laser System, which is also sold by the Spectranetics Corporation.

Referring now to FIGS. 1-2, a distal end of a laser catheter 2 for atherectomy procedures in accordance with one embodiment of the present disclosure is shown. The laser catheter 2 may (as depicted in FIGS. 1 and 2) or may not include a lumen 14. If a lumen 14 is included in the laser catheter 2, a clinician may slide the laser catheter over a guidewire (not shown) through lumen 14. It may, however, be preferable for the catheter to have a separate guidewire lumen located between the inner band and outer jacket. Incorporation of such a guidewire lumen is generally known to one of ordinary skill in the art, and all such guidewire lumens are within the knowledge of one skilled in the art are considered within the scope of this disclosure.

As shown, the catheter 2 comprises an outer jacket 4 or sleeve. The outer jacket 4 comprises a flexible assembly with the ability to resist user-applied forces such as torque, tension, and compression. The proximal end (not shown) of the catheter 2 is attached to a fiber optic coupler (not shown) and includes an outer jacket, inner band and a plurality of optical fibers similar to the configuration and orientation of such components depicted in FIGS. 1 and 2. The distal end 6 of the catheter 2 comprises a tapered outer band 8, which is attached to the distal end of the outer jacket 4, a plurality of optical fibers 10 acting as laser emitters, inner band 12 creating an orifice that provides an entrance to an inner lumen 14 that is connected to an aspiration system discussed in more detail below. The energy emitted by the laser emitters 10 cuts, separates, and/or ablates the scar tissue, plaque build-up, calcium deposits and other types of undesirable lesion or bodily material within the subject's vascular system in a pattern substantially similar to that of the cross sectional configuration of the laser emitters 10.

The cutting means in this embodiment is a laser ablation means that includes laser emitters 10 embedded within a catheter 2 comprising a lumen 14. In this particular embodiment, approximately seventy-four laser emitters 10 are provided in a generally concentric configuration. Also provided substantially concentric with and interior to the laser emitters 10 (and optical fibers) is an inner lumen 14, which provides a potential conduit or passageway for translocation of materials cut or ablated by the laser emitters 10.

As the energy emitted by the laser emitters 10 contacts the undesirable bodily material within the subject's vascular system, it separates and cuts such material in a generally concentric configuration. In other words, one of ordinary skill in the art may refer to this technique as coring. And if the bodily material that is cut is substantially solid, it will appear as generally cylindrically looking core or plug. Although FIGS. 1-2 illustrate the laser emitters 10 in a generally concentric configuration, those skilled in the art will appreciate that there are numerous other ways and configurations in which to arrange a plurality of laser emitters. Additionally, although these two figures illustrate an outer jacket 4 and an inner band 12, those of skill in the art will appreciate that distinct components need not be used, and the optical fibers may be encapsulated within a single sleeve having a lumen. Accordingly, FIGS. 1-2, as well as

17

FIG. 3 discussed below, are not intended to represent the only way that a laser catheter may be configured and constructed, and all such configurations and constructions are within the knowledge of one skilled in the art are considered within the scope of this disclosure.

FIG. 3 is a cross-sectional perspective view of a laser catheter according to one embodiment of the present disclosure. A flexible distal tip 2 is provided, the distal tip 2 comprising a central or inner lumen 14 provided substantially concentric with one or more annular arrays of optical fibers 10 and an outer jacket 4. An inner band 12 is provided at a far distal end of the tip 2. In the depicted embodiment, the inner band 12 has an orifice comprising an internal diameter that is smaller than a minimum internal diameter of the inner lumen 14. The smaller size of orifice of the inner band 12 (either alone or in conjunction with the location and configuration of the laser emitters 10), in comparison to the size of the lumen 14, ensures that the material will have a smaller cross section than that of the lumen 14, thereby reducing the likelihood that the bodily material will become trapped or clogged in the lumen 14 as it is aspirated therethrough. Although FIG. 3 depicts the orifice of the inner band 12 as being less than the minimal internal diameter of the inner lumen 14, the orifice of the inner band 12 may be equal to or greater than the minimal internal diameter of the inner lumen 14.

The inner band 12 comprises a proximal end, a distal end, an interior surface and an exterior surface. When placed within the catheter 2, the distal end of the inner band 12 is substantially aligned or flush with the far distal end of the tip 15. The inner band 12 may be attached to the catheter via numerous means known to one of ordinary skill in the art. For example, the dimension of the exterior diameter (or circumference) of the inner band 12 may be slightly greater than the diameter (or circumference) of the lumen at the distal tip of the catheter such that the inner band is press fit into the distal tip of the catheter 2. Additionally, the inner band 12 may be attached to the lumen by various known adhesives.

The interior surface of the inner band 12 may be straight or tapered. That is the interior diameters of the inner band may be the same or different (e.g., smaller or larger) in comparison to one another. For example, the interior surface of the inner band 12 may be tapered such that the interior diameter at its proximal end is greater than the interior diameter at its distal end.

Upon installation of the inner band 12 into the distal tip of the catheter, the interior surface of the proximal end of the inner band 12 may or may not be aligned or be flush with the surface of the lumen. Regardless of the alignment of the two surfaces, the lumen 14 may include a transition portion that is tapered from the point at which the proximal end of the inner band 12 contacts the lumen until a predetermined point located proximally thereof. The taper may either an increasing or decreasing taper as the lumen transitions proximally of the inner band 12. The tapered portion may also extend distally beyond the proximal end of the inner band 12 and be used to affix the inner band 12 within the catheter. For example, as depicted in FIG. 3, a portion of the inner lumen 14 may comprise a tapered portion 19 to receive and envelope a proximal portion of the inner band 12. The inner band 12 may also provide structural support to the distal end of the catheter, and particularly to the distal ends of the fibers 10, which are surrounded at an outer diameter by a tapered outer band 8.

Outer band 8 is tapered from its proximal end to its distal end 2, thereby facilitating the ease of movement of the

18

catheter within a blood vessel. The outer band 8 abuts outer jacket 4, and in order to further facilitate movement of the catheter within the blood vessel, it may be preferable that the exteriors of the outer band 8 and outer jacket 4 be aligned.

The catheter comprises a flexible distal end 2, the flexible distal end 2 being operable by a user. The position of the distal end is controlled by one or more deflection means 16 which may include, but are not limited to, pullwires, shaping wires, and similar force-transmitting features controlled by a user at a user-proximal location of the device. Actuation of at least one deflection means 16 applies force to the distal tip 2, thus deflecting the distal tip 2 from a longitudinal axis of the remainder of the catheter device. The deflection means allows the clinician to both create a pilot channel and subsequent larger channels, faster than conventional bulk ablation. For example, the clinician initially cuts the bodily material within the vascular system without deflecting the distal end of the catheter. Then, the clinician deflects the distal end of the catheter using the deflection means and subsequently cuts additional bodily material at the same general location within the subject's vascular system, thereby creating a larger channel therethrough in comparison the channel created initially created.

FIGS. 12A & 12B are alternative embodiments of the catheter 2 of the present disclosure. The catheter 2 illustrated in these figures depicts an opening 1204 (or orifice or port) extending through the side of the catheter 2, particularly through the outer jacket 4, as well as plurality of optical fibers 10, to the lumen 14. As discussed elsewhere herein, lumen 14 is in fluid communication with the pulsed aspiration system 17. It may be desirable to block (or close) a portion or all of the opening 1204 during activation of the pulsed aspiration system 17 to control the amount of vacuum pressure or suction from the opening. The embodiment of the catheter 2 depicted in FIGS. 12A & 12B may, therefore, also include an adjustable gate 1208 that covers the opening 1204.

The gate 1208 may slide axially with respect to the longitudinal axis of the catheter 2 to open and/or close the opening 1204. If so, a means of sliding or moving the gate 1208, such as a rod 1212, may be included. Although the gate 1208 is depicted adjacent the catheter wall of the inner lumen 14, the gate 1208 may be located elsewhere within or adjacent the catheter 2, such as interiorly or exteriorly adjacent the jacket 4 or interiorly or exteriorly adjacent the laser emitters 10. It shall also be understood that this disclosure is not limited to a sliding gate 1208 as a means for covering the opening. For example, other means for covering the opening, such as a hinged gate within the opening 1204 may also be used.

FIGS. 12A & 12B depict the opening 1204 extending through the outer jacket 4 and the plurality of optical fibers 10 to the lumen 14. Nevertheless, the opening 1204 may alternatively extend into catheter 2, which may have a second lumen (not shown). That is, the second lumen may be within the wall of the catheter 2. The second lumen may be in fluid communication with either the pulsed aspiration system 17 or a second aspiration system. The second aspiration system can be similar to the pulsed aspiration system 17 or it may be a different aspiration system. For example, the second aspiration system may include a constant or variable speed vacuum pump that is not pulsed but produces a constant suction force that may be further attenuated by the means for covering the opening.

FIG. 4 is a schematic depicting a pulsed aspiration system 17 according to one embodiment of the present disclosure that may be connected to the lumen of the catheter to

19

evacuate the ablated or cored bodily material from a subject's vascular system using various embodiments of a catheter comprising a distal tip having laser cutting means and/or mechanical cutting means. As shown, a vacuum pump **18** is provided, the vacuum pump **18** being interconnected to a pulse width modulator **20** in operative communication with at least one solenoid valve **22**, the actuation of which creates one or more pressure differentials to the aspiration system. Accordingly, rather than creating a constant suction pressure within the lumen of a catheter to evacuate cut and/or ablated bodily material from a subject's vascular system, the aspiration system of the present disclosure applies alternative pressure(s), thereby creating pulses of suction pressure within the lumen. Utilizing a series of constant and/or varying pressure pulses is potentially beneficial in aspirating bodily material, particularly when aspirating larger cylindrically looking core or plug like shapes of bodily material.

A filter **24** is provided upstream of the solenoid valve **22**, the filter **24** provided for filtering debris and aspirated bodily material and also for providing visual feedback to a user related to the type, quantity, and flow rate of material being removed from a patient. Fluid and material is provided to the filter **24** via a catheter **26** interconnected to, for example, an excimer laser system **28** for the treatment of peripheral and coronary arterial disease such as the CVX-300 Excimer Laser System sold by the Spectranetics Corporation.

In various embodiments, a fluid collection jar **21** may also be provided in fluid communications with the vacuum pump **18**. The fluid collection container **21**, such as a jar, comprises one or more known devices for collecting and filtering fluid removed from a patient. The container **21** preferably comprises transparent sidewalls for providing visual feedback to a user regarding flow-rate, content, coloration, etc. Filter means are also provided for removing particulate from liquids. Those of skill in the art will appreciate that various types of fluid collection containers may be used. The fluid collection container **21** and/or filter **24** may also comprise one or more custom filter features with various mesh sizes, capacities, etc. based on the specific application.

Pulse width modulator(s) **20** of the present disclosure provides for automatic control and varied application of vacuum pressure to the remainder of the aspiration system, including features and devices of an excimer laser system **28** provided in communication with the aspiration system **17**. It will be recognized that where an excimer laser system **28** is provided for cutting and ablating debris and particulate from a blood vessel of a patient, efficient removal of such debris is still required. The present disclosure provides an aspiration system **17** for use with an excimer laser cutting system **28** wherein blood and debris may be aspirated or removed in a pulsed fashion, thereby minimizing the amount of clean or healthy blood that is unnecessarily removed from a patient.

A pulse width modulator **20** is provided as a control means for controlling the opening and closing of at least one solenoid valve **22**, the solenoid valve **22** provided for selective application and segregation of a vacuum pressure provided by the vacuum pump **18** from the remainder of a system. Controlling the frequency and duty cycle at which the solenoid valve **22** opens and closes influences the pulse pattern, such as the pulse frequency, the pulse width, the pulse pressure, the rate at which the pulse pressure increases and/or decreases, etc. The settings for the pulse width modulator **20** may be manually adjusted by a user to provide a desired pulse pattern or the settings may be automatically adjusted by parameters stored within computer-readable medium controlled by a CPU. For example, during portions

20

of a procedure where relatively little particulate is being ablated or cut from a patient's vascular system, the pulse width modulator **20** may be manipulated such that applications of vacuum forces are relatively far apart, thus removing a minimal amount of blood and fluid from a patient when such removal is not necessary. Alternatively, where significant amounts of particulate are being ablated and removed from a patient, the pulse width modulator may be manipulated or programmed to provide frequent constant and/or varying vacuum pulses and remove greater amounts of fluid from the patient.

The filter **24** preferably comprises a transparent device such that a user is provided with some level of visual feedback as to how much plaque or particulate is being removed from a patient. Based on this feedback, for example, a user can selectively manipulate the settings of the pulse width modulator **20** to alter the overall flow rate of material from a patient. In various embodiments, the pulse width modulator **20** and/or solenoid valve **22** settings are controlled by a foot pedal, hand switch, or similar user-actuable device.

The filter **24**, vacuum pump **18**, flow sensor(s) (not shown) and/or pressure sensor(s) (not shown) may output signals that are transmitted to the CPU controlling the pulse width modulator **20**. The computer-readable medium may include an algorithm, which receives the output signals and instructs the CPU how to adjust the parameters at which the solenoid valve opens and closes.

An interface circuit **31** may also be provided for communication with the pulse-width modulator **20**. The interface circuit is provided to communicate with, for example, the excimer laser system **28**. The computer readable medium and CPU discussed above may be located in the excimer laser system **28**. In addition to controlling the solenoid valve, the excimer laser system may also provide for a clogged aspiration detection system and control for a conduit-clearing mode based on various additional system parameters, including laser cutting operations.

FIG. **5** is a perspective view of a distal tip **30** of a catheter according to one embodiment of the present disclosure. FIG. **6** is a side elevation view thereof. FIG. **7** is a front elevation view thereof. As shown, the distal tip **30** comprises a combination of a mechanical cutting means and a laser ablation means. Mechanical cutting means of FIGS. **5-7** includes a sharp cutting edge or blade **32** that may be parallel to the longitudinal axis of the catheter or its lumen. Laser ablation means of the depicted embodiments comprise an extending spiral or helix-type array of laser emitters provided in an approximate 360 degree pattern about the longitudinal axis of the catheter and its lumen. The helical array comprises a first terminus **38** at a proximal end of the cutting edge **32** and a second terminus **36** at a distal end of the cutting edge **32**. Provided interior to the helical array is an inner lumen **40** through which material dislodged or ablated by the mechanical cutting feature and/or the laser emitters **34** is removed from a patient.

In various embodiments, the inner lumen **40** comprises a lumen of substantially circular cross-section with an internal diameter of between approximately 0.050 inches and 0.10 inches. In certain embodiments, the inner lumen comprises a lumen of substantially circular cross-section with an internal diameter of between approximately 0.060 inches and 0.090 inches. In a preferred embodiment, the inner lumen comprises a lumen of substantially circular cross-section with an internal diameter of approximately 0.072 inches. In various embodiments, the distal tip **30** comprises an outer diameter of between approximately 0.080 and 0.10

21

inches. In preferred embodiments, the distal tip comprises an external diameter of approximately 0.090 inches.

It will be recognized that distal tips **30** of the present disclosure may be provided with any number of laser emitters. However, in a particular embodiment, a distal tip is provided that comprises 50 optical fibers capable of transmitting light of approximately 130  $\mu$ m wavelength.

The cutting edge or blade of the present disclosure may be constructed of, for example, stainless steels, abrasive materials, diamond tip, etc.

The present disclosure further contemplates that various features of FIGS. 5-7 may be inverted. Referring to FIG. 8, for example, there is depicted in one embodiment, the laser emitters **808** along surface **804** that may be substantially parallel to the longitudinal axis of the catheter. Also included in this embodiment of the distal portion of the catheter is a sharp cutting edge **812** or blade provided in a spiral or helical configuration as it extends from the proximal end **816** of the surface **804** to the distal end **820** of surface **804**.

Various distal tip designs are contemplated by the present disclosure. Although particular embodiments are shown and described herein, the present disclosure is not so limited. Features of the present disclosure may be provided in combination with various catheter distal end designs. For example, the configuration of the laser emitters **34** of FIGS. 5-7 may be arranged such that they extend spirally or helically but in a pattern less than 360 degrees. Similarly, the sharp cutting edge or blade **32** in FIGS. 5-7 may be at an angle or offset from the longitudinal axis of the catheter or its lumen.

Catheter distal tips of the present disclosure include, but are not limited to, purely mechanical cutting devices provided in: circular, off-set, and semi-circular arrangements; various combinations of mechanical and laser-ablative cutting systems; and purely laser-ablative cutting systems. For example, FIGS. 5-8 include tips capable of applying laser energy and/or mechanical force (or pressure) to core through lesion material and create plug-type objects that can be aspirated through the catheter in their entirety. However, certain aspects of this disclosure may be beneficial to various mechanical and/or other types of macerating type devices and catheter tips. For example, FIGS. 9 and 10 illustrate mechanical tips that may be used to cut and/or macerate lesion-type tissue that may be capable of being aspirated in the manner discussed within this disclosure.

Referring to FIGS. 9A & 9B, there is depicted a catheter **900** having a tip **904** having a cutting blade with a plurality of sharp vanes **908** capable of cutting and/or macerating lesion tissue. FIG. 9A illustrates the cutting blade in a retracted position so that the catheter can navigate the subject's vasculature with minimal or no exposure of the vanes **908**. FIG. 9B illustrates the cutting blade in the extended position. As the cutting blade extends, the vanes **908** extend and rotate, thereby cutting and/or macerating the tissue with which the vanes **908** contact. Additionally, as the vanes **908** are extending and retracting, the pulsed aspiration system (previously discussed) can aspirate the cut and macerated tissue through the openings **912** between the vanes **908**, the lumen **916** within the center of the blades and/or both. Furthermore, depending upon the internal configuration of the catheter and the channels to the openings **912** and lumen **916**, one or more aspiration systems may be used in conjunction with the catheter.

Depending upon its use, the catheter may have differently shaped cutting blades and vanes. For example, if it is desirable to use a catheter for lead extraction, it may be preferable that the size of the lumen be increased, such as illustrated in FIGS. 10A-10B, thereby altering the size and

22

configuration of the blades. Similar to FIGS. 9A and 9B, FIGS. 10A and 10B depict a catheter **1000** having a tip **1004** having a cutting blade with a plurality of sharp vanes **1008** capable of cutting and/or macerating lesion tissue. However, in comparison to FIGS. 9A and 9B, FIGS. 10A and 10B have a larger lumen **1016** and larger openings **1012** between the vanes **1008** because there are fewer vanes. Although these two figures illustrate two types of cutting blades that can be used in conjunction with the aspiration system(s) discussed in this disclosure, those of skill in the art will appreciate that other configurations and types of cutting blades may be used in cooperation therewith. Accordingly, FIGS. 9-10 are not intended to represent the only ways that a mechanical, cutting-type catheter may be configured and constructed, and all such configurations and constructions are within the knowledge of one skilled in the art are considered within the scope of this disclosure.

FIG. 11A is a cross-sectional elevation view of one embodiment of a catheter **50** comprising an outer surface **52** and an inner surface **54**. The inner surface **54** of the catheter **50** may comprise a helical structure **56** extending from its distal to its proximal ends either continuously or for portions thereof. The helical structure **56** may comprise a polymer extrusion or metal insert extending radially inwardly from an inner diameter of the inner surface **54** and along a length of the catheter **50** in a helical or spiral manner. Alternatively, however, the helical structure **56** is provided as a recessed feature along the internal surface **54** of the catheter **50**. As the lesion material, either in the form of a plug or in macerated form enters the lumen formed by the inner surface **54**, the helical structure **56** facilitates the spinning of the material within the lumen as it is aspirated, thereby potentially reducing the potential for clogging. Additionally, the helical structure **56** may also macerate or further macerate the material, thereby potentially aiding and/or increasing the material's unimpeded travel from the distal to the proximal end.

A portion of a catheter **50** is depicted in FIGS. 11A-11B and no limitation with respect to which portion or specific length is provided or implied. FIGS. 11A-11B are provided to depict the feature of the helical structure **56** along an internal surface of the catheter **50**. Such a structure **56** may be provided along any length of the catheter, including a distal end of the catheter. Additionally, although not depicted in FIGS. 11A-11B, various additional features as shown and described herein may be provided in combination with the features of FIGS. 11A-11B. For example, the catheter **50** may further comprise distal end cutting features such as laser ablative means and/or mechanical as shown and described herein. Additionally, vacuum pulsing and detection systems as shown and described may be provided in combination with the catheter **50**. It will be recognized that the helical structure **56** depicted in FIGS. 11A-11B comprises a feature that may be integrated with or provided in combination with various features shown and described herein.

It will be recognized that the helical structure **56** of the catheter **50** generally comprises an internal threaded feature. The helical structure **56** may comprise various different thread characteristics, including overall length, pitch, diameter, etc. Preferably, however, the pitch and ramp angle of the helical structure **56** is shallow enough to effectively ablate occlusions within a blood vessel.

A number of variations and modifications of the disclosure can be used. It would be possible to provide for some features of the disclosure without providing others.

23

The present disclosure, in various aspects, embodiments, and configurations, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various aspects, embodiments, configurations, subcombinations, and subsets thereof. Those of skill in the art will understand how to make and use the various aspects, aspects, embodiments, and configurations, after understanding the present disclosure. The present disclosure, in various aspects, embodiments, and configurations, includes providing devices and processes in the absence of items not depicted and/or described herein or in various aspects, embodiments, and configurations hereof, including in the absence of such items as may have been used in previous devices or processes, e.g., for improving performance, achieving ease and/or reducing cost of implementation.

The foregoing discussion of the disclosure has been presented for purposes of illustration and description. The foregoing is not intended to limit the disclosure to the form or forms disclosed herein. In the foregoing Detailed Description for example, various features of the disclosure are grouped together in one or more, aspects, embodiments, and configurations for the purpose of streamlining the disclosure. The features of the aspects, embodiments, and configurations of the disclosure may be combined in alternate aspects, embodiments, and configurations other than those discussed above. This method of disclosure is not to be interpreted as reflecting an intention that the claimed disclosure requires more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed aspects, embodiments, and configurations. Thus, the following claims are hereby incorporated into this Detailed Description, with each claim standing on its own as a separate preferred embodiment of the disclosure.

Moreover, though the description of the disclosure has included description of one or more aspects, embodiments, or configurations and certain variations and modifications, other variations, combinations, and modifications are within the scope of the disclosure, e.g., as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It is intended to obtain rights which include alternative aspects, embodiments, and configurations to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

What is claimed is:

1. A catheter aspiration system comprising:

a catheter having a tubular wall, the tubular wall comprising:

a distal end;

an orifice for an inner lumen extending proximally from the distal end of the catheter; and

an opening in the tubular wall, wherein the opening is disposed in the exterior proximal of the distal end of the catheter;

a plurality of optical fibers located within the tubular wall and exposed at the distal end of the catheter, wherein the plurality of optical fibers comprise corresponding distal ends, wherein the distal ends of the plurality of optical fibers are disposed distally of the opening in the tubular wall;

24

a vacuum pump in fluid communication with the inner lumen and operable to transmit material proximally through the inner lumen; and

an adjustable gate being movable to selectively cover at least a portion of the opening.

2. The catheter aspiration system of claim 1, wherein the opening in the tubular wall extends to the inner lumen.

3. The catheter aspiration system of claim 2, wherein the adjustable gate is disposed within the inner lumen.

4. The catheter aspiration system of claim 1, wherein the catheter further comprises a second lumen extending toward the proximal end, wherein the opening is coupled to the second lumen.

5. The catheter aspiration system of claim 4, wherein the inner lumen and the second lumen are coupled to the vacuum pump.

6. The catheter aspiration system of claim 4, further comprising a second vacuum pump coupled to the second lumen.

7. The catheter aspiration system of claim 1, further comprising:

a valve assembly in communication with the vacuum pump, the valve assembly having an open position and closed position; and

a controller for alternating the position of the valve assembly between the open position and the closed position.

8. The catheter aspiration system of claim 7, wherein the valve assembly comprises a solenoid valve.

9. The catheter aspiration system of claim 7, wherein controller comprises a pulse width modulator.

10. The catheter aspiration system of claim 1, wherein the plurality of optical fibers exposed at the distal end of the catheter are configured in an extending helical configuration.

11. The catheter aspiration system of claim 1, further comprising:

clogging detection means which detects clogging in at least one of the aspiration catheter and an aspiration tube during an aspiration operation, the clogging detection means comprising at least one of pressure sensor and a flow meter for sensing at least one a pressure differential and a flow differential with respect to preferred operating conditions; and

clogging alert means comprising at least one of an audio and a visual indicia when the clogging detection means detects clogging based on the at least one of a pressure differential and a flow differential with respect to preferred operating conditions.

12. The catheter aspiration system of claim 11, wherein the distal end of the catheter further comprises a sharp cutting surface.

13. The catheter aspiration system of claim 12, wherein the sharp cutting surface is aligned with a longitudinal axis of the catheter.

14. The catheter aspiration system of claim 1, wherein the plurality of optical fibers exposed at the distal end are aligned with a longitudinal axis of the catheter.

15. The catheter aspiration system of claim 14, wherein the distal end of the catheter further comprises a sharp cutting surface.

16. The catheter aspiration system of claim 15, wherein the sharp cutting surface is configured in an extending helical configuration.

17. The catheter aspiration system of claim 1, further comprising a means for moving the adjustable gate.

18. The catheter aspiration system of claim 17, wherein the means for moving the adjustable gate is a rod.

25

19. The catheter aspiration system of claim 1, wherein the adjustable gate is slidable relative to the tubular wall of the catheter to selectively cover at least a portion of the opening.

20. A catheter aspiration system comprising:

a catheter having a tubular wall, the tubular wall comprising:

a distal end;

an orifice for an inner lumen extending proximally from the distal end;

an opening in the tubular wall, wherein the opening is disposed in the exterior proximal of the distal end;

a plurality of optical fibers located within the tubular wall and exposed at the distal end of the catheter;

a vacuum pump in fluid communication with the inner lumen; and

an adjustable gate being movable to selectively cover at least a portion of the opening, wherein the adjustable gate is hingedly movable relative to the tubular wall of the catheter to selectively cover at least a portion of the opening.

20

\* \* \* \* \*

26