

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2010366517 B2**

(54) Title
Ink jet printing method

(51) International Patent Classification(s)
G06K 15/10 (2006.01) **H04N 1/60** (2006.01)

(21) Application No: **2010366517** (22) Date of Filing: **2010.12.30**

(87) WIPO No: **WO12/090231**

(43) Publication Date: **2012.07.05**

(44) Accepted Journal Date: **2016.05.12**

(71) Applicant(s)
SICPA HOLDING SA

(72) Inventor(s)
Cattarinussi, Serge;Dimitrijevic, Ana;Regamey, Yves-Julien

(74) Agent / Attorney
Shelston IP Pty Ltd., L 21 60 Margaret St, Sydney, NSW, 2000

(56) Related Art
US 2005/0219278

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2012/090231 A1

(43) International Publication Date
5 July 2012 (05.07.2012)

(51) International Patent Classification:
G06K 15/10 (2006.01) **H04N 1/60** (2006.01)

(21) International Application Number:
PCT/IT2010/000519

(22) International Filing Date:
30 December 2010 (30.12.2010)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **OLIVETTI SpA** [IT/IT]; Via Jervis, 77, I-10015 Ivrea (TO) (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CATTARINUSI, Serge** [IT/CH]; c/o Olivetti Engineering S.A., Avenue des Sports 28, CH-1401 Yverdon-Les-Bains (CH). **DMITRIJEVIC, Ana** [RS/CH]; c/o Olivetti Engineering S.A., Avenue des Sports 28, CH-1401 Yverdon-Les-Bains (CH). **REGAMEY, Yves-Julien** [CH/CH]; c/o Olivetti Engineering S.A., Avenue des Sports 28, CH-1401 Yverdon-Les-Bains (CH).

(74) Agents: **ROBBA, Eugenio** et al.; Interpatent S.r.l., Via Caboto, 35, I-10129 Torino (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BF, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: INK JET PRINTING METHOD




Fig. 3

(57) Abstract: Present invention relates to an ink jet printing method implemented in a computer system comprising the steps of providing an ensemble of dots to be printed, running through the ensemble of the dots to be printed, deleting, for each dot of the ensemble of the dots, all the neighbouring dots whose distance is less than at least one predetermined value (Dmin) and keep non deleted dots as remaining dots, assigning the remaining dots to a certain layer corresponding to the run, removing the remaining dots from the ensemble of the dots, and starting again at the running step for a further run if there are further dots in the ensemble of the dots or stop so as to have all dots assigned to printing layers corresponding to the number of runs done.

WO 2012/090231 A1

WO 2012/090231 A1



Published:

— with international search report (Art. 21(3))

Ink jet printing method

Technical Field

The present invention relates, in general, to an ink jet printing method suitable for printing text or images on a media. In particular, the present invention relates to an ink jet printing method suitable for printing texts or images on plastic cards, as for instance credit cards, bank cards, etc.

Background Art


Any discussion of the prior art throughout the specification should in no way be considered as an admission that such prior art is widely known or forms part of common general knowledge in the field.

A complete printing process, starting for instance from an image displayed on a screen (source image), requires that a computer or a micro-processor duly programmed performs a plurality of conversion steps in order to obtain, starting from an additive primary colours image or RGB (Red, Green, Blue) image, a corresponding subtractive primary colours image or CMYK (Cyan, Magenta, Yellow, Key black) image suitable to be printed by using ink dots.

The conversion steps, as for instance disclosed in Patent Publication WO2009/031165 in the name of the Applicant, comprise, for example:

- a calibration process wherein a weight is assigned to each point of the source image and a corresponding set of subtractive colours image is generated;
- a halftoning process wherein subtractive colours are arranged in order to obtain on the printed media an optical effect similar to that visible on the screen;
- a printing process wherein, according to the result of the halftoning process and a certain printing strategy, CMY and, optionally, K dots are ejected by a print head on a printable media.

The printing process and in particular the printing strategy (shingling strategy), in general, requires that the computer duly programmed avoids coalescence, in particular in



cases where plastic cards need to be printed by using ink jet printing, because drying time of dots is very long.

As known, when ink dot are ejected on a media, a problem of coalescence may exist if not dried dots (dots) superimpose on each other.

Coalescence problem, in general, may be due to two different superimposing situations or problems:

- adjacent dots superimpose during print head dots ejection; in other words the problem can happen if the print head ejects superimposing dots during a carriage pass (a carriage pass is defined as a single travel of the print head from one edge of the media to the other);
- dots ejected in a pass following a previous pass superimpose previous dots before drying thereof.

According to known prior art the first coalescence problem is solved through a shingling strategy based on a raster grid, where each pixel (and therefore the dot deposited on that pixel) is assigned to various layers so as to avoid coalescence; according to present disclosure the term layer is assumed to represent an image that is printed with several non overlapping print swaths or passes.

For instance, Fig. 1 shows a two layer shingling strategy or procedure where the dots on a grey square or pixel are printed in a first layer and those on a white square are printed in a second layer so that coalescence is avoided.

In practical cases the above strategy requires, for instance, that:

- assuming that dots of each layer must have a certain minimum distance, for instance $D_{\min} = 84 \mu\text{m}$;
- assuming that printer is using an asymmetric printing resolution of $600_{\text{vert}} \times 1200_{\text{horiz}}$ dots per inch (dpi) whereby a rectangular pixel is defined having dimensions of $42_{\text{vert}} \times 21_{\text{horiz}} \mu\text{m}$ as shown in Fig. 2a;

an eight layer shingling strategy will be optimal to obtain full coverage because all dots will be printed at exactly 84 μm from each other.

In other words the eight layer shingling strategy is optimal
5 for obtaining a full coverage but may not be optimal in cases where:

- full coverage is not a necessity in order to reach colour saturation; or

- print time is an issue and the number of layers needs to be
10 reduced by using a coverage lower than full coverage.

For instance, assuming that $6/8^{\text{th}}$ of the full coverage could be enough, one could expect 6 layers to be sufficient in order to avoid coalescence. But it is apparent that by using the prior art strategy with 6 layers instead of 8, the
15 required distance between dots (Fig. 2b) will not be enforced and the first coalescence problem will appear. To be more precise, we consider Fig. 2a and 2b which both exemplify prior art shingling strategy when printing at a resolution of $600_{\text{vert}} \times 1200_{\text{horiz}}$ dots per inch, using 8 and 6 shingling
20 passes, respectively. In both cases, the pixel raster grid is represented and pixels are numbered according to the pass to which they belong to. Meaning that dots falling on pixels numbered with 1 are printed on the first shingling pass, pixels numbered with 2 are printed on the second pass, and so
25 on. Considering that, at a resolution of $600_{\text{vert}} \times 1200_{\text{horiz}}$ dots per inch, the pixel size is $42_{\text{vert}} \times 21_{\text{horiz}} \mu\text{m}$, and considering also that $6/8$ of all pixels will be occupied by a dot in a pseudo random way, it becomes evident that :

- on Fig. 2a, the prior art 8 passes shingling strategy
30 always enforce the required coalescence distance of 84 μm .
- on Fig. 2b, the prior art 6 passes shingling strategy only does enforce a distance of 63 μm which does not prevent coalescence.

In summary, Applicant has noted, in general, that known prior art does not optimally solve the first coalescence problem. "Optimally" means that, in order to avoid the first coalescence problem, the classic shingling strategy needs a number of layers larger than due.

Applicant has noted, moreover, that the first coalescence problem is an issue in cases where plastic cards need to be printed.

Disclosure of the Invention

It is an object of the present invention to overcome or ameliorate at least one of the disadvantages of the prior art, or to provide a useful alternative.

At least one embodiment of the present invention provides a solution to the first coalescence problem as outlined above.

According to embodiments of the present invention, there is provided an ink jet printing method having the features set forth in the claims that follow.

One embodiment provides an ink jet printing method comprising the step of

- providing an ensemble of dots to be printed;

wherein the method comprises:

Step-1: run through the ensemble of the dots to be printed;

Step-2: for each dot of the ensemble of the dots delete all the neighbouring dots whose distance is less than at least one predetermined value (D_{min}) and keep non deleted dots as remaining dots;

Step-3: assign the remaining dots to a certain layer corresponding to the run;

Step-4 remove the remaining dots from the ensemble of the dots;

Step-5 start again at step-1, for a further run if there are further dots in the ensemble of the dots or stop.

One embodiment provides an ink jet printing method, comprising:

providing an ensemble of dots to be printed;

performing a current run through the ensemble of the dots to be printed, including:

for each dot of the ensemble of the dots, deleting all neighbouring dots from the current run having a distance less than at least one predetermined value and keeping non-deleted dots as remaining dots in the current run;

assigning the remaining dots to a certain layer corresponding to the current run;

removing the remaining dots of the current run from the ensemble of the dots; and

repeating the performing step for a further run until there are no further dots in the ensemble of the dots.

The present invention also relates to a computer program product loadable in the memory of at least one computer unit and including software code portions for performing the steps of the method of the invention when the product is run on at least one computer unit.

Claims are an integral part of the teaching of the present invention.

According to a feature of a preferred embodiment of the present invention the ink jet printing method provides a shingling strategy wherein, starting from an ensemble of dots of an image, printing layers are built by inserting in each printing layer dots by checking the distance between each dot of the ensemble of dots and its neighbouring dots.

According to a further feature of the present invention enhancements to the general shingling process are provided for taking into account distances between dots made of more than one drop.

According to another feature of the present invention enhancements to the general shingling process are provided for including black dots into the ensemble of the dots and for

forcing printing of the black dots by using C, M, Y drops on the same position.

Again according to a further feature of the present invention enhancements to the general shingling process are provided for reducing the number of layers generated by the general shingling process.

Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise", "comprising", and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in the sense of "including, but not limited to".

Brief Description of Drawings

These and further features and advantages of the present invention will appear more clearly from the following detailed description of preferred embodiments, provided by way of non-limiting examples with reference to the attached drawings, in which components designated by same or similar reference numerals indicate components having same or similar functionality and construction and wherein:

Fig. 1 is a representation of a prior art or classical 2 layers shingling based on raster grid strategy;

Fig. 2a and Fig. 2b are a representation of eight and six layers classical shingling strategy;

Fig. 3 shows a distance evaluation map where distance between each dot and its neighbours is checked;

Fig. 4a, 4b and 4c show examples of deletion masks provided according to the present invention;


Fig. 5 shows an example of black transfer coefficient applicable for enhancing the shingling process of the present invention;

Fig. 6a and 6b shows an example of a further process for enhancing the shingling process of the present invention;

Fig. 7 shows a statistical analysis of the results obtained by applying the shingling process according to the present invention, compared with the classic shingling method.

Best mode for Carrying Out the Invention

With reference to Fig. 3 an approach is shown wherein the distance between each dot (10) and its neighbouring dots



(10) is checked in order to decide on which shingling layer they should be printed.

For instance, starting from the practical case or example already described, by using a printing strategy based on dot distances the number of shingling layers required to avoid dot coalescence depends on:

A) The minimum dot distance D_{\min} ;

B) The number of dots and their spatial distribution;

C) The printing resolution, that according to the exemplary embodiment is $600_{\text{vert}} \times 1200_{\text{horiz}}$ DPI; however printing resolution is a parameter only required because dots must take discrete positions on the media;

D) The ability to optimally dispatch the dots among a given number of layers by using optimisation processes.

Before proceeding with a disclosure of the shingling process according to the present invention, it is important to emphasize that dispatching the dots among printing layers is a typical optimisation problem to be solved by a minimisation procedure in a highly dimensional space.

Any other method must be considered as an approximation. Because the above optimisation requires a huge amount of computing resources, such an optimisation will not be considered in the following.

As a matter of fact, such an approach is considered unpractical.

Instead, an approximated solution is considered practical.

The present invention discloses a shingling process that uses a kind of digital sieve which is briefly summarised here and comprises, in general, the steps that follows.

As easily comprehensible such steps of the shingling process are implemented in a computer or a micro-processor, in general installed in a printer, and comprise, in a basic embodiment:

Step-1: Run through the ensemble of all the dots to be printed;

Step-2: For each dot of the ensemble of all the dots, delete all the neighbouring dots whose distance is less than D_{\min} (the minimum distance which does not produce coalescence) and place them in a new ensemble of dots. The removed dots are not visited anymore in the current run;

Step-3 At the end of the current run, assign the remaining dots to a layer (current layer) corresponding to the current run;

Step-4 Remove the dots of the current layer from the ensemble of all the dots and start again at step-1, for a further run;

Step-5 Do as many runs as needed to have all dots assigned to printing layers corresponding to the runs done;

The above general process discloses a first embodiment of the present invention.

In order to enhance the general shingling process, some improvements have been introduced.

The improvements, alone or in combination are apt to enhance efficiency of the general shingling process of present invention by:

1 - taking into account the fact that a pixel can be occupied by up to three drops, thus progressively enlarging the size of the dots and their minimum coalescence distance;

2 - making the shingling process more efficient by grouping dots on the pixels;

3 - equilibrating the population of the printing layers so as to limit the printing layers, if required.

1 - First enhancement

As known, when more than one drop is deposited on a same pixel position (usually two or three drops of different colours), usual when printing on plastic cards, the resulting dot located on the pixel position has a larger diameter than the dot produced by a single drop.

As a consequence, the minimum distance which does not produce coalescence must be increased accordingly.

The minimum dot distance D_{\min} must then be replaced by a symmetric distance matrix

5

$$D_{\min} = \begin{matrix} & \delta_{11} & \delta_{12} & \delta_{13} \\ \delta_{21} & & \delta_{22} & \delta_{23} \\ \delta_{31} & \delta_{32} & & \delta_{33} \end{matrix}$$

10

using

i as a row index;

and

j as a column index;

the matrix is symmetrical, i.e. $\delta_{ij} = \delta_{ji}$; and

15

δ_{ij} is the required distance between a dot formed with i drops and a dot formed with j drops.

A simple change in the form and application of the general process for generating printing layers by using a deletion masks as provided in Step-2 of the basic smart shingling process can account for the size of both interacting dots.

20

As shown in Figg. 4a, 4b and 4c the structure of the deletion masks changes as a function of the number of drops required in each dot of an image to be printed.

25

For instance, to perform a deletion around a dot formed by 2 drops, the deletion mask of Fig. 4b must be centred on said 2 drops dot. Then, said deletion mask deletes all neighbouring dots formed by 3 drops and falling within a distance δ_{23} , all neighbouring dots formed by 2 or 3 drops and falling within a distance δ_{22} , and all neighbouring dots formed by 1, 2 or 3 drops and falling within a distance δ_{21} .

30

A corresponding process applies, , to the deletion mask of Fig. 4a and Fig. 4c, applied around dots formed by 1 and 3 drops, respectively.

In practical cases, Applicant has noted that in order to have both a limited number of distances to take into account and a good approximation, it is enough to estimate the distances by using a simplified distance matrix wherein:

5

D_{\min} (approx)	δ_{11}	δ_{22}	δ_{33}
	δ_{22}	δ_{22}	δ_{33}
	δ_{33}	δ_{33}	δ_{33}

10 In summary, the general shingling process may be applied by introducing an approximated deletion mask, without departing from the process in general terms and without introducing visible errors in the printing process as verified by the Applicant.

15 For instance, by applying the example already used for commenting the prior art, the result is that the approximated distance matrix comprises the following values (in μm) according to empirical measurements made by the Applicant.

20 D_{\min} (approx)	84	93	105
	93	93	105
	105	105	105

Therefore, assuming, according to the practical example, that the deletion mask needs in Step-2 to be applied to each dot of the ensemble of an image as resulting after an halftoning process, the image comprises:

- a 2D matrix whose elements are p_{ij} ;
- indices i and j give the dot position in the image; and
- the value of each element of the image can be:

30 $p_{ij} = 0, p_{ij} = 1, p_{ij} = 2, \text{ or } p_{ij} = 3$

as a function of the number of drops forming the dot at position (i, j) .

Considering that, according to the example, the printer resolution is 600×1200 dpi, the pixel size is $42\mu\text{m} \times 21\mu\text{m}$,

and the deletion masks are constructed by using the values in the distance matrix

D_{\min} (approx), said deletion masks take the form :

5 Del¹ =
 4 4 4 4 3 3 3 3 3 4 4 4 4
 4 3 3 3 2 2 2 2 2 3 3 3 4
 3 3 2 1 1 1 1 1 1 1 2 3 3
 3 3 2 1 1 1 4 1 1 1 2 3 3
 10 3 3 2 1 1 1 1 1 1 1 2 3 3
 4 3 3 3 2 2 2 2 2 3 3 3 4
 4 4 4 4 3 3 3 3 3 4 4 4 4

which is a practical form of the mask in Fig 4a

15 Del² =
 4 4 4 4 3 3 3 3 3 4 4 4 4
 4 3 3 3 1 1 1 1 1 3 3 3 4
 3 3 1 1 1 1 1 1 1 1 1 3 3
 3 3 1 1 1 1 4 1 1 1 1 3 3
 20 3 3 1 1 1 1 1 1 1 1 1 3 3
 4 3 3 3 1 1 1 1 1 3 3 3 4
 4 4 4 4 3 3 3 3 3 4 4 4 4

which is a practical form of the mask in Fig 4b

25 Del³ =
 4 4 4 4 1 1 1 1 1 4 4 4 4
 4 1 1 1 1 1 1 1 1 1 1 1 4
 1 1 1 1 1 1 1 1 1 1 1 1 1
 1 1 1 1 1 1 4 1 1 1 1 1 1
 30 1 1 1 1 1 1 1 1 1 1 1 1 1
 4 1 1 1 1 1 1 1 1 1 1 1 4
 4 4 4 4 1 1 1 1 1 4 4 4 4

which is a practical form of the mask in Fig 4c

- Wherein the central element of the deletion mask is placed on the dot p_{ij} ; and
- 1 means no dots can be accepted in that location;
- 2 means only a dot made of 1 drop can be accepted in that location;
- 3 means only a dot made of 1 or 2 drops can be accepted in that location;
- 4 means only a dot made of 1, 2 or 3 drops can be accepted in that location (i.e. any dot is accepted in a practical case).

I.e., by using a mathematical expression, when $p_{ij} = n$, deletion is provided if:

$$p_{i+k,j-1} \geq Del_{k,1}^n$$

wherein indices k and l span the deletion mask.

For instance, the deletion mask provides that, by centering the mask Del^2 on an image dot formed by 2 drops, at position (i,j) , the dots that can be inserted in the current layer, in positions wherein the deletion mask Del^2 has a value of 3, are dots made of 1 or 2 drops, and the dots that can be inserted in the current layer, in positions wherein the deletion mask Del^2 has a value of 4, are dots made of 1, 2 or 3 drops.

The above example application corresponds to the approximated distance matrix $D_{min (approx)}$, but it can be readily extended to the more general distance matrix D_{min} .

The first enhancement provides the feature of optimizing printing process when halftoning process is arranged to provide dots comprising more than one drop.

2 - Second enhancement

A further enhancement to the shingling process according to the present invention requires, for instance, to reduce the number and the density of dots by providing (favoring) dots having more than one drop on pixels.

A simple solution to this requirement consist in adapting calibration process and/or halftoning process so as to use black ink even if black ink is not physically available in the printer.

5 According to this enhancement it is provided that the logical set of inks becomes C M Y K and that a recipe which replaces some C M Y triplets by one K drop be given.

According to the preferred embodiment of present invention a known recipe is used, referred to as UCR (Under Color
10 Removal), that operates at the color calibration level and includes the following steps:

(I) Start from the C M Y color specification and find the minimum of the three value: $U = \min(C, M, Y)$. This value represent the gray component of the color C M Y. This gray
15 component U could be rendered using black (K) ink.

(II) Define a black transfer coefficient $\alpha = T(U)$ as a function of U as shown, for instance, in Fig. 5. The definition of a black transfer coefficient is useful because rendering the totality of the gray component with black ink
20 produces very grainy prints in the light gray areas and conversely, dark gray areas benefit from the large light absorption of the K inks.

(III) Calculate the new C M Y K components wherein:

$$U = \min(C, M, Y)$$

25
$$\alpha = T(U)$$

$$K = \alpha \cdot U$$

$$C' = C - K$$

$$M' = M - K$$

$$Y' = Y - K$$

30 wherein a value $\alpha = 1$ means that the totality of the gray component is rendered using black K ink.

Therefore, according to the second enhancement, even if there is no black K ink available, for instance the UCR procedure can be used to produce K dots which can be printed

using three overlapping C,M,Y drops. The net result being that some C, M, and Y dots potentially placed on neighboring pixels are forced to be on the same pixel .

In other words, the data to be sent to the printer, including the halftoning process, is prepared as if there was a K ink component, using, preferably, a suitably tuned UCR procedure and, then, as a last step, every K drop is replaced by three C, M, and Y overlapping drops.

3 - Third enhancement

A third enhancement to the shingling process according to the present invention is directed to optimize the population of the printing layers in order to limit the number of printing layers.

The shingling process according to present invention, theoretically may occupy pixels in a large number of layers, as shown in Fig. 6a curve A.

Clearly, if a large number of low populated layers is produced a corresponding large number of printing passes need to be provided.

According to one of the possible enhancements of the shingling process according to present invention, a procedure is proposed, herein referred to as refolding, which redistribute the dots assigned to low populated layers on the previous more populated ones.

As shown in Fig 6b the refolding procedure provides the following steps:

- Firstly, the maximum number of layers, L_{max} , is fixed;
- Secondly, all the dots assigned to a layer $L_i > L_{max}$ will be redistributed (refolded) among the layers $L_j \leq L_{max}$.

According to the preferred embodiment, the position (i, j) of the dots is not changed. For each « refolded » dot, a specific layer L_j is chosen according to its interaction energy E_j with its neighbors on L_j .

Preferably, the energy E_j can be any decreasing monotonous function of the distances between the "refolded" dot (i, j) and its neighbors on layer L_j .

By applying the refolding procedure, as disclosed, it is possible to obtain a limited number of layers as shown in Fig. 6a, curve B.

It must be understood that the refolding procedure necessarily produce some violation of the minimum dot distances and, therefore, may provide some coalescence conflict.

However, Applicant has demonstrated that the shingling process according to the present invention enhanced with the refolding procedure gives better results than the known shingling process, in particular when a limited number of layers is required.

As a matter of fact Applicant has noted that, by using, for instance, the $6/8^{\text{th}}$ of the full coverage as in the prior art example, and by calculating for one layer the so named Pair Correlation Function (PCF), the prior art shingling process (Fig. 7, curve A) produces PCF values:

- showing a first peak at distance 0, which corresponds to the case where a dot form a pair with itself (ininfluent);
- strictly equal to zero for distances $x < 63$; i.e. a zero probability of having a pair of dots closer than 63 μm ;
- a first peak for distances $x = 63$, i.e. a high probability of having two dots at a distance less than the coalescence distance $D_{\text{min}} = 84 \mu\text{m}$.

The shingling process according to present invention produces PCF values (Fig. 7, curve B):

- showing a first peak at distance 0, which corresponds to the case where a dot form a pair with itself (ininfluent);
- very small values for pair distances $x < 84$, i.e. a very low probability of having two dots at a distance smaller than 84 μm ;

- a first peak for distances $x = 84$, i.e. a high probability of having two dots at a distance larger or equal than the coalescence distance $D_{\min} = 84 \mu\text{m}$.

In summary, Applicant believes that the shingling
5 process as disclosed with or without the cited enhancements
can be superior in most cases to the known raster shingling
process as known.

Of course, obvious changes and/or variations to the
above disclosure are possible, as regards dimensions and
10 components, as well as details of the described construction
and operation method without departing from the scope of the
invention as defined by the claims that follow.

CLAIMS

1. An ink jet printing method, comprising:
providing an ensemble of dots to be printed;
performing a current run through the ensemble of the dots
5 to be printed, including:
for each dot of the ensemble of the dots, deleting all
neighbouring dots from the current run having a distance less
than at least one predetermined value and keeping non-deleted
dots as remaining dots in the current run;
10 assigning the remaining dots to a certain layer
corresponding to the current run;
removing the remaining dots of the current run from the
ensemble of the dots; and
repeating the performing step for a further run until
15 there are no further dots in the ensemble of the dots.

2. The ink jet printing method according to claim 1, wherein
the deleting all the neighbouring dots comprises: determining
for each dot of the ensemble a set of distance values, each
value being determined as a function of a number of drops to be
20 deposited on the dot of the ensemble and on the neighbouring
dots.

3. The ink jet printing method according to claim 2, wherein
the providing an ensemble of dots comprises:
conducting calibration and halftoning processes arranged
25 to provide black ink dots to be printed by forcing subtractive
colors drops on a same position.

4. The ink jet printing method according to claim 3, wherein
the calibration process comprises utilizing an Under Color
Procedure that includes using a black transfer coefficient for
30 generating the black ink dots.

5. The ink jet printing method according to claim 4, wherein the halftoning process includes replacing every black ink dot by three subtractive colors overlapping drops.

6. The ink jet printing method according to claim 3, wherein the halftoning process includes replacing every black ink dot by three subtractive colors overlapping drops.

7. The ink jet printing method according to claim 3, defining a predetermined number of layers to be printed; and redistributing the dots assigned to layers having a number higher than the predetermined number of layers into the layers having a number lower or equal to the predetermined number of layers.

8. The ink jet printing method according to claim 2, further comprising:

defining a predetermined number of layers to be printed; and

redistributing the dots assigned to layers having a number higher than the predetermined number of layers into the layers having a number lower or equal to the predetermined number of layers.

9. The ink jet printing method according to claim 8, wherein the redistributing the dots comprises:

choosing the layer, having a number lower or equal to the predetermined number, on the basis of an interaction function or energy function of the distances between the redistributed dot with the neighbouring dots on the layer.

10. The ink jet printing method according to claim 1, wherein the providing an ensemble of dots comprises:

conducting a calibration and halftoning process arranged to provide black ink dots to be printed by forcing subtractive colors drops on a same position.

11. The ink jet printing method according to claim 10, wherein the calibration process comprises utilizing an Under Color Procedure that includes using a black transfer coefficient for generating the black ink dots.

12. The ink jet printing method according to claim 11, wherein the halftoning process includes replacing every black ink dot by three subtractive colors overlapping drops.

13. The ink jet printing method according to claim 10, wherein the halftoning process includes replacing every black ink dot by three subtractive colors overlapping drops.

14. The ink jet printing method according to claim 10, defining a predetermined number of layers to be printed; and redistributing the dots assigned to layers having a number higher than the predetermined number of layers into the layers having a number lower or equal to the predetermined number of layers.

15. The ink jet printing method according to claim 14, wherein the redistributing the dots comprises:

choosing the layer, having a number lower or equal to the predetermined number, on the basis of an interaction function or energy function of the distances between the redistributed dot with the neighbouring dots on the layer.

16. The ink jet printing method according to claim 14, wherein the redistributing the dots comprises:

choosing the layer, having a number lower or equal to the predetermined number, on the basis of an interaction function or

energy function of the distances between the redistributed dot with the neighbouring dots on the layer.

17. The ink jet printing method according to claim 1, further comprising:

5 defining a predetermined number of layers to be printed;
and

redistributing the dots assigned to layers having a number higher than the predetermined number of layers into the layers having a number lower or equal to the predetermined
10 number of layers.

18. The ink jet printing method according to claim 17, wherein the redistributing the dots comprises:

choosing the layer, having a number lower or equal to the predetermined number, on the basis of an interaction function or
15 energy function of the distances between the redistributed dot with the neighbouring dots on the layer.

19. A computer program product or set of computer program products loadable in a memory of at least one computer and including software code portions arranged to perform, when the
20 product is run on at least one computer, the method according to any one of the preceding claims.




Fig. 1 - Prior Art




Fig. 2A - Prior Art




Fig. 2B - Prior Art




Fig. 3




Fig. 4A




Fig. 4B




Fig. 4C




Fig. 5




Fig. 6A




Fig. 6B




Fig. 7