



(51) International Patent Classification:

C11D 1/22 (2006.01) *C11D 3/42* (2006.01)
C11D 3/20 (2006.01) *C11D 17/00* (2006.01)
C11D 3/37 (2006.01) *C11D 17/04* (2006.01)

(21) International Application Number:

PCT/US2016/035373

(22) International Filing Date:

2 June 2016 (02.06.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

15170808.8 5 June 2015 (05.06.2015) EP
 16158417.2 3 March 2016 (03.03.2016) EP

(71) Applicant: **THE PROCTER & GAMBLE COMPANY**
[US/US]; One Procter & Gamble Plaza, Cincinnati, Ohio
45202 (US).(72) Inventors: **GUMMEL, Jeremie, Robert Marcel**; Procter & Gamble Technical Centres Limited, Whitley Road, PO Box: Forest Hall No. 2, Longbenton Newcastle upon Tyne NE12 9TS (GB). **SOUTER, Philip, Frank**; Procter & Gamble Technical Centres Limited, Whitley Road, PO Box: Forest Hall No. 2, Longbenton Newcastle upon Tyne NE12 9TS (GB). **SOMERVILLE-ROBERTS, Nigel, Patrick**; Procter & Gamble Technical Centres Limited, Whitley Road, PO Box: Forest Hall No. 2, Longbenton Newcastle upon Tyne NE12 9TS (GB). **BROOKER, Alan, Thomas**; Procter & Gamble Technical Centres Limited, Whitley Road, PO Box: Forest Hall No. 2, Longbenton Newcastle upon Tyne NE12 9TS (GB). **XU, Dan**;

Procter & Gamble Technical Centres Limited, Whitley Road, PO Box: Forest Hall No. 2, Longbenton Newcastle upon Tyne NE12 9TS (GB).

(74) Agent: **KREBS, Jay A.**; c/o The Procter & Gamble Company, Global Patent Services, One Procter & Gamble Plaza, C8-229, Cincinnati, Ohio 45202 (US).(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: COMPACTED LIQUID LAUNDRY DETERGENT COMPOSITION

(57) **Abstract:** A liquid laundry detergent composition comprising; a. a liquid phase; b. between 0.5% and 7.5% by weight of the liquid detergent composition of a solid cleaning active, wherein said active is selected from the group of soil-release polymer, brightener, polycarboxylate polymer or mixtures thereof; wherein the solid is dispersed within the liquid phase; wherein the liquid phase comprises between 5% and 40% by weight of the liquid of an alcohol selected from the group comprising ethylene glycol, 1,3 propanediol, 1,2 propanediol, tetramethylene glycol, pentamethylene glycol, hexamethylene glycol, 2,3-butane diol, 1,3 butanediol, diethylene glycol, triethylene glycol, polyethylene glycol, glycerol formal, dipropylene glycol, polypropylene glycol, dipropylene glycol n-butyl ether, and mixtures thereof, preferably the alcohol is selected from the group comprising 1,2 propanediol, dipropylene glycol, polypropylene glycol, 2,3- butane diol, dipropylene glycol n-butyl ether and mixtures thereof; and from 10% to 30% by weight of the composition of a non-amine neutralized linear alkylbenzene sulphonate and wherein the liquid laundry detergent composition comprises less than 10% by weight of the liquid laundry detergent composition of an amine-neutralised anionic surfactant; and wherein the composition comprises between 0.5% and 20% by weight of the composition of water; and wherein the composition comprises less than 5% by weight of the composition of a hydroxyl-containing amine.



COMPACTED LIQUID LAUNDRY DETERGENT COMPOSITION

FIELD OF THE INVENTION

The present invention is to the field of liquid laundry detergent compositions and their
5 methods of use.

BACKGROUND OF THE INVENTION

Liquid laundry detergent compositions with low equilibrium relative humidities have the advantage of being less susceptible to microbial contamination. There is also a trend towards so called compacted liquids that minimise the presence of unnecessary 'filler' liquids
10 such as water. Such compositions are more environmentally friendly as less unnecessary material needs to be transported, so reducing the environmental impact of such transport operations. Therefore, there is a move in the industry to using so called compacted liquids which minimise the levels of non-active materials such as water. Such liquid laundry detergent compositions require both the presence of anionic surfactant such as linear
15 alkylbenzene sulphonate and other non-surfactant cleaning and/or care actives.

However, such compacted composition can often have high viscosities due to the high relative concentration of the cleaning materials such as anionic surfactants. Traditionally, hydroxyl-containing amines have been used in such compositions to ensure consumer acceptable viscosity of the liquid laundry detergent composition. Also, acceptable viscosity is
20 required to allow processability of the composition during manufacture. The hydroxyl-containing amines are often used as neutralising agents for the anionic detergent surfactants such as linear alkylbenzene sulphonate.

However, there is now a desire to reduce the overall level of such hydroxyl-containing amines.

25 Reduction in the level of the hydroxyl-containing amines of known low relative humidity laundry detergent compositions can result in high viscosity of the composition which negatively impacts the ability of the consumer to accurately pour and dose the composition. Also, processability of the composition is impacted as it is difficult to handle such viscous compositions during manufacture.

30 Thus, there is a need in the art for low relative humidity liquid laundry detergent compositions containing lower levels of hydroxyl-containing amine compounds, but which exhibit consumer acceptable and/or process acceptable viscosities.

It has been surprisingly found that the above problems are overcome by the specific formulation space of the present invention. The formulation space described below can

provide a liquid composition having a low relative humidity and comprising lower levels of hydroxyl-containing amine compounds but which has acceptable viscosity.

SUMMARY OF THE INVENTION

5

The present invention is to a liquid laundry detergent composition comprising;

- a. a liquid phase;
- b. between 0.5% and 7.5% by weight of the liquid detergent composition of a solid cleaning active, wherein said active is selected from the group of soil-release polymer, brightener, polycarboxylate polymer or mixtures thereof,

10

wherein the solid is dispersed within the liquid phase, and wherein the water-soluble solid phase is defined as the solid obtained when the liquid laundry detergent composition is centrifuged at 1200 G for 10 mins; and

wherein the liquid phase comprises between 5% and 40% by weight of the liquid of an alcohol selected from the group comprising ethylene glycol, 1,3 propanediol, 1,2 propanediol, tetramethylene glycol, pentamethylene glycol, hexamethylene glycol, 2,3-butane diol, 1,3 butanediol, diethylene glycol, triethylene glycol, polyethylene glycol, glycerol formal, dipropylene glycol, polypropylene glycol, dipropylene glycol n-butyl ether, and mixtures thereof, preferably the alcohol is selected from the group comprising 1,2 propanediol, dipropylene glycol, polypropylene glycol, 2,3- butane diol, dipropylene glycol n-butyl ether and mixtures thereof; and

from 10% to 30% by weight of the composition of a non-amine neutralized linear alkylbenzene sulphonate and wherein the liquid laundry detergent composition comprises less than 10% by weight of the liquid laundry detergent composition of an amine-neutralised anionic surfactant; and

wherein the composition comprises between 0.5% and 20% by weight of the composition of water; and

wherein the composition comprises less than 5% by weight of the composition of a hydroxyl-containing amine.

DETAILED DESCRIPTION OF THE INVENTION

Laundry Detergent Composition

The liquid laundry detergent composition of the present invention comprises a liquid phase and a solid active. The solid active is dispersed within the liquid phase and is present between 0.5% and 7.5% by weight of the liquid laundry detergent composition. The solid active is selected from the group of soil-release polymer, brightener, polycarboxylate polymer or mixtures thereof. The solid active and liquid phases are described in more detail below.

Preferably, the liquid laundry detergent composition has a viscosity of between 300mPa.s and 700mPa.s, more preferably between 350mPa.s and 600mPa.s at a shear rate of 1000s⁻¹. An exemplary method for measuring viscosity is to use a Rheometer DHR1 from TA instruments using a gap of 1000µm at 20°C as according to the manufacturer's instructions.

The liquid laundry detergent composition of the present invention is preferably opaque. Without wishing to be bound by theory, consumers prefer opaque compositions as this signals excellent cleaning. By opaque we herein mean the composition has a fresh hunter L value of greater than 70, more preferably greater than 72, more preferably greater than 75. The Hunter colour space is organized as a cube. The L axis runs from top to bottom; the maximum L being 100 which is white and the minimum value is zero, which is black. The a and b axes have no specific numerical limits, however positive a is red, negative a is green, positive b is yellow and negative b is blue (see figure 1). Delta values (Δ L, Δa and Δb) can be measured and are associated with a colour change. The total colour difference, ΔE, can also be calculated. The ΔE is a single value that takes into account the differences between the L, a and b of test and comparison samples. The ΔE is calculated as follows;

Using L₁, a₁, b₁ and L₂, a₂ and b₂

$$\Delta E = \sqrt{(L_2 - L_1)^2 + (a_2 - a_1)^2 + (b_2 - b_1)^2}$$

A just noticeable difference (JND) is characterized as a ΔE of greater than 2.3. The JND is the smallest detectable difference possible with the human eye between a starting and secondary level of a particular sensory stimulus.

The measurements of the present invention are taken on a HunterLab colour measurement instrument (Hunter Lab Color Quest XE), set as follows;

Illuminant: D65, Angle of observer: 10°, Mode: reflection

The instrument is used as per the manufacturer's instructions. A sample of 20mL are tested in an optically clear glass cell having a fixed path length of 10mm and dimensions 55mm by 57mm. The measurement type is reflectance measurement RSIN, which measures the diffuse and specular reflectance of the sample at the port. The measurements are made with the specular exclusion port door closed.

Fresh Hunter colour value is a measure of the colour parameters of a fresh sample, immediately after preparation.

The liquid laundry detergent composition of the present invention overall is liquid in nature. That is to say, even though it comprises a solid dispersed within a liquid phase, the composition has the nature of a liquid rather than a solid or granular composition. In relation to the laundry detergent composition of the present invention, the term 'liquid' encompasses forms such as dispersions, gels, pastes and the like. The liquid composition may also include gases in suitably subdivided form. However, the liquid composition excludes forms which are non-liquid overall, such as tablets or granules.

The term 'liquid laundry detergent composition' refers to any laundry detergent composition comprising a liquid capable of wetting and treating fabric e.g., cleaning clothing in a domestic washing machine,

The liquid composition may be formulated into a unit dose article. The unit dose article of the present invention comprises a water-soluble film which fully encloses the liquid composition in at least one compartment. Suitable unit dose articles are described in more detail below.

The liquid laundry detergent composition can be used as a fully formulated consumer product, or may be added to one or more further ingredient to form a fully formulated consumer product. The liquid laundry detergent composition may be a 'pre-treat' composition which is added to a fabric, preferably a fabric stain, ahead of the fabric being added to a wash liquor.

The liquid laundry detergent composition comprises from 10% to 30% by weight of the composition of linear alkylbenzene sulphonate.

The liquid laundry detergent composition comprises less than 10% by weight, or even less than 5% by weight, or even less than 2% by weight of the liquid laundry detergent composition of an amine-neutralised anionic surfactant, wherein the anionic surfactant is preferably selected from the group comprising linear alkylbenzene sulphonate, alkyl sulphate and mixtures thereof.

The liquid laundry detergent composition comprises between 0.5% and 20% by weight of the composition of water and may have an equilibrium relative humidity of less than 65% at 20°C.

The composition comprises less than 5% by weight of the composition of a hydroxyl-containing amine compound. Suitable amines are described in more detail below.

The liquid laundry detergent composition may comprise a structurant. Suitable structurants are described in more detail below.

The liquid laundry detergent composition may comprise a perfume raw material. The perfume raw material is preferably selected from aldehydes, ketones or a mixture thereof.

5 The liquid laundry detergent composition of the present invention may comprise adjunct ingredients, wherein the adjunct ingredients are present in the solid phase, the liquid phase or both.

Without wishing to be bound by theory, it is believed that the removal of the hydroxyl-containing amine compounds results in a number of detergent ingredients, to come
10 out of solution. This in turn results in increased viscosity of the composition. The present invention carefully balances the form of the ingredients between the solid and liquid forms, so resulting in a composition of acceptable viscosity.

Furthermore, removal of the hydroxyl-containing amine can cause the formulation to phase split (i.e. at least two visibly distinct phases can be seen). The present invention
15 provides the additional benefit of providing a composition having a low relative humidity and lower levels of hydroxyl-containing amine compounds, whilst minimising phase splitting.

Solid active

The liquid laundry detergent composition of the present invention comprises a solid
20 cleaning active, wherein the solid active is dispersed in the liquid phase.

By 'solid active' we herein mean any material that provides a cleaning benefit and is solid, i.e. not liquid. The solid active may be in particulate form. The particles may have a mean particle size distribution of between 2 μ m and 50 μ m.

By 'water-soluble' we herein mean at least 75%, or even at least 85% or even at least
25 95% of the solid dissolves in water as measured by the method set out here after using a glass-filter with a maximum pore size of 20 microns:

5 grams $\pm$ 0.1 gram of solid is added in a pre-weighed 3L beaker and 2L $\pm$ 5ml of distilled water is added. This is stirred vigorously on a magnetic stirrer, Labline model No. 1250 or equivalent and 15cm magnetic stirrer, set at 600 rpm, for 30 minutes at 35°C. Then, the
30 mixture is filtered through a folded qualitative sintered-glass filter with a pore size as defined above (max. 20 micron). The water is dried off from the collected filtrate by any conventional method, and the weight of the remaining material is determined (which is the dissolved or dispersed fraction). Then, the percentage solubility or dispersability can be calculated.

The water-soluble solid phase can be obtained when the liquid laundry detergent composition is centrifuged at 1200 G for 10 mins. A preferred method is;

1. Before use, pre heat the centrifuge (Sigma Centrifuge 6-15H, 6-pot rotor) to the desired temperature. When loading centrifuge tubes into the rotor, they should always be placed opposite each other in diametrically opposed positions, number of samples can be tested are 2, 3, 4 and 6.
2. 85ml polycarbonate with screw lids test tubes are used. Each tube was filled with 50g of material and the total mass: tube+lid+testing material measured
3. Place the tubes in the centrifuge rotor so that they are evenly spaced, and fasten the rotor cover firmly. When loading centrifuge tubes into the rotor, they should always be placed opposite each other in diametrically opposed positions, number of samples can be tested are 2, 3, 4 and 6.
4. Set the centrifuge time to 90 minutes. Start the centrifuge (it will gradually increase the speed automatically until 17119 Relative Centrifugal Force (Maximum RCF for this centrifuge is used to maximise the separation rate) is achieved.
5. At the end of the 90 minutes, reweigh each tube to ensure that no material has been lost, as centrifuge tubes can crack after several uses.
6. Different fractions can result at end of the centrifugation and the number of fractions depends on the nature of the sample, solid fraction is the most dense, opaque fraction at the bottom and the relative high viscosity. The bottom fraction can then be obtained by simply removing the top phase(s) from the tube.

The liquid laundry detergent composition comprises between 0.5% and 7.5% by weight of the liquid laundry detergent composition of the solid active.

The solid active is selected from the group of soil-release polymer, brightener, polycarboxylate polymer or mixtures thereof. Suitable soil release polymers, brighteners and polycarboxylate polymers are described in more detail below.

The solid active may comprise between 0.5% and 2.5%, or even between 0.5% and 5%, or even between 0.5% and 7.5% by weight of the solid active of a soil release polymer. The liquid laundry detergent composition may comprise between 0.5% and 2.5% or even 0.75% and 2% by weight of the liquid laundry detergent composition of a soil release polymer.

The solid active may comprise between 0.5% and 2.5%, or even between 0.5% and 5%, or even between 0.5% and 7.5% by weight of the solid active of a brightener. The liquid

laundry detergent composition may comprise between 0.5% and 2.5% or even 0.75% and 2% by weight of the liquid laundry detergent composition of a brightener.

The solid active may comprise between 0.5% and 2.5%, or even between 0.5% and 5%, or even between 0.5% and 7.5% by weight of the solid active of a polycarboxylate

5 polymer. The liquid laundry detergent composition may comprise between 0.5% and 2.5% or even 0.75% and 2% by weight of the liquid laundry detergent composition of a polycarboxylate polymer.

The composition may comprise a solid non-cleaning active. Non-cleaning actives include ingredients that provide aesthetic or sensorial benefits, or those classed as filler
10 materials. For example, non-cleaning actives include clays, perfumes, perfume delivery technologies, softness technologies, pigments, silicones, antifoams, deposition-enhancement technologies and the like.

Liquid Phase

15 The liquid laundry detergent composition of the present invention comprises a liquid phase into which the solid active is dispersed.

The liquid phase comprises between 5% and 40% by weight of the liquid of an alcohol. The alcohol is described in more detail below.

The liquid phase may comprise between 5% and 20%, or even between 5% and 15%
20 by weight of the composition of the alcohol.

The liquid phase may comprise a natural or synthetically derived fatty alcohol ethoxylate non-ionic surfactant. Preferred synthetically derived fatty alcohol ethoxylate non-ionic surfactant or those derived from the oxo-synthesis process, or so-called oxo-synthesised non-ionic surfactants. The composition may comprise from 0% to 30% or even from 0.1% to
25 25% by weight of the composition of fatty alcohol ethoxylate non-ionic surfactant.

The ethoxylated nonionic surfactant may be, e.g., primary and secondary alcohol ethoxylates, especially the C₈-C₂₀ aliphatic alcohols ethoxylated with an average of from 1 to 50 or even 20 moles of ethylene oxide per mole of alcohol, and more especially the C₁₀-C₁₅ primary and secondary aliphatic alcohols ethoxylated with an average of from 1 to 10 moles
30 of ethylene oxide per mole of alcohol.

The ethoxylated alcohol non-ionic surfactant can be, for example, a condensation product of from 3 to 8 mol of ethylene oxide with 1 mol of a primary alcohol having from 9 to 15 carbon atoms.

The non-ionic surfactant may comprise a fatty alcohol ethoxylate of formula $R(EO)_n$, wherein R represents an alkyl chain between 4 and 30 carbon atoms, (EO) represents one unit of ethylene oxide monomer and n has an average value between 0.5 and 20.

The composition may comprise other non-ionic surfactants, preferably natural or synthetic non-ionic surfactants.

Alcohol

The liquid phase comprises between 5% and 40%, or even between 5% and 20% or even between 5% and 15% by weight of the composition of an alcohol, wherein preferably the alcohol has a molecular weight of between 20 and 400 and an eRH of between 50% and 80%, or even between 52% and 75% at 20°C as measured via the alcohol eRH test.

The alcohol eRH test comprises the steps of preparing a solution of 80% alcohol in deionised water, followed by adding this to a calibrated Rotronic Hygrolab meter (in a plastic sample liner of 14mm depth) at room temperature (20°C +/- 1°C) and allowing this to equilibrate for 25 minutes, and finally measuring the eRH recorded. The volume of sample used was sufficient to fill the plastic sample liner.

By 'alcohol' we herein mean either a single compound or a mixture of compounds that when taken together collectively each have a molecular weight of between 20 and 400 and an overall eRH of the compound or mixture of between 50% and 80% at 20°C when the alcohol mixture is present as a 80% active solution in deionised water. Without wishing to be bound by theory, an alcohol is any compound comprising at least one OH unit, preferably polyols and diols, more preferably diols. Preferred diols included glycols.

The alcohol may be selected from the group comprising ethylene glycol, 1,3 propanediol, 1,2 propanediol, tetramethylene glycol, pentamethylene glycol, hexamethylene glycol, 2,3-butane diol, 1,3 butanediol, diethylene glycol, triethylene glycol, polyethylene glycol, glycerol formal, dipropylene glycol, polypropylene glycol, dipropylene glycol n-butyl ether, and mixtures thereof.

Most preferably, the alcohol may be selected from the group comprising ethylene glycol, 1,2 propanediol, 2,3-butane diol, 1,3 butanediol, triethylene glycol, polyethylene glycol, glycerol formal, dipropylene glycol, polypropylene glycol, dipropylene glycol n-butyl ether, and mixtures thereof.




Even more preferably the alcohol is selected from the group comprising 1,2 propanediol, dipropylene glycol, polypropylene glycol, 2,3- butane diol, dipropylene glycol n-butyl ether and mixtures thereof.

Most preferably, the alcohol may be selected from the group comprising 1,2 propanediol, dipropylene glycol, polypropylene glycol, dipropylene glycol n-butyl ether and mixtures thereof.

5 Soil release polymer

The cleaning active may comprise a soil release polymer. The soil release polymer may comprise a polyester soil release polymer. Suitable polyester soil release polymers may be selected from terephthalate polymers, amine polymers or mixtures thereof. Suitable polyester soil release polymers may have a structure as defined by one of the following

10 structures (I), (II) or (III):



wherein:

15 a, b and c are from 1 to 200;

d, e and f are from 1 to 50;

Ar is a 1,4-substituted phenylene;

sAr is 1,3-substituted phenylene substituted in position 5 with SO₃Me;

Me is H, Na, Li, K, Mg/2, Ca/2, Al/3, ammonium, mono-, di-, tri-, or tetraalkylammonium

20 wherein the alkyl groups are C₁-C₁₈ alkyl or C₂-C₁₀ hydroxyalkyl, or any mixture thereof;

R¹, R², R³, R⁴, R⁵ and R⁶ are independently selected from H or C₁-C₁₈ n- or iso-alkyl; and

R⁷ is a linear or branched C₁-C₁₈ alkyl, or a linear or branched C₂-C₃₀ alkenyl, or a cycloalkyl group with 5 to 9 carbon atoms, or a C₈-C₃₀ aryl group, or a C₆-C₃₀ arylalkyl group.

Suitable polyester soil release polymers may be terephthalate polymers having the structure of

25 formula (I) or (II) above.

Suitable polyester soil release polymers include the Repel-o-tex series of polymers such as Repel-o-tex SF2 (Rhodia) and/or the Texcare series of polymers such as Texcare SRA300 (Clariant).

30 Brightener

The cleaning active may comprise a brightener. The brightener is preferably selected from stilbene brighteners, hydrophobic brighteners and mixtures thereof

The brightener may comprise stilbenes, such as brightener 15. Other suitable brighteners are hydrophobic brighteners, and brightener 49. The brightener may be in

micronized particulate form, having a weight average particle size in the range of from 3 to 30 micrometers, or from 3 micrometers to 20 micrometers, or from 3 to 10 micrometers. The brightener can be alpha or beta crystalline form.

Suitable brighteners include: di-styryl biphenyl compounds, e.g. Tinopal® CBS-X, di-
 5 amino stilbene di-sulfonic acid compounds, e.g. Tinopal® DMS pure Xtra and Blankophor® HRH, and Pyrazoline compounds, e.g. Blankophor® SN, and coumarin compounds, e.g. Tinopal® SWN.

Preferred brighteners are: sodium 2 (4-styryl-3-sulfophenyl)-2H-naphthol[1,2-
 d]triazole, disodium 4,4'-bis{[(4-anilino-6-(N methyl-N-2 hydroxyethyl)amino 1,3,5- triazin-
 10 2-yl)]amino}stilbene-2-2' disulfonate, disodium 4,4'-bis{[(4-anilino-6-morpholino-1,3,5- triazin-2-yl)]amino} stilbene-2-2' disulfonate, and disodium 4,4'- bis(2-sulfostyryl)biphenyl.
 A suitable fluorescent brightener is C.I. Fluorescent Brightener 260, which may be used in its beta or alpha crystalline forms, or a mixture of these forms.


15 Polycarboxylate polymers

The cleaning active may comprise a polycarboxylate polymer. The cleaning active may comprise at least 5% by weight of the composition of a polycarboxylate polymer. The solid phase may comprise between 1% and 5%, or even between 1% and 2% by weight of the solid phase of a polycarboxylate polymer. The liquid laundry detergent composition may
 20 comprise between 0.5% and 2.5% or even 0.75% and 2% by weight of the liquid laundry detergent composition of a polycarboxylate.

The polycarboxylate polymer may comprise a maleate/acrylate random copolymer or polyacrylate homopolymer. Suitable polycarboxylate polymers include: polyacrylate homopolymers having a molecular weight of from 4,000 Da to 9,000 Da; maleate/acrylate
 25 random copolymers having a molecular weight of from 50,000 Da to 100,000 Da, or from 60,000 Da to 80,000 Da.


Another suitable polycarboxylate polymer is a co-polymer that comprises: (i) from 50 to less than 98 wt% structural units derived from one or more monomers comprising carboxyl groups; (ii) from 1 to less than 49 wt% structural units derived from one or more monomers
 30 comprising sulfonate moieties; and (iii) from 1 to 49 wt% structural units derived from one or more types of monomers selected from ether bond-containing monomers represented by formulas (I) and (II):

formula (I):



wherein in formula (I), R_0 represents a hydrogen atom or CH_3 group, R represents a CH_2 group, CH_2CH_2 group or single bond, X represents a number 0-5 provided X represents a

formula (II)



wherein in formula (II), R_0 represents a hydrogen atom or CH_3 group, R represents a CH_2 group, CH_2CH_2 group or single bond, X represents a number 0-5, and R_1 is a hydrogen atom or C_1 to C_{20} organic group.

It may be preferred that the polymer has a weight average molecular weight of at least 50kDa, or even at least 70kDa.

Anionic surfactant

The liquid laundry detergent composition comprises from 10% to 30% by weight of the composition of a non-amine neutralized linear alkylbenzene sulphonate. The linear alkylbenzene sulphonate may be present in the liquid or may be present as a solid, or a mixture thereof. If the linear alkylbenzene sulphonate is present as a solid, preferably it is in the form of a lamellar liquid crystal alkylbenzene sulphonate. By 'lamellar liquid crystal' we herein mean the system being in a state where the surfactant molecules are organised in stacks

of bilayers of surfactant in the melted state separated by thin layers of solvent. This structure has both liquid properties in term of flowability as well as solid properties in term of being structured. The structure is characterised by its d-spacing, the sum of the bilayer thickness and the solvent layer between sheets. The repetition and periodicity of this structure yields to sharp x-ray diffraction peaks characteristic of crystal phases.

Non-amine neutralized linear alkylbenzene sulphonates are those in which the linear alkylbenzene sulphonic acid is neutralized to the correspond linear alkylbenzene sulphonate salt using a neutralizing material other than an amine. Non-limiting examples of such neutralizing groups include sodium, potassium, magnesium and mixtures thereof. The non-amine neutralized linear alkylbenzene sulphonate may be a sodium linear alkylbenzene sulphonate, a potassium alkylbenzene sulphonate, a magnesium alkylbenzene sulphonate or a mixture thereof.

Exemplary linear alkylbenzene sulphonates are C₁₀-C₁₆ alkyl benzene sulfonic acids, or C₁₁-C₁₄ alkyl benzene sulfonic acids. By 'linear', we herein mean the alkyl group is linear. Alkyl benzene sulfonates are well known in the art. Especially useful are the sodium, potassium and magnesium linear straight chain alkylbenzene sulfonates in which the average number of carbon atoms in the alkyl group is from about 11 to 14.

The cleaning technology may comprise an amine neutralized anionic surfactant, preferably an amine neutralized linear alkylbenzene sulphonate, an amine neutralized alkyl sulphate or a mixture thereof. The liquid laundry detergent composition may comprise an amine neutralized anionic surfactant in the solid phase, liquid phase or both.

The liquid laundry detergent composition may comprise an alkyl sulphate anionic surfactant. The liquid laundry detergent composition may comprise from 10% to 30% or even from 15% to 25% by weight of the laundry detergent composition of alkyl sulphate anionic surfactant.

The alkyl sulphate anionic surfactant may be non-amine neutralised, amine neutralised or a mixture thereof, preferably the alkyl sulphate is non-amine neutralised. The non-amine neutralized alkyl sulphate may be a sodium alkyl sulphate, a potassium alkyl sulphate, a magnesium alkyl sulphate or a mixture thereof.

The alkyl sulphate anionic surfactant may be present in the liquid or may be present as a solid, or a mixture thereof. If the alkyl sulphate is present as a solid, preferably it is in the form of a lamellar liquid crystal alkyl sulphate. The alkyl sulphate anionic surfactant may be alkoxylated or non-alkoxylated or a mixture thereof. The alkyl sulphate anionic surfactant may be a C₁₀-C₂₀ primary, branched-chain and random alkyl sulfates (AS), including

predominantly C₁₂ alkyl sulfates. Alternatively, the alkyl sulphate anionic surfactant may be a C₁₀-C₁₈ secondary (2,3) alkyl sulfates. Alternatively, the alkyl sulphate anionic surfactant may be a C₁₀-C₁₈ alkyl alkoxy sulfates (AE_xS) wherein x is from 1-30. Alternatively, the alkyl sulphate anionic surfactant may be a mixture of all the above alkyl sulphate anionic surfactants. Non-limiting examples of suitable cations for the alkyl sulphate anionic surfactant include sodium, potassium, ammonium, amine and mixtures thereof.

Amine

The detergent composition comprises less than 5% by weight of the composition of a hydroxyl-containing amine compound, or even from 0.1% to 5%, or even from 0.1% to 4% by weight of the composition of a hydroxyl-containing amine compound. By 'hydroxyl-containing amine compound' we herein mean a compound comprising an alcohol (OH) group and an amine group. The hydroxyl-containing amine compound may be selected from monoethanolamine, triethanolamine, diisopropanolamine, triisopropanolamine, Monoamino hexanol, 2-[(2-methoxyethyl) methylamino]- ethanol, Propanolamine, N-Methylethanolamine, diethanolamine, Monobutanol amine, Isobutanolamine, Monopentanol amine, 1-Amino-3-(2-methoxyethoxy)- 2-propanol, 2-Methyl-4-(methylamino)- 2-butanol, 6-amino-1-hexanol, Heptaminol, Isoetarine, Norepinephrine, Sphingosine, Phenylpropanolamine and mixtures thereof.

The hydroxyl-containing amine compound may be selected from the group comprising monoethanol amine, triethanolamine and mixtures thereof.

Preferably, the hydroxyl-containing amine compound has a molecular weight of less than 500, or even less than 250.

The detergent composition may comprise other amine containing compounds.

Structurant

The composition of the present invention may comprises less than 2% by weight of the composition of a structurant. If a structurant is present, preferably the composition comprises from 0.05% to 2%, preferably from 0.1% to 1% by weight of a structurant. The structurant may be selected from non-polymeric or polymeric structurants. The structurant may be a non-polymeric structurant, preferably a crystallisable glyceride. The structurant may be a polymeric structurant, preferably a fibre based polymeric structurant, more preferably a cellulose fibre-based structurant. The structurant may be selected from crystallisable glyceride, cellulose-fibre based structurants, TiO₂, silica and mixtures thereof.

Suitable structurants are preferably ingredients which impart a sufficient yield stress or low shear viscosity to stabilize the liquid laundry detergent composition independently from, or extrinsic from, any structuring effect of the deterative surfactants of the composition.

Preferably, they impart to the laundry detergent composition a high shear viscosity at 20 sec⁻¹ at 21°C of from 1 to 1500 cps and a viscosity at low shear (0.05 sec⁻¹ at 21°C) of greater than 5000 cps. The viscosity is measured using an AR 550 rheometer from TA instruments using a plate steel spindle at 40 mm diameter and a gap size of 500 μm. The high shear viscosity at 20s⁻¹ and low shear viscosity at 0.5s⁻¹ can be obtained from a logarithmic shear rate sweep from 0.1-1 to 25-1 in 3 minutes time at 21°C.

The structurant may be a polymeric crystalline, hydroxy-functional structurant that comprises a crystallizable glyceride, preferably hydrogenated castor oil or "HCO". HCO as used herein most generally can be any hydrogenated castor oil or derivative thereof, provided that it is capable of crystallizing in the non-polymeric crystalline, hydroxy-functional structurant premix. Castor oils may include glycerides, especially triglycerides, comprising C₁₀ to C₂₂ alkyl or alkenyl moieties which incorporate a hydroxyl group. Hydrogenation of castor oil, to make HCO, converts the double bonds which may be present in the starting oil as ricinoleyl moieties. As such, the ricinoleyl moieties are converted into saturated hydroxyalkyl moieties, e.g., hydroxystearyl. The HCO herein may be selected from: trihydroxystearin; dihydroxystearin; and mixtures thereof. The HCO may be processed in any suitable starting form, including, but not limited to those selected from solid, molten and mixtures thereof. HCO of use in the present invention includes those that are commercially available.

Non-limiting examples of commercially available HCO of use in the present invention include: THIXCIN® from Rheox, Inc.

The structurant may comprise a fibre-based structurant. The structurant may comprise a microfibrillated cellulose (MFC), which is a material composed of nanosized cellulose fibrils, typically having a high aspect ratio (ratio of length to cross dimension). Typical lateral dimensions are 1 to 100, or 5 to 20 nanometres, and longitudinal dimension is in a wide range from nanometres to several microns. For improved structuring, the microfibrillated cellulose preferably has an average aspect ratio (l/d) of from 50 to 200,000, more preferably from 100 to 10,000. Microfibrillated cellulose can be derived from any suitable source, including bacterial cellulose, citrus fibers, and vegetables such as sugar beet, chicory root, potato, carrot, and the like.

The structurant may be selected from the group consisting of titanium dioxide, tin dioxide, any forms of modified TiO_2 , TiO_2 or stannic oxide, bismuth oxychloride or bismuth oxychloride coated TiO_2 , silica coated TiO_2 or metal oxide coated TiO_2 and mixtures thereof. Modified TiO_2 may comprise carbon modified TiO_2 , metallic doped TiO_2 or mixtures thereof.

5 Metallic doped TiO_2 may be selected from platinum doped TiO_2 , Rhodium doped TiO_2 .

The structurant may comprise silica. Those skilled in the art will know suitable silica materials to use. The silica may comprise fumed silica.

Water and equilibrium relative humidity

10 The liquid laundry detergent composition comprises between 0.5% and 15% by weight of the composition of water. The liquid laundry detergent composition may comprise between 0.5% and 12%, or even between 0.5% and 10% by weight of the composition of water.

The liquid laundry detergent composition may have an equilibrium relative humidity
15 of less than 65% at 20°C.

A preferred method for measuring the eRH of the composition is via the composition eRH test. The composition eRH test comprises the steps of adding a sample of the composition to a calibrated Rotronic Hygrolab meter (in a plastic sample liner of 14mm depth) at room temperature (20°C +/- 1°C) and allowing this to equilibrate for 25 minutes, and
20 finally measuring the eRH recorded. The volume of sample used was sufficient to fill the plastic sample liner.

Adjunct ingredients

The liquid laundry detergent composition may comprise an adjunct ingredient. The
25 liquid laundry detergent composition may comprise from 20% to 40% by weight of the composition of an adjunct ingredient. The adjunct ingredient may be selected from the group comprising bleach, bleach catalyst, dye, hueing dye, cleaning polymers including alkoxyated polyamines and polyethyleneimines, surfactant, solvent, dye transfer inhibitors, chelant, enzyme, perfume, encapsulated perfume, cellulosic polymers and mixtures thereof.

30

Water-soluble pouch

The liquid laundry detergent composition may be present in a water-soluble unit dose article, wherein the liquid laundry detergent composition comprises between 0.5% and 15%, preferably between 0.5% and 12%, more preferably between 0.5% and 10% by weight of the

liquid laundry detergent composition of water. In such an embodiment, the water-soluble unit dose article comprises at least one water-soluble film shaped such that the unit-dose article comprises at least one internal compartment surrounded by the water-soluble film. The at least one compartment comprises the liquid laundry detergent composition. The water-soluble film is sealed such that the liquid laundry detergent composition does not leak out of the compartment during storage. However, upon addition of the water-soluble unit dose article to water, the water-soluble film dissolves and releases the contents of the internal compartment into the wash liquor.

The compartment should be understood as meaning a closed internal space within the unit dose article, which holds the composition. Preferably, the unit dose article comprises a water-soluble film. The unit dose article is manufactured such that the water-soluble film completely surrounds the composition and in doing so defines the compartment in which the composition resides. The unit dose article may comprise two films. A first film may be shaped to comprise an open compartment into which the composition is added. A second film is then laid over the first film in such an orientation as to close the opening of the compartment. The first and second films are then sealed together along a seal region. The film is described in more detail below.

The unit dose article may comprise more than one compartment, even at least two compartments, or even at least three compartments. The compartments may be arranged in superposed orientation, i.e. one positioned on top of the other. Alternatively, the compartments may be positioned in a side-by-side orientation, i.e. one orientated next to the other. The compartments may even be orientated in a 'tyre and rim' arrangement, i.e. a first compartment is positioned next to a second compartment, but the first compartment at least partially surrounds the second compartment, but does not completely enclose the second compartment. Alternatively one compartment may be completely enclosed within another compartment.

The film of the present invention is soluble or dispersible in water. The water-soluble film preferably has a thickness of from 20 to 150 micron, preferably 35 to 125 micron, even more preferably 50 to 110 micron, most preferably about 76 micron.

Preferably, the film has a water-solubility of at least 50%, preferably at least 75% or even at least 95%, as measured by the method set out here after using a glass-filter with a maximum pore size of 20 microns:

5 grams $\pm$ 0.1 gram of film material is added in a pre-weighed 3L beaker and 2L $\pm$ 5ml of distilled water is added. This is stirred vigorously on a magnetic stirrer, Labline model No.

1250 or equivalent and 5 cm magnetic stirrer, set at 600 rpm, for 30 minutes at 30°C. Then, the mixture is filtered through a folded qualitative sintered-glass filter with a pore size as defined above (max. 20 micron). The water is dried off from the collected filtrate by any conventional method, and the weight of the remaining material is determined (which is the dissolved or dispersed fraction). Then, the percentage solubility or dispersability can be calculated.

Preferred film materials are preferably polymeric materials. The film material can, for example, be obtained by casting, blow-moulding, extrusion or blown extrusion of the polymeric material, as known in the art.

Preferred polymers, copolymers or derivatives thereof suitable for use as pouch material are selected from polyvinyl alcohols, polyvinyl pyrrolidone, polyalkylene oxides, acrylamide, acrylic acid, cellulose, cellulose ethers, cellulose esters, cellulose amides, polyvinyl acetates, polycarboxylic acids and salts, polyaminoacids or peptides, polyamides, polyacrylamide, copolymers of maleic/acrylic acids, polysaccharides including starch and gelatine, natural gums such as xanthum and carragum. More preferred polymers are selected from polyacrylates and water-soluble acrylate copolymers, methylcellulose, carboxymethylcellulose sodium, dextrin, ethylcellulose, hydroxyethyl cellulose, hydroxypropyl methylcellulose, maltodextrin, polymethacrylates, and most preferably selected from polyvinyl alcohols, polyvinyl alcohol copolymers and hydroxypropyl methyl cellulose (HPMC), and combinations thereof. Preferably, the level of polymer in the pouch material, for example a PVA polymer, is at least 60%. The polymer can have any weight average molecular weight, preferably from about 1000 to 1,000,000, more preferably from about 10,000 to 300,000 yet more preferably from about 20,000 to 150,000.

Mixtures of polymers can also be used as the pouch material.

Preferred films exhibit good dissolution in cold water, meaning unheated distilled water. Preferably such films exhibit good dissolution at temperatures of 24°C, even more preferably at 10°C. By good dissolution it is meant that the film exhibits water-solubility of at least 50%, preferably at least 75% or even at least 95%, as measured by the method set out here after using a glass-filter with a maximum pore size of 20 microns, described above.

Preferred films are those supplied by Monosol under the trade references M8630, M8900, M8779, M8310.

The film may be opaque, transparent or translucent. The film may comprise a printed area.

The area of print may be achieved using standard techniques, such as flexographic printing or inkjet printing.

The film may comprise an aversive agent, for example a bittering agent. Suitable bittering agents include, but are not limited to, naringin, sucrose octaacetate, quinine hydrochloride, denatonium benzoate, or mixtures thereof. Any suitable level of aversive agent may be used in the film. Suitable levels include, but are not limited to, 1 to 5000ppm, or even 100 to 2500ppm, or even 250 to 2000rpm.

Method of making

The liquid laundry detergent composition of the present invention may be made using any suitable manufacturing techniques known in the art. Those skilled in the art would know appropriate methods and equipment to make the composition according to the present invention.

A preferred process comprises the step of adding the solid phase wherein the solid phase comprises particles wherein the particles have a mean particle size distribution of less than 500 μ m.

HCO premix may be formed by melting HCO and adding into a small volume of a hot liquid laundry detergent composition wherein the composition does not comprise enzymes or perfume materials. The HCO premix is then added to other ingredients to form the liquid laundry detergent composition.

Method of use

The composition or unit dose article of the present invention can be added to a wash liquor to which laundry is already present, or to which laundry is added. It may be used in an washing machine operation and added directly to the drum or to the dispenser drawer. The washing machine may be an automatic or semi-automatic washing machine. It may be used in combination with other laundry detergent compositions such as fabric softeners or stain removers. It may be used as pre-treat composition on a stain prior to being added to a wash liquor.

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

EXAMPLES

The viscosity of various compositions were compared. The following compositions were prepared;

5

Table 1

	Compositions (wt%)		
	A	B	C
water	7.16	7.16	7.44
Dipropylene glycol	14.66	14.66	31.19
1,2-propanediol		10.00	
Dipropylene glycol n-butyl ether	9.80	9.80	
Glycerol	15.00	5.00	5.00
Linear alkylbenzene sulphonate neutralized with monoethanolamine			23.59
Linear alkylbenzene sulphonate neutralized with sodium carbonate	23.59	23.59	
Ethoxylated polyethyleneimine	2.16	2.16	2.16
Alkyl sulphate with an average degree of ethoxylation of 3, neutralized with monoethanolamine			11.00
Alkyl sulphate with an average degree of ethoxylation of 3, neutralized with sodium carbonate	11.00	11.00	
HEDP	1.81	1.81	1.81
Amphiphilic graft copolymer	2.72	2.72	2.72
Brightener 49	0.24	0.24	0.24
Soil release polymer commercially available from Clariant as SRA-300	0.32	0.32	0.32
Carboxymethyl cellulose	1.07	1.07	1.07
Siloxane polymeric suds suppressor	0.13	0.13	0.13
Perfume	2.68	2.68	2.68
protease	0.10	0.10	0.10

	20		
TiO ₂	0.50	0.50	0.50
palm kernel fatty acid	3.26	3.26	3.26
Guerbet alcohol non-ionic surfactant commercially available from BASF as Lutensol XL100	0.56	0.56	0.56
minors	2.36	2.36	2.77

The compositions were made by preparing a 1L beaker having an IKA Eurostar 200 mixer with 10cm impeller. This was operated at 250rpm. To the beaker with the rotating impeller, the solvent materials were added, followed by the surfactant materials. Once these had dispersed, the polymers and salts were added. The pH of the composition was adjusted using NaOH to approximately 8 (measured using a Sartorius PT-10 pH meter). Remaining ingredients were then added and mixed. All materials were weighed out using a Mettler Toledo PB3002-S balance.

Composition C comprised 6.25% by weight of composition C of monoethanolamine.

Compositions A and B comprised no monoethanolamine.

The viscosity of the compositions were then measured using a Rheometer DHR1 from TA instruments using a gap of 1000 μ m at 20°C. Samples were equilibrated for 1 min at 0.05s⁻¹ followed by a measured flow curve from 0.05s⁻¹ to 1200s⁻¹ over 10 mins. Results for 0.05s⁻¹ and 1000s⁻¹ are shown in Table 2.

Table 2

	0.05s ⁻¹	1000s ⁻¹
	mPa.s	mPa.s
A	1560	870
B	1112	413
C	1310	315

Shear at 0.05s⁻¹ corresponds to that experienced by the composition during pouring of the composition by the consumer. Shear at 1000s⁻¹ corresponds to that experienced by the composition during manufacture.

Composition C which comprises 6.25% monoethanolamine shows an acceptable viscosity profile at low and high shear corresponding to consumer pouring shear and process dosing shear.

However, when the monoethanolamine is removed in composition A (and correspondingly the surfactants are neutralized with sodium carbonate), there is an increase in viscosity to unacceptable levels.

Composition B corresponds to the present invention in which the monoethanolamine
5 has been removed and the surfactants neutralized with sodium carbonate, but also 1,2-propandiol has been added. The viscosity returns to acceptable levels.


CLAIMS

What is claimed is:

1. A liquid laundry detergent composition comprising;
 - a. a liquid phase;
 - b. between 0.5% and 7.5% by weight of the liquid detergent composition of a solid cleaning active, wherein said active is selected from the group of soil-release polymer, brightener, polycarboxylate polymer or mixtures thereof, wherein the solid is dispersed within the liquid phase, and wherein the water-soluble solid phase is defined as the solid obtained when the liquid laundry detergent composition is centrifuged at 1200 G for 10 mins; and wherein the liquid phase comprises between 5% and 40% by weight of the liquid of an alcohol selected from the group comprising ethylene glycol, 1,3 propanediol, 1,2 propanediol, tetramethylene glycol, pentamethylene glycol, hexamethylene glycol, 2,3-butane diol, 1,3 butanediol, diethylene glycol, triethylene glycol, polyethylene glycol, glycerol formal, dipropylene glycol, polypropylene glycol, dipropylene glycol n-butyl ether, and mixtures thereof, preferably the alcohol is selected from the group comprising 1,2 propanediol, dipropylene glycol, polypropylene glycol, 2,3- butane diol, dipropylene glycol n-butyl ether and mixtures thereof; and from 10% to 30% by weight of the composition of a non-amine neutralized linear alkylbenzene sulphonate and wherein the liquid laundry detergent composition comprises less than 10% by weight of the liquid laundry detergent composition of an amine-neutralised anionic surfactant; and wherein the composition comprises between 0.5% and 20% by weight of the composition of water; and wherein the composition comprises less than 5% by weight of the composition of a hydroxyl-containing amine.
2. The detergent composition according to claim 1 wherein the soil release polymer is a polyester soil release polymer, preferably selected from the group comprising terephthalate polymers, amine polymers or mixtures thereof.
3. The detergent composition according to any preceding claims, wherein the brightener is selected from stilbene brighteners, hydrophobic brighteners and mixtures thereof.


4. The detergent composition according to any preceding claims, wherein the polycarboxylate polymer is selected from a maleate/acrylate random copolymer or polyacrylate homopolymer, or a co-polymer that comprises: (i) from 50 to less than 98 wt% structural units derived from one or more monomers comprising carboxyl groups; (ii) from 1 to less than 49 wt% structural units derived from one or more monomers comprising sulfonate moieties; and (iii) from 1 to 49 wt% structural units derived from one or more types of monomers selected from ether bond-containing monomers represented by formulas (I) and (II):

formula (I):



wherein in formula (I), R_0 represents a hydrogen atom or CH_3 group, R represents a CH_2 group, CH_2CH_2 group or single bond, X represents a number 0-5 provided X represents a number 1-5 when R is a single bond, and R_1 is a hydrogen atom or C_1 to C_{20} organic group;

formula (II)



wherein in formula (II), R_0 represents a hydrogen atom or CH_3 group, R represents a CH_2 group, CH_2CH_2 group or single bond, X represents a number 0-5, and R_1 is a hydrogen atom or C_1 to C_{20} organic group.

5. The detergent composition according to any preceding claims, wherein the composition has an equilibrium relative humidity of less than 65% at 20°C, preferably as measured via the composition eRH test described herein.
6. The detergent composition according to any preceding claims, wherein the liquid phase comprises between 5% and 20%, or even between 5% and 15% by weight of the composition of the alcohol.
7. The detergent composition according to any preceding claims, wherein the liquid phase comprises alkyl sulphate anionic surfactant, natural or synthetically derived fatty alcohol ethoxylate non-ionic surfactant or mixtures thereof.
8. The detergent composition according to any preceding claims comprising from 0.1% to 4% by weight of the composition of a hydroxyl-containing amine.
9. The detergent composition according to any preceding claims wherein the amine is selected from the group comprising monoethanol amine, triethanolamine and mixtures thereof.
10. The detergent composition according to any preceding claims comprising a structurant.
11. The detergent composition according to any preceding claims, wherein the solid is in particulate form and wherein the particles have a mean particle size distribution of between 2 μ m and 50 μ m.
12. The detergent composition according to any preceding claims comprising a perfume raw material, wherein the perfume raw material is preferably selected from aldehydes, ketones or a mixture thereof.

13. The detergent composition according to any preceding claims comprising an adjunct ingredient, preferably between 20% and 40% by weight of the composition of an adjunct ingredient, wherein the adjunct ingredient is selected from the group comprising bleach, bleach catalyst, dye, hueing dye, cleaning polymers including alkoxyated polyamines and polyethyleneimines, surfactant, solvent, dye transfer inhibitors, chelant, enzyme, perfume, encapsulated perfume, cellulosic polymers and mixtures thereof.
14. A water-soluble unit dose article comprising a water-soluble film and a detergent composition according to any preceding claims wherein the composition comprises between 0.5% and 15% by weight of the composition of water.
15. The unit dose article according to claim 14 wherein the unit dose article comprises at least two compartments, or even at least three or even at least four compartments.
16. A process of making a composition according to any preceding claims, comprising the step of adding the solid wherein the solid comprises particles wherein the particles have a mean particle size distribution of less than 500 μ m.

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2016/035373

A. CLASSIFICATION OF SUBJECT MATTER		
INV.	C11D1/22	C11D3/20
	C11D17/04	
		C11D3/37
		C11D3/42
		C11D17/00
ADD.		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
C11D		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
EPO-Internal, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 059 351 A1 (PROCTER & GAMBLE) 13 December 2000 (2000-12-13) examples 1,3	1-16
X	EP 0 253 151 A2 (HENKEL KGAA) 20 January 1988 (1988-01-20) example 2	1-16
X	WO 99/00477 A1 (PROCTER & GAMBLE) 7 January 1999 (1999-01-07) examples I-III	1-16
☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
9 August 2016		22/08/2016
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016		Authorized officer Hillebrecht, Dieter

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2016/035373

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 1059351	A1	13-12-2000	AU	5598100 A		02-01-2001
			EP	1059351 A1		13-12-2000
			WO	0077155 A1		21-12-2000

EP 0253151	A2	20-01-1988	DE	3621536 A1		07-01-1988
			DK	330887 A		27-12-1987
			EP	0253151 A2		20-01-1988
			JP	S638495 A		14-01-1988
			US	4929380 A		29-05-1990

WO 9900477	A1	07-01-1999	AR	029599 A1		10-07-2003
			AT	252631 T		15-11-2003
			BR	9810482 A		12-09-2000
			CA	2295115 A1		07-01-1999
			DE	69819153 D1		27-11-2003
			DE	69819153 T2		15-07-2004
			EP	0991748 A1		12-04-2000
			JP	4318759 B2		26-08-2009
			JP	2002507227 A		05-03-2002
			US	6281187 B1		28-08-2001
			WO	9900477 A1		07-01-1999
