



US007726847B2

(12) **United States Patent**
Bingaman

(10) **Patent No.:** **US 7,726,847 B2**
(45) **Date of Patent:** **Jun. 1, 2010**

(54) **METHOD AND APPARATUS FOR POSITIONING A LIGHT IN A REFLECTOR**

(75) Inventor: **Tim Bingaman**, Brighton, CO (US)

(73) Assignee: **Cooper Technologies Company**, Houston, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 174 days.

(21) Appl. No.: **11/339,271**

(22) Filed: **Jan. 25, 2006**

(65) **Prior Publication Data**

US 2007/0171653 A1 Jul. 26, 2007

(51) **Int. Cl.**
F21V 7/00 (2006.01)

(52) **U.S. Cl.** **362/296.01**; 362/341; 362/347; 362/350; 362/368; 362/370; 403/326; 403/329; 403/408.1

(58) **Field of Classification Search** 362/271, 362/294, 296, 302, 319, 341, 345, 347, 350, 362/368, 370, 373, 432, 260, 220, 225, 285, 362/297, 346, 430; 403/326, 329, 408.1
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,913,517 A	6/1933	Smith et al.	
D130,258 S	11/1941	Tucker	
2,783,452 A	2/1957	Falge et al.	
3,167,258 A	1/1965	Wilde	
3,188,459 A *	6/1965	Bridwell	362/227
3,340,393 A	9/1967	Kurt et al.	
3,358,133 A	12/1967	Thoman	
3,363,091 A	1/1968	Cooper	

3,558,870 A	1/1971	Morrison
3,663,990 A	5/1972	Shane
3,686,495 A	8/1972	Medley
3,745,326 A	7/1973	Hernandez
3,991,905 A	11/1976	Nicpon
3,997,778 A	12/1976	Fieldstad
D254,094 S	1/1980	Jaksich
4,206,499 A	6/1980	Urbanek
4,317,625 A	3/1982	Van Allen
4,379,322 A	4/1983	Kelly
4,410,931 A	10/1983	DeCandia et al.
4,412,276 A	10/1983	Blinow
4,450,511 A	5/1984	Micha
4,587,602 A	5/1986	Dean et al.
4,617,615 A	10/1986	Eychaner
D308,114 S	5/1990	Shemitz
D308,260 S	5/1990	Shemitz

(Continued)

Primary Examiner—Sandra L. O’Shea


Assistant Examiner—Mary Zettl

(74) *Attorney, Agent, or Firm*—King & Spalding LLP

(57) **ABSTRACT**

The invention provides a method and apparatus for positioning a lighting device in a reflector. The exemplary apparatus includes a reflector member comprising a side wall with a reflector surface extending from the side wall. A lighting device support member is coupled to and extends from the side wall and defines at least one channel for engaging a support arm and a fastener channel for engaging a fastener member. The apparatus further includes a lighting device secured to a bracket for coupling the lighting device to the lighting device support member. The bracket defines a support arm for engaging the at least one support arm channel. The lighting device support member positions the lighting device adjacent to the reflector surface. The apparatus also includes a fastener for securing the bracket to the lighting device support member by engaging the fastener channel.

20 Claims, 24 Drawing Sheets



U.S. PATENT DOCUMENTS

D312,886 S	12/1990	Brown		D482,487 S	11/2003	Russello et al.	
D316,306 S	4/1991	Shemitz		6,652,113 B2	11/2003	Tant	
5,205,633 A *	4/1993	Kasboske	362/519	6,773,135 B1	8/2004	Packer	
5,243,507 A	9/1993	Atkins et al.		6,902,303 B2	6/2005	Lee	
5,329,667 A	7/1994	Erskine		7,018,070 B2 *	3/2006	McCoy	362/260
5,765,942 A	6/1998	Shirai et al.		D545,471 S	6/2007	Guercio	
5,887,969 A *	3/1999	Gordin	362/347	D549,380 S	8/2007	Guercio	
5,971,571 A	10/1999	Rose		D550,392 S	9/2007	Guercio	
6,056,416 A *	5/2000	Ngai et al.	362/225	7,357,538 B2	4/2008	Gaines et al.	
6,152,583 A	11/2000	Langner		2004/0085770 A1 *	5/2004	Tyler et al.	362/297
6,154,945 A	12/2000	Voelzke		2005/0047128 A1	3/2005	Monroe et al.	
D439,355 S	3/2001	Ford		2005/0047129 A1 *	3/2005	Eppler	362/217
6,264,342 B1 *	7/2001	von Hagen	362/17	2007/0171643 A1	7/2007	Gaines et al.	
6,386,723 B1 *	5/2002	Eberlein et al.	362/33	2007/0171648 A1	7/2007	Tickner et al.	
6,409,029 B1 *	6/2002	Bermes	211/70.6	2007/0171652 A1	7/2007	Gaines et al.	
6,461,026 B1	10/2002	Wang		2007/0171653 A1	7/2007	Bingaman	
D472,339 S	3/2003	Russello et al.		2007/0171657 A1	7/2007	Tickner et al.	
6,530,676 B1	3/2003	Krogman		2007/0171658 A1	7/2007	Tickner et al.	
D479,015 S	8/2003	Tang		2007/0171659 A1	7/2007	Tickner et al.	
				2007/0171660 A1	7/2007	Wilkinson et al.	

* cited by examiner




FIG. 1




Fig. 2a




Fig. 2a

Fig. 2b

Fig. 2c






Fig. 3a






Fig. 3C




Fig. 3e






Fig. 4a






Fig. 4c





Fig. 4d






Fig. 4h




Fig. 4j




Fig. 4k




Fig. 4l




Fig. 5a




Fig. 5b







Fig. 5c






Fig. 7a




Fig. 7c




Fig. 7d

METHOD AND APPARATUS FOR POSITIONING A LIGHT IN A REFLECTOR

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is related to (1) U.S. Utility application Ser. No. 11/339,387, filed on Jan. 25, 2006, the disclosure which is incorporated herein by reference; (2) U.S. Utility application Ser. No. 11/339,426, filed on Jan. 25, 2006, the disclosure which is incorporated herein by reference; (3) U.S. Utility application Ser. No. 11/339,270, filed on Jan. 25, 2006, the disclosure which is incorporated herein by reference; (4) U.S. Utility application Ser. No. 11/339,164, filed on Jan. 25, 2006, the disclosure which is incorporated herein by reference; (5) U.S. Utility application Ser. No. 11/339,363, filed on Jan. 25, 2006, this disclosure is incorporated herein by reference; (6) U.S. Utility application Ser. No. 11/339,028, filed on Jan. 25, 2006, the disclosure which is incorporated herein by reference; (7) U.S. Utility application Ser. No. 11/339,207, filed on Jan. 25, 2006, the disclosure which is incorporated herein by reference; (8) U.S. Design application Ser. No. 29/252,645, filed on Jan. 25, 2006, the disclosure which is incorporated herein by reference; and (9) U.S. Design application Ser. No. 29/252,649, filed on Jan. 25, 2006, the disclosure which is incorporated herein by reference.

BACKGROUND

The present disclosure relates in general to lighting and in particular to a method and apparatus for positioning a light in a reflector.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an exploded view illustrating an exemplary embodiment of a lighting apparatus.

FIG. 2a is an exploded view illustrating an exemplary embodiment of a lighting device chassis used in the lighting apparatus of FIG. 1.

FIG. 2b is a side view illustrating an exemplary embodiment of a chassis base used in the lighting device chassis of FIG. 2a.

FIG. 2c is a perspective view illustrating an exemplary embodiment of the lighting device chassis of FIG. 2a.

FIG. 3a is an exploded view illustrating an exemplary embodiment of a reflector member used in the lighting apparatus of FIG. 1.

FIG. 3b is a cross sectional view illustrating an exemplary embodiment of a reflector used in the reflector member of FIG. 3a.

FIG. 3c is a perspective view illustrating an exemplary embodiment of the reflector member of FIG. 3a.

FIG. 3d is a cut-away perspective view illustrating an exemplary embodiment of the reflector member of FIG. 3c.

FIG. 3e is a perspective view illustrating an exemplary embodiment of the reflector member of FIG. 3c coupled to the lighting device chassis of FIG. 2c.

FIG. 4a is an exploded view illustrating an exemplary embodiment of a door used in the lighting apparatus of FIG. 1.

FIG. 4b is a side view illustrating an exemplary embodiment of a door base used in the door of FIG. 4a.

FIG. 4c is a perspective view illustrating an exemplary embodiment of the coupling of a lens and a gasket used in the door of FIG. 4a.

FIG. 4d is a perspective view illustrating an exemplary embodiment of the lens of FIG. 4c coupled to the gasket of FIG. 4c.

FIG. 4e is a perspective view illustrating an exemplary embodiment of the lens, gasket, and door base of FIG. 4a coupled together.

FIG. 4f is a cross sectional view illustrating an exemplary embodiment of the door of FIG. 4e.

FIG. 4g is a side view illustrating an exemplary embodiment of the door base of FIG. 4b being coupled to the chassis base of FIG. 2b.

FIG. 4h is a side view illustrating an exemplary embodiment of the door base of FIG. 4b being coupled to the chassis base of FIG. 2b.

FIG. 4i is a side view illustrating an exemplary embodiment of the door base of FIG. 4b being coupled to the chassis base of FIG. 2b.

FIG. 4j is a side view illustrating an exemplary embodiment of the door base of FIG. 4b coupled to the chassis base of FIG. 2b.

FIG. 4k is a side view illustrating an exemplary embodiment of the door base of FIG. 4b coupled to the chassis base of FIG. 2b.

FIG. 4l is a side view illustrating an exemplary embodiment of the door base of FIG. 4b coupled to the chassis base of FIG. 2b.

FIG. 4m is a cross sectional view illustrating an exemplary embodiment of the door of FIG. 4f being secured to the lighting device chassis of FIG. 2c.

FIG. 4n is a cross sectional view illustrating an exemplary embodiment of the door of FIG. 4f secured to the lighting device chassis of FIG. 2c.

FIG. 5a is a cross sectional view illustrating an exemplary embodiment of a support arm used in the lighting apparatus of FIG. 1.

FIG. 5b is a side view illustrating an exemplary embodiment of the support arm of FIG. 5a coupled to the lighting device chassis of FIG. 2c.

FIG. 5c is a cross sectional view illustrating an exemplary embodiment of the support arm and the lighting device chassis of FIG. 5b.

FIG. 6a is a graph illustrating an exemplary experimental embodiment of the operation of the lighting apparatus of FIG. 1.

FIG. 6b is a graph illustrating an exemplary experimental embodiment of the operation of the lighting apparatus of FIG. 1.

FIG. 6c is a graph illustrating an exemplary experimental embodiment of the operation of the lighting apparatus of FIG. 1.

FIG. 7a is an exploded view illustrating an exemplary embodiment of a louver member being coupled to the door of FIG. 4a.

FIG. 7b is a perspective view illustrating an exemplary embodiment of the louver member of FIG. 7a coupled to the door of FIG. 4a.

FIG. 7c is a side view illustrating an exemplary embodiment of a coupling member coupling the louver member of FIG. 7a to the door of FIG. 4a.

FIG. 7d is a side view illustrating an exemplary embodiment of a coupling member coupling the louver member of FIG. 7a to the door of FIG. 4a.

DETAILED DESCRIPTION

Referring now to FIG. 1, a lighting apparatus 100 is illustrated. The lighting apparatus 100 includes a lighting device

chassis 200 that houses a reflector member 300. A door 400 is coupled to the lighting device chassis 100. The lighting device chassis 100 is coupled to a chassis support member 500.

Referring now to FIGS. 1, 2a, 2b, and 2c, the lighting device chassis 200 is illustrated. The lighting device chassis 200 includes a chassis base 202 having a pair of side walls 204a and 204b that are coupled together and spaced apart in a substantially V-shaped orientation by a bottom wall 204c. A lighting device housing 206 is defined between the side walls 204a and 204b and the bottom wall 204c. A plurality of end cap coupling members 208a and 208b extend from the side wall 204a, along the length of the chassis base 202, and into the lighting device housing 206. A door support 210 extends from the side wall 204a, along the length of the chassis base 202, and is located adjacent the end cap coupling member 208a. A end cap coupling member 212 extends from the side wall 204b, along the length of the chassis base 202, and into the lighting device housing 206. A cable aperture 214 is defined by the side wall 204b, located adjacent the end cap coupling member 212, and provides access to the lighting device housing 206 through the side wall 204b. A door coupling member 216 is located on the distal end of the side wall 204b adjacent the end cap coupling member 212 and along the length of the chassis base 202. The door coupling member 216 defines a semi-circular door coupling channel 216a along the length of the chassis base 202. A stop member 216b is located adjacent the door coupling channel 216a and along the length of the chassis base 202. An L-shaped support beam 216c extends above the door coupling channel 216a, partially defines the door coupling channel 216a, and is located opposite the door coupling channel 216a from the stop member 216b. In an exemplary embodiment, the chassis base 202 may include a variety of different cross sections that include a door coupling member 216.

A pair of substantially similar end caps 218 are coupled to opposing ends of the chassis base 202, illustrated in FIGS. 2a and 2c. Each end cap 218 includes a front wall 218a and a rear wall 218b that extend from a side wall 218c in a substantially V-shaped orientation. A door support 220 extends between the front wall 218a, the rear wall 218b, and the side wall 218c. An L-shaped door securing member 220a extends from the door support 220 and defines a securing channel 220aa. A door rest 220b extends from the door support 220 and is located adjacent the side wall 218c in a spaced apart orientation from the door securing member 220a. A reflector securing member 220c extends from an edge of the door support 220 opposite the side wall 218c and between the front wall 218a and the rear wall 218b. A chassis coupling member 222a extends from the end cap 218 and is located adjacent the rear wall 218b and the door support 220. A chassis coupling member 222b extends from the end cap 218 and is located adjacent the front wall 218b. A chassis coupling member 222c extends from the end cap 218 and is located adjacent the front wall 218a and the door support 220 in a spaced apart orientation from the chassis coupling member 222b. A conical rotational coupling member 224 extends from a coupling member channel 224 that is defined by the side wall 218c. The rotational coupling member 224 defines a fastener coupler 224b that extends partially through the center of the rotational coupling member 224. A coupling member stop beam 224c extends from the rotational coupling member 224 and along a length of the rotational coupling member 224. The end caps 218 may be coupled to the chassis base 202 using a variety of methods known in the art such as, for example, engaging the chassis coupling members 222a, 222b, and 222c with the end cap coupling members 212, 208b, and 208a, respectively,

and/or welding the end caps 218 to the chassis base 202. In an exemplary embodiment, the end caps 218 may include a variety of different designs other than the substantially V-shaped design illustrated in FIGS. 2a and 2c.

A visor 226 is coupled to the end caps 218 and the chassis base 202. The visor 226 includes a base 226a having a bottom edge 226b that extends between a pair of opposing side edges 226c. The visor may be coupled to the end caps 218 and the chassis base 202 using a variety of methods known in the art such as, for example, positioning the side edges 226c adjacent the front walls 218a of the end caps 218 with the bottom edge 226b adjacent the side wall 204a and the door support 210 of the chassis base 202 and welding the visor 226 to the end caps 218 and the chassis base 202, as illustrated in FIG. 2c. In an embodiment, the base 226a of the visor 226 may define a window for allowing light to pass through the base 226a of the visor 226, and the window may include a variety of translucent materials known in the art.

Referring now to FIGS. 1, 2c, 3a, 3b, 3c, 3d, and 3e, the reflector member 300 is illustrated. The reflector member 300 includes a reflector 302 having a pair of side walls 302a and 302b that are held in a substantially parallel and spaced apart orientation by a first arcuate reflector surface 302c and a second arcuate reflector surface 302d. The first arcuate reflector surface 302c includes a first surface finish and a first reflector edge 302ca. In an exemplary embodiment, the first arcuate reflector surface 302c has an involute shape, as illustrated in FIG. 3b. In an exemplary embodiment, the first arcuate reflector surface 302c has a specular surface finish. In an exemplary embodiment, the first arcuate reflector surface 302c has a Miro 4 surface finish. The second arcuate reflector surface 302d includes a second surface finish that is different from the first surface finish and a second reflector edge 302da. In an exemplary embodiment, the second arcuate reflector surface 302d has a parabolic shape, as illustrated in FIG. 3b. In an exemplary embodiment, the second arcuate reflector surface 302d has a diffuse surface finish. In an exemplary embodiment, the second arcuate reflector surface 302d has a Miro 5 surface finish. A step wall 302e couples the first arcuate reflector surface 302c to the second arcuate reflector surface 302d such that the first reflector edge 302ca is located in a spaced apart orientation from the second reflector edge 302da, as illustrated in FIG. 3b. The side walls 302a and 302b, the first arcuate reflector surface 302c, and the second arcuate reflector surface 302d define a light housing 302f between them. A pair of coupling ledges 304 extend from the side walls 302a and 302b, each coupling ledge 304 defining a pair of bracket couplers 304a and a chassis coupler 304b in a spaced apart orientation along its length. The side wall 302a defines a support member mounting aperture 302aa and a cable passageway 302ab that provide access to the light housing 302f through the side wall 302a.

A pair of brackets 306 are coupled to the reflector 302. Each bracket 306 includes a base 306a having an L-shaped cross section. The base 306a defines a pair of coupling apertures 306b on either end of the base 306a and a fastener channel 306c located between the coupling apertures 306b. A support beam 308 extends from the base 306a, defines a coupling aperture 308a through its center, and includes a support arm 308b that extends substantially perpendicularly from the support beam 308. The brackets 306 may be coupled to the reflector 302 using a variety of methods known in the art such as, for example, positioning a plurality of rivets 310 through the bracket couplers 304a on the coupling ledges 304 of the reflector 302 and through the coupling apertures 306b on the brackets 306, as illustrated in FIGS. 3c and 3d. With the bracket 306 coupled to the reflector 302 adjacent the side wall

302a, the support beam **308** is positioned adjacent the support member mounting aperture **302aa**.

A lighting device support member **312** is coupled to the bracket **306** and extends through the support member mounting aperture **302aa**. The lighting device support member **312** includes an elongated base **312a** having a length **312aa**. The base **312a** defines a pair of support channels **312b** located on opposite sides of the base **312a** and running along the length of the base **312a**. A fastener channel **312c** is also defined by the base **312a**, is centrally located on the base **312a** between the support channels **312b**, and runs along the length of the base **312a**. The lighting device support member **312** is positioned in the support member mounting aperture **302aa** and coupled to the bracket **306** partially due to the support arm **308b** on the support beam **308** being positioned in the support channel **312b**, as illustrated in FIGS. **3c** and **3d**.

A lighting device **314** is coupled to the lighting device support member **312** and positioned in the light housing **302f**. The lighting device **314** includes a lamp **314a** having a cable **314b** that extends from the lamp **314a** and is operable to provide power to the lamp **314a**. A bracket **314c** is coupled to the lamp **314a** and includes a support beam **314ca** that extends from the bracket **314c**. The support beam **314ca** defines a fastener coupler **314cb** and includes a support arm **314cc** that extends substantially perpendicularly from the support beam **314ca**. The lighting device **314** is coupled to the lighting device support member **312** by positioning the support arm **314cc** on the bracket **314c** in the support channel **312b** on the lighting device support member **312** and positioning a fastener **316** through the fastener coupler **314cb** on the bracket **314c**, the fastener channel **312c** on the lighting device support member **312**, and the coupling aperture **308a** on the bracket **306**, illustrated in FIGS. **3c** and **3d**. The fastener **316** also helps to couple the bracket **306** to the lighting device support member **312**. The cable **314b** from the lighting device **314** may exit the light housing **302f** through the cable passageway **302ab**, as illustrated in FIG. **3c**, and be connected to a conventional power supply known in the art. In an exemplary embodiment, with the lighting device **314** coupled to the lighting device support member **312**, the lamp **314a** is centrally positioned in the light housing **302f**. The positioning of the lighting device **314** with the lighting device support member **312** allows the lamp **314a** to be precisely positioned in the light housing **302f** without the need for any support members extending from or through the first arcuate reflector surface **302c** and the second arcuate reflector surface **302d** such that there are no structures or apertures on or in the first arcuate reflector surface **302c** and the second arcuate reflector surface **302d** that might provide interference between the lamp **314a** and the first arcuate reflector surface **302c** and the second arcuate reflector surface **302d**. The positioning of the support arms **308b** and **314cc** on the brackets **306** and **314c**, respectively, in the support channels **312b** on the lighting device support member **312** and the positioning of the lighting device support member **312** in the support member mounting aperture **302aa** prevent rotation of the lamp **314a** and the lighting device **314**. In an exemplary embodiment, the lighting device support member **312** provides a heat sink for the light **314** during the operation of the light **314**. In an exemplary embodiment, the use of the lighting device support member **312** and the brackets **306** and **314c** provide a lighting device mount with less parts than a conventional lighting device mount such that the tolerance circuit for the lighting device mount is lowered. In an exemplary embodiment, the length **312aa** of the lighting device support member **312** may be varied depending on desired positioning of the lamp **314a** along the length of the horizontal axis of the reflector **302**. In

an exemplary embodiment, the side wall **302b** may define apertures similar to those defined by side wall **302a**, and a lighting device support member similar to the lighting device support member **312** may be coupled to and/or extend from the side wall **302b** in order to provide additional support for the lighting device from the side wall **302b**.

The reflector member **300** is coupled to the lighting device chassis **200** by positioning the reflector member **300** in the lighting device housing **206** on the lighting device chassis **200** such that the chassis couplers **304b** defined by the coupling ledges **304** on the reflector member **300** are positioned immediately adjacent the reflector securing members **220c** defined by the end caps **218** on the lighting device chassis **200**. A plurality of fasteners **318** are then positioned in the chassis couplers **304b** and the reflector securing members **220c** to secure the reflector member **300** to the lighting device chassis **200**, as illustrated in FIG. **3e**. In operation, the first arcuate reflector surface **302c** with the first surface finish is designed to direct light away from the reflector member **300** at any angle while the second arcuate reflector surface **302d** with the second surface finish is designed to diffuse light from the reflector member **300**.

Referring now to FIGS. **4a**, **4b**, **4c**, **4d**, **4e**, **4f**, **4g**, **4h**, **4i**, **4j**, **4k**, **4l**, **4m**, and **4n**, the door **400** is illustrated. The door **400** includes a base **402** having a top surface **402a**, a bottom surface **402b** located opposite the top surface **402a**, a front edge **402c** extending between the top surface **402a** and the bottom surface **402b**, a rear edge **402d** located opposite the front edge **402c** and extending between the top surface **402a** and the bottom surface **402b**, and a pair of opposing side edges **402e** extending between the top surface **402a**, the bottom surface **402b**, the front edge **402c**, and the rear edge **402d**. A light passageway **404** is defined by the base **402** and extends through the base **402** from the top surface **402a** to the bottom surface **402b**. A plurality of securing channels **406** are defined by the base **402**, extend through the base **402** from the top surface **402a** to the bottom surface **402b**, and are located adjacent the sides walls **402e** on either side of the light passageway **404**. A louver channel **408a** and a louver channel **408b** are defined by the base **402** and located adjacent the opposing side edges **402e**. A door support **410** extends from the front edge **402c** of the base **402** and along a length of the base **402** in a substantially perpendicular orientation to the base **402**.

A chassis coupling member **412** extends from the rear edge **402d** of the base **402** and along a length of the base **402** in a substantially perpendicular orientation to the base **402**. The chassis coupling member **412** includes an arcuate distal end **412a** that defines a coupling channel **412b**. A stop member **412c** extends from the arcuate distal end **412a** and is located opposite the coupling channel **412b**. A stop surface **412d** is included on the chassis coupling member **412** and located adjacent the arcuate distal end **412a**.

A latch **414** and a latch actuator **416** are coupled to each securing channel **406** by a plurality of fasteners **418** that engage the latch **414** and the latch actuator **416** such that the latch actuators **416** are positioned adjacent the top surface **402a** of the base **402** and the latches **414** are positioned adjacent the bottom surface **402b** of the base **402**, illustrated in FIGS. **4a**, **4e** and **4f**. Each latch **414** includes an arcuate distal end **414a** located opposite its connection to the latch actuator **416**.

A rectangular gasket **420** and a rectangular lens **422** are coupled to each other and the base **402**. The gasket **420** includes a rectangular base **420a** that defines a rectangular light passageway **420b** through its center. A rectangular lens mounting channel **420c** is defined by a first channel surface

420d and a second channel surface **420e** on the base **420a** and located adjacent the perimeter of the light passageway **420b**. In an exemplary embodiment, the first channel surface **420d** is substantially perpendicular to the second channel surface **420e**. The lens **422** includes a first lens surface **422a** and a second lens surface **422b** that is substantially perpendicular to the first lens surface **422a** and located about the perimeter of the lens **422**. The lens **422** is positioned in the lens mounting channel **420c** such that a portion of the first lens surface **422a** engages the first channel surface **420d** and the second lens surface **422b** engages the second channel surface **420e**, illustrated in FIGS. **4c** and **4d**. The lens **422** may be coupled to the gasket **420** using a variety of methods known in the art such as, for example, adhesives. The gasket **420** is then positioned adjacent the bottom surface **402b** of the base **402** such that the light passageway **420b** defined by the gasket **420** is substantially aligned with the light passageway **404** defined by the base **402** and between the latches **414**, illustrated in FIGS. **4e** and **4f**. The gasket **420** may be coupled to the base **402** using a variety of methods known in the art such as, for example, adhesives. In operation, the surfaces **420e** on the gasket **420** prevent light from escaping from the lens **422** through the second lens surface **422b**. Furthermore, the gasket **420** eliminates the need for a frame coupled to the lens **422** to prevent light from escaping from second lens surface **422b** on the lens **422**.

The door **400** is operable to pivotally couple to and decouple from the lighting device chassis **200**. The door **400** may be pivotally coupled to the lighting device chassis **200** by first positioning the door **400** in a position A, illustrated in FIG. **4g**, such that the chassis coupling member **412** on the door **400** is positioned adjacent the door coupling member **216** on the lighting device chassis **200** and the door support **410** on the door **400** is positioned adjacent the door support **210** on the lighting device chassis **200**. The door **400** is then moved in a direction B such that a portion of the arcuate distal end **412a** of the chassis coupling member **412** enters the door coupling channel **216a** and the door **400** is in a position C, illustrated in FIG. **4h**. The door **400** is then moved in a direction D such that a portion of the support beam **216c** enters the coupling channel **412b** and the stop member **412c** on the chassis coupling member **412** may clear the stop member **216b** on the door coupling member **216** when the door **400** is rotated about the support beam **216c** into a position E, illustrated in FIG. **4i**.

The door **400** is then moved in a direction F such that door **400** is in a position G with the stop member **216b** and the arcuate distal end **412a** of the chassis coupling member **412** positioned in the door coupling channel **216a**, as illustrated in FIG. **4j**. In the position G, the door **400** is coupled to the lighting device chassis **200** in an open position, and the stop surface **412d** on the door **400** will engage the side wall **204b** to prevent over-rotation of the door **400**. With the stop member **412c** and the arcuate distal end **412a** of the chassis coupling member **412** positioned in the door coupling channel **216a**, the door **400** may now be rotated about the door coupling channel **216a** into a position H, illustrated in FIGS. **4k** and **4l**. In the position H, the door **400** is coupled to the lighting device chassis **200** in a closed position, and the stop member **412c** on the chassis coupling member **412** engages the stop member **216b** on the door coupling member **216** to prevent the chassis coupling member **412** from decoupling from the door coupling member **216**, illustrated in FIGS. **4k** and **4l**. Also, in the position H, the chassis coupling member **412** engages the support beam **216c** on the lighting device chassis **200** and the door support **410** on the door **400** may engage the door support **210** on the lighting device chassis

200. The door **400** may then be decoupled from the lighting device chassis **200** by reversing the steps shown in FIGS. **4g**, **4h**, **4i**, **4j**, and **4k**. Thus, the door **400** is provided that may be pivotally coupled to the lighting device chassis **200** without a hinge and removed from the lighting device chassis **200** by manipulating the door **400** as described above in FIGS. **4g**, **4h**, **4i**, **4j**, and **4k**.

With the door **400** in the position H, the gasket **420** engages the chassis base **202** and the door supports **220** on the lighting device chassis **200**, and the latches **414** on the door **400** are positioned adjacent the door securing members **220a** on the lighting device chassis **200**, as illustrated in FIG. **4m**. The door **400** may then be secured to the lighting device chassis **200** free of the use of a tool by applying a force to the top surface **402a** of the base **402** on the door **400** in order to compress the gasket **420** such that the latches **414** may be moved by the latch actuators **416** in a direction I to position the arcuate distal ends **414a** on the latches **414** in the securing channels **220aa** on the lighting device chassis **200**, illustrated in FIG. **4n**. The compressing of the gasket **420** before positioning the arcuate distal ends **414a** in the securing channels **220aa** provides a tight seal between the door **400** and the lighting device chassis **200** upon the engagement of the latches **414** and the door securing members **220a**. In an exemplary embodiment, the gasket **420** includes a compression/depression ratio such that a liquid tight seal is provided between the door **400** and the lighting device chassis **200** while still allowing engagement of the latches **414** and the door securing members **220a**. Furthermore, upon release of the latches **414** from the door securing members **220a**, the gasket **420** is allowed to expand, which pushes the door **400** away from the lighting device chassis **200** in order to allow access to the front edge **402c** of the door **400** such that the door **400** may be opened.

Referring now to FIGS. **1**, **5a**, **5b**, and **5c**, the chassis support member **500** is illustrated. The chassis support member **500** includes a support arm **502** that extends from the chassis support member **500** and includes a distal end **502a**. A conical rotational coupling member passageway **504** is defined by the support arm **502** and located adjacent the distal end **502a** of the support arm **502**. A support arm stop beam **506** extends from the support arm **502** and into the rotational coupling member passageway **504**.

The chassis support member **500** is coupled to the lighting device chassis **200** by positioning the rotational coupling member **224** on lighting device chassis **200** in the rotational coupling member passageway **504**, illustrated in FIGS. **5b** and **5c**. A cap **508** defining a coupling aperture **508a** is then placed on the support arm **502** such that the coupling aperture **508a** is aligned with the fastener coupler **224b** on the rotational coupling member **224**. A fastener **510** is then positioned in the coupling aperture **508a** and the fastener coupler **224b**, illustrated in FIG. **5c**. The lighting device chassis **200** is now coupled to the support arm **502** and the chassis support member **500** and may rotate about the rotational coupling of the rotational coupling member **224** and the support arm **502**. However, due to the coupling member stop beam **224c** on the rotational coupling member **224** and the support arm stop beam **506** on the chassis support member **500**, the lighting device chassis **200** may not rotate beyond the point where the coupling member stop beam **224c** engages the support arm stop beam **506**. In an exemplary embodiment, the support arm stop beam **506** may be positioned such that the lighting device chassis **200** may not rotate beyond a predetermined point such as, for example, the point where the lighting device chassis **200** would be directing light at the chassis support member **500** or on a wall that the chassis support member **500** is

and

Vert. Angles	Horizontal Angles						
	225	247.5	270	292.5	315	337.5	360
0	9401	9401	9401	9401	9401	9401	9401
2.5	10170	9752	9450	9278	9148	9120	9206
5	11004	10155	9609	9321	9177	9177	9378
7.5	12212	10759	9738	9436	9364	9378	9220
10	13535	11407	9882	9494	9594	8918	8501
12.5	14902	12169	9896	9522	9206	8357	7954
15	16268	12974	9925	9652	8659	7983	7523
17.5	17103	13838	9939	9709	8113	7667	7178
20	17117	14672	9939	9479	7825	7264	6775
22.5	16628	15693	10026	9004	7537	6861	6430
25	15707	16686	10054	8630	7221	6502	6156
27.5	14427	17534	10026	8314	6847	6185	5826
30	12672	17937	10011	7998	6617	5854	5538
32.5	10918	17951	9997	7854	6502	5538	5293
35	9091	17793	10054	7652	6487	5265	5135
37.5	7192	17390	9983	7595	6458	5034	5063
40	5610	16743	9680	7393	6530	4919	5006
42.5	4229	16139	9335	7322	6617	4804	4963
45	3179	15592	8501	6458	6689	4689	4819
47.5	2388	13464	8098	5754	6775	4502	4617
50	1755	10903	8199	4991	6689	4330	4286
52.5	1295	8314	8645	3970	6617	4071	3093
55	949	6156	8256	4919	6574	3150	1496
57.5	690	4330	7264	5710	6329	1553	647
60	489	3049	6530	5423	5595	734	345
62.5	374	2086	5955	4963	3423	374	259
65	302	1424	5495	4488	1496	288	173
67.5	245	892	4847	4200	403	216	129
70	187	547	3956	3884	273	144	86
72.5	173	345	2992	2877	173	86	58
75	144	216	1784	1338	115	58	29
77.5	129	158	1021	288	72	29	14
80	115	129	575	115	43	29	14
82.5	101	101	259	72	29	14	14
85	72	86	86	43	29	14	14
87.5	58	58	43	29	14	14	0
90	0	0	0	0	0	0	0

The zonal lumen summary for experimental embodiment 604 was as follows:

Zone	Lumens	% Lamp	% Fixt	
5	0-30	9019.74	27.3	37.6
	0-40	14137.33	42.8	59
	0-60	22036.11	66.8	92
	0-90	23962.61	72.6	100
10	90-120	0	0	0
	90-130	0	0	0
	90-150	0	0	0
	90-180	0	0	0
	0-180	23962.61	72.6	100

Total Luminaire Efficiency = 72.6%

and

Zone	Lumens	
20	0-10	997.61
	10-20	3262.69
	20-30	4759.44
25	30-40	5117.58
	40-50	4724.15
	50-60	3174.64
	60-70	1422.88
	70-80	440.16
	80-90	63.47
30	90-100	0
	100-110	0
	110-120	0
	120-130	0
	130-140	0
	140-150	0
35	150-160	0
	160-170	0
	170-180	0

The coefficients of utilization for experimental embodiment 604, using the zonal cavity method and with an effective floor cavity reflectance of 0.20, was as follows:

	RC																	
	80		70		50		30		10		0							
	RW																	
	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	86	86	86	86	84	84	84	84	81	81	81	77	77	77	74	74	74	73
1	81	78	75	73	79	76	74	72	73	71	70	71	69	68	68	67	66	64
2	75	70	66	62	73	68	65	62	66	63	60	64	61	59	62	59	58	56
3	69	63	58	54	67	61	57	53	59	55	52	57	54	51	56	53	50	49
4	64	56	51	47	62	55	50	46	54	49	46	52	48	45	51	47	45	43
5	59	51	45	41	58	50	45	41	49	44	40	47	43	40	46	42	40	38
6	55	46	41	36	54	46	40	36	44	40	36	43	39	36	42	38	35	34
7	51	42	37	33	50	42	36	32	41	36	32	40	35	32	39	35	32	30
8	48	39	33	29	47	38	33	29	37	33	29	37	32	29	36	32	29	27
9	45	36	30	27	44	35	30	27	35	30	26	34	29	26	33	29	26	25
10	42	33	28	24	41	33	28	24	32	27	24	31	27	24	31	27	24	23

and

Vert. An-gles	Horizontal Angles						
	225	247.5	270	292.5	315	337.5	360
0	10063	10063	10063	10063	10063	10063	10063
2.5	10903	10515	10155	9724	9364	9163	9076
5	11450	10889	10227	9465	8832	8472	8343
7.5	12140	11234	10285	9220	8285	7854	7695
10	12903	11637	10357	8976	7897	7365	7235
12.5	13607	12068	10457	8746	7508	6933	6746
15	14125	12586	10558	8515	7178	6588	6415
17.5	14542	13061	10659	8314	6890	6300	6099
20	14701	13564	10831	8170	6674	6027	5854
22.5	14600	13981	11033	8084	6502	5826	5667
25	14168	14413	11191	8012	6401	5653	5452
27.5	13449	14715	11335	7954	6286	5466	5279
30	12529	14888	11407	7854	6200	5308	5092
32.5	11248	14902	11363	7724	6113	5135	4905
35	9810	14758	11205	7508	6041	4934	4689
37.5	8357	14470	10874	7206	5926	4732	4473
40	7106	13924	10357	6847	5797	4502	4258
42.5	5840	13118	9738	6458	5624	4272	3999
45	4689	12068	9163	5941	5437	4056	3711
47.5	3754	10946	8630	5437	5193	3797	3423
50	3049	9522	8113	4919	4876	3452	3035
52.5	2417	8113	7595	4617	4531	3136	2560
55	1913	6804	7019	4330	4128	2647	1999
57.5	1525	5610	6387	4013	3654	2129	1553
60	1223	4589	5696	3639	3164	1683	1223
62.5	993	3812	5006	3236	2675	1338	964
65	820	3064	4330	2805	2201	1050	719
67.5	676	2445	3711	2445	1812	849	547
70	561	1913	3035	2057	1410	647	403
72.5	460	1510	2402	1683	1079	475	302
75	374	1122	1827	1352	791	360	201
77.5	273	806	1280	1007	532	230	129
80	201	532	863	676	345	144	86
82.5	144	331	503	403	187	72	43
85	101	173	230	187	86	43	29
87.5	58	58	72	58	29	14	14
90	0	0	0	0	0	0	0

The zonal lumen summary for experimental embodiment 604 was as follows:

Zone	Lumens	% Lamp	% Fixt
0-30	8525.99	25.8	36.2
0-40	13577.78	41.1	57.6
0-60	21049.5	63.8	89.3
0-90	23577.69	71.4	100
90-120	0	0	0
90-130	0	0	0
90-150	0	0	0
90-180	0	0	0
0-180	23577.69	71.4	100

Total Luminaire Efficiency = 71.4%

and

Zone	Lumens
0-10	972.53
10-20	2977.05
20-30	4576.41
30-40	5051.79
40-50	4410.09
50-60	3061.63
60-70	1684.64
70-80	709.24
80-90	134.3
90-100	0
100-110	0
110-120	0
120-130	0
130-140	0
140-150	0
150-160	0
160-170	0
170-180	0

The coefficients of utilization for experimental embodiment 604, using the zonal cavity method and with an effective floor cavity reflectance of 0.20, was as follows:

RC																				
RW																				
	80	70	50	30	10	0	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	85	85	85	85	83	83	83	83	79	79	79	76	76	76	73	73	73	73	71	
1	79	76	74	71	77	75	72	70	72	70	68	69	67	66	66	65	64	63		
2	73	68	64	60	71	67	63	60	64	61	58	62	59	57	60	58	56	54		
3	67	61	56	52	66	60	55	51	58	54	50	56	52	49	54	51	49	47		
4	62	55	49	45	61	54	48	44	52	47	44	50	46	43	49	46	43	41		
5	58	49	44	39	56	49	43	39	47	42	39	46	42	38	44	41	38	36		
6	53	45	39	35	52	44	39	35	43	38	34	42	37	34	41	37	34	32		
7	50	41	35	31	49	40	35	31	39	34	31	38	34	31	37	33	30	29		
8	47	38	32	28	45	37	32	28	36	31	28	35	31	28	34	30	27	26		
9	44	35	29	25	43	34	29	25	33	29	25	33	28	25	32	28	25	24		
10	41	32	27	23	40	32	27	23	31	26	23	30	26	23	30	26	23	22		

Referring now to FIG. 6c, in an exemplary experimental embodiment 608, a 400 Watt metal halide light was used for the lamp 314a. A candela plot 610 was generated when power was supplied to the lamp 314a. The lighting apparatus 100 of exemplary experimental embodiment 608 included a plot with a pair of peaks 610a and 610b. This was an unexpected result. The peaks 610a and 610b allow a plurality of lighting apparatus 100 to be spaced further apart than a plurality of conventional lighting apparatus while providing an equal amount of light.

Referring now to FIGS. 7a, 7b, 7c, and 7d, in an alternative embodiment, a louver member 700 is coupled to the door 400. The louver member 700 includes a first support beam 702 that is held in a substantially parallel and spaced apart orientation from a second support beam 704 by a plurality of louvers 706. The first support beam 702 includes a pair of opposing ends 702a and 702b and defines a first chassis channel 702c that runs along the length of the first support beam 702 from the end 702a to the end 702b. A first clip coupling member 702d extends from the first support beam 702 adjacent the end 702a and defines an chassis edge channel 702da. A first clip coupling member 702e extends from the first support beam 702 adjacent the end 702b and defines an chassis edge channel 702ea. The second support beam 704 includes a pair of opposing ends 704a and 704b and defines a second chassis channel 704c that runs along the length of the second support beam 704 from the end 704a to the end 704b. A fastener coupler 704d is defined by the second support member 704 and located adjacent the end 704a of the second support member 704. A fastener coupler 704e is defined by the second support member 704 and located adjacent the end 704b of the second support member 704. A pair of coupling devices 708 are operable to couple to the second support member 704. Each coupling device 708 includes a second clip coupling member 708a that defines a chassis edge channel 708b. A fastener coupler 708c is defined by each coupling device 708 and located adjacent the second clip coupling member 708a.

The louver member 700 is coupled to the door 400 by positioning the front edge 402c of the base 402 on door 400 in the chassis edge channels 702da and 702ea on the first coupling members 702d and 702e, illustrated in FIGS. 7b and 7c. With the front edge 402c of the base 402 on door 400 in the chassis edge channels 702da and 702ea, the base 402 becomes partially located in the first chassis channel 702c and the second chassis channel 704c. One of the coupling devices 708 is then positioned on the second support beam 704 such that the second clip coupling member 708a is positioned in the louver channel 408a on the base 402 of door 400 with the base 402 of the door 400 positioned in the chassis edge channel 708b, illustrated in FIGS. 7b and 7d. One of the coupling devices 708 is then positioned on the second support beam 704 such that the second clip coupling member 708a is positioned in the louver channel 408b on the base 402 of door 400 with the base 402 of the door 400 positioned in the chassis edge channel 708b, illustrated in FIG. 7b. A pair of fasteners 710 are then positioned in the fasteners couplers 708c on the coupling devices 708 and in the fastener couplers 704d and 704e on the second support beam 704 in order to couple the coupling devices 708 to the louver member 700 such that the louver member 700 is coupled to the base 402 of the door 400. Thus, an apparatus is provided that allows the louver member 700 to be coupled to the door 400 without modification to the door 400 such as, for example, drilling threaded channels in the door 400 in order to couple the louver member 700 to the door 400. In an exemplary embodiment, the height and spacing of the louvers 706 determines the cutoff angle of the lighting apparatus 100.

A lighting apparatus has been described that includes a lighting device chassis defining a lighting device housing, a reflector member located in the lighting device housing and comprising a first arcuate reflector surface and a second arcuate reflector surface, a lighting device extending from a side wall of the reflector member and positioned adjacent the first arcuate reflector surface and the second arcuate reflector surface, a door coupled to the lighting device chassis, wherein the door is operable to couple to, decouple from, and be secured to the lighting device chassis without the use of a tool, a gasket and a lens coupled to the door, whereby the gasket is operable to prevent light from escaping the lens through a perimeter surface of the lens, and a support member coupled to the lighting device chassis, whereby the support member is operable to prevent the lighting device chassis from rotating with respect to the support member.

A lighting apparatus has been described that includes means for housing a means for reflecting light, means for reflecting light housed in the means for housing a means for reflecting light, means for providing light located in the means for reflecting light, a door coupled to the means for housing a means for reflecting light, wherein the door comprises means for allowing the door to couple to, decouple from, and be secured to the means for housing a means for reflecting light without the use of a tool, means for sealing the door to the means for housing a means for reflecting light, whereby the means for sealing comprises means for preventing light from escaping a perimeter surface of a lens, and means for supporting the means for housing a means for reflecting light, whereby the means for supporting comprises means for preventing the means for housing a means for reflecting light from rotating with respect to the means for supporting the means for housing a means for reflecting light.

A method for providing light has been described that includes providing a lighting device housing that houses a reflector member and a lighting device, whereby the lighting device housing is coupled to a support member, coupling a door to the lighting device housing without the use of a tool, securing the door to the lighting device housing without the use of a tool, providing a seal between the door and the lighting device chassis with a gasket, rotating the lighting device housing relative to the support member, preventing the lighting device housing from rotating relative to the support member by engaging the support member and the lighting device housing, and providing light with the lighting device through a lens positioned in the door, whereby the gasket prevent light from escaping from a perimeter surface of the lens.

A lighting apparatus has been described that includes a lighting device chassis defining a lighting device housing and comprising a rotational coupling member, a reflector member located in the lighting device housing, the reflector member comprising a side wall, a first arcuate reflector surface extending from the side wall and comprising a first surface finish and a first reflector edge, a second arcuate reflector surface extending from the side wall and comprising a second surface finish and a second reflector edge, whereby the second arcuate reflector surface is positioned adjacent the first arcuate reflector surface such that the second reflector edge is located in a spaced apart orientation from the first reflector edge; and a lighting device support member extending from the side wall, a lighting device coupled to the lighting device support member and positioned by the lighting device support member adjacent the first arcuate reflector surface and the second arcuate reflector surface, a door coupled to the lighting device chassis, wherein the door is operable to couple to, decouple from, and be secured to the lighting device chassis without the

use of a tool, whereby the door comprises a latch moveably coupled to the door, whereby the latch is operable to move into engagement with the lighting device chassis to secure the door to the lighting device chassis, a chassis coupling member extending along a length of the door, a coupling channel defined by the chassis coupling member, and a stop member extending from the chassis coupling member, a gasket and a lens coupled to the door, wherein the gasket is operable to prevent light from escaping the lens through a perimeter surface of the lens, whereby the gasket includes a first light passageway defined by the gasket, and a lens mounting channel defined by the gasket, located adjacent a perimeter of the first light passageway, and comprising a first channel surface and a second channel surface, whereby the lens is located in the lens mounting channel, a support member coupled to the lighting device chassis, whereby the support member comprises a rotational coupling member passageway defined by the support arm, whereby the rotational coupling member is positioned in the rotational coupling member passageway, and a support arm stop beam extending from the support arm and into the rotational coupling member passageway, a louver member, at least one first coupling member extending from the louver member, and at least one second coupling member that is operable to couple to the louver member and engage the door in order to couple the louver member to the door.

A lighting apparatus has been described that includes a reflector member, comprising a side wall, a reflector surface extending from the side wall, a lighting device support member extending from the side wall, and a lighting device coupled to the lighting device support member and positioned by the lighting device support member adjacent the reflector surface. In an exemplary embodiment, a mounting aperture is defined by the side wall, wherein the lighting device support member extends through the mounting aperture. In an exemplary embodiment, a first bracket is secured to the side wall and coupled to the lighting device support member, and a second bracket is secured to the lighting device and coupled to the lighting device support member. In an exemplary embodiment, the lighting device support member defines at least one support channel. In an exemplary embodiment, the first bracket includes a support arm positioned in the at least one support channel. In an exemplary embodiment, the second bracket includes a support arm positioned in the at least one support channel. In an exemplary embodiment, the lighting device support member provides a heat sink for the lighting device. In an exemplary embodiment, the lighting device support member comprises dimensions such that the lighting device is positioned at approximately the center of the reflector member.

A lighting apparatus has been described that includes means for reflecting light, including means for supporting a means for reflecting light, means for reflecting light extending from the means for supporting a means for reflecting light, means for supporting a means for providing light extending from the means for supporting a means for reflecting light, and means for providing light coupled to the means for supporting a means for providing light and positioned by the means for supporting a means for providing light adjacent the means for reflecting light. In an exemplary embodiment, the apparatus further includes means for allowing the means for supporting a means for providing light to extend through the means for supporting a means for reflecting light. In an exemplary embodiment, the apparatus further includes means for securing the means for supporting a means for providing light to the means for supporting a means for reflecting light, and means for securing the means for providing light to the means for supporting a means for providing light. In an exemplary

embodiment, the means for supporting a means for providing light provides a means for dissipating heat from the means for providing light. In an exemplary embodiment, the means for supporting a means for providing light comprises dimensions such that the means for providing light is positioned at approximately the center of the means for reflecting light.

A method for reflecting light has been described that includes providing a reflector member comprising a side wall and a reflector surface extending from the side wall, positioning a lighting device adjacent the reflector surface by coupling the lighting device to a lighting device support member and extending the lighting device support member from the side wall, activating the lighting device, and reflecting light from the lighting device from the reflector surface. In an exemplary embodiment, the positioning comprises positioning the lighting device at approximately the center of the reflector member. In an exemplary embodiment, the method further comprises preventing rotation of the lighting device with the coupling of the lighting device to the lighting device support member. In an exemplary embodiment, the method further comprises dissipating heat from the lighting device with the lighting device support member.

A lighting apparatus has been described that includes a reflector member, including a side wall defining a mounting aperture, a reflector surface extending from the side wall, a lighting device support member extending from the side wall through the mounting aperture and defining at least one support channel, a first bracket secured to the side wall and coupled to the lighting device support member, wherein the first bracket includes a support arm positioned in the at least one support channel, a lighting device coupled to the lighting device support member and positioned by the lighting device support member adjacent the reflector surface, wherein the lighting device support member comprises dimensions such that the lighting device is positioned at approximately the center of the reflector member, and a second bracket secured to the lighting device and coupled to the lighting device support member, wherein the second bracket includes a support arm positioned in the at least one support channel.

A lighting apparatus has been described that includes means for reflecting light, including means for supporting a means for reflecting light, means for reflecting light extending from the means for supporting a means for reflecting light, means for supporting a means for providing light extending from the means for supporting a means for reflecting light, means for securing the means for supporting a means for providing light to the means for supporting a means for reflecting light, means for allowing the means for supporting a means for providing light to extend through the means for supporting a means for reflecting light, and means for providing light coupled to the means for supporting a means for providing light and positioned by the means for supporting a means for providing light adjacent the means for reflecting light, wherein the means for supporting a means for providing light comprises dimensions such that the means for providing light is positioned at approximately the center of the means for reflecting light, means for securing the means for providing light to the means for supporting a means for providing light.

A method for reflecting light has been described that includes providing a reflector member comprising a side wall and a reflector surface extending from the side wall, positioning a lighting device adjacent the reflector surface by coupling the lighting device to a lighting device support member and extending the lighting device support member from the side wall, wherein the positioning comprises positioning the lighting device at approximately the center of the reflector

member, preventing rotation of the lighting device with the coupling of the lighting device to the lighting device support member, activating the lighting device, reflecting light from the lighting device from the reflector surface, and dissipating heat from the lighting device with the lighting device support member.

A lighting apparatus has been described that includes a chassis operable to house a lighting device, a door moveably coupled to the chassis, and a latch moveably coupled to the door, whereby the latch is operable to move into engagement with the chassis to secure the door to the chassis. In an exemplary embodiment, the door comprises a gasket that is operable to engage the chassis to provide a seal between the door and the chassis. In an exemplary embodiment, the gasket compresses against the chassis upon engagement with the chassis and prior to the latch becoming operable to move into engagement with the chassis. In an exemplary embodiment, the chassis comprises a latch engagement feature, whereby the latch is operable to move into engagement with the latch engagement feature to secure the door to the chassis. In an exemplary embodiment, the latch engagement feature defines a latch channel that is operable to couple the latch to the latch engagement feature. In an exemplary embodiment, the latch includes a distal end that is operable to become positioned in the latch channel upon the coupling of the latch with the latch engagement feature. In an exemplary embodiment, the door provides access to a lighting device housing defined by the chassis. In an exemplary embodiment, a latch actuator is located adjacent a first surface on the door and coupled to the latch, wherein the latch is located adjacent a second surface on the door and operable to be actuated into engagement with the chassis by the latch actuator. In an exemplary embodiment, the first surface is located opposite the second surface on the door. In an exemplary embodiment, the door is pivotally coupled to the chassis. In an exemplary embodiment, the latch is slideably coupled to the door.

A lighting apparatus has been described that includes means for housing a lighting device, a door moveably coupled to the means for housing a lighting device; and means for securing the door to the means for housing a lighting device free of the use of a tool. In an exemplary embodiment, the door comprises a means for providing a seal between the door and the means for housing a lighting device. In an exemplary embodiment, the means for providing a seal compresses against the means for housing a lighting device upon engagement with the means for housing a lighting device and prior to the means for securing the door becoming operable to secure the door to the means for housing a lighting device. In an exemplary embodiment, the means for housing a lighting device comprises a means for engaging the means for securing the door, whereby the means for securing the door is operable to move into engagement with the means for engaging the means for securing the door to secure the door to the means for housing a lighting device. In an exemplary embodiment, the means for engaging the means for securing the door defines a channel that is operable to couple the means for securing the door to the means for engaging the means for securing the door. In an exemplary embodiment, the means for securing the door includes a distal end that is operable to become positioned in the channel upon the coupling of the means for securing the door with the means for engaging the means for securing the door. In an exemplary embodiment, the door provides access to a lighting device housing defined by the means for housing a lighting device. In an exemplary embodiment, the apparatus further includes a means for actuating the means for securing the door located adjacent a first surface on the door and coupled to the means for securing the

door, wherein the means for securing the door is located adjacent a second surface on the door and operable to be actuated into engagement with the means for housing a lighting device by the means for actuating the means for securing the door. In an exemplary embodiment, the first surface is located opposite the second surface on the door. In an exemplary embodiment, the door is pivotally coupled to the means for housing a lighting device. In an exemplary embodiment, the means for securing the door is slideably coupled to the door.

A method for securing a door to a lighting device chassis has been described that includes providing a lighting device chassis and a door moveably coupled to the lighting device chassis, and securing the door to the lighting device chassis without the use of a tool. In an exemplary embodiment, the method further includes providing a seal between the door and the lighting device chassis. In an exemplary embodiment, the providing the seal provides opposite forces on the door and the lighting device chassis to enhance the securing of the door to the chassis. In an exemplary embodiment, the securing comprises engaging a latch that is moveably coupled to the door with the lighting device chassis.

A lighting apparatus has been described that includes a chassis operable to house a lighting device and comprising a latch engagement feature, a door pivotally coupled to the chassis and operable to provide access to a lighting device housing defined by the chassis, a gasket that is coupled to the door and operable to engage the chassis to provide a seal between the door and the chassis, and a latch slideably coupled to the door, whereby the latch is operable to move into engagement with the latch engagement feature to secure the door to the chassis, whereby the gasket compresses against the chassis upon engagement with the chassis and prior to the latch becoming operable to move into engagement with the latch engagement feature.

A lighting apparatus has been described that includes means for housing a lighting device, a door pivotally coupled to the means for housing a lighting device and comprising a means for providing a seal between the door and the means for housing a lighting device, wherein the door provides access to a lighting device housing defined by the means for housing a lighting device, and means for securing the door to the means for housing a lighting device free of the use of a tool slideably coupled to the door, whereby the means for providing a seal compresses against the means for housing a lighting device upon engagement with the means for housing a lighting device and prior to the means for securing the door becoming operable to secure the door to the means for housing a lighting device. A method for securing a door to a lighting device chassis has been described that includes providing a lighting device chassis and a door moveably coupled to the lighting device chassis, securing the door to the lighting device chassis without the use of a tool, wherein the securing comprises engaging a latch that is moveably coupled to the door with the lighting device chassis, and providing a seal between the door and the lighting device chassis, wherein the providing the seal provides opposite forces on the door and the lighting device chassis to enhance the securing of the door to the chassis.

A lighting apparatus has been described that includes a door, a chassis coupling member extending along a length of the door, a coupling channel defined by the chassis coupling member, and a stop member extending from the chassis coupling member. In an exemplary embodiment, the door is operable to pivotally couple to a lighting device chassis. In an exemplary embodiment, the chassis coupling member comprises an arcuate distal end that defines the coupling channel.

In an exemplary embodiment, the stop member extends from the chassis coupling member opposite the coupling channel. In an exemplary embodiment, the apparatus further includes a stop surface on the chassis coupling member located adjacent the coupling channel. In an exemplary embodiment, the apparatus further includes a lighting device chassis, whereby the door is operable to pivotally couple to and decouple from the lighting device chassis. In an exemplary embodiment, the lighting device chassis defines a door coupling channel. In an exemplary embodiment, the apparatus further includes a stop member located adjacent the door coupling channel. In an exemplary embodiment, the apparatus further includes a support beam located adjacent the door coupling channel and defining a door coupling channel entrance. In an exemplary embodiment, the door is operable to pivotally couple to and decouple from the lighting device chassis without the use of a tool. In an exemplary embodiment, the door is operable to pivotally couple to and decouple from the lighting device chassis without the use of a fastener. In an exemplary embodiment, the door is operable to pivotally couple to and decouple from the lighting device chassis by manipulating the door relative to the lighting device chassis

A lighting apparatus has been described that includes a door, and means for coupling the door to a means for housing a lighting device. In an exemplary embodiment, the means for coupling the door to a means for housing a lighting device pivotally couples the door to a means for housing a lighting device. In an exemplary embodiment, the means for coupling the door to a means for housing a lighting device comprises a means for allowing the means for coupling the door to a means for housing a lighting device to enter a channel defined by a means for housing a lighting device. In an exemplary embodiment, the means for coupling the door to a means for housing a lighting device comprises a means for preventing the means for coupling the door to a means for housing a lighting device from exiting a channel defined by a means for housing a lighting device. In an exemplary embodiment, the apparatus further includes means for preventing pivoting of the door when the door is coupled to a means for housing a lighting device. In an exemplary embodiment, the apparatus further includes means for housing a lighting device, whereby the door is operable to pivotally couple to and decouple from the means for housing a lighting device. In an exemplary embodiment, the means for housing a lighting device defines a means for allowing the door to couple to the means for housing a lighting device. In an exemplary embodiment, the apparatus further includes means for preventing the door from exiting the means for allowing the door to couple to the means for housing a lighting device. In an exemplary embodiment, the apparatus further includes means for supporting the door located adjacent the means for allowing the door to couple to the means for housing a lighting device. In an exemplary embodiment, the door is operable to pivotally couple to and decouple from the means for housing a lighting device without the use of a tool. In an exemplary embodiment, the door is operable to pivotally couple to and decouple from the means for housing a lighting device by manipulating the door relative to the means for housing a lighting device.

A method for coupling a door to a lighting device chassis has been described that includes providing a door comprising a chassis coupling member, positioning the chassis coupling member in a door coupling channel on a lighting device chassis, and pivotally coupling the door to the lighting device chassis. In an exemplary embodiment, the positioning com-

prises positioning a portion of the chassis in a channel defined by the chassis coupling member in order to allow the chassis coupling member to enter the door coupling channel. In an exemplary embodiment, the pivotally coupling comprises preventing the chassis coupling member from exiting the door coupling channel by engaging a first stop member on the chassis coupling member with a second stop member located adjacent the door coupling channel. In an exemplary embodiment, the pivotally coupling comprises coupling the door to the lighting device chassis without the use of a tool. In an exemplary embodiment, the pivotally coupling comprises coupling the door to the lighting device chassis without the use of a fastener. In an exemplary embodiment, the pivotally coupling comprises coupling the door to the lighting device chassis by manipulating the door relative to the lighting device chassis. In an exemplary embodiment, the method further includes removing the door from the lighting device chassis by manipulating the door relative to the lighting device chassis.

A lighting apparatus has been described that includes a door, a chassis coupling member extending along a length of the door comprising an arcuate distal end that defines a chassis coupling channel and a stop surface located adjacent the chassis coupling channel, a stop member extending from the chassis coupling member opposite the chassis coupling channel, a lighting device chassis defining a door coupling channel and comprising a stop member located adjacent the door coupling channel and a support beam located adjacent the door coupling channel that defines a door coupling channel entrance, whereby the door is operable to pivotally couple to and decouple from the lighting device chassis by manipulating the door relative to the lighting device chassis and without the use of a tool or a fastener.

A lighting apparatus has been described that includes a door, means for housing a lighting device that defines a means for allowing the door to couple to the means for housing a lighting device, means for preventing the door from exiting the means for allowing the door to couple to the means for housing a lighting device, means for supporting the door located adjacent the means for allowing the door to couple to the means for housing a lighting device, and means for pivotally coupling the door to the means for housing a lighting device comprising a means for allowing the means for coupling the door to the means for housing a lighting device to enter a channel defined by the means for housing a lighting device, a means for preventing the means for coupling the door to the means for housing a lighting device from exiting the channel defined by the means for housing a lighting device, and a means for prevent pivoting of the door when the door is coupled to the means for housing a lighting device, whereby the door is operable to pivotally couple to and decouple from the means for housing a lighting device by manipulating the door relative to the means for housing a lighting device and without the use of a tool or a fastener.

A method for coupling a door to a lighting device chassis has been described that includes providing a door comprising a chassis coupling member, positioning the chassis coupling member in a door coupling channel on a lighting device chassis by positioning a portion of the chassis in a channel defined by the chassis coupling member in order to allow the chassis coupling member to enter the door coupling channel, pivotally coupling the door to the lighting device chassis by manipulating the door relative to the lighting device chassis and without the use of a tool or fastener, preventing the chassis coupling member from exiting the door coupling channel by engaging a first stop member on the chassis coupling member with a second stop member located adjacent

the door coupling channel, and removing the door from the lighting device chassis by manipulating the door relative to the lighting device chassis.

A lighting apparatus has been described that includes a gasket defining a first light passageway, and a lens mounting channel defined by the gasket, located adjacent a perimeter of the first light passageway, and comprising a first channel surface and a second channel surface. In an exemplary embodiment, the gasket, the first light passageway, and the lens mounting channel are rectangular in shape. In an exemplary embodiment, the gasket is operable to provide a seal between a door and a lighting device chassis. In an exemplary embodiment, the first channel surface is substantially perpendicular to the second channel surface. In an exemplary embodiment, the apparatus further includes a lens comprising a first lens surface and a second lens surface and positioned in the lens mounting channel and immediately adjacent the first light passageway. In an exemplary embodiment, the first lens surface engages the first channel surface and the second lens surface engages the second channel surface. In an exemplary embodiment, the engagement of the second lens surface and the second channel surface prevents light from escaping from the lens through second lens surface. In an exemplary embodiment, the apparatus further includes a door defining a second light passageway, whereby the gasket is coupled to the door adjacent the second light passageway. In an exemplary embodiment, the gasket is located about the perimeter of the second light passageway such that the first light passageway is located adjacent the second light passageway and the lens is located between the first light passageway and the second light passageway. In an exemplary embodiment, the gasket is operable to provide a seal between the door and a lighting device chassis.

A lighting apparatus has been described that includes means for providing a seal, and means for preventing light from escaping a means for directing light on the means for providing a seal. In an exemplary embodiment, the means for providing a seal and means for preventing light from escaping a lens are rectangular in shape. In an exemplary embodiment, the means for providing a seal is operable to provide a seal between a door and a means for housing a lighting device. In an exemplary embodiment, the apparatus further includes means for directing light coupled to the means for providing a seal and positioned in the means for preventing light from escaping a means for directing light on the means for providing a seal. In an exemplary embodiment, the means for directing light engages the means for preventing light from escaping a means for directing light on the means for providing a seal. In an exemplary embodiment, the engagement of means for directing light and the means for preventing light from escaping a means for directing light on the means for providing a seal prevents light from escaping from the means for directing light. In an exemplary embodiment, the apparatus further includes a door, whereby the means for providing a seal is coupled to the door. In an exemplary embodiment, the means for providing a seal is operable to provide a seal between the door and a means for housing a lighting device.

A method for coupling a lens to a lighting apparatus has been described that includes providing a gasket that defines a light passageway and a lens mounting channel about the perimeter of the light passageway, positioning a lens in the lens mounting channel and adjacent the light passageway, and coupling the gasket to a lighting apparatus. In an exemplary embodiment, the method further includes directing light through the lens, whereby the lens mounting channel prevents light from escaping from a perimeter surface of the lens. In an exemplary embodiment, the gasket is coupled to a door on the

lighting apparatus. In an exemplary embodiment, the method further includes providing a seal between the door and a lighting apparatus chassis with the gasket.

A lighting apparatus has been described that includes a gasket defining a first light passageway, a lens mounting channel defined by the gasket, located adjacent a perimeter of the first light passageway, and comprising a first channel surface and a second channel surface, whereby the first channel surface is substantially perpendicular to the second channel surface, a lens comprising a first lens surface and a second lens surface and positioned in the lens mounting channel and immediately adjacent the first light passageway, wherein the first lens surface engages the first channel surface and the second lens surface engages the second channel surface, whereby the engagement of the second lens surface and the second channel surface prevents light from escaping from the lens through second lens surface, and a door defining a second light passageway, wherein the gasket is coupled to the door adjacent the second light passageway and located about the perimeter of the second light passageway such that the first light passageway is located adjacent the second light passageway and the lens is located between the first light passageway and the second light passageway, whereby the gasket is operable to provide a seal between the door and a lighting device chassis.

A lighting apparatus has been described that includes means for providing a seal, means for preventing light from escaping a means for directing light on the means for providing a seal, means for directing light coupled to the means for providing a seal and positioned in the means for preventing light from escaping a means for directing light on the means for providing a seal, wherein the means for directing light engages the means for preventing light from escaping a means for directing light on the means for providing a seal, whereby the engagement of means for directing light and the means for preventing light from escaping a means for directing light on the means for providing a seal prevents light from escaping from the means for directing light, and a door, whereby the means for providing a seal is coupled to the door, wherein the means for providing a seal is operable to provide a seal between the door and a means for housing a lighting device.

A method for coupling a lens to a lighting apparatus has been described that includes providing a gasket that defines a light passageway and a lens mounting channel about the perimeter of the light passageway, positioning a lens in the lens mounting channel and adjacent the light passageway, coupling the gasket to a door on a lighting apparatus, directing light through the lens, whereby the lens mounting channel prevents light from escaping from a perimeter surface of the lens, and providing a seal between the door and a lighting apparatus chassis with the gasket.

A lighting apparatus has been described that includes a reflector member, including a side wall, a first arcuate reflector surface extending from the side wall and comprising a first surface finish and a first reflector edge, and a second arcuate reflector surface extending from the side wall and comprising a second surface finish and a second reflector edge, whereby the second arcuate reflector surface is positioned adjacent the first arcuate reflector surface such that the second reflector edge is located in a spaced apart orientation from the first reflector edge. In an exemplary embodiment, the first arcuate reflector surface comprises an involute shape. In an exemplary embodiment, the first surface finish comprises a specular finish. In an exemplary embodiment, the specular finish comprises a Miro 4 finish. In an exemplary embodiment, the second arcuate reflector surface comprises a parabolic shape.

In an exemplary embodiment, the second surface finish comprises a diffuse finish. In an exemplary embodiment, the diffuse finish comprises a Miro 5 finish. In an exemplary embodiment, the apparatus further includes a step wall coupling the first arcuate reflector surface to the second arcuate reflector surface. In an exemplary embodiment, the first reflector edge is substantially parallel to the second reflector edge. In an exemplary embodiment, the apparatus further includes a lighting device coupled to the reflector member and positioned adjacent the first arcuate reflector surface and the second arcuate reflector surface, wherein the lighting device comprises a spacing criteria of approximately 1.68 for angles between 90 and 270 degrees. In an exemplary embodiment, the apparatus further includes a lighting device coupled to the reflector member and positioned adjacent the first arcuate reflector surface and the second arcuate reflector surface, wherein the lighting device comprises a spacing criteria of approximately 1.62 for angles between 90 and 270 degrees.

A lighting apparatus has been described that includes means for reflecting light, including means for supporting a means for reflecting light, first arcuate means for reflecting light extending from the means for supporting a means for reflecting light, and second arcuate means for reflecting light extending from the means for supporting a means for reflecting light, whereby the second arcuate means for reflecting light is positioned adjacent the first arcuate means for reflecting light such that the second arcuate means for reflecting light is located in a spaced apart orientation from the first arcuate means for reflecting light. In an exemplary embodiment, the first arcuate means for reflecting light comprises an involute means for reflecting light. In an exemplary embodiment, the second arcuate means for reflecting light comprises a parabolic means for reflecting light. In an exemplary embodiment, the apparatus further includes means for coupling the first arcuate means for reflecting light to the second arcuate means for reflecting light in a spaced apart orientation. In an exemplary embodiment, the apparatus further includes means for providing a spacing criteria of approximately 1.68 for angles between 90 and 270 degrees when a means for providing light is activated in the means for reflecting light. In an exemplary embodiment, the apparatus further includes means for providing a spacing criteria of approximately 1.62 for angles between 90 and 270 degrees when a means for providing light is activated in the means for reflecting light.

A method for reflecting light has been described that includes providing a reflector member comprising a side wall, a first arcuate reflector surface extending from the side wall, and a second arcuate reflector surface extending from the side wall and in a spaced apart orientation from the first arcuate reflector surface, positioning a lighting device adjacent the first arcuate reflector surface and the second arcuate reflector surface, activating the lighting device, and reflecting light from the lighting device from the first arcuate reflector surface and the second arcuate reflector surface. In an exemplary embodiment, the positioning comprises positioning the lighting device at approximately the center of the reflector member.

A lighting apparatus has been described that includes a reflector member, including a side wall, a first involute reflector surface extending from the side wall and comprising a specular surface finish and a first reflector edge, a second parabolic reflector surface extending from the side wall and comprising a diffuse surface finish and a second reflector edge, whereby the second arcuate reflector surface is positioned adjacent the first arcuate reflector surface such that the second reflector edge is located in a spaced apart orientation

from the first reflector edge, and a step wall coupling the first arcuate reflector surface to the second arcuate reflector surface; wherein the first reflector edge is substantially parallel to the second reflector edge.

A lighting apparatus has been described that includes means for reflecting light, including means for supporting a means for reflecting light, first involute means for reflecting light extending from the means for supporting a means for reflecting light, second parabolic means for reflecting light extending from the means for supporting a means for reflecting light, whereby the second arcuate means for reflecting light is positioned adjacent the first arcuate means for reflecting light such that the second arcuate means for reflecting light is located in a spaced apart orientation from the first arcuate means for reflecting light, and means for coupling the first arcuate means for reflecting light to the second arcuate means for reflecting light in a spaced apart orientation.

A method for reflecting light has been described that includes providing a reflector member comprising a side wall, a first arcuate reflector surface extending from the side wall, and a second arcuate reflector surface extending from the side wall and in a spaced apart orientation from the first arcuate reflector surface, positioning a lighting device adjacent the first arcuate reflector surface and the second arcuate reflector surface, wherein the positioning comprises positioning the lighting device at approximately the center of the reflector member, activating the lighting device, and reflecting light from the lighting device from the first arcuate reflector surface and the second arcuate reflector surface.

A lighting apparatus has been described that includes a lighting device chassis, a rotational coupling member extending from a side of the lighting device chassis, and a coupling member stop beam extending from a surface of the rotational coupling member. In an exemplary embodiment the rotational coupling member defines fastener coupler. In an exemplary embodiment, the rotational coupling member is conical in shape. In an exemplary embodiment, the coupling member stop beam extends along a length of the rotational coupling member. In an exemplary embodiment, the apparatus further includes a chassis support member comprising a support arm, a rotational coupling member passageway defined by the support arm, whereby the rotational coupling member is positioned in the rotational coupling member passageway, and a support arm stop beam extending from the support arm and into the rotational coupling member passageway. In an exemplary embodiment, the rotational coupling member passageway is conical in shape. In an exemplary embodiment, the support arm stop beam is operable to engage the coupling member stop beam to prevent rotation of the lighting device chassis relative in the rotational coupling member passageway beyond the support arm stop beam. In an exemplary embodiment, the apparatus further includes a fastener coupled to the rotational coupling member and the support arm. In an exemplary embodiment, the fastener is operable to engage a surface on the rotational coupling member with a surface on the support arm adjacent the rotational coupling member passageway to prevent rotation of the lighting device chassis relative to the support arm. In an exemplary embodiment, the support arm stop beam extends along a length of the support arm and into the rotational coupling member passageway.

A lighting apparatus has been described that includes means for housing a lighting device, means for rotatably coupling the means for housing a lighting device to a means for supporting a means for housing a lighting device, and first means for preventing rotation of the means for housing a lighting device relative to a means for supporting a means for

housing a lighting device. In an exemplary embodiment, the means for rotatably coupling the means for housing a lighting device to a means for supporting a means for housing a lighting device comprises a means for coupling a fastener to the means for rotatably coupling the means for housing a lighting device to a means for supporting a means for housing a lighting device. In an exemplary embodiment, the apparatus further includes means for supporting the means for housing a lighting device, and second means for preventing rotation of the means for housing a lighting device relative to a means for supporting a means for housing a lighting device.

A method for preventing rotation of a lighting device chassis has been described that includes providing a lighting device chassis comprising a rotational coupling member and a coupling member stop beam extending from a surface of the rotational coupling member, positioning the rotational coupling member in a rotational coupling member passageway defined by a support arm, and preventing rotation of the lighting device chassis by engaging the coupling member stop beam with a support arm stop beam that extends into the rotational coupling member passageway. In an exemplary embodiment, the method further includes coupling a fastener to the rotational coupling member and the support arm. In an exemplary embodiment, the method further includes rotating the lighting device chassis relative to the support arm into a position. In an exemplary embodiment, the method further includes engaging a surface on the rotational coupling member with a surface on the support arm using the fastener.

A lighting apparatus has been described that includes a lighting device chassis, a conical rotational coupling member extending from a side of the lighting device chassis and defining a fastener coupler, a coupling member stop beam extending along a length of the rotational coupling member, a chassis support member comprising a support arm, a conical rotational coupling member passageway defined by the support arm, whereby the rotational coupling member is positioned in the rotational coupling member passageway, a support arm stop beam extending along a length of the support arm and into the rotational coupling member passageway, whereby the support arm stop beam is operable to engage the coupling member stop beam to prevent rotation of the lighting device chassis relative in the rotational coupling member passageway beyond the support arm stop beam, and a fastener coupled to the rotational coupling member and the support arm, whereby the fastener is operable to engage a surface on the rotational coupling member with a surface on the support arm adjacent the rotational coupling member passageway to prevent rotation of the lighting device chassis relative to the support arm.

A lighting apparatus has been described that includes means for housing a lighting device, means for rotatably coupling the means for housing a lighting device to a means for supporting a means for housing a lighting device, wherein the means for rotatably coupling the means for housing a lighting device to a means for supporting a means for housing a lighting device comprises a means for coupling a fastener to the means for rotatably coupling the means for housing a lighting device to a means for supporting a means for housing a lighting device, first means for preventing rotation of the means for housing a lighting device relative to a means for supporting a means for housing a lighting device, means for supporting the means for housing a lighting device, and second means for preventing rotation of the means for housing a lighting device relative to a means for supporting a means for housing a lighting device.

A method for preventing rotation of a lighting device chassis has been described that includes providing a lighting

device chassis comprising a rotational coupling member and a coupling member stop beam extending from a surface of the rotational coupling member, positioning the rotational coupling member in a rotational coupling member passageway defined by a support arm, preventing rotation of the lighting device chassis by engaging the coupling member stop beam with a support arm stop beam that extends into the rotational coupling member passageway, coupling a fastener to the rotational coupling member and the support arm, rotating the lighting device chassis relative to the support arm into a position, and engaging a surface on the rotational coupling member with a surface on the support arm using the fastener.

A lighting apparatus has been described that includes a louver member, at least one first coupling member extending from the louver member, and at least one second coupling member that is operable to couple to the louver member and engage a lighting device chassis in order to couple the louver member to a lighting device chassis. In an exemplary embodiment, the louver member comprises a plurality of louvers extending between a first support beam and a second support beam, whereby the at least one first coupling member extends from a first support beam. In an exemplary embodiment, the first support beam defines a first chassis channel and the second support beam defines a second chassis channel. In an exemplary embodiment, the louver member defines at least one fastener coupler. In an exemplary embodiment, the apparatus further includes a fastener, whereby the fastener is operable to couple the second coupling member to the louver member by positioning the fastener in the second coupling member and the fastener coupler. In an exemplary embodiment, the at least one first coupling member comprises a clip defining a chassis edge channel. In an exemplary embodiment, a pair of first coupling members extend from a support beam on louver member and are oriented in a spaced apart relationship on the support beam. In an exemplary embodiment, a pair of second coupling member are operable to couple to the louver member and engage a lighting device chassis in order to couple the louver member to a lighting device chassis. In an exemplary embodiment, the apparatus further includes a lighting device chassis door comprising a first edge and a second edge, whereby the first coupling member engages the first edge and the second coupling member engages the second edge to couple the louver member to the lighting device chassis door. In an exemplary embodiment, the lighting device chassis door defines at least one first coupling member channel and at least one second coupling member channel. In an exemplary embodiment, the lighting device chassis door defines a pair of first coupling channels in a spaced apart orientation on the first edge, a second coupling member channel on the second edge, and a second coupling member channel on a third edge of the lighting device chassis door, the third edge located opposite the second edge. In an exemplary embodiment, the at least one first coupling member and the at least one second coupling member allow the louver member to be coupled to the lighting device chassis door without modification of the lighting device chassis door.

A lighting apparatus has been described that includes means for directing light, means for coupling the means for directing light to a means for housing a lighting device without modification of the means for housing a light device. In an exemplary embodiment, the means for directing light comprises means for coupling the means for coupling the means for directing light to a means for housing a lighting device to the means for directing light. In an exemplary embodiment, the means for coupling the means for directing light to a means for housing a lighting device comprises means for positioning the means for directing light in the means for

coupling the means for directing light to a means for housing a lighting device. In an exemplary embodiment, the apparatus further includes means for allowing access to a means for housing a lighting device, whereby the means for directing light is coupled to the means for allowing access to a means for housing a lighting device by the means for coupling the means for directing light to a means for housing a lighting device. In an exemplary embodiment, the means for allowing access to a means for housing a lighting device comprises means for allowing the means for coupling the means for directing light to a means for housing a lighting device to be positioned in the means for allowing access to a means for housing a lighting device.

A method for coupling a louver member to a lighting device chassis has been described that includes providing a louver member comprising a first coupling member, engaging the first coupling member with a lighting device chassis door, engaging a second coupling member to the lighting device chassis door, and coupling the louver member to the lighting device chassis door by coupling the second coupling member to the louver member. In an exemplary embodiment, the coupling comprises coupling the louver member to the lighting device chassis door without modification of the lighting device chassis door. In an exemplary embodiment, the engaging the first coupling member with a lighting device chassis door comprises positioning the lighting device chassis door in a channel defined by the first coupling member. In an exemplary embodiment, the engaging a second coupling member to the lighting device chassis door comprises positioning the lighting device chassis door in a channel defined by the second coupling member.

A lighting apparatus has been described that includes a louver member comprising a plurality of louvers extending between a first support beam and a second support beam, the first support beam defining a first chassis channel and the second support beam defining a second chassis channel, at least one fastener coupler defined by the second support beam, a pair of first coupling members extending from the first support beam in a spaced apart orientation on the louver member, each first coupling member comprising a clip defining an edge channel, a pair of second coupling members that are coupled to the louver member by a fastener that engages the second coupling member and the fastener coupler, a lighting device chassis door comprising a first edge, a second edge, and a third edge located opposite the second edge, wherein the lighting device chassis door defines a pair of first coupling channels in a spaced apart orientation on the first edge, a second coupling member channel on the second edge, and a second coupling member channel on the third edge, whereby the first coupling members engage the first edge in the first coupling channels and the second coupling members engages the second edge and the third edge in the second coupling channels in order to couple the louver member to the lighting device chassis door without modification of the lighting device chassis door.

A lighting apparatus has been described that includes means for directing light, means for coupling the means for directing light to a means for housing a lighting device without modification of the means for housing a lighting device, wherein the means for coupling the means for directing light to a means for housing a lighting device comprises means for positioning the means for directing light in the means for coupling the means for directing light to a means for housing a lighting device, means for coupling the means for directing light to a means for housing a lighting device to the means for directing light, and means for allowing access to a means for housing a lighting device, whereby the means for directing light is coupled to the means for allowing access to a means for housing a lighting device by

the means for coupling the means for directing light to a means for housing a lighting device, wherein the means for allowing access to a means for housing a lighting device comprises means for allowing the means for coupling the means for directing light to a means for housing a lighting device to be positioned in the means for allowing access to a means for housing a lighting device.

A method for coupling a louver member to a lighting device chassis has been described that includes providing a louver member comprising a first coupling member, engaging the first coupling member with a lighting device chassis door by positioning the lighting device chassis door in a channel defined by the first coupling member, engaging a second coupling member to the lighting device chassis door by positioning the lighting device chassis door in a channel defined by the second coupling member, and coupling the louver member to the lighting device chassis door by coupling the second coupling member to the louver member, whereby the coupling comprises coupling the louver member to the lighting device chassis door without modification of the lighting device chassis door.

It is understood that variations may be made in the foregoing without departing from the scope of the disclosure.

Any foregoing spatial references such as, for example, "upper," "lower," "above," "below," "rear," "between," "vertical," "angular," etc., are for the purpose of illustration only and do not limit the specific orientation or location of the structure described above.

In several exemplary embodiments, it is understood that one or more of the operational steps in each embodiment may be omitted. Moreover, in some instances, some features of the present disclosure may be employed without a corresponding use of the other features. Moreover, it is understood that one or more of the above-described embodiments and/or variations may be combined in whole or in part with any one or more of the other above-described embodiments and/or variations.

Although exemplary embodiments of this disclosure have been described in detail above, those skilled in the art will readily appreciate that many other modifications, changes and/or substitutions are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of this disclosure. Accordingly, all such modifications, changes and/or substitutions are intended to be included within the scope of this disclosure as defined in the following claims. In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents, but also equivalent structures.

What is claimed is:

1. A lighting apparatus, comprising:

a reflector member, comprising:

a side wall;

a reflector surface extending from the side wall;

a lighting device support member coupled to and extending from the side wall, the lighting device support member defining at least one channel for engaging a support arm and a fastener channel for engaging a fastener member;

a lighting device secured to a bracket for coupling the lighting device to the lighting device support member, the bracket defining a support arm that engages the at least one support arm channel, wherein the lighting device support member positions the lighting device adjacent the reflector surface; and

a fastener for securing the bracket to the lighting device support member by engaging the fastener channel.

33

2. The apparatus of claim 1, further comprising:
a mounting aperture defined by the side wall, wherein the lighting device support member extends through the mounting aperture.
3. The apparatus of claim 2, further comprising:
a second bracket secured to the side wall and coupled to the lighting device support member.
4. The apparatus of claim 3, wherein the fastener member further secures the lighting device support member to the second bracket.
5. The apparatus of claim 3, wherein the second bracket includes a support arm positioned in the at least one support channel.
6. The apparatus of claim 3, wherein the side wall has a first side facing the lighting device and a second side opposite to the lighting device; and
wherein the second bracket is coupled to the second side of the side wall.
7. The apparatus of claim 2, wherein the at least one channel is disposed longitudinally along the length of lighting device support member;
wherein the fastener channel is disposed longitudinally through the length of the lighting device support member; and
wherein the lighting device support member comprises a cross section substantially similar to the shape of the mounting aperture, the cross section further defining openings for the at least one channel and for the fastener channel, wherein the cross section is translated over the length of the lighting device support member.
8. The apparatus of claim 1, wherein the lighting device and the lighting device support member do not contact the reflector surface.
9. The apparatus of claim 1, wherein the lighting device support member provides a heat sink for the lighting device.
10. The apparatus of claim 1, wherein the lighting device support member comprises dimensions such that the lighting device is positioned at approximately the center of the reflector member.
11. A lighting apparatus, comprising:
Means for reflecting light, comprising:
a side wall;
a reflector surface extending from the side wall;
a lighting device;
means for supporting the lighting device coupled to the side wall, the means for supporting the lighting device including a support arm engaging means comprising a first channel and a fastener engaging means comprising a second channel;
a securing means comprising a bracket for securing the lighting device to the means for supporting the lighting device, the bracket coupled to the lighting device and the means for supporting the lighting device, wherein the means for supporting the lighting device positions the lighting device adjacent to the reflector surface;
at least one support arm extending from the bracket, wherein the support arm engages the support arm engaging means; and
a fastening means for fastening the securing means to the supporting means in the first channel, wherein the fastening means engages the fastener engaging means in the second channel.
12. The apparatus of claim 11, further comprising:
an aperture for allowing the means for supporting a lighting device to extend through the side wall.
13. The apparatus of claim 12, further comprising:
a second bracket for securing the means for supporting the lighting device to the side wall.

34

14. The apparatus of claim 11, wherein the means for supporting the lighting device provides a means for dissipating heat from the lighting device.
15. The apparatus of claim 11, wherein the means for supporting the lighting device comprises dimensions such that the lighting device is positioned at approximately the center of the reflector surface.
16. A method for positioning a light in a reflector, comprising:
providing a reflector member comprising a side wall and a reflector surface extending from the side wall;
coupling a lighting device support member to the side wall, the lighting device support member defining at least one support arm positioning channel and one fastener channel;
positioning the lighting device adjacent the reflector surface by coupling to lighting device to a lighting device bracket that is coupled to the lighting device support member, the lighting device bracket having a support arm, the support arm engaging the at least one support arm positioning channel; and
fastening the lighting device to the lighting device support member by securing a fastener to the lighting device bracket and the fastener channel,
whereby light from the lighting device will be reflected from the reflector surface upon activation of the lighting device.
17. The method of claim 16, wherein the positioning comprises positioning the lighting device at approximately the center of the reflector member.
18. The method of claim 16, further comprising:
providing a mounting aperture in the side wall; and
extending the lighting device support member through the mounting aperture.
19. The method of claim 16, further comprising:
dissipating heat from the lighting device with the lighting device support member.
20. A lighting apparatus, comprising:
a reflector member, comprising:
a side wall defining a mounting aperture and comprising a first side and a second side facing the opposite direction of the first side;
a reflector surface extending from the first side of the side wall;
a lighting device support member coupled to and extending from the side wall through the mounting aperture and defining at least one support channel and a fastener channel;
a first bracket secured to the second side of the side wall and coupled to the lighting device support member, wherein the first bracket includes a support arm positioned in the at least one support channel;
a lighting device coupled to the lighting device support member and positioned by the lighting device support member adjacent the reflector surface, wherein the lighting device support member comprises dimensions such that the lighting device is positioned at approximately the center of the reflector member;
a second bracket secured to the lighting device and coupled to the lighting device support member, wherein the second bracket includes a support arm positioned in the at least one support channel; and
a fastener fastened to the first bracket, the second bracket, and the lighting device support member, the fastener engaging the fastener channel.