



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2617610 C 2013/04/02

(11)(21) **2 617 610**

(12) **BREVET CANADIEN
CANADIAN PATENT**

(13) **C**

(86) Date de dépôt PCT/PCT Filing Date: 2006/08/01
(87) Date publication PCT/PCT Publication Date: 2007/02/22
(45) Date de délivrance/Issue Date: 2013/04/02
(85) Entrée phase nationale/National Entry: 2008/01/31
(86) N° demande PCT/PCT Application No.: US 2006/029895
(87) N° publication PCT/PCT Publication No.: 2007/021532
(30) Priorité/Priority: 2005/08/09 (US60/706,617)

(51) Cl.Int./Int.Cl. *B01J 20/00* (2006.01),
B01D 69/00 (2006.01), *B01D 71/06* (2006.01),
C01B 17/16 (2006.01), *C07C 7/00* (2006.01),
C07C 7/20 (2006.01), *C08K 5/17* (2006.01),
C08L 61/20 (2006.01), *C08L 79/04* (2006.01),
D02G 3/00 (2006.01)
(72) Inventeurs/Inventors:
WANG, FRANK CHEN-YU, US;
SISKIN, MICHAEL, US
(73) Propriétaire/Owner:
EXXONMOBIL RESEARCH AND ENGINEERING
COMPANY, US
(74) Agent: BORDEN LADNER GERVAIS LLP

(54) Titre : SEL DE POLYALKYLENEACRYLAMIDE POUR UN PROCEDE DE NETTOTAGE DE GAZ ACIDE
(54) Title: POLYALKYLENEACRYLAMIDE SALT FOR ACID GAS SCRUBBING PROCESS

(57) Abrégé/Abstract:

Hydrocarbyl substituted and unsubstituted polyethylene imines and polyacrylamide salts are absorption compositions and are useful in processes for the treatment of acid gas mixtures.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 February 2007 (22.02.2007)

PCT

(10) International Publication Number
WO 2007/021532 A1

(51) International Patent Classification:

B01J 20/00 (2006.01) **C08L 61/20** (2006.01)
B01D 69/00 (2006.01) **C08L 79/04** (2006.01)
B01D 71/06 (2006.01) **C07C 7/00** (2006.01)
C08K 5/17 (2006.01) **C07C 7/20** (2006.01)
D02G 3/00 (2006.01) **C01B 17/16** (2006.01)

(21) International Application Number:

PCT/US2006/029895

(22) International Filing Date: 1 August 2006 (01.08.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/706,617 9 August 2005 (09.08.2005) US

(71) Applicant (for all designated States except US): **EXXON-MOBIL RESEARCH AND ENGINEERING COMPANY** [US/US]; 1545 ROUTE 22 East, P.O.Box 900, Annandale, NJ 08801-0900 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WANG, Frank, Chen-yu** [US/US]; 9 Cambridge Drive, Annandale, NJ 08801 (US). **SISKIN, Michael** [US/US]; 50 Shongum Road, Randolph, NJ 07869 (US).

(74) Agents: **PURWIN, Paul, E.** et al.; EXXONMOBIL RESEARCH AND, ENGINEERING COMPANY, 1545 Route 22 East, P.O.Box 900, Annandale, NJ 08801-0900 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: POLYALKYLENEIMINES AND POLYALKYLENEACRYLAMIDE SALT FOR ACID GAS SCRUBBING PROCESS

(57) Abstract: Hydrocarbyl substituted and unsubstituted polyethylene imines and polyacrylamide salts are absorption compositions and are useful in processes for the treatment of acid gas mixtures.

WO 2007/021532 A1

- 1 -

**POLYALKYLENEACRYLAMIDE SALT FOR ACID GAS SCRUBBING
PROCESS**

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

[0001] The present invention relates to an absorbent composition and to a process for the selective absorption of one or more gaseous acidic components, preferably H₂S, from a gaseous acidic component(s) containing gas mixture using the absorbent composition.

DESCRIPTION OF THE RELATED ART

[0002] It is well known in the art to treat gases and liquids, such as mixtures containing acidic gases including CO₂, H₂S, CS₂, HCN, COS and oxygen and sulfur derivatives of C₁ to C₄ hydrocarbons with amine solutions to remove these acidic gases. The amine usually contacts the acidic gases and the liquids as an aqueous solution containing the amine in an absorber tower with the aqueous amine solution contacting the acidic fluid countercurrently.




[0003] The treatment of acid gas mixtures containing, inter alia, CO₂ and H₂S with amine solutions typically results in the simultaneous removal of substantial amounts of both the CO₂ and H₂S. For example, in one such process generally referred to as the "aqueous amine process", relatively concentrated amine solutions are employed. A recent improvement of this process involves the use of sterically hindered amines as described in USP 4,112,052, to obtain nearly complete removal of acid gases such as CO₂ and H₂S. This type of process may be used where the partial pressures of the CO₂ and related gases are low. Another process often used for specialized applications where the partial pressure of CO₂ is extremely high and/or where many acid gases are present, e.g., H₂S, COS, CH₃SH and CS₂ involves the use of an amine in combination with a physical absorbent, generally referred to as the "nonaqueous solvent

- 2 -

process". An improvement on this process involves the use of sterically hindered amines and organic solvents as the physical absorbent such as described in USP 4,112,051.

[0004] It is often desirable, however, to treat acid gas mixtures containing both CO₂ and H₂S so as to remove the H₂S selectively from the mixture, thereby minimizing removal of the CO₂. Selective removal of H₂S results in a relatively high H₂S/CO₂ ratio in the separated acid gas which simplifies the conversion of H₂S to elemental sulfur using the Claus process.

[0005] The typical reactions of aqueous secondary and tertiary amines with CO₂ and H₂S can be represented as follows:



wherein each R is an organic radical which may be the same or different and may be substituted with an hydroxy group. The above reactions are reversible, and the partial pressures of both CO₂ and H₂S are thus important in determining the degree to which the above reactions occur.

[0006] While selective H₂S removal is applicable to a number of gas treating operations including treatment of hydrocarbon gases from shale pyrolysis, refinery gas and natural gas having a low H₂S/CO₂ ratio, it is particularly desirable in the treatment of gases wherein the partial pressure of H₂S is relatively low compared to that of CO₂ because the capacity of an amine to

- 3 -

absorb H_2S from the latter type gases is very low. Examples of gases with relatively low partial pressures of H_2S include synthetic gases made by coal gasification, sulfur plant tail gas and low-Joule fuel gases encountered in refineries where heavy residual oil is being thermally converted to lower molecular weight liquids and gases.

[0007] Although it is known that solutions of primary and secondary amines such as monoethanolamine (MEA), diethanolamine (DEA), dipropanolamine (DPA), and hydroxyethoxyethylamine (DGA) absorb both H_2S and CO_2 gas, they have not proven especially satisfactory for preferential absorption of H_2S to the exclusion of CO_2 because the amines undergo a facile reaction with CO_2 to form carbamates.

[0008] Diisopropanolamine (DIPA) is relatively unique among secondary aminoalcohols in that it has been used industrially, alone or with a physical solvent such as sulfolane, for selective removal of H_2S from gases containing H_2S and CO_2 , but contact times must be kept relatively short to take advantage of the faster reaction of H_2S with the amine compared to the rate of CO_2 reaction shown in Equations 2 and 4 hereinabove.

[0009] In 1950, Frazier and Kohl, Ind. and Eng. Chem., 42, 2288 (1950) showed that the tertiary amine, methyldiethanolamine (MDEA), has a high degree of selectivity toward H_2S absorption over CO_2 . This greater selectivity was attributed to the relatively slow chemical reaction of CO_2 with tertiary amines as compared to the rapid chemical reaction of H_2S . The commercial usefulness of MDEA, however, is limited because of its restricted capacity for H_2S loading and its limited ability to reduce the H_2S content to the level at low pressures which is necessary for treating, for example, synthetic gases made by coal gasification.

- 4 -

[0010] Recently, U.K. Patent Publication No. 2,017,524A to Shell disclosed that aqueous solutions of dialkylmonoalkanolamines, and particularly diethylmonoethanolamine (DEAE), have higher selectivity and capacity for H₂S removal at higher loading levels than MDEA solutions. Nevertheless, even DEAE is not very effective for the low H₂S loading frequency encountered in the industry. Also, DEAE has a boiling point of 161°C, and as such, it is characterized as being a low-boiling, relatively highly volatile amino alcohol. Such high volatilities under most gas scrubbing conditions result in large material losses with consequent losses in economic advantages.

[0011] U.S. Pat. Nos. 4,405,581; 4,405,583 and 4,405,585 disclose the use of severely sterically hindered amine compounds for the selective removal of H₂S in the presence of CO₂. Compared to aqueous methyldiethanolamine (MDEA) severely sterically hindered amines lead to much higher selectivity at high H₂S loadings.

[0012] USP 4,487,967 discloses a catalytic synthesis process for selectively preparing severely sterically hindered secondary aminoether alcohols by reacting a primary amino compound with a polyalkenyl ether glycol in the presence of an hydrogenation catalyst at elevated temperatures and pressures.


[0013] USP 4,665,195 discloses a catalytic synthesis process for producing di-amino-polyalkenyl ethers by reacting (a) one or more acyclic or heterocyclic amino compounds with (b) one or more polyalkenyl ether glycols or polyalkenyl amino ether alcohols, in the presence of an hydrogenation catalyst at elevated temperatures and pressures.

[0014] The composition of BTEE has been disclosed in USP 4,405,583 and synthesized from tertiarybutylamine and bis-(2-chloroethoxy)-ethane. However, an aqueous BTEE solution suffered from phase separation under regeneration conditions (about 110°C). EEETB is disclosed as a new composition of matter

- 5 -

in USP 4,471,138 and can be prepared from tertiary-butylamine and chloroethoxyethoxyethanol. EEETB in aqueous solution can be used for the selective removal of H₂S in the presence of CO₂. However, the BTEE/EEETB mixture gives a better selectivity and a higher capacity for H₂S than EEETB. The mixture does not have phase separation under regeneration conditions, i.e., this mixture overcomes the phase separation problem of BTEE. The BTEE/EEETB mixture also gives higher selectivities for H₂S than observed with the severely sterically hindered amines, e.g., ethoxyethanol-tertiary-butylamine (EETB), described in U.S. Pat. Nos. 4,405,581 and 4,405,585.


[0015] USP 4,417,075 teaches a class of di-secondary amino ethers of the formula



wherein R¹ and R⁸ are each independently selected from the group consisting of primary alkyl having 1-8 carbon atoms, and primary hydroxy alkyl having 2-8 carbon atoms, secondary alkyl and secondary hydroxy alkyl radicals having 3-8 carbon atoms, tertiary alkyl and tertiary hydroxy alkyl radicals having 4 to 8 carbon atoms, R², R³, R⁴, R⁵, R⁶ and R⁷ are each independently selected from the group consisting of hydrogen, C₁-C₃ alkyl and hydroxyalkyl radicals, with that proviso that R², R³, R⁶ and R⁷ are C₁-C₄ alkyl or hydroxy alkyl radicals when R¹ and R⁸ are primary alkyl or hydroxy alkyl radicals and at least one of R² or R³ and R⁶ and R⁷ are C₁ to C₃ alkyl or hydroxyalkyl radicals when R¹ and R⁸ are secondary alkyl radicals, m, n and p are positive integers ranging from 2 to 4 and a is either zero or a positive integer ranging from 1 to 10. These compounds are useful in the selective removal of H₂S from gaseous mixtures containing H₂S and CO₂.

- 6 -

[0016] USP 4,894,178 teaches a mixture of two severely hindered amines with the following formula:



with x being an integer ranging from 2 to 6, and the weight ratio of the first amine to the second amine ranging from 0.43:1 to 2.3:1. This mixture can be prepared in the one-step synthesis, by the catalytic tertiary-butylamination of the polyalkenyl ether glycol, $\text{HO}-(\text{CH}_2\text{CH}_2\text{O})_x-\text{CH}_2\text{CH}_2-\text{OH}$. For example, a mixture of bis(tertiary-butylaminoethoxy)ethane (BTEE) and ethoxyethoxyethanol-tertiary-butylamine (EEETB) can be obtained by the catalytic tertiary-butylamination of triethylene glycol.

SUMMARY OF THE INVENTION

[0017] The present invention is directed to unsubstituted or hydrocarbyl substituted polyalkyleneimines and polyalkyleneacrylamide salts and mixtures thereof and their use in processes for the treatment of acid gas mixtures.


DESCRIPTION OF THE FIGURE

[0018] Figure 1 is a diagrammatic flow sheet illustrating an absorption regeneration unit for the selective removal of H_2S from gaseous streams containing H_2S and CO_2 .

DETAILED DESCRIPTION OF THE INVENTION

[0019] Unsubstituted or hydrocarbyl substituted polyalkylene acrylamide salts have been identified and have been found to be useful in processes for the treatment of acid gas mixtures.

[0020] The unsubstituted or hydrocarbyl substituted polyalkyleneacrylamide salts of the present invention are generally represented by the following formula



wherein Rs are the same or different and selected from H, C₁-C₉ alkyl radical, C₃-C₉ branched chain alkyl, cyclic, cycloalkyl, alkylcyclo radicals, C₆-C₉ aryl, arylalkyl or alkylaryl radicals, hydroxy substituted derivatives thereof, preferably H or C₁-C₄ alkyl;

and z is an integer of at least 1, there being no upper limit because the materials are all water soluble, preferably 1 to 200; and salt is a basic salt (pH_≥8), for example, from NaOH, KOH, Zn(OH)₂, Mg(OH)₂, Ca(OH)₂, NR₄OH wherein R is as defined above, and W are end groups which do not affect the overall base nature of the absorbent.

- 8 -

[0021] The absorbents described above exhibit high selectivity for the removal of one or more gaseous acidic components, such as H_2S , from gaseous mixtures of such acidic component(s) and non-acidic gaseous component(s) and CO_2 , and retain their high selectivity and loading capacity even after regeneration.

[0022] The absorbents are utilized for the selective absorption of gaseous acidic components, preferably H_2S from a normally gaseous mixture containing gaseous acidic components, preferably H_2S , and CO_2 comprising:

- (a) contacting said normally gaseous mixture with an absorbent solution characterized as capable of selectively absorbing one or more of the gaseous acidic component, preferably H_2S from said mixture;
- (b) regenerating, at least partially, said absorbent solution containing the absorbent gaseous acidic component, e.g., H_2S ; and
- (c) recycling the regenerated solution for the selective absorption of gaseous acidic components, preferably H_2S by contacting as in step (a).

Preferably, the regeneration step is carried out by heating and stripping and more preferably heating and stripping with steam.

[0023] The term "absorbent solution" as used herein includes but is not limited to solutions wherein the amino compound is dissolved in a solvent selected from water or a physical absorbent or mixtures thereof. Solvents which are physical absorbents (as opposed to the amino compounds which are chemical absorbents) are described, for example, in USP 4,112,051 and include, e.g., aliphatic acid amides, N-alkylated pyrrolidones, sulfones, sulfoxides, glycols and the mono- and diethers thereof. The preferred physical absorbents herein are sulfones, and most particularly, sulfolane. The preferred liquid medium comprises water.

- 9 -

[0024] The absorbent solution ordinarily has a concentration of amino compound of about 0.1 to 6 moles per liter of the total solution, and preferably 1 to 4 moles per liter, depending primarily on the specific amino compound employed and the solvent system utilized. If the solvent system is a mixture of water and a physical absorbent, the typical effective amount of the physical absorbent employed may vary from 0.1 to 5 moles per liter of total solution, and preferably from 0.5 to 3 moles per liter, depending mainly on the type of amino compound being utilized. The dependence of the concentration of amino compound on the particular compound employed is significant because increasing the concentration of amino compound may reduce the basicity of the absorbent solution, thereby adversely affecting its selectivity for H₂S removal, particularly if the amino compound has a specific aqueous solubility limit which will determine maximum concentration levels within the range given above. It is important, therefore, that the proper concentration level appropriate for each particular amino compound be maintained to insure satisfactory results.

[0025] The solution of this invention may include a variety of additives typically employed in selective gas removal processes, e.g., antifoaming agents, antioxidants, corrosion inhibitors, and the like. The amount of these additives will typically be in the range that they are effective, i.e., an effective amount.

[0026] Also, the amino compounds described herein may be admixed with other amino compounds as a blend. The ratio of the respective amino compounds may vary widely, for example, from 1 to 99 wt% of the amino compounds described herein.

[0027] Three characteristics which are of ultimate importance in determining the effectiveness of the amino compounds herein for H₂S removal are "selectivity", "loading" and "capacity". The term "selectivity" as used throughout the specification is defined as the following mole ratio fraction:

- 10 -

$$\frac{(\text{moles of H}_2\text{S}/\text{moles of CO}_2) \text{ in liquid phase}}{(\text{moles of H}_2\text{S}/\text{moles of CO}_2) \text{ in gaseous phase}}$$

The higher this fraction, the greater the selectivity of the absorbent solution for the H₂S in the gas mixture.

[0028] By the term “loading” is meant the concentration of the H₂S and CO₂ gases physically dissolved and chemically combined in the absorbent solution as expressed in moles of gas per moles of the amine. The best amino compounds are those which exhibit good selectivity up to a relatively high loading level. The amino compounds used in the practice of the present invention typically have a “selectivity” of not substantially less than 10 at a “loading” of 0.1 moles, preferably, a “selectivity” of not substantially less than 10 at a loading of 0.2 or more moles of H₂S and CO₂ per moles of the amino compound.

[0029] “Capacity” is defined as the moles of H₂S loaded in the absorbent solution at the end of the absorption step minus the moles of H₂S loaded in the absorbent solution at the end of the desorption step. High capacity enables one to reduce the amount of amine solution to be circulated and use less heat or steam during regeneration.

[0030] The acid gas mixture herein necessarily includes H₂S, and may optionally include other gases such as CO₂, N₂, CH₄, H₂, CO, H₂O, COS, HCN, C₂H₄, NH₃, and the like. Often such gas mixtures are found in combustion gases, refinery gases, town gas, natural gas syn gas, water gas, propane, propylene, heavy hydrocarbon gases, etc. The absorbent solution herein is particularly effective when the gaseous mixture is a gas, obtained, for example, from a shale oil retort, coal liquefaction or gasification, liquefaction of heavy oil with steam, air/steam or oxygen/steam, thermal conversion of heavy residual oil to lower molecular weight liquids and gases, e.g., fluid coker, Flexicoker, delayed coker, or in sulfur plant tail gas cleanup operations.

- 11 -

[0031] The absorption step of this invention generally involves contacting the normally gaseous stream with the absorbent solution in any suitable contacting vessel. In such processes, the normally gaseous mixture containing H_2S and CO_2 from which the H_2S is to be selectively removed may be brought into intimate contact with the absorbent solution using conventional means, such as a tower or vessel packed with, for example, rings or with sieve plates, or a bubble reactor. Other acidic gaseous components will also be removed preferentially as compared with CO_2 .

[0032] In a typical mode of practicing the invention, the absorption step is conducted by feeding the normally gaseous mixture into the lower portion of the absorption tower while fresh absorbent solution is fed into the upper region of the tower. The gaseous mixture, freed largely from the H_2S , emerges from the upper portion of the tower, and the loaded absorbent solution, which contains the selectively absorbed H_2S , leaves the tower near or at its bottom. Preferably, the inlet temperature of the absorbent solution during the absorption step is in the range of from about 20°C to about 100°C , and more preferably from 30°C to about 60°C . Pressures may vary widely; acceptable pressures are between 5 and 2000 psia, preferably 20 to 1500 psia, and most preferably 25 to 1000 psia in the absorber. The contacting takes place under conditions such that the H_2S is selectively absorbed by the solution. The absorption conditions and apparatus are designed so as to minimize the residence time of the liquid in the absorber to reduce CO_2 pickup while at the same time maintaining sufficient residence time of gas mixture with liquid to absorb a maximum amount of the H_2S gas. The amount of liquid required to be circulated to obtain a given degree of H_2S removal will depend on the chemical structure and basicity of the amino compound and on the partial pressure of H_2S in the feed gas. Gas mixtures with low partial pressures such as those encountered in thermal conversion processes

- 12 -

will require more liquid under the same absorption conditions than gases with higher partial pressures such as shale oil retort gases.

[0033] A typical procedure for the selective H₂S removal phase of the process comprises selectively absorbing H₂S via countercurrent contact of the gaseous mixture containing H₂S and CO₂ with the solution of the amino compound in a column containing a plurality of trays at a low temperature, e.g., below 45°C, and at a gas velocity of at least about 0.3 ft/sec (based on “active” or aerated tray surface), depending on the operating pressure of gas, said tray column having fewer than 20 contacting trays, with, e.g., 4-16 trays being typically employed.

[0034] After contacting the normally gaseous mixture with the absorbent solution, which becomes saturated or partially saturated with H₂S, the solution may be at least partially regenerated so that it may be recycled back to the absorber. As with absorption, the regeneration may take place in a single liquid phase. Regeneration or desorption of the absorbent solution may be accomplished by conventional means such as pressure reduction of the solution or increase of temperature to a point at which the absorbed H₂S flashes off, or bypassing the solution into a vessel of similar construction to that used in the absorption step, at the upper portion of the vessel, and passing an inert gas such as air or nitrogen or preferably steam upwardly through the vessel. The temperature of the solution during the regeneration step should be in the range from about 50°C to about 170°C, and preferably from about 80°C to 120°C, and the pressure of the solution on regeneration should range from about 0.5 to about 100 psia, preferably 1 to about 50 psia. The absorbent solution, after being cleansed of at least a portion of the H₂S gas, may be recycled back to the absorbing vessel. Makeup absorbent may be added as needed.

[0035] In the preferred regeneration technique, the H₂S-rich solution is sent to the regenerator wherein the absorbed components are stripped by the steam

- 13 -

which is generated by re-boiling the solution. Pressure in the flash drum and stripper is usually 1 to about 50 psia, preferably 15 to about 30 psia, and the temperature is typically in the range from about 50°C to 170°C, preferably about 80°C to 120°C. Stripper and flash temperatures will, of course, depend on stripper pressure, thus at about 15 to 30 psia stripper pressures, the temperature will be about 80°C to about 120°C during desorption. Heating of the solution to be regenerated may very suitably be effected by means of indirect heating with low-pressure steam. It is also possible, however, to use direct injection of steam.

[0036] In one embodiment for practicing the entire process herein, as illustrated in Figure 1, the gas mixture to be purified is introduced through line 1 into the lower portion of a gas-liquid countercurrent contacting column 2, said contacting column having a lower section 3 and an upper section 4. The upper and lower sections may be segregated by one or a plurality of packed beds as desired. The absorbent solution as described above is introduced into the upper portion of the column through a pipe 5. The solution flowing to the bottom of the column encounters the gas flowing countercurrently and dissolves the H₂S preferentially. The gas freed from most of the H₂S exits through a pipe 6, for final use. The solution, containing mainly H₂S and some CO₂, flow toward the bottom portion of the column, from which it is discharged through pipe 7. The solution is then pumped via optional pump 8 through an optional heat exchanger and cooler 9 disposed in pipe 7, which allows the hot solution from the regenerator 12 to exchange heat with the cooler solution from the absorber column 2 for energy conservation. The solution is entered via pipe 7 to a flash drum 10 equipped with a line (not shown) which vents to line 13 and then introduced by pipe 11 into the upper portion of the regenerator 12, which is equipped with several plates and effects the desorption of the H₂S and CO₂ gases carried along in the solution. This acid gas is passed through a pipe 13 into a condenser 14 wherein cooling and condensation of water and amine solution from the gas occur. The gas then enters a separator 15 where further condensation is effected.

- 14 -

The condensed solution is returned through pipe 16 to the upper portion of the regenerator 12. The gas remaining from the condensation, which contains H_2S and some CO_2 , is removed through pipe 17 for final disposal (e.g., to a vent or incinerator or to an apparatus which converts the H_2S to sulfur, such as a Claus unit or a Stretford conversion unit (not shown)).

[0037] The solution is liberated from most of the gas which it contains while flowing downward through the regenerator 12 and exits through pipe 18 at the bottom of the regenerator for transfer to a reboiler 19. Reboiler 19, equipped with an external source of heat (e.g., steam injected through pipe 20 and the condensate exits through a second pipe (not shown)), vaporizes a portion of this solution (mainly water) to drive further H_2S therefrom. The H_2S and steam driven off are returned via pipe 21 to the lower section of the regenerator 12 and exited through pipe 13 for entry into the condensation stages of gas treatment. The solution remaining in the reboiler 19 is drawn through pipe 22, cooled in heat exchanger 9, and introduced via the action of pump 23 (optional if pressure is sufficiently high) through pipe 5 into the absorber column 2.

[0038] Typically, a gaseous stream to be treated having a 1:10 mole ratio of $\text{H}_2\text{S}:\text{CO}_2$ from an apparatus for thermal conversion of heavy residual oil, or a Lurgi coal gas having a mole ratio of $\text{H}_2\text{S}:\text{CO}_2$ of less than 1:10 will yield an acid gas having a mole ratio of $\text{H}_2\text{S}:\text{CO}_2$ of about 1:1 after treatment by the process of the present invention. The process herein may be used in conjunction with another H_2S selective removal process; however, it is preferred to carry out the process of this invention by itself, since the amino compounds are extremely effective by themselves in preferential absorption of H_2S .

EXPERIMENTAL PROCEDURE

1. Absorption tests were carried out at 35°C on 0.15 M aqueous solutions of absorbent using a test gas mixture of nitrogen:carbon dioxide:hydrogen sulfide of 89:10:1 for 2 hours.
2. Desorption was run at 85°C in flowing N₂ for 2 hours at the same flow rate as the test gas mixture.


TABLE 1

Compound	Molecular Weight	Selectivity	Loading (%)	Capacity (%)	Selectivity - Reabsorption
EETB (USP 4,405,585)	161.24	15.4	16.3	60	13.3
Bis-SE (USP 4,405,583)	216.36	16.7	28.2	80	25.2
Polyethyleneimine	42x+86y	85.5	7.3	57	102.8
Polyacrylamide	71.08 z	4.51	--	--	--
Polyacrylamide-KOH salt	71.08 z	77.3	10.1	71.3	112.4

- 16 -

CLAIMS:

1. A process for the selective removal of H₂S from a normally gaseous mixture containing H₂S, CO₂ and non-acidic components comprising contacting the normally gaseous mixture with an absorbent of a basic unsubstituted or hydrocarbyl substituted polyalkyleneacrylamide salt under conditions whereby the H₂S mixture is selectively absorbed from said mixture.
2. The process of claim 1 wherein the polyalkyleneacrylamide salt absorbent is a basic salt with a pH of greater than 8 and of the formula



wherein Rs are the same or different and selected from H, C₁-C₉ alkyl radical, C₃-C₉ branched chain alkyl, cyclic, cycloalkyl, alkylcyclo radicals, C₆-C₉ aryl, arylalkyl or alkylaryl radicals, hydroxy substituted derivatives thereof, and z is an integer of at least 1; and W are end groups which do not affect the overall base nature of the absorbent.

3. The process of claim 2 wherein Rs are H or C₁-C₄ alkyl and salt is derived from NaOH, KOH, Zn(OH)₂, Mg(OH)₂, Ca(OH)₂, or NR₄OH.

Figure 1
Adsorption-Regeneration Unit for Selective H₂S Removal

