

(19)



(11)

EP 2 988 990 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:

12.06.2019 Bulletin 2019/24

(51) Int Cl.:

B63B 25/12 (2006.01) **B63B 25/08** (2006.01)
B63B 25/28 (2006.01) **B63B 27/10** (2006.01)
B63B 27/24 (2006.01) **B63J 2/08** (2006.01)
B63B 27/34 (2006.01) **B63J 2/14** (2006.01)

(21) Application number: **14787917.5**

(22) Date of filing: **14.04.2014**

(86) International application number:
PCT/NO2014/000029

(87) International publication number:
WO 2014/175742 (30.10.2014 Gazette 2014/44)

(54) **OFFSHORE SUPPLY VESSEL**

OFFSHORE-VERSORGUNGSSCHIFF

NAVIRE D'APPROVISIONNEMENT EN MER

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

• **JONGH, Martijn de**
N-6065 Ulsteinvik (NO)

(30) Priority: **23.04.2013 NO 20130563**

(43) Date of publication of application:
02.03.2016 Bulletin 2016/09

(74) Representative: **Acapo AS**
P.O. Box 1880 Nordnes
5817 Bergen (NO)

(73) Proprietor: **Rolls-Royce Marine AS**
6025 Alesund (NO)

(56) References cited:
WO-A1-2005/054048 WO-A1-2005/054048
WO-A1-2005/056379 WO-A1-2012/022355
DE-A1- 19 707 213 GB-A- 1 000 297
GB-A- 1 407 602 GB-A- 2 269 565
US-A- 3 031 856 US-A- 3 557 740
US-A- 3 844 239 US-A1- 2006 213 419

(72) Inventors:

• **LEENDERS, Erik**
N-6065 Ulsteinvik (NO)

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 988 990 B1

Description

[0001] The present invention relates to an offshore supply ship for transport of cargo comprising an, in the main, open deck, and also several cargo tanks that lie below the deck where one or more watertight rooms extend between a number of said cargo tanks and the deck.

[0002] Meant by offshore supply ship is both PSV (platform supply vessel) and OSV (offshore service vessel), or for that matter other suitable supply ships for use offshore.

[0003] The present ship is preferably supplied with a central cargo rail (foundation), where the cargo rail can be, for example, equipped with a centrally placed derrick crane which can be moved along on the cargo rail. Because of its central location the cargo rail can preferably be equipped with outlets for ventilation lines for, for example, type 1 and 2 cargo tanks. The central cargo rail can also be used for outlets for ventilation lines for other cargo tanks, such as slop tanks, i.e. for example, tanks for the collection of contaminated liquids such as oil and water.

[0004] From patent literature, reference is made to WO 2005/054048 A1, which relates to an offshore supply ship for the transport of deck cargo, comprising an, in the main, open deck. The ship has cargo rails along the starboard and port sides. Pipe lines go from the cargo tanks to the cargo rails. The cargo rails are equipped with derrick cranes.

[0005] US 2006/0213419 A1 and GB 2162880 A show vessels with cargo tanks below an, in the main, open deck with cargo rails along the starboard and port sides.

[0006] WO 2005/056379 A1 shows an open work deck with cargo tanks below and pipelines that go in a centrally, longitudinal channel.

[0007] GB 1407602 A relates to a vessel for transportation of liquefied gases. US 3031856 A relates to a vessel for transporting low temperature liquids. GB 1000297 A relates to vessel with thermally insulated tanks suitable for containing low temperature liquids. GB 2269565 A relates to a tanker with access trunk.

[0008] IBC, International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk, is an international standard that places operating and construction limitations for safe transport at sea. Type 1 vessels are a chemical tanker for the transport of "Chapter 17" products with serious environmental and safety related cargo that requires maximum safety initiatives to prevent discharges of such cargo. Type 2 vessels are chemical tankers to transport "Chapter 17" products with considerable environmental and safety cargo, and which require stringent safety initiatives to prevent discharges of such cargo. Chapter 17 gives an overview of different chemicals and places the limitations for: Pollution category, safety category, type of ships required for the transport of the products (type 1, 2 or 3), specific operating requirements for the transport of the products, etc.

[0009] The ventilation lines for type 1 cargo are not permitted in side cargo rails. The advantage with the present solution is that shorter lines/pipes can be used, in some cases, usually nearly straight up from the cargo tanks and which are far from said injury zone. Another advantage with a central cargo rail is that lower cargo rails can be used at the sides. This can be important as it will give a better ventilation of the cargo deck which is important when poisonous substances are being transported. Another advantage with lower side cargo rails is that it improves the view from and to the cargo deck.

[0010] For example, for IBC type 1 OSV, use of a central cargo rail (foundation) will be a unique solution which does not exist today. As far as it is known, the only vessels that are permitted to transport IBC type 1 products are a few chemical tankers.

[0011] With the use of a central cargo rail there is a need for one cargo station only, in contrast to the standard stations on starboard and port sides. This can also lead to simpler evacuation routes, as watertight sliding doors, for example, are not necessary.

[0012] A possible advantage is that there might be no need for cofferdams, i.e. for example, watertight rooms between the cargo deck and the cargo tanks, for a pipeline installation over the whole width of the cargo deck. This might be able to increase the cargo capacity for, for example, sludge and saltwater tanks (mud/brine) and other liquid tanks (FO).

[0013] The present invention was basically developed in a response to the above mentioned IBC codes, but it must be emphasised that the invention can, of course, also be used on vessels other than just type 1 and 2 vessels.

[0014] As mentioned, the invention relates, for one thing, to the placing of a cargo rail centrally on the vessel. On traditional offshore supply ships cargo rails are meant to allow the cargo to be stored against the cargo rail, protect the pipe systems, such as for loading and unloading, function as escape routes and also be used as a work area on each side of the vessel. Ventilation channels and pipelines, as well as escape routes, must be routed through the cargo rails, which means extra lengths on the pipelines and also a risk of flooding in cases of damage to the sides that also damage the cargo rails. In addition, for loading and unloading of bulk cargo, it is often necessary to have loading and unloading stations on each side of the vessel.

[0015] Placing of a central cargo rail, generally in combination with two lower and simple cargo rails on each side, will give a better and more efficient way in which to arrange the tanks. This also reduces the amount of pipelines, which in turn results in reduced costs, less maintenance and smaller risks of damages to the pipe systems. This also leads to better protection of the cargo tanks with chemicals and can reduce the need for double loading and unloading stations. Furthermore, it can mean simpler and safer escape routes, a simpler way to arrange the ventilation of pumps and other rooms below

the deck and better ventilation of the work deck in cases where the vessel transports dangerous chemicals.

[0016] The above mentioned advantages and aims are obtained with an offshore supply ship for the transport of cargo, comprising an, in the main, open deck, and also several cargo tanks that lie below deck, where one or more watertight rooms extend between a number of said cargo tanks and the deck, and where, on said deck in the longitudinal direction of the ship, a central longitudinally running cargo rail is placed, wherein the cargo rail can support a derrick crane and can be equipped with tracks for said crane, and a number of ventilation lines that run from said cargo tanks through the watertight room and up into the centrally placed cargo rail.

[0017] According to the invention, said ventilation lines can alternatively run from a number of collection tanks, such as slop tanks, and up into the centrally placed cargo rail.

[0018] Furthermore, an outlet to the ventilation lines in the centrally placed cargo rail can comprise a valve, such as a pressure vacuum valve, arranged to regulate the ventilation of the cargo tanks. Each cargo tank can preferably be equipped with a ventilation line that runs up into the centrally placed cargo rail.

[0019] The cargo rail is internally open and has an internal height greater than the normal standing height of a person.

[0020] The central cargo rail is equipped with tracks to move a derrick crane in the longitudinal direction of the deck.

[0021] The invention shall now be described in more detail with reference to the enclosed figures, in which,

Figure 1 shows a partially cross section of a vessel according to the invention.

Figure 2 shows a partially longitudinal cross section of a vessel according to the invention.

[0022] Figure 1 shows an offshore supply ship 10, of the type PSV, OSV, or the like, which is equipped with a central cargo rail 18 that extends centrally and longitudinally on the deck 12 in the longitudinal direction of the ship. Meant by centrally is not exactly mid ship, as the central cargo rail can also be placed, if appropriate, somewhat off-centre. Thereby, the deck 12 is divided into two cargo decks, one on the starboard side and one on the port side, respectively, in contrast to standard ships where the deck is comprised of one large cargo deck. Alternatively, the cargo rail 18 can support a derrick crane 14 (only the lower part of the crane 14 is shown) and furthermore, can be equipped with tracks 20 to permit longitudinal movement of the crane 14. The cargo rail 18 can be a relatively wide, full-height cargo rail with access to personnel centrally. Thereby, the sides of the ship 10 can be equipped with two relatively low and narrower side edges/railings 36 in contrast to the standard full height cargo rails with access for personnel.

[0023] Thereby, the cargo station in a central cargo rail

(the foundation 14) gives access for and can be used from both the starboard and port sides, in contrast to the standard need for two cargo stations in each cargo rail on both the starboard and port sides.

[0024] A number of tanks such as cargo tanks 30, slop tanks 32 for the collection of liquid and sludge tanks and saltwater tanks 34 can preferably be placed below the cargo deck 12. It can be seen in the figures that the cargo tanks 30 are placed centrally mid-ship and in a row in the longitudinal direction of the ship 10. Furthermore, the cargo tanks 30 can be equipped with loading and unloading equipment 28 in the form of pumps, pipes and the like.

[0025] In particular, in the area between the cargo tanks 30 and the deck 12, so called cofferdams 24 are provided and which are watertight rooms for the pipe installation or the like. According to the invention ventilation lines/pipes 22 run from the cargo tanks 30, and generally also from the slop tanks 32, through said cofferdams 24 and up into the centrally placed cargo rail 18. The ventilation lines 22 can end up in the cargo rail, possibly on the top or the side of the cargo rail, and one or more of the ventilation line's 22 outlets can be equipped with a valve such as a pressure vacuum valve 26 to control and regulate the venting of each tank.

Thus, shorter ventilation lines are provided, in particular from the central cargo tanks and which are especially important for type 1 products that can not have ventilation within a B/5 safety zone. A B/5 safety zone is the zone that extends from the hull to a fifth part of the line towards the centre for the summer waterline (IBC code Ch. 2.5). Furthermore, there is not a need for cofferdams to guide the pipes to the cargo rails at the sides, in contrast to known solutions where the ventilation lines must go to the sides of the ship through the cofferdams and which thereby take up valuable cargo space. A further advantage is that the ventilation of pump rooms and other rooms that need ventilation is simplified as there is no need for costly, watertight ventilation valves.

[0026] Furthermore, it shall be mentioned that the central cargo rail 14 can be placed both in line with the B/5 safety zone or, for that matter, also somewhat deviating from B/5, i.e. off-centre.

Claims

1. Offshore supply ship (10) for transport of cargo, comprising an, in the main, open deck (12), several cargo tanks (30) that lie below the open deck (12), and one or more watertight rooms (24) extend between a number of said cargo tanks (30) and the open deck (12), wherein the ship (10) further comprises

- a centrally and longitudinally running cargo rail (18) extending on said open deck (12) in longitudinal direction of the ship (10), dividing the deck (12) into two cargo decks, one on starboard side and one on port side, respectively, wherein

the cargo rail supports a derrick crane (14) and is equipped with tracks (20) for movement of said derrick crane (14), and the cargo rail (18) is open internally and has an internal height greater than the normal standing height for a person, and

- a number of ventilation lines (22) runs from said cargo tanks (30), through said watertight rooms (24) and up into the centrally placed cargo rail (18).

2. Offshore supply ship according to claim 1, **characterised in that** said ventilation lines (22) runs from a number of collecting tanks (32), such as slop tanks, and up into the centrally placed cargo rail (18).

3. Offshore supply ship according to claim 1, **characterised in that** an outlet to the ventilation lines (22) in the centrally placed cargo rail (18) comprises a valve (26), such as a pressure/vacuum valve, arranged to regulate the ventilation from the cargo tanks (30).

4. Offshore supply ship according to claim 1, **characterised in that** each type 1 cargo tank (30) is equipped with a ventilation line (22) that runs up into the centrally placed cargo rail (18).

Patentansprüche

1. Offshore-Versorgungsschiff (10) zum Transportieren von Fracht, umfassend ein im Wesentlichen offenes Deck (12), mehrere Frachtbehälter (30), die unter dem offenen Deck (12) angeordnet sind, und einen oder mehrere wasserdichte Räume (24), die sich zwischen einer Vielzahl der Frachtbehälter (30) und dem offenen Deck (12) erstrecken, wobei das Schiff (10) ferner umfasst

- eine zentral und longitudinal verlaufende Frachtschiene (18), die sich auf dem offenen Deck (12) in longitudinaler Richtung des Schiffs (10) erstreckt und das Deck (12) in zwei Frachtdecks unterteilt, wobei eines an der Steuerbordseite und eines entsprechend an der Backbordseite angeordnet ist, wobei die Frachtschiene einen Derrick-Kran (14) trägt und mit Gleisen (20) zum Bewegen des Derrick-Krans (14) ausgestattet ist, und wobei die Frachtschiene (18) innen offen ist und eine innere Höhe aufweist, die größer ist als die normale Stehhöhe einer Person, und

- eine Vielzahl von Belüftungsleitungen (22), die von den Frachtbehältern (30) durch die wasserdichten Räume (24) und hoch in die zentral angeordnete Frachtschiene (18) verläuft.

2. Offshore-Versorgungsschiff nach Anspruch 1, **dadurch gekennzeichnet, dass** Belüftungsleitungen (22) von einer Vielzahl von Sammelbehältern (32), wie Schmutzwasserbehältern, aufwärts in die zentral angeordnete Frachtschiene (18) verlaufen.

3. Offshore-Versorgungsschiff nach Anspruch 1, **dadurch gekennzeichnet, dass** ein Auslass der Belüftungsleitungen (22) in der zentral angeordneten Frachtschiene (18) ein Ventil (26), wie ein Druck-/Vakuumventil, umfasst, das dazu eingerichtet ist, die Belüftung der Frachtbehälter (30) zu regulieren.

4. Offshore-Versorgungsschiff nach Anspruch 1, **dadurch gekennzeichnet, dass** jeder Frachtbehälter (30) von Typ 1 mit einer Belüftungsleitung (22) ausgestattet ist, die aufwärts in die zentral angeordnete Frachtschiene (18) verläuft.

Revendications

1. Navire de ravitaillement en mer (10) pour le transport de cargaisons, comprenant un pont en majeure partie découvert (12), plusieurs citernes à cargaison (30) situées sous le pont découvert (12), et une ou plusieurs chambres étanches (24) s'étendent entre un nombre desdites citernes à cargaison (30) et le pont découvert (12), dans lequel le navire (10) comprend en outre

- un rail de charge à course centrale et longitudinale (18) s'étendant sur ledit pont découvert (12) dans la direction longitudinale du navire (10), divisant le pont (12) en deux ponts de chargement, l'un à tribord et l'autre à bâbord, respectivement, dans lequel le rail de charge supporte une grue de forage (14) et est équipé de chenilles (20) pour le déplacement de ladite grue de forage (14), et le rail de charge (18) est ouvert à l'intérieur et a une hauteur interne supérieure à la hauteur debout normale pour une personne, et

- plusieurs lignes de ventilation (22) partent desdites citernes à cargaison (30), à travers lesdites chambres étanches (24) et jusque dans le rail de charge (18) placé au centre.

2. Navire de ravitaillement en mer selon la revendication 1, **caractérisé en ce que** lesdites lignes de ventilation (22) partent d'une pluralité de citernes collectrices (32), telles que des citernes de décantation, et montent dans le rail de cargaison (18) placé au centre.

3. Navire de ravitaillement en mer selon la revendication 1, **caractérisé en ce qu'**une sortie vers les lignes de ventilation (22) dans le rail de cargaison (18)

placé au centre comprend une soupape (26), telle qu'une soupape de pression/dépression, agencée pour réguler la ventilation des citernes à cargaison (30).

5

4. Navire de ravitaillement en mer selon la revendication 1, **caractérisé en ce que** chaque citerne à cargaison de type 1 (30) est équipée d'une conduite de ventilation (22) qui monte dans le rail de cargaison (18) placé au centre.

10

15

20

25

30



35

40

45

50

55



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 2005054048 A1 [0004]
- US 20060213419 A1 [0005]
- GB 2162880 A [0005]
- WO 2005056379 A1 [0006]
- GB 1407602 A [0007]
- US 3031856 A [0007]
- GB 1000297 A [0007]
- GB 2269565 A [0007]