



(11) (21) (C) **2,115,528**  
(22) 1994/02/11  
(43) 1995/08/12  
(45) 2000/04/11


(72) Hart, David, GB

(73) Hart, David, GB

(51) Int.Cl.<sup>5</sup> A61H 3/04

(54) **DEAMBULATEUR ORTHETIQUE**

(54) **ORTHOTIC WALKER**



(57) In an orthotic walker, mechanism is provided to bias alternate motion of a user's legs. The mechanism may be a reciprocating bar at hip level, or at least one strap ends of which are attached to leg braces the bight passing round a fixed frame member. A stirrup mechanism may be pivoted at an "ankle joint" and the pivotal motion may be limited to avoid toe down position. The stirrup may have a clamp for a shoe. Brake mechanism may be movable between operative and inoperative positions. In the operative position rearward rolling is disallowed while forward motion is allowed.



## ABSTRACT OF THE INVENTION

In an orthotic walker, mechanism is provided to bias alternate motion of a user's legs. The mechanism may be a reciprocating bar at hip level, or at least one strap ends of which are attached to leg braces the bight passing round a fixed frame member. A stirrup mechanism may be pivoted at an "ankle joint" and the pivotal motion may be limited to avoid toe down position. The stirrup may have a clamp for a shoe. Brake mechanism may be movable between operative and inoperative positions. In the operative position rearward rolling is disallowed while forward motion is allowed.

## BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to an orthosis to provide adjustable support and control to a patient suffering from cerebral palsy or of a similar medical condition, allowing the patient to stand and walk.

Description of the Prior Art

There is no known cure for cerebral palsy. Therefore, treatment for the condition is aimed at helping the patient make best use of his or her physical abilities. For many people with cerebral palsy, there are available braces and other devices that can provide that degree of support which will enable the person to walk, but for many, the severity of their condition prevents them from even attaining a standing position.

British Patent No. 2,231,500 issued to David Hart, who is also the inventor of this invention, discloses a walking support orthosis intended for those people having disabilities which may not be so severe that they would normally be unable to even attain standing position. The orthosis of said British Patent No. 2,231,500 comprises a wheeled frame, support mechanism, a body brace means for releasably securing the body brace to support mechanism, means for patient to control steering of wheeled frame, means for adjusting amount of lifting support to the patient, means for automatically braking the rear floor wheels in the event of the patient failing to maintain an upright posture.

The body brace of said British Patent 2,231,500 holds the body of the user fixed in position in relation to the support. No provision has been made for the normal leg swinging that is normal in walking. Such leg swinging is normal in walking in able bodied persons and therefore desirable to mimic in an orthosis. it would also be desirable to accentuate this action in an

orthosis in order, inter alia, to provide follow through impetus to the user to take the next step.

Further desirable features in an orthosis of the type described and claimed in said British Patent would be the provision of foot manipulation means to discourage a toe-down stance in the user, shoe clamping means which is easily operable while providing a firm grip on the shoe. Also, importantly, an automatic brake to guard against undesirable uncontrolled rearward movement would be desirable. Such brakes should, of course, be disengageable when rearward movement is desired.

The present invention has addressed these concerns and has devised improvements to the orthosis which is the subject of this British Patent No. 2,231,500.

15

#### SUMMARY OF THE INVENTION

According to the invention there is provided a walking support orthosis comprising:

a wheeled frame and a support member for a body brace, the support member being located to extend at least partially behind the body of a user;

a body brace including leg braces having support engagement means to engage said support, the engagement means being located on a rear part of the body brace, and the leg braces having generally hip level pivotal connections to said support member to allow articulation of the hip joint of the user;

reciprocating bar mechanism to bias opposite action of legs of a user at generally hip level, the bar mechanism comprising;

a generally horizontal reciprocable bar behind the body brace pivoted to the frame for reciprocating movement so that ends of said reciprocable bar move alternatively forwards and rearwards;

upward extensions of said leg braces extending upwardly of said pivotal connections, and

links between each of said ends of the reciprocable bar with respective ones of said upward extensions  
5 whereby movement of one leg of a user in one direction reciprocates said reciprocable bar to bias the other leg of the user in the opposite direction.

Each of said links may comprise a bar pivoted at one end to one of said ends of the reciprocable bar and at  
10 the other end to one of said upward extension of said leg braces. The links may be straight bars either horizontal or tilted or they have a bend to adjust for any difference in height between the reciprocable bar and the upward extensions or the leg braces.

The height of the upward extensions has appreciable influence on the action of the reciprocable bar. The  
15 higher the extensions, the greater the travel of the ends of the reciprocable bar and the greater the effect on the user. The height of the upward extensions must, therefore, be chosen according to the effect desired.  
20

The length of each of the links is adjustable to allow for differences in front to rear distance according to the user. The length of the reciprocable bar may also be adjustable to allow for different side to side widths  
25 of the user.

Also according to the invention there is provided a walking support orthosis comprising:

a wheeled frame a support member for a body brace, the support member being located to extend at least  
30 partially behind the body of a user;

a body brace including leg braces, and having support engagement means to engage said support, the engagement means being located on a rear part of the body

brace, and the leg braces having generally hip-level pivotal connections to said support member to allow articulation of a hip joint of a user;

5 a reciprocating strap mechanism to bias opposite action of legs of a user, the said strap mechanism comprising a strap connected at each end to respective ones of said leg braces, a bight of the strap extending between the ends about a fixed part of said frame forward or rearward of the leg braces and distanced therefrom by  
10 approximately half the length of the strap.

The strap mechanism may comprise a rear strap having a rearwardly extending bight which passes around a post upstanding from a rear lower frame member. Each end of the strap may be attached to a thigh member of the leg  
15 brace.

Alternatively or additionally the strap mechanism may comprise a front strap having a forwardly extending bight which passes round a forward lower frame member. Each end of the front strap is attached to the leg brace  
20 through attachments on a lower part of the leg brace. When all of the reciprocable bar and a rear strap and a forward strap are all present, impetus may be given to the legs of a user at hip level, thigh level and shoe level, thus providing balanced strong impetus.

25 Also according to the invention there is provided a walking support orthosis comprising:

a wheeled frame;

a support member for a body brace, the support member being located to extend at least partially behind  
30 the body of a user;

a body brace including leg braces, and having support engagement means to engage said support, the engagement means being located on a rear part of the body brace, and the leg braces having generally hip level

connections to the support member to allow for articulation of a hip joint of a user;

each leg brace including:

5 a stirrup for supporting the foot of a user, the stirrup means comprising a generally horizontal support bar located to lie under the instep of a user and a stirrup leg fixed to the support bar at one leg end extending rearwardly upwardly, for example at 60 degrees, from the support bar to a pivotal connection with a lower  
10 end of a shank member of the leg brace;

a stop being provided to limit pivotal travel of the stirrup leg.

15 A clamp may be provided to clamp a shoe of the user to be fixed against swivelling on the support bar of the stirrup. The clamp may serve another function in that it may hold the shoe firmly on the support bar and prevent it swivelling on the support bar.

20 The stop may comprise a lug projecting from a rearward upward extension of the stirrup leg. The lug may abut a lower portion of said shank member to limit said pivotal travel of the stirrup leg beyond a preset limit.

25 The lug includes an enlarged portion to abut said shank member, whereby the limit of said pivotal travel is set according to the size of the enlarged portion. The enlarged portion may be an adjustable cam whereby the limit of said pivotal travel is adjustable.

The invention also includes a walking support orthosis comprising:

30 a wheeled frame;

a support member for a body brace, the support member being located to extend at least partially behind the body of a user;

a body brace including leg braces, and having support engagement means to engage said support, the engagement means being located on a rear part of the body brace, and the leg braces having generally hip level connections to the support member to allow for articulation of a hip joint of a user;

a brake mechanism being settable to an inoperative condition and into an operative condition, whereby, in the inoperative condition, no braking against rearward movement is applied, and, in the operative condition, automatic braking against rearward braking is applied while forward movement is unbraked. The brake mechanism may be located on a side lower frame member extending forwardly of a rear wheel of the wheeled frame, a brake block is attached to said side lower frame member to be movable between a forward inoperative position and a rear operative position in which it bears on said wheel when said wheel is rotated into a position for rearward rolling and in which said wheel is clear of the brake block when it is rotated into position for forward rolling. Preferably the brake mechanism is located on each of two side lower frame members.

Each brake block may be attached to said side lower frame member through a resiliently expansible strap whereby the strap is manually expansible to allow movement of the block between its operative and inoperative positions.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the present invention, reference will now be made by way of example to the accompanying drawings in which:-

Figure 1 shows a patient using a support orthosis according to the invention;

Figure 2 illustrates part of an orthosis such as that of Figure 1 and having a reciprocating mechanism to provide limb swinging;

Figures 3A and 3B illustrate apparatus to provide follow through impetus to the legs;

5           Figures 4A, 4B, 4C, etc. are simplistic sketches showing the effect of the apparatus of Figures 3A and 3B on a user;

Figures 5 illustrates a mechanism for discouraging toe-down orientation of a user's foot and a shoe clamping mechanism;

10           Figure 6 illustrates an automatic disengageable brake against rearward movement.

#### DETAILED DESCRIPTION OF THE DRAWINGS

The illustrated walking support orthosis of the drawings comprises a frame 12 having a lower frame portion comprising a front horizontal member 12A, side members 12B and a rear member 12C and four wheels 14. The frame members may be, for example, square or round section steel tube and may be telescopic for adjustment of size. A rear portion of the frame 12 extends upwardly to provide a support member 16 for a body brace 17 which includes leg braces 19. The height of support 16 may be adjustable by any convenient means, for example, those illustrated in the aforementioned British Patent 2,231,500 but it should be generally in the mid-region of the body. Possibly a generally horizontal body brace 17 may be around hip level and an upstanding support hook (not shown) for the body brace 17 may be of adjustable height above the support member 16. The device includes reciprocating bar mechanism 18, shown is detail in Figure 2 to help the user swing his legs alternately. The device also includes a reciprocating strap mechanism 20, shown in more detail in Figure 3, to supplement the reciprocating bar mechanism by providing follow through

15  
20  
25

movement to the user's legs. The device also includes  
foot orientation mechanism 24 and a shoe clamp 26, shown  
in more detail in Figure 5, to discourage the tendency of  
users to have their feet in a position with the toes  
5 pointing unnaturally downwards. A brake 28, shown more  
fully in Figures 6A and 6B, is provided which may be set  
in one position to automatically engage against rearward  
motion. Alternatively the brake 28 may be set so that  
rearward movement is allowed.

10 Figure 2 shows a view of the reciprocating bar  
mechanism 18 from the rear in the region of a horizontal  
U-shaped frame member 34 of the support 16. The frame  
member 34 is pivoted at each end 35a, 35b to the  
respective thigh members 38a, 38b of the leg braces of  
15 the orthotic device. Each thigh member 38a, 38b has a  
short extension 42a, 42b, upward of its respective pivot  
point 40a, 40b with the respective frame member end 35a,  
35b of the support 16. A generally horizontal,  
reciprocable bar 30 is located above and slightly behind  
20 the frame member 34 and is pivoted to it through a  
vertical pivot 32 so that it may pivot in a generally  
horizontal plane. The reciprocable bar 30 is connected  
to the upper ends of the thigh member extensions 42a, 42b  
through links 44a, 44b. Each link 44a, 44b is pivoted at  
25 one end to the reciprocable bar 30 and at the other end  
to the respective thigh member extension 42a, 42b so that  
the link extends forwardly from the reciprocable bar 30  
to the respective thigh member extension 42a, 42b. Each  
link may be generally horizontal or may be tilted to  
30 allow for a difference in height between the level of the  
respective end of reciprocable bar 30 and the top of the  
respective thigh member extension 42a, 42b.  
Alternatively or additionally, as shown, the pivot arm  
may have a bend to allow for this difference of level or  
35 to extend the link about the user's hips. The pivot arms  
44a, 44b may, themselves, be extensible to allow for

adjustment in the distance between the respective end of reciprocable bar 30 and the respective thigh extension member 42a, 42b.

5 In use, when the leg of a user is moved forward in walking step, the thigh member 38a pivots at pivot 40a on the frame member 34. Thus, the lower end of thigh member 38a, which corresponds roughly to the user's knee moves forwardly and the top end of extension member 42a moves slightly rearwardly. The rearward movement of the top of  
10 extension member 42a pushes pivot arm 44a rearwardly to push the respective first end 35a of reciprocable bar 30 rearwardly also. This causes reciprocable bar 30 to pivot on pivot 32 to move its other end 35b forwardly. Forward movement of end 35b pushes on the pivot arm 44b.  
15 This other pivot arm 44b cannot move forwardly until there is movement in the other thigh member brace 38b. In order to allow forward movement of pivot member 44b, the lower part of thigh member 38b must move rearwardly to pivot it on pivot 40b so that the top of its extension  
20 member 42b moves forwardly with pivot arm 44b.

Thus, movement of the leg of a user so that thigh member 38a moves forwardly at its lower end exerts appreciable force on the hips of the user to bias the opposing hip to swing the opposing leg rearwardly.

25 The encouragement to leg swinging given by the action of the reciprocable bar 30 may be enhanced by the strap mechanism of Figure 3 which acts directly on the legs of the user. The strap mechanism 20 of Figure 3 may be utilized on an orthosis which is provided or which  
30 is not provided with the reciprocable bar mechanism described above. When the reciprocable bar mechanism is present the strap mechanism 20 provides enhancement but when the reciprocable bar mechanism is not present the

strap mechanism may provide the sole impetus for moving the legs alternately.

5 The strap mechanism 20 comprises a strap 50 and/or a strap 52. The strap 50 is attached at each end to a lower part of the leg brace. For example, each end 51a, 51b, of strap 50 may be attached to a lower part of thigh member 38a, 38b of the leg brace. Shank members 52a and 52b are connected respectively below thigh members 38a and 38b through a pivoting joint 54a, 54b which, for 10 verbal illustration, will be referred to as a "knee joint". The knee joint is free motion.

The strap 50 extends rearwardly from the leg braces to extend around a post 56 extending upwardly from the rear part of the main frame. Post 56 may be provided 15 with a slot 55 or other restraining means to maintain the bight of strap 50 within a confined vertical region of the post 56 which may have a rotating sleeve to promote easy movement of the strap around the post. The ends 51a and 51b may be releasably attached to the thigh members 20 38a and 38b through any suitable quick release means such as a quick release snap having a manually withdrawable latch. The snaps may be attached to the strap 50 through a swivel.

In use, when the thigh portion 38a of the user is 25 moved forwardly the thigh portion 38b is forced rearwardly as the bight of the strap 50 travels around the post 56. The strap 50 may be provided with an adjustment buckle 58 both for the purpose of adjusting to different user sizes and also to vary its effect. A 30 shorter strap will cause a shorter step size. The strap may be made of any material sufficiently strong to stand up to the pressure to cause one leg to be forced to move in a direction opposite to the other. Webbing made from

nylon or polypropylene is very suitable but cotton webbing or other material may also be used.

5 Strap 60 may be used to supplement the action of strap 50 or to replace it. The action of strap 60 is very similar to that of strap 50 but the bight of the strap passes forwardly around a forward horizontal frame member 12A and the ends 61a and 61b are attached to the stirrup 70. Strap 60, like strap 50, may be provided with adjustment means and any convenient means may be  
10 used.

When all of the reciprocable bar 30, the strap 50 and the strap 60 are all provided, considerable impetus in alternate leg movement may be provided at different points along of the length of the leg. This may be  
15 demonstrated by the sketches of Figures 4A, 4B and 4C.

Since strap 60 has its bight around a horizontal member, it may vary in its position along the length of the horizontal member according to the direction in which the user is facing. Thus if the user is angled to the  
20 left then the bight of strap 60 will tend to be towards one end of the horizontal member 62 which may have a rotatable sleeve to promote easy movement of the strap therearound. If the user is angled towards the right the bight will tend to be towards the other end. Thus the  
25 effect of strap 60 will be similar irrespective of the direction in which the user is facing.

Figure 5 and 6 illustrate the mechanism 24 for inhibiting the natural tendency of some non-ambulatory users to take up a toe-down position and the shoe  
30 clamping mechanism 26.

Figure 5 shows the lower end of shank member 52 of the leg brace pivoted at pivot 72 to outer leg 74 of

stirrup 70 for shoe 76. The pivot 72 mimics the ankle joint of the user.

5 The stirrup 70, itself, is generally L-shaped. One leg of the L is the outer upstanding leg 74 and the support bar is a horizontal member 78 extending under the shoe 76 in the groove between heel 80 and sole 82. It is not necessary to form the stirrup as a U-shaped member having an inner leg. Indeed, the absence of an inner leg may have significant advantages in that inwardly  
10 projecting parts of adjacent inner legs will not foul each other when they are not present but, when they are present, there may be a significant risk of entanglement. Nevertheless, the presence of an inner leg is not positively excluded.

15 The upstanding stirrup leg 74 projects upwardly and rearwardly from its lower end connected with support bar 78 in the groove between the heel 80 and the sole 82 of the shoe to the pivot 72. The angle of the leg 74 to the horizontal is about 60 degrees. In the position shown in  
20 Figure 5 the shoe is held in balanced horizontal position on support bar 78. If leg 74 rotates on pivot 72 in an anticlockwise direction, support bar 78 will tend to raise the toe of the shoe as the lower end of leg 74 rises toward the horizontal. If, on the other hand, it  
25 were possible for leg 74 to rotate in a clockwise direction on pivot 72 the toe of the shoe would drop until the leg 74 became vertical. This clockwise movement is prevented by the provision of an outwardly projecting lug 84 on a rearward extension 86 of leg 74.  
30 Rearward extension 86 is axially aligned with leg 74 and integral with it. Lug 84 projects from it to abut the lower part of shank member 52 to prevent clockwise rotation of leg 74 beyond a predetermined angle in which shoe 76 is held horizontal.

In order to inhibit swivelling of the user's foot or support bar 78, the shoe 76 should be clamped in position with respect to it. Convenient clamping may be carried out as described hereafter.

5           The force of a user's toe-down inclination may be appreciable and therefore, the length of rearward extension 86 and the location of lug 84 should be such that sufficient leverage is exerted to hold the shoe horizontal. When the length of extension 86 is  
10 significant, it will be necessary to make lug 84 of sufficient diameter as to maintain the angle of leg 74 to maintain the shoe horizontal. The diameter may either be increased over the whole length of lug 84 or an enlarged boss 88 may be provided to bear against shank member 52  
15 of the leg brace. The length of the rearward extension 86 and the diameter of leg 84 are interdependent but their choices will be easily apparent.

The angle of leg 74 to the horizontal plane of the sole of the shoe may suitably in the region of 60  
20 degrees. This angle, however, is a matter of choice. The steeper the angle, i.e. the more nearly vertical is leg 74, the less influence it has in holding the toe of the shoe up. If, on the other hand, the angle of leg 74 is much shallower i.e. its lower end projects much  
25 further forward, problems may be encountered in locating the horizontal leg 78 in the groove between the heel and the sole of the shoe and there may be difficulties in sizing lug 84 to abut shank member 52 to maintain leg 74 at its set angle against clockwise rotation. When an  
30 orthopaedic shoe is utilized in the groove between heel and sole may be, to an extent, located according to choice to allow for a particular angle of stirrup leg 74. Nevertheless, for at least aesthetic reasons the groove between heel and sole should be located conventionally.

When lug 84 is provided with an enlarged boss 88 to bear against the lower part of shank member 52, it may be convenient, in certain circumstances, to allow a greater toe-down orientation. Thus, boss 88 may be a cam pivotable on lug 84 so that it can be moved into a position where no clockwise movement of leg 74 is permitted, i.e. no toe-down allowed (see Figure 5). Alternatively it may be pivoted out of contact with shank member 52 so that some toe-down movement is allowed.

The stirrup 70 provides a base for the clamping arrangement 26 which may give a firm clamp to the user's shoe without the need of multiple straps and awkward fastenings.

The leg 74 is a two part leg having an upper part 73 and a lower part 75. The lower part 75 carries the support bar 78 and is connected to the upper part 73 to be rigid with it in use. A hook 79 is provided at the inner end of support bar 78 to hook over a projecting edge of sole 82 of shoe 76. A clamp 90 is connected to act at the outer edge of shoe 76 to clamp the projecting edge of the sole 82 at that point and to press the shoe firmly against hook 79. The clamping bar 90 is provided with a lower edge 96 adapted to clamp firmly against the top seam between the upper of shoe 76 and the base. Screw 92 may be tightened in apertures through upper and lower parts of leg 74 to bias the clamp 90 against the shoe and to bias the shoe against hook 79. Loosening the screw loosens clamp 90. Thus when the clamping bar is located in the position shown in Figure 6, the base 77 of the shoe 76 is held firmly between the support leg 78 of stirrup 70 and the clamping bar 90.

When it is desired to release the shoe 76 from the clamp, all that it is necessary to loosen nut 94 to allow the clamping bar to loosen on bolt 92.

5 Figure 6 illustrates the brake 28 on side rail 12B<sup>1</sup> in inoperative position. Figure 6 illustrates the brake 28 on side rail 12B<sup>11</sup> in operative position. The orthosis is attempting to move rearwardly in the direction of arrow A and the brake 28 is engaged.

10 The brake mechanism 28 comprises brake blocks 100 mounted on respective lower side frame members 12B which extend from front to rear of the frame of the orthosis. The side lower frame members 102 of the orthosis have, at their rear ends, wheels 104.

15 When it is desired to move brake block into a position where it automatically brakes the orthosis against rearward rolling, the brake block is moved rearwardly on frame member 102 into the position shown on side member 12B<sup>11</sup>. The brake block 100 is attached by a resiliently expansible strap. When the orthosis attempts  
20 to roll rearwardly in the direction of the arrow against the bias of the strap, the brake block is drawn against the wheel to jam it and thus brake rearward motion. On the other hand, when the orthosis rolls forwardly, no rearward impetus is exerted on the block 100.

EMBODIMENTS OF THE INVENTION IN WHICH EXCLUSIVE PROPERTY  
OR PRIVILEGE IS CLAIMED, ARE AS FOLLOWS:

1. A walking support orthosis comprising:

5 a wheeled frame and a support member for a body brace, the support member  
being located to extend at least partially behind the body of a user;

said body brace including leg braces and support engagement means to  
engage said support member, the engagement means being located on a rear part of  
the body brace, and the leg braces having generally hip level pivotal connections to  
said support member to allow articulation of the hip joint of the user;

10 reciprocating bar mechanism to bias opposite action of the leg braces at  
generally hip level, the bar mechanism comprising;

a generally horizontal reciprocable bar behind the body brace pivoted to the  
frame for reciprocating movement so that ends of said reciprocable bar move  
alternatively forwards and rearwards,

15 upward extensions of said leg braces extending upwardly of said pivotal  
connections, and

links between each of said ends of the reciprocable bar with respective ones  
of said upward extensions whereby movement of one leg of a user in one direction  
reciprocates said reciprocable bar to bias the other leg of the user in the opposite  
20 direction.

2. A walking support orthosis as claimed in claim 1 in which each of said links  
comprises a bar pivoted at one end to one of said ends of the reciprocable bar and  
at the other end to one of said upward extension of said leg braces.

3. A walking support orthosis as claimed in claim 2 in which the length of each  
25 of said links is adjustable.

4. A walking support orthosis comprising:  
a wheeled frame;  
a support member for a body brace, the support member being located to extend at least partially behind the body of a user;

5 said body brace including leg braces, and having support engagement means to engage said support member, the engagement means being located on a rear part of the body brace, and the leg braces having generally hip-level pivotal connections to said support member to allow articulation of a hip joint of a user;

10 a reciprocating strap mechanism to bias opposite action of the leg braces, the said strap mechanism comprising a strap connected at each end to respective ones of said leg braces, a bight of the strap extending between the ends about a fixed part of said frame forward or rearward of the leg braces and distanced therefrom by approximately half the length of the strap.

15 5. A walking support orthosis as claimed in claim 4 in which said strap mechanism comprises a rear strap having a rearwardly extending bight which passes around a post upstanding from a rear lower frame member.

6. A walking support orthosis as claimed in claim 5 in which each end of the strap is attached to a member of the leg brace.

20 7. A walking support orthosis as claimed in claim 4 in which the said strap mechanism comprises a front strap having a forwardly extending bight which passes round a forward lower frame member.

8. A walking support orthosis as claimed in claim 7 in which each end of the front strap is attached to the leg brace through a lower part of the leg brace.

9. A walking orthosis as claimed in claim 4 also comprising:  
reciprocating bar mechanism to bias opposite action of legs of a user at  
generally hip level, the bar mechanism comprising;

5 a generally horizontal reciprocable bar behind the body brace pivoted to the  
frame for reciprocating movement so that ends of said reciprocable bar move  
alternatively forwards and rearwards, upward extensions of said leg braces  
extending upwardly of said pivoted connections, and

10 links between each of said ends of the reciprocal bar with respective ones of  
said upward extensions whereby movement of one leg of a user in one direction  
reciprocates said reciprocal bar to bias the other leg of the user in the opposite  
direction.

10. A walking support orthosis comprising:

a wheeled frame;

15 a support member for a body brace, the support member being located to  
extend at least partially behind the body of a user;

said body brace including leg braces, and having support engagement means  
to engage said support member, the engagement means being located on a rear part  
of the body brace, and the leg braces having generally hip level connections to the  
support member to allow for articulation of a hip joint of a user;

20 each leg brace including:

a stirrup means for supporting the foot of a user, the stirrup means  
comprising a generally horizontal support bar located to lie under the instep of a user  
and a stirrup leg fixed to the support bar, said stirrup leg extending rearwardly  
upwardly from the support bar to a pivotal connection with a lower end of a shank  
25 member of the leg brace;

a stop being provided to limit pivotal travel of the stirrup leg.

11. A walking support orthosis as claimed in claim 10 in which a clamp is provided to clamp a shoe of the user to be fixed against swivelling on the support bar of the stirrup.

5 12. A walking support orthosis as claimed in claim 11 in which the stirrup leg extends rearwardly upwardly from the support bar at an angle of about 60 degrees to the horizontal.

10 13. A walking support orthosis as claimed in claim 10 in which the stop comprises a lug projecting from a rearward upward extension of the stirrup leg, the lug abutting a lower portion of said shank member to limit said pivotal travel of the stirrup leg beyond a preset limit.

14. A walking support orthosis as claimed in claim 13 in which said lug includes an enlarged portion to abut said shank member, whereby the limit of said pivotal travel is set according to the size of the enlarged portion.

15 15. A walking support orthosis as claimed in claim 14 in which the enlarged portion is an adjustable cam whereby the limit of said pivotal travel is adjustable.

16. A walking support orthosis comprising:

a wheeled frame;

a support member for a body brace, the support member being located to extend at least partially behind the body of a user;

20 said body brace including leg braces, and having support engagement means to engage said support member, the engagement means being located on a rear part of the body brace, and the leg braces having generally hip level connections to the support member to allow for articulation of a hip joint of a user;

a brake mechanism being settable to an inoperative condition and into an operative condition, whereby, in the inoperative condition, no braking against rearward movement is applied, and, in the operative condition, automatic braking against rearward braking is applied while forward movement is unbraked.

5 17. A walking support orthosis as claimed in claim 16 in which a side lower  
frame member extends forwardly of a rear castor wheel of the wheeled frame and  
a brake block is attached to said side lower frame member to be movable between  
a forward inoperative position and a rear operative position in which it is drawn  
10 against the wheel to jam against the wheel when said wheel rotates rearwardly but  
is clear of the wheel when it is rotated forwardly.

18. A walking support orthosis as claimed in claim 17 in which two side lower  
frame members are present, each extending forwardly of a wheel and each provided  
with a brake block.

15 19. A walking support orthosis as claimed in claim 18 in which said brake block  
is attached to said side lower frame member through a resiliently expansible strap  
whereby the strap is manually expansible to allow movement of the block between  
it operative and inoperative positions.

20. A walking support orthosis comprising:  
a wheeled frame;  
20 a body brace engaged with said wheeled frame, said body brace including  
two movable leg braces;  
a reciprocating mechanism engaging said leg braces and said wheeled frame  
to bias opposite action of said leg braces such that as one leg brace moves forward  
the second leg brace moves rearward.

21. A walking support orthosis as claimed in claim 20, wherein said body brace is removably engaged with said wheeled frame.
22. A walking support orthosis as claimed in claim 20, said reciprocating mechanism comprising:
- 5 a reciprocable bar pivotally fitted to said wheeled frame so that ends of said reciprocable bar move alternatively forwards and rearwards, and
- links between each of said ends of said reciprocable bar and respective leg braces whereby movement of one leg brace in one direction reciprocates said reciprocable bar to bias the other leg brace in the opposite direction.
- 10 23. A walking support orthosis as claimed in claim 22, each of said links comprising a bar pivoted at one end to one of said ends of said reciprocable bar and at the other end to one of said leg braces.
24. A walking support orthosis as claimed in claim 23, wherein the length of each of said links is adjustable.
- 15 25. A walking support orthosis as claimed in claim 20, said reciprocating mechanism comprising:
- a flexible member connected at each end to respective ones of said leg braces and a bight of said flexible member being movably connected to said wheeled frame.
- 20 26. A walking support orthosis as claimed in claim 25, said wheeled frame including guide means for guiding said flexible member.
27. A walking support orthosis as claimed in claim 25, said bight of said flexible member extending rearwardly.

28. A walking support orthosis as claimed in claim 27, wherein each end of the flexible member is attached to respective leg braces at an upper part of the leg brace.

29. A walking support orthosis as claimed in claim 25, wherein said flexible member is detachably connected to said leg braces.

5 30. A walking support orthosis as claimed in claim 25 said bight of said flexible member extending forwardly.

31. A walking support orthosis as claimed in claim 30, wherein each end of the flexible member is attached to respective leg braces at a lower part of the leg brace.

10 32. A walking orthosis as claimed in claim 25, said reciprocating mechanism further comprising:

a reciprocable bar pivotally fitted to said wheeled frame so that ends of said reciprocable bar move alternatively forwards and rearwards, and

15 links between each of said ends of said reciprocal bar and respective leg braces whereby movement of one leg brace in one direction reciprocates said reciprocal bar to bias movement of the other leg brace in the opposite direction.

33. A walking support orthosis comprising:

a wheeled frame;

20 a body brace engaged with said wheeled frame, said body brace including two leg braces, each leg brace including a stop mechanism for preventing a foot of a user from having a toe-down orientation.

34. A walking support orthosis as claimed in claim 33, wherein each said leg brace includes a shank member, said stop mechanism comprising

a support bar for supporting the foot of a user;

a stirrup leg fixed to the support bar, said stirrup leg extending from said support bar to a pivotal connection with a lower end of said shank member;  
a stop provided to limit pivotal travel of the stirrup leg.

5 35. A walking support orthosis as claimed in claim 33, each said leg brace further including a clamp to prevent a shoe of the user from swivelling on said support bar.

36. A walking support orthosis as claimed in claim 34, wherein said stirrup leg extends rearwardly upwardly from said support bar at an angle of about 60 degrees to the horizontal.

10 37. A walking support orthosis as claimed in claim 34, said stop comprising a lug projecting from a rearward upward extension of said stirrup leg, said lug abutting a lower portion of said shank member to limit said pivotal travel of said stirrup leg beyond a preset limit.

15 38. A walking support orthosis as claimed in claim 37, said lug comprising an enlarged portion of said stirrup leg that abuts said shank member, whereby the limit of said pivotal travel is set according to the size of the enlarged portion.

39. A walking support orthosis as claimed in claim 37, wherein said lug is an adjustable cam whereby the limit of said pivotal travel is adjustable.

20 40. A walking support orthosis comprising:  
a wheeled frame;  
a body brace engaged with said wheeled frame, said body brace including two leg braces;

a brake mechanism settable to an inoperative position and to an operative position, whereby, in said inoperative position, no braking is applied, and, in said operative position, automatic braking against rearward movement is applied while forward movement is unbraked.

5 41. A walking support orthosis as claimed in claim 40,  
said wheeled frame including a side frame member and a rear wheel, said  
side frame member extending forwardly of said rear wheel; and

10 said brake mechanism comprising a brake block provided to said side frame  
member such that when in said operative position said brake block is drawn against  
said rear wheel when said rear wheel rotates rearwardly but is pushed clear of said  
rear wheel when said rear wheel rotates forwardly.

42. A walking support orthosis as claimed in claim 40, said wheeled frame  
including two side frame members and two rear wheels, said side frame members  
extending forwardly of said rear wheels; and

15 said brake mechanism comprising brake blocks provided to said side frame  
members such that when in said operative position respective said brake blocks are  
drawn against respective said rear wheels when respective said rear wheels rotate  
rearwardly but are pushed clear of respective said rear wheels when respective said  
rear wheels rotate forwardly.

20 43. A walking support orthosis as claimed in claim 41, said brake mechanism  
further comprising a resiliently expansible strap for attaching said brake block to  
said side frame member whereby said strap is manually expansible to allow  
movement of said brake block between said operative position and said inoperative  
position.






FIG. 1






FIG. 3B




FIG. 4A




FIG. 4B






FIG. 4C



C