



(12) **PATENT**

(11) **345786**

(13) **B1**

NORWAY

(19) **NO**

(51) **Int Cl.**

E21B 43/116 (2006.01)


E21B 43/117 (2006.01)

Norwegian Industrial Property Office

(21)	Application nr.	20171759	(86)	International Filing Date and Application Number	2014.07.16 PCT/CA2014/050673
(22)	Date of Filing	2017.11.07	(85)	Date of Entry into National Phase	2017.11.07
(24)	Date of Effect	2014.07.16	(30)	Priority	2013.07.18, CA, 2 821 506
(41)	Publicly Available	2016.01.06			
(45)	Granted	2021.08.09			
(62)	Divisional application	20160017, 2016.01.06			
(73)	Proprietor	DynaEnergetics Europe GmbH, Kaiserstrasse 3, 53840 TROISDORF, Tyskland			
(72)	Inventor	David C Parks, c/o JDP Engineering & Machine Inc., 12 Crestmont Way SW, ABT3B5Z6 CALGARY, Canada Frank Haron Preiss, An der Arndtruhe 20, 53175 BONN, Tyskland Liam McNelis, Gallusstrasse 72, 53227 BONN, Tyskland Eric Mulhern, 2936-41 Avenue NW, ABT6T1K5 EDMONTON, Canada Thilo Scharf, Derora Churchhill, LETTERKENNY CO., DONEGAL, Irland			
(74)	Agent or Attorney	BRYN AARFLOT AS, Stortingsgata 8, 0161 OSLO, Norge			

(54)	Title	PERFORATION GUN COMPONENTS AND SYSTEM
(56)	References Cited:	US 2010/089643 A1 US 2012/298361 A1
(57)	Abstract	

A perforation gun system based on combinations of basic components including a top connector, a self-centralizing charge holder system and a bottom connector that can double as a spacer. Any number of spacers can be used with any number of holders for any desired specific metric or imperial shot density, phase and length gun system. A perforation gun system kit as well as a method of assembling a perforation gun system is also disclosed.



FIELD

[0001] A perforation gun system is generally described. More particularly, various perforation gun components that can be modularly assembled into a perforation gun system, the assembled perforated gun system itself, a perforation gun system kit, and a method for assembling a perforation gun system are generally described.

BACKGROUND

[0002] Perforation gun systems are used in well bore perforating in the oil and natural gas industries to tie a bore hole with a storage horizon within which a storage reservoir of oil or natural gas is located.

[0003] A typical perforation gun system consists of an outer gun carrier, arranged in the interior of which there are perforators-usually hollow or projectile charges-that shoot radially outwards through the gun carrier after detonation. Penetration holes remain in the gun carrier after the shot.

[0004] In order to initiate the perforators, there is a detonating cord leading through the gun carrier that is coupled to a detonator.

[0005] Different perforating scenarios often require different phasing and density of charges or gun lengths. Moreover, it is sometimes desirable that the perforators shooting radially outwards from the gun carrier be oriented in different directions along the length of the barrel. Therefore, phasing may be required between different guns along the length.

[0006] Onsite assembly of perforation gun systems may also be problematic under certain conditions as there are certain safety hazards inherent to the assembly of perforation guns due to the explosive nature of certain of its sub-components, including the detonator and the detonating cord.

[0007] There is thus a need for a perforation gun system, which by virtue of its design and components would be able to address at least one of the above-mentioned needs, or overcome or at least minimize at least one of the above-mentioned drawbacks.

SUMMARY

[0008] According to an embodiment, an object is to provide a perforation gun system that

addresses at least one of the above-mentioned needs.

[0009] The main features of the present invention are given in the independent claim 1. Additional features of the invention are given in the dependent claims. According to an embodiment, there is provided a perforation gun system having an outer gun carrier and comprising:

- 5 - a top connector;
- at least one stackable charge holder for centralizing a single shaped charge within the gun carrier;
- a detonation cord connected to the top connector and to each stackable charge holder;
- at least one bottom connector for terminating the detonation cord in the gun system; and
- 10 - a detonator energetically coupled to the detonation cord,

wherein each of the top connector, at least one stackable charge holder and at least one bottom connector comprise a rotation coupling for providing a selectable clocking rotation between each of the top connector, at least one stackable charge holder and at least one bottom connector.

[0010] In some embodiments, the bottom connector may double as a spacer for spacing a plurality of stackable charge holders, and may either act as a metric dimensioned spacer or as an imperial dimensioned spacer for any specific metric or imperial shot density, phase and length gun system.

[0011] According to another aspect, there is also provided a perforation gun system kit having component parts capable of being assembled within an outer gun carrier, the kit comprising a combination of:

- a top connector;
- at least one stackable charge holder for centralizing a single shaped charge within the gun carrier;
- a detonation cord connectable to the top connector and to each stackable charge holder;
- 25 - at least one bottom connector adapted for terminating the detonation cord in the gun system; and
- a detonator energetically couplable to the detonation cord,

wherein each of the top connector, at least one stackable charge holder and at least one bottom connector comprise a coupling having a plurality of rotational degrees of freedom for providing a selectable rotation between each of the top connector, at least one stackable charge holder and at least one bottom connector.

5 [0012] According to another aspect, there is also provided a method for assembling a perforation gun system, comprising the steps of:

providing a perforation gun system kit having component parts capable of being assembled within an outer gun carrier, the kit comprising a combination of:

- a top connector;
- 10 - at least one stackable charge holder for centralizing a single shaped charge within the gun carrier;
- a detonation cord connectable to the top connector and to each stackable charge holder;
- at least one bottom connector adapted for terminating the detonation cord in the gun system and adapted for doubling as a spacer for spacing a plurality of stackable charge holders; and
- 15 - a detonator energetically couplable to the detonation cord,

wherein each of the top connector, at least one stackable charge holder and at least one bottom connector comprise a coupling having a plurality of rotational degrees of freedom for providing a selectable rotation between each of the top connector, at least one stackable charge holder and at least one bottom connector;

20 assembling a plurality of the stackable charge holders in a predetermined phase to form a first gun assembly;

running the detonation cord into a bottommost bottom connector;

assembling the bottommost bottom connector onto the assembled plurality of stackable charge holders;

25 running a through wire between the bottommost bottom connector and the top connector, so that the wire goes from the top connector to the bottom connector;

clicking the detonation cord into recessed formed in capturing projections, the captured projec-

tions being provided in each of the charge holders;
 running the detonation cord into the top connector;
 cutting the detonator cord; and
 installing charges into each of the charge holders.

5 [0013] A number of optional steps that are detailed below may be added to the above-described steps of the method.

[0014] According to another aspect, there is also provided a top connector for a perforation gun system comprising:

- a coupler for providing energetic coupling between a detonator and a detonating cord;
- 10 - at least one directional locking fin for locking the top connector within a gun carrier;
- a rotation coupling for providing a selectable clocking rotation between the top connector, and a charge holder

wherein the top connector is configured to receive electrical connections therethrough.

15 [0015] According to another aspect, there is also provided a stackable charge holder for a perforation gun system having an outer gun carrier, the charge holder comprising:

- a charge receiving structure for receiving a single shaped charge;
- a plurality of projections for centralizing the shaped charge within the gun carrier; and
- at least one rotation coupling for providing a selectable clocking rotation between the charge holder and an adjacent component in the perforation gun system;
- 20 wherein a pair of the plurality of projections is configured for capturing a detonation cord traversing the charge holder.

[0016] According to another aspect, there is also provided a bottom connector for a perforation gun system comprising:

- a terminating structure arranged for terminating a detonation cord in the gun system;
- 25 - a plurality of wings for axially locking the bottom connector to a snap ring fixed in the carrier.
- a rotation coupling for providing a selectable clocking rotation between the bottom connector

and a charge holder;

wherein the rotation coupling is arranged such that bottom connector doubles as a spacer for spacing a plurality of stackable charge holders.

BRIEF DESCRIPTION OF THE DRAWINGS

- 5 [0017] These and other objects and advantages will become apparent upon reading the detailed description and upon referring to specific embodiments thereof that are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments and are not therefore to be considered to be limiting of its scope, exemplary embodiments will be described and explained with additional specificity and detail through the use of the accompa-
- 10 nying drawings in which:
- [0018] FIG. 1 is a side cut view of a perforation gun system according to an embodiment;
- [0019] FIG. 2 is a side view of a top connector, bottom connector and stackable charge holders of a perforation gun system in accordance with another embodiment;
- [0020] FIG. 3 is a side view of a top connector, bottom connector and stackable charge
- 15 holders of a perforation gun system in accordance with another embodiment;
- [0021] FIG. 4 is a front perspective view of a bottom connector in accordance with an embodiment;
- [0022] FIG. 5 is a rear perspective view of the bottom connector shown in FIG. 4;
- [0023] FIG. 6 is a front view of a stackable charge holder in accordance with an embodi-
- 20 ment;
- [0024] FIG. 7 is a front perspective view of the stackable charge holder shown in FIG. 6;
- [0025] FIG. 8 is a rear perspective view of the stackable charge holder shown in FIG. 6;
- [0026] FIG. 9 is a bottom view of the stackable charge holder shown in FIG. 6;
- [0027] FIG. 10 is a top view of the stackable charge holder shown in FIG. 6;
- 25 [0028] FIG. 11 is a bottom view of a half-portion of a top connector in accordance with an embodiment;
- [0029] FIG. 12 is a side view of the half-portion of the top connector shown in FIG. 11;

[0030] FIG. 13 is a top perspective view of the half-portion of the top connector shown in FIG. 11;

[0031] FIG. 14 is a bottom perspective view of the half-portion of the top connector shown in FIG. 11;

5 [0032] FIG. 15 is a perspective view of a top connector in accordance with an embodiment;

[0033] FIG. 16 is a front end view of the top connector shown in FIG. 15;

[0034] FIG. 17 is a rear end view of the top connector shown in FIG. 15;

[0035] FIG. 18 is a rear perspective view of the top connector shown in FIG. 15;

10 [0036] FIG. 19 is an enlarged detailed side cut view of a portion of the perforation gun system including a bulkhead and stackable charge holders shown in FIG. 1;

[0037] FIG. 20 is a perspective view of a bottom sub of a gun system in accordance with an embodiment;

15 [0038] FIG. 21 is a side view of a gun carrier of a gun system in accordance with an embodiment;

[0039] FIG. 22 is a side cut view of the gun carrier shown in FIG. 21;

[0040] FIG. 23 is a side view of a top sub of a gun system in accordance with an embodiment;

[0041] FIG. 24 is a side cut view of the top sub shown in FIG. 23;

20 [0042] FIG. 25 is a side view of a tandem seal adapter of a gun system in accordance with an embodiment;

[0043] FIG. 26 is a perspective view of the tandem seal adapter shown in FIG. 25;

[0044] FIG. 27 is a perspective view of a detonator in accordance with an embodiment;

[0045] FIG. 28 is a detailed perspective view of the detonator shown in FIG. 27;

25 [0046] FIG. 29 is another detailed perspective view of the detonator shown in FIG. 27;

[0047] FIG. 30 is another detailed perspective view of the detonator shown in FIG. 27;

[0048] FIG. 31 is another detailed perspective view of the detonator shown in FIG. 27, with a crimp sleeve;

[0049] FIG. 32 is a detailed side view of a tandem seal adapter and detonator in accordance with another embodiment;

5 [0050] FIG. 33 is a side cut view of a portion of a perforation gun system illustrating the configuration of the top sub in accordance with another embodiment;

[0051] FIG. 34 is a side cut view of a portion of a perforation gun system illustrating the configuration of the bottom sub in accordance with another embodiment; and

[0052] FIGS. 35A and 35B are electrical schematic views of a detonator and of wiring
10 within a perforated gun system in accordance with another embodiment.

DETAILED DESCRIPTION

[0053] In the following description and accompanying FIGS., the same numerical references refer to similar elements throughout the FIGS. and text. Furthermore, for the sake of simplicity and clarity, namely so as not to unduly burden the FIGS. with several reference
15 numbers, only certain FIGS. have been provided with reference numbers, and components and features of the embodiments illustrated in other FIGS. can be easily inferred therefrom. The embodiments, geometrical configurations, and/or dimensions shown in the FIGS. are for exemplification purposes only. Various features, aspects and advantages of the embodiments will become more apparent from the following detailed description.

20 [0054] Moreover, although some of the embodiments were primarily designed for well bore perforating, for example, they may also be used in other perforating scenarios or in other fields, as apparent to a person skilled in the art. For this reason, expressions such as “gun system”, etc., as used herein should not be taken as to be limiting, and includes all other kinds of materials, objects and/or purposes with which the various embodiments could be used and may
25 be useful. Each example or embodiment are provided by way of explanation, and is not meant as a limitation and does not constitute a definition of all possible embodiments.

[0055] In addition, although some of the embodiments are illustrated in the accompanying drawings comprise various components and although the embodiment of the adjustment system as shown consists of certain geometrical configurations as explained and illustrated herein, not

all of these components and geometries are essential and thus should not be taken in their restrictive sense, i.e. should not be taken as to limit the scope. It is to be understood, as also apparent to a person skilled in the art, that other suitable components and cooperations thereinbetween, as well as other suitable geometrical configurations may be used for the adjustment systems, and corresponding parts, according to various embodiments, as briefly explained and as can easily be inferred herefrom by a person skilled in the art, without departing from the scope.

[0056] Referring to FIGS. 1 to 3, an object is to provide a perforation gun system 10 having an outer gun carrier 12. The gun system 10 includes a top connector 14. At least one stackable charge holder 16 is provided for centralizing a single shaped charge 18 within the gun carrier 12. A detonation cord 20 is connected to the top connector 14 and to each stackable charge holder 16.

[0057] The gun system 10 includes at least one bottom connector 22 for terminating the detonation cord 20 in the gun system. As better shown in FIG. 2, it is also possible that the bottom connector 22 double as or serve the function of a spacer 24 for spacing a plurality of stackable charge holders 16.

[0058] In an embodiment, the gun system also includes a detonator 26 energetically coupled to the detonation cord 20.

[0059] As better shown in FIGS. 4 to 18, each of the top connector 14, stackable charge holder 16 and bottom connector 22 includes a rotation coupling 30 for providing a selectable clocking rotation between each of the above-mentioned components. As seen, for instance, in Fig. 8, the rotation coupling 30 includes a first rotation coupling 30a and a second rotation coupling 30b.

[0060] Hence, a user can build multiple configurations of gun systems using various combinations of basic components. A first of these basic components includes a top connector. Another basic component is a single charge holder that centralizes a single shaped charge. The holder is adapted to be stacked and configured into 0, 30, 60, up to 360 degrees or any other combination of these phases for any specified length. Another basic component is a bottom connector that terminates the detonation cord in the gun. The bottom connector may carry as well an electrical connection therethrough. The bottom connector may also double as an imperial measurement stackable spacer to provide any gun shot density up to, for example, 6 shots per

foot. Alternately, another bottom connector may be provided or configured to double as a metric measurement stackable spacer to provide any gun shot density up to, for example, 20 shots per meter. Another basic component includes a push-in detonator that does not use wires to make necessary connections. The push-in detonator may use spring-loaded connectors, thus replacing any required wires and crimping.

[0061] Therefore, within the self-centralizing charge holder system, any number of spacers can be used with any number of holders for any specific metric or imperial shot density, phase and length gun system.

[0062] In an embodiment, only two pipe wrenches are required for assembly on site of the gun system, as no other tools are required.

[0063] In an embodiment, the top connector 14 provides energetic coupling between the detonator and detonating cord.

[0064] In an embodiment, each of the top connector 14, stackable charge holder 16 and bottom connector 22 are configured to receive electrical connections therethrough.

[0065] In an embodiment, all connections are made by connectors, such as spring-loaded connectors, instead of wires, with the exception of the through wire that goes from the top connector 14 to the bottom connector 22, whose ends are connectors.

[0066] In an embodiment, components of the assembly may include molded parts, which may also be manufactured to house the wiring integrally, through, for instance, overmolding, to encase the wiring and all connectors within an injection molded part. For example, the charge holder 16 could be overmolded to include the through wire.

[0067] In an embodiment, and as shown in FIGS. 4 and 5, each bottom connector 22 includes a plurality of fins 32 for axially locking each bottom connector against a snap ring 54, or an equivalent retainment mechanism to keep the charge holder 16 from sliding out of the bottom of carrier 12 as it is handled, (shown on FIG. 1). According to an aspect, and as illustrated in FIG. 19, the bottom connector 22 may be recessed into the tandem seal adapter 48. The bottom connector 22 from a first gun assembly can accommodate or house an electrical connection through a bulkhead assembly 58 to the top connector 14 of a second or subsequent gun assembly, as seen for instance in FIG. 19. The top and bottom connector, as well as the

spacer, in an embodiment, are made of 15% glass fiber reinforced, injection molding PA6 grade material, commercially available from BASF under its ULTRAMID® brand, and can provide a positive snap connection for any configuration or reconfiguration. As better shown in FIG. 5, a terminating means structure 34 is provided to facilitate terminating of the detonation cord. The snap ring 54 is preinstalled on the bottom of the carrier 12. The assembly can thus shoulder up to the snap ring 54 via the bottom connector fins 32.

[0068] In an embodiment and as shown in FIGS. 6 to 10, each stackable charge holder 16 has a plurality of projections 40 resting against an inner surface 13 or diameter of the gun carrier 12 (as shown in FIG. 1) and thereby centralizing the shaped charge therewithin. A pair of the plurality of projections 42 may also be configured for capturing the detonation cord (not shown) traversing each stackable charge holder 16. The pair of the plurality of projections 42 are also used for centralizing the shaped charge within an inner surface of the gun carrier.

[0069] In an embodiment, as shown in FIGS. 11 to 18, the top connector 14 includes at least one directional locking fin 46. Although the use of directional locking fins is described, other methods of directional locking may be used, in order to eliminate a top snap ring that would otherwise be used to lock the assembly. As better shown in FIG. 19, the locking fins 46 are engageable with corresponding complementarily-shaped structures 47 housed within the carrier 12, upon a rotation of the top connector 14, to lock the position of the top connector along the length of the carrier 12.

[0070] In an embodiment, as better shown in FIG. 19, the bottom connector 22 on one end and the top connector 14 on the other end abuts/connects to the bulkhead assembly 58. The tandem seal adapter 48 is configured to seal the inner components within the carrier 12 from the outside environment, using sealing means 60 (shown herein as o-rings). Thus, the tandem seal adapter 48 seals the gun assemblies from each other along with the bulkhead 58, and transmits a ground wire to the carrier 12. Hence, the top connector 14 and bulkhead 58 accommodate electrical and ballistic transfer to the charges of the next gun assembly for as many gun assembly units as required, each gun assembly unit having all the components of a gun assembly.

[0071] In an embodiment, the tandem seal adapter 48 is a two-part tandem seal adapter (not shown) that fully contains the bulkhead assembly 58 (comprised of multiple small parts as shown, for instance, in FIG. 19) and that is reversible such that it has no direction of installation.

[0072] In an embodiment and as better shown in FIGS. 27-31 and 35A, the detonator assembly 26 includes a detonator head 100, a detonator body 102 and a plurality of detonator wires 104, including a through wire 106, a signal-in wire 108 and a ground wire 110. The through wire 106 traverses from the top to the bottom of the perforating gun system 10, making a connection at each charge holder 16. The detonator head 100 further includes a through wire connector element 112 connected to the through wire 106 (not shown), a ground contact element 114 for connecting the ground wire 110 to the tandem seal adapter (also not shown), through ground springs 116, and a bulkhead connector element 118 for connecting the signal-in wire 108 to the bulkhead assembly 58 (also not shown). Different insulating elements 120A, 120B are also provided in the detonator head 100 for the purpose of insulating the detonator head 100 and detonator wires 104 from surrounding components. As better shown in FIG. 31, a crimp sleeve 122 can be provided to cover the detonator head 100 and body 102, thus resulting in a more robust assembly. The above configuration allows the detonator to be installed with minimal tooling and wire connections.

[0073] In an embodiment as shown in FIGS. 32, 33 and 35B illustrate a connection of the above-described detonator assembly 26 to the tandem seal adapter 48 and a pressure bulkhead 124. The bulkhead 124 includes spring connector end interfaces comprising contact pins 126A, 126B, linked to coil springs 128A, 128B. This dual spring pin connector assembly including the bulkhead 124 and coil springs 128A, 128B is positioned within the tandem seal adapter 48 extending from a conductor slug 130 to the bulkhead connector element. The dual spring pin connector assembly is connected to the through wire 106 of the detonator assembly 26.

[0074] In an embodiment and as better shown in FIGS. 11 to 18, the top connector 14 may have a split design to simplify manufacturing and aid in assembly. By “split design” what is meant is that the top connector 14 can be formed of two halves - a top half 15A and a bottom half 15B. As better shown in FIGS. 15 or 18, the top connector 14 may also include a blind hole 47 to contain or house the detonation cord, thus eliminating the need for crimping the detonation cord during assembly.

[0075] In an embodiment and as shown for example in FIGS. 4 to 18, the rotation coupling 30 may either include a plurality of pins 50 (FIG. 5) symmetrically arranged about a central axis of the rotation coupling 30, or a plurality of sockets 52 (FIG. 4) symmetrically

arranged about the central axis of the rotation coupling 30 and configured to engage the plurality of pins 50 of an adjacent rotation coupling 30.

[0076] In another embodiment, the rotation coupling 30 may either include a polygon-shaped protrusion, or a polygon-shaped recess configured to engage the polygon-shaped protrusion of an adjacent rotation coupling. The polygon can be 12-sided for example for 30 degree increments.

[0077] In another embodiment, the top and bottom subs work with off the shelf running/setting tools as would be understood by one of ordinary skill in the art.

[0078] In one embodiment and as shown in FIG. 33, the top sub 72 facilitates use of an off the shelf quick change assembly 140 to enable electrical signals from the surface, as well as to adapt perforating gun system to mechanically run with conventional downhole equipment. The quick change assembly 140 may include a threaded adapter 143 to set an offset distance between an electrical connector 142 and the contact pin 126B extending from the bulkhead assembly 58.

[0079] In one embodiment and as shown in FIG. 34, the bottom sub 70 may be configured as a sealing plug shoot adapter (SPSA) to be used specifically with this embodiment. The SPSA may receive an off the shelf quick change assembly 140 (not shown) and insulator 150 that communicates with a firing head threaded below it (not shown). A setting tool (not shown) may run on the bottom side of the perforating gun.

[0080] In an embodiment, final assembly of the tool string requires only two pipe wrenches. No tools are required to install the detonator or any electrical connections.

[0081] An object is to also provide a perforation gun system kit having the basic component parts described above and capable of being assembled within an outer gun carrier.

[0082] In an embodiment, a method for assembling a perforation gun system is provided, to which a certain number of optional steps may be provided. The steps for assembling the gun system for transport include the steps of:

providing a perforation gun system kit having component parts capable of being assembled within an outer gun carrier (element 12 in FIGS. 1, 21 and 22), the kit comprising a combination of:

- a top connector;

- at least one stackable charge holder for centralizing a single shaped charge within the gun carrier;
- a detonation cord connectable to the top connector and to each stackable charge holder;
- at least one bottom connector adapted for terminating the detonation cord in the gun system and adapted for doubling as a spacer for spacing a plurality of stackable charge holders; and
- a detonator energetically couplable to the detonation cord,

wherein each of the top connector, at least one stackable charge holder and at least one bottom connector comprise a coupling having a plurality of rotational degrees of freedom for providing a selectable rotation between each of the top connector, at least one stackable charge holder and at least one bottom connector;

assembling a plurality of the stackable charge holders in a predetermined phase to form a first gun assembly;

running the detonation cord into a bottommost bottom connector;

assembling the bottommost bottom connector onto the assembled plurality of stackable charge holders;

running a through wire between the bottommost bottom connector and the top connector, so that the through wire goes from the top connector to the bottom connector;

clicking the detonation cord into recessed formed in capturing projections, the capturing projections being provided in each of the charge holders;

running the detonation cord into the top connector;

cutting the detonator cord, if the detonator cord is not precut a predetermined length; and

installing charges into each of the charge holders.

[0083] In an embodiment, the method further includes, prior to transport, the steps of: pushing assembled components together to engage all pin connections therebetween; and carrying out a continuity test to ensure complete connectivity of the detonating chord.

[0084] In an embodiment, on location, to complete the assembly, the method further comprises the steps of:

threading on the previously assembled components a bottom sub (element 70 on FIGS. 1 and 20);

installing and connecting the detonator;

pushing in a tandem seal adapter with o-rings onto the first gun assembly;

5 pushing in a bulkhead (element 58 in FIG. 19) onto the tandem seal adapter, if the bulkhead and the tandem seal adapter are not pre-assembled;

threading a subsequent gun assembly onto the first gun assembly or threading a top sub (element 72 in FIGS. 1, 23 and 24) onto a topmost assembled gun assembly, for connection to a quick change assembly.

10 [0085] Of course, the scope of the perforation gun system, various perforation gun components, the perforation gun system kit, and the method for assembling a perforation gun system should not be limited by the various embodiments set forth herein, but should be given the broadest interpretation consistent with the description as a whole. The components and methods described and illustrated are not limited to the specific embodiments described herein, but rather,
15 features illustrated or described as part of one embodiment can be used on or in conjunction with other embodiments to yield yet a further embodiment. Further, steps described in the method may be utilized independently and separately from other steps described herein. Numerous modifications and variations could be made to the above-described embodiments without departing from the scope of the FIGS. and claims, as apparent to a person skilled in the art.

20 [0086] In this specification and the claims that follow, reference will be made to a number of terms that have the following meanings. The singular forms "a", "an" and "the" include plural referents unless the context clearly dictates otherwise. Further, reference to "top," "bottom", "front", "rear", and the like are made merely to differentiate parts and are not necessarily determinative of direction. Similarly, terms such as "first", "second", etc. are used to identify one
25 element from another, and unless otherwise specified are not meant to refer to a particular order or number of elements.

[0087] As used herein, the terms "may" and "may be" indicate a possibility of an occurrence within a set of circumstances; a possession of a specified property, characteristic or function; and/or qualify another verb by expressing one or more of an ability, capability, or

possibility associated with the qualified verb. Accordingly, usage of "may" and "may be" indicates that a modified term is apparently appropriate, capable, or suitable for an indicated capacity, function, or usage, while taking into account that in some circumstances the modified term may sometimes not be appropriate, capable, or suitable. For example, in some circumstances an event or capacity can be expected, while in other circumstances the event or capacity cannot occur--this distinction is captured by the terms "may" and "may be".

[0088] As used in the claims, the word "comprises" and its grammatical variants logically also subtend and include phrases of varying and differing extent such as for example, but not limited thereto, "consisting essentially of" and "consisting of".

C L A I M S

1. A perforation gun system (10) comprising:

at least one top connector (14) comprising a coupler for providing energetic coupling
5 between a detonator (26) and a detonation cord (20), and at least one directional locking fin (46)
for locking the top connector (14) within a gun carrier (12); and

at least one bottom connector (22) for terminating the detonation cord (20) in the perfora-
tion gun system (10), wherein the at least one bottom connector (22) optionally doubles as a
spacer for spacing a plurality of stackable charge holders (16),

10 characterized in that at least one of: the top connector (14) and/or the bottom connector
(22) comprises a rotation coupling (30) for providing a selectable clocking rotation, and
that the top and bottom connectors (14, 22) receive electrical connections therethrough.

2. The perforation gun system (10) of Claim 1, wherein the at least one rotation
15 coupling (30) provides the selectable clocking rotation between the top connector (14), the bottom
connector (22) and a charge holder (16).

3. The perforation gun system (10) of any one of Claims 1 to 2, wherein at least one
of: the top connector (14) and/or the bottom connector (22) is injection molded.

20 4. The perforation gun system (10) of Claim 1, wherein the at least one rotation
coupling (30) comprises:

a first rotation coupling; and

a second rotation coupling, wherein

25 the first rotation coupling and the second rotation coupling are positioned on
opposite ends of the bottom connector, and

each of the first rotation coupling and the second rotation coupling comprises at
least a plurality of pins (50) and/or a plurality of sockets (52) arranged about a central axis of the
bottom connector (22).

30 5. The perforation gun system (10) of Claim 1, wherein the at least one rotation

coupling (30) comprises:

a first rotation coupling; and

a second rotation coupling, wherein

the first rotation coupling and the second rotation coupling are positioned on

5 opposite ends of the top connector (14), and

each of the first rotation coupling and the second rotation coupling comprises at least a plurality of pins (50) and/or a plurality of sockets (52) arranged about a central axis of the top connector (14).

10 6. The perforation gun system (10) of any of Claims 1 to 5, wherein the bottom connector (22) comprises:

a terminating structure for terminating the detonation cord (20); and

a plurality of fins (32) for axially locking the bottom connector (22) in the perforation gun system (10).

15

P A T E N T K R A V

1. Perforeringskanonsystem (10) omfattende:

minst én toppkonnektor (14) omfattende en kopler for tilveiebringelse av energisk kobling mellom en detonator (26) og en detoneringslunte (20), og minst én retningsbestemt låsefinne (46) for å låse toppkonnektoren (14) innenfor en kanon-bærer (12); og

minst én bunnkonnektor (22) for terminering av detoneringslunten (20) i perforeringskanonsystemet (10), hvor den minst ene bunnkonnektoren (22) eventuelt fungerer som et avstandsstykke for å adskille et flertall av ladningsholdere (16) som er egnet til å stables,

karakterisert ved at minst én av: toppkonnektoren (14) og/eller bunnkonnektoren (22) omfatter en rotasjonskopling (30) for tilveiebringelse av en valgbar klokkeotasjon, og

at topp- og bunnkonnektorene (14, 22) mottar elektriske forbindelser derigjennom.

2. Perforeringskanonsystem (10) ifølge krav 1, hvor den minst ene rotasjonskopling (30) tilveiebringer den valgbare klokkeotasjonen mellom toppkonnektoren (14), bunnkonnektoren (22) og en ladningsholder (16).

3. Perforeringskanonsystem (10) ifølge et hvilket som helst av krav 1 til 2, hvor minst én av: toppkonnektoren (14) og/eller bunnkonnektoren (22) er sprøytetstøpt.

4. Perforeringskanonsystem (10) ifølge krav 1, hvor den minst ene rotasjonskoblingen (30) omfatter:

en første rotasjonskobling; og

en andre rotasjonskobling, hvor

den første rotasjonskoblingen og den andre rotasjonskoblingen er posisjonert på motsatte ender av bunnkonnektoren, og

hver av den første rotasjonskoblingen og den andre rotasjonskoblingen omfatter i det minste et flertall av pinner (50) og/eller et flertall av kontakter (52) anordnet rundt en sentral akse til bunnkonnektoren (22).

5. Perforeringskanonsystem (10) ifølge krav 1, hvor den minst ene rotasjonskoblingen (30) omfatter:

en første rotasjonskobling; og

en andre rotasjonskobling, hvor

den første rotasjonskoblingen og den andre rotasjonskoblingen er posisjonert på motsatte ender av toppkonnektoren (14), og

hver av den første rotasjonskoblingen og den andre rotasjonskoblingen omfatter i det minste et flertall av pinner (50) og/eller et flertall av kontakter (52) anordnet rundt en sentral akse til toppkonnektoren (14).

6. Perforeringskanonsystem (10) ifølge et hvilket som helst av krav 1 til 5, hvor bunnkonnektoren (22) omfatter:

en termineringsstruktur for terminering av detonasjonslunten (20); og

et flertall av finner (32) for aksial låsing av bunnkonnektoren (22) i perforeringskanonsystemet (10).








FIG. 1



2/18

**FIG. 2****FIG. 3**




3/18

FIG. 4**FIG. 5**



4/18

**FIG. 6****FIG. 7**



5/18

FIG. 8**FIG. 9****FIG. 10**



6/18

**FIG. 11****FIG. 12**



7/18

**FIG. 13****FIG. 14**



8/18

**FIG. 15****FIG. 16**

9/18

**FIG. 17****FIG. 18**

10/18

**FIG. 19****FIG. 20**




FIG. 21








FIG. 22



12/18

**FIG. 23****FIG. 24**



13/18

**FIG. 25****FIG. 26**



14/18

**FIG. 27****FIG. 28**



15/18

FIG. 29**FIG. 30**

16/18

**FIG. 31****FIG. 32**

17/18

**FIG. 33****FIG. 34**




FIG. 35A




FIG. 35B