



US009204179B2

(12) **United States Patent**  
**Bahnck et al.**

(10) **Patent No.:** **US 9,204,179 B2**  
(45) **Date of Patent:** **Dec. 1, 2015**

(54) **LOCATION-BASED SERVICE GROUP DISCOVERY FOR SWITCHED DIGITAL VIDEO**

(75) Inventors: **Thomas J. Bahnck**, Lafayette Hill, PA (US); **David M. Bjordammen**, Blue Bell, PA (US)

(73) Assignee: **ARRIS Technology, Inc.**, Suwanee, GA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1072 days.

(21) Appl. No.: **12/822,766**

(22) Filed: **Jun. 24, 2010**

(65) **Prior Publication Data**

US 2011/0321113 A1 Dec. 29, 2011

(51) **Int. Cl.**

**H04N 21/226** (2011.01)  
**H04N 21/2668** (2011.01)  
**H04N 21/426** (2011.01)  
**H04N 21/475** (2011.01)  
**H04N 21/258** (2011.01)  
**H04N 21/45** (2011.01)

(52) **U.S. Cl.**

CPC ..... **H04N 21/25808** (2013.01); **H04N 21/2668** (2013.01); **H04N 21/4516** (2013.01)

(58) **Field of Classification Search**

None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2002/0007491 A1\* 1/2002 Schiller et al. .... 725/87  
2006/0190964 A1\* 8/2006 Eldering ..... H04N 7/165  
725/42  
2009/0144797 A1 6/2009 Wang et al.  
2009/0150926 A1 6/2009 Schlack  
2009/0158380 A1\* 6/2009 Derham ..... H04N 21/2385  
725/131

\* cited by examiner

*Primary Examiner* — Brian T Pendleton

*Assistant Examiner* — Jean D Saint Cyr

(74) *Attorney, Agent, or Firm* — Stewart M. Wiener

(57) **ABSTRACT**

A broadcast system and method that includes a video content network that connects a video server, a discovery server, a switched digital video service, a switched video manager, and a set-top box. The set-top box receives and stores an assigned location identifier, and receives a mapping from the discovery server, where the mapping includes records, each record associating a location identifier and a service group. The set-top box matches the assigned location identifier to the mapping to determine an assigned service group for the set-top box. The set-top box receives an address from the discovery server that identifies the switched video manager that is associated with the assigned service group. The set-top box operates in the broadcast system by communicating with the switched digital video service, and the switched video manager.

**20 Claims, 2 Drawing Sheets**




FIG. 1




FIG. 2





FIG. 3



1

## LOCATION-BASED SERVICE GROUP DISCOVERY FOR SWITCHED DIGITAL VIDEO

### BACKGROUND

A digital video broadcast system allows a multiple system operator (MSO) to deliver television programs and multimedia services to subscribers. The capacity, or bandwidth, of the system determines the programs and services that the MSO delivers. In legacy broadcast systems, the MSO sends all of the available programs and services to the subscriber's set-top box on a single cable. Thus, the only way to increase the programs and services available to subscribers in legacy broadcast systems is to increase the bandwidth.

Switched digital video is an improvement to the legacy broadcast systems that requires less bandwidth to deliver high-bandwidth digital services by allowing the MSO to send only the content requested by a service group, where each service group includes a set of set-top boxes with visibility to a common set of switched edge quadrature amplitude modulator (QAM) devices. To make this possible, the subscriber's set-top box communicates with a network side video server to request the program that the subscriber wants to watch in real time. The switched digital system responds by delivering the requested program to the subscriber's service group. Thus, the service group only receives the programs that subscribers in the service group are watching. In addition, the switched digital system collects data on the usage of the set-top boxes and reports this data to the MSO.

The assignment of service groups in existing switched digital video standards and protocols uses switched edge QAM devices to determine the service group. These standards do not define a message or method to autonomously segment the set-top box population into service groups, or send the group number to a set-top box client. Thus, in a legacy broadcast system, the issue that arises is the assignment of a service group to each set-top box when there are no switched edge QAM devices to distinguish the service groups, thereby allowing the set-top boxes to benefit from the advantages provided by a switched digital system.

There is a demand for a method and system to assign a service group to a set-top box where no switched edge QAM devices are visible to the in-band tuner. The presently disclosed invention satisfies this demand.

### SUMMARY

Aspects of the present invention provide a broadcast system and method that includes a video content network that connects a video server, a discovery server, a switched digital video service, a switched video manager, and a set-top box. The set-top box receives and stores an assigned location identifier. The set-top box receives a mapping from the discovery server, where the mapping includes records, each record associating a location identifier and a service group. The set-top box matches the assigned location identifier to the mapping to determine an assigned service group for the set-top box. The set-top box receives an address from the discovery server that identifies the switched video manager that is associated with the assigned service group. The set-top box operates in the broadcast system by communicating with the switched digital video service, and the switched video manager.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a network diagram that illustrates one embodiment of the hardware components of a system that performs the present invention.

2

FIG. 2 is a block diagram that illustrates, in detail, one embodiment of the hardware components shown in FIG. 1.

FIG. 3 is a message flow diagram that illustrates methods according to various embodiments of the present invention.

### DETAILED DESCRIPTION

FIG. 1 is a network diagram that illustrates one embodiment of the hardware components of a system that performs the present invention. A broadcast system 100 includes a network 110 and a hybrid fiber-coaxial (HFC) network 150. The HFC network 150 is a data and video content network that connects a gateway, such as a cable television head end 120, to a switched digital video (SDV) cluster 130, discovery server 140, and subscriber location 170. The broadband network 100 shown in FIG. 1 may include any number of interconnected networks 110, head ends 120, SDV clusters 130, discovery servers 140, HFC networks 150, and subscriber locations 170.

The head end 120, in one embodiment, is a cable television master head end facility for receiving television signals for processing and distribution over a cable television system. The head end 120 provides the subscriber location 170 with a variety of services and/or connections, such as the connection to the network 110. For example, the head end 120 may provide a connection to external services such as video servers, public switched telephone network voice, multimedia messages, and internet data. The head end 120 includes a user interface, such as a digital addressable controller (DAC) 125, to allow an operator to configure the head end 120 components, and define channel map assignments and Federal Information Processing Standard (FIPS) codes.

The switched video operations manager (SVOM) 132, edge resource manager (ERM) 134, and switched video manager (SVM) 136 are the components comprising the SDV cluster 130 for the broadcast system 100. The SVOM 132 is a computing device, including a processor and memory, which configures, monitors, and collects data from the ERM 134 and SVM 136 components. A cable operator uses the SVOM 132 to configure channels for SDV services, manage service group mappings, and administer the ERM 134, SVM 136, and edge QAM device (not shown) relationships. The SVOM 132 also collects usage and statistics information from set-top boxes 180. This allows cable operators to centrally measure important information and generate reports on critical operational topics, including channel usage, set-top box 180 usage, channel change rates, and service group bandwidth utilization. The ERM 134 is a computing device, including a processor and memory, which manages the edge QAM device relationships in the head end 120 as established by the cable operator's policies. The ERM 134 receives requests for edge QAM devices, and selects the appropriate edge QAM device to satisfy the bandwidth requirements of the request. The SVM 136 is a computing device, including a processor and memory, which manages the SDV streams that are active at any given time, and directs each stream to the appropriate set-top box 180 that requested the stream. The SVM 136 also tracks the channels viewed by each set-top box 180, and communicates with the ERM 134 to establish the requested channels.

The discovery server 140 is a searchable registry of components and services accessible in the broadcast system 100. In one embodiment, the discovery server 140 is a Domain Name System (DNS) server that the set-top box 180 can query for a well known or advertised (e.g., carousel) SDV service identifier. In another embodiment, the discovery server 140 is a ubiquitous DNS server such as BIND.

The subscriber location **170** includes a computing device, such as a set-top box **180**, to receive, decode and display data and video content, and provide access to the services and/or connections that the head end **120** provides. A service group **160** is an organization that includes a number of subscriber locations **170**, each subscriber location **170** including one or more set-top boxes **180**. A unique identifier associated with each service group **160**, subscriber location **170**, and/or set-top box **180** supports the functionality and advantages provided by the head end **120**, SDV cluster **130**, and discovery server **140**.

In one embodiment shown in FIG. 1, the broadcast system **100** is a switched digital video (SDV) broadcast system. In the switched broadcast system **100**, the SDV cluster **130** manages a set of edge QAM devices (not shown) that the broadcast system **100** bind and unbind to particular services based on requests from the set-top boxes **180** at the subscriber locations **170**. The SDV cluster **130** monitors the requests that the set-top boxes **180** send to measure viewership. When a viewer decides to change the channel, the set-top box **180** sends a channel change message that the SVM **136** monitors. The SVM **136** parses the channel change message to obtain an identifier of the service group **160**, subscriber location **170**, and/or set-top box **180** that identifies the set of switched edge QAM devices visible to the set-top box **180**. Typically, a set-top box **180** assigns the identifier via an in-band carousel, or a message exchange with the SVM **136** known as auto-discovery. In a typical switched broadcast system **100**, the SDV cluster **130** uses the identifier to bind the requested channel to an edge QAM device visible to the service group.

In another embodiment shown in FIG. 1, the broadcast system **100** is a legacy, non-switched, broadcast system. In the non-switched broadcast system **100**, since there is an excess of bandwidth, switched edge QAM devices (not shown) are not yet necessary. However, the SDV cluster **130** can still provide value to the subscribers in the non-switched broadcast system **100** because it can provide channel change statistics and reporting. In addition, when the non-switched broadcast system **100** combines the channel change data with an electronic program guide (EPG), the cable operator obtains a very accurate description of the viewership for every channel on the cable plant. In the non-switched broadcast system **100**, the SDV cluster **130** does not manage the edge QAM devices, but it still assigns and supports an identifier of the service group **160**, subscriber location **170**, and/or set-top box **180**. This allows the SDV cluster **130** to still use standard protocols (e.g., ISA and NGOD), while also maintaining a similar code base for both switched and non-switched deployments. In the non-switched broadcast system **100**, the identifier of the service group **160**, subscriber location **170**, and/or set-top box **180** has value to the cable operators, and third parties such as advertisers, because the SDV cluster **130** can generate reports based on the identifier. These reports are particularly valuable if the cable operators and third parties use the identifier to represent a designated market area (DMA), or other geographic area. The geographic boundaries of a service group in a switched broadcast system **100** depend on the reach of associated switched edge QAM devices, but the boundaries of interest to the cable operators and third parties will likely correspond to a narrower geographic region.

The network **110** shown in FIG. 1, in one embodiment, is a public communication network or wide area network (WAN) that connects to the head end **120**. The present invention also contemplates the use of comparable network architectures. Comparable network architectures include the Public Switched Telephone Network (PSTN), a public packet-

switched network carrying data and voice packets, a wireless network, and a private network. A wireless network includes a cellular network (e.g., a Time Division Multiple Access (TDMA), Code Division Multiple Access (CDMA), or Orthogonal Frequency Division Multiplexing (OFDM) network), a satellite network, and a wireless Local Area Network (LAN) (e.g., a wireless fidelity (Wi-Fi) network). A private network includes a LAN, a Personal Area Network (PAN) such as a Bluetooth network, a wireless LAN, a Virtual Private Network (VPN), an intranet, or an extranet. An intranet is a private communication network that provides an organization such as a corporation, with a secure means for trusted members of the organization to access the resources of the organization's network. In contrast, an extranet is a private communication network that provides an organization, such as a corporation, with a secure means for the organization to authorize non-members of the organization to access certain resources on the organization's network. The system also contemplates network architectures and protocols such as Ethernet, Token Ring, Systems Network Architecture, Internet Protocol, Transmission Control Protocol, User Datagram Protocol, Asynchronous Transfer Mode, and proprietary network protocols comparable to the Internet Protocol.

The HFC network **150** is a broadband network that combines optical fiber and coaxial cable, technology commonly employed globally by cable television operators since the early 1990s. The fiber optic network extends from the cable operators master head end, sometimes to regional head ends, and out to a neighborhood hubsite, and finally to a fiber optic node that serves anywhere from 25 to 2000 homes. The master head end will usually have satellite dishes for reception of distant video signals as well as IP aggregation routers. Some master head ends also house telephony equipment for providing telecommunications services to the community. The regional head ends receive the video signal from the master head end and add to it the Public, Educational and/or Governmental (PEG) channels as required by local franchising authorities or insert targeted advertising that would appeal to the region. The various services are encoded, modulated and up-converted onto RF carriers, combined onto a single electrical signal and inserted into a broadband optical transmitter. This optical transmitter converts the electrical signal to a downstream optically modulated signal that is sent to the nodes. Fiber optic cables connect the head end to optical nodes in a point-to-point or star topology, or in some cases, in a protected ring topology.

FIG. 2 is a block diagram that illustrates, in detail, one embodiment of the hardware components shown in FIG. 1. In particular, FIG. 2 illustrates the hardware components and software comprising the set-top box **180** shown in FIG. 1.

The set-top box **180**, in one embodiment, is a general-purpose computing device that performs the present invention. A bus **205** is a communication medium that connects a processor **210**, data storage device **215** (such as a Serial ATA (SATA) hard disk drive, optical drive, Small Computer System Interface (SCSI) disk, flash memory, or the like), communication interface **220**, infrared (IR) interface **225**, video output processing **235**, and memory **250** (such as Random Access Memory (RAM), Dynamic RAM (DRAM), non-volatile computer memory, flash memory, or the like). The communication interface **220** connects the set-top box **180** to the HFC network **150**. The IR interface **225** connects the set-top box **180** to a remote controller **230**. The video output processing **235** connects the set-top box **180** to a display device such as a television **240**, and sends the video content that the television **240** screen displays. In one embodiment,

the implementation of the set-top box **180** is an application-specific integrated circuit (ASIC).

The processor **210** performs the disclosed methods by executing the sequences of operational instructions that comprise each computer program resident in, or operative on, the memory **250**. The reader should understand that the memory **250** may include operating system, administrative, and database programs that support the programs disclosed in this application. In one embodiment, the configuration of the memory **250** of the set-top box **180** includes an application program **251**, SDV client program **252**, and assigned location identifier **253**. The application program **251** provides the viewer with access to basic functions, such as the display of a video content stream on the television **240**, and advanced functions, such as video-on-demand (VOD), interactive television, and other next-generation television application programs. The SDV client program **252** is a program that interfaces with the SDV cluster **130** and discovery server **140**. The SDV client program **252** enables the SDV cluster **130** and discovery server **140** to centrally measure important information and generate reports on critical operational topics, including channel usage, set-top box **180** usage, channel change rates, and service group bandwidth utilization. The assigned location identifier **253** is an identifier that associates the set-top box **180** to a location, such as a service group **160** or subscriber location **170**. The application program **251**, SDV client program **252**, and assigned location identifier **253** perform the methods of the present invention disclosed in detail in FIG. **3**. When the processor **210** performs the disclosed methods, it stores intermediate results in the memory **250** or data storage device **215**. In another embodiment, the memory **250** may swap these programs, or portions thereof, in and out of the memory **230** as needed, and thus may include fewer than all of these programs at any one time.

FIG. **3** is a flow diagram that illustrates a method according to one embodiment of the present invention. In particular, FIG. **3** illustrates the communication between the SDV cluster **130**, discovery server **140**, and the set-top box **180**.

The process **300** shown in FIG. **3**, with reference to FIG. **1** and FIG. **2**, begins with an operator at a head end **120** assigning a location identifier to the set-top box **180** (step **305**). In one embodiment, the operator uses the digital addressable controller **125** in the head end **120** to send the location identifier to the set-top box **180**. The set-top box **180** receives and stores the location identifier (step **310**). In one embodiment, the set-top box **180** stores the location identifier in the assigned location identifier **253** segment of the memory **250**. In one embodiment, the location identifier is a FIPS code, zip code, or Designated Market Area (DMA) code that associates the service group **160** or subscriber location **170** to a set-top box **180**. When the location identifier is a FIPS code, the location identifier is, for example, "042091".

After assigning the location identifier, the process **300** requests a well known or advertised (e.g., carousel) SDV service identifier (step **315**). In one embodiment, the request is for a well known or advertised (e.g., carousel) SDV service identifier. In another embodiment, the request is sent to a Domain Name System (DNS) as the discovery server **140**. In one exemplary DNS embodiment, the request is a standard DNS query for an SDV service identifier, where the record type is TXT, and the domain name is "svm.testdomain.com". After receiving the query, the discovery server **140** prepares a mapping of location identifiers to service groups **160** or subscriber locations **170**. In one embodiment, the mapping provides the set-top box **180** with a list of service groups based on location identifiers for every set-top box **180** in the broadcast system. In the exemplary DNS

embodiment, the mapping is "042091=100", "042092=101", "042093=102", "042094=103", and "042095=104". In one embodiment, when the mapping includes more mappings than will fit in a single DNS message, the DNS server will set a bit in the DNS response message that indicates that more records are available. This will allow a virtually unlimited number of records in the response. The discovery server **140** sends the mapping in response to the query (step **320**). When the set-top box **180** receives the mapping, it matches the assigned location identifier **253** to the mapping (step **325**) to determine an identifier of the assigned service group **160** or subscriber location **170** for the set-top box **180**. In the exemplary DNS embodiment, the set-top box **180** obtains the associated assigned service group **160** as "100". The set-top box **180** uses the associated assigned service group **160** to send a second request to the discovery server **140** for an address of the SVM associated with the service group **160** (step **330**). In one embodiment, the address is internet protocol (IP) address. In the exemplary DNS embodiment, the second request is a standard DNS query for an IP address, where the record type is A, and the domain name is "sg100.svm.testdomain.com". The discovery server **140** receives the second request (step **335**), and sends the address for the SVM (step **340**). In the exemplary DNS embodiment, the reply is a DNS reply, where type is A, and the value is "10.0.0.1". The set-top box **180** receives the address for the SVM (step **345**), and uses the SVM address to operate the set-top box in an SDV environment (step **350**). In one embodiment, the operation of the set-top box **180** includes sending usage data to the switched digital video cluster **130**, where the usage data includes channel usage data, set-top box **180** usage data, channel change data, and bandwidth utilization data.

Before a set-top box **180** can successfully complete the discovery process, the process **300**, asynchronous to the service group **160** discovery, adds the correct mapping to the SDV cluster **130**, and the discovery server **140**. The SDV cluster **130** sends a request to add a mapping of location identifier to service group **160** or subscriber location **170** to the discovery server **140** (step **355**). The discovery server **140** receives the request and adds the mapping (step **360**). If the addition of the mapping is successful, the discovery server **140** sends a success response (step **365**) that the SDV cluster **130** receives (step **370**). In one embodiment, the SDV cluster **130** keeps the DNS discovery servers **140** up-to-date with service group **160** or subscriber location **170** mappings via Dynamic DNS (DDNS), which is supported today in ubiquitous DNS servers such as BIND. Furthermore, the use of DDNS alleviates the burden on operators to manually keep the DNS discovery server **140** in-sync with the configuration of the SDV cluster **130**. In one embodiment, the updates to the discovery server **140** are secure updates using the transaction signature.

Although the disclosed embodiments describe a fully functioning method and system for assigning a service group to a set-top box where no switched edge QAM devices are visible to the in-band tuner, the reader should understand that other equivalent embodiments exist. Since numerous modifications and variations will occur to those reviewing this disclosure, the method and system for assigning a service group to a set-top box where no switched edge QAM devices are visible to the in-band tuner is not limited to the exact construction and operation illustrated and disclosed. Accordingly, this disclosure intends all suitable modifications and equivalents to fall within the scope of the claims.

We claim:

1. A method, comprising:  
receiving an assigned location identifier for a set-top box;  
receiving a mapping from a discovery server, the mapping  
having at least one record, each record associating a  
location identifier and a service group;  
matching, by a computer, the assigned location identifier to  
the mapping to determine an assigned service group for  
the set-top box;  
receiving an address from the discovery server, the address  
identifying a switched video management server that is  
associated with the assigned service group; and  
operating the set-top box in a broadcast system by commu-  
nicating with the switched digital video service, and the  
switched video management server.
2. The method of claim 1, wherein the receiving of the  
assigned location identifier further comprises:  
receiving a configuration request message that includes the  
assigned location identifier; and  
storing the assigned location identifier in the set-top box,  
wherein the assigned location identifier associates the set-  
top box with an assigned service group.
3. The method of claim 1, wherein the receiving of the  
mapping further comprises:  
sending a first request to the discovery server, the first  
request including an identifier of a switched digital  
video service; and  
receiving a first response from the discovery server,  
wherein the first response is to the first request, and  
includes the mapping.
4. The method of claim 3, wherein the identifier of the  
switched digital video service is well known or advertised.
5. The method of claim 1, wherein the matching of the  
assigned location identifier further comprises:  
comparing the assigned location identifier to each location  
identifier in the mapping,  
wherein the assigned service group is the service group  
associated with the location identifier that matches the  
assigned location identifier.
6. The method of claim 1, wherein the receiving of the  
address further comprises:  
sending a second request to the discovery server, the sec-  
ond request including the assigned service group; and  
receiving a second response from the discovery server,  
wherein the second response is to the second request,  
and includes the address.
7. The method of claim 1, wherein the operating of the  
set-top box further comprises:  
sending at least one of channel usage data, set-top box  
usage data, channel change data, and bandwidth utiliza-  
tion data.
8. The method of claim 1, wherein the broadcast system  
includes the switched digital video service, the discovery  
server, and the switched video management server.
9. The method of claim 8, wherein the broadcast system is  
a switched digital video broadcast system.
10. The method of claim 8, wherein the broadcast system is  
a non-switched digital video broadcast system.
11. A broadcast system, comprising:  
a video content network that connects a video server, a  
discovery server, a switched digital video service, and a  
switched video management server;  
a computing device connected to the video content network  
and a video display device, the computing device com-  
prising:  
a memory device resident in the computing device; and

- a processor disposed in communication with the memory  
device, the processor configured to:  
receive an assigned location identifier for the computing  
device;  
receive a mapping from the discovery server, the mapping  
having at least one record, each record associating a  
location identifier and a service group;  
match the assigned location identifier to the mapping to  
determine an assigned service group for the computing  
device;  
receive an address from the discovery server, the address  
identifying the switched video management server that  
is associated with the assigned service group; and  
operate the computing device by communicating with the  
switched digital video service, and the switched video  
management server.
12. The broadcast system of claim 11, wherein to receive  
the assigned location identifier, the processor is further con-  
figured to:  
receive a configuration request message that includes the  
assigned location identifier; and  
store the assigned location identifier in the set-top box,  
wherein the assigned location identifier associates the  
computing device with an assigned service group.
  13. The broadcast system of claim 11, wherein to receive  
the mapping, the processor is further configured to:  
send a first request to the discovery server, the first request  
including an identifier of the switched digital video ser-  
vice; and  
receive a first response from the discovery server, wherein  
the first response is to the first request, and includes the  
mapping.
  14. The broadcast system of claim 13, wherein the identi-  
fier of the switched digital video service is well known or  
advertised.
  15. The broadcast system of claim 11, wherein to match the  
assigned location identifier, the processor is further config-  
ured to:  
compare the assigned location identifier to each location  
identifier in the mapping,  
wherein the assigned service group is the service group  
associated with the location identifier that matches the  
assigned location identifier.
  16. The broadcast system of claim 11, wherein to receive  
the address, the processor is further configured to:  
send a second request to the discovery server, the second  
request including the assigned service group; and  
receive a second response from the discovery server,  
wherein the second response is to the second request,  
and includes the address.
  17. The broadcast system of claim 11, wherein to operate  
the computing device, the processor is further configured to:  
send at least one of channel usage data, set-top box usage  
data, channel change data, and bandwidth utilization  
data.
  18. The broadcast system of claim 11, wherein the broad-  
cast system is a switched digital video broadcast system.
  19. The broadcast system of claim 11, wherein the broad-  
cast system is a non-switched digital video broadcast system.
  20. A non-transitory computer-readable medium, compris-  
ing computer-executable instructions that, when executed on  
a computing device, perform steps of:  
receiving an assigned location identifier for a set-top box;  
receiving a mapping from a discovery server, the mapping  
having at least one record, each record associating a  
location identifier and a service group;

matching the assigned location identifier to the mapping to  
determine an assigned service group for the set-top box;  
receiving an address from the discovery server, the address  
identifying a switched video management server that is  
associated with the assigned service group; and  
operating the set-top box in a broadcast system by commu-  
nicating with the switched digital video service, and the  
switched video management server.

5

\* \* \* \* \*