(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 8 November 2001 (08.11.2001)

PCT

(10) International Publication Number WO 01/83380 A1

(51) International Patent Classification⁷: C02F 1/50

(21) International Application Number: PCT/US01/10642

(22) International Filing Date: 29 March 2001 (29.03.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

09/564,244 4 May 2000 (04.05.2000) US

- (71) Applicant: ONDEO NALCO COMPANY [US/US]; One Ondeo Nalco Center, Naperville, IL 60563-1198 (US).
- (72) Inventors: ROBERTSON, Linda, R.; 35 W. 752 Highview Court, St. Charles, IL 60175 (US). KEHOE, Victoria, M.; 3141 Booth Bay Lane, Aurora, IL 60504 (US). RICE, Laura, E.; 400 South Green Street #512, Chicago, IL 60607 (US). SHETTY, Chandrashekar; 6824 Greene Road, Woodridge, IL 60517-1474 (US).

- (74) Agent: KEEFER, Timothy, J.; Wildman, Harrold, Allen & Dixon, 225 West Wacker Drive, Chicago, IL 60606 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

METHOD OF INHIBITING BIOFILM FORMATION IN COMMERCIAL AND INDUSTRIAL WATER SYSTEMS

FIELD OF THE INVENTION

This invention relates generally to the field of water treatment technologies and, more particularly, to a method of inhibiting biofilm formation in commercial and industrial water systems.

BACKGROUND OF THE INVENTION

Biofouling has always been problematic in commercial and industrial water systems, such as cooling tower waters and air washers, because it can adversely affect heat transfer efficiency and fluid frictional resistance, thereby subsequently reducing production rates.

Biofouling is also a problem in pulp and paper mill systems because the growth of microorganisms in papermachine fluids can adversely affect finished paper products, thereby requiring the papermachine to be shut down, resulting in the loss of productivity brought on by the down time of the machine. Furthermore, biofouling plays an important role in microbiologically influenced corrosion.

The presence of microorganisms in commercial and industrial waters cannot be totally eliminated, even with the excessive use of chemical biocides. The most common way to control biofouling is through the application of toxic chemical biocides such as chlorine, bromine, isothiazolones, glutaraldehyde or other antimicrobials. These biocides are added in an attempt to kill both planktonic and attached microorganisms.

Some microorganisms attach to inert surfaces forming aggregates with a complex matrix consisting of extracellular polymeric substances (EPS). This consortium of attached microorganisms and the associated EPS is

2

commonly referred to as a biofilm. Biocides have difficulty penetrating biofilms and removing them from surfaces. Although excessive biocide dosages may be able to control biofouling, such use is costly and the presence of biocides in effluent waters is usually environmentally unacceptable.

Accordingly, it would be desirable to provide a method of inhibiting biofilm formation in commercial and industrial water systems which utilizes a low-cost, non-biocidal substance.

SUMMARY OF THE INVENTION

The method of the invention calls for adding one or more plant oils to a commercial or industrial water system. The addition of plant oil efficiently and effectively inhibits biofilm formation in commercial and industrial water systems. Moreover, the inventive method is economically appealing and environmentally acceptable because plant oils are low in cost and non-biocidal.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is directed to a method of inhibiting biofilm formation in commercial and industrial water systems. In accordance with this invention, one or more plant oils are added to the commercial or industrial water system.

"Plant oils" (which are also known in the art as "natural oils" or "essential oils") are generally defined as volatile oils obtained from plants which possess the odor and other characteristics of the plant. The plant oils that may be used in the practice of this invention include eucalyptus, cinnamon, retsin, tea tree, clove, camphor, pine, spruce, neem, peppermint, spearmint, wintergreen, lime, orange, grapefruit, mandarin,

lemongrass and citronella oils, as well as mixtures thereof. Eucalyptus oil and cinnamon oil are the most preferred plant oils.

The plant oils can be added to the commercial or industrial water system by any conventional method at a concentration which effectively inhibits biofilm formation. It is preferred that the amount of plant oil which is added to the commercial or industrial water system be in the range of about 1 ppm to about 10,000 ppm. More preferably, the amount of plant oil is from about 1 ppm to about 5,000 ppm, with about 1 ppm to about 250 ppm being most preferred.

The commercial and industrial water systems to which the plant oils may be added to inhibit biofilm formation include cooling waters; food, beverage and industrial process waters; pulp and paper mill systems; brewery pasteurizers; sweetwater systems; air washer systems; oil field drilling fluids and muds; petroleum recovery processes; industrial lubricants; cutting fluids; heat transfer systems; gas scrubber systems; latex systems; clay and pigment systems; decorative fountains; water intake pipes; ballast water tanks; and ship reservoirs, among others.

EXAMPLE

The following example is intended to be illustrative of the present invention and to teach one of ordinary skill how to make and use the invention. The example is not intended to limit the invention or its protection in any way.

A jar test was conducted to demonstrate the ability of the plant oils to interfere with the attachment of filamentous bacteria to surfaces. The plant oils of the invention were applied to paper machine fluids to prevent the attachment of microorganisms to machine surfaces and

thereby prevent contamination of the machine by filamentous and other bacteria. Furthermore, by preventing the attachment of the biofilm, the plant oils also helped prevent contamination by wood fibers and fillers.

Sphaerotilus natans (a filamentous, slime-forming bacterium common to paper mills) was grown in a modified nutrient medium designed to promote biofilm formation. The uniform inoculum was harvested and aliquots were frozen and stored at 70°C until needed.

Eight-ounce flush glass jars were rinsed once in acetone and twice in deionized water to remove any surface contaminants. The jars were autoclaved at 121°C for 30 minutes. Predetermined volumes of the plant oils (cinnamon oil, eucalyptus oil and tea tree oil) were added directly to the jars.

50 mL of sterile medium were added to each jar and 100 µl of the thawed Sphaerotilus natans culture were added to each jar. The jars were placed into a New Brunswick Series 25 orbital shaker at 35°C at 210 rpm. After 48 hours of incubation, the biofilms which attached and formed at the base of the jars were measured for diameter in centimeters and rated for vigor on a scale of 0 to +4. As used herein, "vigor" is defined as the visual characterization of the thickness and tenacity of the biofilm. A modified geometric mean was calculated for each jar by taking the square root of the diameter (in centimeters) multiplied by the vigor. Each experiment was set up with a minimum of three jars per concentration and treatment chemical. The average of all modified geometric means calculated for a specific plant oil and dosage was then averaged and listed in Table 1.

5

The results of the treatments are shown below in Table 1. The data illustrates that with cinnamon oil, the modified geometric mean of diameter and vigor at a 25 ppm dose is 1.6, which is significantly better than the ethylene oxide/propylene oxide (EO/PO) copolymer (Nalco product N-7611) in preventing microbial attachment to surfaces since a lower response number indicates a more active compound. EO/PO copolymers are currently used in industry to inhibit biofilm formation.

Table 1 also shows eucalyptus oil and tea tree oil at 100 ppm to perform better than the EO/PO copolymer at inhibiting biofilm formation.

6 Table 1

Treatment	Average Modified Geometric Mean	Average Diameter (cm)				
Eucalyptus oil						
@ 250 pp @ 200 pp @ 100 pp @ 20 pp	n 1.98 n 2.5	1.47 2.18 3.08 3.63				
Cinnamon Oil						
@ 25 pp @ 10 pp @ 5 pp	m 3.07	2.38 3.77 5				
Tea Tree Oil						
@ 100 pp @ 20 pp		2.55 6				
Ethylene oxide/ propylene oxide copolymer						
@ 30 pp @ 15 pp @ 5 pp	m 3.4	3.2 4.7 5.8				
untreated	4.7	6				

While the present invention is described above in connection with preferred or illustrative embodiments, these embodiments are not intended to be exhaustive or limiting of the invention. Rather, the invention is intended to cover all alternatives, modifications and equivalents included within its spirit and scope, as defined by the appended claims.

7 CLAIMS

1. A method of inhibiting biofilm formation in commercial and industrial water systems comprising the step of adding thereto an effective inhibiting amount of at least one plant oil.

- 2. The method of claim 1 wherein the plant oil is selected from the group consisting of eucalyptus, cinnamon, retsin, tea tree, clove, camphor, pine, spruce, neem, peppermint, spearmint, wintergreen, lime, orange, grapefruit, mandarin, lemongrass and citronella oils, and mixtures thereof.
- 3. The method of claim 1 wherein the plant oil is eucalyptus oil.
- 4. The method of claim 1 wherein the plant oil is cinnamon oil.
- 5. The method of claim 1 wherein the plant oil is added to the water system in an amount from about 1 ppm to about 10,000 ppm.
- 6. The method of claim 1 wherein the plant oil is added to the water system in an amount from about 1 ppm to about 5,000 ppm.
- 7. The method of claim 1 wherein the plant oil is added to the water system in an amount from about 1 ppm to about 250 ppm.
- 8. The method of claim 1 wherein the commercial and industrial water systems are selected from the group consisting of cooling waters; food, beverage and industrial process waters; pulp and paper mill systems; brewery pasteurizers; sweetwater systems; air washer systems; oil field drilling fluids and muds; petroleum recovery processes; industrial lubricants; cutting fluids; heat transfer systems; gas scrubber systems; latex systems; clay and pigment systems; decorative

8 fountains; water intake pipes; ballast water tanks; and ship reservoirs.

INTERNATIONAL SEARCH REPORT

International application No. PCT/US01/10642

A. CLASSIFICATION OF SUBJECT MATTER						
IPC(7) :C02F 1/50 US CL :210/764						
According to International Patent Classification (IPC) or to both national classification and IPC						
	EARCHED					
Minimum docume	entation searched (classification system followe	d by classification sy	mbols)	CONTROL OF THE PROPERTY OF THE		
U.S. : 210/764						
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched						
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) WEST						
C. DOCUMENTS CONSIDERED 10 BE RELEVANT						
Category* (Citation of document, with indication, where ap	propriate, of the rele	vant passages	Relevant to claim No.		
X, P US	US 6,096,225 A (YANG et al) 01 August 2000, entire document.			1-8		
Further do	cuments are listed in the continuation of Box	Son matou	· ·			
			nt family annex.			
"A" document d	tegories of cited documents: defining the general state of the art which is not considered	date and not i		rnational filing date or priority ication but cited to understand invention		
to be of pa	rticular relevance			claimed invention cannot be		
"L" document	nument published on or after the international filing date which may throw doubts on priority claim(s) or which is	considered nov		red to involve an inventive step		
	tablish the publication date of another citation or other son (as specified)			claimed invention cannot be		
"O" document means	referring to an oral disclosure, use, exhibition or other	with one or n		when the document is combined ents, such combination being		
"P" document 1	published prior to the international filing date but later riority date claimed		nber of the same patent	family		
	completion of the international search	Date of mailing of the	ne international se	arch report		
24 JULY 2001		%	3 AUG 200)1		
	r address of the ISA/US Patents and Trademarks	Authorized officer	DEY Mujel	Valla		
Washington, D.C. Facsimile No. (,			
racsiline ivo.	703) 305-3230	Telephone No. (7	'03) 305 - 0651			